Safety is Contextual, LLM-Judges Are Not:
Navigating the Rigid Priors of Evaluators

Abstract

LLMs-as-judges are the only way to evaluate safety at scale. Despite their importance, LLM-judges themselves are rarely evaluated beyond human agreement in simple, static benchmarks. We therefore investigate two under-explored but crucial properties of LLMs-as-judges: their **susceptibility** to relying on in context-information, and their **steerability** to differing safety definitions, which may not align with their internal safety priors. We evaluate the safety judging abilities of many generalist LLMs and safety-specific judges, and investigate the impact of task demonstrations, novel in-context information, and changing safety definitions. We find that while LLM-judges can learn from new information, they are broadly unlikely to adjust their evaluations if the context or safety definition contradicts their prior.

1 Introduction

Safety evaluations at scale depend on the use of LLMs-as-judges (Liu et al., 2025). In assessing the safety of user requests and LLM responses, there is no single ground-truth answer, and thus no easily verifiable reward, so domains like this depend almost entirely on LLM judges. Yet despite their omnipresence, it is still unclear how reliable they are. An increasing number of their failures have been documented, for instance lack of robustness to stylistic prompt changes or susceptibility to adversarial attacks (Gu et al., 2025; Chen and Goldfarb-Tarrant, 2025; Wei et al., 2025; Weng et al., 2026). But there hasn't yet been a comprehensive analysis of the adaptability of judges to the breadth of cases in which they are currently used.

LLM-judges are used across a wide range of practical scenarios in safety – they are used across varied languages and cultures (Ning et al., 2025), across different deployment domains from education to finance (Gu et al., 2025), and across time in a changing world (Wang et al., 2026). With each

Figure 1: We test whether LLMs-judges for safety are **steerable** to specific safety policies and whether they are **susceptible** to using in-context information (demonstrations and additional information on the user request).

new scenario come many unanswered questions about the suitability of an LLM-judge.

Across languages and cultures, there is no universal definition of safety (Townsend, 2025). A request about alcohol is unsafe in many Arabic speaking nations (Noufaily et al., 2025) but is fine elsewhere, preaching or evangelising is not allowed in China (Delun) – the list of regional safety differences is so lengthy that similarities in specific safety policy are less common than variation. A globally useful safety judge will thus need to evaluate prompts and completions with respect to a range of safety policies. Similarly, safety policies vary across domains and use cases. Violence or drug is usually acceptable in creative writing, and is required for accurate journalistic writing, but tends to be restricted in a general-purpose chatbot. Existing work tends to handle these variable safety policies by defining safety policy in the judge prompt (Jindal et al., 2025; Weng et al., 2026). But it is still unclear if the judge will follow the new safety policy or simply apply the latent safety boundary that it was extensively post-trained on. As this is not tested explicitly, we do not know whether a given gap in agreement with human labels is an instance of many possible sources of error, or stems from differences in safety boundaries being applied. We therefore introduce the notion of **steerability** as a

desirable property of a judge, to quantify and examine how adaptable judges are to differing policies.

Across time, language changes, the world changes, and LLMs do not. This temporal drift is a known weakness of LLMs (Zhu et al., 2025) and safety-related language changes even more quickly than other language, exacerbating this vulnerability. Many pressures drive this rapid change: heavy use of social media and internet subcultures, the arms race to evade content moderation, and the quick rise and fall of misinformation and conspiracy theories, which are often connected to current events (Mehta and Giunchiglia, 2025; Mei et al., 2024). As time passes, and slang, current affairs, politics, and the threat landscape evolve, can an LLM-judge be adapted and augmented to remain an accurate judge? We introduce the notion of **susceptibility** as a second desirable property, to quantify how susceptible judges are to injection of information to improve performance or address temporal drift.

In this work, we seek to clarify these questions to better understand how LLM-judges should be used to evaluate safety in varied, complex, real-world set-ups. We group our investigations into two main questions: Does a judge utilise in-context information (**susceptibility**)? Can a judge be steered to custom safety policies (**steerability**)? To answer these questions, we evaluate a comprehensive suite of 13 models, spanning various model families and sizes, both open- and closed-source, and general purpose and safety-specific judges. As we are interested in breadth of LLM judge use cases, we evaluate on human annotated safety data in five languages that represent four scripts and very different cultures: English, French, Japanese, Arabic, and Korean. We make the following key contributions:

1. We introduce two important and overlooked properties of LLM-judges for safety: their **susceptibility** to learning from in-context information and their **steerability** to different safety definitions.

2. We show that susceptible judges *can* learn from novel in-context information, provided they had weak priors. Conversely, contrary to common practice (Gu et al., 2025), judges are rarely susceptible to demonstrations.

3. We show that safety judges are *not* steerable, and instead rely on their internal safety boundary to judge, despite system instructions.

4. Finally, we release our NovelPrompts dataset and our evaluation framework, so the community can comprehensively evaluate any judge's combined properties of susceptibility, steerability, and accuracy.

2 Background and Related Work

2.1 Human Agreement of LLM-Judges

Many benchmarks of LLM-judges have been established across a range of domains, with the primary aim of verifying that judges reliably align with gold-standard human annotators, typically measured through metrics such as accuracy or Cohen's kappa (Zheng et al., 2023; Son et al., 2025; Xu et al., 2025; Xie et al., 2025). On standard LLM-as-judge benchmarks, powerful LLMs reach high human agreement, often matching or exceeding the level of inter-annotator agreement (Zheng et al., 2023; Zeng et al., 2024; Tan et al., 2025).

2.2 What Human Agreement Misses

Despite this, in certain benchmarks, LLMs-as-judges do surprisingly poorly. A number of recent works have brought attention to the brittleness of judges, with evaluations showing that LLM judgements can vary hugely depending on small changes to the prompt template or response-being-evaluated (Gu et al., 2025; Chen and Goldfarb-Tarrant, 2025; Wei et al., 2025; Weng et al., 2026). Despite high human agreement in one benchmark, a judge may perform poorly out-of-distribution (Schwinn et al., 2026; Eiras et al., 2025).

It is unclear how much LLMs-as-judges use in-context information. Robustness is not the only property of a judge that is not revealed by accuracy. In certain use-cases, such as a task requiring the assimilation of multiple pieces of information, or context-dependent task instructions, a judge must respond to semantically meaningful changes in its prompt. For instance, when asked to evaluate a sample *given* some context, Xu et al. (2025) find that the best judge, o1, barely reaches 55% accuracy. Similarly, In et al. find that common safety judges like Llama-guard also struggle with evaluations given context, and show very high false negative rates when tasked with judging safety *given* a user profile (user-specific safety).

Research on the interaction between LLMs and context in standard tasks (i.e., not judging), also shows mixed results on how much LLMs can and will use context. For instance, one line of work shows that LLMs *can* learn from in-context demonstrations, using them as cues about the label space

and the expected output format, including how to format responses correctly (Min et al., 2022; Kossen et al., 2024; Long et al., 2024). Others have shown that when LLM context contradicts their parametric knowledge (what they have learnt during training), models are likely to ignore it, particularly on topics they are confident about (Du et al., 2024; Kossen et al., 2024; Ming et al., 2025).

Despite these inconsistent results, common evaluation practices assume that judges do learn from context, and therefore often include task demonstrations or other judging-relevant information in the prompt (Kim et al., 2024; Xu et al., 2025).

It is unclear if LLM-judges can adapt to varying task instructions. It is also common practice to include evaluation criteria or task rubrics in the judge prompt, as some work has shown this improves judge accuracy (Kim et al., 2024; Asai et al., 2026) and can outperform task-specific fine-tuning (Souly et al., 2024). Weng et al. (2026) even find that some LLM judges *can* adapt to simple changes in the task definition, though this work is limited to only four judges and one strict-to-lenient transformation of the safety definition. On the other hand, Murugadoss et al. (2025) find that the best judges perform better without any task instructions or evaluation rubrics. This suggests that judges are using their prior knowledge to solve the task, rather than relying on augmentation from specific task instructions. Since most LLM-as-judge evaluation tasks have evaluation schemes that align with what an LLM would learn during pre- and post-training (e.g. a response is better if it is clear, a request is unsafe if it incites harm, etc.), we are yet to understand whether LLM judgements reflect the judging instructions or simply their training priors.

Taken together, these results cast doubt on whether judges can follow evaluation instructions and incorporate new in-context information. Given the mixed picture of these few judge evaluation papers, and their inability to isolate the impact of context information vs. training data, a structured investigation is needed. This is particularly important in the field of safety evaluation, where judges are relied upon for almost all evaluations, but where the task will not always align with the judge's prior.

3 Experimental Setup

Our objective is to meta-evaluate the ability of LLM-judges to evaluate safety. In the standard setup, given a user request and a safety policy, a judge model is asked to predict whether the prompt is safe or unsafe.[1]

Let $\mathcal{J}$ denote a set of judge models. Each sample $x_i \in \mathcal{X}$ consists of a user prompt. A judge $j \in \mathcal{J}$ receives x_i together with a safety definition s and an evaluation context c_i (part of the prompt), and outputs a binary safety prediction

$$\hat{y}_{i,j}(x_i; s, c_i) = f_j(x_i; s, c_i) \in \{\text{SAFE}, \text{UNSAFE}\}.$$

The context c may contain several components:

$$c_i = (\tau, \mathcal{D}, r_i),$$

where τ denotes the task instructions, $\mathcal{D}$, the set of demonstrations, and r any additional information related to the prompt x_i. In our experiments, additional information consists of a few sentence explanation of terms or concepts in the prompt likely to be unknown to the LLM, either because they are niche regionally specific terms, or because they post-date the LLM's training data cutoff.

We evaluate the judge prediction $\hat{y}$ relative to the ground-truth human-annotated safety label y, and investigate how changes in the above components s and c affect judge predictions both at the sample level $\hat{y}_j$ and in aggregate over all $\hat{y}$. This allows us to evaluate judge behaviour beyond static safety classification, and to better understand key properties of LLMs-as-judges for safety.

3.1 Data

We use two challenging evaluation datasets for most of our analyses. Both contain human-generated user requests, a human-annotated coarse and granular safety label, and various auxiliary metadata (e.g., safety category mentioned, language, etc.), also human-annotated. Both are annotated by professional safety annotators, and cover five key safety categories (further detailed in §A.1).

MultilingualPrompts is an internal multilingual dataset which contains 779 safe and unsafe prompts and completions across French, Arabic, Korean, and Japanese. The prompts are natively multilingual, and approximately half are designed to require specific niche local knowledge to understand. The safe prompts in this dataset are all designed to be challenging by being very similar to unsafe prompts, in the style of exaggerated refusal testing (Röttger et al., 2024).

---

[1]Some safety evaluation setups judge user prompts, some also include model completions. Here we focus on judging solely user prompts, but the picture revealed by the results is consistent across both, as shown in Appendix B.2.1-D.

NovelPrompts is an English dataset of 194 safe and unsafe prompts created for this research, where prompts specifically contain language or references to **novel concepts** from after July 2025 (chosen as this post-dates the training cutoff of most of the judge models we investigate). The prompts were created such that their safety is ambiguous without knowledge of the novel concept. We will release NovelPrompts upon paper publication. Further dataset details are presented in Appendix A.2.

3.2 Judge Models

We select 13 judges which encompass a broad range of competitive models across varied sizes, which are both open- and closed-source, and include multilingually powerful models (listed in §A.3). In practice, general capability models like GPT are most used as safety judges (Xie et al., 2025), but, for completeness, we include three safety-specific judges, which have been fine-tuned specifically for safety evaluation. Each judge is prompted in the same way to classify the user request into safe or unsafe given a safety policy. Prompt templates, safety definitions, and experimental details are shared in Appendix A.1 - A.4.

3.3 Metrics

We run inference on each judge with 5 different seeds, extract a binary safety judgement from their output, and obtain a mean and standard deviation across those seeds. We evaluate the judges based on accuracy and F1 score relative to human labels. We analyse overall performance changes across experiments, for instance the difference in accuracy with the standard template vs. when the judge is given extra context, $\Delta_{Acc_{context}} = Acc_{context} - Acc_{base}$. We also evaluate per-sample changes, such as prediction flip rate between an experimental setup and the base setup, $\text{FlipRate} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}[\hat{y}_i^{\text{base}} \neq \hat{y}_i^{\text{context}}]$, where $\hat{y}_i$ is the majority-vote prediction across seeds for sample i. We elaborate in §A.5.

In the following sections we use this experimental setup to evaluate for **susceptibility** (§4) and **steerability** (§5) under our various conditions.

4 Is a judge susceptible to in-context information?

When a judge is given additional information in the context to use for evaluation, it is unclear whether they use this information. We investigate how judges use two types of in-context information: demonstrations (§4.1) and novel contextual information (§4.2). Demonstrations test whether judges learn format and task parameters like label space (as found in older models by Min et al. (2022)). Novel context information tests whether judges learn from new semantic knowledge.

To make this property explicit, we adapt Du et al. (2024)'s definition of susceptibility[2] to LLMs-as-judges. We define **susceptibility** as, given a judge and a sample to evaluate, the likelihood that a judge changes its prediction when given additional context (i.e., demonstrations, extra information etc.).

4.1 Demonstrations barely affect judging, even when explicitly misleading.

We investigate whether **demonstrations** are effective by including 2 to 4 examples for the judge evaluations of MultilingualPrompts and NovelPrompts. These examples are randomly sampled (stratified by class) from both datasets and held out from evaluation. If judges utilise demonstrations, there should be a performance change in their presence. We test 3 conditions: no examples, helpful examples, and misleading examples, the latter being examples where the safe/unsafe label is swapped.

Table 1 shows that including demonstrations of the task in the prompt marginally improves the judges' evaluation abilities, providing an average F1 benefit of 0.03 in MultilingualPrompts and 0.02 in NovelPrompts. This benefit is also inconsistent across judges (see Appendix B.1) and cannot be relied upon. This small but inconsistent benefit aligns with prior empirical results on LLM judges (Xie et al., 2025; Koh et al., 2024), and differs significantly from the strong results of Min et al. (2022) on earlier models.

Notably, providing the judges with incorrect demonstrations has no significant impact on judge performance, which aligns with Min et al. (2022)'s findings, but is stronger (as they found a small effect). Longpre et al. (2021); Du et al. (2024) found that LLM's can ignore information that causes a knowledge conflict with their parametric knowledge from training. This suggests a reason why judges are robust to misleading examples. It also aligns with our findings in §5 that judges struggle to evaluate with respect to safety definitions that depart from their internal safety boundary.

---

[2]They define susceptibility as the ability of a generative model to be swayed from its prior knowledge of entities (people and places) by new context. We take inspiration from their definition, broadening it and adapting it to a judge setting.

Demonstrations	MultilingualPrompts F1 ± std	NovelPrompts F1 ± std
None	0.68 ± 0.00	0.57 ± 0.01
Correct	0.71 ± 0.00	0.59 ± 0.01
Incorrect	0.69 ± 0.00	0.58 ± 0.01

Table 1: **Demonstrations provide a marginal gain to judging performance, while misleading demonstrations have little effect.** F1 score and std dev across 10 judges and 5 seeds.

4.2 Novel in-context information can bridge knowledge gaps.

Figure 2: **Context can bridge knowledge gaps** in Novel-Prompts. Bars show F1 scores (mean and std dev of 5 seeds) when judges are only given the user request vs. when they are also given in-context information explaining the request.

While task demonstrations barely affect judges, we investigate whether context information *can* have an impact by providing judges with novel semantic knowledge.

Experiments We test whether judges are susceptible to task-relevant information provided in-context on MultilingualPrompts and NovelPrompts. Both datasets include annotations describing information needed to assess the safety of each prompt. In MultilingualPrompts, these annotations explain region-specific terms or events; for example, ' "les meufs" is a French slang term for [...]'. In NovelPrompts, they explain the novel (post July 2025) slang or events mentioned in the prompt (e.g., "'Bombakhalas': Something that is crazy and like it's about to finish". Safety cannot be determined without understanding these novel concepts. We test three conditions: no context, correct context, and irrelevant context (where context samples from the dataset are shuffled so they do not match the user prompt).

Judges learn novel concepts from NovelPrompts context. Figure 2 shows that giving judges additional novel information in the context can have a large impact. In NovelPrompts, it boosts the

judges' F1 score by an average of 0.06, a 10% increase. Context also allows less powerful and smaller models like Command-a and Llama-70b to reach performance levels that are competitive with GPT-5-2 and Claude-4-5-sonnet. This suggests that in a changing world, when judges cannot be continually fine-tuned with new data, an alternative can be to provide them with context on these new events, and that it can also enable the use of cheaper, more efficient models. However in the MultilingualPrompts dataset, context provides no consistent benefit (see Appendix §B.2.1). It is most likely not helpful because most judges are powerful multilingually and already understand the regional information mentioned, more so than they know the novel concepts mentioned in NovelPrompts (which are after their training cutoff), as discussed in §4.3.

Judges are robust to irrelevant context. Across both datasets, judges are broadly unaffected by irrelevant context. Shuffled context leads to fewer prediction flips, causing no significant drop in performance compared to no context at all (Appendix §B.2.2). This aligns with prior work which finds that LLMs do not consider all in-context information equally (Kossen et al., 2024).

4.3 Judges only learn from context when their priors are weak (and not all judges do)

Across both sets of demonstrations experiments and novel context experiments, we find that judge susceptibility is heterogenous. The impact of context and demonstrations depend on both the sample being evaluated and the judge itself.

Judges change predictions on a very small percentage of samples. We evaluate susceptibility to context at the sample level, and find that, surprisingly, judges keep their predictions fixed on most samples, even when presented with new or contradictory information in the context and with correct or incorrect demonstrations. Figure 3 (left) shows that in MultilingualPrompts, changes in overall performance are due to prediction flips that happen on only a minority of samples, as judges maintain their predictions on over 80% of the samples.[3] This seems to be reflective of model certainty or strength of model priors, since there are on average two times more prediction flips in the NovelPrompts dataset than the MultilingualPrompts dataset, and the NovelPrompts dataset was designed to be after

---

[3]We find similar trends in NovelPrompts (Appendix B.3)

Figure 3: **Judges are more susceptible to changing their predictions on samples on which they have less prior knowledge**, in MultilingualPrompts. Left: bars represent the proportion of samples on which judges change their prediction in response to being given: novel context information, irrelevant context information, task demonstrations, and incorrect demonstrations. Right: the likelihood that judges change their prediction increases as the frequency of words in the evaluation sample decreases. Word frequency is measured on a large pre-training dataset FineWeb-2 and used as a proxy for judge prior knowledge.

the models' training cut-off date.

Judges are more susceptible on samples with low corpus frequency. To quantify the prior knowledge judges are likely to have of each sample, we measure how frequent words are in large pre-training corpora adapted from CommonCrawl (Fine-web 1 and 2 (Penedo et al., 2024, 2025)), and use this as a proxy for each model's prior knowledge on the sample it is evaluating (further details in Appendix A.6). Figure 3 (right) and Appendix B.3 show a significant negative correlation between prompt frequency and likelihood of a judge modifying its prediction, in MultilingualPrompts and NovelPrompts respectively. We also note that there are 25% out-of-vocabulary words in NovelPrompts compared to only about 3% in MultilingualPrompts (Appendix A.6), which explains why judges are more susceptible on NovelPrompts. This supports our hypothesis that judges are more susceptible when they have weaker priors on the evaluation samples – susceptibility significantly increases the less a judge has encountered a word. It also aligns with Du et al. (2024)'s findings, which we broaden to a much wider range of models and context types.

Susceptibility is a property inherent to the judge. There is still significant variability in context effects across judges. For instance, NovelPrompts context boosts Command-A's performance by 0.19, but is slightly detrimental for Qwen3 (Figure 2). We hypothesise that each judge has some inherent level of "susceptibility" to in-context information, which impacts both how much it will benefit from in-context information and be harmed by irrelevant or misleading context. Indeed, Figure 4 and Appendix B.4 show that across tasks and datasets,

there are strong and significant positive correlations between how much models change their predictions in response to helpful context and demonstrations, and how vulnerable they are to irrelevant and incorrect ones. For instance, Tiny-Aya is consistently one of the most susceptible judges in both context and demonstrations experiments – both for good and for ill. This suggests that something in each model's training procedure impacts their susceptibility to learning from new in-context information, and thus also their robustness to distracting or misleading in-context information. This goes beyond Du et al. (2024) in showing that susceptibility is also model dependent.

Figure 4: **Judges change their predictions similarly in response to context, demonstrations, irrelevant context, and misleading demonstrations**. Each dot represents the average ranking of how susceptible a judge is across one type of context experiment in NovelPrompts and MultilingualPrompts.

5 Can you steer a judge to specific safety policies?

Our experiments on susceptiblity show that the likelihood of judges changing their predictions is determined by the priors they acquire during training. We now investigate whether these priors also affect their ability to adapt to different safety definitions,

which vary over practical, cultural, or geographical contexts of evaluation. To do this, we characterise the **steerability** of different judges – the likelihood that a judge changes its prediction on a sample when given a modified safety policy.

Experiments We prompt judges to evaluate safety given different safety definitions in five conditions: no definition, our base safety definition (which should align well with judge priors), two variants of our safety definition, and an absurd definition. The first (variant a) makes a change to the policies of two out of the five safety categories, saying that any mention of self harm is safe while any mention of sexual content is unsafe. The second (b) is a stricter version of the initial policy, where any mention of a safety-related category, even if it is just neutral information content is unsafe (e.g., "Where can I find resources on self-harm?" would be unsafe). The full definitions are presented in Appendix A.1. We also test a fifth condition – an absurd safety definition – where any mention of a ball sport is defined as unsafe. We generate a dataset of sports-related prompts and completions for this analysis, which we describe further in Appendix A.2. We measure steerability at the sample level (i.e., the proportion of predictions which change relative to when not given a definition) and at the aggregate level (i.e., judge overall accuracy relative to the modified ground-truth).

Judges perform equivalently without a safety definition. Figure 5 shows that, surprisingly, judge performance with and without the safety definition is remarkably similar. Judge accuracy relative to the ground-truth safety definition is the same, if not slightly higher, than when not given any safety definition (+ 0.02 in MultilingualPrompts, -0.00 in NovelPrompts). This is most likely because our base safety definition broadly aligns with those that the LLMs were trained with,[4] and small variations will not result in significant overall performance changes. This is precisely the issue with most evaluation setups; standard evaluations broadly align with judge priors.

Judges struggle to adapt to new safety definitions Our experiments on safety definition variants allow us to test whether judges *are* actually fol-

lowing the safety definitions by pushing the prompt definition further from their prior. We find that judges struggle to adapt to these definitions, only changing an average of 5% and 3% of their predictions in MultilingualPrompts and NovelPrompts respectively, when they should be changing 15% of their predictions. Their accuracy, relative to the adjusted ground truth, drops by an average of 0.11 and 0.13 in MultilingualPrompts (Figure 5) and 0.05 and 0.03 in NovelPrompts (Appendix C.1).

Figure 5: **Most judges cannot adapt to safety definition variants**. The first two bars show accuracy relative to the base safety policy when they are given/not given the policy, and the last two show accuracy relative to the two safety definition variants they are given in the prompt. Mean and st dev across 10 judges and seeds in MultilingualPrompts is shown.

We push this evaluation further by giving them an absurd safety definition where only ball sports are unsafe – a very easy classification task that all judges should be able to do, that is also orthogonal to any learned safety boundaries. Contrary to the previous results, most judges correctly predict all evaluation samples (Appendix C.2). Surprisingly, there is still variation between judges in steerability to this absurd definition. In particular, when tested on truly unsafe data (but not unsafe according to the sports policy) the Claude family of models get 15 to 35% of the samples wrong, despite it being a very simple task. Together these results show that steerability is surprisingly challenging when intersecting with model priors, but it is usually possible when orthogonal (also supported by our results on safety evaluation as classification in §5).

Steerability is a property inherent to the judge Similar to susceptibility, we find that certain judges are more or less steerable, and this holds across safety definition changes (a and b) and datasets. Indeed, steerability to definition a and b show strong Pearson correlations of 0.60 and 0.67 in MultilingualPrompts and NovelPrompts respectively (see Appendix C.4). This suggests that all judges have an inherent amount of safety steerability which affects how much they can adapt to new definitions.

---

[4]This is plausible because frontier model safety policies share many common elements. For instance, OpenAI, Google, Anthropic, and others collaborated to establish a standardised taxonomy of 13 hazard categories for the MLCommons AI safety v0.5 and AILuminate benchmarks(Ghosh et al., 2025).

Importantly, steerable judges are not necessarily susceptible judges, nor are they necessarily accurate judges, as we show in Appendix D.1.

Masking a safety evaluation task as an arbitrary classification task improves steerability. We explore whether a conceptual association to safety (conflicts with model priors) is what makes judges so un-steerable. We reframe the judging task as an arbitrary classification task, where instead of instructing the judges to predict "Safe"/"Unsafe", we instruct them to classify the completions as belonging to classes "A"/"B". We define A and B exactly as previously, with the same five categories, but with no mention of the concept of safety.

When given the baseline safety definition, judge performance is very similar whether they are evaluating safety or doing classification (-0.00 and +0.01 F1 in MultilingualPrompts and NovelPrompts respectively). This is expected, as the underlying definition is exactly the same. Remarkably, when given the two safety definition variants, judge steerability (measured by prediction flips in response to the new definition), is over two times higher for classification than for safety evaluation (Figure 6).[5] Although judges still fall short of perfect steerability to the two safety definition variants, the classification framing brings them much closer to this ideal (dotted line) and results in consistently higher performance. Altogether, these results suggest that lack of steerability is not due to misunderstanding of the definition or of the data sample, or general model brittleness, but is rather that judge internal safety boundary is difficult to modify.

Figure 6: **Steerability is much higher when the safety judging task is masked as a classification task** (hashed bars) in MultilingualPrompts.[5] Steerability is measured as mean judge prediction flips (relative to the expected number of flips) when given a safety definition variant.

6 Conclusion

Safety policy, and thus safety evaluation, widely varies across languages, cultures, and use cases.

But most LLM judge evaluations do not explicitly acknowledge this – they test an LLM's human agreement, but not its adaptability. Common evaluation setups are "aligned" with frontier models' priors, such that simply evaluating the human agreement of LLMs-as-judges misses other crucial judge properties – whether they follow instructions when given to them, whether they can be augmented with additional information (**susceptibility**), and whether they will follow new or modified safety policies (**steerability**). We found judges to be remarkably poor at adapting to any of these, though with some variability. This means that in practice, though safety is varied, judges are not. Practitioners may *intend* to judge safety based on their own policy and use case, but will end up judging safety based on the policy of one of the frontier labs.

There are some options for mitigating this. We found some judges to be more inherently susceptible or steerable than others – though these characteristics do not correlate with each other, nor do they correlate with accuracy of human agreement. We found all judges to be more susceptible on data samples of which they had little prior knowledge; where terms important to understanding prompts had low or non-existent training data frequency. We similarly found all judges to be more steerable when a safety evaluation task was masked as an arbitrary category A vs. category B classification task, or when the safety evaluation task was an absurd toy task that clearly didn't interact with safety. Judges become more susceptible and steerable when the task and data is set up to not conflict with their priors. This is a promising avenue for more adaptable judges, but also a dangerous one, as increased adaptability comes with increased vulnerability to incorrect or irrelevant information.

We recommend that safety judge properties should inform the choice of judge based on a given deployment scenario. If good judging requires the judge to consider additional or novel information, as would be the case in judging real-time misinformation, prioritise a susceptible judge. If good judging should be relative to a specific enterprise policy, or a nuanced cultural safety policy, prioritise a more steerable judge should be selected. If the base-LLM should be trusted above all, then human agreement can be relied on irrespective of these things. But if selecting based on agreement alone, any input instructions, demonstrations, or definitions may amount to nothing more than a false sense of security for the practitioner.

---

[5]Similar results are shown for NovelPrompts in §C.3

Limitations

As in most empirical evaluations, our work is limited in only considering a limited number of judges and evaluation datasets. We hope that by providing a framework for safety judge evaluation, other researchers can extend our evaluation to make it even more comprehensive. Furthermore, while we aimed to make our experiments systematic, we only consider a limited number of evaluation setups, e.g., 0, 2, or 4 demonstrations, or one of three safety definition variants, which may not show us the full range of judge behaviours, especially given how prone LLMs are to spurious biases in the prompt. Also, while it is interesting to connect judge susceptibility to the prior knowledge they have on a sample, our current analysis of judge prior knowledge could be refined to consider differences judges may have in their prior knowledge instead of looking at word frequency across one standard pre-training corpora. For example, judge knowledge of the topic could be elicited beforehand, or judge perplexity with respect to the sample could be used as a proxy for how much they know about the sample.

References

Anthropic. 2024. Introducing computer use, a new claude 3.5 sonnet, and claude 3.5 haiku. Accessed 2026-05-25.

Anthropic. 2025. Introducing claude sonnet 4.5. Accessed 2026-05-25.

Akari Asai, Jacqueline He, Rulin Shao, Weijia Shi, Amanpreet Singh, Joseph Chee Chang, Kyle Lo, Luca Soldaini, Sergey Feldman, Mike D'Arcy, and 1 others. 2026. Synthesizing scientific literature with retrieval-augmented language models. *Nature*, pages 1–7.

Hongyu Chen and Seraphina Goldfarb-Tarrant. 2025. Safer or luckier? LLMs as safety evaluators are not robust to artifacts. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 19750–19766, Vienna, Austria. Association for Computational Linguistics.

Cohere. 2024. Cohere's command r model. Accessed 2026-05-25.

Team Cohere, Arash Ahmadian, Marwan Ahmed, Jay Alammar, Milad Alizadeh, Yazeed Alnumay, Sophia Althammer, Arkady Arkhangorodsky, Viraat Aryabumi, Dennis Aumiller, and 1 others. 2025. Command a: An enterprise-ready large language model. *arXiv preprint arXiv:2504.00698*.

Cohere Labs. 2026. Tiny aya. Global variant: tiny-aya-global. Accessed 2026-05-25.

Zhu Delun. Holy firewalls: China's new rules for online clergy conduct. Bitter Winter.

Kevin Du, Vésteinn Snæbjarnarson, Niklas Stoehr, Jennifer White, Aaron Schein, and Ryan Cotterell. 2024. Context versus Prior Knowledge in Language Models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13211–13235, Bangkok, Thailand. Association for Computational Linguistics.

Francisco Eiras, Eliott Zemour, Eric Lin, and Vaikkunth Mugunthan. 2025. Know thy judge: On the robustness meta-evaluation of llm safety judges. In *Proceedings on "I Can't Believe It's Not Better: Challenges in Applied Deep Learning" at ICLR 2025 Workshops*, volume 296 of *Proceedings of Machine Learning Research*, pages 56–66. PMLR.

Shaona Ghosh, Heather Frase, Adina Williams, Sarah Luger, Paul Röttger, Fazl Barez, Sean McGregor, Kenneth Fricklas, Mala Kumar, Quentin Feuillade-Montixi, Kurt Bollacker, Felix Friedrich, Ryan Tsang, Bertie Vidgen, Alicia Parrish, Chris Knotz, Eleonora Presani, Jonathan Bennion, Marisa Ferrara Boston, and 83 others. 2025. Ailuminate: Introducing v1.0 of the ai risk and reliability benchmark from mlcommons. *Preprint*, arXiv:2503.05731.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, Saizhuo Wang, Kun Zhang, Yuanzhuo Wang, Wen Gao, Lionel Ni, and Jian Guo. 2025. A survey on llm-as-a-judge. *The Innovation*.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring Massive Multitask Language Understanding. In *International Conference on Learning Representations*.

Yeonjun In, Wonjoong Kim, Kanghoon Yoon, Sungchul Kim, Mehrab Tanjim, Sangwu Park, Kibum Kim, and Chanyoung Park. Is Safety Standard Same for Everyone? User-Specific Safety Evaluation of Large Language Models.

Madhur Jindal, Hari Shrawgi, Parag Agrawal, and Sandipan Dandapat. 2025. SAGE: A Generic Framework for LLM Safety Evaluation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 11–33, Suzhou (China). Association for Computational Linguistics.

Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoo Yun, Seongjin Shin, Sungdong Kim, James Thorne, and Minjoon Seo. 2024. Prometheus: Inducing Fine-Grained Evaluation Capability in Language Models. In *International Conference on Learning Representations*.

Hyukhun Koh, Dohyung Kim, Minwoo Lee, and Kyomin Jung. 2024. Can LLMs recognize toxicity? a structured investigation framework and toxicity metric. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 6092–6114, Miami, Florida, USA. Association for Computational Linguistics.

Jannik Kossen, Yarin Gal, and Tom Rainforth. 2024. In-Context Learning Learns Label Relationships but Is Not Conventional Learning.

Songyang Liu, Chaozhuo Li, Jiameng Qiu, Xi Zhang, Feiran Huang, Litian Zhang, Yiming Hei, and Philip S. Yu. 2025. The scales of justitia: A comprehensive survey on safety evaluation of llms. *Preprint*, arXiv:2506.11094.

Quanyu Long, Yin Wu, Wenya Wang, and Sinno Jialin Pan. 2024. Does In-Context Learning Really Learn? Rethinking How Large Language Models Respond and Solve Tasks via In-Context Learning.

Shayne Longpre, Kartik Perisetla, Anthony Chen, Nikhil Ramesh, Chris DuBois, and Sameer Singh. 2021. Entity-Based Knowledge Conflicts in Question Answering. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 7052–7063, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Manisha Mehta and Fausto Giunchiglia. 2025. Understanding gen alpha's digital language: Evaluation of llm safety systems for content moderation. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '25, page 2863–2873, New York, NY, USA. Association for Computing Machinery.

Lingrui Mei, Shenghua Liu, Yiwei Wang, Baolong Bi, and Xueqi Cheng. 2024. SLANG: New concept comprehension of large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 12558–12575, Miami, Florida, USA. Association for Computational Linguistics.

Meta Llama. 2024. meta-llama/llama-3.1-70b-instruct. Accessed 2026-05-25.

Meta Llama. 2025. Llama guard 4. Accessed 2026-05-25.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the Role of Demonstrations: What Makes In-Context Learning Work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11048–11064, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Yifei Ming, Senthil Purushwalkam, Shrey Pandit, Zixuan Ke, Xuan-Phi Nguyen, Caiming Xiong, and Shafiq Joty. 2025. FaithEval: Can Your Language Model Stay Faithful to Context, Even if "The Moon Is Made of Marshmallows". In *International Conference on Learning Representations*.

Bhuvanashree Murugadoss, Christian Poelitz, Ian Drosos, Vu Le, Nick McKenna, Carina Suzana Negreanu, Chris Parnin, and Advait Sarkar. 2025. Evaluating the Evaluator: Measuring LLMs' Adherence to Task Evaluation Instructions. In *Annual AAAI Conference on Artificial Intelligence*.

Zhiyuan Ning, Tianle Gu, Jiaxin Song, Shixin Hong, Lingyu Li, Huacan Liu, Jie Li, Yixu Wang, Meng Lingyu, Yan Teng, and Yingchun Wang. 2025. LinguaSafe: A Comprehensive Multilingual Safety Benchmark for Large Language Models. *arXiv preprint*. ArXiv:2508.12733 [cs].

Lynn Noufaily, Alessandro Monaco, Robin Goldstein, and Tilman Reinhardt. 2025. Twenty-two shades of grey – an analysis of alcohol regulations in the arab world. *IVES Conference Series*. Short communication.

NVIDIA. 2025. Llama 3.1 nemotron safety guard 8b v3. Accessed 2026-05-25.

OpenAI. 2025a. Gpt-5 mini model. Accessed 2026-05-25.

OpenAI. 2025b. gpt-oss-120b & gpt-oss-20b model card. Accessed 2026-05-25.

OpenAI. 2025c. gpt-oss-safeguard technical report. Accessed 2026-05-25.

OpenAI. 2025d. Introducing gpt-5.2. Accessed 2026-05-25.

Guilherme Penedo, Hynek Kydlíček, Loubna Ben allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. 2024. The fineweb datasets: Decanting the web for the finest text data at scale. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Guilherme Penedo, Hynek Kydlíček, Vinko Sabolčec, Bettina Messmer, Negar Foroutan, Amir Hossein Kargaran, Colin Raffel, Martin Jaggi, Leandro Von Werra, and Thomas Wolf. 2025. Fineweb2: One pipeline to scale them all – adapting pre-training data processing to every language. *Preprint*, arXiv:2506.20920.

Qwen. 2025. Qwen/qwen3-235b-a22b-instruct-2507. Accessed 2026-05-25.

Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2024. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5377–5400, Mexico City, Mexico. Association for Computational Linguistics.

Leo Schwinn, Moritz Ladenburger, Tim Beyer, Mehrnaz Mofakhami, Gauthier Gidel, and Stephan Günnemann. 2026. A Coin Flip for Safety: LLM Judges Fail to Reliably Measure Adversarial Robustness. *arXiv preprint*. ArXiv:2603.06594 [cs].

Shivalika Singh, Angelika Romanou, Clémentine Fourrier, David Ifeoluwa Adelani, Jian Gang Ngui, Daniel Vila-Suero, Peerat Limkonchotiwat, Kelly Marchisio, Wei Qi Leong, Yosephine Susanto, Raymond Ng, Shayne Longpre, Sebastian Ruder, Wei-Yin Ko, Antoine Bosselut, Alice Oh, Andre Martins, Leshem Choshen, Daphne Ippolito, and 4 others. 2025. Global MMLU: Understanding and addressing cultural and linguistic biases in multilingual evaluation. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 18761–18799, Vienna, Austria. Association for Computational Linguistics.

Guijin Son, Dongkeun Yoon, Juyoung Suk, Javier Aula-Blasco, Mano Aslan, Vu Trong Kim, Shayekh Bin Islam, Jaume Prats-Cristià, Lucía Tormo-Bañuelos, and Seungone Kim. 2025. MM-Eval: A Multilingual Meta-Evaluation Benchmark for LLM-as-a-Judge and Reward Models. *arXiv preprint*. ArXiv:2410.17578 [cs].

Alexandra Souly, Qingyuan Lu, Dillon Bowen, Tu Trinh, Elvis Hsieh, Sana Pandey, Pieter Abbeel, Justin Svegliato, Scott Emmons, Olivia Watkins, and Sam Toyer. 2024. A strongreject for empty jailbreaks. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NeurIPS '24, Red Hook, NY, USA. Curran Associates Inc.

Sijun Tan, Siyuan Zhuang, Kyle Montgomery, William Yuan Tang, Alejandro Cuadron, Chenguang Wang, Raluca Popa, and Ion Stoica. 2025. JudgeBench: A Benchmark for Evaluating LLM-Based Judges. In *International Conference on Learning Representations*.

Beverley A Townsend. 2025. Multiculturalism and ai value alignment. In Philipp Hacker, editor, *Oxford Intersections: AI in Society*. Oxford University Press.

Yixu Wang, Xin Wang, Yang Yao, Xinyuan Li, Xibang Yang, Yan Teng, Xingjun Ma, and Yingchun Wang. 2026. Agenticeval: Toward agentic and self-evolving safety evaluation of large language models. *Preprint*, arXiv:2509.26100.

Hui Wei, Shenghua He, Tian Xia, Fei Liu, Andy Wong, Jingyang Lin, and Mei Han. 2025. Systematic Evaluation of LLM-as-a-Judge in LLM Alignment Tasks: Explainable Metrics and Diverse Prompt Templates. *arXiv preprint*. ArXiv:2408.13006 [cs].

Shihao Weng, Yang Feng, and Xiaofei Xie. 2026. Beyond accuracy: Policy invariance as a reliability test for llm safety judges. *Preprint*, arXiv:2605.06161.

Tinghao Xie, Xiangyu Qi, Yi Zeng, Yangsibo Huang, Udari Madhushani Sehwag, Kaixuan Huang, Luxi He, Boyi Wei, Dacheng Li, Ying Sheng, Ruoxi Jia,

Bo Li, Kai Li, Danqi Chen, Peter Henderson, and Prateek Mittal. 2025. SORRY-Bench: Systematically Evaluating Large Language Model Safety Refusal. In *International Conference on Learning Representations*.

Austin Xu, Srijan Bansal, Yifei Ming, Semih Yavuz, and Shafiq Joty. 2025. Does context matter? Contextual-JudgeBench for evaluating LLM-based judges in contextual settings. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9541–9564, Vienna, Austria. Association for Computational Linguistics.

Zhiyuan Zeng, Jiatong Yu, Tianyu Gao, Yu Meng, Tanya Goyal, and Danqi Chen. 2024. Evaluating Large Language Models at Evaluating Instruction Following. In *International Conference on Learning Representations*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Neural Information Processing Systems*.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. 2023. Instruction-following evaluation for large language models. *Preprint*, arXiv:2311.07911.

Chenghao Zhu, Nuo Chen, Yufei Gao, Yunyi Zhang, Prayag Tiwari, and Benyou Wang. 2025. Is your LLM outdated? a deep look at temporal generalization. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 7433–7457, Albuquerque, New Mexico. Association for Computational Linguistics.

A Further experimental details

A.1 Safety definition:

For the core of our analysis, we use a safety policy similar to the one introduced in (Cohere et al., 2025). We define a prompt or response to be UNSAFE if it is high-severity according to one or more of the following categories:

- **misinformation**: content that is either about false but widely believed theories, such as conspiracy theories, as well as misinformation about civic processes and politics. Low Severity is neutral informational content. High Severity is any content that is explicitly or implicitly promoting false or misleading information.

- **self-harm information**: content that is about self-harm, including eating disorders and suicide. Low Severity is news, academic, statistics and resources for victims. Rest is High Severity.

- **sexual content**: any content that is about sex. Low severity is neutral informational content. High Severity is any content that is trying to elicit arousal. Highest severity is any content that depicts sexual violence.

- **child sexual exploitation and abuse**: only High Severity.

- **violence and hate**: targeted expressions of hate, violence or discrimination, including denying a past violent event. Low Severity is neutral informational content. High Severity is any content explicitly or implicitly supporting hateful ideologies.

A.2 Datasets

MultilingualPrompts is a natively multilingual dataset of 779 human generated user requests along with completions. Completions were generated by 5 models: command-a, gpt-4o, command-r, claude-4-5-sonnet, and DeepSeek-R1. The dataset is approximately evenly split between French, Arabic, Japanese, and Korean prompts and completions. Each prompt and completion were annotated by human annotators to describe whether any safety-related categories were mentioned in the prompt or completion (i.e., misinformation, self-harm, sexual content, child sexual exploitation and abuse, and violence and hate). If the prompt or completion did mention a safety category, the severity of the prompt or completion was also annotated. Severity is low if the mention is neutral information content, and high otherwise. From these category annotations and severity, an overall safety label was set: unsafe if there is at least one high severity mention of a safety category, and safe otherwise. Having this granular safety-related data allowed us to later modify the safety policy and explore how steerable judges are. According to our base definition, 310 prompts and completions are unsafe, and 469 safe. Approximately half of the samples in each language require specific regional knowledge to be understood. For these prompts, annotators were asked to provide some context explaining the difficult concept mentioned in the prompt (for instance, " Les meufs is a French slang word for [...]").

NovelPrompts is an English safety dataset of 194 prompts and completions generated specifically for these experiments. Human annotators from the AI data and safety company Alice generated user safe and unsafe requests that specifically contain references to information available from after July 2025. These **novel concepts** can be an event, a new word or new meaning of an existing word (e.g. slang). We choose this date as many of the models have pre-training cutoffs before July 2025, allowing us to see how they approach truly novel information. The requests were designed in such a way that it is impossible to evaluate their safety without understanding the novel concept. Completions were generated by the same 5 models as for MultilingualPrompts, except models were given the context in addition to the prompt (as without this, they often misunderstood the prompt). Human annotators were asked to annotate the safety category and severity level of both prompts and completions, according to the same definitions as above. Annotators also provided a few sentences of context for all novel concepts. For example, "Bombakhalas: Something that is crazy and like it's about to finish". In total, there are 61 unsafe prompts and 133 safe ones, across all the five safety categories.

Model	Company	Date	Size	Open	Safety judge?
gpt-5-2	OpenAI	2025-12	–	Closed	No
gpt-5-mini-08-2025	OpenAI	2025-08	–	Closed	No
claude-4-5-sonnet	Anthropic	2025	–	Closed	No
claude-3-5-haiku	Anthropic	2024	–	Closed	No
command-a	Cohere	2025-03	111B	Closed	No
command-r	Cohere	2024-12	7B	Closed	No
qwen3-235b-a22b-instruct-2507-tput	Alibaba	2025-07	235B	Open	No
meta-llama-3-1-70b-instruct-turbo	Meta	2024	70B	Open	No
gpt-oss-20b	OpenAI	2025-08	20B	Open	No
tiny-aya-global	Cohere	2026-03	3B	Open	No
Llama-3.1-Nemotron-Safety-Guard-8B-v3	NVIDIA	2025	8B	Open	Yes
Llama-Guard-4-12B	Meta	2025	12B	Open	Yes
gpt-oss-safeguard-20b	OpenAI	2025	20B	Open	Yes

Table 2: **LLM-as-judges** used in our evaluations. Date refers to release date, and safety judge to whether the model was specifically optimised for safety evaluation tasks.

Other judging benchmarks   We supplement our analysis with other existing public benchmarks. On the judge evaluations side, we also use SORRY-Bench, a dataset of 7000 potentially unsafe instructions, LLM responses, and human annotations of the LLM responses. Given its size, we select a random subset of 1000 samples. We also analyse how well the judges perform on standard LLM benchmarks, including MMLU-mini, GlobalMMLU (specifically in French, Arabic, Korean, and Japanese), IFEval, and an internal translated version of IFEval (in Arabic, Korean, and Japanese), an internal English safety benchmark, and an internal multilingual safety benchmark (also in the 4 languages we use).

Sports dataset   We create a synthetic English dataset of 240 prompt-completion pairs (48 per model, generated by the same five models as MultilingualPrompts: command-a, gpt-4o, command-r, claude-3-5-sonnet, and DeepSeek-R1) designed to probe judge steerability under an arbitrary, off-policy safety definition. Each completion belongs to one of three strata: 100 completions about ball sports (e.g., soccer, basketball, tennis), 40 about non-ball sports (e.g., swimming, gymnastics, boxing), and 100 about unrelated educational topics (e.g., photosynthesis, black holes). Models used for generation are steered to a specific topic via a hidden system prompt, while the user-visible prompt stored in the dataset is a neutral generic request (e.g., "Tell me something interesting about a sport."), so the judge only sees the topic through the completion itself. Because this policy bears no relation to any model's training-time notion of safety, accuracy on this dataset isolates how well a judge follows the policy it is given. We will also release this dataset upon paper publication.

A.3   Judges

We use the judges listed in Table 2. Specific references for these judges are as follows: (OpenAI, 2025d), (OpenAI, 2025a), (Anthropic, 2025), (Anthropic, 2024), (Cohere et al., 2025), (Cohere, 2024), (Qwen, 2025), (Meta Llama, 2024), (OpenAI, 2025b), (Cohere Labs, 2026), (NVIDIA, 2025), (Meta Llama, 2025), (OpenAI, 2025c). All judges are used with a temperature of 0 and max_tokens set to 512. If a judge fails to produce a correctly-formatted judgement within this token limit, that sample counts as an error. Errors are not included in the final calculation scores. Only evaluations with <2% errors are considered in this paper.[6] We do not use the safety-specific judges for the steering or demonstrations experiments as they are inflexible to (and not optimised for) bespoke, complex templates, such as modified safety definitions, demonstrations and additional context.

A.4   Prompt templates

The base template we prompt the judges with is as follows:

---

[6]We tried gpt-5-nano and llama-3-8b but excluded them from the analysis as they exceeded our NaN threshold.

When the task is to judge the safety of the model completion to the user request, the prompt template is modified accordingly and the model completion is included in the conversation. For certain experiments we also add demonstrations before task definition, and for others we add context after the model conversation.

For the three safety-specific judges, nemotron, llama-guard, and gpt-oss-safeguard, we make small modifications to the prompt template to match their recommended format, while still keeping our safety definition. For instance, for Nemotron, we use the following template:

Safety definition changes. We test three variants of the base safety definition. In the first, we provide no safety definition at all. In variant a, we modify the definition by saying that self harm information is always low severity while sexual content is always high severity. In variant b we say that a message is unsafe if it is low or high-severity. We also experiment with disguising the safety judging task as a simple classification task. For this we modify the base template as follows:

Absurd safety definition on ball sports. Finally, we experiment with providing the judges with a completely absurd safety definition.

A.5 Metrics

We complement overall accuracy and F1 with per-sample metrics that more precisely capture how judges respond to changes in their input. As described in the main body, for each sample i we obtain a majority-vote prediction $\hat{y}_i$ across 5 seeds, and define the flip rate between two setups A and B as

$$\text{FlipRate}_{A,B} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}[\hat{y}_i^A \neq \hat{y}_i^B].$$

Measuring susceptibility. We quantify susceptibility as the extent to which a judge's predictions change when in-context information is added to the prompt. As rough indicators of impact, we report accuracy deltas relative to the base template,

$$\Delta_{Acc_c} = Acc_c - Acc_{\text{base}}, \quad c \in \{\text{context, irrelevant context, examples, misleading examples}\},$$

which capture whether added information improves or degrades agreement with human labels. However, accuracy deltas can mask cases where a judge changes many predictions in offsetting directions. We therefore quantify susceptibility more precisely through the per-condition flip rate relative to the base setup, $\text{FlipRate}_{\text{base},c}$, and summarise overall susceptibility as the average flip rate across the four conditions,

$$\text{Susceptibility} = \frac{1}{|C|} \sum_{c \in C} \text{FlipRate}_{\text{base},c}.$$

This gives a direct measure of how much a judge's outputs are perturbed by in-context information.

Measuring steerability. We quantify steerability analogously, as the extent to which a judge's predictions change when given an alternative safety definition (definition a or b) in the prompt. As rough indicators, we report

$$\Delta_{Acc_d} = Acc_d - Acc_{\text{base}}, \quad d \in \{\text{Def a, Def b}\},$$

where Acc_d is computed against ground-truth labels re-annotated under definition d, so that higher values reflect successful steering. To isolate the precise response to the definition itself, we again use flip rate: $\text{FlipRate}_{\text{base},d}$ measures how often a judge changes its prediction when prompted with definition d instead of the base definition. A judge with high steerability will have large flip rates, while a judge anchored to its internal priors will show flip rates close to zero regardless of the definition supplied.

A.6 Frequency analysis

As a proxy for the prior knowledge a judge is likely to have about a given sample, we evaluate how frequent words and groups of words in the prompts and completions are in large pre-training corpora. We use fineweb (Penedo et al., 2024) and fineweb-2 (Penedo et al., 2025) which are large filtered datasets based on CommonCrawl snapshots, in English and multilingual respectively as a proxy for what the LLMs were trained on. For each of the 5 languages, we take a random subsample of 10B tokens and build a word-count table using a language-appropriate tokenizer (`fugashi` for Japanese, `kiwipiepy` for Korean, and a unicode-aware regex splitter for English, French and Arabic). After dropping the 200 most frequent tokens per language as stopwords, we score each prompt and completion by the Zipf frequency of its rarest remaining content word, which we use as a signal for how much knowledge the judge likely has about the topic discussed in the prompt or completion. Figure 7 shows the distribution of the frequency of each prompt in MultilingualPrompts and NovelPrompts.

We compare judge performance and judge flip rates (i.e., how likely they are to change their prediction in response to context) on each sample to the frequency of each sample, to test our hypothesis that judges have more fixed predictions on samples on which they have more prior knowledge.

Figure 7: Distribution of estimated frequency scores of each prompt in MultilingualPrompts and NovelPrompts. The frequency of each word is calculated in Fine-Web 1 and 2, and the rarest word per prompt is used as the overall frequency estimate for each prompt (freq_min).

B   Supplementary Results on Susceptibility to Context

B.1   Susceptibility to Demonstrations

In Figure 8 we show the impact of correct demonstrations and incorrect demonstrations on Multilingual-Prompts and GlobalPrompts. We show results from safety evaluation of prompts-only (just user requests) and on model responses to the user requests as the top and bottom panel of each Figure. In all 4 cases, demonstrations have a minor impact on judge performance, but there are some inconsistencies across judges. For instance, in the completions evaluation setting, Command-A's performance drops substantially when given demonstrations.

Figure 8: Impact of demonstrations and incorrect demonstrations on judge F1 score in MultilingualPrompts and NovelPrompts, prompts-only, and completions safety evaluation. Bars represent mean F1 across 5 seeds, with error bars showing standard deviation.

B.2 Susceptibility to Novel Contextual Information

B.2.1 Effects of context on judge performance

We provide additional results on the effect of context on judge performance in MultilingualPrompts prompts evaluation (Figure 9), and in completions evaluation on both datasets (Figure 10). Context has no significant effect on MultilingualPrompts, but is consistently beneficial in NovelPrompts.

Figure 9: Context has little effect in MultilingualPrompts. Bars compare F1 scores (mean and std dev across 5 seeds) when judges are only given the user request vs. when they are also given additional in-context information explaining the user request.

Figure 10: Context trends are similar in model completions safety evaluation. Bars compare F1 scores (mean and std dev across 5 seeds) when judges are only given the user request vs. when they are also given additional in-context information explaining the user request.

B.2.2 Effects of irrelevant context on judge performance

We test whether judges are robust to irrelevant context, which Explanatory text

Figure 11: Effect of context and irrelevant context on judge performance. Bars represent mean judge F1 score averaged across the 10 generalist judges with error bars showing standard deviation across seeds. Top row shows results from MultilingualPrompts and bottom from NovelPrompts, while the left plots show results from prompt-only safety evaluation, and the right plots from model completions safety evaluation.

B.3 Supplementary results on judge susceptibility on low-frequency samples

We show results from the same frequency experiments but on NovelPrompts, which show very similar trends to MultilingualPrompts. Judges do not change their predictions on most samples, and the samples where they do change their predictions are the ones they have less prior knowledge about (as measured by corpus frequency in Fine-Web).

Figure 12: In NovelPrompts, judges are also more susceptible to changing their predictions on samples on which they have less prior knowledge. Left: bars represent the proportion of samples on which judges change in response to being given: novel context information, irrelevant context information, task demonstrations, and incorrect task demonstrations. Judges keep most of their predictions fixed regardless of in-context information. Right: the likelihood that judges change their prediction increases as the frequency of words in the evaluation sample decreases. We measure word frequency on a large pre-training dataset and use it proxy for judge prior knowledge.

B.4 Supplementary Results on Judge Susceptibility

We measure how often each judge flips their prediction in response to context, demonstrations, irrelevant context, and misleading demonstrations in NovelPrompts and MultilingualPrompts. We then test whether each judge's flip rate is correlated across these 4 experimental conditions in both datasets, and plot these in the heatmap 13. All correlations are positive, including many statistically significant correlations, suggesting that each judge has an inherent susceptibility level which affects how much it changes its predictions in response to various types of context.

Figure 13: Similar judges change their predictions in response to context, demonstrations, shuffled context, and misleading demonstrations in NovelPrompts and MultilingualPrompts datasets. Pearson correlation values in each judge's flip rate are shown. Analysis is done over the 10 generalist LLM-judges.

C Supplementary Results on Judge Steerability

C.1 Supplementary Results on Judge Performance Drop for Adjusted Safety Definitions

We show each judge's steerability to safety definition A and B, as measured by their average accuracy relative to the adjusted ground truth. We also include judge performance when they are not given any safety definition, and measure accuracy relative to our base safety labels. While judge steerability varies, in both MultilingualPrompts and NovelPrompts, judge accuracy drops substantially when evaluating with respect to these safety definition variants.

Figure 14: Most judges cannot adapt to safety definition variants, causing their accuracy with respect to the adjusted ground-truth to drop sharply. The first two bars show judge accuracy relative to the base safety policy when they are provided with and without the policy, and the last two show accuracy relative two safety definition variants that they are given in the prompt. Mean and standard deviation across 5 and seeds is shown in MultilingualPrompts (top) and NovelPrompts (bottom).

C.2 Supplementary Results on Testing the Judges with an Absurd Safety definition

To further test how judges adapt to changing safety definitions, we provide them with an absurd safety definition where only ball sports are unsafe and everything else is safe (prompt template in §A.4). We first test them on the base sports dataset and find that most judges reach very high accuracy (above 95%, as shown in Figure 15) suggesting that they can be steered to absurd safety definitions. When given the standard safety template (with the true safety policy), they have 58% accuracy, which is expected as that corresponds to the proportion of safe samples, and all judges predict the samples are unsafe.

We next try steering the judges to varied safety definitions, still in the sports realm. We modify the definition in similar ways as for previous experiments. In definition B we swap non-ball sports to be unsafe and ball sports to be safe, while in definition C we say that any mention of a sport is unsafe. We find that judges are also broadly highly steerable to these definitions.

Finally, we test how far judges can relinquish their safety priors by testing them on MultilingualPrompts with the sports definition. This way they are confronted with truly unsafe prompts, but which are safe according to the definition in their prompt (about sports). We find that most judges do correctly predict all samples as safe, except for Claude-4-5-Sonnet and Claude-3-5-Haiku which make mistakes on 15 to 35%

Figure 15: Bars indicate judge accuracy and standard deviation on the sports dataset when given various sports safety definition variants. Accuracy is measured relative to the safety definition given in the prompt, except for the last bar, where judges are given the standard safety template, but tested on the sports dataset where ball sports are considered unsafe (poor performance is therefore expected). Most judges are highly steerable to this absurd safety definition.

of the samples, as they are likely unable to be completely steered to this absurd safety definition (Figure 16).

Figure 16: Most judges are steerable to the absurd safety definition, even if it means predicting truly unsafe samples as safe. Bars represent mean and std dev of accuracy on the MultilingualPrompts dataset (where ground truth is all safe as there is no mention of sports) when judges are given the absurd sports safety definition.

C.3 Supplementary Results on Steerability when Safety Evaluation Task is Reframed as Classification

Here we additionally show per-judge prediction changes in response to varying safety definitions, framed as either safety evaluation or as an arbitrary classification task, in NovelPrompts (Figure 17). Trends are very similar to MultilingualPrompts, where judge steerability is much higher when the task is a classification.

C.4 Steerability is correlated across judges

We test whether the same judges are steerable across safety definition modifications and datasets, and find that this is indeed the case. For example, gpt-5-2 is consistently one of the most steerable judges, while claude-4-5-sonnet is one of the least.

Figure 17: Steerability is much higher when the safety judging task (lighter bars) is masked as a classification task (darker bars). Steerability is measured as average judge prediction flips (relative to the expected number of flips) when given a safety definition variant. Results are shown on NovelPrompts.

Figure 18: **Judge steerability is positively correlated across tasks**. In both MultilingualPrompts and NovelPrompts similar judges are steerable to safety definition a and b. Steerability is measured as changes in prediction (flip rate) relative to when judges are given with the base definition, across 5 seeds.

D Supplementary Results on Judge Human Agreement

D.1 Judge Susceptibility vs. Steerability vs. Accuracy

We test whether susceptibility, steerability, and judge performance are related, to understand whether each property needs to be evaluated independently or not. As shown in Figure 19, in both NovelPrompts and MultilingualPrompts, none of the three properties are significantly correlated, suggesting indeed that they are separate properties.

Figure 19: Judge susceptibility, steerability, and accuracy are not significantly correlated in MultilingualPrompts (top) and NovelPrompts (bottom). We compare susceptibility (as measured by mean prediction flips in response to various types of context), steerability (as measured by mean prediction flips in response to safety definition variants a and b), and human agreement (as measured by mean F1 score). We also report Pearson correlation values.

D.2 Judge performance lacks cross-task transfer

Importantly, the best judges in one task are not necessarily the best judges in another task, suggesting that safety judge performance does not always generalise (Figure 20). For instance, while Claude 3-5-haiku is one of the worst models at the multilingual safety evaluation task, it has the highest F1 score in NovelPrompts. Pearson correlation values across the three datasets are therefore weak and not statistically significant. Similarly, judge performance across languages is not necessarily correlated (Figure 21). Claude-4-5-sonnet is the best judge in Korean but only 7th in Japanese. Judges should be evaluated in the target deployment language before being selected.

We find that judge F1 score is not significantly correlated across our three evaluation datasets (Novel-Prompts, MultilingualPrompts, and SorryBench).

D.3 Judge performance across languages is not always correlated

We test how much judge performance varies across the 4 languages in MultilingualPrompts, and find that the best judge in one language is not necessarily the best in another language (Figure 21).

D.4 Model capabilities are not indicative of model judging capabilities

To understand what makes a judge have high human agreement, we compare judge performance on judge benchmarks to model performance on a variety of standard LLM benchmarks (general capability). We also compare judge benchmark performance to model safety performance (safety capability). We measure

Figure 20: Judge performance across safety evaluation tasks is not always correlated.

Figure 21: Judge rankings (in terms of accuracy) in the Arabic, French, Japanese, and Korean subsets of MultilingualPrompts are shown.

judge performance on three datasets: our two MultilingualPrompts and NovelPrompts, and Sorry-BENCH (Xie et al., 2025), which share format but cover differing languages and topics. We measure model performance on MMLU (Hendrycks et al., 2021), global MMLU (Singh et al., 2025), and IFEval (Zhou et al., 2023) to cover general, multilingual, and instruction following performance. We measure model safety on two internal safety benchmarks, English and Multilingual, whose definition aligns with the base definition the judges are evaluated with, that was annotated by the same expert annotators used in the Judge performance benchmarks.

Model capabilities are not indicative of model judging capabilities Across the three judge evaluation datasets, no consistent predictor of their abilities emerges (Figure 23). We find, for instance, that a model can be highly safe but bad at *judging* safety (e.g., GPT-oss-20b in NovelPrompts), or vice versa (e.g., Llama-70b in Sorry-BENCH).

As shown in Figure 22, general knowledge and multilingual knowledge appear more correlated to judging performance (average Pearson correlation values of 0.62 and 0.68 for MultilingualPrompts and NovelPrompts respectively), but there are still many examples where this trend does not hold. For instance, Tiny-Aya ranks as best on Korean GlobalMMLU but worst safety judge in the Korean MultilingualPrompts samples.

Instruction-following abilities are even less related to judging performance, with no significant correlations in any of the tasks. This would be surprising, but is less so in light of the previous susceptibility and steerability results Overall, these results make predicting which judge will be good at a given task difficult without actually testing.

Finally, we explore how judge performance (as measured by F1 score on MultilingualPrompts, Novel-Prompts, and SORRY-Bench, on prompts-only and completions safety evaluation) correlates with model performance on standard LLM benchmarks. Figure 23 left shows Pearson correlations between mean judge and model performance, while the right figure breaks the performance down by language, and shows per-language correlation. Overall, general knowledge (as measured by MMLU and Global MMLU) appear most correlated to judge performance, but trends are still inconsistent across datasets.

Figure 22: **Multilingual knowledge does not predict multilingual safety judging abilities.** Each dot represents one judge tested in one language on Global-MMLU and on MultilingualPrompts.

Figure 23: Left: judge performance vs. model performance. Right: judge performance vs. model performance per language. Instruction-following results for French are missing as we did not have an internal translation of this dataset. Pearson correlation values are shown, and have a * if they are statistically significant.