TEST-TIME ADAPTATION VIA SELF-TRAINING WITH NEAREST NEIGHBOR INFORMATION

ABSTRACT

Test-time adaptation (TTA) aims to adapt a trained classifier using online unlabeled test data only, without any information related to the training procedure. Most existing TTA methods adapt the trained classifier using the classifier's prediction on the test data as pseudo-label. However, under test-time domain shift, accuracy of the pseudo labels cannot be guaranteed, and thus the TTA methods often encounter performance degradation at the adapted classifier. To overcome this limitation, we propose a novel test-time adaptation method, called *Test-time Adaptation via Self-Training with nearest neighbor information (TAST)*, which is composed of the following procedures: (1) adds trainable adaptation modules on top of the trained feature extractor; (2) newly defines a pseudo-label distribution for the test data by using the nearest neighbor information; (3) trains these modules only a few times during test time to match the nearest neighbor-based pseudo label distribution and a prototype-based class distribution for the test data; and (4) predicts the label of test data using the average predicted class distribution from these modules. The pseudo-label generation is based on the basic intuition that a test data and its nearest neighbor in the embedding space are likely to share the same label under the domain shift. By utilizing multiple randomly initialized adaptation modules, TAST extracts useful information for the classification of the test data under the domain shift, using the nearest neighbor information. Our experiments on two standard benchmark tasks, domain generalization and image corruption, show that TAST outperforms the state-of-the-art TTA methods.

1 INTRODUCTION

Deep neural networks often encounter significant performance degradations under domain shift (i.e., distribution shift). This phenomenon has been observed in various tasks including classification (Taori et al., 2020; Wang et al., 2021b), visual recognition (Saenko et al., 2010; Csurka, 2017), and reinforcement learning (Cobbe et al., 2019; Mendonca et al., 2020; Lee and Chung, 2021b). There are two broad classes of domain adaptation methods that attempt to solve this problem: supervised domain adaptation (SDA) (Tzeng et al., 2015; Motiian et al., 2017) and unsupervised domain adaptation (UDA) (Ganin and Lempitsky, 2015; Long et al., 2016; Sener et al., 2016). Both SDA and UDA methods aim to obtain domain-invariant representations by aligning the representations of training and test data closely in the embedding space. While testing, UDA methods require the training dataset and SDA methods additionally require labeled data of the test domain. However, in practice, it is often difficult to access training datasets or labeled data in the test domain during test time, due to data security or labeling cost.

Test-time adaptation (TTA) (Iwasawa and Matsuo, 2021; Wang et al., 2021a) is a prominent approach to alleviate the problems caused by the domain shift. TTA methods aim to adapt the trained model to the test domain without a labeled dataset in the test domain and any information related to the training procedure (e.g., training dataset, feature statistics of training domain (Sun et al., 2020; Liu et al., 2021; Eastwood et al., 2022)). TTA methods have access to the online unlabeled test data only, whereas domain adaptation methods assume access to the whole (i.e., offline) test data.

There are two popular categories for TTA: entropy minimization (Liang et al., 2020; Wang et al., 2021a) and prototype-based methods (Iwasawa and Matsuo, 2021). Entropy minimization methods fine-tune the trained feature extractor, which is the trained classifier except the last linear layer, by

minimizing the prediction entropy of test data. These methods force the classifier to have over-confident predictions for the test data, and thus have a risk of degrading model calibration (Guo et al., 2017; Mukhoti et al., 2020), a measure of model interpretability and reliability. One form of entropy minimization is self-training (Rosenberg et al., 2005; Lee, 2013; Arazo et al., 2020; Xie et al., 2020). Self-training methods use predictions from the classifier as pseudo labels for the test data and fine-tune the classifier to make it fit to the pseudo labels. These methods have a limitation that the fine-tuned classifier can overfit to the inaccurate pseudo labels, resulting in confirmation bias (Arazo et al., 2020). This limitation can be harmful when the performance of the trained classifier is significantly degraded due to domain shift. On the other hand, Iwasawa and Matsuo (2021) proposed a prototype-based TTA method, named T3A, that simply modifies a trained linear classifier (the last layer) by using the pseudo-prototype representations of each class and the prototype-based classification for test data, where the prototypes are constructed by previous test data and the prediction for the data from trained classifier. T3A does not update the trained feature extractor at test time. T3A is simple but it brings a marginal performance gain (Table 1 and 3).

In this work, we propose a new test-time adaptation method, which is simple yet effective in mitigating the confirmation bias problem of self-training, by adding adaptation modules on top of the feature extractor, which are simply trainable during test time. We use the prototype-based classifier as in T3A, but not in the embedding space of the original feature extractor but in the embedding space of the adaptation modules, trained with nearest neighbor information, to achieve higher performance gains than the original simple prototype-based classifier method. Our method, named *Test-time Adaptation via Self-Training with nearest neighbor information (TAST)*, is composed of the following procedures: (1) adds randomly initialized adaptation modules on top of the feature extractor at the beginning of test time (Figure 1); (2) generates pseudo label distribution for a test data considering the nearest neighbor information; (3) trains the adaptation modules only a few times during test time to match the nearest neighbor-based pseudo label distribution and a prototype-based class distribution for the test data; and (4) predicts the label of test data using the average predicted class distribution from the adaptation modules. Specifically, in (1), we add the trainable adaptation modules to obtain new feature embeddings that are useful for classification in the test domain. In (2), TAST assigns the mean of the labels of the nearby examples in the embedding space as the pseudo label distribution for the test data based on the idea that a test data and its nearest neighbors are more likely to have the same label. In (3), TAST trains the adaptation modules to output the pseudo label distribution when the test data is fed into (Figure 1 *Right*). And in (4), we average the predicted class distributions from adaptation modules for the prediction of test data (Figure 1 *Left*).

We investigate the effectiveness of TAST on two standard benchmarks, domain generalization and image corruption. We demonstrate that TAST outperforms the current state-of-the-art test-time adaptation methods such as Tent (Wang et al., 2021a), T3A, and TTT++ (Liu et al., 2021) on the two benchmarks. For example, TAST surpasses the current state-of-the-art algorithm by 1.01% on average with ResNet-18 learned by Empirical Risk Minimization (ERM) on the domain generalization benchmarks. Extensive ablation studies show that both the nearest neighbor information and the adaptation module utilization contribute to the performance increase. Moreover, we experimentally found that the adaptation modules adapt feature extractor outputs effectively although the adaptation modules are randomly initialized at the beginning of test time and trained with a few gradient steps per test batch during test time.

2 PRELIMINARIES

Test-time domain shift   Consider a labeled dataset $D^{\text{train}} = \{(x_i, y_i)\}_{i=1}^{n_{\text{train}}}$ drawn from a distribution P^{train}, where $x \in \mathbb{R}^d$ and $y \in \mathcal{Y} := \{1, 2, \cdots, K\}$ for a K-class classification problem. A number of classifiers have been proposed that easily classify unseen test data under the i.i.d. assumption that unseen test data D^{test} is drawn from the same distribution as training data, i.e., $P^{\text{train}} = P^{\text{test}}$. We assume the classifier is a deep neural network composed of two parts: a feature extractor $f_\theta : \mathbb{R}^d \to \mathbb{R}^{d_z}$ and a linear classifier $g_w : \mathbb{R}^{d_z} \to \mathcal{Y}$, where θ and w are the neural network parameters. ERM optimizes θ and w to obtain a good classifier for future samples in D^{test} by minimizing the objective function $\mathcal{L}(\theta, w) = \mathbb{E}_{(x,y) \in D^{\text{train}}} [l(g_w(f_\theta(x)), y)]$, where l is a loss function such as cross-entropy loss. However, under the test-time domain shift (i.e., distribution shift), the i.i.d. assumption between the training and test distributions does not hold, i.e., $P^{\text{train}} \neq P^{\text{test}}$, and the trained classifiers often show poor classification performance for the test data.

Figure 1: Overview of our proposed algorithm TAST. *Left:* A schematic of TAST compared to T3A. The dashed class indicates the ground-truth class. (a) T3A constructs prototypes that represent classes in the embedding space of feature extractor f_θ using a support set $\mathbb{S}$. Then T3A predicts the label of the test data x as the class of the nearest prototype. (b) TAST adds trainable adaptation modules $\{h_{\phi_i}\}$ on top of f_θ and computes the estimated class distributions of x by aggregating the pseudo labels of the nearest support examples of x in the embedding space of adaptation modules. We predict the label of x using the averaged estimated class distribution of x over adaptation modules. *Right:* Overview of TAST training. Based on the intuition that a test data x and its nearest neighbors $\mathcal{NN}(x; \mathbb{S})$ are likely to share the same label, we use the mean of prototype-based predictions of the support examples in $\mathcal{NN}(x; \mathbb{S})$ as the pseudo label of x. We train the adaptation modules to predict the pseudo labels when the test data is fed into. Notice that the feature extractor f_θ is frozen during test time.

Prototype-based classification in test-time adaptation Prototype-based classification refers to a method that obtains prototype representations, which represent each class in the embedding space, and then predicts the label of an input as the class of the nearest prototype. Since labeled data is not available in the TTA setting, T3A utilizes a support set that is composed of previous test data and their predictions for the test data by the trained classifier. T3A does not modify parameters of the classifier. Since the embedding space of the feature extractor is unchanged during the test time, T3A constructs the support set using the feature representations for test data instead of the data itself. Specifically, a support set $\mathbb{S}_t = \{\mathbb{S}_t^1, \mathbb{S}_t^2, \cdots, \mathbb{S}_t^K\}$ is a set of test samples until time t. The support set is initialized with the weight of the last linear classifier, i.e., $\mathbb{S}_0^k = \left\{ \frac{w^k}{\|w^k\|} \right\}$, where w^k is the parts of w related to k-th class for $k = 1, 2, \ldots, K$. At time t, the support set is updated as

$$\mathbb{S}_t^k = \begin{cases} \mathbb{S}_{t-1}^k \cup \left\{ \frac{f_\theta(x_t)}{\|f_\theta(x_t)\|} \right\} & \text{if } \arg\max_c p_c = k \\ \mathbb{S}_{t-1}^k & \text{otherwise,} \end{cases} \tag{1}$$

where p_k represents the likelihood that the classifier assigns x_t to the k-th class. Using the support set $\mathbb{S}_t^k$, one can obtain the class prototype for class k by taking the centroid of the representations in the support set. Formally, the prototype μ_k for class k is computed as $\mu_k = \frac{1}{|\mathbb{S}_t^k|} \sum_{z \in \mathbb{S}_t^k} z$ for $k = 1, 2, \cdots, K$. Then, the prediction for an input x_t is made by comparing the distances between the embedding of x_t and the prototypes, i.e., $\hat{y} = \arg\min_c d(f_\theta(x_t), \mu_c)$ with a pre-defined metric d such as Euclidean distance or cosine similarity.[1] Since the wrongly pseudo labeled examples can degrade the classification performance, the support examples with unconfident pseudo labels are regarded as unreliable examples and filtered out, i.e., at time stamp t,

$$\mathbb{S}_t^k = \{z | z \in \mathbb{S}_t^k, H(\sigma(g_w(z))) \le \alpha_k\}, \tag{2}$$

where α_k is the M-th largest prediction entropy of the samples from $\mathbb{S}_t^k$, H is Shannon entropy (Lin, 1991), and σ is the softmax function. T3A modifies only the support set configuration and does not update the trained model parameters at test time. Thus, T3A cannot effectively mitigate the classification performance degradation caused by test-time domain shift. To address this issue, we extract useful information for classification of the test data by utilizing multiple randomly initialized adaptation modules that are trained using nearest neighbor-based pseudo labels.

---

[1] We use the cosine similarity for experiments throughout this paper.

Algorithm 1 TAST

Require: Feature extractor f_θ, number of adaptation modules N_e, adaptation modules $\{h_{\phi_i}\}_{i=1}^{N_e}$, test batch $\mathbb{B}$, support set $\mathbb{S}$, number of gradient steps per adaptation T, number of support examples per each class M, number of nearby support examples N_s, learning rate α
Ensure: Predictions for all $x \in \mathbb{B}$
  Update the support set $\mathbb{S}$ with eq. (1) and (2)
  Retrieve the nearest neighbors $\mathcal{NN}(x; \mathbb{S})$ for all $x \in \mathbb{B}$ with eq. (3)
  for $t = 1 : T$ **do**
    for $i = 1 : N_e$ **do**
      for $x \in \mathbb{B}$ **do**
        Obtain the nearest neighbor-based pseudo label $\hat{p}_i^{\text{TAST}}(\cdot|x)$ of x with eq. (5)
        Compute the prototype-based class distribution $p_i^{\text{proto}}(\cdot|x)$ of x with eq. (7)
      end for
      $\phi_i \leftarrow \phi_i - \alpha \nabla_{\phi_i} \frac{1}{|\mathbb{B}|} \sum_{x \in \mathbb{B}} \text{CE}(\hat{p}_i^{\text{TAST}}(\cdot|x), p_i^{\text{proto}}(\cdot|x))$
    end for
  end for
  Compute the predictions for all $x \in \mathbb{B}$ with eq. (9)

---

3 METHODOLOGY

In this section, we describe two main components of our method TAST: adaptation module utilization (Section 3.1) and pseudo-label generation considering nearest neighbor information (Section 3.2).

3.1 ADAPTATION MODULE

We first discuss the parts to be fine-tuned in the trained classifier before explaining our test-time adaptation method. One possible choice is to fine-tune the whole network parameters in the classifier during test time, but this approach can be unstable and inefficient (Wang et al., 2021a; Kumar et al., 2022). Another choice is to fine-tune only the parameters of batch normalization (BN) layers in the classifier as in Wang et al. (2021a). Although it achieves effective test-time adaptation, it has a limitation that it can be utilized only if there are BN layers in the trained classifier. The other choice is to train a new classifier added on top of the frozen feature extractor during test time as in Lee and Chung (2021a). We construct the new classifier by adding a randomly initialized adaptation module as illustrated in Figure 1. During the test time, we train the adaptation module and predict the label of the test data using prototype-based class distributions in the embedding space of the adaptation module. Furthermore, we consider an ensemble scheme that uses multiple adaptation modules. Ensemble schemes (Wen et al., 2020; YM. et al., 2020; Mesbah et al., 2021) refer to methods of combining independently trained classifiers to obtain more robust and accurate predictions than those of a single classifier. We train the adaptation modules independently and predict the label of the test data using the average predicted class distribution from the adaptation modules.

3.2 SELF-TRAINING WITH NEAREST NEIGHBOR INFORMATION

TAST generates pseudo label distributions for unlabeled test data with the nearest neighbor information and fine-tunes the adaptation modules with the pseudo label distributions. The whole adaptation procedure of TAST is described in Algorithm 1. We first update the support set $\mathbb{S}$ and filter out the unconfident examples from the support set as in Iwasawa and Matsuo (2021) with the equations (1) and (2). Then, we find N_s nearby support examples of test data x in the embedding space of f_θ. We denote $\mathcal{NN}(x; \mathbb{S})$ as the set of nearby support examples of x,

$$\mathcal{NN}(x; \mathbb{S}) := \{z \in \mathbb{S} | d(f_\theta(x), z) \le \beta_x\}, \tag{3}$$

where β_x is the distance between x and the N_s-th nearest neighbor of x from $\mathbb{S}$ in the embedding space of f_θ. Each adaptation module is trained individually during test time. For the i-th adaptation module, we compute the prototype representations $\mu_{i,1}, \mu_{i,2}, \ldots, \mu_{i,K}$ in the embedding space of $h_{\phi_i} \circ f_\theta$ with a support set $\mathbb{S} = \{\mathbb{S}^1, \mathbb{S}^2, \cdots, \mathbb{S}^K\}$, i.e., $\mu_{i,k} = \frac{1}{|\mathbb{S}^k|} \sum_{z \in \mathbb{S}^k} h_{\phi_i}(z)$, for $k = 1, 2, \ldots, K$. With the prototypes, we compute the prototype-based predicted class distribution

of the nearby support examples in the embedding space of $h_{\phi_i} \circ f_\theta$, i.e., for $z \in \mathcal{NN}(x; \mathbb{S})$, the likelihood that the prototype-based classifier assigns z to the k-th class is computed as

$$p_i^{\text{proto}}(k|z) := \frac{\exp(-d(h_{\phi_i}(z), \mu_{i,k})/\tau)}{\sum_c \exp(-d(h_{\phi_i}(z), \mu_{i,c})/\tau)}, \tag{4}$$

where τ is the softmax temperature[2]. With the nearest neighbor information, TAST generates a pseudo label distribution $\hat{p}_i^{\text{TAST}}$ of x by aggregating prototype-based predicted class distribution of the nearby support examples in $\mathcal{NN}(x; \mathbb{S})$ as

$$\hat{p}_i^{\text{TAST}}(k|x) := \frac{1}{N_s} \sum_{z \in \mathcal{NN}(x;\mathbb{S})} \mathbb{1}[\arg\max_c p_i^{\text{proto}}(c|z) = k], \tag{5}$$

for $k = 1, 2, \ldots, K$. Especially, we use the one-hot class distributions for pseudo label generation as in Lee (2013); Sohn et al. (2020). Then, we fine-tune the adaptation modules by minimizing the cross-entropy loss between the predicted class distribution of the test example and the nearest neighbor-based pseudo label distribution:

$$\mathcal{L}^{\text{TAST}}(\phi_i) = \frac{1}{|D^{\text{test}}|} \sum_{x \in D^{\text{test}}} \text{CE}(\hat{p}_i^{\text{TAST}}(\cdot|x), p_i^{\text{proto}}(\cdot|x)), \tag{6}$$

$$p_i^{\text{proto}}(k|x) := \frac{\exp(-d(h_{\phi_i}(f_\theta(x)), \mu_{i,k})/\tau)}{\sum_c \exp(-d(h_{\phi_i}(f_\theta(x)), \mu_{i,c})/\tau)}, \ k = 1, 2, \ldots, K, \tag{7}$$

where CE denotes the standard cross-entropy loss. We iterate the pseudo labeling and fine-tuning processes for T steps per batch. Finally, we predict the label of x using the average predicted class distribution p_i^{TAST} from the adaptation modules, i.e.,

$$p_i^{\text{TAST}}(k|x) := \frac{1}{N_s} \sum_{z \in \mathcal{NN}(x;\mathbb{S})} p_i^{\text{proto}}(k|z) \tag{8}$$

$$\hat{y}^{\text{TAST}} = \arg\max_c p^{\text{TAST}}(c|x) = \arg\max_c \frac{1}{N_e} \sum_{i=1}^{N_e} p_i^{\text{TAST}}(c|x) \tag{9}$$

On the other hand, for the case when BN layers exist in the feature extractor, we consider a variant of TAST, named TAST-BN, that fine-tunes the BN layers instead of adaptation modules. The support set stores the test data itself instead of the feature representations since the embedding space of the feature extractor steadily changes during the test time. The pseudocode for TAST-BN is presented in Appendix B.

4 EXPERIMENTS

In this section, we show the effectiveness of our method compared to the state-of-the-art test-time adaptation methods on two standard benchmarks, i.e., domain generalization and image corruption. We compare TAST with the following baseline methods: (1) Pseudo Labeling (PL) (Lee, 2013) fine-tunes the trained classifier using confident pseudo labels based on classifier predictions; (2) PLClf is a modified version of PL that fine-tunes only the last linear classifier; (3) Tent (Wang et al., 2021a) fine-tunes only the parameters of the BN layers to minimize the prediction entropy of test data; (4) TentBN is a modified version of Tent that adds a BN layer between the feature extractor and the last linear classifier, and fine-tunes only the added BN layer; (5) TentClf is a modified version of Tent that fine-tunes only the last linear classifier instead of the BN layers; (6) SHOTIM (Liang et al., 2020) updates the feature extractor to maximize the mutual information between an input and its prediction; (7) SHOT is a method that adds a pseudo-label loss to SHOTIM; (8) T3A predicts the label of the test data by comparing distances between test data and the generated pseudo-prototypes. Originally, SHOT is one of source-free domain adaptation methods which focus on the offline setting, but we compare our method with the online version of SHOT for a fair comparison.

---

[2]We set τ manually to 0.1 inspired by Oreshkin et al. (2018) for experiments throughout this paper. More experimental results with different τ are summarized in Appendix C

Table 1: Average accuracy (%) using classifiers learned by ERM on the domain generalization benchmarks. We use ResNet-18 and ResNet-50 as backbone networks. **Bold** indicates the best performance for each benchmark. Our proposed method TAST outperforms all the baselines on all of the benchmarks.

Method	Backbone	VLCS	PACS	OfficeHome	TerraIncognita	Avg
ERM		74.88±0.46	79.29±0.77	62.10±0.31	40.62±1.19	64.22
+Tent		72.88±0.82	83.89±0.54	60.86±0.39	33.70±1.09	62.83
+TentBN		67.02±1.16	80.75±1.01	62.64±0.38	39.91±0.76	62.58
+TentClf		72.96±1.48	78.57±1.78	59.33±0.62	38.30±3.44	62.29
+SHOT		65.24±2.29	82.36±0.63	62.58±0.39	33.57±1.04	60.94
+SHOTIM	ResNet-18	64.86±2.22	82.33±0.61	62.57±0.39	33.35±1.23	60.78
+PL		62.97±2.72	70.98±1.78	58.20±3.21	37.44±7.20	57.40
+PLClf		74.89±0.61	78.11±2.30	61.92±0.41	41.78±1.94	64.18
+T3A		77.26±1.49	80.83±0.67	63.21±0.50	40.20±0.60	65.38
+TAST (Ours)		**77.27±0.67**	81.94±0.44	**63.70±0.52**	**42.64±0.72**	**66.39**
+TAST-BN (Ours)		75.21±2.36	**87.07±0.53**	62.79±0.41	39.43±2.24	66.13
ERM		76.71±0.50	83.21±1.14	67.13±0.99	45.93±1.34	68.25
+Tent		72.96±1.27	85.16±0.62	66.29±0.77	37.08±2.04	65.37
+TentBN		69.65±1.17	83.69±1.16	67.91±0.89	43.89±1.25	66.29
+TentClf		75.80±0.68	82.66±1.59	66.79±0.98	43.64±2.59	67.22
+SHOT		67.07±0.90	84.07±1.23	67.65±0.72	35.20±0.82	63.50
+SHOTIM	ResNet-50	66.93±0.84	84.14±1.25	67.65±0.77	34.37±1.07	63.27
+PL		69.41±3.12	81.72±4.61	62.85±3.05	38.09±2.35	63.02
+PLClf		75.65±0.88	83.33±1.59	67.01±1.00	46.66±2.12	68.16
+T3A		77.29±0.39	83.92±1.13	68.26±0.84	45.61±1.10	68.77
+TAST (Ours)		**77.66±0.48**	84.11±1.22	68.63±0.70	**47.43±2.09**	**69.46**
+TAST-BN (Ours)		73.52±1.37	**89.16±0.47**	**68.88±0.50**	41.47±2.88	68.26

4.1 DOMAIN GENERALIZATION

The domain generalization benchmarks are designed to evaluate the generalization ability of the trained classifiers to the unseen domain. The evaluation is performed by a leave-one-domain-out procedure, which uses a domain as a test domain and the remaining domains as training domains. We use the publicly released code [3] of T3A for the domain generalization benchmarks.

4.1.1 EXPERIMENTAL SETUP

Datasets We test TAST on four domain generalization benchmarks, specifically VLCS (Fang et al., 2013), PACS (Li et al., 2017), OfficeHome (Venkateswara et al., 2017), and TerraIncognita (Beery et al., 2018). VLCS is composed of photographic images from four different datasets (PASCAL VOC207 (Everingham et al., 2010), LableMe (Russell et al., 2008), Caltech 101 (Fei-Fei et al., 2007), and SUN09 (Choi et al., 2010)), consisting of 10,729 examples of 5 categories (bird, car, chair, dog, and person). PACS is composed of images of objects from four different domains (photo, art, cartoon, and sketch), consisting of 9,991 examples of 7 categories (dog, elephant, giraffe, guitar, horse, house, and person). OfficeHome is composed of images of objects in the office and home from 4 different domains (artistic images, clip art, product, and real-world images), consisting of 15,588 examples of 65 categories (e.g., alarm clock, backpack, and batteries). TerraIncognita is composed of wild animal images taken from 4 different locations (L100, L38, L43, and L46), consisting of 24,788 examples of 10 classes.

Training setup For a fair comparison, we follow the training setup including dataset splits and hyperparameter selection method used in Iwasawa and Matsuo (2021). We use residual networks (He et al., 2016) including batch normalization layers with 18 and 50 layers (hereinafter referred to as ResNet-18 and ResNet-50, respectively), which are widely used for classification tasks. We train the networks with various learning algorithms such as ERM and CORAL (Sun and Saenko, 2016). Details about the learning algorithms are explained in Appendix A. The backbone networks

---
[3]https://github.com/matsuolab/T3A

Table 2: Ablation studies to evaluate the effects of the number of adaptation module and the nearest neighbor information. We use ResNet-18 trained by ERM. TAST-N is a method that removes adaptation modules from TAST.

Method	N_e	VLCS	PACS	OfficeHome	TerraIncognita	Avg
ERM	-	74.88±0.46	79.29±0.77	62.10±0.31	40.62±1.19	64.22
+T3A	-	77.26±1.49	80.83±0.67	63.21±0.50	40.20±0.60	65.38
+TAST-N (Ours)	-	76.20±1.87	81.62±0.52	63.54±0.63	41.88±1.21	65.81
	1	75.20±0.77	81.23±0.70	62.09±0.64	42.59±0.41	65.28
+TAST (Ours)	5	76.68±0.77	81.81±0.13	63.51±0.59	42.68±0.80	66.17
	10	77.43±0.62	81.56±0.85	63.39±0.56	42.60±0.63	66.25
	20	77.27±0.67	81.94±0.44	63.70±0.52	42.64±0.72	66.39

are trained with the default hyperparameters introduced in Gulrajani and Lopez-Paz (2021). We use a BatchEnsemble (Wen et al., 2020), which is an efficient ensemble method that reduces the computational cost by weight-sharing, for the adaptation modules of TAST. The output dimension of each adaptation module is set to a quarter of the output dimension of the feature extractor[4], e.g., 128 for ResNet-18. We use Kaiming normalization (He et al., 2015) for initializing the adaptation modules at the beginning of test time. We run experiments using four different random seeds. More details on the training setups can be found in Appendix A. Moreover, a discussion on computation complexity such as runtime comparison is summarized in Appendix A.

Hyperparameters For a fair comparison, the baseline methods use the same hyperparameters as in Iwasawa and Matsuo (2021). TAST uses the same set of possible values for each hyperparameter with baseline methods. TAST involves four hyperparameters: the number of gradient steps per adaptation T, the number of support examples per each class M, and the number of nearby support examples N_s, the number of adaptation modules N_e. We define a finite set of possible values for each hyperparameter, $N_s \in \{1, 2, 4, 8\}$, $T \in \{1, 3\}$, and $M \in \{1, 5, 20, 50, 100, -1\}$, where -1 means to storing all samples without filtering. N_e is set to 20. We use Adam optimizer with a learning rate of 0.001. More details on the hyperparameters can be found in Appendix A. Moreover, refer to Appendix C for the sensitivity analysis on hyperparameters including the test batch sizes.

4.1.2 EXPERIMENTAL RESULTS

In Table 1, we summarize the experimental results of test-time adaptation methods using classifiers trained by ERM. Our method consistently improves the performance of the trained classifiers by 2.17% for ResNet-18 and 1.21% for ResNet-50 on average, respectively. TAST also outperforms the baseline methods including the state-of-the-art test-time adaptation method T3A. Compared to T3A, TAST shows better performance by 1.01% for ResNet-18 and 0.69% for ResNet-50 on average, respectively. Especially, we find that our method significantly improves the performance of the trained classifiers in the TerraIncognita benchmark, which is a challenging benchmark in that the trained classifier shows the lowest prediction accuracy. We observe that the performance of the baseline methods, which fine-tune the feature extractors, is lower than that of the classifiers without adaptation, whereas TAST-BN improves the performance of the trained classifiers. Refer to Appendix C for the experimental results of test-time adaptation methods using classifiers trained by different learning algorithms such as CORAL (Sun and Saenko, 2016), MMD (Li et al., 2018), and Mixup (Xu et al., 2020).

Effect of nearest neighbor information To understand the effect of nearest neighbor information, we compare Tent and TAST-BN, both of which fine-tine the BN layers. To adjust the BN layers, Tent uses entropy minimization loss, whereas TAST-BN uses the pseudo-label loss using the nearest neighbor information. As shown in Table 1, the performances of TAST-BN is better than those of Tent by 3.3% for ResNet-18 and 2.89% for ResNet-50, respectively. In addition, we consider an ablated variant of TAST, named TAST-N, that removes adaptation modules from TAST. TAST-N is optimization-free and has the same support set configuration as T3A. T3A uses the prototype-based

---

[4]More experimental results with different output dimensions are summarized in Appendix C.

prediction of the test data itself, whereas TAST-N uses the aggregated predicted class distribution of the nearby support examples. As shown in Table 2, the prediction using the nearest neighbor information leads to a performance gain of 0.43% on average.

Effect of adaptation modules TAST adds randomly initialized adaptation modules on top of the trained feature extractor as illustrated in Figure 1 and trains the adaptation modules during test time. For each test batch, we update the adaptation modules T times using pseudo label distributions considering nearest neighbor information. We set T to 1 or 3 throughout all experiments. To verify that the few step updates are sufficient to train the adaptation modules, we conduct experiments with different $T \in \{0, 1, 2, 4, 8\}$. We test on PACS using classifiers learned by ERM while M and N_s are set to -1 and one of $\{1, 2, 4, 8\}$. We summarize the experimental results in Figure 2. We observe that the performance of the adapted classifier is better than that of the non-adapted classifier (i.e., $T = 0$) and robust to changes in T. Hence, we conjecture that we can obtain a sufficiently good adaptation module with a few-step updates similar to Lee and Chung (2021a).

In addition, to investigate the effect of adaptation modules, we test TAST with a varying number of adaptation modules, e.g., $N_e \in \{1, 5, 10, 20\}$. In Table 2, we find that utilizing a single adaptation module leads to degraded performance than TAST-N. However, TAST with multiple adaptation modules shows improvement over TAST-N and T3A on average.

Method	CIFAR-10C	CIFAR-100C
No adaptation	29.14	60.35
+SHOT	15.32	41.54
+Tent	13.95	39.04
+PL	22.34	40.06
+T3A	26.68	58.28
+TAST (Ours)	26.61	60.74
+TAST-BN (Ours)	**13.08**	**37.82**
+TTT++	14.33	42.38

Figure 2: Sensitivity analysis about N_s and T. Average accuracy on test environment A using classifiers learned by ERM on PACS when M is set to -1.

Table 3: Average error rate (%) on CIFAR-10C/100C. We test on the highest level of image corruption. **Bold** indicates the best performance for each image corruption.

4.2 Image Corruption

The image corruption benchmark is designed to evaluate the robustness of a classifier to an unseen corrupted test domain, when the classifier learned on a clean training domain. We use the publicly released code [5] of TTT++ (Liu et al., 2021) for the image corruption benchmark.

4.2.1 Experimental setup

We test robustness of TAST to image corruption on CIFAR-10/100 (Krizhevsky and Hinton, 2009). The CIFAR-10/100 dataset is composed of generic images consisting of a training and a test dataset with 50000 and 10000 examples of 10/100 classes, respectively. To make a corrupted test dataset, we apply 15 types of common image corruptions (e.g., Gaussian noise, shot noise) to the test dataset. We call the corrupted dataset CIFAR-10C/100C (Hendrycks and Dietterich, 2019). We use the highest level (i.e., level-5) of image corruption for this experiment. We use ResNet-50 as a backbone network. For a fair comparison, we use the released trained model of Liu et al. (2021) and the same hyperparameters whenever possible. We use Adam optimizer with a learning rate of 0.001 for test-time adaptation. The number of nearby support examples N_s is set to 1, the number of gradient steps per adaptation T is set to 1, the number of adaptation modules N_e is set to 20, the number of support examples per each class M is set to 100, and the test batch size is set to 128. We run experiments using four different random seeds. More experimental results on other combinations of hyperparameters are summarized in Appendix C.

---

[5] https://github.com/vita-epfl/ttt-plus-plus

4.2.2 EXPERIMENTAL RESULTS

The overall experimental results on CIFAR-10C/100C are summarized in Table 3. We compare our method with the existing TTA methods and the online version of TTT++, which is one of the state-of-the-art methods on CIFAR-10C/100C. TTT++ is one of the test-time training methods, which fine-tunes the feature extractor using the instance discrimination task along with matching the feature statistics of training and test time. In Table 3, we observe that the TTA methods which use the frozen feature extractor such as T3A and TAST show slight performance changes compared to existing TTA methods that fine-tune the feature extractor. On the other hand, TAST-BN outperforms all the TTA methods and TTT++ and it achieves better performance by 1.25% for CIFAR-10C and 4.56% for CIFAR-100C on average, respectively. Refer to Appendix D for the detailed experimental results on 15 types of image corruptions.

5 RELATED WORKS

Test-time training methods   Test-time training methods fine-tune trained classifiers using the self-supervised learning task used at training time. Sun et al. (2020) uses a rotation prediction task (Feng et al., 2019), which predicts the rotation angle of the rotated images. Liu et al. (2021) use an instance discrimination task (Chen et al., 2020). However, TTA methods, our focus in this paper, have no access to any information related to the training procedure. We empirically demonstrated that our TAST outperforms the existing test-time training methods on the image corruption benchmark even without the knowledge about the self-supervised learning task.

Source-free domain adaptation methods   Source-Free Domain Adaptation (SFDA) methods (Liang et al., 2020; Ishii and Sugiyama, 2021; Yeh et al., 2021; Eastwood et al., 2022) aim to adapt trained classifiers to unseen test domains without training dataset. SFDA methods mainly focus on the setting that they can access the whole unlabeled test data, whereas TTA methods focus on the setting that they can access the online unlabeled test data only. Recently, several SFDA methods using nearest neighbor information (Tang et al., 2021; Yang et al., 2021) have achieved good performances in domain adaptation benchmarks. Especially, NRC (Yang et al., 2021) is built on the similar intuition that a test data and its nearest neighbors in the embedding space share the same label under domain shift. The main difference between NRC and our proposed methods is the adaptation module utilization. Unlike NRC, TAST is a prototype-based method and proposes an ensemble scheme for TTA that adds adaptation modules on the top of the feature extractor.

Ensemble scheme in test-time adaptation   BACS (Zhou and Levine, 2021) incorporates a Bayesian inference framework into the TTA setting. BACS learns an approximate posterior for model parameter during training time, and adapts the trained model with a regularization term induced by the approximated posterior during test time. The main difference between ensemble schemes of TAST and BACS is the timing when the ensemble of models is built. BACS constructs the ensemble of predictive models at the beginning of training time and trains the models independently during training time. Also, the ensemble members are individually adapted during test time. However, TAST focuses on building an ensemble of adaptation modules at the beginning of test time.

6 CONCLUSION

We propose a simple and efficient test-time adaptation method, named TAST, that defines new pseudo-label distributions for test data using the nearest neighbor information and improves the classification performance by using prototype-based classification in the embedding space of adaptation modules trained with the pseudo-label distributions. We demonstrate that our method outperforms the state-of-the-art test-time adaptation methods on domain generalization and image corruption benchmarks. To the best of our knowledge, our work is the first work that utilizes adaptation modules which are randomly initialized at the beginning of test time and trained only a few times during test time. We expect that utilization of adaptation module can be combined with the other methods in source-free domain adaptation or test-time training.

REFERENCES

E. Arazo, D. Ortego, P. Albert, N. E. O'Connor, and K. McGuinness. Pseudo-labeling and confirmation bias in deep semi-supervised learning, 2020.

S. Beery, G. Van Horn, and P. Perona. Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 1597–1607. PMLR, 13–18 Jul 2020.

M. J. Choi, J. J. Lim, A. Torralba, and A. S. Willsky. Exploiting hierarchical context on a large database of object categories. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 129–136, 2010. doi: 10.1109/CVPR.2010.5540221.

K. Cobbe, O. Klimov, C. Hesse, T. Kim, and J. Schulman. Quantifying generalization in reinforcement learning. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 1282–1289. PMLR, 09–15 Jun 2019.

G. Csurka. Domain adaptation for visual applications: A comprehensive survey. *CoRR*, abs/1702.05374, 2017.

C. Eastwood, I. Mason, C. Williams, and B. Schölkopf. Source-free adaptation to measurement shift via bottom-up feature restoration. In *International Conference on Learning Representations*, 2022.

M. Everingham, L. Gool, C. K. Williams, J. Winn, and A. Zisserman. The pascal visual object classes (voc) challenge. *Int. J. Comput. Vision*, 88(2):303–338, jun 2010. ISSN 0920-5691. doi: 10.1007/s11263-009-0275-4.

C. Fang, Y. Xu, and D. N. Rockmore. Unbiased metric learning: On the utilization of multiple datasets and web images for softening bias. In *2013 IEEE International Conference on Computer Vision*, pages 1657–1664, 2013. doi: 10.1109/ICCV.2013.208.

L. Fei-Fei, R. Fergus, and P. Perona. Learning generative visual models from few training examples: An incremental bayesian approach tested on 101 object categories. *Comput. Vis. Image Underst.*, 106(1):59–70, apr 2007. ISSN 1077-3142. doi: 10.1016/j.cviu.2005.09.012.

Z. Feng, C. Xu, and D. Tao. Self-supervised representation learning by rotation feature decoupling. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10356–10366, 2019. doi: 10.1109/CVPR.2019.01061.

Y. Ganin and V. Lempitsky. Unsupervised domain adaptation by backpropagation. In F. Bach and D. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 1180–1189, Lille, France, 07–09 Jul 2015. PMLR.

I. Gulrajani and D. Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021.

C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger. On calibration of modern neural networks. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1321–1330. PMLR, 06–11 Aug 2017.

K. He, X. Zhang, S. Ren, and J. Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pages 1026–1034, 2015. doi: 10.1109/ICCV.2015.123.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016. doi: 10.1109/CVPR.2016.90.

D. Hendrycks and T. Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

M. Ishii and M. Sugiyama. Source-free domain adaptation via distributional alignment by matching batch normalization statistics. *ArXiv*, abs/2101.10842, 2021.

Y. Iwasawa and Y. Matsuo. Test-time classifier adjustment module for model-agnostic domain generalization. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 2427–2440. Curran Associates, Inc., 2021.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization, 2014. cite arxiv:1412.6980Comment: Published as a conference paper at the 3rd International Conference for Learning Representations, San Diego, 2015.

A. Krizhevsky and G. Hinton. Learning multiple layers of features from tiny images. Technical Report 0, University of Toronto, Toronto, Ontario, 2009.

A. Kumar, A. Raghunathan, R. M. Jones, T. Ma, and P. Liang. Fine-tuning can distort pretrained features and underperform out-of-distribution. In *International Conference on Learning Representations*, 2022.

D.-H. Lee. Pseudo-label : The simple and efficient semi-supervised learning method for deep neural networks. *ICML 2013 Workshop : Challenges in Representation Learning (WREPL)*, 07 2013.

D. H. Lee and S.-Y. Chung. Unsupervised embedding adaptation via early-stage feature reconstruction for few-shot classification. In M. Meila and T. Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 6098–6108. PMLR, 18–24 Jul 2021a.

S. Lee and S.-Y. Chung. Improving generalization in meta-rl with imaginary tasks from latent dynamics mixture. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 27222–27235. Curran Associates, Inc., 2021b.

D. Li, Y. Yang, Y. Song, and T. M. Hospedales. Deeper, broader and artier domain generalization. In *IEEE International Conference on Computer Vision, ICCV 2017, Venice, Italy, October 22-29, 2017*, pages 5543–5551. IEEE Computer Society, 2017. doi: 10.1109/ICCV.2017.591.

H. Li, S. J. Pan, S. Wang, and A. C. Kot. Domain generalization with adversarial feature learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

J. Liang, D. Hu, and J. Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International Conference on Machine Learning (ICML)*, pages 6028–6039, 2020.

J. Lin. Divergence measures based on the shannon entropy. *IEEE Transactions on Information Theory*, 37(1):145–151, Jan. 1991. ISSN 0018-9448. doi: 10.1109/18.61115.

Y. Liu, P. Kothari, B. van Delft, B. Bellot-Gurlet, T. Mordan, and A. Alahi. Ttt++: When does self-supervised test-time training fail or thrive? In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 21808–21820. Curran Associates, Inc., 2021.

M. Long, H. Zhu, J. Wang, and M. I. Jordan. Unsupervised domain adaptation with residual transfer networks. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

R. Mendonca, X. Geng, C. Finn, and S. Levine. Meta-reinforcement learning robust to distributional shift via model identification and experience relabeling. *CoRR*, abs/2006.07178, 2020.

Y. Mesbah, Y. Y. Ibrahim, and A. M. Khan. Domain generalization using ensemble learning. *CoRR*, abs/2103.10257, 2021.

S. Motiian, M. Piccirilli, D. A. Adjeroh, and G. Doretto. Unified deep supervised domain adaptation and generalization. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, Oct 2017.

J. Mukhoti, V. Kulharia, A. Sanyal, S. Golodetz, P. Torr, and P. Dokania. Calibrating deep neural networks using focal loss. In *Advances in Neural Information Processing Systems*, volume 33, pages 15288–15299. Curran Associates, Inc., 2020.

B. Oreshkin, P. Rodríguez López, and A. Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

C. Rosenberg, M. Hebert, and H. Schneiderman. Semi-supervised self-training of object detection models. *2005 Seventh IEEE Workshops on Applications of Computer Vision (WACV/MOTION'05) - Volume 1*, 1:29–36, 2005.

B. Russell, A. Torralba, K. Murphy, and W. Freeman. Labelme: A database and web-based tool for image annotation. *International Journal of Computer Vision*, 77(1-3):157–173, 2008. ISSN 0920-5691. doi: 10.1007/s11263-007-0090-8.

K. Saenko, B. Kulis, M. Fritz, and T. Darrell. Adapting visual category models to new domains. In *Proceedings of the 11th European Conference on Computer Vision: Part IV*, ECCV'10, page 213–226, Berlin, Heidelberg, 2010. Springer-Verlag. ISBN 364215560X.

O. Sener, H. O. Song, A. Saxena, and S. Savarese. Learning transferrable representations for unsupervised domain adaptation. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

J. Snell, K. Swersky, and R. Zemel. Prototypical networks for few-shot learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

K. Sohn, D. Berthelot, C.-L. Li, Z. Zhang, N. Carlini, E. D. Cubuk, A. Kurakin, H. Zhang, and C. Raffel. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. *arXiv preprint arXiv:2001.07685*, 2020.

B. Sun and K. Saenko. Deep CORAL: correlation alignment for deep domain adaptation. *CoRR*, abs/1607.01719, 2016.

Y. Sun, X. Wang, L. Zhuang, J. Miller, M. Hardt, and A. A. Efros. Test-time training with self-supervision for generalization under distribution shifts. In *ICML*, 2020.

S. Tang, Y. Yang, Z. Ma, N. Hendrich, F. Zeng, S. S. Ge, C. Zhang, and J. Zhang. Nearest neighborhood-based deep clustering for source data-absent unsupervised domain adaptation. *CoRR*, abs/2107.12585, 2021.

R. Taori, A. Dave, V. Shankar, N. Carlini, B. Recht, and L. Schmidt. Measuring robustness to natural distribution shifts in image classification. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 18583–18599. Curran Associates, Inc., 2020.

E. Tzeng, J. Hoffman, T. Darrell, and K. Saenko. Simultaneous deep transfer across domains and tasks. In *ICCV*, 2015.

H. Venkateswara, J. Eusebio, S. Chakraborty, and S. Panchanathan. Deep hashing network for unsupervised domain adaptation. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5385–5394, 2017.

D. Wang, E. Shelhamer, S. Liu, B. Olshausen, and T. Darrell. Tent: Fully test-time adaptation by entropy minimization. In *International Conference on Learning Representations*, 2021a.

J. Wang, C. Lan, C. Liu, Y. Ouyang, and T. Qin. Generalizing to unseen domains: A survey on domain generalization. In Z.-H. Zhou, editor, *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21*, pages 4627–4635. International Joint Conferences on Artificial Intelligence Organization, 8 2021b. doi: 10.24963/ijcai.2021/628. Survey Track.

Y. Wen, D. Tran, and J. Ba. Batchensemble: an alternative approach to efficient ensemble and lifelong learning. In *International Conference on Learning Representations*, 2020.

Q. Xie, M.-T. Luong, E. Hovy, and Q. V. Le. Self-training with noisy student improves imagenet classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

M. Xu, J. Zhang, B. Ni, T. Li, C. Wang, Q. Tian, and W. Zhang. Adversarial domain adaptation with domain mixup. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence*, pages 6502–6509. AAAI Press, 2020.

S. Yang, Y. Wang, J. van de weijer, L. Herranz, and S. JUI. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

H.-W. Yeh, B. Yang, P. C. Yuen, and T. Harada. Sofa: Source-data-free feature alignment for unsupervised domain adaptation. In *2021 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pages 474–483, 2021. doi: 10.1109/WACV48630.2021.00052.

A. YM., R. C., and V. A. Self-labelling via simultaneous clustering and representation learning. In *International Conference on Learning Representations*, 2020.

A. Zhou and S. Levine. Bayesian adaptation for covariate shift. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

A IMPLEMENTATION DETAILS

A.1 IMPLEMENTATION DETAILS ON DOMAIN GENERALIZATION BENCHMARKS

We follow the dataset splits and the hyperparameter selection method used in T3A. We split each dataset of training domains into training and validation sets. The training and validation sets are used for network training and hyperparameter selection, respectively. Specifically, we split each dataset into 80% and 20% and use the smaller set as the validation set. We choose the hyperparameters that maximize the validation accuracy of the adapted classifier. This hyperparameter selection method is called the training-domain validation. We train backbone networks using four different learning algorithms: ERM, CORAL, MMD, and Mixup. ERM is explained in Section 2 of the manuscript; CORAL aims to obtain domain-invariant representations by aligning covariance matrices of training data and test data; MMD tries to match the training and test data distributions using the MMD measure; Mixup trains classifiers using mixed images/features and mixed labels created by linear interpolation of examples from the training domains. We run experiments using four different random seeds: 0, 1, 2, and 3.

All the hyperparameters for training and test-time adaptation are taken from T3A and DomainBed. We train the network with Adam optimizer with default hyperparameters introduced in DomainBed, e.g., a learning rate of 0.00005, a weight decay of 0, a dropout rate of 0, and a batch size of 32. In addition to the hyperparameters for test-time adaptation described in Section 4.1.1 of the manuscript, there is one more hyperparameter β for the baseline methods. The learning rate for test-time adaptation is obtained by multiplying β to the learning rate used in training time. We set the confidence threshold for PL and PLClf to 0.9. The possible values for β are set to 0.1, 1.0, and 10.0. For TAST-BN, we restrict the size of the whole support set to 150 due to effective memory usage and reduced runtime since the test data and the support examples are fed into the classifier for every test batch.

A.2 IMPLEMENTATION DETAILS ON IMAGE CORRUPTION BENCHMARKS

We use the same hyperparameters introduced in TTT++. We train ResNet-50 for 1000 epochs using the classification and instance discrimination tasks jointly. The weight on the instance discrimination task for balancing the two tasks is set to 0.1. For the instance discrimination task, we use the same data augmentation schemes of TTT++, e.g., RandomResizeCrop, RandomHorizontalCrop, HorizontalFlip, ColorJitter, RandomGrayscale, and Normalization. We set the batch size for training the networks to 256. At test time, PL, SHOT, and TTT++ use SGD optimizer with a learning rate of 0.001 and a momentum of 0.9. On the other hand, Tent, TAST, and TAST-BN use Adam optimizer with a learning rate of 0.001. We set the batch size to 128 during the test time due to effective memory usage. We run experiments using four different random seeds: 0, 1, 2, and 3. We set the confidence threshold for PL and PLClf to 0.9. For PL, we adjust only the BN layers in the trained model as in Tent. For TAST-BN, we restrict the size of the whole support set to 200. However, even in CIFAR-100C experiments, we can store only two support examples per class if the support set size is fixed at 200. Thus, we do not restrict the size of support set for TAST-BN on CIFAR-100C.

A.3 RUNTIME COMPARISON

We conduct our experiments on TITAN XP. We report the average runtime spent to adapt classifiers that use ResNet-18 as a backbone network in Table 4. We observe that T3A is one of the algorithms having the least running time since it is optimization-free. The methods that fine-tune only the small parts of the trained classifier such as Tent and SHOT also require more running time than T3A. On the other hand, TAST and TAST-BN require more running time than the other TTA methods since these methods require to train the some parts of the classifier and retrieve the nearest neighbors in the embedding space for each test sample.

A.4 COMPUTATIONAL COMPLEXITY OF ADAPTATION MODULES

As shown in Table 4, our method requires more running time than the existing test-time adaptation methods. However, our method is more computationally efficient than the existing method such as BACS that uses an ensemble of classifiers trained at training time. TAST constructs an ensemble

Table 4: Mean runtime to adapt classifiers that use ResNet-18 as a backbone network.

Method	VLCS	PACS	OfficeHome	TerraIncognita
Tent	7m 28s	3m 16s	7m 25s	10m 34s
TentBN	2m 8s	33s	1m 57s	2m 58s
TentClf	2m 7s	34s	1m 57s	2m 56s
SHOT	8m 9s	4m 22s	8m 38s	12m 40s
SHOTIM	8m 8s	4m 19s	8m 35s	12m 35s
PL	8m 18s	4m 43s	8m 43s	12m 55s
PLClf	2m 7s	35s	1m 59s	2m 57s
T3A	2m 9s	33s	2m 15s	2m 59s
TAST (Ours)	10m 34s	9m 30s	22m 24s	26m 14s
TAST-BN (Ours)	18m 43s	16m 32s	38m 27s	45m 5s

of classifiers at the beginning of test-time and trains these classifiers only a few times at test-time. However, BACS trains the ensemble of classifiers independently by several epochs during training time and adapts the classifiers individually during test-time.

B PSEUDOCODE FOR TAST-BN

We present the pseudocode for TAST-BN in Algorithm 2. TAST-BN fine-tunes the BN layers in the feature extractor instead of adaptation modules. Since the embedding space of the feature extractor steadily changes, the support set stores the test data itself instead of the feature representations. Formally, a support set $\mathbb{S}_t = \{\mathbb{S}_t^1, \mathbb{S}_t^2, \ldots, \mathbb{S}_t^K\}$ is a set of test samples until time t. The support set is initialized as an empty set. At the time t, the support set is updated as

$$\mathbb{S}_t^k = \begin{cases} \mathbb{S}_{t-1}^k \cup \{x_t\}, & \text{if } \arg\max_c p_c = k \\ \mathbb{S}_{t-1}^k, & \text{otherwise,} \end{cases} \tag{10}$$

where p_k is the likelihood the classifier assigns x_t to the class k. Using the support set, we retrieve N_s nearby support examples of x in the embedding space of f_θ, i.e.,

$$\mathcal{NN}(x; \mathbb{S}) := \{z \in \mathbb{S} | d(f_\theta(x), f_\theta(z)) \leq \beta_x\}, \tag{11}$$

where β_x is the distance between x and the N_s-th nearest neighbor of x from $\mathbb{S}$ in the embedding space of f_θ. Then, we generate a pseudo label distribution for the test data and fine-tune the BN layers to match the nearest neighbor-based pseudo label and a prototype-based class distributions for the test data with the same procedure described in Section 3 of the manuscript.

C ADDITIONAL EXPERIMENTS

C.1 EXPERIMENTAL RESULTS USING CLASSIFIERS TRAINED BY DIFFERENT LEARNING ALGORITHMS

In Table 5, we show the results of test-time adaptation methods using classifiers trained by three different learning algorithms, namely CORAL, MMD, and Mixup. TAST consistently enhances the performance of the trained classifiers on the benchmarks by 1.73%, 1.81%, and 2.30% on average using the classifiers trained by CORAL, MMD, and Mixup, respectively. We find that TAST has a minor performance gain compared to the results in Table 1 of manuscript, whereas it surpasses T3A on most of benchmarks. Compared to T3A, TAST shows better performance on the benchmarks by 0.21%, 0.14%, and 0.40% on average with the classifiers trained by CORAL, MMD, and Mixup, respectively. Refer to Section 4 in Appendix D for the experimental results of the other baseline methods.

C.2 FINE-TUNING BOTH ADAPTATION MODULES AND BN LAYERS SIMULTANEOUSLY

We consider a method, named TAST-both, that fine-tunes both the attached adaptation modules and the BN layers in the feature extractor simultaneously. Table 6 reports the experimental results

---

Algorithm 2 TAST-BN

Require: Feature extractor f_θ, test batch $\mathbb{B}$, support set $\mathbb{S}$, number of gradient steps per adaptation T, number of support examples per each class M, number of nearby support examples N_s, learning rate α
Ensure: Predictions $\hat{y}_x$ for all $x \in \mathbb{B}$
  Update the support set $\mathbb{S}$ with eq. (10) in Section B
  Retrieve the nearest neighbors $\mathcal{NN}(x; \mathbb{S})$ for all $x \in \mathbb{B}$ with eq. (11) in Section B
  for $t = 1 : T$ **do**
    Compute prototypes $\{\mu_k\}_{k=1}^K$ using the support set in the embedding space of f_θ
    for $z \in \mathcal{NN}(x; \mathbb{S})$ **do**
      $p^{\text{proto}}(k|z) \leftarrow \frac{\exp(-d(f_\theta(z), \mu_k)/\tau)}{\sum_c \exp(-d(f_\theta(z), \mu_c)/\tau)}, k = 1, 2, \ldots, K$
    end for
    for $x \in \mathbb{B}$ **do**
      $\hat{p}^{\text{TAST}}(k|x) \leftarrow \frac{1}{N_s} \sum_{z \in \mathcal{NN}(x; \mathbb{S})} \mathbb{1}[\arg\max_c p^{\text{proto}}(c|z) = k], k = 1, 2, \ldots, K$
      $p^{\text{proto}}(k|x) \leftarrow \frac{\exp(-d(f_\theta(x), \mu_k)/\tau)}{\sum_c \exp(-d(f_\theta(x), \mu_c)/\tau)}, k = 1, 2, \ldots, K$
    end for
    $\theta \leftarrow \theta - \alpha \nabla_\theta \frac{1}{|\mathbb{B}|} \sum_{x \in \mathbb{B}} \text{CE}(\hat{p}^{\text{TAST}}(\cdot|x), p^{\text{proto}}(\cdot|x))$
  end for
  for $x \in \mathbb{B}$ **do**
    $p^{\text{TAST}}(k|x) \leftarrow \frac{1}{N_s} \sum_{z \in \mathcal{NN}(x; \mathbb{S})} p^{\text{proto}}(k|z), k = 1, 2, \ldots, K$
    $\hat{y}_x \leftarrow \arg\max_c p^{\text{TAST}}(c|x)$
  end for

Table 5: Average accuracy (%) on domain generalization benchmarks using classifiers trained by different learning algorithms, namely CORAL, MMD, and Mixup. We use ResNet-18 as a backbone network. **Bold** indicates the best performance for each benchmark. TAST and TAST-BN consistently improve the performance of the trained classifiers and they outperform T3A on most of the benchmarks.

Method	VLCS	PACS	OfficeHome	TerraIncognita	Avg
CORAL	74.00±1.13	81.00±0.79	62.78±0.06	36.51±2.35	63.57
+T3A	75.49±1.67	82.75±0.51	63.72±0.32	38.39±1.39	65.09
+TAST (Ours)	74.82±2.43	83.16±0.81	**64.00±0.25**	**39.21±1.75**	65.30
+TAST-BN (Ours)	**77.01±0.36**	**87.21±0.57**	62.98±0.23	37.45±1.11	**66.16**
MMD	74.90±0.50	81.06±0.92	62.20±0.48	35.73±2.70	63.47
+T3A	**77.28±0.45**	82.52±0.53	63.34±0.55	37.40±1.86	65.14
+TAST (Ours)	76.21±0.79	83.29±0.26	**63.49±0.49**	38.12±2.47	65.28
+TAST-BN (Ours)	76.06±0.89	**86.35±0.76**	63.22±0.26	**39.46±1.63**	**66.27**
Mixup	74.97±0.86	78.29±0.88	61.83±0.88	41.04±1.01	64.03
+T3A	**78.43±0.76**	81.91±0.54	63.49±0.86	39.89±0.90	65.93
+TAST (Ours)	77.19±0.80	82.85±0.36	**63.83±0.74**	41.44±1.67	66.33
+TAST-BN (Ours)	76.89±0.86	**87.14±0.56**	62.09±0.86	**42.70±1.90**	**67.21**

using classifiers learned by ERM on domain generalization benchmarks. We use ResNet-18 as a backbone network. As shown in Table 6, TAST-both shows worse performance than TAST-BN and TAST. We conjecture that the random initialization of adaptation modules and the changes in feature representation due to BN layer training negatively affect the learning of the other layers.

C.3 EXPERIMENTAL RESULTS USING DIFFERENT HYPERPARAMETERS ON CIFAR-10C

In Table 4 of the manuscript, we report the experimental results when N_s and M are set to 1 and 100 on the CIFAR-10C, respectively. In Table 7, we summarize the experimental results using different combinations of N_s and M on the CIFAR-10C. There are two observations in Table 7: (1) T3A has shown the best performances when M is set to 100; and (2) TAST and TAST-BN perform better with smaller N_s.

Table 6: Average accuracy (%) using classifiers trained by ERM on domain generalization benchmarks. We use ResNet-18 as a backbone network. TAST-both is a method fine-tunes both the attached adaptation modules and the BN layers simultaneously. TAST-both shows worse performances than TAST-BN and TAST.

Method	N_e	VLCS	PACS	OfficeHome	TerraIncognita	avg
ERM	-	74.88±0.46	79.30±0.77	62.09±0.31	40.63±1.19	64.22
+T3A	-	77.26±1.49	80.83±0.67	63.21±0.50	40.20±0.60	65.38
+TAST-N	-	76.20±1.87	81.62±0.52	63.54±0.63	41.88±1.21	65.81
+TAST-BN	-	75.21±2.36	87.07±0.53	62.79±0.41	39.43±2.24	66.13
+TAST	1	75.20±0.77	81.23±0.70	62.09±0.64	42.59±0.41	65.28
+TAST	5	76.68±0.77	81.81±0.13	63.51±0.59	42.68±0.80	66.17
+TAST	10	77.43±0.62	81.56±0.85	63.39±0.56	42.60±0.63	66.25
+TAST	20	77.27±0.67	81.94±0.44	63.70±0.52	42.64±0.72	66.39
+TAST-both	1	73.35±0.57	84.85±0.56	61.70±0.39	39.27±2.05	64.79
+TAST-both	5	73.88±0.35	84.99±0.63	61.81±0.44	39.16±1.57	64.96
+TAST-both	10	73.66±1.57	85.13±0.27	62.03±0.52	38.50±1.25	64.83
+TAST-both	20	75.16±0.17	85.52±0.05	62.01±0.67	38.54±1.52	65.31

Table 7: Average error rate (%) in the online setting on CIFAR-10C with different hyperparameters.

Method	M	N_s	gauss	brit	contr	defoc	elast	fog	frost	glass	impul	jpeg	motn	pixel	shot	snow	zoom
No adaptation	-	-	48.73	7.01	13.27	11.84	23.38	29.41	28.24	50.78	57.00	19.46	23.38	47.88	44.00	21.93	10.84
+T3A	1	-	44.56	8.28	13.27	13.45	22.18	28.59	27.18	46.43	55.11	18.96	22.59	42.92	40.32	21.77	10.53
+T3A	5	-	44.65	7.94	14.11	13.34	22.67	29.00	28.57	45.92	56.03	19.67	24.16	40.18	40.55	22.61	12.02
+T3A	20	-	44.26	7.72	13.82	13.35	22.24	28.71	28.36	45.49	55.87	19.34	23.76	39.82	40.38	22.44	12.20
+T3A	50	-	42.82	7.43	13.65	12.36	22.15	28.54	27.69	44.42	54.91	19.13	22.83	38.33	38.53	22.09	11.15
+T3A	100	-	41.87	7.30	13.61	11.99	22.06	28.52	27.13	44.10	54.26	18.71	22.54	37.53	37.84	21.97	10.72
+T3A	-1	-	43.83	7.33	13.56	11.63	22.11	29.07	27.56	46.79	55.16	18.73	22.77	41.16	39.58	22.23	10.34
+TAST	1	1	47.24	8.68	12.93	16.74	22.31	28.66	27.23	48.76	55.97	19.21	22.63	48.32	42.80	21.57	10.34
+TAST	5	1	47.19	9.78	15.88	15.58	24.30	30.94	29.70	48.66	58.05	21.49	27.57	41.00	44.21	24.58	14.75
+TAST	5	2	48.08	11.34	17.73	17.10	25.93	31.99	30.54	49.77	58.54	23.72	29.55	44.09	45.55	26.23	16.41
+TAST	5	4	48.53	10.95	17.25	16.82	25.58	31.78	30.19	50.00	58.86	23.67	29.35	43.37	45.35	25.63	16.26
+TAST	20	1	43.58	7.74	14.01	12.97	21.90	28.73	27.76	45.62	55.20	19.78	23.63	38.77	39.22	22.73	12.13
+TAST	20	2	44.38	8.22	14.51	13.73	22.28	29.07	28.66	46.30	55.92	20.49	24.39	40.60	40.38	23.37	12.76
+TAST	20	4	44.41	8.19	14.26	13.60	22.22	29.05	28.81	46.17	56.05	20.09	24.24	40.33	40.39	23.18	12.67
+TAST	50	1	42.47	7.37	13.65	12.14	21.48	28.30	26.88	44.99	54.52	19.26	22.76	37.59	37.73	22.06	11.03
+TAST	50	2	42.79	7.62	14.11	12.30	21.57	28.73	27.50	45.26	55.18	19.96	23.10	38.99	38.43	22.43	11.25
+TAST	50	4	42.89	7.54	13.90	12.15	21.45	28.51	27.48	45.10	54.93	19.71	22.87	38.94	38.21	22.29	11.02
+TAST	100	1	42.02	7.34	13.55	11.86	21.38	28.58	26.51	44.99	54.19	18.96	22.55	37.08	37.62	21.84	10.64
+TAST	100	2	42.35	7.61	13.89	11.95	21.50	28.75	27.06	45.15	54.55	19.58	22.77	38.09	37.64	21.99	10.73
+TAST	100	4	42.34	7.50	13.80	11.72	21.45	28.32	26.89	44.75	54.46	19.18	22.54	38.00	37.61	21.97	10.67
+TAST	-1	1	45.20	7.44	14.05	11.55	22.87	30.19	27.87	50.28	57.07	19.65	22.95	41.99	41.35	22.65	10.20
+TAST	-1	2	44.86	7.45	13.88	11.62	22.03	29.38	28.03	50.37	58.25	20.02	22.73	42.67	41.04	22.48	10.30
+TAST	-1	4	44.93	7.36	13.64	11.17	21.57	28.82	28.17	49.63	58.74	19.64	22.41	43.38	41.02	22.15	9.86
+TAST-BN	1	1	19.46	11.95	11.02	12.84	21.54	19.38	16.64	26.03	27.76	17.93	15.29	14.01	19	17.94	11.78
+TAST-BN	5	1	16.21	8.4	8.48	9.56	17.92	15.59	13.06	23.1	23.68	13.58	12.79	11.06	14.85	14.02	8.36
+TAST-BN	5	2	17.26	9.27	9.23	10.51	19.51	16.17	13.86	24.32	24.69	14.57	13.81	12.05	15.98	15.06	8.95
+TAST-BN	5	4	18.89	10.29	11.05	13.23	20.66	16.99	14.79	24.95	26.1	16.12	17.02	13.57	18.42	17.11	10.22
+TAST-BN	20	1	14.91	7.68	7.81	8.62	16.81	15.10	12.25	21.82	22.54	12.38	11.67	10.34	13.77	12.99	7.57
+TAST-BN	20	2	15.11	7.85	7.96	8.75	17.00	15.02	12.32	22.07	22.54	12.57	11.99	10.50	13.98	13.12	7.70
+TAST-BN	20	4	15.00	7.98	8.00	8.71	16.87	14.89	12.24	21.88	22.43	12.55	11.89	10.47	14.06	13.06	7.59

C.4 SENSITIVITY ANALYSIS ON HYPERPARAMETERS

We follow the hyperparameter selection method used in T3A. We split the dataset of training domains into training and validation sets. The validation set is used to select hyperparameters that maximize the validation accuracy of the adapted classifier. On the other hand, for the image corruption benchmark, we use manually determined hyperparameters as in Tent. Thus, we summarized experimental results on other combinations of hyperparameters in Table 8-11.

Additionally, we investigate the sensitivity of two hyperparameters which are set manually throughout all experiments, the softmax temperature τ and the output dimension of adaptation modules d_ϕ. We set τ and d_ϕ to 0.1 and $d_z/4$, where d_z is the output dimension of the feature extractor. In Table 8-11, we report the average accuracy of the adapted classifier by TAST with the different combinations of τ and d_ϕ. In the experiments, we use ResNet-18 as a backbone network trained by ERM on PACS, which is one of the domain generalization benchmarks. We experimentally show that the performance of TAST is robust to changes in τ and d_ϕ. We especially think that the classification performance of TAST is not significantly affected by changes in τ because τ affects both

the prototype-based predicted class distribution of test data and the new pseudo-label distribution using nearest neighbor information and then we train the adaptation modules with the cross-entropy loss affected by τ only a few times per each test batch during test time. Moreover, we can observe a similar classification performance regardless of the dimension of adaptation modules similar to Chen et al. (2020).

Table 8: Sensitivity analysis about the softmax temperature τ and the output dimension of adaptation modules d_ϕ. Average accuracy on test environment A using classifiers learned by ERM on PACS.

| testenv:A | | d_ϕ | | | |
	d_z	$d_z/2$	$d_z/4$ (used)	$d_z/8$	$d_z/16$
10	0.8025	0.8028	0.8024	0.8023	0.8026
1	0.8034	0.8038	0.8029	0.8034	0.8034
τ 0.1 (used)	0.8031	0.8038	0.8056	0.8038	0.8034
0.01	0.8026	0.8018	0.8025	0.8028	0.8023
0.001	0.8020	0.8030	0.8023	0.8019	0.8001

Table 9: Sensitivity analysis about the softmax temperature τ and the output dimension of adaptation modules d_ϕ. Average accuracy on test environment C using classifiers learned by ERM on PACS.

| testenv:C | | d_ϕ | | | |
	d_z	$d_z/2$	$d_z/4$ (used)	$d_z/8$	$d_z/16$
10	0.7842	0.7838	0.7841	0.7838	0.7835
1	0.7830	0.7836	0.7829	0.7837	0.7836
τ 0.1 (used)	0.7817	0.7815	0.7826	0.7816	0.7824
0.01	0.7810	0.7816	0.7842	0.7832	0.7825
0.001	0.7811	0.7796	0.7802	0.7806	0.7803

Table 10: Sensitivity analysis about the softmax temperature τ and the output dimension of adaptation modules d_ϕ. Average accuracy on test environment P using classifiers learned by ERM on PACS.

| testenv:P | | d_ϕ | | | |
	d_z	$d_z/2$	$d_z/4$ (used)	$d_z/8$	$d_z/16$
10	0.9611	0.9611	0.9614	0.9613	0.9609
1	0.9614	0.9614	0.9611	0.9614	0.9616
τ 0.1 (used)	0.9615	0.9620	0.9644	0.9613	0.9606
0.01	0.9621	0.9609	0.9613	0.9606	0.9604
0.001	0.9611	0.9615	0.9607	0.9606	0.9613

Table 11: Sensitivity analysis about the softmax temperature τ and the output dimension of adaptation modules d_ϕ. Average accuracy on test environment S using classifiers learned by ERM on PACS.

| testenv:S | | d_ϕ | | | |
	d_z	$d_z/2$	$d_z/4$ (used)	$d_z/8$	$d_z/16$
10	0.7180	0.7208	0.7186	0.7155	0.7185
1	0.7175	0.7214	0.7180	0.7211	0.7202
τ 0.1 (used)	0.7211	0.7222	0.7252	0.7216	0.7220
0.01	0.7236	0.7232	0.7223	0.7225	0.7209
0.001	0.7246	0.7196	0.7251	0.7235	0.7225

We used the test batch size as in T3A and Tent for domain generalization and image corruption benchmarks, respectively, as described in Appendix A and Section 4 of the manuscript. We summarize experimental results using different test batch size. We conduct experiments using classifiers, which have ResNet-18 backbone networks, learned by ERM on PACS. As shown in Table 12, we

can find that Tent and PL show reduced performance in experiments using smaller test batch size, but T3A, TAST, and TAST-BN are robust to changes in test batch size.

Table 12: Ablation studies to evaluate the effects of the test batch size.

Methods	Batch size B				
	8	16	32 (used)	64	128
ERM	79.31± 0.75	79.30±0.76	79.29±0.77	79.29±0.76	79.28±0.70
+Tent	77.52±0.49	81.16±0.46	83.89±0.54	83.90±0.54	83.85±0.12
+SHOT	81.44±0.32	82.12±0.75	82.36±0.63	83.18±0.34	82.95±0.33
+PL	67.90±4.26	70.33±3.53	70.98±1.78	77.52±2.89	78.90±0.39
+T3A	81.21±0.76	81.22±0.69	80.83±0.67	81.20±0.73	81.27±0.6
+TAST (ours)	81.81±0.35	81.52±1.04	81.94±0.44	81.92±0.87	81.69±0.64
+TAST-BN (ours)	**86.78±0.78**	**86.66±1.24**	**87.07±0.53**	**86.90±0.49**	**86.92±0.42**

D FULL RESULTS

Table 13: Full results using classifiers trained by ERM for Table 1 of the manuscript on VLCS. We use ResNet-18 as a backbone network.

Method	C	L	S	V	Avg
ERM	94.70±1.33	63.79±1.30	67.90±1.97	73.15±1.37	74.88
+Tent	89.82±2.89	61.98±1.10	65.51±1.91	74.21±1.61	72.88
+TentBN	79.80±4.74	58.51±1.44	61.62±0.92	68.14±1.74	67.02
+TentClf	94.75±1.43	63.74±1.41	67.92±2.22	65.40±6.91	72.96
+SHOT	91.45±6.83	48.26±1.77	54.75±2.59	66.51±1.25	65.24
+SHOTIM	90.28±7.00	47.96±1.45	54.66±2.47	66.52±1.19	64.86
+PL	93.57±2.24	53.82±2.51	50.58±9.50	53.91±2.78	62.97
+PLClf	94.67±1.38	63.64±1.31	67.90±2.21	73.34±1.00	74.89
+T3A	97.52±1.99	65.32±2.24	70.70±3.48	75.51±1.75	77.26
+TAST (Ours)	99.17±0.60	65.87±1.90	68.13±1.76	75.92±1.75	77.27
+TAST-BN (Ours)	92.60±8.66	64.75±1.29	67.27±3.14	76.23±3.73	75.21

Table 14: Full results using classifiers trained by ERM for Table 1 of the manuscript on PACS. We use ResNet-18 as a backbone network.

Method	A	C	P	S	Avg
ERM	77.78±0.81	75.09±1.22	95.19±0.29	69.11±1.22	79.29
+Tent	82.21±1.07	81.20±0.51	95.32±0.33	76.82±1.97	83.89
+TentBN	78.89±0.67	77.45±0.82	95.77±0.40	70.89±2.75	80.75
+TentClf	78.16±1.05	75.01±1.53	95.50±0.35	65.60±5.96	78.57
+SHOT	81.09±0.86	79.68±0.91	96.18±0.27	72.48±2.04	82.36
+SHOTIM	81.10±0.90	79.66±0.95	96.18±0.27	72.35±2.03	82.33
+PL	76.42±4.89	61.05±5.48	95.70±0.56	50.75±8.79	70.98
+PLClf	79.09±1.41	75.46±2.93	95.43±0.32	62.48±7.31	78.11
+T3A	78.81±0.97	77.14±1.20	95.92±0.36	71.44±1.63	80.83
+TAST (Ours)	80.56±0.53	78.26±0.99	96.44±0.20	72.52±0.77	81.94
+TAST-BN (Ours)	86.49±0.20	83.70±2.57	97.23±0.11	80.85±1.42	87.07

Table 15: Full results using classifiers trained by ERM for Table 1 of the manuscript on OfficeHome. We use ResNet-18 as a backbone network.

Method	A	C	P	R	Avg
ERM	55.19±0.49	47.76±1.02	72.22±0.53	73.21±0.89	62.10
+Tent	53.39±0.61	48.28±0.88	70.50±0.68	71.29±0.72	60.86
+TentBN	55.53±0.43	49.53±0.95	72.47±0.27	73.01±1.23	62.64
+TentClf	55.17±0.67	36.73±1.94	72.21±0.52	73.22±0.97	59.33
+SHOT	55.14±0.57	50.27±1.18	71.69±0.45	73.21±0.91	62.58
+SHOTIM	55.08±0.56	50.29±1.17	71.71±0.40	73.21±0.90	62.57
+PL	54.49±1.06	34.66±13.13	71.45±0.37	72.20±0.65	58.20
+PLClf	55.14±0.70	47.70±1.25	72.21±0.54	72.62±0.96	61.92
+T3A	55.10±0.74	49.56±1.14	74.10±0.55	74.07±1.18	63.21
+TAST (Ours)	56.15±0.68	50.04±1.31	74.33±0.28	74.28±1.23	63.70
+TAST-BN (Ours)	55.11±0.58	51.35±0.85	72.58±0.80	72.13±0.78	62.79

Table 16: Full results using classifiers trained by ERM for Table 1 of the manuscript on TerraIncognita. We use ResNet-18 as a backbone network.

Method	L100	L38	L43	L46	Avg
ERM	37.18±2.46	36.12±4.20	53.18±1.27	36.02±1.37	40.62
+Tent	38.29±0.48	25.82±3.91	41.53±1.59	29.15±1.83	33.70
+TentBN	40.55±1.46	37.44±2.22	46.33±1.32	35.30±1.26	39.91
+TentClf	34.44±13.31	34.19±5.76	52.71±2.03	31.86±2.26	38.30
+SHOT	33.87±0.66	28.58±2.10	40.99±2.07	30.83±1.26	33.57
+SHOTIM	33.83±1.29	28.13±2.30	40.81±2.18	30.64±1.46	33.35
+PL	51.92±1.19	35.61±20.74	39.97±10.98	22.26±8.21	37.44
+PLClf	45.22±2.45	36.03±5.81	52.76±1.54	33.10±2.27	41.78
+T3A	36.22±1.89	40.08±1.98	50.72±1.02	33.79±1.25	40.20
+TAST (Ours)	43.67±2.83	39.24±3.79	52.64±3.02	35.01±1.09	42.64
+TAST-BN (Ours)	51.06±7.31	32.74±7.54	41.70±2.86	32.21±3.05	39.43

Table 17: Full results using classifiers trained by ERM for Table 1 of the manuscript on VLCS. We use ResNet-50 as a backbone network.

Method	C	L	S	V	Avg
ERM	97.66±0.64	63.87±1.71	71.21±1.52	74.09±2.06	76.71
+Tent	92.36±2.44	58.46±3.29	67.84±2.03	73.19±2.68	72.96
+TentBN	85.36±3.49	58.35±3.46	66.47±2.71	68.42±2.11	69.65
+TentClf	97.61±0.58	63.67±2.10	68.77±1.27	73.16±1.31	75.80
+SHOT	98.72±1.50	46.82±2.57	55.70±1.78	67.04±2.88	67.07
+SHOTIM	98.65±1.46	46.54±2.32	55.81±2.32	66.73±2.82	66.93
+PL	98.48±0.34	53.45±2.82	59.45±9.24	66.24±8.63	69.41
+PLClf	97.63±0.64	63.36±2.10	69.74±0.78	71.86±4.53	75.65
+T3A	99.17±0.38	64.78±1.61	73.01±3.24	72.20±2.84	77.29
+TAST (Ours)	99.35±0.30	65.64±1.78	73.63±3.58	72.01±2.68	77.66
+TAST-BN (Ours)	96.09±2.40	60.22±6.08	65.78±6.51	71.99±5.90	73.52

Table 18: Full results using classifiers trained by ERM for Table 1 of the manuscript on PACS. We use ResNet-50 as a backbone network.

Method	A	C	P	S	Avg
ERM	82.92±1.65	78.05±3.36	96.50±0.32	75.38±3.31	83.21
+Tent	82.54±1.32	84.90±1.35	95.45±0.93	77.74±1.36	85.16
+TentBN	82.75±2.01	79.50±2.26	96.78±0.20	75.73±3.22	83.69
+TentClf	83.00±1.87	77.86±4.20	96.55±0.36	73.25±6.14	82.66
+SHOT	84.67±1.70	80.17±1.39	96.58±0.52	74.86±2.95	84.07
+SHOTIM	84.62±1.79	80.24±1.41	96.54±0.46	75.16±2.88	84.14
+PL	84.59±5.51	76.35±2.57	96.41±0.68	69.54±11.22	81.72
+PLClf	83.88±2.00	78.93±3.68	96.53±0.40	73.96±6.08	83.33
+T3A	83.56±2.03	79.75±3.14	96.99±0.24	75.36±3.57	83.92
+TAST (Ours)	83.85±2.05	79.15±3.03	96.93±0.27	76.49±3.13	84.11
+TAST-BN (Ours)	87.11±2.04	88.50±1.93	97.79±0.47	83.23±1.42	89.16

Table 19: Full results using classifiers trained by ERM for Table 1 of the manuscript on OfficeHome. We use ResNet-50 as a backbone network.

Method	A	C	P	R	Avg
ERM	61.32±0.69	53.44±1.11	75.84±1.10	77.90±0.92	67.13
+Tent	60.98±0.67	53.94±1.24	74.49±0.71	75.75±0.53	66.29
+TentBN	62.63±0.45	54.90±1.17	76.20±1.09	77.92±1.01	67.91
+TentClf	61.35±0.73	52.72±1.40	75.23±1.05	77.86±1.07	66.79
+SHOT	61.91±0.33	55.58±0.91	75.49±1.54	77.60±0.80	67.65
+SHOTIM	61.84±0.32	55.63±0.92	75.56±1.60	77.57±0.79	67.65
+PL	59.42±1.55	42.40±12.31	73.80±2.26	75.77±1.50	62.85
+PLClf	61.35±0.40	52.87±1.96	75.86±1.09	77.94±1.10	67.01
+T3A	61.91±0.59	55.07±1.14	77.39±1.38	78.67±0.61	68.26
+TAST (Ours)	62.43±0.80	55.81±1.26	77.46±1.07	78.83±0.93	68.63
+TAST-BN (Ours)	63.22±0.85	58.20±0.98	77.14±1.10	76.94±0.39	68.88

Table 20: Full results using classifiers trained by ERM for Table 1 of the manuscript on TerraIncognita. We use ResNet-50 as a backbone network.

Method	L100	L38	L43	L46	Avg
ERM	46.84±1.96	43.24±2.51	53.32±1.92	40.30±1.93	45.93
+Tent	41.20±2.71	29.72±3.59	41.35±2.92	36.03±2.85	37.08
+TentBN	46.64±1.17	41.11±3.16	49.31±1.05	38.52±2.04	43.89
+TentClf	49.87±3.80	43.31±3.19	53.01±2.31	28.40±6.19	43.64
+SHOT	36.17±2.70	29.80±2.92	41.00±0.30	33.83±1.86	35.20
+SHOTIM	35.56±2.76	27.49±4.01	40.77±0.45	33.67±1.84	34.37
+PL	56.75±5.78	46.12±1.03	29.44±10.14	20.06±4.65	38.09
+PLClf	52.28±3.95	43.76±2.96	52.78±2.15	37.81±2.49	46.66
+T3A	45.13±1.26	44.67±2.56	52.52±0.78	40.13±2.31	45.61
+TAST (Ours)	53.01±3.95	43.27±3.21	53.79±2.72	39.66±3.65	47.43
+TAST-BN (Ours)	55.75±2.37	33.92±9.86	43.87±4.70	32.33±4.40	41.47

Table 21: Average accuracy(%) using classifiers trained by CORAL on the domain generalization benchmarks for Table 5, namely VLCS, PACS, OfficeHome, and TerraIncognita. We use ResNet-18 and ResNet-50 as backbone networks. **Bold** indicates the best performance for each benchmark. Our proposed method TAST outperforms all the baselines on most of the benchmarks.

Method	Backbone	VLCS	PACS	OfficeHome	TerraIncognita	Avg
CORAL		74.00±1.13	81.00±0.79	62.78±0.06	36.51±2.35	63.57
+Tent		71.13±1.45	84.17±0.61	62.37±0.09	36.71±0.77	63.60
+TentBN		65.66±1.86	82.28±0.36	63.37±0.13	37.89±1.23	62.30
+TentClf		72.27±1.29	75.71±1.74	62.65±0.08	30.27±6.34	60.23
+SHOT		66.01±3.75	84.67±0.47	63.54±0.23	33.20±0.49	61.86
+SHOTIM	ResNet-18	65.75±3.70	84.63±0.49	63.53±0.21	33.10±0.42	61.75
+PL		66.58±1.92	76.46±3.23	61.19±1.52	29.32±5.57	58.39
+PLClf		73.70±0.39	76.16±2.44	62.68±0.13	34.29±3.96	61.71
+T3A		75.49±1.67	82.75±0.51	63.72±0.32	38.39±1.19	65.09
+TAST (Ours)		74.82±2.43	83.16±0.81	**64.00±0.25**	**39.21±1.75**	65.30
+TAST-BN (Ours)		**77.01±0.36**	**87.21±0.57**	62.98±0.23	37.45±1.11	**66.16**
CORAL		76.39±1.01	83.52±0.67	66.89±0.20	42.79±1.27	67.40
+Tent		74.43±0.98	86.50±0.77	66.30±0.28	42.15±2.81	67.35
+TentBN		68.26±1.39	85.05±0.59	67.68±0.20	41.54±0.93	65.63
+TentClf		76.45±1.00	82.14±1.71	64.03±0.56	39.74±2.47	65.59
+SHOT		64.11±0.79	85.09±1.03	67.73±0.29	33.96±0.59	62.72
+SHOTIM	ResNet-50	63.63±0.60	85.06±0.93	67.72±0.29	34.17±0.90	62.65
+PL		72.74±1.32	75.96±6.46	60.74±2.91	36.69±3.47	61.53
+PLClf		75.68±1.23	83.56±0.80	66.24±0.42	**44.93±3.76**	67.60
+T3A		77.33±0.97	84.54±0.63	68.08±0.34	43.50±0.19	68.36
+TAST (Ours)		77.23±1.25	85.04±0.49	68.39±0.54	44.22±1.33	68.72
+TAST-BN (Ours)		**79.13±0.43**	**90.41±0.64**	**69.04±0.36**	43.46±4.46	**70.51**

Table 22: Full results using classifiers trained by CORAL for Table 21 on VLCS. We use ResNet-18 as a backbone network.

Method	C	L	S	V	Avg
CORAL	93.31±3.73	61.11±1.66	70.62±0.87	70.95±0.36	74.00
+Tent	95.78±1.20	59.24±0.85	63.38±2.06	66.13±3.09	71.13
+TentBN	79.89±5.76	54.29±3.98	62.72±1.06	65.76±1.79	65.66
+TentClf	94.96±2.77	58.42±3.37	71.01±1.26	64.71±5.42	72.27
+SHOT	88.21±11.66	50.29±2.91	58.00±1.79	67.55±0.51	66.01
+SHOTIM	87.74±11.38	49.89±2.74	57.73±1.76	67.61±0.49	65.75
+PL	95.78±1.34	54.09±4.31	55.03±2.09	61.42±9.04	66.58
+PLClf	95.04±2.59	57.67±3.74	71.00±1.33	71.09±0.48	73.70
+T3A	97.10±3.42	63.61±3.43	67.90±0.78	73.34±1.26	75.49
+TAST (Ours)	95.36±7.76	62.95±3.23	69.06±1.05	71.89±1.95	74.82
+TAST-BN (Ours)	98.90±0.58	61.01±2.41	69.74±2.57	78.40±1.15	77.01

Table 23: Full results using classifiers trained by CORAL for Table 21 on PACS. We use ResNet-18 as a backbone network.

Method	A	C	P	S	Avg
CORAL	78.74±1.79	74.57±1.79	92.48±0.90	78.21±1.51	81.00
+Tent	82.11±0.95	81.22±1.02	95.15±0.04	78.20±1.33	84.17
+TentBN	80.06±0.86	77.14±1.35	94.05±0.31	77.87±0.50	82.28
+TentClf	77.14±0.99	63.00±6.22	92.93±1.12	69.77±2.86	75.71
+SHOT	82.92±1.33	81.13±1.18	95.28±0.60	79.37±1.05	84.67
+SHOTIM	82.92±1.24	81.06±1.17	95.30±0.57	79.23±1.10	84.63
+PL	83.44±1.79	67.36±9.25	94.20±2.49	60.82±12.65	76.46
+PLClf	79.72±1.06	62.98±8.19	93.12±0.60	68.81±1.23	76.16
+T3A	80.68±1.15	77.52±0.54	93.25±0.66	79.53±0.70	82.75
+TAST (Ours)	80.88±1.33	77.86±0.92	94.28±0.56	79.60±1.60	83.16
+TAST-BN (Ours)	86.96±0.66	83.58±1.32	96.59±0.62	81.69±1.16	87.21

Table 24: Full results using classifiers trained by CORAL for Table 21 on OfficeHome. We use ResNet-18 as a backbone network.

Method	A	C	P	R	Avg
CORAL	55.78±0.29	50.09±0.09	72.09±0.32	73.16±0.39	62.78
+Tent	55.33±0.33	50.79±0.31	71.08±0.32	72.29±0.41	62.37
+TentBN	56.59±0.34	51.54±0.07	72.19±0.19	73.17±0.30	63.37
+TentClf	55.56±0.40	49.96±0.16	72.07±0.44	73.00±0.44	62.65
+SHOT	55.77±0.29	52.67±0.44	72.22±0.64	73.50±0.28	63.54
+SHOTIM	55.72±0.28	52.64±0.39	72.23±0.63	73.52±0.29	63.53
+PL	54.17±1.83	46.74±4.73	71.53±0.40	72.34±0.89	61.19
+PLClf	55.77±0.38	50.04±0.44	71.90±0.37	73.03±0.42	62.68
+T3A	55.83±0.36	51.68±0.51	73.70±0.43	73.66±0.55	63.72
+TAST (Ours)	56.22±0.57	51.73±0.48	74.05±0.73	74.00±0.52	64.00
+TAST-BN (Ours)	54.71±0.40	52.07±0.61	72.80±0.65	72.33±0.49	62.98

Table 25: Full results using classifiers trained by CORAL for Table 21 on TerraIncognita. We use ResNet-18 as a backbone network.

Method	L100	L38	L43	L46	Avg
CORAL	38.41±2.79	25.98±6.65	45.59±2.53	36.08±1.75	36.51
+Tent	37.31±3.54	24.76±1.90	45.99±0.73	38.79±1.78	36.71
+TentBN	41.76±1.23	33.9±2.32	40.59±3.21	35.29±0.98	37.89
+TentClf	29.99±12.66	15.84±18.76	43.36±4.29	31.89±2.89	30.27
+SHOT	35.95±0.88	25.85±1.40	38.33±0.69	32.67±0.83	33.20
+SHOTIM	35.81±0.77	25.64±1.15	38.16±0.75	32.78±0.45	33.10
+PL	37.32±23.49	24.27±24.17	31.84±7.57	23.84±6.83	29.32
+PLClf	45.07±7.63	20.52±19.27	44.4±1.32	27.18±3.00	34.29
+T3A	37.14±2.17	34.49±3.47	45.00±3.91	36.91±1.86	38.39
+TAST (Ours)	46.01±2.18	32.11±4.30	43.31±3.17	35.42±2.53	39.21
+TAST-BN (Ours)	43.04±3.00	32.25±5.90	42.53±2.54	31.99±0.81	37.45

Table 26: Full results using classifiers trained by CORAL for Table 21 on VLCS. We use ResNet-50 as a backbone network.

Method	C	L	S	V	Avg
CORAL	96.82±1.06	62.51±0.81	71.46±1.71	74.79±3.23	76.39
+Tent	96.53±2.09	59.55±0.71	67.96±3.68	73.69±2.62	74.43
+TentBN	84.24±2.39	56.07±2.77	63.90±1.46	68.84±2.75	68.26
+TentClf	96.99±1.16	61.48±1.68	72.32±1.97	75.00±3.07	76.45
+SHOT	85.07±1.63	46.27±2.62	56.77±1.03	68.34±1.01	64.11
+SHOTIM	83.57±0.89	45.86±2.93	56.55±0.81	68.53±0.98	63.63
+PL	98.32±0.64	53.64±6.70	67.76±1.16	71.22±5.85	72.74
+PLClf	96.85±1.30	58.71±2.76	72.20±1.96	74.94±3.89	75.68
+T3A	98.24±0.70	64.69±1.64	73.06±2.04	73.34±3.81	77.33
+TAST (Ours)	99.15±0.28	64.17±2.37	72.32±1.75	73.27±3.27	77.23
+TAST-BN (Ours)	99.14±0.45	64.95±2.74	73.39±0.94	79.04±2.19	79.13

Table 27: Full results using classifiers trained by CORAL for Table 21 on PACS. We use ResNet-50 as a backbone network.

Method	A	C	P	S	Avg
CORAL	84.40±1.36	79.88±2.80	95.58±0.69	74.24±3.09	83.52
+Tent	86.12±1.37	85.15±1.85	96.28±0.78	78.47±1.52	86.50
+TentBN	84.34±0.98	81.63±2.47	96.38±0.50	77.86±1.10	85.05
+TentClf	84.68±1.88	80.32±2.89	95.98±1.01	67.59±8.18	82.14
+SHOT	85.75±1.92	82.38±2.52	96.88±0.92	75.37±2.56	85.09
+SHOTIM	85.72±1.82	82.38±2.43	96.84±0.94	75.29±1.96	85.06
+PL	84.87±3.66	77.93±3.78	96.29±0.73	44.74±20.19	75.96
+PLClf	85.43±1.52	79.81±3.15	96.21±0.91	72.78±5.06	83.56
+T3A	84.71±1.96	81.30±2.98	96.68±0.53	75.47±2.36	84.54
+TAST (Ours)	85.74±1.77	81.05±2.79	96.88±0.49	76.48±2.33	85.04
+TAST-BN (Ours)	90.95±1.20	86.78±1.39	98.17±0.43	85.72±0.63	90.41

Table 28: Full results using classifiers trained by CORAL for Table 21 on OfficeHome. We use ResNet-50 as a backbone network.

Method	A	C	P	R	Avg
CORAL	60.84±1.18	53.82±0.69	76.06±0.25	76.85±1.15	66.89
+Tent	61.11±1.05	54.16±0.56	73.61±0.66	76.31±1.28	66.30
+TentBN	61.91±1.17	55.73±0.67	76.28±0.47	76.82±1.09	67.68
+TentClf	54.31±1.96	49.96±1.28	75.30±0.08	76.56±1.64	64.03
+SHOT	61.79±1.61	56.93±0.72	75.97±0.79	76.23±1.08	67.73
+SHOTIM	61.75±1.52	56.93±0.79	75.94±0.81	76.24±0.95	67.72
+PL	54.78±3.96	40.71±10.95	74.19±0.49	73.28±1.81	60.74
+PLClf	59.80±0.85	53.40±1.46	75.60±0.17	76.15±1.39	66.24
+T3A	61.59±1.51	55.57±0.85	77.45±0.74	77.72±1.36	68.08
+TAST (Ours)	62.02±1.30	55.88±0.86	78.06±1.01	77.60±1.41	68.39
+TAST-BN (Ours)	63.45±1.48	59.01±1.14	76.68±0.74	77.00±1.13	69.04

Table 29: Full results using classifiers trained by CORAL for Table 21 on TerraIncognita. We use ResNet-50 as a backbone network.

Method	L100	L38	L43	L46	Avg
CORAL	45.52±0.53	39.33±2.81	48.98±2.28	37.35±2.71	42.79
+Tent	46.72±2.57	34.14±3.01	48.05±10.46	39.70±3.14	42.15
+TentBN	48.27±2.51	38.07±1.08	44.89±2.73	34.92±3.07	41.54
+TentClf	42.57±5.73	38.35±3.37	44.10±2.18	33.92±5.58	39.74
+SHOT	38.95±1.35	26.99±1.76	40.93±2.51	28.98±4.77	33.96
+SHOTIM	39.52±2.40	26.45±3.94	41.07±2.21	29.64±4.16	34.17
+PL	51.29±12.49	47.88±5.50	29.58±10.72	17.99±10.59	36.69
+PLClf	53.69±5.34	43.78±6.46	47.67±6.30	34.57±5.18	44.93
+T3A	45.57±1.04	40.31±1.50	49.81±2.10	38.31±1.60	43.50
+TAST (Ours)	53.81±0.58	39.99±2.38	48.07±3.86	35.02±3.12	44.22
+TAST-BN (Ours)	54.80±3.22	41.56±6.79	47.09±5.58	30.38±4.60	43.46

Table 30: Average accuracy(%) using classifiers trained by MMD for Table 5 on the domain generalization benchmarks, namely VLCS, PACS, OfficeHome, and TerraIncognita. We use ResNet-18 as a backbone network.

Method	VLCS	PACS	OfficeHome	TerraIncognita	Avg
MMD	74.90±0.50	81.06±0.92	62.20±0.48	35.73±2.70	63.47
+Tent	74.59±0.66	84.47±0.19	62.15±0.33	36.11±0.72	64.33
+TentBN	65.94±1.91	82.44±0.26	62.80±0.46	37.66±0.34	62.21
+TentClf	74.91±0.60	57.76±5.32	62.10±0.50	28.94±6.56	55.93
+SHOT	65.41±2.03	85.57±0.28	63.25±0.53	32.34±0.68	61.64
+SHOTIM	65.00±2.20	85.53±0.29	63.20±0.56	32.25±0.55	61.50
+PL	66.17±1.73	74.42±4.09	60.49±1.03	22.30±8.42	55.85
+PLClf	74.84±0.50	69.95±0.95	62.16±0.45	31.94±5.67	59.72
+T3A	77.28±0.45	82.52±0.53	63.34±0.55	37.40±1.86	65.14
+TAST (Ours)	76.21±0.79	83.29±0.26	63.49±0.49	38.12±2.47	65.28
+TAST-BN (Ours)	76.06±0.89	86.35±0.76	63.22±0.26	39.46±1.63	66.27

Table 31: Full results using classifiers trained by MMD for Table 30 on VLCS. We use ResNet-18 as a backbone network.

Method	C	L	S	V	Avg
MMD	95.51±2.59	62.32±0.68	70.09±0.80	71.68±0.83	74.90
+Tent	97.20±0.55	61.53±0.60	69.32±2.58	70.33±0.92	74.59
+TentBN	80.71±5.21	54.94±2.31	61.88±0.30	66.25±1.58	65.94
+TentClf	95.71±2.16	61.87±1.02	70.15±0.91	71.90±0.82	74.91
+SHOT	88.10±8.59	48.99±2.74	57.14±1.13	67.43±0.47	65.41
+SHOTIM	86.93±8.90	48.71±2.70	56.98±1.17	67.37±0.48	65.00
+PL	95.63±1.07	51.75±2.10	59.89±11.04	57.40±6.85	66.17
+PLClf	95.69±2.19	61.65±0.85	70.14±0.86	71.87±0.79	74.84
+T3A	99.15±0.52	64.19±0.76	71.16±0.74	74.62±1.63	77.28
+TAST (Ours)	99.29±0.46	63.14±0.66	69.62±1.23	72.81±1.30	76.21
+TAST-BN (Ours)	99.14±0.48	61.54±2.74	65.03±1.95	78.53±0.35	76.06

Table 32: Full results using classifiers trained by MMD for Table 30 on PACS. We use ResNet-18 as a backbone network.

Method	A	C	P	S	Avg
MMD	79.52±0.50	74.66±1.28	93.46±0.95	76.60±2.62	81.06
+Tent	82.84±0.97	81.22±0.85	95.49±0.40	78.32±0.48	84.47
+TentBN	80.51±0.84	77.09±0.44	94.55±0.33	77.59±0.64	82.44
+TentClf	56.53±16.38	47.89±6.86	93.37±0.67	33.26±8.17	57.76
+SHOT	84.50±0.13	81.98±0.98	95.58±0.22	80.19±0.95	85.57
+SHOTIM	84.49±0.20	81.94±0.93	95.58±0.22	80.09±0.89	85.53
+PL	84.59±0.48	53.96±10.45	95.10±0.18	64.04±11.28	74.42
+PLClf	80.04±0.60	63.87±8.49	93.60±0.57	42.28±7.47	69.95
+T3A	81.92±0.41	75.35±1.11	94.99±0.36	77.81±1.62	82.52
+TAST (Ours)	81.76±0.31	77.13±0.51	95.37±0.70	78.91±1.12	83.29
+TAST-BN (Ours)	86.23±1.18	82.16±1.93	97.46±0.14	79.55±1.08	86.35

Table 33: Full results using classifiers trained by MMD for Table 30 on OfficeHome. We use ResNet-18 as a backbone network.

Method	A	C	P	R	Avg
MMD	54.39±0.86	49.71±1.02	71.95±0.59	72.74±0.41	62.20
+Tent	55.73±0.47	49.71±0.20	70.75±0.74	72.41±0.45	62.15
+TentBN	55.34±0.56	51.09±1.09	72.11±0.46	72.68±0.27	62.80
+TentClf	54.39±0.72	49.28±1.18	71.95±0.66	72.77±0.27	62.10
+SHOT	54.83±0.77	52.38±0.95	72.59±0.71	73.18±0.15	63.25
+SHOTIM	54.85±0.85	52.27±0.97	72.54±0.71	73.15±0.17	63.20
+PL	53.26±1.14	44.63±3.44	71.76±0.68	72.33±0.08	60.49
+PLClf	54.44±0.67	49.67±0.97	71.97±0.65	72.57±0.29	62.16
+T3A	54.43±1.26	51.25±0.83	73.86±0.57	73.84±0.47	63.34
+TAST (Ours)	55.17±1.04	50.80±1.14	74.20±0.57	73.78±0.51	63.49
+TAST-BN (Ours)	54.40±0.60	52.21±0.38	73.30±0.35	72.96±0.42	63.22

Table 34: Full results using classifiers trained by MMD for Table 30 on TerraIncognita. We use ResNet-18 as a backbone network.

Method	L100	L38	L43	L46	Avg
MMD	34.57±3.77	26.57±6.18	46.08±2.85	35.72±1.17	35.73
+Tent	37.04±3.72	25.40±1.81	44.82±0.72	37.19±1.64	36.11
+TentBN	40.04±2.45	33.38±2.98	42.38±2.80	34.84±1.06	37.66
+TentClf	22.92±9.25	15.19±15.33	45.24±4.15	32.39±1.27	28.94
+SHOT	33.79±1.34	25.68±2.73	37.81±0.67	32.07±2.71	32.34
+SHOTIM	33.48±1.14	25.77±1.95	37.87±0.61	31.87±2.44	32.25
+PL	29.45±26.19	13.78±20.60	27.69±10.39	18.27±5.75	22.30
+PLClf	36.96±8.00	17.63±18.15	46.28±4.42	26.87±2.41	31.94
+T3A	35.16±2.74	34.41±2.73	43.83±4.22	36.19±1.79	37.40
+TAST (Ours)	44.70±1.82	31.97±4.96	42.30±4.83	33.50±4.40	38.12
+TAST-BN (Ours)	43.81±5.05	37.35±2.57	44.41±1.55	32.28±1.73	39.46

Table 35: Average accuracy(%) using classifiers trained by Mixup for Table 5 on the domain generalization benchmarks, namely VLCS, PACS, OfficeHome, and TerraIncognita. We use ResNet-18 as a backbone network.

Method	VLCS	PACS	OfficeHome	TerraIncognita	Avg
Mixup	74.97±0.86	78.29±0.88	61.83±0.88	41.04±1.01	64.03
+Tent	72.73±0.41	83.88±0.51	61.82±0.45	39.52±0.36	64.49
+TentBN	62.83±0.83	81.44±0.27	62.82±0.64	40.72±1.81	61.95
+TentClf	74.33±0.92	68.95±2.86	61.45±0.88	37.21±4.79	60.49
+SHOT	68.69±0.91	84.43±0.39	62.81±0.42	36.32±0.50	63.06
+SHOTIM	68.31±0.98	84.52±0.36	62.80±0.43	36.03±0.61	62.92
+PL	59.90±2.19	68.02±2.43	60.66±0.63	32.30±6.83	55.22
+PLClf	74.19±0.78	70.94±3.00	61.67±0.86	40.63±4.88	61.86
+T3A	78.43±0.76	81.91±0.54	63.49±0.86	39.89±0.90	65.93
+TAST (Ours)	77.19±0.80	82.85±0.36	63.83±0.74	41.44±1.67	66.33
+TAST-BN (Ours)	76.89±0.86	87.14±0.56	62.09±0.86	42.70±1.90	67.21

Table 36: Full results using classifiers trained by Mixup for Table 35 on VLCS. We use ResNet-18 as a backbone network.

Method	C	L	S	V	Avg
Mixup	94.73±1.35	62.52±0.79	69.70±0.89	72.93±1.27	74.97
+Tent	95.27±0.47	59.84±1.01	68.61±1.04	67.19±1.62	72.73
+TentBN	76.52±1.36	52.40±1.05	60.00±1.63	62.41±2.25	62.83
+TentClf	94.87±1.31	61.72±0.73	68.44±1.04	72.29±2.22	74.33
+SHOT	96.47±3.75	51.01±1.22	58.83±1.55	68.47±0.27	68.69
+SHOTIM	95.63±4.31	50.49±1.13	58.71±1.71	68.41±0.35	68.31
+PL	94.94±1.82	49.88±0.35	45.87±7.30	48.90±4.44	59.90
+PLClf	94.82±1.29	59.16±0.65	69.85±0.94	72.92±1.54	74.19
+T3A	99.11±0.76	64.75±1.02	72.69±2.16	77.16±0.79	78.43
+TAST (Ours)	98.97±0.87	63.19±0.77	71.04±1.80	75.56±1.03	77.19
+TAST-BN (Ours)	99.27±0.32	60.76±4.75	69.63±2.58	77.91±1.76	76.89

Table 37: Full results using classifiers trained by Mixup for Table 35 on PACS. We use ResNet-18 as a backbone network.

Method	A	C	P	S	Avg
Mixup	80.28±2.31	70.69±1.19	94.26±0.85	67.94±0.73	78.29
+Tent	81.51±0.82	79.49±1.01	95.58±0.18	78.94±1.04	83.88
+TentBN	82.40±1.00	75.98±0.79	94.63±0.45	72.75±1.57	81.44
+TentClf	79.66±3.73	64.24±4.07	94.17±1.01	37.75±13.33	68.95
+SHOT	85.20±0.56	80.13±0.88	96.20±0.75	76.18±0.45	84.43
+SHOTIM	85.17±0.56	80.64±0.92	96.22±0.77	76.05±0.50	84.52
+PL	82.82±2.54	66.48±8.08	95.40±0.64	27.37±5.71	68.02
+PLClf	79.32±2.88	70.61±1.26	94.26±0.89	39.58±15.47	70.94
+T3A	83.06±1.31	75.92±0.58	95.87±0.66	72.80±2.09	81.91
+TAST (Ours)	83.93±0.99	76.75±1.32	96.34±0.63	74.39±1.69	82.85
+TAST-BN (Ours)	86.18±0.49	82.69±1.44	97.27±0.48	82.43±1.80	87.14

Table 38: Full results using classifiers trained by Mixup for Table 35 on OfficeHome. We use ResNet-18 as a backbone network.

Method	A	C	P	R	Avg
Mixup	53.92±1.21	49.17±1.49	71.66±0.52	72.56±0.82	61.83
+Tent	53.22±0.92	50.75±0.79	71.22±0.74	72.10±0.62	61.82
+TentBN	54.78±1.29	51.47±1.09	72.21±0.25	72.82±0.74	62.82
+TentClf	53.87±1.20	48.22±1.48	71.65±0.42	72.06±0.84	61.45
+SHOT	53.95±1.17	52.20±1.27	72.29±0.36	72.79±0.43	62.81
+SHOTIM	53.94±1.22	52.15±1.30	72.28±0.42	72.83±0.41	62.80
+PL	52.82±0.96	48.17±1.38	70.97±0.82	70.70±1.00	60.66
+PLClf	53.85±1.10	49.12±1.43	71.64±0.47	72.06±1.04	61.67
+T3A	54.83±1.49	50.97±1.51	74.14±0.63	74.00±0.31	63.49
+TAST (Ours)	54.97±0.96	51.31±1.84	74.88±0.66	74.16±0.22	63.83
+TAST-BN (Ours)	53.09±1.44	51.04±1.81	72.44±0.64	71.80±0.64	62.09

Table 39: Full results using classifiers trained by Mixup for Table 35 on TerraIncognita. We use ResNet-18 as a backbone network.

Method	L100	L38	L43	L46	Avg
Mixup	52.26±1.44	35.90±4.46	41.23±2.04	34.77±2.14	41.04
+Tent	41.35±2.74	33.05±2.75	44.17±1.50	39.51±1.83	39.52
+TentBN	45.35±2.22	44.17±2.15	42.25±1.98	31.11±2.43	40.72
+TentClf	49.62±7.17	37.29±12.05	37.45±2.99	24.48±0.73	37.21
+SHOT	42.78±3.48	31.04±2.88	39.58±1.29	31.86±3.47	36.32
+SHOTIM	42.14±3.38	30.71±3.18	39.37±1.34	31.89±3.51	36.03
+PL	52.56±0.16	34.80±21.65	23.33±4.85	18.51±6.10	32.30
+PLClf	53.30±1.59	35.52±18.76	40.68±1.15	33.04±2.57	40.63
+T3A	43.05±2.28	38.53±2.37	43.32±3.33	34.65±1.22	39.89
+TAST (Ours)	57.57±5.18	36.43±3.72	38.34±2.38	33.40±2.08	41.44
+TAST-BN (Ours)	56.81±4.34	42.44±2.03	41.01±2.50	30.54±1.52	42.70

Table 40: Full results using classifiers trained by ERM for Table 2 of manuscript on VLCS. We use ResNet-18 as a backbone network.

Method	N_e	C	L	S	V	Avg
ERM	-	94.70±1.33	63.79±1.30	67.90±1.97	73.15±1.37	74.88
+T3A	-	97.52±1.99	65.32±2.24	70.70±3.48	75.51±1.75	77.26
+TAST-N (Ours)	-	95.31±4.33	65.62±1.79	68.9±3.22	74.96±1.66	76.20
+TAST (Ours)	1	98.62±1.06	62.61±1.90	66.84±3.01	72.73±1.17	75.20
+TAST (Ours)	5	99.15±0.68	65.58±3.08	67.53±1.49	74.46±1.87	76.68
+TAST (Ours)	10	99.22±0.45	66.21±1.36	68.62±2.39	75.66±2.03	77.43
+TAST (Ours)	20	99.17±0.60	65.87±1.90	68.13±1.76	75.92±1.75	77.27

Table 41: Full results using classifiers trained by ERM for Table 2 of manuscript on PACS. We use ResNet-18 as a backbone network.

Method	N_e	A	C	P	S	Avg
ERM	-	77.78±0.81	75.09±1.22	95.19±0.29	69.11±1.22	79.29
+T3A	-	78.81±0.97	77.14±1.20	95.92±0.36	71.44±1.63	80.83
+TAST-N (Ours)	-	80.18±0.88	77.34±1.38	96.57±0.27	72.38±0.77	81.62
+TAST (Ours)	1	80.21±0.80	77.06±1.44	96.13±0.53	71.51±1.22	81.23
+TAST (Ours)	5	80.85±0.86	77.91±0.71	96.49±0.37	72.00±1.16	81.81
+TAST (Ours)	10	79.95±1.42	78.12±0.98	96.51±0.25	71.65±2.32	81.56
+TAST (Ours)	20	80.56±0.53	78.26±0.99	96.44±0.20	72.52±0.77	81.94

Table 42: Full results using classifiers trained by ERM for Table 2 of manuscript on OfficeHome. We use ResNet-18 as a backbone network.

Method	N_e	A	C	P	R	Avg
ERM	-	55.19±0.49	47.76±1.02	72.22±0.53	73.21±0.89	62.10
+T3A	-	55.10±0.74	49.56±1.14	74.10±0.55	74.07±1.18	63.21
+TAST-N (Ours)	-	55.25±0.97	50.45±1.03	74.24±0.55	74.23±1.37	63.54
+TAST (Ours)	1	53.53±0.90	49.46±1.39	72.84±0.69	72.53±1.30	62.09
+TAST (Ours)	5	55.34±1.04	50.51±1.03	74.23±0.43	73.97±0.95	63.51
+TAST (Ours)	10	55.76±0.68	49.52±1.38	74.17±0.49	74.11±1.00	63.39
+TAST (Ours)	20	56.15±0.68	50.04±1.31	74.33±0.28	74.28±1.23	63.70

Table 43: Full results using classifiers trained by ERM for Table 2 of manuscript on TerraIncognita. We use ResNet-18 as a backbone network.

Method	N_e	L100	L38	L43	L46	Avg
ERM	-	37.18±2.46	36.12±4.20	53.18±1.27	36.02±1.37	40.62
+T3A	-	36.22±1.89	40.08±1.98	50.72±1.02	33.79±1.25	40.20
+TAST-N (Ours)	-	39.75±1.76	39.20±2.65	52.33±2.63	36.24±1.28	41.88
+TAST (Ours)	1	43.23±0.87	42.49±2.08	51.22±3.69	33.41±1.05	42.59
+TAST (Ours)	5	43.95±2.33	38.89±2.42	52.44±3.04	35.42±1.27	42.68
+TAST (Ours)	10	43.96±2.92	38.48±3.56	53.27±2.73	34.67±1.24	42.60
+TAST (Ours)	20	43.67±2.83	39.24±3.79	52.64±3.02	35.01±1.09	42.64

Table 44: Average error rate (%) on CIFAR-10C for the highest severe corruptions. **Bold** indicates the best performance for each image corruption.

Method	gauss	brit	contr	defoc	elast	fog	frost	glass	impul	jpeg	motn	pixel	shot	snow	zoom
No adaptation	48.73	**7.01**	13.27	11.84	23.38	29.41	28.24	50.78	57.00	19.46	23.38	47.88	44.00	21.93	10.84
+SHOT	17.09	8.64	8.57	9.83	19.53	19.72	13.93	25.60	27.15	13.98	14.01	11.68	16.02	15.89	8.22
+Tent	15.91	7.91	7.85	9.27	18.13	16.45	12.62	23.48	24.52	13.19	12.70	10.93	14.59	14.06	7.68
+PL	33.56	7.54	11.53	10.60	20.21	23.86	21.78	38.36	43.64	16.88	18.72	29.83	30.43	18.75	9.43
+T3A	41.87	7.30	13.61	11.99	22.06	28.52	27.13	44.10	54.26	18.71	22.54	37.53	37.84	21.97	10.72
+TAST (Ours)	42.02	7.34	13.55	11.86	21.38	28.58	26.51	44.99	54.19	18.96	22.55	37.08	37.62	21.84	10.64
+TAST-BN (Ours)	**14.91**	7.68	7.81	**8.62**	**16.81**	**15.10**	**12.25**	**21.82**	**22.54**	**12.38**	**11.67**	**10.34**	**13.77**	**12.99**	**7.57**
+TTT++	16.25	7.27	**7.46**	9.12	18.17	17.72	12.36	25.74	26.43	13.13	12.85	11.38	15.02	14.40	7.59

Table 45: Average error rate (%) on CIFAR-100C for the highest severe corruptions. **Bold** indicates the best performance for each image corruption.

Method	gauss	brit	contr	defoc	elast	fog	frost	glass	impul	jpeg	motn	pixel	shot	snow	zoom
No adaptation	80.77	**28.86**	50.93	39.62	59.54	68.11	60.19	54.79	82.26	87.75	49.96	54.22	72.27	77.84	54.58
+SHOT	45.95	30.14	31.93	32.81	46.19	49.49	40.65	54.79	57.02	37.99	39.22	37.57	44.33	44.08	30.97
+Tent	43.02	29.65	30.52	31.48	43.88	44.03	39.21	50.91	53.10	36.22	36.31	34.10	41.58	41.85	29.73
+PL	43.94	30.14	31.20	32.11	45.07	46.57	40.11	52.66	54.48	37.48	36.92	34.59	42.68	42.77	30.19
+T3A	76.95	29.54	48.02	39.64	55.68	65.90	58.45	78.23	86.39	48.82	53.46	66.31	74.14	55.01	37.68
+TAST (Ours)	80.13	29.40	50.86	40.43	58.13	69.24	60.89	81.94	88.94	50.44	57.26	70.58	77.47	56.98	38.46
+TAST-BN (Ours)	**42.01**	29.00	**30.20**	**30.74**	**42.97**	**41.02**	**38.19**	**48.95**	**51.20**	**35.70**	**35.03**	**33.38**	**40.01**	**39.88**	**29.07**
+TTT++	47.10	29.99	31.10	32.61	47.73	51.74	41.37	57.36	60.40	38.93	39.01	37.17	45.34	44.53	31.31