Combinatorial Bandits with Linear Constraints: Beyond Knapsacks and Fairness

Abstract

This paper proposes and studies for the first time the problem of combinatorial multi-armed bandits with linear long-term constraints. Our model generalizes and unifies several prominent lines of work, including bandits with fairness constraints, bandits with knapsacks (BwK), etc. We propose an upper-confidence bound LP-style algorithm for this problem, called UCB-LP, and prove that it achieves a logarithmic problem-dependent regret bound and zero constraint violations in expectation. In the special case of fairness constraints, we further provide a sharper constant regret bound for UCB-LP. Our regret bounds outperform the existing literature on BwK and bandits with fairness constraints simultaneously. We also develop another low-complexity version of UCB-LP and show that it yields $\tilde{O}(\sqrt{T})$ problem-independent regret and zero constraint violations with high-probability. Finally, we conduct numerical experiments to validate our theoretical results.

1 Introduction

In this paper, we study the problem of combinatorial bandits with long-term linear constraints. Our model captures important application scenarios like ad placement in online advertising systems [30], real-time traffic scheduling in wireless networks, and task assignment in crowdsourcing platforms [22], etc. Although being studied for the first time, our model subsumes several well-known problems in the Constrained Multi-Armed Bandit (CMAB) literature, including bandits with knapsacks, bandits with fairness constraints, etc. Details about these problems and how they fit into our framework are provided in Section 1.1.

Specifically, we consider an agent's online decision problem faced with a fixed finite set of N arms labelled $1, 2, ..., N$, within the time horizon T. At each round t ($1 \leq t \leq T$), every arm $i \in [N]$ is associated with a random reward $f_i(t) \in [0, 1]$ sampled from a time-invariant distribution P_i. The reward $f_i(t)$ and its distribution P_i are unknown to the agent *a priori*. The mean reward of distribution P_i is denoted as $\mu_i \in [0, 1]$. We denote $\boldsymbol{\mu} = (\mu_1, ..., \mu_N)^\top \in [0, 1]^N$ the mean reward vector, and define $\mu^* := \max_{i \in [N]} \mu_i$ as the maximum mean reward value of all arms. At the beginning of each round t, the agent is allowed to pull multiple, but no more than m arms. At round t, the action taken by the agent is represented by an action vector $\boldsymbol{a}(t) = (a_1(t), ..., a_N(t))^\top \in \{0, 1\}^N$, where $a_i(t) = 1$ if and only if arm i is pulled. The set of all feasible action vectors is defined as $\mathcal{A} = \{\boldsymbol{a} | \boldsymbol{a} \in \{0, 1\}^N, ||\boldsymbol{a}||_1 \leq m\}$. After taking action $\boldsymbol{a}(t)$, the agent can observe reward from each pulled arm. Summing up the reward from the pulled arms, at round t, the agent receives a total reward of $R_t := \sum_{i=1}^N f_i(t) a_i(t)$.

Beyond the standard combinatorial bandit setting above, we consider that the agent is subject to some constraints $\boldsymbol{g}(\cdot)$ at every round t, defined as $\boldsymbol{g}(\boldsymbol{a}(t)) := [g_1(\boldsymbol{a}(t)), g_2(\boldsymbol{a}(t)), ..., g_K(\boldsymbol{a}(t))]^\top$, where $g_1, g_2, \ldots, g_K : \mathbb{R}^N \to \mathbb{R}$ are linear functions. The goal of the agent is to maximize the accumulated expected reward up to the time horizon T, while satisfying the constraints in the long term, i.e.,

$$\max \sum_{t=1}^T R_t , \quad \text{s.t.} \ \sum_{t=1}^T \boldsymbol{g}(\boldsymbol{a}(t)) \leq \boldsymbol{0}. \tag{1}$$

(The comparison operator $\leq$ is coordinate-wise) Define OPT(T) as the expected accumulated reward in T rounds of the optimal policy satisfying the long term constraints. The agent's performance is measured in terms of regret and constraint violations defined respectively as

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

$$Regret_T = \text{OPT}(T) - \text{E}[\sum_{t=1}^{T} R_t], \ \text{Vio}(T) = \sum_{t=1}^{T} \boldsymbol{g}(\boldsymbol{a}(t)),$$

where the expectation is taken w.r.t. the randomness of the reward and algorithm's internal randomness.

Consider the following linear programming problem (LP):

$$\text{OPT}_{\text{LP}} = \max_{\boldsymbol{x} \in \mathbb{R}^N} \ \boldsymbol{\mu}^\top \boldsymbol{x} \qquad \text{s.t. } \boldsymbol{g}(\boldsymbol{x}) \leq \boldsymbol{0}, \ \boldsymbol{0} \leq \boldsymbol{x} \leq \boldsymbol{1}, \ ||\boldsymbol{x}||_1 \leq m. \tag{2}$$

[4] showed that $\text{OPT}(T) \leq T \cdot \text{OPT}_{\text{LP}}$. We denote the set of optimal solutions to LP (2) as $\mathcal{X}^*$, and define $\boldsymbol{x}^* \in \mathcal{X}^*$ as one of these optimal solutions. Following a common approach, we use the optimal randomized policy $\boldsymbol{x}^*$ as the benchmark in the regret:

$$Regret_T \leq T \cdot \text{OPT}_{\text{LP}} - \text{E}[\sum_{t=1}^{T} R_t] = T\langle \boldsymbol{\mu}, \boldsymbol{x}^* \rangle - \text{E}[\sum_{t=1}^{T} R_t]. \tag{3}$$

1.1 Representative problems and related works

In this section, we outline several motivating and representative problems which fit into our general formulation and review the literature closely related to them (listed in Table 1). Problem-dependent parameters $\Delta_{\min}$ and Δ will be formally defined in Section 2.1.

Table 1: The comparison between our results and prior closely-related works. In this table, $r_{\min} = \min_i r_i$. "Single-arm" means $m = 1$. "LP" means the algorithm should solve a linear program. "Complexity" refers to the computational-complexity of the algorithm at each round.

ALGORITHM	SETTING	ASSUMPTIONS	REGRET	VIOLATION	COMPLEXITY
[12]	SINGLE-ARM, KNAPSACKS	N/A	$O\left(\min\{N,K\}\binom{N+K}{K}\frac{\log T}{\Delta_{\min}}\right)$	0	LP
[12]	SINGLE-ARM, KNAPSACKS	$|\mathcal{X}^*| = 1$	$O((\min\{N,K\})^3 \log T / \Delta_{\min}^2)$	0	LP
[31]	SINGLE-ARM, KNAPSACKS	ONE RESOURCE ($K=2$) "BEST-ARM-OPTIMALITY"	$\tilde{O}(N \log T / G_{\text{LAG}}^2)$	0	LP
[29]	SINGLE-ARM, KNAPSACKS	$|\mathcal{X}^*| = 1$, PRIOR KNOWLEDGE	$\tilde{O}(N \log T / \Delta_{\min})$	0	LP
[9]	COMBINATORIAL, KNAPSACKS	ONE RESOURCE ($K=2$)	$\tilde{O}(\log^2 T)$	0	LP
[22]	COMBINATORIAL, FAIRNESS	N/A	$O(\sqrt{mNT \log T})$	$o(T)$	$\tilde{O}(N)$
[14]	COMBINATORIAL, FAIRNESS	N/A	$O(\sqrt{mNT \log T})$	$o(T)$	$\tilde{O}(N)$
[35]	COMBINATORIAL, FAIRNESS	N/A	$O(\sqrt{mNT \log T})$	$O(\sqrt{mNT \log T})$	$\tilde{O}(N^2)$
[28]	SINGLE-ARM, FAIRNESS	$\max_{i \in [N]} r_i < 1/N$	$O(N\Delta(1 + [8\ln T / \Delta^2 - r_{\min}T]^+))$	$O(1)$	$\tilde{O}(N)$
[7]	SINGLE-ARM, FAIRNESS	N/A	$O(N \log T / \Delta)$	N/A	$\tilde{O}(N)$
(THIS WORK) UCB-LP	COMBINATORIAL, LINEAR	N/A	$O(mN \log T / \Delta_{\min})$	0	LP
(THIS WORK) UCB-LP	COMBINATORIAL, FAIRNESS	N/A	$O(1)$	0	$\tilde{O}(N)$
(THIS WORK) UCB-PLLP	COMBINATORIAL, LINEAR	N/A	$O(m\sqrt{T \log T})$	0 (HIGH-PROB)	$\tilde{O}(N)$

Bandits with knapsacks. The BwK (Bandits with Knapsacks) problem with deterministic costs studied in [12, 31, 29] assumes that there are K resources consumed over time, each with budgets $B_1, B_2, \ldots, B_K$ respectively. Every resource $i \in [K]$ is associated with a fixed consumption vector $\boldsymbol{\lambda}_i = (\lambda_{i,1}, \lambda_{i,2}, \ldots, \lambda_{i,N}) \in \mathbb{R}_{\geq 0}^N$. The agent maximizes the accumulated reward subject to the budget constraints $\sum_{i \in [T]} \boldsymbol{\lambda}_i^\top \boldsymbol{a}(t) \leq B_i, \forall i \in [K]$. One can see that, this problem is equivalent with the special case of our setting where the linear constraint functions have the form $\boldsymbol{g}(\boldsymbol{a}(t)) = (\boldsymbol{\lambda}_1^\top \boldsymbol{a}(t) - B_1/T, \ldots, \boldsymbol{\lambda}_K^\top \boldsymbol{a}(t) - B_K/T)$.

The existing BwK literature [1, 4, 11] has derived algorithms that achieve the problem-independent regret bounds of the similar order $\tilde{O}(\sqrt{KNT})$. Such order of the regret bound is also obtained by [30, 31, 21] for combinatorial setting. However, the problem-dependent regret of BwK with deterministic costs is less explored. [12] achieved one regret bound of $O\left(\min\{N,K\}\binom{N+K}{K}\frac{\log T}{\Delta_{\min}}\right)$ with unsatisfying exponential dependence on K and N. They also provide another regret bound of $O((\min\{N,K\})^3 \frac{\log T}{\Delta_{\min}^2})$ with polynomial dependence on N, K but require an additional assumption of the optimal solution of LP (2) being unique. Later [29] improves this regret to $O(N \frac{\log T}{\Delta_{\min}})$ also under the assumption that LP (2) has an unique optimal solution. But their algorithm requires the knowledge of some parameters of the problem instance a priori (characterized by $\Delta_{\min}$ and μ^*), which is unpractical. Under the assumption of "best-arm-optimality", i.e., there is an optimal policy that only pulls one arm, [31] achieved the regret of $O(N \cdot \log T / G_{\text{LAG}}^2)$ (G_{LAG} is their defined

Lagrangian gap) when there is only one resource ($K = 2$), whose practicability is also restricted. Very recently, [9] derives a regret bound of $O(\log^2 T)$ for combinatorial setting and one resource constraint, which is the best so far in the area of combinatorial BwK but still sub-optimal in terms of T.

For BwK problems with stochastic costs, [12, 34, 33, 31, 23] obtained logarithmic regrets under different restrictive assumptions, e.g., non-degeneracy of (2), $K = 2$ (single source) or "best-arm-optimality". [12, 31] showed that it is impossible to achieve any problem-dependent regret bound of $o(\sqrt{T})$ without additional assumptions in general.

Bandits with fairness constraints. Recently, [22, 35, 28] studied the problem of bandits with fairness constraints. Under their setting, the agent maximizes the cumulative expected reward, and needs to ensure that each arm $i \in [N]$ is pulled for at least $r_i \in (0, 1)$ fraction of times at the end of T rounds. In our model, such fairness constraints are equivalent with the following special kind of linear long-term constraints: $\boldsymbol{g}(\boldsymbol{a}(t)) = -\boldsymbol{a}(t) + \boldsymbol{r}$, where $\boldsymbol{r} = (r_1, r_2, \ldots, r_N)^\top$.

[22] first studied the combinatorial (sleeping) bandits with fairness constraints. Their algorithm LFG combines virtual queue technique and UCB learning. LFG yields $\tilde{O}(\sqrt{T})$ regret and sublinear ($o(T)$) constraint violations. [14] replaced the UCB learning with Thompson Sampling in LFG and obtained performance guarantees with the same order. Later [35] improved the constraint violations bound to $O(\sqrt{T})$ with the same regret order by using online convex optimization techniques and RRS rounding. A big advancement is made by recent works [7, 28] that they achieve $O(\log T)$ and $o(\log T)$ regret bounds, respectively, for MAB ($m = 1$) with fairness constraints based on the modified UCB1 algorithm. And [10] achieved a "penalized" regret bound of $O(\log T)$ in the single-arm setting.

Bandits with group fairness. In scenarios like ad-display optimization, the agent is subject to the group fairness constraint, e.g., arms belonging to one group should be pulled more frequently than arms belonging to another group [25], or the arm with higher average reward should be pulled more times than the arm with lower average reward [17], etc. This problem also fits into our formulation of linear constraints. Only problem-dependent regrets of $\tilde{O}(\sqrt{T})$ are obtained in related works.

Other related literature. A large body of literature (e.g., [6, 32]) derived $O(\log T)$ regret bounds for unconstrained combinatorial bandits. [16, 18] studied the BwK problem under the adversarial setting. [2, 27, 3, 24] studied constrained linear bandits.

1.2 Discussion: significance of linear constraints

In this section, we discuss the significance of generalization to linear constraints. Previous literature on constrained bandits only studies constraints with specific forms, namely, the fairness constraint and the knapsacks constraint, etc. As we only require $\boldsymbol{g}(\cdot)$ to be linear, our model not only subsumes both of them as its special cases, but also solves a larger group of constraints, enabling broader applications. For example: **1.** Our model for the first time addresses scenarios where both fairness and knapsack constraints exists simultaneously. **2.** Our model solves the case of weighted fairness constraints, i.e., weighted sums of pulls of each arm are required to be larger than a threshold: $\sum_{i=1}^N \kappa_{ij} h_i(T) \geq r_j T$, where κ_{ij} is the j^{th} weight of the i^{th} arm. In contrast, traditional fairness constraints treat each arm as unweighted and could be seen as a special case of weight fairness constraints.

In fact, there are many applications where combinatorial bandits with various complicated linear constraints are required. We show some concrete examples as follows. (a) In crowdsourcing, where a group of workers are assigned with tasks to achieve high accuracy, a set of complex linear constraints occurs: each tasks should have enough workers, while each worker should have a fair workload. (b) In network routing where multiple paths (each path consists of a series of links) needs to be selected to send the traffic within the time budget and the bandwidth constraints. (c) Case of Internet of Things where a set of sensors need to be selected at each round to guarantee the QoS requirement [15] (e.g., throughput, Age of Information) under budget constraint on data collection cost.

1.3 Our contributions

Our main contributions are summarized below.

(a) We define a general formulation termed combinatorial bandits with linear long-term constraints. In contrast to previously outlined pieces of work, we consider the problem in its full generality and do not assume or require any prior knowledge of the problem instance. We design an upper-confidence

bound LP-style algorithm named UCB-LP, and develop a novel analytical technique to build a relationship between LP solution (distribution support over arms) and "reward allocation", with which we show that UCB-LP guarantees a problem-dependent regret of $O(mN\frac{\log T}{\Delta_{\min}})$ and no constraint violation in expectation. To the best of our knowledge, this is the first logarithmic regret bound for bandits with long term linear constraints under the combinatorial setting.

(b) For the special case of fairness constraints, we show that UCB-LP achieves $O(1)$ regret and guarantees zero expected constraint violation at the same time. To the best of our knowledge, both the regret and the constraint violations outperform all existing works on combinatorial bandits with fairness constraints. We also show that UCB-LP has a low running time of $\tilde{O}(N)$ in this special case.

(c) To overcome the potentially time-consuming LP in UCB-LP, we further develop a low-complexity version of UCB-LP, called UCB-PLLP, since it builds on the Lagrangian (L) of UCB-LP and pessimistically (P) tracks the constraint violations. We show that it yields $\tilde{O}(\sqrt{T})$ problem-independent regret and guarantees zero constraint violations for any $\tau \leq T$ with high-probability. The computational complexity of UCB-PLLP is $\tilde{O}(N)$.

2 Main results

In this section, we present our algorithm and corresponding performance analysis for our general formulation. All the proofs of listed lemmas, propositions and corollaries are deferred to the supplementary material. Our experimental results are given in the suppmetary material.

2.1 Preliminary: notations and existing techniques

Notations. For every arm i, define $h_i(t) := \sum_{\tau=1}^{t-1} a_i(\tau)$ as the number of pulls of it at the beginning of round t, and $\bar{\mu}_i(t) := \frac{1}{h_i(t)} \sum_{\tau=1}^{t-1} a_i(\tau)f_i(\tau)$ as its empirical reward estimate at round t. Denote the feasible region of LP (2) as $\mathcal{D} := \{\boldsymbol{x} | \boldsymbol{x} \in [0,1]^N, ||\boldsymbol{x}||_1 \leq m, \boldsymbol{g}(\boldsymbol{x}) \leq \boldsymbol{0}\}$. In this paper, for any vector $\boldsymbol{v}$, we use v_i to denote its i^{th} coordinate. For any event E, we use $\overline{E}$ to denote its negation.

Extreme points and general sub-optimality measure. Note that the feasible region $\mathcal{D}$ to LP (2) is a convex polytope, and we let $\mathcal{B}$ be the set of its extreme points. An extreme point of $\mathcal{D}$ is a point in $\mathcal{D}$ which does not lie in any open line segment joining two points of $\mathcal{D}$. It is well-known in the theory of LP that extreme points and basic feasible solutions are equivalent, and any LP attains its optimal value at an extreme point [5]. Recall that $\boldsymbol{x}^*$ is an optimal solution to LP (2), and we define the sub-optimality gap for any $\boldsymbol{x} \in \mathcal{B}$ as $\Delta_{\boldsymbol{x}} := \langle \boldsymbol{\mu}, \boldsymbol{x}^* \rangle - \langle \boldsymbol{\mu}, \boldsymbol{x} \rangle$. Define $\Delta_{\min} := \min_{\boldsymbol{x} \in \mathcal{B} \setminus \mathcal{X}^*} \Delta_{\boldsymbol{x}}$. Since $\mathcal{B}$ is finite, $\Delta_{\min}$ is well-defined and strictly positive. The same definition of the sub-optimality gap is also used in [12]. We note that $\Delta_{\min}$ can be seen as a generalization of the minimum sub-optimality gap in standard MAB problem defined as $\Delta := \min_{i:\mu_i \neq \mu^*} |\mu^* - \mu_i|$. Specifically, under the standard MAB setting, $m = 1, \mathcal{B} = \{\boldsymbol{a} | \boldsymbol{a} \in \{0,1\}^N, ||\boldsymbol{a}||_1 \leq 1\}$, $\Delta_{\min}$ coincides with Δ. In this paper, we will state our problem-dependent regret bounds in terms of $\Delta_{\min}$.

2.2 The general algorithm UCB-LP and its Performance analysis

Now we introduce our algorithm UCB-LP for combinatorial bandits with long-term linear constraints. UCB-LP is a generalization of SemiBwK algorithm [30] to the general linear constraints setting which chooses arms through randomized policy. In our setting, one main challenge is that no super-arm is optimal across all rounds, but there exists an optimal sampling distribution over arms and the intuition behind UCB-LP is to identify such distribution and sampling arms based on it. At each round, UCB-LP consists of two stages. In the first stage, we first compute the truncated UCB estimate vector $\hat{\boldsymbol{\mu}}(t) \in \mathbb{R}^N$ defined as $\hat{\mu}_i(t) = \min\left\{\bar{\mu}_i(t) + \sqrt{\frac{2\ln t}{h_i(t)}}, 1\right\}, \forall i \in [N]$. Then we solve the following LP and get an optimal solution $\boldsymbol{x}(t) \in \mathcal{B}$:

$$\max_{\boldsymbol{x} \in \mathbb{R}^N} \langle \hat{\boldsymbol{\mu}}(t), \boldsymbol{x} \rangle \qquad \text{s.t.} \quad \boldsymbol{g}(\boldsymbol{x}) \leq \boldsymbol{0}, \ \boldsymbol{0} \leq \boldsymbol{x} \leq \boldsymbol{1}, \ ||\boldsymbol{x}||_1 \leq m. \tag{4}$$

(Note that LP (2) and LP (4) have the same feasible region $\mathcal{D}$, hence the same set of extreme points $\mathcal{B}$.) Here we require the solved optimal solution $\boldsymbol{x}(t)$ to be an extreme point of LP (4), i.e., $\boldsymbol{x}(t) \in \mathcal{B}$. In fact, this is naturally satisfied by many LP algorithms, e.g., Simplex Method. Even if the optimal solution of LP is not an extreme point, it can be efficiently converted to one by tightening some slack constraints in (4) [26, 13].

166 The second stage is to construct a distribution $\pi_t(\cdot)$ over $\mathcal{A}$ with expectation $\boldsymbol{x}(t)$, i.e.,
167 $\sum_{\boldsymbol{a}\in\mathcal{A}} \pi_t(\boldsymbol{a}) \cdot \boldsymbol{a} = \boldsymbol{x}(t)$, and sample super-arm $\boldsymbol{a}(t) \sim \pi_t$. Since $\boldsymbol{x}(t) \in \mathcal{D} \subseteq \mathrm{Conv}(\mathcal{A})$, such π_t
168 exists and can be generated via a convex decomposition of $\boldsymbol{x}(t)$. Although there are many random-
169 ized rounding methods with $O(N^2)$ running time to achieve this, we show in the supplementary
170 material that computing π_t and sampling $\boldsymbol{a}(t)$ can be finished in $O(N \log N)$ time. The idea of
171 sampling arms maintaining the marginal distribution are also used in [8, 36]. Finally, we pull the
172 arms according to $\boldsymbol{a}(t)$, observe the reward value of pulled arms, and update the statistics.

173 Although motivated by SemiBwK algorithm [30], UCB-LP deals with general linear constraint
174 function without any assumptions and our goal is to derive a problem-dependent regret bound.
175 Therefore, new techniques have to be developed for the analysis of UCB-LP.

176 The following theorem provides the generic bounds of regret and constraint violations for UCB-LP.

177 **Theorem 1** *UCB-LP satisfies*

$$Regret_T = O\left(\frac{mN\log T}{\Delta_{\min}}\right), \tag{5}$$

$$E[Vio(T)] \leq \boldsymbol{0}. \tag{6}$$

178 **Proof sketch of Theorem 1:** Note that (6) is straightforward from LP (4) and the fact that $\boldsymbol{g}(\cdot)$
179 is linear. Now we present the main idea of proving (5). To obtain the regret bound, we cannot
180 directly apply the traditional analysis from bandit community here as we cannot bound $h_i(t)$ and the
181 algorithm might favor sub-optimal arms even if they have already been pulled for $\Omega(\log T)$ times due
182 to the structural property of the LP. Instead, we bound the number of times UCB-LP fails to yield
183 the optimal policy, i.e., $\boldsymbol{x}(t) \notin \mathcal{X}^*$. The most natural idea to achieve this is to bound the number of
184 times $\boldsymbol{x}(t) = \overline{\boldsymbol{x}}$ for every sub-optimal policy $\overline{\boldsymbol{x}} \in \mathcal{B} \setminus \mathcal{X}^*$. However, such an idea fails in the sense
185 that the resulting bound would scale with $|\mathcal{B}|$, which is exponentially large. Addressing this technical
186 challenge is nontrivial and previous works circumvented this problem by assuming special structures
187 (e.g., [12] and [29] assumed $|\mathcal{X}^*| = 1$, [31] assumed only one resource and $\|\boldsymbol{x}^*\|_0 = 1$, etc) or using
188 the prior knowledge of some problem-dependent parameters [29]. In our proof, we overcome this
189 difficulty directly by handling the case $\boldsymbol{x}(t) \notin \mathcal{X}^*$ with the idea of "regret allocation".

190 Define $\boldsymbol{w}(t) = \hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu} = (\sqrt{\frac{2\ln t}{h_i(t)}}, .., \sqrt{\frac{2\ln t}{h_N(t)}})^\top$. Since the regret only occurs when $\boldsymbol{x} \notin \mathcal{X}^*$, we claim
191 that $\langle\boldsymbol{\mu}, \boldsymbol{x}^*\rangle \leq \langle\hat{\boldsymbol{\mu}}(t), \boldsymbol{x}(t)\rangle$, $\langle\hat{\boldsymbol{\mu}}(t), \boldsymbol{x}(t)\rangle \geq \langle\boldsymbol{\mu}(t), \boldsymbol{x}(t)\rangle + \Delta_{\boldsymbol{x}(t)}$ and $\langle\boldsymbol{w}, \boldsymbol{x}(t)\rangle \geq \Delta_{\boldsymbol{x}(t)}/2$ all hold with
192 high probability in such case since $\langle\hat{\boldsymbol{\mu}}(t), \boldsymbol{x}(t)\rangle \geq$ (LP property)$\langle\hat{\boldsymbol{\mu}}(t), \boldsymbol{x}^*\rangle \geq$ (high-prob)$\langle\boldsymbol{\mu}, \boldsymbol{x}^*\rangle \geq$
193 $\langle\boldsymbol{\mu}, \boldsymbol{x}(t)\rangle + \Delta_{\boldsymbol{x}(t)} \Rightarrow \langle\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}, \boldsymbol{x}(t)\rangle \geq$ (high-prob)$\Delta_{\boldsymbol{x}(t)} \Rightarrow \langle 2\boldsymbol{w}, \boldsymbol{x}(t)\rangle \geq$ (high-prob)$\Delta_{\boldsymbol{x}(t)} \Rightarrow$
194 $\langle\boldsymbol{w}, \boldsymbol{x}(t)\rangle \geq$ (high-prob)$\Delta_{\boldsymbol{x}(t)}/2$. With these properties, when $\boldsymbol{x} \notin \mathcal{X}^*$, we could allocate the in-
195 curred regret $R_t = E[\langle\boldsymbol{\mu}, \boldsymbol{x}^*\rangle - \langle\boldsymbol{\mu}, \boldsymbol{x}(t)\rangle] = \Delta_{\boldsymbol{x}(t)}$ to every base arm in the following way, and we
196 will argue that this allocation is correct since:

$$R_t = E[\langle\boldsymbol{\mu}, \boldsymbol{x}^*\rangle - \langle\boldsymbol{\mu}, \boldsymbol{x}(t)\rangle] = \Delta_{\boldsymbol{x}(t)} = E[\langle\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}, \boldsymbol{x}(t)\rangle] - E[\langle\boldsymbol{\mu}, \boldsymbol{x}^*\rangle - \langle\hat{\boldsymbol{\mu}}(t), \boldsymbol{x}(t)\rangle]$$
$$\leq \text{(high-prob)}E[\langle\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}, \boldsymbol{x}(t)\rangle] \leq \text{(high-prob)}E[\langle 2\boldsymbol{w}, \boldsymbol{x}(t)\rangle] = 2E[\sum_{i\in[N]} x_i(t)\sqrt{2\ln t/h_i(t)}]$$

197 Thus each arm contributes $2x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}$ to the regret $\Delta_{\boldsymbol{x}(t)}$. Next we claim that the sum above
198 regret allocation on all arms is dominated by the arms in the set $V(t) = \{i : h_i(t) \leq \frac{32m^2\ln t}{\Delta_{\min}^2}\}$, i.e.,
199 $\frac{1}{2}\sum_{i\in[N]} 2x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}} \leq \sum_{i\in V(t)} 2x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}$, which is derived by:

200 $\sum_{i\in[N]/V(t)} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}} \leq \sum_{i\in[N]/V(t)} x_i(t)\frac{\Delta_{\min}}{4m} \leq \sum_{i\in[N]} x_i(t)\frac{\Delta_{\min}}{4m} \leq \frac{\Delta_{\min}}{4} \leq \frac{\Delta_{\boldsymbol{x}(t)}}{4}$, and
201 $\sum_{i\in[N]} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}} = \langle\boldsymbol{w}(t), \boldsymbol{x}(t)\rangle \geq \frac{\Delta_{\boldsymbol{x}(t)}}{2}$.

202 Therefore, the following total regret decomposition holds with high-probability:

$$Regret_T \leq 2E[\sum_{t=1}^{T}\sum_{i\in[N]} x_i(t)\sqrt{2\ln t/h_i(t)}\mathbf{I}\{\boldsymbol{x}(t) \notin \mathcal{X}^*\}]$$

$$\leq 4E[\sum_{t=1}^{T}\sum_{i\in V(t)} x_i(t)\sqrt{2\ln t/h_i(t)}\mathbf{I}\{\boldsymbol{x}(t) \notin \mathcal{X}^*\}] \leq 4E[\sum_{t=1}^{T}\sum_{i\in V(t)} x_i(t)\sqrt{2\ln t/h_i(t)}]. \tag{7}$$

203 Define $G(i) = \{t : i \in V(t)\}$, and $T_i = \arg\max_{\tau \in G(i)} \tau$. Continuing from (7) we obtain

$$Regret_T \leq 4E[\sum_{t=1}^{T}\sum_{i \in V(t)} x_i(t)\sqrt{2\ln t/h_i(t)}] = 4E[\sum_{i \in N}\sum_{t \in G(i)} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}] \leq 4E[\sum_{i \in N}\sum_{t=1}^{T_i} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}].$$

204 Now the remaining problem is to bound $4E[\sum_{i \in N}\sum_{t=1}^{T_i} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}]$, which is solved by the follow-
205 ing lemma.

206 **Lemma 1** $E[\sum_{\tau=1}^{t} x_i(\tau)\sqrt{\ln\tau/h_i(\tau)}] \leq 3\sqrt{\ln t} \cdot E[\sqrt{h_i(t)+1}]$.

207 Applying Lemma 1 yields $4E[\sum_{i \in N}\sum_{t=1}^{T_i} x_i(t)\sqrt{\frac{2\ln t}{h_i(t)}}] \leq 12\sum_{i \in [N]}\sqrt{2\ln T_i(h_i(T_i)+1)} \leq$
208 $12\sum_{i \in [N]}\sqrt{2\ln T_i(\frac{32m^2\ln T_i}{\Delta_{\min}^2}+1)}$ (Since $T_i \in V(T_i)$) $\leq 12\sum_{i \in [N]}\sqrt{2\ln T(32m^2\ln T/\Delta_{\min}^2+1)} =$
209 $O(\frac{mN}{\Delta_{\min}}\ln T)$. Put all things together we complete the proof of Theorem 1.

210 **Proof Sketch of Lemma 1:** Our proof idea is using the facts (a): $1/\sqrt{x} \leq 3(\sqrt{x+1}-\sqrt{x})$, $x \geq 1$;
211 (b): $E[\sqrt{h_i(\tau+1)}|\mathcal{F}_t] = E[x_i(\tau)\sqrt{h_i(\tau)+1}|\mathcal{F}_{t-1}] + E[(1-x_i(\tau))\sqrt{h_i(\tau)}|\mathcal{F}_{t-1}]$, where $\mathcal{F}_t =$
212 $\{\boldsymbol{x}(\tau)\}_{\tau=1}^{t}$. Then $E[\sum_{\tau=1}^{t} E[x_i(\tau)\sqrt{\ln\tau/h_i(\tau)}|\mathcal{F}_{\tau-1}]] \leq \sqrt{\ln t}E[\sum_{\tau=1}^{t} E[x_i(\tau)\sqrt{1/h_i(\tau)}|\mathcal{F}_{\tau-1}]] \overset{(a)}{\leq}$
213 $3\sqrt{\ln t}E[\sum_{\tau=1}^{t} E[x_i(\tau)(\sqrt{h_i(\tau)+1}-\sqrt{h_i(\tau)})|\mathcal{F}_{\tau-1}]] \overset{(b)}{=} 3\sqrt{\ln t}E[\sum_{\tau=1}^{t} E[\sqrt{h_i(\tau+1)}|\mathcal{F}_\tau] -$
214 $E[\sqrt{h_i(\tau)}|\mathcal{F}_{\tau-1}]] \leq 3\sqrt{\ln t}E[E[\sqrt{h_i(t+1)}|\mathcal{F}_t]] \leq \sqrt{\ln t}E[\sqrt{h_i(t+1)}] \leq 3\sqrt{\ln t}E[\sqrt{h_i(t)+1}]$.

215 **Comparison with previous results.** Several previous works (e.g., [12, 31, 29, 28]) studying bandits
216 with long term constraints have also achieved $O(\log T)$ regret bounds. Our regret bound has four
217 major improvements over theirs: (a) Our regret bound has a better dependence on $\Delta_{\min}$ and N. (b)
218 Previous regret bounds only apply to the single-armed setting, while ours applies to the combinatorial
219 setting. (c) Our regret bound is valid for all linear constraints, while theirs is only valid for specific
220 kind of constraints, either BwK with deterministic costs, or fairness constraints (which are the special
221 cases of linear constraints). (d) Almost all of them require additional assumptions or knowledge
222 of some parameters of the problem instance a prior. For example, [12] explicitly admitted that
223 their (poly-)logarithmic regret and the corresponding analysis only valid under the assumption of
224 $|\mathcal{X}^*| = 1$. (See Appendix A.1 and Assumption 9 in their arxiv version.) However, $|\mathcal{X}^*| = 1$ does not
225 always hold. When consider BwK problem with only one resource, if there exist arms p, q such
226 that $\frac{\mu_p}{\lambda_p} = \frac{\mu_q}{\lambda_q}$, where λ_i is the amount of resource consumed by arm i if it gets pulled, then LP (2)
227 has non-unique optimal solution, i.e., $|\mathcal{X}^*| \neq 1$. Even consider problem of bandits with fairness
228 constraints, if there exist two arms with the same required probability of being pulled, the optimal
229 solution to LP (2) also may not be unique. Beyond assuming $|\mathcal{X}^*| = 1$, the algorithms in [29] still
230 require some prior knowledge of the problem instance (characterized by μ^* and $\Delta_{\min}$). Substantial
231 assumptions including only one resource and "best-arm-optimality" are also required in [31]. On the
232 contrary, we do not require any assumptions and prior knowledge of the problem instance.

233 **Reduction to unconstrained (combinatorial) bandits setting.** When there are no constraints, i.e.,
234 $\boldsymbol{g}(t) = \boldsymbol{0}$, UCB-LP reduces to the standard (Comb) UCB1 algorithm [19] and we could also recover
235 the results of [19] in such case. This further justifies the tightness of our regret bound.

2.3   Achieving constant regret for fairness constraints

237 In this section, we consider the special case of fairness constraints. Following the same setting
238 in the literature, e.g., [22, 35, 28], each arm $i \in [N]$ is required to be pulled at least $r_i \in (0, 1)$
239 fraction of times, and $\sum_{i \in [N]} r_i < m$. Namely, the agent has to satisfy $h_i(T) \geq r_i T, \forall i \in [N]$. Define
240 $\boldsymbol{r} = (r_1, r_2, \ldots, r_N)^\top$, then the equivalent linear long term constraint function $\boldsymbol{g}(\cdot)$ under our setting
241 is $\boldsymbol{g}(\boldsymbol{a}(t)) = -\boldsymbol{a}(t) + \boldsymbol{r}$. In the fairness constraints setting, the main challenge is that the time horizon
242 T is unknown to the algorithm beforehand, and thus the "forced exploration" trick cannot be directly
243 applied here. A lot of work (See Table 1) has sprung up recently to tackle this difficulty, but the best
244 previous result is only $\tilde{O}(\sqrt{T})$ under the combinatorial setting. The following theorem shows that
245 UCB-LP could guarantee a constant regret.

246 **Theorem 2** *Define $r_{\min} := \min_{i \in [N]} r_i$. In the case of fairness constraints, UCB-LP guarantees that*

$$Regret_T \leq \frac{32mN^2}{r_{\min}^2\Delta_{\min}^2}\ln^2\left(\frac{32N^2}{r_{\min}^2\Delta_{\min}^2}\right) + \frac{mN\pi^2}{2}.$$

Basic analysis of Theorem 2. To derive a constant regret, one natural idea is to show that the quantity $E[h_i(T)] - r_i \cdot T$ is bounded for every sub-optimal arm i (whose mean reward is not Top-m). However, this is not the case in classic bandit analysis (e.g., for UCB-based algorithms) and thus cannot directly apply here. Our main proof idea is to show that UCB-LP only chooses a sub-optimal distribution over arms (i.e., $\boldsymbol{x}(t) \notin \mathcal{X}^*$) a limited number of times for fairness constraints. To achieve this, we first transform the event of $\boldsymbol{x}(t) \notin \mathcal{X}^*$ to the events associated with arm's UCB estimate error, i.e., we use the following lemma to characterize the case of $\boldsymbol{x}(t) \notin \mathcal{X}^*$ by the sensitivity analysis of LP (4).

Lemma 2 *If* $||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_1 < \Delta_{\min}$, *then* $\boldsymbol{x}(t) \in \mathcal{X}^*$.

In other words, when $\boldsymbol{x}(t) \notin \mathcal{X}^*$ we have $||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_1 > \Delta_{\min}$. And then we just have to prove that $||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_1 > \Delta_{\min} \Rightarrow \max_{i \in [N]} |\hat{\mu}_i - \mu_i| \geq \Delta_{\min}/N$ only happens a finite number of times. This is a little counterintuitive for UCB-style algorithms, but it holds for UCB-LP in the fairness setting as UCB-LP guarantees that every arm has a positive probability of being pulled at each round which leads to the diminishing confidence width of all arms and the bonus of concentration inequality. In particular, by martingale analysis and extending the concentration bound to a random process that evolves over time, we prove that there exists a constant $c > 0$ (e.g., $\frac{32N^2}{r_{\min}^2 \Delta_{\min}^2} \ln^2 \frac{32N^2}{r_{\min}^2 \Delta_{\min}^2}$) such that $h_i(t) \geq \frac{8N^2}{\Delta_{\min}^2} \ln t$ holds with high-probability for each arm i when $t > c$, which gives that $|\hat{\mu}_i(t) - \mu_i| \leq \Delta_{\min}/N$ holds with high-probability when $t > c$. It is worth noting that such properties do not hold for classic bandit algorithms (e.g., algorithms based on the UCB1 framework). And to the best of our knowledge there is no such results in the literature. Finally, to fit into our Lemma 2, we handle the regret as $Regret_T \leq m \sum_{t=1}^{T} \Pr[\boldsymbol{x}(t) \notin \mathcal{X}^*] \leq mc + m \sum_{t=c+1}^{T} \Pr[\boldsymbol{x}(t) \notin \mathcal{X}^*] \leq mc + m \sum_{t=c+1}^{T} \Pr[||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_1 \geq \Delta_{\min}]$. Put all things together then we complete the proof.

Breaking the $\Omega(\log T)$ **lower bound.** The constant regret bound given by Theorem 2 might seem counter-intuitive at first glance, since the lower bound of regret under classical MAB setting is $\Omega(\log T)$ [20]. However, note that the fairness level r_i is required to be strictly positive, and the benchmark policy in the regret also needs to satisfy the long term constraints. This distinguishes our setting from the classical MAB setting. Thus, the traditional $\Omega(\log T)$ lower bound no longer applies.

The reason why UCB-LP achieves a constant regret is: UCB-LP guarantees that every arm has a positive probability of being pulled at each round. This leads to more accurate reward estimates of arms and a diminishing gap between $\hat{\boldsymbol{\mu}}(t)$ and $\boldsymbol{\mu}$, which makes UCB-LP output the sub-optimal action distribution only a finite number of times. That said, it still requires non-trivial techniques to establish a constant regret bound. In fact, even $O(\log T)$ regret bound has not yet been achieved for combinatorial setting in prior works.

Note that our regret bound has a quadratic dependence on $1/r_{\min}$, which goes to infinity as $\boldsymbol{r} \to \boldsymbol{0}$. In fact, when $\boldsymbol{r} = \boldsymbol{0}$, i.e., there are no fairness constraints, our problem degenerates to classical MAB setting where achieving constant regret bound is impossible. This indicates that such dependence on extra parameters is inevitable for any constant regret bound. Of course, the general $O(\log T)$ regret bound developed in Theorem 1 still applies when $\boldsymbol{r} \to \boldsymbol{0}$, since it does not depend on $1/r_{\min}$.

$\tilde{O}(N)$ **running time.** The structural property of the fairness constraints allows us to obtain a closed form solution to LP (4), as shown in the following proposition.

Proposition 1 *For each round t, rearrange the coordinates of UCB estimate vector $\hat{\boldsymbol{\mu}}(t)$ in descending order such that $\hat{\mu}_{\sigma_1^t}(t) \geq \hat{\mu}_{\sigma_2^t}(t) \geq \cdots \geq \hat{\mu}_{\sigma_N^t}(t)$, where $\sigma_1^t, \ldots, \sigma_N^t$ is a permutation of $1, \ldots, N$. Then one of the optimal extreme points to LP (4) (denoted as $\boldsymbol{x}(t)$) has the following form:*

$$x_{\sigma_i^t}(t) = 1, \ \forall i < k_t; \ x_{\sigma_i^t}(t) = r_{\sigma_i^t}, \forall i > k_t; x_{\sigma_{k_t}^t}(t) = m + 1 - k_t - \sum_{i > k_t} r_{\sigma_i^t},$$

where $k_t = \min\{q \in \mathbb{Z}^+ \mid \sum_{i=1}^{q}(1 - r_{\sigma_i^t}) \geq m - \sum_{i=1}^{N} r_i\}$.

Proposition 1 immediately implies that UCB-LP is computationally efficient when dealing with fairness constraints. To solve LP (4), one can simply sort all coordinates of $\hat{\boldsymbol{\mu}}(t)$ in $O(N \log N)$ time, then compute k_t and $\boldsymbol{x}(t)$ according to the closed form expression in proposition 1 (note that $\boldsymbol{x}(t)$ in Proposition 1 also lies in $\mathcal{B}$). Since the running time of computing distribution π_t and sampling $\boldsymbol{a}(t)$ is also $O(N \log N)$, we conclude that the time average complexity of UCB-LP is $O(N \log N) = \tilde{O}(N)$.

Another constant regret bound. Proposition 1 further provides two important implications:

(a) Since LP (2) has the same form with LP (4), the optimal solution $\boldsymbol{x}^*$ to LP (2) can also be written in closed form in the same manner to Proposition 1. Specifically, rearrange the coordinates of $\boldsymbol{\mu}$

Algorithm 1 UCB-PLLP

1: **Initialization:** $\mathcal{A} = \{\boldsymbol{x} | \boldsymbol{x} \in \{0,1\}^N, ||\boldsymbol{x}||_1 \le m\}$
2: **for** round $t = 1, ...T - 1$ **do**
3:     Compute UCBs: $\hat{\mu}_i(t) = \min\{\overline{\mu}_i(t) + \sqrt{\frac{2\ln t}{h_i(t)}}, 1\}, \ \forall i.$
4:     Update the primal iterate: $\boldsymbol{a}(t) = \arg\max_{\boldsymbol{a} \in \mathcal{A}} \langle \hat{\boldsymbol{\mu}}(t) - \alpha_t \sum_{k=1}^{K} \nabla g_k(\boldsymbol{a}(t-1)) Q_k(t), \boldsymbol{a} \rangle$
5:     Play arm i and receive $f_i(t)$ if $a_i(t) = 1$.
6:     Update the virtual queues: $\boldsymbol{Q}(t+1) = [\boldsymbol{Q}(t) + \boldsymbol{g}(\boldsymbol{a}(t)) + \epsilon_t \boldsymbol{I}]^+.$
7:     Update the statistics: $h_i(t+1), \overline{\mu}_i(t+1), \ \forall i.$
8: **end for**

---

in descending order as $\mu_{\sigma_1} \ge \mu_{\sigma_2} \ge \cdots \ge \mu_{\sigma_N}$, and define $k = \min\{q \in \mathbb{Z}^+ \mid \sum_{i=1}^{q}(1 - r_{\sigma_i}) \ge m - \sum_{i=1}^{N} r_i\}$. Then $\boldsymbol{x}^*$ has the following form:

$$x_{\sigma_i}^* = 1, \ \forall i < k; \ x_{\sigma_i}^* = r_{\sigma_i}, \forall i > k; x_{\sigma_k}^* = m + 1 - k - \sum r_{\sigma_i}.$$

(b) The optimal solution $\boldsymbol{x}(t)$ to LP (4) only depends on the relative order, not the absolute value of $\hat{\mu}_1(t), \ldots, \hat{\mu}_N(t)$. This motivates us to characterize the sensitivity of LP (4) from a new perspective. Intuitively, if $\hat{\boldsymbol{\mu}}$ and $\boldsymbol{\mu}$ are close enough such that the relative order between the coordinates is (at least partially) preserved, then the optimal solutions of LP (4) and LP (2) will coincide.

The above two implications motivate us to define a new parameter $\epsilon := \min_{\mu_i \ne \mu_{\sigma_k}} |\mu_i - \mu_{\sigma_k}|$, and propose the following corollary to characterize the sensitivity of LP (4).

Corollary 1 *If* $||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_\infty < \frac{\epsilon}{2}$, *then* $\boldsymbol{x}(t) \in \mathcal{X}^*$.
Proof sketch of Corollary 1. Proposition 1 shows that when $\boldsymbol{r}$ is fixed, for $\forall i \ne \sigma_{k_t}^t$, the value of $x_i(t)$ only depends on whether $\hat{\mu}_i(t) < \hat{\mu}_{\sigma_{k_t}^t}(t)$ or not. Similarly, for $\forall i \ne \sigma_k$, the value of x_i^* only depends on whether $\mu_i < \mu_{\sigma_k}$ or not. This implies that, if $k_t = k, \sigma_{k_t}^t = \sigma_k$, and $\hat{\mu}_i(t) - \hat{\mu}_{\sigma_{k_t}^t}(t)$ have the same sign with $\mu_i - \mu_{\sigma_k}$, then $x_i(t) = x_i^*$. In other words, if $\mu_i > \mu_{\sigma_k} \Rightarrow \hat{\mu}_i(t) > \hat{\mu}_{\sigma_k}(t)$ and $\mu_i < \mu_{\sigma_k} \Rightarrow \hat{\mu}_i(t) < \hat{\mu}_{\sigma_k}(t)$ holds for $\forall i \in [N]$, then $\boldsymbol{x}(t) = \boldsymbol{x}^*$. When $||\hat{\boldsymbol{\mu}}(t) - \boldsymbol{\mu}||_\infty < \frac{\epsilon}{2}$, by the definition of ϵ, for $\forall i$ we have $\mu_i > \mu_{\sigma_k} \Rightarrow \mu_i \ge \mu_{\sigma_k} + \epsilon \Rightarrow \hat{\mu}_i(t) > \mu_i - \frac{\epsilon}{2} \ge \mu_{\sigma_k} + \frac{\epsilon}{2} > \hat{\mu}_{\sigma_k}(t)$ and $\mu_i < \mu_{\sigma_k} \Rightarrow \mu_i \le \mu_{\sigma_k} - \epsilon \Rightarrow \hat{\mu}_i(t) < \mu_i + \frac{\epsilon}{2} \le \mu_{\sigma_k} - \frac{\epsilon}{2} < \hat{\mu}_{\sigma_k}(t)$. Then $\boldsymbol{x}(t) = \boldsymbol{x}^*$.

With Corollary 1, we derive another constant regret bound of UCB-LP in the following theorem.

Theorem 3 *UCB-LP also guarantees the following regret bound for fairness constraints,*
$$Regret_T \le \frac{64m}{r_{\min}^2 \epsilon^2} \ln^2 \left(\frac{64}{r_{\min}^2 \epsilon^2} \right) + \frac{mN\pi^2}{2}.$$

In the supplementary material, we show that $\Delta_{\min} = \epsilon = \Delta$ when our formulation reduces to the classical MAB setting, which suggests that $\Delta_{\min}$ and ϵ are both reasonable generalizations of Δ. Although ϵ and $\Delta_{\min}$ are generally incomparable, we believe that the regret bound given by Theorem 3 is tighter than Theorem 2. To provide evidences for this, in supplementary material, we investigate the closed form expression of $\Delta_{\min}$. We show that $\epsilon = \Delta \ge \Delta_{\min} = \Delta(1 - \sum_i r_i)$ in the special case of $m = 1$. Intuitively, ϵ characterizes the structural properties of fairness constraints, while $\Delta_{\min}$ is more general and applies to all linear constraints.

Remark 1 *LP-sensitivity arguments are not new in bandit analyses and was firstly shown in [31] which used a technique based on LP-sensitivity to analyze the UcbBwK algorithm [1] for BwK problem in the single-arm setting. Here we would like to point out that the technique based on LP-sensitivity we used is completely different from theirs. Specifically, their analysis relies on the assumptions of single resource and that the best distribution over arms reduces to the best fixed arm, while we do not require any assumptions. Moreover, our technique is also non-standard as our sensitivity analysis (Lemma 2, Corollary 1) takes full advantage of the fairness structure (e.g., closed-form solution of LP). Thus, our result is sharper than standard results about LP sensitivity and leads to the $O(1)$ regret bound.*

2.4 $\tilde{O}(N)$ **running time version of UCB-LP and its theoretical performance**

As mentioned earlier, UCB-LP might be computationally inefficient when constraint function $\boldsymbol{g}(\cdot)$ is complicated. In this section, we present the low computational-complexity version of UCB-LP,

the UCB-PLLP algorithm, for problems of combinatorial bandits with linear long-term constraint. Note that the main computational bottleneck of UCB-LP is caused by the constraint $\boldsymbol{g}(\boldsymbol{x}) \leq \boldsymbol{0}$. To be computationally efficient, we optimize the (partial) Lagrangian of LP (4) at each round t:

$$\max_{\boldsymbol{x} \in R^N} \mathcal{L}_t(\boldsymbol{x}, \boldsymbol{\lambda}_t) = \langle \hat{\boldsymbol{\mu}}(t), \boldsymbol{x} \rangle - \boldsymbol{\lambda}_t^T \boldsymbol{g}(\boldsymbol{x}) \quad s.t. \quad \boldsymbol{0} \leq \boldsymbol{x} \leq \boldsymbol{1}, \; \|\boldsymbol{x}\|_1 \leq m. \tag{8}$$

In (8) $\boldsymbol{\lambda}_t$ is the Lagrange multiplier associated with the constraints at round t. The main challenge is how to design $\boldsymbol{\lambda}_t$ to make a good balance between reward maximization and long-term constraints satisfaction. To address this challenge, we construct a virtual queue $\boldsymbol{Q}(t)$ to keep track of the "debt" of constraint violations up to round t, i.e., $\boldsymbol{Q}(t) = [\boldsymbol{Q}(t-1) + \boldsymbol{g}(\boldsymbol{a}(t-1))]^+$, and let $\boldsymbol{\lambda}_t = \alpha_t \boldsymbol{Q}(t)$, where α_t could be time-varying. However, this Lagrange multiplier deign may lead to large constraint violations as $\boldsymbol{g}(\cdot)$ becomes a "soft" constraint in LP (8) while in LP (4) it is a "hard" constraint.

To yield lower constraint violations, we incorporate the virtual queue update with "pessimistic" mechanism so that the virtual queues overestimate the constraint violations, which is a novelty of our UCB-PLLP. Although the idea of using a "pessimistic" mechanism has been exploited in linear (contextual) bandits with safety constraints (e.g., [2, 27], etc), the pessimism in our algorithm is achieved via adding a time-varying tightness constant to virtual queue update, i.e., $\boldsymbol{Q}(t) = [\boldsymbol{Q}(t-1) + \boldsymbol{g}(\boldsymbol{a}(t-1)) + \epsilon_{t-1}\boldsymbol{I}]^+$, which is completely different from the pessimism in previous works. Since $\boldsymbol{g}(\cdot)$ is linear, the optimization problem (8) has an integral closed-form solution and is equivalent to the following optimization problem:

$$\max_{\boldsymbol{x}} \; \langle \hat{\boldsymbol{\mu}}(t) - \alpha_t \sum_{k \in [K]} \nabla g_k(\boldsymbol{a}(t-1))Q_k(t), \boldsymbol{x} \rangle \quad s.t. \quad \boldsymbol{x} \in [0,1]^N, \; \|\boldsymbol{x}\|_1 \leq m.$$
$$\Longleftrightarrow \max_{\boldsymbol{a}} \; \langle \hat{\boldsymbol{\mu}}(t) - \alpha_t \sum_{k \in [K]} \nabla g_k(\boldsymbol{a}(t-1))Q_k(t), \boldsymbol{a} \rangle \quad s.t. \quad \boldsymbol{a} \in \{0,1\}^N, \; \|\boldsymbol{a}\|_1 \leq m. \tag{9}$$

We illustrate this algorithmic approach in Algorithm 1. Note that if we set $\alpha_t = \eta$ and $\epsilon_t = 0$, the algorithm LBF in [22] is our special case as $\nabla g_k(\cdot) = -\boldsymbol{e}_k$ and $K = N$ for fairness constraints setting. Apparently, the computational-complexity of UCB-PLLP is essentially the same as choosing the top m arms with maximum positive compound value, which is $\tilde{O}(N)$.

Theoretical performance of UCB-PLLP. Here we present the regret bound and constraint violations for UCB-PLLP. Our result relies on a mild assumption of Slater condition (Interior condition), i.e., there exists a $\delta > 0$ and $\hat{\boldsymbol{x}} \in \mathcal{D}$ such that $\boldsymbol{g}(\hat{\boldsymbol{x}}) \leq -\delta\boldsymbol{I}$. Note that Slater condition automatically holds for fairness constraints as $r_i < 1, \; \forall i$, and $\sum_{i \in [N]} r_i < m$. It is also a default assumption in BwK literature (They all assume the null arm denoted by 0 exists, i.e, $\lambda_{i,0} = 0, \; \forall i \in [K]$).

Theorem 4 *Set $\epsilon_t = O(\frac{\delta}{\sqrt{t}})$ and $\alpha_t = O(\frac{N}{\delta\sqrt{t}})$, then UCB-PLLP achieves*

$$Regret_T \leq \tilde{O}(m\sqrt{T}), \quad \Pr[Vio_k(\tau) > 0] \leq O(e^{-\delta\sqrt{\tau}}), \; \forall k \in [K], \; \tau \leq T.$$

We give the proof of Theorem 4 in supplementary material. Our proof technique is based on the Lyapunov-drift analysis for queueing systems. The bounds in Theorem 4 are sharp in the perspective that the regret bound matches the problem-independent regret of UCB1 algorithm in standard MAB setting, and the probability of constraints not being violated converges to 1, i.e, holds asymptotically almost surely.

Intuition behind Theorem 4. Here we explain the intuition why UCB-PLLP has such performance guarantees. Since $\alpha = O(1/\sqrt{t})$, the reward term dominates the whole term in (9) when $Q_k(t) = o(\sqrt{t})$. If $Q_k(t) = \omega(\sqrt{t})$, the term containing virtual queues dominates the reward term, and UCB-PLLP tends to reduce the virtual queues $Q_k(t)$. Slater's condition implies that there exists a policy that can reduce $Q_k(t)$ by a constant (related to δ) in each round. Therefore, the algorithm takes at most $O(\sqrt{t})$ rounds to reduce $Q_k(t)$ to $o(\sqrt{t})$, which may lead to $O(\sqrt{t})$ increase of the regret. Thus, we could derive that $Q_k(t) = O(\sqrt{t})$. Recall that $Q_k(t+1) \geq \sum_{t=1}^{T} g_k(\boldsymbol{a}(t)) + \sum_{t=1}^{T} \epsilon_t \Rightarrow Vio_k(T) = \sum_{t=1}^{T} g_k(\boldsymbol{a}(t)) \leq Q_k(T+1) - \sum_{t=1}^{T} \epsilon_t$, we can obtain zero constraint violation via choosing proper ϵ_t. Then, the high probability constraint violation guarantee is established by bounding the exponential moment of the virtual queues since $\Pr(Vio_k(T) \geq 0) \leq \Pr(Q_k(T+1) \geq \sum_{t=1}^{T} \epsilon_t) \leq E[e^{\|\boldsymbol{Q}(T+1)\|_1}]/e^{\sum_{t=1}^{T} \epsilon_t}$.

2.5 Experiments

The results of our numerical experiments are given in the supplementary material.

References

[1] Shipra Agrawal and Nikhil R Devanur. Bandits with concave rewards and convex knapsacks. In *Proceedings of the fifteenth ACM conference on Economics and computation*, pages 989–1006, 2014.

[2] Sanae Amani, Mahnoosh Alizadeh, and Christos Thrampoulidis. Linear stochastic bandits under safety constraints. *Advances in Neural Information Processing Systems*, 32:9256–9266, 2019.

[3] Sanae Amani, Mahnoosh Alizadeh, and Christos Thrampoulidis. Generalized linear bandits with safety constraints. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3562–3566. IEEE, 2020.

[4] Ashwinkumar Badanidiyuru, Robert Kleinberg, and Aleksandrs Slivkins. Bandits with knapsacks. *Journal of the ACM (JACM)*, 65(3):1–55, 2018.

[5] Dimitris Bertsimas and John N Tsitsiklis. *Introduction to linear optimization*, volume 6. Athena Scientific Belmont, MA, 1997.

[6] Wei Chen, Yajun Wang, and Yang Yuan. Combinatorial multi-armed bandit: General framework and applications. In *International conference on machine learning*, pages 151–159. PMLR, 2013.

[7] Houston Claure, Yifang Chen, Jignesh Modi, Malte Jung, and Stefanos Nikolaidis. Multi-armed bandits with fairness constraints for distributing resources to human teammates. In *Proceedings of the 2020 ACM/IEEE International Conference on Human-Robot Interaction*, pages 299–308, 2020.

[8] Richard Combes, Chong Jiang, and Rayadurgam Srikant. Bandits with budgets: Regret lower bounds and optimal algorithms. *ACM SIGMETRICS Performance Evaluation Review*, 43(1):245–257, 2015.

[9] Debojit Das, Shweta Jain, and Sujit Gujar. Budgeted combinatorial multi-armed bandits. *arXiv preprint arXiv:2202.03704*, 2022.

[10] Guanhua Fang, Ping Li, and Gennady Samorodnitsky. A new look at fairness in stochastic multi-armed bandit problems. 2021.

[11] Kris Johnson Ferreira, David Simchi-Levi, and He Wang. Online network revenue management using thompson sampling. *Operations research*, 66(6):1586–1602, 2018.

[12] Arthur Flajolet and Patrick Jaillet. Logarithmic regret bounds for bandits with knapsacks. *arXiv preprint arXiv:1510.01800*, 2015.

[13] Dongdong Ge, Chengwenjian Wang, Zikai Xiong, and Yinyu Ye. From an interior point to a corner point: Smart crossover. *arXiv preprint arXiv:2102.09420*, 2021.

[14] Zhiming Huang, Yifan Xu, Bingshan Hu, Qipeng Wang, and Jianping Pan. Thompson sampling for combinatorial semi-bandits with sleeping arms and long-term fairness constraints. *arXiv preprint arXiv:2005.06725*, 2020.

[15] Ziyao Huang, Weiwei Wu, Chenchen Fu, Vincent Chau, Xiang Liu, Jianping Wang, and Junzhou Luo. Aoi-constrained bandit: Information gathering over unreliable channels with age guarantees. *arXiv preprint arXiv:2112.02786*, 2021.

[16] Nicole Immorlica, Karthik Abinav Sankararaman, Robert Schapire, and Aleksandrs Slivkins. Adversarial bandits with knapsacks. In *2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 202–219. IEEE, 2019.

[17] Matthew Joseph, Michael Kearns, Jamie Morgenstern, and Aaron Roth. Fairness in learning: Classic and contextual bandits. *arXiv preprint arXiv:1605.07139*, 2016.

[18] Thomas Kesselheim and Sahil Singla. Online learning with vector costs and bandits with knapsacks. In *Conference on Learning Theory*, pages 2286–2305. PMLR, 2020.

[19] Branislav Kveton, Zheng Wen, Azin Ashkan, and Csaba Szepesvari. Tight regret bounds for stochastic combinatorial semi-bandits. In *Artificial Intelligence and Statistics*, pages 535–543. PMLR, 2015.

[20] Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[21] Feng Li, Jichao Zhao, Dongxiao Yu, Xiuzhen Cheng, and Weifeng Lv. Harnessing context for budget-limited crowdsensing with massive uncertain workers. *arXiv preprint arXiv:2107.01385*, 2021.

[22] Fengjiao Li, Jia Liu, and Bo Ji. Combinatorial sleeping bandits with fairness constraints. *IEEE Transactions on Network Science and Engineering*, 7(3):1799–1813, 2019.

[23] Xiaocheng Li, Chunlin Sun, and Yinyu Ye. The symmetry between arms and knapsacks: A primal-dual approach for bandits with knapsacks. *arXiv preprint arXiv:2102.06385*, 2021.

[24] Xin Liu, Bin Li, Pengyi Shi, and Lei Ying. An efficient pessimistic-optimistic algorithm for stochastic linear bandits with general constraints. *Advances in Neural Information Processing Systems*, 34, 2021.

[25] Will Ma, Pan Xu, and Yifan Xu. Group-level fairness maximization in online bipartite matching. *arXiv preprint arXiv:2011.13908*, 2020.

[26] Nimrod Megiddo. On finding primal-and dual-optimal bases. *ORSA Journal on Computing*, 3(1):63–65, 1991.

[27] Aldo Pacchiano, Mohammad Ghavamzadeh, Peter Bartlett, and Heinrich Jiang. Stochastic bandits with linear constraints. In *International Conference on Artificial Intelligence and Statistics*, pages 2827–2835. PMLR, 2021.

[28] Vishakha Patil, Ganesh Ghalme, Vineet Nair, and Y Narahari. Achieving fairness in the stochastic multi-armed bandit problem. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5379–5386, 2020.

[29] Wenbo Ren, Jia Liu, and Ness B Shroff. On logarithmic regret for bandits with knapsacks. In *2021 55th Annual Conference on Information Sciences and Systems (CISS)*, pages 1–6. IEEE, 2021.

[30] Karthik Abinav Sankararaman and Aleksandrs Slivkins. Combinatorial semi-bandits with knapsacks. In *International Conference on Artificial Intelligence and Statistics*, pages 1760–1770. PMLR, 2018.

[31] Karthik Abinav Sankararaman and Aleksandrs Slivkins. Bandits with knapsacks beyond the worst case. In *Thirty-Fifth Conference on Neural Information Processing Systems*, 2021.

[32] Siwei Wang and Wei Chen. Thompson sampling for combinatorial semi-bandits. In *International Conference on Machine Learning*, pages 5114–5122. PMLR, 2018.

[33] Yingce Xia, Wenkui Ding, Xu-Dong Zhang, Nenghai Yu, and Tao Qin. Budgeted bandit problems with continuous random costs. In *Asian conference on machine learning*, pages 317–332. PMLR, 2016.

[34] Yingce Xia, Haifang Li, Tao Qin, Nenghai Yu, and Tie-Yan Liu. Thompson sampling for budgeted multi-armed bandits. In *Twenty-Fourth International Joint Conference on Artificial Intelligence*, 2015.

[35] Huanle Xu, Yang Liu, Wing Cheong Lau, and Rui Li. Combinatorial multi-armed bandits with concave rewards and fairness constraints. In *IJCAI*, pages 2554–2560, 2020.

[36] Julian Zimmert, Haipeng Luo, and Chen-Yu Wei. Beating stochastic and adversarial semi-bandits optimally and simultaneously. In *International Conference on Machine Learning*, pages 7683–7692. PMLR, 2019.