Improving black-box optimization in VAE latent space using decoder uncertainty

Abstract

Optimization in the latent space of variational autoencoders is a promising approach to generate high-dimensional discrete objects that maximize an expensive black-box property (e.g., drug-likeness in molecular generation, function approximation with arithmetic expressions). However, existing methods lack robustness as they may decide to explore areas of the latent space for which no data was available during training and where the decoder can be unreliable, leading to the generation of unrealistic or invalid objects. We propose to leverage the epistemic uncertainty of the decoder to guide the optimization process. This is not trivial though, as a naive estimation of uncertainty in the high-dimensional and structured settings we consider would result in high estimator variance. To solve this problem, we introduce an importance sampling-based estimator that provides more robust estimates of epistemic uncertainty. Our uncertainty-guided optimization approach does not require modifications of the model architecture nor the training process. It produces samples with a better trade-off between black-box objective and validity of the generated samples, sometimes improving both simultaneously. We illustrate these advantages across several experimental settings in digit generation, arithmetic expression approximation and molecule generation for drug design.

1 Introduction

We consider the task of optimizing an expensive black-box objective function taking inputs in a *high-dimensional discrete* space. This could be for example finding new molecules for drug design, or automatically generating a computer program that matches a desired output. Solving this task directly in the original space (e.g., with discrete local search methods such as genetic algorithms) may be challenging given the complex structure and high dimensionality of the data. Recently, Variational autoencoders (VAEs) [1, 2] have been successfully leveraged to model a wide range of discrete data modalities — from natural language [3], to arithmetic expressions [4], computer programs [5] or molecules [6]. By learning a lower-dimensional continuous representation of objects in their latent space, VAEs allow to transform the original discrete optimization problem into a simpler *continuous* optimization one in latent space. For example, this can be achieved via Bayesian Optimization in the latent space, or via gradient ascent with a jointly-trained neural network predicting the black box property from the latent space representation [6, 7]. Initial methods in this area have suffered from the fact that the search in latent space may explore areas for which no data was available at train time, and therefore where the decoder network of the VAE will be unreliable [8]: seemingly good candidate points in latent space may be decoded into objects that are invalid, unrealistic or low quality.

While several methods have been introduced to promote validity of decoded objects (§2.1), they either focus on modifying the generative model learning procedure or adapting the decoder architecture to satisfy the syntactic requirements of the data modality of interest. We propose instead to quantify

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: **Uncertainty-guided optimization in VAE latent space** The goal of black-box optimization in latent space is to attain regions with high values of the back-box objective after decoding, while avoiding the regions that lead to invalid decodings (left). Standard Bayesian Optimization in latent space may query these suboptimal areas (e.g., regions on left hand side, center). High decoder uncertainty regions overlap with regions leading to invalid decodings (right), so that censoring high uncertainty points helps guiding the optimization towards the most promising latent points.

and leverage the uncertainty of the decoder network to guide the optimization process in latent space (Fig. 1). This approach does not require any change to the model training nor architecture, and can easily be integrated within several optimization frameworks. It results in a better trade-off between the values of the black-box objective and the validity of the newly generated objects, sometimes improving both simultaneously.

To be effective, this method requires robust estimates of model uncertainty for high dimensional structured data. Existing methods for uncertainty estimation in this domain often rely on heuristics or make independence assumptions to make computations tractable (§2.2). We demonstrate that such assumptions are not appropriate in our setting, and propose new methods for uncertainty estimation in high dimensional structured data instead.

Our contributions are as follows:

- We introduce an algorithm to quantify the uncertainty of high-dimensional discrete data, and use it to estimate the uncertainty of the decoder (§3);

- We show how the uncertainty of the decoder can be incorporated across several optimization frameworks, including gradient ascent and Bayesian optimization (§4);

- We illustrate our approach in a digit generation setting — a simple setup to provide intuition for the method — then quantify its benefits in the more complex tasks of arithmetic expressions approximation and molecule generation, covering a diverse set of decoder architectures across experiments (Convolutional, Recurrent and Graph Neural Networks) (§5).

2   Background

2.1   Optimization of high-dimensional discrete objects with generative models

Focusing on molecular generation, Gómez-Bombarelli et al. [6] propose to train a VAE to learn a distribution over the so-called SMILES representation of molecules (ie. linear sequences of characters) [9], and subsequently perform the optimization in the latent space. Since the SMILES representation follows strict syntactic requirements that are not explicitly enforced by the generative model, promising points in latent space may be decoded into invalid molecules. To improve the validity of decoded sequences, Kusner et al. [4] and Dai et al. [5] develop task-specific grammar rules into the VAE decoder, focusing on use cases in molecular and computer program generation. However, crafting the corresponding rules requires domain-specific knowledge, needs to be designed from scratch for each new task, and may not be straightforward to elicit in the first place (e.g., digit generation example in 5.1). Liu et al. [10] propose instead to formulate the problem as a

chance-constrained optimization task to simultaneously optimize the target property as well as the probability to generate valid sequences. A different line of research has focused on representing high-dimensional structured objects as graphs instead [11, 12]. The Junction Tree VAE (JT-VAE) [13] generates systematically valid molecular graphs, by first generating a tree-structured scaffold over a finite set of molecular clusters, and then assembling these clusters back into molecules with a message passing network. The MolDQN [14] casts the optimization problem as a reinforcement learning task (double Q-learning), which allows in turn to more naturally extend to simultaneous optimization of different objectives. GraphAF [15] combines the strengths of autoregressive and flow-based approaches to efficiently generate realistic and valid molecular graphs. Lastly, Tripp et al. [16] show that the black-box optimization performance can be further enhanced by iteratively retraining the generative model on the data points selected during optimization, with weights that directly depend on their objective function value.

Our approach deviates from all the above in that it is is representation-agnostic (works with sequences or graphs), does not change the model architecture nor the learning procedure and can be combined with several of these approaches to reach even stronger optimization performance.

2.2 Quantifying model uncertainty

Adopting a Bayesian viewpoint, the overall uncertainty of a model in a given region of the input space can be broken down into two types of uncertainty [17]:

- **Epistemic uncertainty:** Uncertainty due to lack of knowledge about that particular region of the input space — the posterior predictive distribution is broad in that region due to lack of information that can be reduced by collecting more data;

- **Aleatoric uncertainty:** Uncertainty due to inherent stochasticity/noise in the observations in that region — collecting additional data would not further reduce that uncertainty.

We denote input points as x, outputs as y and the training data as $\mathcal{D}$. The total uncertainty $\mathcal{U}$ of a model at an input point x is typically measured by the predictive entropy, ie. the entropy of the predictive posterior distribution $P(y|x, \mathcal{D})$:

$$\mathcal{U}(x) = \mathcal{H}(P(y|x, \mathcal{D})) = \sum_y -P(y|x, \mathcal{D}) \log P(y|x, \mathcal{D}) dy. \tag{1}$$

Denoting $P(\theta|\mathcal{D})$ the posterior distribution over model parameters θ, we can further decompose the predictive entropy $\mathcal{U}$ as the sum of two terms:

$$\mathcal{U}(x) = \underbrace{(\mathcal{H}(P(y|x, \mathcal{D})) - \mathbb{E}_{P(\theta|\mathcal{D})}(\mathcal{H}(P(y|x, \theta))))}_{\text{Mutual Information } \mathcal{M}} + \underbrace{\mathbb{E}_{P(\theta|\mathcal{D})}(\mathcal{H}(P(y|x, \theta)))}_{\text{Expected entropy E}} \tag{2}$$

The first term — the Mutual Information $\mathcal{M}$ between model parameters θ and the prediction y — is a measure of epistemic uncertainty, as it quantifies the magnitude of the change in model parameters that would result from observing y. If the model is uncertain about its prediction for y, the change in model coefficients from observing y should be high. Conversely, if the model is confident about its prediction for y, model parameters will not vary from observing y:

$$\mathcal{M}(x) = \mathcal{H}(P(y|x, \mathcal{D})) - \mathbb{E}_{P(\theta|\mathcal{D})}(\mathcal{H}(P(y|x, \theta))). \tag{3}$$

The second term — the Expected Entropy $\mathcal{E}$ — is a measure of the residual uncertainty, ie. the aleatoric uncertainty:

$$\mathcal{E}(x) = \mathbb{E}_{P(\theta|\mathcal{D})}(\mathcal{H}(P(y|x, \theta))). \tag{4}$$

In high dimensional settings, an exact estimation of these different quantities is not tractable, therefore, several approximations and heuristics have been introduced. The softmax variance, i.e. the variance of predictions across model parameters, has been shown to approximate epistemic uncertainty well in certain settings [18–20].

In the context of sequential data, the inherent structure in the data generating process often introduces strong dependencies between the output dimensions, e.g., the tokens in a generated sentence. In cases where there exist weak correlations between tokens, quantifying the different types of uncertainties above can be made tractable by ignoring these dependencies [21], in which case the predictive

entropy for a sequence $y = (y_1, y_2, ..., y_L)$ may be approximated as the sum of token-level predictive entropies over the L tokens:

$$\mathcal{U}(x) = \sum_{l=1}^{L} \mathbb{E}_{P(y|x,\mathcal{D})}[\log P(y_l|x, y_{k<l}, \mathcal{D})] \approx \sum_{l=1}^{L} \mathbb{E}_{P(y_l|x,y_{k<l},\mathcal{D})}[\log P(y_l|x, y_{k<l}, \mathcal{D})]. \quad (5)$$

Unlike the standard expectation definition which integrates over all y, here only y_l is integrated over, and we condition on $y_{k<l}$, which are obtained from a sample from $P(y|x, \mathcal{D})$. The process is repeated for several of these samples and an average is finally computed to reduce variance.

While the above has been shown to work well in certain experiments [21], valuable information is being discarded when we ignore dependencies across tokens. These dependencies are likely to be informative in applications such as the ones considered in §5.3.1. Alternative approaches have been suggested which make use of domain-specific metrics in Natural Language Processing such as the BLEU score [22], but these are difficult to extend to other domains. Lastly, a naive Monte Carlo estimation is expected to perform poorly in high dimensions since the majority of samples will be in regions with negligible contribution to the sum (Appendix A).

3 Importance sampling estimator

We consider discrete output points y that belong to a high-dimensional structured object space $\mathcal{S}$ (e.g., long sequences, large graphs), of cardinality $|\mathcal{S}|$. An exact estimation of the Mutual Information between outcomes y and model parameters θ (equation 3) is impractical because the expectation involves a sum over exponentially many possible outcomes for $y \in \mathcal{S}$.

In lieu of the heuristics previously discussed, we obtain a principled approximation to the Mutual Information via Monte Carlo estimation using *importance sampling*, with an adequately chosen importance distribution.

We denote $q(\theta) \approx P(\theta|\mathcal{D})$ the learnt approximation to the posterior, and assume we can approximate expectations over model parameters by sampling M independent samples from $q(\theta)$. We can then re-write the Mutual Information $\mathcal{M}$ in equation 3 as follows:

$$\mathcal{M}(x) \approx \left[-\sum_{s=1}^{|\mathcal{S}|} p_s \log p_s \right] + \left[\frac{1}{M} \sum_{m=1}^{M} \sum_{s=1}^{|\mathcal{S}|} p_{s,m} \log p_{s,m} \right] \quad (6a)$$

$$= \sum_{s=1}^{|\mathcal{S}|} (\underbrace{\left[\frac{1}{M} \sum_{m=1}^{M} (p_{s,m} \log p_{s,m}) - p_s \log p_s \right]}_{h(y_s)}. \quad (6b)$$

where p_s and $p_{s,m}$ are shorthands, respectively, for $P(y = y_s|x, \mathcal{D})$ — the posterior predictive distribution — and $P(y = y_s|x, \theta = \theta_m)$ — the probability of a given output $y_s \in \mathcal{S}$ given x and a sample θ_m from the approximate posterior distribution over model parameters $q(\theta)$.

We can then obtain a tractable approximation to equation 6b via importance sampling:

$$\mathcal{M}(x) = \sum_{s=1}^{|\mathcal{S}|} h(y_s) \cdot \frac{1}{\bar{p}(y_s)} \cdot \bar{p}(y_s) = \mathbb{E}_{\bar{p}}\left[h(y) \cdot \frac{1}{\bar{p}(y)} \right] \approx \frac{1}{N} \sum_{s=1}^{N} \left[h(\tilde{y}_s) \cdot \frac{1}{\bar{p}(\tilde{y}_s)} \right] \quad (7)$$

with $\tilde{y}_s \sim \bar{p}(.)$, where $\bar{p}$ is the importance distribution.

We choose the importance distribution to be the approximate posterior predictive defined over the outputs. We generate an outcome $\tilde{y}_s$ by first sampling a set of parameters $\tilde{\theta}_0$ from the approximate posterior, and then generating $\tilde{y}_s$ from a model defined by that set of parameters $\tilde{\theta}_0$. This distribution will sample mostly from regions in $\mathcal{S}$ with high probability under the true posterior predictive for input x. This is in contrast to a naive sum over all possible outcomes y, many of which will have a

145 negligible contribution to the sum. This gives rise to an estimator of Mutual information (obtained
146 with Algorithm 1) with lower variance than its naive Monte Carlo counterpart (see Appendix A).

Algorithm 1: Importance sampling estimator of MI

for $s = 1$ **to** N **do**
    Sample $\tilde{\theta}_0 \sim q(\theta)$; $\tilde{y}_s \sim P(y|x, \theta = \tilde{\theta}_0)$;
    for $m = 1$ **to** M **do**
        Sample $\tilde{\theta}_m \sim q(\theta)$; Compute $p_{s,m} = P(y = \tilde{y}_s|z, \theta = \tilde{\theta}_m)$;
    end for
    Compute $p_s = \frac{1}{M}\sum_{m=1}^{M} p_{s,m}$; $h_s = \frac{1}{M}\sum_{m=1}^{M}(p_{s,m}\log p_{s,m}) - p_s \log p_s$;
end for
Return $\mathcal{M}(x) = \frac{1}{N}\sum_{s=1}^{N}\left[h_s \cdot \frac{1}{p_s}\right]$

---

4 Uncertainty-guided optimization in VAE latent space

149 **Black box optimization in VAE latent space.** We want to optimize the black-box objective $\mathcal{O}$ over
150 a high dimensional discrete object space $\mathcal{S}$. We train a VAE, with encoder g and decoder f, to
151 learn a continuous lower-dimensional embedding of objects in $\mathcal{S}$. The optimization of $\mathcal{O}$ is then
152 performed in latent space and the best candidates are subsequently decoded into the original space.
153 As discussed in § 2.1, this may lead to invalid or unrealistic decodings when the decoder f operates in
154 regions different from the ones seen during training. We propose to detect this regime by quantifying
155 the epistemic uncertainty of the decoder: avoiding regions with high epistemic uncertainty for the
156 decoder will make the overall optimization process more efficient by avoiding invalid decodings. We
157 next cover two optimization approaches commonly used in latent space optimization settings and
158 discuss how we can leverage the uncertainty of the decoder to guide the optimization process.

159 **Bayesian Optimization with an uncertainty-aware surrogate model or uncertainty censoring.**
160 We first train a surrogate model, e.g., a Gaussian Process [23], to predict $\mathcal{O}(x)$ based on its latent
161 representation z. We then perform Bayesian Optimization using an appropriate acquisition function
162 (e.g., Upper Confidence Bound or Expected Improvement heuristic). There are two main ways to
163 incorporate the decoder uncertainty to guide this process. The first approach consists in training
164 the surrogate model on an objective that penalizes points with high uncertainty (e.g., optimizing
165 $\mathcal{O}(x) - \alpha \cdot \mathcal{M}(z)$). Another method is to censor proposal points z that would have a Mututal
166 Information $\mathcal{M}(z)$ above a predefined uncertainty threshold $\mathcal{T}$ (e.g., highest value observed on the
167 training data) at each step of a batch Bayesian Optimization process.

168 **Uncertainty-constrained gradient ascent.** A common architecture design when performing black-
169 box optimization in latent space is to jointly train the VAE with an auxiliary network h (Fig.D.1) that
170 predicts the value of the black box objective $\mathcal{O}(x)$ from the encoding z of x in latent space [6, 7, 13].
171 This construct is particularly useful in constrained optimization settings in which we want to perform
172 a local search in latent space to maximize $\mathcal{O}$ while remaining close to a known input object. The
173 joint training consists of optimizing the sum of the VAE loss (i.e., the ELBO) and the loss from
174 the black-box objective prediction (e.g., MSE loss for a continuous output $\mathcal{O}$) via gradient descent,
175 backpropagating gradients through the entire architecture. To optimize objects under this framework,
176 we start from a set of initial points in latent space z — either a random sample of latent points, or a
177 subset of points x that we encode in the latent space ($z = g(x)$). We then compute the gradient $\nabla_z h$
178 of the auxiliary network with respect to z and perform gradient ascent $z \leftarrow z + \alpha \cdot \nabla_z h$. We repeat
179 this process a few times until satisfying a stopping criteria (e.g., threshold on predicted values $h(z)$
180 or after a fixed number of gradient updates). Finally, we decode the latest latent positions to obtain
181 the set of candidates $\tilde{x} = f(z)$ and measure their actual properties $\mathcal{O}(\tilde{x})$. We can further improve the
182 quality of the candidate set by censoring the moves in latent during gradient ascent that would result
183 in a value of uncertainty above a predefined threshold $\mathcal{T}$.

5 Experimental results

185 After describing the common experimental setting across applications, we demonstrate the effective-
186 ness of using the uncertainty of the decoder to guide the optimization for constrained digit generation.
187 Our objective is to illustrate the concepts introduced above in a simple and intuitive example. We then

move on to quantify the benefits of our approach in the more complex cases of arithmetic expression approximation and molecular generation for drug design.

Uncertainty estimators and baselines Across all experiments, we quantify the Mutual Information between outputs and decoder parameters with both the Importance sampling estimator (IS-MI) described in §3 and based on the token independence approximation (TI-MI) described in §2.2. When computing the IS-MI estimator, sampling from model parameters is achieved via Monte Carlo dropout [24]. We compare optimization results with two baselines: the standard approach that fully ignores decoder uncertainty, and an approach in which we censor proposal points with low probability under the prior distribution (standard normal) of the VAEs in latent space (referred to as 'NLLP').

Optimization We perform uncertainty-guided optimization in latent space as per the two approaches described in §4. For Bayesian Optimization, we train a single task Gaussian Process as our surrogate model based on a random subset of training points embedded in latent space and their corresponding black-box objective values. We then perform several iterations of batch Bayesian Optimization using the Expected Improvement heuristic as our acquisition function. At each iteration we select a batch of 20 latent vectors by sequentially maximizing the acquisition function. We select the point with the highest predicted target value for which the decoder uncertainty is below a predefined threshold (e.g., 99^{th} percentile of decoder uncertainty values observed on the training set) or the one with lowest uncertainty if no point in the batch is below the threshold. We re-train the surrogate model with the newly generated point at each step. For gradient ascent, we randomly sample points from the training set, embed them in latent space, and use these as our starting positions. We then compute the gradient of the auxiliary property network with respect to latent positions and accept proposal moves along these directions if the decoder uncertainty at the corresponding position in latent is below a predefined threshold (e.g., 99^{th} percentile of decoder uncertainty on the training set). All optimization experiments are carried out 10 times independently with different random seeds. Hyperparameter values across experiments are detailed in Appendix B-E.

5.1 Illustrative example in digit generation

Setup In this first setting, our objective is to generate *valid* images of the digit 3 that are as *thick* as possible. We train a VAE model generating images of the digit 3 jointly with an auxiliary network predicting their thickness. We use a 'Conv-Deconv'[25] architecture for the VAE and a 3-layer feedforward network for property prediction. The underlying data consist of grayscale images of the digit 3 extracted from the MNIST dataset [26] that we discretize to form tensors of binary values. We use the sum of pixel intensities across a given image as a proxy for the thickness of the corresponding digit. An unconstrained optimization in the latent space would ultimately lead to the generation of *invalid* white 'blobs'. To avoid this failure mode and promote validity of the resulting candidate set, we leverage the uncertainty of the decoder network. In order to assess the validity of objects, we independently train a deep Convolutional Neural Network to classify images of the digit 3 (binary classification).

Results Latent points with high decoder uncertainty lead to a higher rate of invalid decoded digits (Appendix B.3), which help avoid the aforementioned failure mode during optimization. For both Bayesian Optimization and gradient ascent, we observe that the decoder uncertainty constraints help ensuring the generated digits remain valid, while preserving the ability of the optimization algorithm to increase the thickness (Fig.2).

5.2 Arithmetic expressions approximation

Setup We follow an experimental design similar to Kusner et al. [4], in which we seek to optimize univariate arithmetic expressions generated by a formal grammar (rules and examples are provided in Appendix C). The objective is to find an expression that minimizes the mean squared error (MSE) with respect to a predefined target expression ($1/3 * x * sin(x * x)$). More specifically, since the presence of exponentials in expressions may results in very large MSE values, the black-box objective is defined as $-log(1 + MSE)$. We train a 'Character VAE' (CVAE) [4] on $80,000$ expressions generated by the formal grammar, then perform optimization in the latent space.

Results We observe that methods leveraging the decoder uncertainty result in almost always valid decodings, and reach higher average values of the black box objective for valid decoded expressions compared to baselines (Fig. 3; gradient ascent results in Appendix C.4). In particular, censoring candidate points based on their probability under the standard normal prior does not help promoting

Starting points

Gradient ascent with no uncertainty

Gradient ascent with decoder uncertainty

Bayesian Optimization with no uncertainty

Bayesian Optimization with decoder uncertainty

Figure 2: **Top 5 decoded digits after optimization** Leveraging decoder uncertainty helps preventing the generation of invalid digits.

Method	Top 10 avg. ↑	Validity (%) ↑
No uncertainty	-0.96 ± 0.04	$77\% \pm 0.6\%$
NLLP	-0.97 ± 0.05	$76\% \pm 0.8\%$
TI-MI	-0.72 ± 0.06	$96\% \pm 0.5\%$
IS-MI	**-0.70 $\pm$ 0.04**	**98% $\pm$ 0.5%**

Figure 3: **Arithmetic expressions approximation results** Mutual Information-based constraints during Bayesian optimization in latent space help promoting higher validity % of decodings while increasing black-box objective values. Uncertainty threshold values used for censoring candidate points are based on decoder uncertainty values observed on the training data (95^{th} percentile).

validity of decodings at all. In this setting with relatively short sequences (arithmetic expressions have at most 19 characters), leveraging the TI-MI or IS-MI estimators leads to comparable performance.

5.3 Molecule generation for drug discovery

Molecular generation for drug design seeks to identify new molecules satisfying desired chemical properties. Molecules are typically either represented as sequences of characters, using their SMILES representation [9], or as graphs of atoms [11]. We demonstrate the effectiveness of the approach described in § 4 for these two different representations: experiments with the 'Character VAE' (CVAE) for molecules [6] leverage the SMILES representation, while experiments with the JT-VAE [13] are based on a graph representation of molecules. For both architectures, we trained our models on a set of 250k drug-like molecules from the ZINC dataset [27].

5.3.1 Character VAE (CVAE)

Setup We jointly train a CVAE model, which learns to encode and decode molecules SMILES strings, along with an auxiliary property network that predicts a target property of these molecules. Following prior work [4, 5, 13], we define the black-box objective as the octanol-water partition coefficient penalized by the synthetic accessibility score and the number of long cycles, (Appendix D.1) and we refer to it as 'Penalized logP' for brevity. Since the SMILES representation of molecules follows a strict syntax that determines whether a given expression is valid or not, we are interested in generating molecules that simultaneously maximize the target property and represent valid SMILES expressions.

Results We first verify that our estimator is able to discriminate points in-distribution (low uncertainty) vs out-of-distribution (high uncertainty). We consider 4 distinct sets of points in latent: embeddings into latent space of a random sample from the train and test sets, random samples from the VAE prior (standard normal) and random samples "far from the prior" (we sample from an isotropic gaussian with standard deviation equal to 10). As can be seen on Fig.5a, uncertainty estimates for the first 3 sets strongly overlap while being disjoint from the estimates corresponding to points far from the prior. Furthermore, we observe a strong correlation between low decoder uncertainty and regions that lead to valid SMILES decodings (Fig. 4). This is corroborated by the analysis described in Fig. 5c: when considering latent points "far from the prior", points for which the decoder uncertainty is lower than a predefined threshold (e.g., maximum value observed on training data) will lead to a significantly higher proportion of valid decoded molecules compared to latent points with uncertainty above the threshold. This is critical as it allows to censor points that will likely lead to invalid decodings, even when we move *far from the prior* in latent space.

For the Bayesian Optimization experiments, we investigate the impact of different bounds on the space we optimize within, as well as different uncertainty thresholds. As we increase the bounds, we typically reach higher optima, at the cost of a higher fraction of invalid decodings during search. We

Figure 4: **CVAE latent space visualization.** We apply Principal Component Analysis on the embedding of the full training data and keep the first 2 components. We then create a grid on the resulting 2D-space and measure the penalized logP (a), decoder uncertainty (b) and the proportion of valid decodings in that region (c) (a c averaged over 300 decodings; b measured via IS by sampling 100 times from the importance distribution, and averaging over 100 samples of model parameters.; for a, white squares correspond to regions where none of the 300 decodings was valid). We observe a strong overlap between decoder uncertainty (b) and validity of decodings (c).

Figure 5: **Uncertainty estimator.** a) Distribution of decoder uncertainty values (IS-MI) for 1k samples for 4 distinct sets (train test set samples embedded in latent space; samples from the prior; samples far from the prior). b) Valid decodings (%) as a function of the proportion of samples kept based on their uncertainty — eliminating points with high uncertainty first (dataset comprised of 50% samples from test set & 50% of samples far from the prior). The IS-MI estimator has superior ability to identify points leading to invalid decodings. c) Valid decodings (%) for samples from a normal distribution with increasing standard deviation. Samples with decoder uncertainty below a predefined threshold (maximum IS-MI value observed on training data) have a much higher rate of valid decodings. Points above the threshold are very likely to lead to invalid decodings.

obtain higher validity % and penalized logP values when leveraging the decoder uncertainty (Table 1). In this setting, the token-level independence assumption (TI-MI) leads to poor performance compared to the importance sampling-based estimator (IS-MI). Results are also robust to the choice of decoder uncertainty thresholds (D.4).

5.3.2 Junction Tree VAE (JT-VAE)

Setup We train a junction tree VAE model (JT-VAE) [13] using the same dataset of 250k molecules (ZINC) and black-box objective (penalized logP) as for the CVAE experiments. All molecules generated by the JT-VAE are valid by design. Our objective is to demonstrate we can generate molecules of comparable penalized logP values but with higher *quality* by factoring in the decoder uncertainty during the optimization in latent space. To that end, we use the quality filters proposed by Brown et al. [28] which aim at ruling out "compounds which are potentially unstable, reactive, laborious to synthesize, or simply unpleasant to the eye of medicinal chemists." Using notations from § 3, sampling a new object $\tilde{y}_s$ is achieved by successively decoding from the junction tree decoder and then the graph decoder. We decompose $\log p_{s,m}$ as the sum of the log probabilities corresponding to each prediction made by the junction tree decoder and graph decoder (for the graph outcome generated in the previous step), namely the topology and node predictions in the junction

Table 1: **CVAE - Bayesian Optimization results.** Censoring proposal points with high decoder uncertainty values with the IS-MI estimator helps increase validity across experiments. As we increase the bounds on the Bayesian Optimization search space, validity % generally decreases but remains 5-10x higher when leveraging IS-MI compared to baselines. This is critical as is helps uncover molecules with very high penalized logP values.

Search bounds	Decoder uncertainty	Penalized logP		Validity (%) ↑
		Top 1 ↑	Avg. top 10 ↑	
5	None	4.0 ± 0.2	2.5 ± 0.2	$22\% \pm 1.4\%$
	NLLP	4.2 ± 0.2	2.7 ± 0.1	$30\% \pm 1.3\%$
	TI-MI	4.1 ± 0.3	2.3 ± 0.1	$21\% \pm 0.8\%$
	IS-MI	$\mathbf{4.5 \pm 0.2}$	$\mathbf{3.0 \pm 0.1}$	$\mathbf{33\% \pm 1.8\%}$
10	None	3.9 ± 1.2	-2.3 ± 2.8	$1\% \pm 0.4\%$
	NLLP	2.9 ± 0.8	0.5 ± 0.8	$3\% \pm 0.7\%$
	TI-MI	5.9 ± 3.6	1.1 ± 1.5	$2\% \pm 0.4\%$
	IS-MI	$\mathbf{6.6 \pm 0.6}$	$\mathbf{1.6 \pm 0.8}$	$\mathbf{11\% \pm 0.8\%}$
15	None	10.3 ± 4.3	5.0 ± 2.6	$1\% \pm 0.3\%$
	NLLP	3.9 ± 2.5	0.8 ± 1.2	$1\% \pm 0.3\%$
	TI-MI	6.7 ± 3.8	6.4 ± 3.9	$1\% \pm 0.3\%$
	IS-MI	$\mathbf{27.6 \pm 2.2}$	$\mathbf{9.9 \pm 1.3}$	$\mathbf{5\% \pm 0.7\%}$

Table 2: **JT-VAE - Gradient ascent results.** We perform gradient ascent with 10 consecutive updates, following the gradient of the property network with respect to latent positions. We observe only slightly higher penalized logP values when leveraging decoder uncertainty (IS-MI) compared to the two baselines, but we generate molecules of better *quality*[28] on average.

Decoder uncertainty	Penalized logP		Quality (%) ↑
	Top 1 ↑	Avg. top 10 ↑	
None	4.2 ± 0.1	$\mathbf{3.3 \pm 0.1}$	0.73 ± 0.03
NLLP	2.3 ± 0.2	1.0 ± 0.2	0.70 ± 0.04
IS-MI	$\mathbf{4.4 \pm 0.1}$	$\mathbf{3.3 \pm 0.05}$	$\mathbf{0.83 \pm 0.03}$

tree decoder, and the subgraph prediction in the graph decoder. We replicate the analysis described in 5.3.1 with the 4 distinct datasets in latent space (i.e., train, test, prior and far from prior) and observe similar results: the histogram of decoder uncertainty values for points "far from the prior" is disjoint from the other three histograms (Appendix E.3), confirming the ability of the estimator to identify out-of-distribution points.

Results We replicate the uncertainty-guided gradient ascent and Bayesian Optimization introduced earlier. Leveraging decoder uncertainty leads to the generation of higher *quality* molecules (i.e., a larger proportion pass the quality filters from Brown et al. [28]) in both experiments (Table 2 and Appendix E.4). Guiding the optimization in latent with the likelihood under the prior (NLLP), with the intention to generate higher quality molecules resembling the training data, is detrimental to optimization performance.

6   Conclusion

Black-box optimization in the latent space of VAEs can be substantially enhanced by leveraging the uncertainty of the decoder to avoid regions that will eventually lead to an invalid or low-quality decodings. This is even more critical when one has to explore regions that are far away from the VAE prior to uncover optimal objects. As a future research direction, leveraging the uncertainty of the property network jointly with constraints on the decoder uncertainty may make the search in latent even more robust to invalid decodings. Lastly, the importance sampling-based estimator introduced in this work is general-purpose and may be relevant to other applications that would benefit from reliable epistemic uncertainty estimates for complex high-dimensional data (e.g., active learning or anomaly detection).

References

[1] Diederik P Kingma and Max Welling. Auto-encoding variational bayes, 2014.

[2] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models, 2014.

[3] Samuel R. Bowman, Luke Vilnis, Oriol Vinyals, Andrew M. Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space, 2016.

[4] Matt J. Kusner, Brooks Paige, and José Miguel Hernández-Lobato. Grammar variational autoencoder, 2017.

[5] Hanjun Dai, Yingtao Tian, Bo Dai, Steven Skiena, and Le Song. Syntax-directed variational autoencoder for structured data, 2018.

[6] Rafael Gómez-Bombarelli, Jennifer N. Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D. Hirzel, Ryan P. Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS Central Science*, 4(2):268–276, Jan 2018. ISSN 2374-7951. doi: 10.1021/acscentsci.7b00572. URL http://dx.doi.org/10.1021/acscentsci.7b00572.

[7] John Bradshaw, Brooks Paige, Matt J. Kusner, Marwin H. S. Segler, and José Miguel Hernández-Lobato. A model to search for synthesizable molecules, 2019.

[8] David Janz, Jos van der Westhuizen, and José Miguel Hernández-Lobato. Actively learning what makes a discrete sequence valid, 2017.

[9] David Weininger. Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. *J Chem Inf Comput Sci*, 28(1):31–36, 1988. doi: 10.1021/ci00057a005. URL http://dx.doi.org/10.1021/ci00057a005.

[10] Xianggen Liu, Sen Song, Qiang Liu, and Jian Peng. A chance-constrained generative framework for sequence optimization, 2020.

[11] David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P. Adams. Convolutional networks on graphs for learning molecular fingerprints, 2015.

[12] Yujia Li, Oriol Vinyals, Chris Dyer, Razvan Pascanu, and Peter Battaglia. Learning deep generative models of graphs, 2018.

[13] Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Junction tree variational autoencoder for molecular graph generation, 2019.

[14] Zhenpeng Zhou, Steven Kearnes, Li Li, Richard N. Zare, and Patrick Riley. Optimization of molecules via deep reinforcement learning. *Scientific Reports*, 9(1), Jul 2019. ISSN 2045-2322. doi: 10.1038/s41598-019-47148-x. URL http://dx.doi.org/10.1038/s41598-019-47148-x.

[15] Chence Shi, Minkai Xu, Zhaocheng Zhu, Weinan Zhang, Ming Zhang, and Jian Tang. Graphaf: a flow-based autoregressive model for molecular graph generation, 2020.

[16] Austin Tripp, Erik Daxberger, and José Miguel Hernández-Lobato. Sample-efficient optimization in the latent space of deep generative models via weighted retraining, 2020.

[17] Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision?, 2017.

[18] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks, 2016.

[19] Reuben Feinman, Ryan R. Curtin, Saurabh Shintre, and Andrew B. Gardner. Detecting adversarial samples from artifacts, 2017.

[20] Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection, 2018.

[21] Andrey Malinin and Mark Gales. Uncertainty in structured prediction, 2020.

[22] Tim Xiao, Aidan Gomez, and Yarin Gal. Wat heb je gezegd? detecting out-of-distribution translations with variational transformers. *Bayesian Deep Learning Workshop at NIPS 2019*, 2019.

[23] Andrew Mchutchon and Carl Rasmussen. Gaussian process training with input noise. In J. Shawe-Taylor, R. Zemel, P. Bartlett, F. Pereira, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 24. Curran Associates, Inc., 2011. URL `https://proceedings.neurips.cc/paper/2011/file/a8e864d04c95572d1aece099af852d0a-Paper.pdf`.

[24] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning, 2016.

[25] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. Beta-VAE: Learning basic visual concepts with a constrained variational framework. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings*, 2017. ISSN 1078-0874.

[26] Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[27] J. J. Irwin, T. Sterling, Michael M. Mysinger, Erin S. Bolstad, and R. Coleman. Zinc: A free tool to discover chemistry for biology. *Journal of Chemical Information and Modeling*, 52:1757 – 1768, 2012.

[28] Nathan Brown, Marco Fiscato, Marwin H.S. Segler, and Alain C. Vaucher. Guacamol: Benchmarking models for de novo molecular design. *Journal of Chemical Information and Modeling*, 59(3):1096–1108, Mar 2019. ISSN 1549-960X. doi: 10.1021/acs.jcim.8b00839. URL `http://dx.doi.org/10.1021/acs.jcim.8b00839`.

[29] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017.

[30] Kyunghyun Cho, Bart van Merrienboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches, 2014.

[31] Maximilian Balandat, Brian Karrer, Daniel R. Jiang, Samuel Daulton, Benjamin Letham, Andrew Gordon Wilson, and Eytan Bakshy. BoTorch: A Framework for Efficient Monte-Carlo Bayesian Optimization. In *Advances in Neural Information Processing Systems 33*, 2020. URL `http://arxiv.org/abs/1910.06403`.