LANGUAGE MODELS CAN DO ZERO-SHOT VISUAL REFERRING EXPRESSION COMPREHENSION

ABSTRACT

The use of visual referring expressions is an important aspect of human-robot interactions. Comprehending referring expressions (ReC) like "the brown cookie near the cup" requires to understand both self-referential expressions, "brown cookie", and relational referential expressions, "near the cup". Large pretrained Vision-Language models like CLIP excel at handling self-referential expressions, while struggle with the latter. In this work, we reframe ReC as a language reasoning task and explore whether it can be addressed using large pretrained language models (LLMs), including Bing Chat and ChatGPT. Given the textual attribute tuples {object category, color, center location, size}, ChatGPT performs unstably on understanding spatial relationships even with heavy prompt engineering, while Bing Chat shows strong and stable zero-shot relation reasoning. Evaluation on RefCOCO/g datasets and scenarios of interactive robot grasping shows that LLMs can do ReC with decent performance. It suggests a vast potential of using LLMs to enhance the reasoning in vision tasks.

1 INTRODUCTION

Visual referring expressions comprehension (ReC) Yu et al. (2016); Shridhar et al. (2020); Deng et al. (2021), a sub-task of visual grounding, is important for human-robot interaction. It aims to localize an object in a visual scene given a referring expression like "the brown cookie near the cup". ReC involves grounding both self-referential expressions ("the brown cookie") and relational referential expressions ("near of the cup"). It has long been formulated as a visual-language reasoning task, approached with models integrating visual and language encoders, trained on a large amount of annotated bounding boxes and paired expressions (Yu et al., 2018; Deng et al., 2021).

Large pretrained Vision-Language models like CLIP Radford et al. (2021) have shown strong zero-shot performance on various visual recognition tasks. Despite the advantages in grounding self-referring expressions, CLIP is largely incapable of performing spatial reasoning. ReCLIP (Subramanian et al., 2022) mitigates this weakness by adopting manually-designed spatial relationship heuristics. However, this rule-based system is brittle in real-world scenarios (See Figure 11 in the Appendix of (Subramanian et al., 2022) for failed examples). Is it possible to reframe ReC as a *pure language-reasoning* task, similar to humans playing blindfold chess using only language?

Large language models (LLMs) (Brown et al., 2020; Ouyang et al., 2022; Wei et al., 2022; Chowdhery et al., 2022; Touvron et al., 2023) have demonstrated strong zero-shot understanding and common-sense reasoning with text. Naturally, we could leverage the spatial relationship understanding of LLMs to do ReC without training. With this insight in mind, we propose to reformulate ReC as a language reasoning task, name as ChatRef. Different from the traditional paradigm that integrates visual perception with language reasoning, ChatRef decouples these two submodules, by passing the recognized objects in a scene as text to an LLM for ReC.

Given a visual scene, ChatRef first recognize the objects and their attributes, including category, location, and color, and then feed these textual descriptions and referring expressions to an LLM to locate the target object. Leveraging the power of LLMs, ChatRef offers two advantages: 1) human-like zero-shot generalization ability, i.e., working on novel visual scenes or referring expressions, without supervision. 2) implicit concept hierarchy, e.g., matching general concepts with specific ones ("tool" and "scissors"). The decent performance of ChatRef suggests a vast potential of using LLMs to enhance the reasoning in vision tasks.

Prompt: An image is (X, Y)=(640, 480). Object 1: {category: woman, center: (256, 264), size: (105, 270), color: yellow}. Object 2: {category: woman, center: (342, 288), size: (129, 330), color: pink}. Object 3: {category: woman, location: (596, 285), size: (89, 329), color: red}. Object 4: {category: woman, center: (111, 285), size: (95, 268), color: white}.

Q1: locate the yellow walker near the center.

Bing: The yellow walker near the center is object 1. It is a woman wearing a yellow dress and walking on the right side of the image. Her location is (256, 264) and her size is (105, 270).

Prompt: An image is (X, Y)=(500, 375). Object 1: {category: person, color: black, location: (80, 207), size: (160, 332)}. Object 2: {category: person, color: black, location: (277, 188), size: (102, 208)}.

Q1: Locate the person closest to the image viewer.

Bing: The person closest to the image viewer is object 1. It is a person wearing a black outfit and standing on the left side of the image. Their location is (80, 207) and their size is (160, 332). This is the person closest to the image viewer because their size is larger than the other person's size. This implies that they are closer to the camera that took the image.

Prompt: Background: An image is (X, Y)=(640, 512). Object 1: category: train, color: blue, center: (430, 241), size: (413, 474). Object 2: category: train, color: green, center: (291, 292), size: (473, 321).

Q1: locate the smallest train.

Bing: To locate the smallest train, you need to compare the sizes of the two objects. The size of an object is the product of its width and height. In this case, object 1 has a size of 413 x 474 = 195762 pixels, and object 2 has a size of 473 x 321 = 151833 pixels. Therefore, object 2 is the smallest train.

Prompt: Background: An image is (X, Y)=(600, 420). Object 1: {category: soda can, color: blue, center: (84, 228), size: (55, 121)}. Object 2: {category: soda can, color: blue, center: (164, 216), size: (59, 129)}. Object 3: {category: soda can, color: blue, center: (242, 206), size: (40, 113)}. Object 4: {category: phone, color: black, center: (267, 349), size: (56, 88)}.

Q1: locate the soda can behind the phone.

Bing: The soda can behind the phone is object 3. It has a center of (242, 206) and a size of (40, 113).

Q2: locate the blue soda can in the middle

Bing: The blue soda can in the middle is object 2. It has a center of (164, 216) and a size of (59, 129).

Figure 1: Examples from RefCOCO (columns 1 and 2), RefCOCOg (colume 3) and robot grasping scenes (column 3) on Bing Chat. It shows chain-of-thought reasoning with spatial common sense.

2 METHOD AND EXPERIMENTS

ChatRef consists the following steps: 1) Use an open-world detector RegionCLIP (Zhong et al., 2022), which does fine-grained region-text alignment for detection, to derive the category, center-location and size attributes of the objects in an image; 2) For each detected object, use a prompt-based categorical classification method to estimate the color attribute. We used a template containing 12 colors. 3) Feed the object attributes as text to ChatGPT[1] and Bing Chat[2] to evaluate the performance of LLMs for referring expression comprehension.

Datasets All our experiments on LLMs were done through manual input. Due to Bing Chat's daily limit of 100 chats, we were only able to evaluate on small datasets. We randomly sampled 40 images from the test set of RefCOCO (Kazemzadeh et al., 2014; Yu et al., 2016), and 40 from the validation set of RefCOCOg (Yu et al., 2016), respectively. We used two queries for each image. In addition, we evaluated on 10 real-world scenes of cluttered things on a table from INGRESS (Shridhar et al., 2020), with two queries for each image.

Results On the sampled 80 images and 160 queries from RefCOCO/g, Bing Chat achieved an accuracy of 75%, higher than the accuracy of ReCLIP (around 50%-60%)[3]. However, ChatGPT only achieved an accuracy of 23%, as it performs unstably, even under heavy prompt engineering.

Figure 1 shows a few typical examples using Bing Chat. Not just locating the target object, Bing Chat also provides the chain-of-thoughts, demonstrating that it has understanding of spatial relationships. In particular, the example in colume 3 is a failed case of ReCLIP. In contrast, Bing Chat is able to locate the target correctly through computing and comparing the object sizes.

Discussion We believe that there will be various visual-language applications that can leverage the power of LLMs to obtain reasoning abilities with hands down, in a similar way as ChatRef.

---

[1] https://chat.openai.com/chat

[2] https://www.bing.com/?FORM=UNKSBD

[3] This is not a strict comparison, as Bing Chat is only evaluated on a small sampled dataset.

URM STATEMENT

The first author and 3rd author acknowledge that they meet the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language Models are Few-Shot Learners. In *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL `https://papers.nips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html`.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. PaLM: Scaling Language Modeling with Pathways, October 2022. URL `http://arxiv.org/abs/2204.02311`. arXiv:2204.02311 [cs].

Jiajun Deng, Zhengyuan Yang, Tianlang Chen, Wengang Zhou, and Houqiang Li. TransVG: End-to-End Visual Grounding With Transformers. pp. 1769–1779, 2021. URL `https://openaccess.thecvf.com/content/ICCV2021/html/Deng_TransVG_End-to-End_Visual_Grounding_With_Transformers_ICCV_2021_paper.html`.

Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. Referitgame: Referring to objects in photographs of natural scenes. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 787–798, 2014.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Gray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. October 2022. URL `https://openreview.net/forum?id=TG8KACxEON`.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning Transferable Visual Models From Natural Language Supervision. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8748–8763. PMLR, 2021. URL `http://proceedings.mlr.press/v139/radford21a.html`.

Mohit Shridhar, Dixant Mittal, and David Hsu. INGRESS: Interactive visual grounding of referring expressions. *The International Journal of Robotics Research*, 39(2-3):217–232, 2020.

Sanjay Subramanian, William Merrill, Trevor Darrell, Matt Gardner, Sameer Singh, and Anna Rohrbach. ReCLIP: A Strong Zero-Shot Baseline for Referring Expression Comprehension. In *ACL*, 2022.

Hugo Touvron et al. LLaMA: Open and Efficient Foundation Language Models - Meta Research, 2023.

Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. Finetuned Language Models are Zero-Shot Learners. January 2022. URL https://openreview.net/forum?id=gEZrGCozdqR.

Licheng Yu, Patrick Poirson, Shan Yang, Alexander C Berg, and Tamara L Berg. Modeling context in referring expressions. In *European Conference on Computer Vision*, pp. 69–85. Springer, 2016.

Licheng Yu, Zhe Lin, Xiaohui Shen, Jimei Yang, Xin Lu, Mohit Bansal, and Tamara L. Berg. MAttNet: Modular Attention Network for Referring Expression Comprehension. pp. 1307–1315, 2018. URL https://openaccess.thecvf.com/content_cvpr_2018/html/Yu_MAttNet_Modular_Attention_CVPR_2018_paper.html.

Yiwu Zhong, Jianwei Yang, Pengchuan Zhang, Chunyuan Li, Noel Codella, Liunian Harold Li, Luowei Zhou, Xiyang Dai, Lu Yuan, Yin Li, and Jianfeng Gao. RegionCLIP: Region-Based Language-Image Pretraining. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16793–16803, June 2022.

A APPENDIX

A.1 EXPERIMENTS WITH CHATGPT

Prior to the experiments on Bing Chat, we evaluated how well ChatGPT does referential comprehension, on the sampled Refcoco/g data.

To instill more common sense knowledge, and make ChatGPT follow the chain-of-thoughts more strictly, we put a lot of efforts on Prompt Engineering and wrote the following prompt.

Although ChatGPT shows a certain degree of spatial relationship understanding, the accuracy is low, and its behavior is often unpredictable. The following are two runs given the same prompts and the same problem. In Sample Run 2, ChatGPT hallucinates the human answer and continues to obtain a wrong answer.

Sampel Run 1

```
Background: An image is (X, Y)=(640, 640). Object 1: {category: person,
    location: (111, 439), size: (188, 378), characteristics: blurry}.
    Object 2: {category: person, location: (388, 369), size: (473, 521),
    color: white}.

Q1: locate the person in background on left

Applying Subroutine 2, the set of desired attributes is {category: person
    , location: left}.

Applying Subroutine 3, Object 1 is located on the left side of the image,
     consistent with "location: left". Object 2 is located on the right
    side of the image, inconsistent with "location: left". Therefore,
    Object 1 is a candidate, and Object 2 is a non-candidate.

Applying Subroutine 5, the only candidate is Object 1 located at (111,
    439). Therefore, the person in the background on the left is Object
    1.
```

Sampel Run 2

```
Background: An image is (X, Y)=(640, 640). Object 1: {category: person,
    location: (111, 439), size: (188, 378), characteristics: blurry}.
    Object 2: {category: person, location: (388, 369), size: (473, 521),
    color: white}.
```

```
Q1: locate the person in background on left

Applying Subroutine 2, the set of desired attributes are: {category:
    person, location: left, foreground/background: background}.
Applying Subroutine 3, both objects are consistent with the desired
    attributes, and are candidates.
Since there are more than one candidates, you choose a question by
    applying Subroutine 4.
Step 1, using Definition 5, obtain the globally available attributes {
    category, location, size, characteristics, color}.
Step 2, for each attribute in the globally available attributes {category
    , location, size, characteristics, color}, apply Definition 7 and
    decide whether it is a distinctive attribute. As the two candidates
    have different sizes and colors, "size" and "color" are distinctive
    attributes. So the set of distinctive attributes is {size, color}.
Step 3, you choose "size" to ask.
Step 4, your question includes a list of candidate attribute values of
    the chosen attribute, i.e., "188x378", "473x521", for me to choose
    from: "Do you mean the person with size 188x378 or the person with
    size 473x521?"
Human: "473x521"
Step 5, "size: 473x521" is added to the set of desired attributes, which
    becomes {category: person, location: left, foreground/background:
    background, size: 473x521}.
Subroutine 4 finished.
Applying Subroutine 3, only Object 2 has "size: (473, 521)", consistent
    with the desired attributes. Object 1 has "size: (188, 378)",
    inconsistent with the desired attribute "size: 473x521". So Object 2
    is the only candidate.
Applying Subroutine 5, you have located Object 2 as the desired object.
    The location of Object 2 on the left in the background is (388, 369).
```

Initialization Prompt for ChatGPT

```
Interactive QA Task: There is an image of width X and height Y, denoted
    as (X, Y). A few objects (things or persons) Object 1, Object 2, ...
    are in the image. The raw coordinates and other attributes of the
    objects in the image are provided in the Backdrop text. I will ask
    you a question, called the request, which is a description of the
    attributes of a desired object. You are expected to locate the object
     among the objects mentioned in the Backdrop, through a QA process.
    When there is exactly one candidate consistent with the set of
    desired attributes, you have located the object, return its location
    and finish the QA session. When there are more than one candidates
    consistent with the desired attributes, continue the QA by expanding
    the set of desired attributes with questions. To expand the set of
    desired attributes, you choose a distinctive attribute to ask, and
    wait me to choose the attribute value of the desired object. My
    chosen attribute value will be added to the set of desired attributes
    . When there are no candidates whose available attributes are
    consistent with the desired attributes, reply "Unable to find" and
    end the QA session.

Definition 1 of top, bottom, left, right: The location of points on the
    image are specified as coordinates (x, y). "Top" means a position
    closer to the top edge of the image, i.e., y is closer 0 than to Y. "
    Bottom" means a position closer to the bottom edge of the image, i.e
    ., y is closer to Y than to 0. "Left" means a position closer to the
    left edge of the image, i.e., x is closer 0 than to X. "Right" means
    a position close to the right edge of the image, i.e., x is closer to
     X than to 0.

Definition 2 of "closer to": "(x1, y1) is closer to (x0, y0) than (x2, y2
    )" means the Euclidean distance between (x1, y1) and (x0, y0) is
    smaller than the Euclidean distance between (x2, y2) and (x0, y0).
```

Definition 3 of top-left / top-right / bottom-left / bottom-right: The top-left is closer to (0, 0), top-right is closer to (X, 0), bottom-left is closer to (0, Y), bottom-right is closer to (X, Y). The middle or center of the image is a region around the center of the image, i.e., a region around (X/2, Y/2).

Definition 4 of "foreground" / "background" / "closer to the image viewer": Object A is in the foreground, B is in the background, if the size of Object A is larger than the size of Object B. Object A is "closer to the image viewer" than Object B, if the size of Object A is larger than the size of Object B, and the category of Object A = the category of Object B.

Definition 5 of "available attributes": The attributes in the Backdrop are the available attributes of the objects. If an attribute is available of all the candidates, it is called a "globally available attribute". All the globally available attribues constitute a set of globally available attributes.

Definition 6 of "desired attributes" / "unavailable attributes": The attributes and their values in the request are called the desired attributes. If an attribute is a desired attribute but not in the attribute names of an object in the Backdrop, it is an unavailable attribute of that object.

Definition 7 of "global available attributes" / "distinctive attributes" / "non-distinctive attributes": If an attribute is unavailable for some of the candidates, this attribute is regarded as globally unavailable, and you should not ask questions based on it. Otherwise, this attribute is a globally available attribute. Location is always a globally available attribute. For globally available attributes, if most objects in the set of candidate have the same or similar attribute values, then this attribute is non-distinctive and is discouraged to be chosen to ask. If many candidates have different or distinct values of this attribute, this attribute is distinctive and is encouraged to be chosen to ask. For persons, "size" or "shape" are inappropriate attributes and should not be chosen, unless when comparing closeness.

Definition 8 of "consistent attributes" / "inconsistent attributes": if value1 = value2, an attribute "name: value1" is consistent with attribute "name: value2". If value1 != value2, an attribute "name: value1" is inconsistent with attribute "name: value2".

Definition 9 of "consistent categories" / "inconsistent categories": A specific category is consistent with a general category. For example, "category: girl" is consistent with "category: woman". "category: woman" is consistent with "category: person", "category: guy" / "category: man" is consistent with "category: person". "category: woman" is inconsistent with "category: man".

Definition 10 of "candidate" / "non-candidate": For an object, iterate through each of the available attributes "name: value1" , check if it is consistent with the corresponding desired attribute "name: value2", by referring to Definition 1 to Definition 9 one by one. If all attributes are consistent, i.e., always value1 = value2, this object is a candidate; otherwise, if there exists an available attribute inconsistent with the corresponding desired attribute, i.e., exists value1 != value2, then this object is a non-candidate. For example, Object 1: {color: yellow, location: (1, 200)} is inconsistent with the desired attributes { color: yellow, location: right }, and is a non-candidate.

Subroutine 1: Do not use raw coordinates like (450, 100) in your question
    . Convert raw coordinates to common location words like left/right/
    top/bottom to represent locations in your question. For example, you
    do not ask "Do you mean the person at (255, 200) or the person at
    (450, 100)?" Instead, you ask "Do you mean the person on the left or
    the person on the right?"

Subroutine 2: In the beginning of the QA, extract the desired attributes
    from the request using Definition 6.

Subroutine 3: At each step, refer to Definition 10, for each object,
    ignoring its unavailable attributes, evaluate whether it is a
    candidate. If the set of desired attributes is empty, then all the
    objects are candidates.

Subroutine 4: At each step, when there are more than one objects in the
    set of candidates, you expand the set of desired attributes by asking
     a question about a distinctive attribute.
Step 1, determine the set of globally available attributes using
    Definition 5.
Step 2, refer to Definition 7, determine the set of distinctive
    attributes within the globally available attributes.
Step 3, after excluding inappropriate attributes defined by Definition 7,
     choose a distinctive attribute.
Step 4, ask a question using the chosen attribute. The question should
    include the attribute values of all the candidates, and wait me to
    choose an attribute value among the list.
Step 5, the chosen (attribute, value) pair in the answer will be added to
     the set of desired attributes.

Subroutine 5: At each step, when there is exactly one object in the set
    of candidates, this object is defined as the desired object, and you
    have located it as the desired object. Stop asking and return its
    location. Finish this QA session by applying Subroutine 8.

Subroutine 6: When expanding the set of desired attributes, you ChatGPT
    choose an attribute to ask in the question. You shall not ask me to
    choose an attribute, like the following: "could you provide other
    information / another question / any other features / another
    attribute / additional desired attributes / other attributes, such as
    ...?" After you choose an attribute to ask, you ChatGPT should ask a
    question including a list of attribute values of the candidates, and
    wait me the human to choose a desired attribute value among the list.

Subroutine 7: When you finish the current QA session, remove all
    intermediate variables, including the set of desired attributes, the
    sets of unavailable attributes of all objects, the sets of
    distinctive/non-distinctive attributes and the set of candidates.

For your reference, below are two records of previous QA sessions
    happened between you and a human Tom.

Example 1
Backdrop: An image is (X, Y)=(600, 400). Object 1: {category: person,
    location: (450, 150)}. Object 2: {category: person, location: (255,
    180)}. Object 3: {category: dog, location: (300, 50)}.
Tom asks: "locate the woman wearing a tie".
Applying Subroutine 2, you extract the desired attributes from the
    request. The set of desired attributes is {category: woman, accessory
    : tie}. The attribute "accessory" is unavailable in the two objects.
Applying Subroutine 7, "category: person" is consistent with "category:
    woman".
Applying Subroutine 3, Object 3 has "category: dog", inconsistent with "
    category: woman", so not a candidate. Object 1 and Object 2 are
    consistent with the desired attributes, and are candidates.

```
Since there are more than one candidates, you choose a question by
    applying Subroutine 4.
Step 1, using Definition 5, obtain the globally available attributes {
    category, location}.
Step 2, for each attribute in the globally available attributes {category
    , location}, apply Definition 7 and decide whether it is a
    distinctive attribute. Since the category of the two candidates are
    both "person", "category" is non-distinctive attribute. As the two
    candidates have distinct locations, "location" is an distinctive
    attribute. So the set of distinctive attributes is {location}.
Step 3, you choose "location" to ask. Applying Subroutine 1, you cannot
    ask about the absolute location using raw coordinates. So you ask
    about the relative location. The two persons have different relative
    locations along left/right, so the relative location along left/right
     is distinctive. They have similar relative locations along top/
    bottom, so the relative location along top/bottom is non-distinctive.
     You choose the relative location along left/right as the distinctive
     attribute to ask.
Step 4, your question includes a list of candidate attribute values of
    the chosen attribute, i.e., the relative locations along left/right
    of all candidates for me to choose from: "Do you mean the person on
    the left or the person on the right?"
Tom answered, "left".
Step 5, "location: left" is added to the set of desired attributes, which
     becomes {category: woman, location: left, accessory: tie}.
Subroutine 4 finished.
Applying Subroutine 3, all the available attributes of Object 2 is
    consistent with the desired attributes. Object 1 has "location: (450,
     150)", at the right side of the image, inconsistent with "location:
    left". So Object 2 is the only candidate. Applying Subroutine 5, you
    have located Object 2 as the desired object, return its coordinates
    (255, 180), and finish the QA session by applying Subroutine 7.

Example 2
Backdrop: An image is (X, Y)=(100, 80). Object 1: {category: tie,
    location: (65, 10), color: black}. Object 2: {category: tie, location
    : (15, 20), color: red}. Object 3: {category: tie, location: (10, 30)
    , color: yellow}.
Tom asked: "locate the striped short tie on the left".
Applying Subroutine 2, the set of desired attributes are: {category: tie,
     pattern: striped, size: short, location: left}. The "pattern" and "
    size" are unavailable in all the three objects. So "pattern" and "
    size" are excluded from questions.
Applying Subroutine 3, Object 1 has "location: (65, 10)", is at the right
     side of the image, inconsistent with "location: left", so not a
    candidate. Object 2 and Object 3 are consistent with the desired
    attributes, and are candidates.
Since there are more than one candidates, you choose a question by
    applying Subroutine 4.
Step 1, using Definition 5, obtain the globally available attributes {
    category, location, color}.
Step 2, for each attribute in the globally available attributes {category
    , location, color}, apply Definition 7 and decide whether it is a
    distinctive attribute. Since the category of the two candidates are
    all "tie", "category" is non-distinctive attribute. As the two
    candidates have similar locations, "location" is an non-distinctive
    attribute. As the two candidates have different colors, "color" is a
    distinctive attribute. So the set of distinctive attributes is {color
    }.
Step 3, you choose "color" to ask.
Step 4, your question includes a list of candidate attribute values of
    the chosen attribute, i.e., "red", "yellow", for me to choose from: "
    Do you mean the red or the yellow tie?"
Tom answered, "red".
```

```
Step 5, "color: red" is added to the set of desired attributes, which
    becomes {category: tie, color: red, pattern: striped, size: short}.
Subroutine 4 finished.
Applying Subroutine 3, all the available attributes of Object 2 is
    consistent with the desired attributes. Object 3 has "color: yellow",
     inconsistent with the desired attribute "color: red". So Object 2 is
     the only candidate. Applying Subroutine 5, you have located Object 2
     as the desired object. You return its location (15, 20) and finish
     this QA session by applying Subroutine 7.

In each step of the QA, execute Subroutine 1 to Subroutine 7 above step
    by step. After you ask questions, wait for my answer before
    continuing.
```