Countering the Attack-Defense Complexity Gap for Robust Classifiers

Abstract

We consider the decision version of defending and attacking Machine Learning classifiers. We provide a rationale for the well-known difficulties in building robust models: in particular we prove that, under broad assumptions, attacking a polynomial-time classifier is NP-complete, while training a polynomial-time model that is robust on even a single input is Σ_2^P-complete. We also provide more general bounds for non-polynomial classifiers. We then show how such a complexity gap can be sidestepped by introducing Counter-Attack (CA), a system that computes on-the-fly robustness certificates for a given input up to an arbitrary distance bound ε. We also prove that, even when attacked with perturbations of magnitude $\varepsilon' > \varepsilon$, CA still provides computational robustness: specifically, while computing a certificate is NP-complete, attacking the system beyond its intended robustness is Σ_2^P-complete. Since the exact form of CA can still be computationally expensive, we introduce a relaxation of this method, which we empirically show to be reliable at identifying non-robust inputs. As part of our work, we introduce UG100, a new dataset obtained by applying a provably optimal attack to six limited-scale networks (three for MNIST and three for CIFAR10), each trained in three different manners.

1 Introduction

Adversarial attacks, i.e. algorithms designed to fool machine learning models, represent a significant threat to the applicability of such models in real-world contexts (Brendel et al., 2019; Brown et al., 2017; Wu et al., 2020). Despite years of research effort, countermeasures (i.e. "defenses") to adversarial attacks are frequently fooled by applying small tweaks to existing techniques (Carlini & Wagner, 2016; 2017a; Croce et al., 2022; He et al., 2017; Hosseini et al., 2019; Tramer et al., 2020).

We argue that this pattern is due to differences between the fundamental mathematical problems that defenses and attacks need to tackle. Specifically, we prove that while attacking a polynomial-time classifier is an NP-complete task, **training a polynomial-time model that is robust even on a single input is Σ_2^P-complete**. We also provide more general bounds for non-polynomial classifiers, showing that a A-time classifier can be attacked in NP^A time. We then provide an informal intuition for our theoretical results, which also applies to heuristic attacks and defenses.

Our result highlights a fundamental difficulty for defense approaches focusing on building robust classifiers at training time. However, we show that the asymmetry can be **sidestepped** via alternative approaches. In particular, we introduce a new technique, named Counter-Attack (CA) that, instead of training a robust model, evaluates on the fly if a model is robust on a specific point by running an adversarial attack on the received input. This approach, while very simple, provides robustness guarantees against perturbations of an arbitrary magnitude ε. Additionally, we prove that while generating a certificate is NP-complete, **attacking CA using perturbations of magnitude $\varepsilon' > \varepsilon$ is Σ_2^P-complete**, which represents a form of computational robustness (Garg et al., 2020).

The use of adversarial attacks also ensures that CA can be applied in any setting where at least one untargeted adversarial attack is known, while also allowing one to capitalize on future improvements in the field of adversarial attacks: **as adversarial attacks become stronger, so does CA**.

While using CA in combination with exact attacks is not scalable in general (due to its NP-completeness), existing attacks may serve as an efficient proxy. We provide empirical evidence

for this claim by introducing **UG100**, a dataset of provably optimal adversarial examples found on 2.2k samples of MNIST and CIFAR10 for 6 small-scale Neural Networks (NNs). We also benchmark seven heuristic adversarial attacks and find that they provide an accurate (average over-estimate between 2.04% and 4.65%) and predictable (average $R^2 > 0.99$) approximation of the true optimum. UG100 can also serve as a benchmark for future attacks, and allows for a comparison with both exact and heuristic approaches. All our code, datasets, pretrained weights and results are available anonymously at https://anonymous.4open.science/r/counter-attack under MIT license.

2 RELATED WORK

Robustness bounds for NNs were first provided in (Szegedy et al., 2013), followed by (Hein & Andriushchenko, 2017) and (Weng et al., 2018b). One major breakthrough was the introduction of automatic verification tools, such as the Reluplex solver (Katz et al., 2017). However, the same work also showed that proving properties of a ReLU network is NP-complete. Researchers tried to address this issue by working in three directions. The first is building more efficient solvers based on alternative formulations (Dvijotham et al., 2018; Singh et al., 2018; Tjeng et al., 2019). The second involves training models that can be verified with less computational effort (Leino et al., 2021; Xiao et al., 2019) or provide inherent robustness bounds (Sinha et al., 2018). The third focuses on guaranteeing robustness under specific threat models (Han et al., 2021) or input distribution assumptions (Dan et al., 2020; Raghunathan et al., 2018; Sinha et al., 2018). Since all these approaches have limitations that reduce their applicability (Silva & Najafirad, 2020), heuristic defenses tend to be more common in practice. Exact approaches can also be used to compute provably optimal adversarial examples (Carlini et al., 2017; Tjeng et al., 2019), although generating them requires a non-trivial amount of computational resources.

Another line of research has focused on understanding the nature of robustness and adversarial attacks. Frameworks such as (Dreossi et al., 2019), (Pinot et al., 2019) and (Pydi & Jog, 2021) focused on formalizing the concept of adversarial robustness. Some studies have highlighted trade-offs between robustness (under specific definitions) and properties such as accuracy (Dobriban et al., 2020; Zhang et al., 2019), generalization (Min et al., 2021) and invariance (Tramèr et al., 2020). However, some of these results have been recently questioned, suggesting that these trade-offs might not be inherent in considered approaches (Yang et al., 2020; Zhang et al., 2020). Adversarial attacks have also been studied from the point of view of Bayesian learning, which has been used to derive robustness bounds and provide insight into the role of uncertainty (Rawat et al., 2017; Richardson & Weiss, 2021; Vidot et al., 2021). Finally, adversarial attacks have also been studied in the context of game theory (Ren et al., 2021), identifying Nash equilibria between attacker and defender (Pal & Vidal, 2020; Zhou et al., 2019).

Finally, some works have also focused on the computational complexity of specific adversarial attacks and defenses. In particular, Mahloujifar & Mahmoody (2019) showed that there exist exact polynomial-time attacks against classifiers trained on product distributions. Similarly, Awasthi et al. (2019) showed that for degree-2 polynomial threshold functions there exists a polynomial-time algorithm that either proves that the model is robust or finds an adversarial example. Other works have also provided hardness results; Degwekar et al. (2019) showed that there exist certain classification tasks such that learning a robust model is as hard as solving the Learning Parity with Noise problem (which is NP-hard); Song et al. (2021) showed that learning a single periodic neuron over noisy isotropic Gaussian distributions in polynomial time would imply that the Shortest Vector Problem (conjectured to be NP-hard) can be solved in polynomial time. Finally, Garg et al. (2020) showed that, by requiring attackers to provide a valid cryptographic signature for inputs, it is possible to prevent attacks with limited computational resources from fooling the model in polynomial time.

3 BACKGROUND AND FORMALIZATION

In this section we introduce the key definitions that will be used in our theoretical work. We chose to focus on capturing the key ideas identified in the relevant literature, while simplifying some of their less essential traits. We believe that this approach has a good chance to identify important properties that can then be translated to other robustness frameworks with reasonable effort.

We start by defining the concept of *adversarial example*, which intuitively represents a modification of a legitimate input that is so limited as to be inconsequential from a practical perspective, but classified erroneously by a target model. Formally, let $f : X \rightarrow \{1, \dots, N\}$ be a discrete classifier. Let $B_p(\boldsymbol{x}, \varepsilon) = \{\boldsymbol{x}' \in X \mid \|\boldsymbol{x} - \boldsymbol{x}'\|_p \leq \varepsilon\}$ be a L^p ball of radius ε and center $\boldsymbol{x}$. Then we have:

Definition 1 (Adversarial Example). *Given an input $\boldsymbol{x}$, a threshold ε, and a norm-order[1] p, an adversarial example is an input $\boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon)$ such that $f(\boldsymbol{x}') \in C(\boldsymbol{x})$, where $C(\boldsymbol{x}) \subseteq \{1, \dots, N\} \setminus \{f(\boldsymbol{x})\}$.*

An *adversarial attack* can then be viewed as an optimization procedure that attempts to find an adversarial example for a given classifier. We define an adversarial attack for a classifier f as a function $a_{f,p} : X \rightarrow X$ that solves the following optimization problem:

$$\arg\min_{\boldsymbol{x}' \in X} \{\|\boldsymbol{x}' - \boldsymbol{x}\|_p \mid f(\boldsymbol{x}') \in C(\boldsymbol{x})\} \tag{1}$$

The attack is considered successful if the returned solution $\boldsymbol{x}' = a_{f,p}(\boldsymbol{x})$ also satisfies $\|\boldsymbol{x}' - \boldsymbol{x}\|_p \leq \varepsilon$. We say that an attack is *exact* if it solves Equation (1) to optimality; otherwise, we say that the attack is *heuristic*. An attack is said to be *targeted* if $C(\boldsymbol{x}) = C_{t,y'}(\boldsymbol{x}) = \{y'\}$ with $y' \neq f(\boldsymbol{x})$; it is instead *untargeted* if $C_u(\boldsymbol{x}) = \{1, \dots, N\} \setminus \{f(\boldsymbol{x})\}$. We define the *decision boundary distance* $d_p^*(\boldsymbol{x})$ of a given input $\boldsymbol{x}$ as the minimum L^p distance between $\boldsymbol{x}$ and another input $\boldsymbol{x}'$ such that $f(\boldsymbol{x}) \neq f(\boldsymbol{x}')$. Note that this is also the value of $\|a_{f,p}(\boldsymbol{x}) - \boldsymbol{x}\|_p$ for an exact, untargeted, attack.

Intuitively, a classifier is *robust w.r.t. an example $\boldsymbol{x}$* iff $\boldsymbol{x}$ cannot be successfully attacked. Formally:

Definition 2 ((ε, p)-Local Robustness). *A discrete classifier f is (ε, p)-locally robust w.r.t. an example $\boldsymbol{x} \in X$ iff $\forall \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon)$ we have $f(\boldsymbol{x}') = f(\boldsymbol{x})$.*

We then provide some additional definitions that are needed for our results, namely ReLU networks and FSFP spaces. ReLU networks are defined as follows:

Definition 3 (ReLU network). *A ReLU network is a composition of sum, multiplication by a constant, and ReLU activation, where $ReLU : \mathbb{R} \rightarrow \mathbb{R}_0^+$ is defined as $ReLU(x) = max(x, 0)$.*

Note that any hardness result for ReLU classifiers also applies to the more general class of classifiers. Fixed-Size Fixed-Precision (FSFP) spaces, on the other hand, capture two common assumptions about real-world input spaces: all inputs can be represented with the same number of bits and there exists a positive minorant of the distance between inputs.

Definition 4 (Fixed-Size Fixed-Precision space). *Given a real $p > 0$, a space $X \subseteq \mathbb{R}^n$ is FSFP if there exists a $\nu \in \mathbb{R}$ such that $\forall \boldsymbol{x}. |r(\boldsymbol{x}')| \leq \nu$ (where $|r(\boldsymbol{x})|$ is the size of the representation of $\boldsymbol{x}$) and there exists a $\mu \in \mathbb{R}$ such that $\mu > 0$ and $\forall \boldsymbol{x}, \boldsymbol{x}' \in X. (\|\boldsymbol{x}' - \boldsymbol{x}\|_p < \mu \implies \boldsymbol{x} = \boldsymbol{x}')$.*

Examples of FSFP spaces include most image encodings, as well as 32-bit and 64-bit IEE754 tensors. Examples of non-FSFP spaces include the set of all rational numbers in an interval. Similarly to ReLU networks, hardness results for FSFP spaces also apply to more general spaces.

4 AN ASYMMETRICAL SETTING

In this section, we study why attacks seem to outperform defenses. We begin our analysis by proving that attacks are less computationally expensive than defenses. Specifically, we prove that the decision version of attacking is NP-complete:

Theorem 1[2] (Untargeted L^∞ attacks against ReLU classifiers are NP-complete). *Let U-ATT_p be the set of all tuples $\langle \boldsymbol{x}, \varepsilon, f \rangle$ such that:*

$$\exists \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon). f(\boldsymbol{x}') \neq f(\boldsymbol{x}) \tag{2}$$

where $\boldsymbol{x} \in X$, X is a FSFP space, f is a ReLU classifier, $B_p(\boldsymbol{x}, \varepsilon) = \{\boldsymbol{x}' \in X \mid \|\boldsymbol{x} - \boldsymbol{x}'\|_p \leq \varepsilon\}$. Then U-ATT_∞ is NP-complete.

Corollary 1.1. *For every $0 < p \leq \infty$, U-ATT_p is NP-complete.*

---

[1] We use the term "norm" for $0 < p < 1$ even if in such cases the L^p function is not subadditive.

[2] The proofs of all our theorems and corollaries can be found in the appendices.

Corollary 1.2. *Targeted L^p attacks (for $0 < p \leq \infty$) against ReLU classifiers are NP-complete.*

Corollary 1.3. *Theorem 1 holds even if we consider the more general set of polynomial-time classifiers w.r.t. the size of the tuple.*

Theorem 1 represents a stronger claim compared to that of Katz et al. (2017), who showed that proving arbitrary properties of ReLU networks is NP-complete: in fact, it shows that even when considering the special case of adversarial attacks, the problem is still NP-complete.

For non-polynomial-time classifiers, we provide a more general upper bound:

Theorem 2. *Let A be a complexity class, let f be a classifier, let $Z_f = \{\langle \boldsymbol{x}, y \rangle \mid y = f(\boldsymbol{x}), \boldsymbol{x} \in X\}$ and let $U\text{-}ATT_p(f) = \{\langle \boldsymbol{x}, \varepsilon, g \rangle \in U\text{-}ATT_p' \mid g = f\}$, where $U\text{-}ATT_p'$ is the same as $U\text{-}ATT_p$ but without the ReLU classifier restriction. If $Z_f \in A$, then for every $0 < p \leq \infty$, $U\text{-}ATT_p(f) \in NP^A$.*

Corollary 2.1. *For every $0 < p \leq \infty$, if $Z_f \in \Sigma_n^P$, then $U\text{-}ATT_p(f) \in \Sigma_{n+1}^P$.*

The latter result implies that, if $Z_f \in P$, then $U\text{-}ATT_p(f) \in NP$. Informally, Corollary 2.1 establishes that, under broad assumptions, the evaluating and attacking a classifier are in distinct complexity classes, with the attack problem being the harder one.

The decision version of *training a robust model* is even more complex:

Theorem 3 (Finding a set of parameters that make a ReLU network (ε, p)-locally robust on an input is Σ_2^P-complete). *Let $PL\text{-}ROB_p$ be the set of tuples $\langle \boldsymbol{x}, \varepsilon, f_{\boldsymbol{\theta}}, v \rangle$ such that:*

$$\exists \boldsymbol{\theta}' . (v_f(\boldsymbol{\theta}') = 1 \implies \forall \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon). f_{\boldsymbol{\theta}'}(\boldsymbol{x}') = f_{\boldsymbol{\theta}'}(\boldsymbol{x})) \tag{3}$$

where $\boldsymbol{x} \in X$, X is a FSFP space and v_f is a polynomial-time function that is 1 iff the input is a valid parameter set for f. Then $PL\text{-}ROB_\infty$ is Σ_2^P-complete.

Corollary 3.1. *$PL\text{-}ROB_p$ is Σ_2^P-complete for all $0 < p \leq \infty$.*

Corollary 3.2. *Theorem 3 holds even if, instead of ReLU classifiers, we consider the more general set of polynomial-time classifiers w.r.t. the size of the tuple.*

In practice, while it is possible to run exact attacks such as the MIP-based one from Tjeng et al. (2019) on moderate-sized neural classifiers, finding the parameters that make a general model robust is infeasible even for small networks. Note that Theorem 3 is valid in general: efficiently finding a robust parameter set may be possible for specific architectures or input distributions.

4.1 Heuristic Relaxations

Even when considering heuristic relaxations of attacks and defenses (which do not provide formal guarantees), there are several factors that lead to the attacker having an advantage. We present an informal overview of such mechanisms, which can provide an intuition to Theorems 1 and 3, are more broadly applicable, and can guide efforts to translate our results to other theoretical frameworks. Note that, despite these factors, defenses can still provide a (limited) degree of robustness.

First, the attacker can easily gather information about the target model, e.g. by using genuine queries (Papernot et al., 2017), while the defender has not such advantage. As a result, the defender often needs to either make assumptions about adversarial examples (Hendrycks & Gimpel, 2017; Roth et al., 2019) or train models to identify common properties (Feinman et al., 2017; Grosse et al., 2017). These assumptions can be exploited, such as in the case of Carlini & Wagner (2017a), who generated adversarial examples that did not have the expected properties.

Second, the attacker can focus on one input at the time, while the defender has to guarantee robustness on a large subset of the input space. Similarly, being robust on an input involves guaranteeing that all the neighboring points have the same predicted class, while an attack only needs to find one counter-example to succeed. Both weaknesses have been successfully exploited. For example, MagNet (Meng & Chen, 2017) relies on a model of the entire genuine distribution, which can be sometimes inaccurate. Carlini & Wagner (2017b) broke MagNet by searching within the neighborhood of the starting point for examples that were both classified differently and mistakenly considered genuine.

Finally, defenses have an additional constraint: they cannot significantly compromise the accuracy of a model. Adversarial training, for example, often reduces the clean accuracy of the model (Madry et al., 2018), leading to a trade-off between accuracy and robustness.

5 COUNTER-ATTACK

Due to the limitations imposed by Theorem 3, we introduce a different approach to provide robust classification, which also allows us to take advantage of existing defenses. Instead of obtaining a robust model from scratch, we propose to evaluate the robustness of the classifier on a case-by-case basis, flagging the input if a robust answer cannot be provided. Specifically, given a norm-order p and threshold ε, we propose to:

- Design a model that is as robust as possible using available and practically viable defenses;
- For every input received, determine if the model is (ε, p)-locally robust on the input by running an adversarial attack on the input;
- If the attack succeeds, flag the input.

We name this technique *Counter-Attack* (CA). Instead of attempting to build a robust model, CA ensures that answers from a partially robust model are flagged as unreliable when they could be the result of an attack. This approach, while very simple, can take advantage of existing defenses, provides robustness guarantees, and is considerably hard to fool, as we will later prove.

The behavior in case an input is flagged depends on the context. Examples include relying on a slower but more robust model (e.g. a human), or rejecting the input altogether.

Note that the flagging rate of CA is heavily dependent on the robustness of the model: a model that is robust on the entire input distribution will have a flagging rate of zero. Therefore, any improvement in the field of adversarial defenses also decreases the flagging rate of CA. Moreover, if there are known robustness bounds, they can be exploited to simplify the attack: for example, if the model is (ε_{cert}, p)-robust on $\boldsymbol{x}$, with $\varepsilon_{cert} < \varepsilon$, the attack can focus on searching adversarial examples in $B_p(\boldsymbol{x}, \varepsilon) \setminus B_p(\boldsymbol{x}, \varepsilon_{cert})$. At the same time, developing stronger and faster attacks also benefits CA, since better attacks can find adversarial examples more quickly.

The major drawback of CA is that it requires running an adversarial attack on every input. As we will show, this phenomenon can be mitigated by employing heuristic attacks, which still provide a significant degree of robustness (see Section 6).

5.1 FORMAL PROPERTIES

We first prove that CA provides robustness guarantees for an arbitrary p and ε:

Theorem 4. *Let $0 < p \le \infty$ and let $\varepsilon > 0$. Let $f : X \to \{1, \ldots, N\}$ be a classifier and let a be an exact attack. Let $f^a_{CA} : X \to \{1, \ldots, N\} \cup \{\star\}$ be defined as:*

$$f^a_{CA}(\boldsymbol{x}) = \begin{cases} f(\boldsymbol{x}) & ||a_{f,p}(\boldsymbol{x}) - \boldsymbol{x}||_p > \varepsilon \\ \star & otherwise \end{cases} \tag{4}$$

Then $\forall \boldsymbol{x} \in X$ any adversarial attack on $\boldsymbol{x}$ of norm p, radius greater than or equal to ε and with $\star \notin C(\boldsymbol{x})$ fails.

The notation $f^a_{CA}(\boldsymbol{x})$ refers to the classifier f combined with CA, relying on attack a. The condition $\star \notin C(\boldsymbol{x})$ requires that the input generated by the attack should not be flagged by CA.

Corollary 4.1. *Let $1 \le p \le \infty$ and let $\varepsilon > 0$. Let f be a classifier on inputs with n elements that uses CA with norm p and radius ε. Then for all inputs and for all $1 \le r < p$, L^r attacks of radius greater than or equal to ε and with and $\star \notin C(\boldsymbol{x})$ will fail. Similarly, for all inputs and for all $r > p$, L^r attacks of radius greater than or equal to $n^{\frac{1}{r} - \frac{1}{p}} \varepsilon$ and with $\star \notin C(\boldsymbol{x})$ will fail (treating $\frac{1}{\infty}$ as 0).*

Since the only expensive step in CA consists in applying an adversarial attack to an input, the complexity is the same as that of a regular attack. CA therefore represents a more feasible task compared to training a robust model.

Attacking with a Higher Radius In addition to robustness guarantees for a chosen ε, CA provides a form of computational robustness even beyond its intended radius. To prove this statement, we first formalize the task of attacking CA (referred to as Counter-CA, or CCA).This involves finding, given a starting point $\boldsymbol{x}$, an input $\boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon')$ that is adversarial but not flagged by CA, i.e. such that $f(\boldsymbol{x}') \in C(\boldsymbol{x}) \wedge \forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}', \varepsilon).f(\boldsymbol{x}'') = f(\boldsymbol{x}')$. Note that, for $\varepsilon' \le \varepsilon$, no solution exists, since $\boldsymbol{x} \in B_p(\boldsymbol{x}', \varepsilon)$ and $f(\boldsymbol{x}) \ne f(\boldsymbol{x}')$.

Theorem 5 (Attacking CA with a higher radius is Σ_2^P-complete)**.** *Let CCA_p be the set of all tuples $\langle \boldsymbol{x}, \varepsilon, \varepsilon', C, f \rangle$ such that:*

$$\exists \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon'). \, (f(\boldsymbol{x}') \in C(\boldsymbol{x}) \wedge \forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}', \varepsilon).f(\boldsymbol{x}'') = f(\boldsymbol{x}')) \tag{5}$$

where $\boldsymbol{x} \in X$, X is a FSFP space, $\varepsilon' > \varepsilon$, $f(\boldsymbol{x}) \notin C(\boldsymbol{x})$ f is a ReLU classifier and whether an output is in $C(\boldsymbol{x}^*)$ for some $\boldsymbol{x}^*$ can be decided in polynomial time. Then CCA_∞ is Σ_2^P-complete.

Corollary 5.1. *CCA_p is Σ_2^P-complete for all $0 < p \leq \infty$.*

Corollary 5.2. *Theorem 5 holds even if, instead of ReLU classifiers, we consider the more general set of polynomial-time classifiers w.r.t. the size of the tuple.*

In other words, fooling CA is harder than running CA even when we use a higher radius. This phenomenon represents a form of computational robustness (Garg et al., 2020). Corollary 2.1 also implies that, unless the polynomial hierarchy collapses, it is impossible to obtain a better gap between running the model and attacking (e.g. a P-time model that is Σ_2^P-hard to attack). Note that while Theorem 5 shows that fooling CA with a higher radius is Σ_2^P-complete, there are two special cases where attacking is very simple. First, for ε' large enough that $B_p(\boldsymbol{x}, \varepsilon') \approx X$, one can compute the decision boundary distance of several inputs and build a database of potential adversarial examples. Similarly, if ε is much smaller than the average decision boundary distance, one can simply sample a point in $B_p(\boldsymbol{x}, \varepsilon') \setminus B_p(\boldsymbol{x}, \varepsilon)$, since the chances that CA flags the altered input are very small. However, these are both edge cases of limited practical interest.

5.2 RELAXATION

Due to the NP-completeness of CA, it cannot be used in its exact form at large scale. For this reason, we study a heuristic relaxation of CA. Specifically, we flag the input $\boldsymbol{x}'$ if a *heuristic* adversarial attack fails to find an adversarial example in a radius of $\varepsilon + b(\boldsymbol{x}')$, where $b : X \to \mathbb{R}_0^+$ is a buffer model. The idea behind b is that if a heuristic attack can identify an adversarial example within a radius of $\varepsilon + b(\boldsymbol{x}')$, an exact attack would be able to find an adversarial example within a radius of ε. Note that if a heuristic attack overestimates $d_p^*(\boldsymbol{x})$ in a predictable manner, we can train a buffer model to accurately correct the error. This implies that, in the context of CA, a consistent but weak attack can be more effective than a strong but unreliable one.

If the heuristic attack finds an adversarial example with distance less than ε, we can confidently flag the input. However, if the distance is above ε, it is possible that an exact attack would have found an example within a radius of ε (and thus the input should have been flagged). We study how reliably heuristic attacks can approximate exact attacks in Section 6.

Fooling the Heuristic Variant of CA   The fact that the heuristic relaxation of CA can overestimate the decision boundary distance means that it is possible to generate adversarial examples with $\varepsilon' \leq \varepsilon$. Specifically, if an adversarial example $\boldsymbol{x}^{adv}$ for an input $\boldsymbol{x}$ is such that $d_p^*(\boldsymbol{x}^{adv}) \leq \varepsilon$ and $f(\boldsymbol{x}^{adv}) \neq f(\boldsymbol{x})$ but $||a_{f,p}(\boldsymbol{x}^{adv}) - \boldsymbol{x}^{adv}||_p > \varepsilon + b(\boldsymbol{x}^{adv})$, CA will incorrectly accept $\boldsymbol{x}^{adv}$. However, there are several informal considerations suggesting that fooling CA might be harder than running it. Such considerations are backed by empirical evidence in Section 6.

First, both CA and CCA need to attack the same model, but CCA has at most as much information regarding the target model as CA, thus making the attacker at most as sample efficient as the defender. Second, fooling CA involves solving a nested optimization problem, while CA only needs to solve one; specifically, verifying the feasibility of a CCA solution involves running CA on the solution. Finally, any tool capable of determining efficiently if CA overestimates the decision boundary distance can also be used by CA itself to obtain a more accurate buffer model. Similarly, as better attacks are developed the chances of CA being fooled become slimmer, since these attacks will be less likely to find sub-optimal adversarial examples.

6 EXPERIMENTAL EVALUATION

We now evaluate the effectiveness of the heuristic relaxation of CA. Specifically, we test whether $||\boldsymbol{x} - \boldsymbol{x}_h||_p$, where $\boldsymbol{x}_h$ is an adversarial example found by a heuristic attack, is predictably close to

the true decision boundary distance (i.e. $d_p^*(\boldsymbol{x})$). Consistently with Athalye et al. (2018) and Weng et al. (2018a), we focus on the L^∞ norm. Additionally, we focus on *pools* of heuristic attacks. The underlying rationale is that different adversarial attacks should be able to cover for their reciprocal blind spots, providing a more reliable estimate. Since this evaluation is empirical, it requires sampling from a chosen distribution, in our case specific classifiers and the MNIST (LeCun et al., 1998) and CIFAR10 (Krizhevsky et al., 2009) datasets. This means that the results are not guaranteed for other distributions, or for other defended models: studying how adversarial attacks fare in these cases is an important topic for future work.

Experimental Setup We randomly selected ~2.3k samples each from the test set of two datasets, MNIST and CIFAR10. We used three architectures per dataset (named A, B and C), each trained in three settings, namely standard training, PGD adversarial training (Madry et al., 2018) and PGD adversarial training with ReLU loss and pruning (Xiao et al., 2019) (from now on referred to as ReLU training), for a total of nine configurations per dataset. Since our analysis requires computing exact decision boundary distances, and size and depth both have a strong adverse impact on solver times, we used small and relatively shallow networks with parameters between ~2k and ~80k. For this reason, the natural accuracies for standard training are significantly below the state of the art (89.63% - 95.87% on MNIST and 47.85% - 55.81% on CIFAR10). Adversarial training also had a negative effect on natural accuracies (84.54% - 94.24% on MNIST and 45.19% - 51.35% on CIFAR10), similarly to ReLU training (83.69% - 93.57% on MNIST and 32.27% - 37.33% on CIFAR10).

We first ran a pool of heuristic adversarial attacks on each example. Specifically, we used the Basic Iterative Method (Kurakin et al., 2017), the Brendel & Bethge attack (Brendel et al., 2019), the Carlini & Wagner attack (Carlini & Wagner, 2017c), Deepfool (Moosavi-Dezfooli et al., 2016), the Fast Gradient Sign Method (Goodfellow et al., 2015) and the Projected Gradient Descent attack (Madry et al., 2018), as well as simply adding uniform noise to the input. For attacks that take ε as parameter, we performed a mix of linear and binary search to find the adversarial example with minimal distance. Our main choice of attack parameters (from now on referred to as the "strong" parameter set) prioritizes finding adversarial examples at the expense of computational time. For each example, we considered the nearest feasible adversarial example found by any attack in the pool. We then ran the exact solver-based attack MIPVerify (Tjeng et al., 2019), which is able to find the nearest adversarial example to a given input. The entire process (including test runs) required ~45k core-hours on an HPC cluster. Each node of the cluster has 384 GB of RAM and features two Intel CascadeLake 8260 CPUs, each with 24 cores and a clock frequency of 2.4GHz.

We removed the examples for which MIPVerify crashed in at least one setting, obtaining 2241 MNIST examples and 2269 CIFAR10 examples. We also excluded from our analysis all adversarial examples for which MIPVerify did not find optimal bounds (atol = 1e-5, rtol = 1e-10). These examples represent on average 11.95% of MNIST examples and 16.30% of CIFAR10 examples. Additionally, we ran the same heuristic attacks with a faster parameter set (from now on referred to as the "balanced" set) on a single machine with an AMD Ryzen 5 1600X six-core 3.6 GHz processor, 16 GB of RAM and an NVIDIA GTX 1060 6 GB GPU. The process took approximately 8 hours. Refer to Appendix G for a more comprehensive overview of our experimental setup.

Distance Approximation Across all settings, the mean distance found by the strong attack pool is 4.09±2.02% higher for MNIST and 2.21±1.16% higher for CIFAR10 than the one found by MIPVerify. For 79.81±15.70% of the MNIST instances and 98.40±1.63% of the CIFAR10 ones, the absolute difference is less than 1/255, which is the minimum distance in 8-bit image formats. The balanced attack pool performs similarly, finding distances that are on average 4.65±2.16% higher for MNIST and 2.04±1.13% higher for CIFAR10. The difference is below 1/255 for 77.78±16.08% of MNIST examples and 98.74±1.13% of CIFAR10 examples. We compare the distances found by the strong attack pool for MNIST A and CIFAR10 (using standard training) with the true decision bound distances in Figure 1. Refer to Appendix I for the full data.

For all datasets, architectures and training techniques there appears to be a strong, linear, correlation between the distance of the output of the heuristic attacks and the true decision boundary distance. For the strong parameter set, we find that the average R^2 across all settings is 0.992±0.004 for MNIST and 0.997±0.003 for CIFAR10. The balanced parameter set performs similarly, achieving an R^2 of 0.990±0.006 for MNIST and 0.998±0.002 for CIFAR10. From these results, we conjecture that

(a) MNIST A

(b) CIFAR10 A

Figure 1: Distances of the nearest adversarial example found by the strong attack pool compared to those found by MIPVerify on MNIST A and CIFAR10 A with standard training. The black line represents the theoretical optimum.

increasing the computational budget of heuristic attacks does not necessarily improve predictability, although further tests would be needed to confirm such a claim.

The correlation suggests that even a simple linear model for the buffer function b, in the form $b(\boldsymbol{x}) = m||\boldsymbol{x} - a_{f,p}(\boldsymbol{x})||_p + q$, may lead to good results. Therefore, we calibrate a buffer using least-squares fitting on each combination. A more reliable procedure would consist in using quantile fitting, or solving a constrained fitting problem where the model is required to over- or under-estimate a (user-controlled) fraction of the examples. Results for this approach are reported in Appendix H.

Attack Pool Ablation Study   Due to the nontrivial computational requirements of running several attacks on the same input, we now study whether it is possible to drop some attacks from the pool without compromising its predictability. Specifically, we consider all possible pools of size n (with a success rate of 100%) and pick the one with the highest average R^2 value over all architectures and training techniques. As show in Figure 2, adding attacks *does* increase predictability, although with diminishing returns. For example, the pool composed of the Basic Iterative Method, the Brendel & Bethge Attack and the Carlini & Wagner attack achieves on its own a R^2 value of 0.988±0.004 for MNIST+strong, 0.986±0.005 for MNIST+balanced, 0.935±0.048 for CIFAR10+strong and 0.993±0.003 for CIFAR10+balanced. Moreover, dropping both the Fast Gradient Sign Method and uniform noise leads to negligible ($\ll 0.001$) absolute variations in the mean R^2. These findings suggest that, as far as consistency is concerned, the choice of attacks represents a more important factor than the number of attacks in a pool. Refer to Appendix J for a more in-depth overview of how different attack selections affect consistency and accuracy.

Efficient Attacks   We then explore if it possible to increase the efficiency of attacks by optimizing for fast, rather than accurate, results. We pick three new parameter sets (namely Fast-100, Fast-1k and Fast-10k) designed to find the nearest adversarial examples within the respective number of calls to the model. We do not study the Brendel & Bethge and the Carlini & Wagner attacks due to the fact that the number of model calls varies depending on how many inputs are attacked at the same time. We find that while Deepfool is not the strongest adversarial attack (see Appendix I), it provides adequate results in very few model calls. For details on these results see Appendix K.

Fooling CA   Finally, we test how easily CA can be attacked. Specifically, we attempt to fool a CA-defended model (relying on Deepfool Fast-1k) using a proof-of-concept attack based on the PGD method, thus setting a baseline for attacks against CA. This variant uses a custom loss $\mathcal{L}_{CCA}(\boldsymbol{x}, y) = \mathcal{L}_{PGD}(\boldsymbol{x}, y) + \lambda||\boldsymbol{x} - a_{f,p}(\boldsymbol{x})||_p$, which rewards adversarial examples with over-estimated decision boundary distances. We then vary λ in order to test various trade-offs between the two terms. In order to estimate the gradient of the second term, we use Natural Evolution Strategies (Wierstra et al., 2014). We set $\varepsilon = \varepsilon'$ equal to $\{0.025, 0.05, 0.1\}$ for MNIST and $\{2/255, 4/255, 8/255\}$ for

(a) MNIST (b) CIFAR10

Figure 2: Best mean R^2 value in relation to the number of attacks in the pool.

CIFAR10. As a sanity check, we also attack using uniform noise. Due to the high computational requirements of such an experiment (30-60 minutes and $\sim$1.2M model calls per sample on the GTX 1060 machine), we only attack MNIST A Standard and CIFAR10 A Standard on 100 samples each. For comparison, running DeepFool on ten 250-element batches takes approximately 10 seconds.

Overall, the attacks have a success rate of 0% - 3%. However, we find that increasing ε' (while keeping ε constant) increases the success rate, up to 100% for $\varepsilon' = 10 \cdot \varepsilon$. This suggests that as the difference between ε' and ε grows, so does the feasibility of fooling CA, which is consistent with our analysis. More in-depth results of our experiments can be found in Appendix L.

UG100 Dataset We collect all the adversarial examples found by both MIPVerify and the heuristic attacks into a new dataset, which we name UG100. UG100 can be used to benchmark new adversarial attacks. Specifically, we can determine how strong an attack is by comparing it to both the theoretical optimum and heuristic attack pools. Another potential application involves studying factors that affect whether adversarial attacks perform sub-optimally.

7   CONCLUSION

We proved that, for $p > 0$, attacking is NP-complete, while training a robust model is Σ_2^P-complete. We also provided an informal explanation for such a difference, finding three factors that contribute to the advantages attacks have over defenses. We then introduced Counter-Attack, a technique that can identify non-robust points in NP time. We showed that CA can provide robustness guarantees up to an arbitrary ε. We also showed that, for $\varepsilon' > \varepsilon$, fooling CA is Σ_2^P-complete, which represents a strong form of computational robustness. Finally, in an empirical evaluation we showed that, as long as the employed attacks have consistent performance, CA can reliably identify non-robust points.

CA relies on a very general property of adversarial attacks, i.e. the way they approximate the distance from the decision boundary. This makes the approach "future-proof": the method will benefit from further understanding of robustness and attacks. Due to its independence from the specific characteristics of the defended model, CA can also be applied to non-ML tools (e.g. signature-based malware detectors). We also believe that it should be possible to extend CA beyond classification.

Overall, we think that Counter-Attack represents an important step towards viewing adversarial attacks not as a threat to the robustness of models, but rather as a fundamental tool to build more robust models.

REPRODUCIBILITY

We provide all our code and data in the repository linked in Section 1. Additionally, we report the key reproducibility information in Section 6, while all the other information can be found in Appendices G and L. To ensure maximum reproducibility, we also used consistent seeds across all experiments (one for parameter tuning and one for actual experiments). We also made sure to only

rely on tools that are either open-source or for which there are free academic licenses. Concerning theoretical results, we provide full proofs of all theorems and corollaries in the appendices. Finally, for users with a slow internet connection, we also provide UG100 in JSON format (containing only the found adversarial distances).

REFERENCES

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning*, pp. 274–283. PMLR, 2018.

Pranjal Awasthi, Abhratanu Dutta, and Aravindan Vijayaraghavan. On robustness to adversarial examples and polynomial optimization. *Advances in Neural Information Processing Systems*, 32, 2019.

Wieland Brendel, Jonas Rauber, Matthias Kümmerer, Ivan Ustyuzhaninov, and Matthias Bethge. Accurate, reliable and fast robustness evaluation. *Advances in Neural Information Processing Systems*, 32, 2019.

Tom B Brown, Dandelion Mané, Aurko Roy, Martín Abadi, and Justin Gilmer. Adversarial patch. *arXiv preprint arXiv:1712.09665*, 2017.

Nicholas Carlini and David Wagner. Defensive distillation is not robust to adversarial examples. *arXiv preprint arXiv:1607.04311*, 2016.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pp. 3–14, 2017a.

Nicholas Carlini and David Wagner. Magnet and "efficient defenses against adversarial attacks" are not robust to adversarial examples. *arXiv preprint arXiv:1711.08478*, 2017b.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57. IEEE, 2017c.

Nicholas Carlini, Guy Katz, Clark Barrett, and David L Dill. Provably minimally-distorted adversarial examples. *arXiv preprint arXiv:1709.10207*, 2017.

Francesco Croce, Sven Gowal, Thomas Brunner, Evan Shelhamer, Matthias Hein, and Taylan Cemgil. Evaluating the adversarial robustness of adaptive test-time defenses. *arXiv preprint arXiv:2202.13711*, 2022.

Chen Dan, Yuting Wei, and Pradeep Ravikumar. Sharp statistical guaratees for adversarially robust gaussian classification. In *International Conference on Machine Learning*, pp. 2345–2355. PMLR, 2020.

Akshay Degwekar, Preetum Nakkiran, and Vinod Vaikuntanathan. Computational limitations in robust classification and win-win results. In *Conference on Learning Theory*, pp. 994–1028. PMLR, 2019.

Gavin Weiguang Ding, Luyu Wang, and Xiaomeng Jin. AdverTorch v0.1: An adversarial robustness toolbox based on pytorch. *arXiv preprint arXiv:1902.07623*, 2019.

Edgar Dobriban, Hamed Hassani, David Hong, and Alexander Robey. Provable tradeoffs in adversarially robust classification. *arXiv preprint arXiv:2006.05161*, 2020.

Tommaso Dreossi, Shromona Ghosh, Alberto Sangiovanni-Vincentelli, and Sanjit A Seshia. A formalization of robustness for deep neural networks. *arXiv preprint arXiv:1903.10033*, 2019.

Krishnamurthy Dvijotham, Robert Stanforth, Sven Gowal, Timothy A Mann, and Pushmeet Kohli. A dual approach to scalable verification of deep networks. In *UAI*, volume 1, pp. 3, 2018.

Reuben Feinman, Ryan R Curtin, Saurabh Shintre, and Andrew B Gardner. Detecting adversarial samples from artifacts. *arXiv preprint arXiv:1703.00410*, 2017.

Sanjam Garg, Somesh Jha, Saeed Mahloujifar, and Mahmoody Mohammad. Adversarially robust learning could leverage computational hardness. In *Algorithmic Learning Theory*, pp. 364–385. PMLR, 2020.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015. URL http://arxiv.org/abs/1412.6572.

Kathrin Grosse, Praveen Manoharan, Nicolas Papernot, Michael Backes, and Patrick McDaniel. On the (statistical) detection of adversarial examples. *arXiv preprint arXiv:1702.06280*, 2017.

Gurobi Optimization, LLC. Gurobi Optimizer Reference Manual, 2022. URL https://www.gurobi.com.

Husheng Han, Kaidi Xu, Xing Hu, Xiaobing Chen, Ling Liang, Zidong Du, Qi Guo, Yanzhi Wang, and Yunji Chen. Scalecert: Scalable certified defense against adversarial patches with sparse superficial layers. *Advances in Neural Information Processing Systems*, 34, 2021.

Warren He, James Wei, Xinyun Chen, Nicholas Carlini, and Dawn Song. Adversarial example defenses: ensembles of weak defenses are not strong. In *Proceedings of the 11th USENIX Conference on Offensive Technologies*, pp. 15–15, 2017.

Matthias Hein and Maksym Andriushchenko. Formal guarantees on the robustness of a classifier against adversarial manipulation. *Advances in Neural Information Processing Systems*, 30, 2017.

Dan Hendrycks and Kevin Gimpel. Early methods for detecting adversarial images. In *International Conference on Learning Representations (Workshop Track)*, 2017.

Hossein Hosseini, Sreeram Kannan, and Radha Poovendran. Are odds really odd? bypassing statistical detection of adversarial examples. *arXiv preprint arXiv:1907.12138*, 2019.

Guy Katz, Clark Barrett, David Dill, Kyle Julian, and Mykel Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. *arXiv preprint arXiv:1702.01135*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Roger Koenker and Gilbert Bassett Jr. Regression quantiles. *Econometrica: journal of the Econometric Society*, pp. 33–50, 1978.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. Technical report, 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. 2017.

Yann LeCun, Corinna Cortes, and Christopher J.C. Burges. The MNIST database of handwritten digits. http://yann.lecun.com/exdb/mnist/, 1998.

Klas Leino, Zifan Wang, and Matt Fredrikson. Globally-robust neural networks. In *International Conference on Machine Learning*, pp. 6212–6222. PMLR, 2021.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

Saeed Mahloujifar and Mohammad Mahmoody. Can adversarially robust learning leverage computational hardness? In *Algorithmic Learning Theory*, pp. 581–609. PMLR, 2019.

Dongyu Meng and Hao Chen. Magnet: a two-pronged defense against adversarial examples. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, pp. 135–147, 2017.

Yifei Min, Lin Chen, and Amin Karbasi. The curious case of adversarially robust models: More data can help, double descend, or hurt generalization. In *Uncertainty in Artificial Intelligence*, pp. 129–139. PMLR, 2021.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2574–2582, 2016.

Ambar Pal and René Vidal. A game theoretic analysis of additive adversarial attacks and defenses. *Advances in Neural Information Processing Systems*, 33:1345–1355, 2020.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pp. 506–519, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Rafael Pinot, Florian Yger, Cédric Gouy-Pailler, and Jamal Atif. A unified view on differential privacy and robustness to adversarial examples. *arXiv preprint arXiv:1906.07982*, 2019.

Muni Sreenivas Pydi and Varun Jog. The many faces of adversarial risk. *Advances in Neural Information Processing Systems*, 34, 2021.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. *arXiv preprint arXiv:1801.09344*, 2018.

Jonas Rauber, Roland Zimmermann, Matthias Bethge, and Wieland Brendel. Foolbox native: Fast adversarial attacks to benchmark the robustness of machine learning models in pytorch, tensorflow, and jax. *Journal of Open Source Software*, 5(53):2607, 2020.

Ambrish Rawat, Martin Wistuba, and Maria-Irina Nicolae. Adversarial phenomenon in the eyes of bayesian deep learning. *arXiv preprint arXiv:1711.08244*, 2017.

Jie Ren, Die Zhang, Yisen Wang, Lu Chen, Zhanpeng Zhou, Yiting Chen, Xu Cheng, Xin Wang, Meng Zhou, Jie Shi, et al. A unified game-theoretic interpretation of adversarial robustness. *arXiv preprint arXiv:2111.03536*, 2021.

Eitan Richardson and Yair Weiss. A bayes-optimal view on adversarial examples. *Journal of Machine Learning Research*, 22(221):1–28, 2021.

Kevin Roth, Yannic Kilcher, and Thomas Hofmann. The odds are odd: A statistical test for detecting adversarial examples. In *International Conference on Machine Learning*, pp. 5498–5507. PMLR, 2019.

Samuel Henrique Silva and Peyman Najafirad. Opportunities and challenges in deep learning adversarial robustness: A survey. *arXiv preprint arXiv:2007.00753*, 2020.

Gagandeep Singh, Timon Gehr, Matthew Mirman, Markus Püschel, and Martin Vechev. Fast and effective robustness certification. *Advances in Neural Information Processing Systems*, 31, 2018.

Aman Sinha, Hongseok Namkoong, Riccardo Volpi, and John Duchi. Certifying some distributional robustness with principled adversarial training. In *International Conference on Learning Representations*, 2018.

Min Jae Song, Ilias Zadik, and Joan Bruna. On the cryptographic hardness of learning single periodic neurons. *Advances in neural information processing systems*, 34:29602–29615, 2021.

Larry J Stockmeyer. The polynomial-time hierarchy. *Theoretical Computer Science*, 3(1):1–22, 1976.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Vincent Tjeng, Kai Y Xiao, and Russ Tedrake. Evaluating robustness of neural networks with mixed integer programming. In *International Conference on Learning Representations*, 2019.

Florian Tramèr, Jens Behrmann, Nicholas Carlini, Nicolas Papernot, and Jörn-Henrik Jacobsen. Fundamental tradeoffs between invariance and sensitivity to adversarial perturbations. In *International Conference on Machine Learning*, pp. 9561–9571. PMLR, 2020.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *Advances in Neural Information Processing Systems*, 33:1633–1645, 2020.

Guillaume Vidot, Paul Viallard, Amaury Habrard, and Emilie Morvant. A pac-bayes analysis of adversarial robustness. *arXiv preprint arXiv:2102.11069*, 2021.

Lily Weng, Huan Zhang, Hongge Chen, Zhao Song, Cho-Jui Hsieh, Luca Daniel, Duane Boning, and Inderjit Dhillon. Towards fast computation of certified robustness for relu networks. In *International Conference on Machine Learning*, pp. 5276–5285. PMLR, 2018a.

Tsui-Wei Weng, Huan Zhang, Pin-Yu Chen, Jinfeng Yi, Dong Su, Yupeng Gao, Cho-Jui Hsieh, and Luca Daniel. Evaluating the robustness of neural networks: An extreme value theory approach. In *International Conference on Learning Representations*, 2018b.

Daan Wierstra, Tom Schaul, Tobias Glasmachers, Yi Sun, Jan Peters, and Jürgen Schmidhuber. Natural evolution strategies. *The Journal of Machine Learning Research*, 15(1):949–980, 2014.

Zuxuan Wu, Ser-Nam Lim, Larry S Davis, and Tom Goldstein. Making an invisibility cloak: Real world adversarial attacks on object detectors. In *European Conference on Computer Vision*, pp. 1–17. Springer, 2020.

Kai Y Xiao, Vincent Tjeng, Nur Muhammad Shafiullah, and Aleksander Madry. Training for faster adversarial robustness verification via inducing relu stability. In *International Conference on Learning Representations*, 2019.

Yao-Yuan Yang, Cyrus Rashtchian, Hongyang Zhang, Russ R Salakhutdinov, and Kamalika Chaudhuri. A closer look at accuracy vs. robustness. In *Advances in Neural Information Processing Systems*, volume 33, pp. 8588–8601, 2020.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pp. 7472–7482. PMLR, 2019.

Jingfeng Zhang, Xilie Xu, Bo Han, Gang Niu, Lizhen Cui, Masashi Sugiyama, and Mohan Kankanhalli. Attacks which do not kill training make adversarial learning stronger. In *International Conference on Machine Learning*, pp. 11278–11287. PMLR, 2020.

Yan Zhou, Murat Kantarcioglu, and Bowei Xi. A survey of game theoretic approach for adversarial machine learning. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 9(3): e1259, 2019.

A PROOF PRELIMINARIES

A.1 NOTATION

We use f_i to denote the i-th output of a network. We define f as

$$f(\boldsymbol{x}) = \arg\max_i \{f_i(\boldsymbol{x})\} \tag{6}$$

for situations where multiple outputs are equal to the maximum, we use the class with the lowest index.

A.2 μ ARITHMETIC

Given two FSFP spaces X and X' with distance minorants μ and μ', we can compute new positive minorants after applying functions to the spaces as follows:

- Sum of two vectors: $\mu_{X+X'} = min(\mu, \mu')$;
- Multiplication by a constant: $\mu_{\alpha X} = \alpha\mu$;
- ReLU: $\mu_{ReLU(X)} = \mu$.

Since it is possible to compute the distance minorant of a space transformed by any of these functions in polynomial time, it is also possible to compute the distance minorant of a space transformed by any composition of such functions in polynomial time.

A.3 FUNCTIONS

We now provide an overview of several functions that can be obtained by using linear combinations and ReLUs.

max Carlini et al. (2017) showed that we can implement the max function using linear combinations and ReLUs as follows:

$$max(x, y) = ReLU(x - y) + y \tag{7}$$

We can also obtain an n-ary version of max by chaining multiple instances together.

$step$ If X is a FSFP space, then the following scalar function:

$$step_0(x) = \frac{1}{\mu} \left(ReLU(x) - ReLU(x - \mu) \right) \tag{8}$$

is such that $\forall i.\forall \boldsymbol{x} \in X$, $step_0(x_i)$ is 0 for $x_i \leq 0$ and 1 for $x_i > 0$.

Similarly, let $step_1$ be defined as follows:

$$step_1(x) = \frac{1}{\mu} \left(ReLU(x + \mu) - ReLU(x) \right) \tag{9}$$

Note that $\forall i.\forall \boldsymbol{x} \in X$, $step_1(x_i) = 0$ for $x_i < 0$ and $step_1(x_i) = 1$ for $x_i \geq 0$.

Boolean Functions   We then define the Boolean functions $not : \{0, 1\} \to \{0, 1\}$, $and : \{0, 1\}^2 \to \{0, 1\}$, $or : \{0, 1\}^2 \to \{0, 1\}$ and $if : \{0, 1\}^3 \to \{0, 1\}$ as follows:

$$not(x) = 1 - x \tag{10}$$
$$and(x, y) = step_1(x + y - 2) \tag{11}$$
$$or(x, y) = step_1(x + y) \tag{12}$$
$$if(a, b, c) = or(and(not(a), b), and(a, c)) \tag{13}$$

where $if(a, b, c)$ returns b if $a = 0$ and c otherwise.

Note that we can obtain n-ary variants of and and or by chaining multiple instances together.

cnf_3 Given a set $\boldsymbol{z} = \{\{z_{1,1}, \ldots, z_{1,3}\}, \ldots, \{z_{n,1}, z_{n,3}\}\}$ of Boolean atoms (i.e. $z_{i,j}(\boldsymbol{x}) = x_k$ or $\neg x_k$ for a certain k) defined on an n-long Boolean vector $\boldsymbol{x}$, $cnf_3(\boldsymbol{z})$ returns the following Boolean function:

$$cnf_3'(\boldsymbol{x}) = \bigwedge_{i=1,\ldots,n} \bigvee_{j=1,\ldots,3} z_{i,j}(\boldsymbol{x}) \tag{14}$$

We refer to $\boldsymbol{z}$ as a 3CNF formula.

Since cnf_3' only uses negation, conjunction and disjunction, it can be implemented using respectively neg, and and or. Note that, given $\boldsymbol{z}$, we can build cnf_3' in polynomial time w.r.t. the size of $\boldsymbol{z}$.

Comparison Functions We can use $step_0$, $step_1$ and neg to obtain comparison functions as follows:

$$geq(x, k) = step_1(x - k) \tag{15}$$
$$gt(x, k) = step_0(x, k) \tag{16}$$
$$leq(x, k) = not(gt(x, k)) \tag{17}$$
$$lt(x, k) = not(geq(x, k)) \tag{18}$$
$$eq(x, k) = and(geq(x, k), leq(x, k)) \tag{19}$$

Moreover, we define $open : \mathbb{R}^3 \to \{0, 1\}$ as follows:

$$open(x, a, b) = and(gt(x, a), lt(x, b)) \tag{20}$$

B PROOF OF THEOREM 1

B.1 $U\text{-}ATT_\infty \in NP$

To prove that $U\text{-}ATT_\infty \in NP$, we show that there exists a polynomial certificate for $U\text{-}ATT$ that can be checked in polynomial time. The certificate is the value of $\boldsymbol{x}'$, which will have a representation of the same size as $\boldsymbol{x}$ (due to the FSFP space assumption) and can be checked by verifying:

- $\|\boldsymbol{x} - \boldsymbol{x}'\|_\infty \leq \varepsilon$, which can be checked in linear time;
- $f_{\boldsymbol{\theta}}(\boldsymbol{x}') \neq f(\boldsymbol{x})$, which can be checked in polynomial time.

B.2 $U\text{-}ATT_\infty$ IS NP-HARD

We will prove that $U\text{-}ATT_\infty$ is NP-Hard by showing that $3SAT \leq U\text{-}ATT_\infty$.

Given a set of 3CNF clauses $\boldsymbol{z} = \{\{z_{11}, z_{12}, z_{13}\}, \ldots, \{z_{m1}, z_{m2}, z_{m3}\}\}$ defined on n Boolean variables $x_1, \ldots, x_n$, we construct the following query $q(\boldsymbol{z})$ for $U\text{-}ATT_\infty$:

$$q(\boldsymbol{z}) = \langle \boldsymbol{x}^{(s)}, \frac{1}{2}, f \rangle \tag{21}$$

where $\boldsymbol{x}^{(s)} = \left(\frac{1}{2}, \ldots, \frac{1}{2}\right)$ is a vector with n elements. Verifying $q(\boldsymbol{z}) \in U\text{-}ATT_\infty$ is equivalent to checking:

$$\exists \boldsymbol{x}' \in B_\infty \left(x_s, \frac{1}{2}\right) . f(\boldsymbol{x}') \neq f(\boldsymbol{x}^{(s)}) \tag{22}$$

Note that $\boldsymbol{x} \in B_\infty \left(\boldsymbol{x}^{(s)}, \frac{1}{2}\right)$ is equivalent to $\boldsymbol{x} \in [0, 1]^n$.

Truth Values We will encode the truth values of $\hat{\boldsymbol{x}}$ as follows:

$$x_i' \in \left[0, \frac{1}{2}\right] \iff \hat{x}_i = 0 \tag{23}$$

$$x_i' \in \left(\frac{1}{2}, 1\right] \iff \hat{x}_i = 1 \tag{24}$$

We can obtain the truth value of a scalar variable by using $isT(x_i) = gt\left(x_i, \frac{1}{2}\right)$. Let $bin(\boldsymbol{x}) = or(isT(x_1), \ldots, isT(x_n))$.

Definition of f We define f as follows:

$$f_1(\boldsymbol{x}) = and(not(isx^{(s)}(\boldsymbol{x})), cnf_3'(bin(\boldsymbol{x}))) \tag{25}$$
$$f_0(\boldsymbol{x}) = not(f_1(\boldsymbol{x})) \tag{26}$$

where $cnf_3' = cnf_3(z)$ and $isx^{(s)}$ is defined as follows:

$$isx^{(s)}(\boldsymbol{x}) = and\left(eq\left(x_1, \frac{1}{2}\right), \ldots, eq\left(x_n, \frac{1}{2}\right)\right) \tag{27}$$

Note that f is designed such that $f(\boldsymbol{x}^{(s)}) = 0$, while for $\boldsymbol{x}' \neq \boldsymbol{x}^{(s)}$, $f(\boldsymbol{x}') = 1$ iff the formula $\boldsymbol{z}$ is true for the variable assignment $bin(\boldsymbol{x}')$.

Lemma 1. $\boldsymbol{z} \in 3SAT \implies q(\boldsymbol{z}) \in U\text{-}ATT_\infty$

Proof. Let $\boldsymbol{z} \in 3SAT$. Therefore $\exists \boldsymbol{x}^* \in \{0,1\}^n$ such that $cnf_3(\boldsymbol{z})(\boldsymbol{x}^*) = 1$. Since $bin(\boldsymbol{x}^*) = \boldsymbol{x}^*$ and $\boldsymbol{x}^* \neq \boldsymbol{x}^{(s)}$, $f(\boldsymbol{x}^*) = 1$, which means that it is a valid solution for Equation (22). From this we can conclude that $q(\boldsymbol{z}) \in U\text{-}ATT_\infty$. $\square$

Lemma 2. $q(\boldsymbol{z}) \in U\text{-}ATT_\infty \implies \boldsymbol{z} \in 3SAT$

Proof. Since $q(\boldsymbol{z}) \in U\text{-}ATT_\infty$, $\exists \boldsymbol{x}^* \in [0,1]^n \setminus \{\boldsymbol{x}^{(s)}\}$ that is a solution to Equation (22) (i.e. $f(\boldsymbol{x}^*) = 1$). Then $cnf_3'(bin(\boldsymbol{x}^*)) = 1$, which means that there exists a $\hat{\boldsymbol{x}}$ (i.e. $bin(\boldsymbol{x}^*)$) such that $cnf_3'(\hat{\boldsymbol{x}}) = 1$. From this we can conclude that $\boldsymbol{z} \in 3SAT$. $\square$

Since:

- $q(\boldsymbol{z})$ can be computed in polynomial time;
- $\boldsymbol{z} \in 3SAT \implies q(\boldsymbol{z}) \in U\text{-}ATT_\infty$;
- $q(\boldsymbol{z}) \in U\text{-}ATT \implies \boldsymbol{z} \in 3SAT$.

we can conclude that $3SAT \leq U\text{-}ATT_\infty$.

B.3 PROOF OF COROLLARY 1.1

B.3.1 $U\text{-}ATT_p \in NP$

The proof is identical to the one for $U\text{-}ATT_\infty$.

B.3.2 $U\text{-}ATT_p$ IS NP-HARD

The proof that $q(\boldsymbol{z}) \in U\text{-}ATT_p \implies \boldsymbol{z} \in 3SAT$ is very similar to the one for $U\text{-}ATT_\infty$. Since $q(\boldsymbol{z}) \in U\text{-}ATT_p$, we know that $\exists \boldsymbol{x}^* \in B_p(\boldsymbol{x}^{(s)}, \varepsilon) \setminus \{\boldsymbol{x}^{(s)}\}.f(\boldsymbol{x}^*) = 1$, which means that there exists a $\hat{\boldsymbol{x}}$ (i.e. $bin(\boldsymbol{x}^*)$) such that $cnf_3'(\hat{\boldsymbol{x}}) = 1$. From this we can conclude that $\boldsymbol{z} \in 3SAT$.

The proof that $\boldsymbol{z} \in 3SAT \implies q(\boldsymbol{z}) \in U\text{-}ATT_p$ is slightly different, due to the fact that since $\boldsymbol{x}^* \notin B_p(\boldsymbol{x}^{(s)}, \frac{1}{2})$ we need to use a different input to prove that $\exists \boldsymbol{x}' \in B_p(\boldsymbol{x}^{(s)}).f(\boldsymbol{x}') = 1$.

Let $0 < p < \infty$. Given a positive integer n and a real $0 < p < \infty$, let $\rho_{p,n}(r)$ be a positive minorant of the L^∞ norm of a vector on the L^p sphere of radius r. For example, for $n = 2$, $p = 2$ and $r = 1$, any positive value less than or equal to $\frac{\sqrt{2}}{2}$ is suitable. Note that, for $0 < p < \infty$ and $n, r > 0$, $\rho_{p,n}(r) < r$.

Let $\boldsymbol{z} \in 3SAT$. Therefore $\exists \boldsymbol{x}^* \in \{0,1\}^n$ such that $cnf_3(\boldsymbol{z})(\boldsymbol{x}^*) = 1$. Let $\boldsymbol{x}^{**}$ be defined as:

$$x_i^{**} = \begin{cases} \frac{1}{2} - \rho_{p,n}\left(\frac{1}{2}\right) & x_i^* = 0 \\ \frac{1}{2} + \rho_{p,n}\left(\frac{1}{2}\right) & x_i^* = 1 \end{cases} \tag{28}$$

By construction, $\boldsymbol{x}^{**} \in B_p\left(\boldsymbol{x}^{(s)}, \rho_{p,n}\left(\frac{1}{2}\right)\right)$. Additionally, $bin(\boldsymbol{x}^{**}) = \boldsymbol{x}^*$, and since we know that $\boldsymbol{z}$ is true for the variable assignment $\boldsymbol{x}^*$, we can conclude that $f(\boldsymbol{x}^{**}) = 1$, which means that $\boldsymbol{x}^{**}$ is a valid solution for Equation (22). From this we can conclude that $q(\boldsymbol{z}) \in U\text{-}ATT_p$.

B.4 PROOF OF COROLLARY 1.2

The proof is identical to the proof of Theorem 1 (for $p = \infty$) and Corollary 1.1 (for $0 < p < \infty$), with the exception of requiring $f(\boldsymbol{x}') = 1$.

B.5 Proof of Corollary 1.3

The proof that attacking a polynomial-time classifier is in NP is the same as that for Theorem 1.

Attacking a polynomial-time classifier is NP-hard due to the fact that the ReLU networks defined in the proof of Theorem 1 are polynomial-time classifiers. Since attacking a general polynomial-time classifier is a generalization of attacking a ReLU polynomial-time classifier, the problem is NP-hard.

C Proof of Theorem 2

Proving that $U\text{-}ATT_p(f) \in NP^A$ means proving that it can be solved in polynomial time by a non-deterministic Turing machine with an oracle that can solve a problem in A. Since $Z_f \in A$, we can do so by picking a non-deterministic Turing machine with access to an oracle that solves Z_f. We then generate non-deterministically the adversarial example and return the output of the oracle. Due to the FSFP assumption, we know that the size of this input is the same as the size of the starting point, which means that it can be generated non-deterministically in polynomial time. Therefore, $U\text{-}ATT_p(f) \in NP^A$.

C.1 Proof of Corollary 2.1

Follows directly from Theorem 2 and the definition of Σ_n^P.

D Proof of Theorem 3

D.1 Preliminaries

$\Pi_2^P 3SAT$ is the set of all $\boldsymbol{z}$ such that:

$$\forall \hat{\boldsymbol{x}} \exists \hat{\boldsymbol{y}}.R(\hat{\boldsymbol{x}}, \hat{\boldsymbol{y}}) \tag{29}$$

where $R(\hat{\boldsymbol{x}}, \hat{\boldsymbol{y}}) = cnf_3(\boldsymbol{z})(\hat{x}_1, \ldots, \hat{x}_n, \hat{y}_1, \ldots, \hat{y}_n)$.

Stockmeyer (1976) showed that $\Pi_2 3SAT$ is Π_2^P-complete. Therefore, $co\Pi_2 3SAT$, which is defined as the set of all $\boldsymbol{z}$ such that:

$$\exists \hat{\boldsymbol{x}} \forall \hat{\boldsymbol{y}} \neg R(\hat{\boldsymbol{x}}, \hat{\boldsymbol{y}}) \tag{30}$$

is Σ_2^P-complete.

D.2 $PL\text{-}ROB_\infty \in \Sigma_2^P$

$PL\text{-}ROB_\infty \in \Sigma_2^P$ if there exists a problem $A \in P$ and a polynomial q such that $\forall \Gamma = \langle \boldsymbol{x}, \varepsilon, f_{\boldsymbol{\theta}}, v_f \rangle$:

$$\Gamma \in PL\text{-}ROB \iff \exists \boldsymbol{y}.|\boldsymbol{y}| \leq q(|\Gamma|) \wedge (\forall \boldsymbol{z}.(|\boldsymbol{z}| \leq q(|\Gamma|) \implies \langle \Gamma, \boldsymbol{y}, \boldsymbol{z} \rangle \in A)) \tag{31}$$

This can be proven by setting $\boldsymbol{y} = \boldsymbol{\theta}'$, $\boldsymbol{z} = \boldsymbol{x}'$ and A as the set of triplets $\langle \Gamma, \boldsymbol{\theta}', \boldsymbol{x}' \rangle$ such that all of the following are true:

- $v_f(\boldsymbol{\theta}') = 1$;
- $\|\boldsymbol{x} - \boldsymbol{x}'\|_\infty \leq \varepsilon$;
- $f_{\boldsymbol{\theta}}(\boldsymbol{x}) = f_{\boldsymbol{\theta}}(\boldsymbol{x}')$.

Since all properties can be checked in polynomial time, $A \in P$ and thus $PL\text{-}ROB_\infty \in \Sigma_2^P$.

D.3 $PL\text{-}ROB_\infty$ is Σ_2^P-Hard

We will prove that $PL\text{-}ROB_\infty$ is Σ_2^P-hard by showing that $co\Pi_2 3SAT \leq PL\text{-}ROB_\infty$.

Let $n_{\hat{\boldsymbol{x}}}$ be the length of $\hat{\boldsymbol{x}}$ and let $n_{\hat{\boldsymbol{y}}}$ be the length of $\hat{\boldsymbol{y}}$.

Given a set $\boldsymbol{z}$ of 3CNF clauses, we construct the following query $q(\boldsymbol{z})$ for $PL\text{-}ROB$:

$$q(\boldsymbol{z}) = \langle \boldsymbol{x}^{(s)}, \frac{1}{2}, f_{\boldsymbol{\theta}}, v_f \rangle \tag{32}$$

where $\boldsymbol{x}^{(s)} = \left(\frac{1}{2}, \ldots, \frac{1}{2}\right)$ is a vector with $n_{\hat{\boldsymbol{y}}}$ elements and $v_f(\boldsymbol{\theta}) = 1 \iff \boldsymbol{\theta} \in \{0,1\}^{n_{\hat{\boldsymbol{x}}}}$. Note that $\boldsymbol{\theta}' \in \{0,1\}^{n_{\hat{\boldsymbol{x}}}}$ can be checked in polynomial time w.r.t. the size of the input.

Truth Values   We will encode the truth values of $\hat{\boldsymbol{x}}$ as a set of binary parameters $\boldsymbol{\theta}'$, while we will encode the truth values of $\hat{\boldsymbol{y}}$ using $\boldsymbol{x}'$ through the same technique mentioned in Appendix B.2.

Definition of $f_{\boldsymbol{\theta}}$ We define $f_{\boldsymbol{\theta}}$ as follows:

- $f_{\boldsymbol{\theta},1}(\boldsymbol{x}) = and(not(isx^{(s)}(\boldsymbol{x})), cnf_3''(\boldsymbol{\theta}, \boldsymbol{x}))$, where cnf_3'' is defined over $\boldsymbol{\theta}$ and $bin(\boldsymbol{x})$ using the same technique mentioned in Appendix B.2 and $isx^{(s)}(\boldsymbol{x}) = and_{i=1,\ldots,n} eq(x_i, \frac{1}{2})$;
- $f_{\boldsymbol{\theta},0}(\boldsymbol{x}) = not(f_{\boldsymbol{\theta},1}(\boldsymbol{x}))$.

Note that $f_{\boldsymbol{\theta}}(\boldsymbol{x}^{(s)}) = 0$ for all choices of $\boldsymbol{\theta}$. Additionally, $f_{\boldsymbol{\theta}}$ is designed such that:

$$\forall \boldsymbol{x}' \in B_\infty \left(\boldsymbol{x}^{(s)}, \frac{1}{2}\right) \setminus \{\boldsymbol{x}^{(s)}\}. \forall \boldsymbol{\theta}'. (v_f(\boldsymbol{\theta}') = 1 \implies (f_{\boldsymbol{\theta}'}(\boldsymbol{x}') = 1 \iff R(\boldsymbol{\theta}', bin(\boldsymbol{x}')))) \tag{33}$$

Lemma 3. $\boldsymbol{z} \in co\Pi_2 3SAT \implies q(\boldsymbol{z}) \in PL\text{-}ROB_\infty$

Proof. Since $\boldsymbol{z} \in co\Pi_2 3SAT$, there exists a Boolean vector $\boldsymbol{x}^*$ such that $\forall \hat{\boldsymbol{y}}. \neg R(\boldsymbol{x}^*, \hat{\boldsymbol{y}})$.

Then both of the following statements are true:

- $v_f(\boldsymbol{x}^*) = 1$, since $\boldsymbol{x}^* \in \{0,1\}^{n_{\hat{\boldsymbol{x}}}}$;
- $\forall \boldsymbol{x}' \in B_\infty(\boldsymbol{x}^{(s)}, \varepsilon). f_{\boldsymbol{x}^*}(\boldsymbol{x}') = 0$, since $f_{\boldsymbol{x}^*}(\boldsymbol{x}') = 1 \iff R(\boldsymbol{x}^*, bin(\boldsymbol{x}'))$;

Therefore, $\boldsymbol{x}^*$ is a valid solution for Equation (3) and thus $q(\boldsymbol{z}) \in PL\text{-}ROB_\infty$. $\square$

Lemma 4. $q(\boldsymbol{z}) \in PL\text{-}ROB_\infty \implies \boldsymbol{z} \in co\Pi_2 3SAT$

Proof. Since $q(\boldsymbol{z}) \in PL\text{-}ROB_\infty$, there exists a $\boldsymbol{\theta}^*$ such that:

$$v_f(\boldsymbol{\theta}) = 1 \wedge \forall \boldsymbol{x}' \in B_\infty(\boldsymbol{x}^{(s)}, \varepsilon). f_{\boldsymbol{\theta}^*}(\boldsymbol{x}') = f_{\boldsymbol{\theta}^*}(\boldsymbol{x}^{(s)}) \tag{34}$$

Note that $\boldsymbol{\theta}^* \in \{0,1\}^{n_{\hat{\boldsymbol{x}}}}$, since $v_f(\boldsymbol{\theta}^*) = 1$. Moreover, $\forall \hat{\boldsymbol{y}}. \neg R(\boldsymbol{\theta}^*, \hat{\boldsymbol{y}})$, since $bin(\hat{\boldsymbol{y}}) = \hat{\boldsymbol{y}}$ and $f_{\boldsymbol{\theta}^*}(\hat{\boldsymbol{y}}) = 1 \iff R(\boldsymbol{\theta}^*, \hat{\boldsymbol{y}})$.

Therefore, $\boldsymbol{\theta}^*$ is a valid solution for Equation (30), which implies that $\boldsymbol{z} \in co\Pi_2 3SAT$.

$\square$

Since:

- $q(\boldsymbol{z})$ can be computed in polynomial time;
- $\boldsymbol{z} \in co\Pi_2 3SAT \implies q(\boldsymbol{z}) \in PL\text{-}ROB_\infty$;
- $q(\boldsymbol{z}) \in PL\text{-}ROB_\infty \implies \boldsymbol{z} \in co\Pi_2 3SAT$.

we can conclude that $co\Pi_2 3SAT \leq PL\text{-}ROB_\infty$.

D.4   Proof of Corollary 3.1

D.4.1 $PL\text{-}ROB_p \in \Sigma_2^P$

The proof is identical to the one for $PL\text{-}ROB_\infty$.

D.4.2 $PL\text{-}ROB_p$ IS Σ_2^P-HARD

We follow the same approach used in the proof for Corollary 1.1.

Proof of $q(z) \in PL\text{-}ROB_p \implies z \in co\Pi_2 3SAT$ If $q(z) \in PL\text{-}ROB_p$, it means that $\exists \boldsymbol{\theta}^*. \left(v_f(\boldsymbol{\theta}^*) = 1 \implies \forall \boldsymbol{x}' \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right). f(\boldsymbol{x}') = 0 \right)$. Then $\forall \hat{\boldsymbol{y}}$, there exists a corresponding input $\boldsymbol{y}^{**} \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right)$ defined as follows:

$$y_i^{**} = \begin{cases} \frac{1}{2} - \rho_{p,n} \left(\frac{1}{2} \right) & \hat{y}_i = 0 \\ \frac{1}{2} + \rho_{p,n} \left(\frac{1}{2} \right) & \hat{y}_i = 1 \end{cases} \tag{35}$$

such that $e^{(y)}(y^{**}) = \hat{y}$. Since $\boldsymbol{y}^{**} \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right)$, $cnf_3''(\boldsymbol{\theta}^*, bin(\boldsymbol{y}^{**})) = 0$, which means that $R(\boldsymbol{\theta}^*, \hat{\boldsymbol{y}})$ is false. In other words, $\exists \boldsymbol{\theta}^*. \forall \hat{\boldsymbol{y}}. \neg R(\boldsymbol{\theta}^*, \hat{\boldsymbol{y}})$, i.e. $\boldsymbol{z} \in co\Pi_2 3SAT$.

Proof of $z \in co\Pi_2 3SAT \implies q(z) \in PL\text{-}ROB_p$ The proof is very similar to the corresponding one for Theorem 3.

If $\boldsymbol{z} \in co\Pi_2 3SAT$, then $\exists \hat{\boldsymbol{x}}^*. \forall \hat{\boldsymbol{y}}. \neg R(\hat{\boldsymbol{x}}, \hat{\boldsymbol{y}})$. Set $\boldsymbol{\theta}^* = \hat{\boldsymbol{x}}^*$. We know that $f_{\boldsymbol{\theta}}^*(\boldsymbol{x}^{(s)}) = 0$. We also know that $\forall \boldsymbol{x}' \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right) \setminus \{\boldsymbol{x}^{(s)}\}. (f_{\boldsymbol{\theta}^*}(\boldsymbol{x}) = 1 \iff cnf_3''(\boldsymbol{\theta}^*, \boldsymbol{x}') = 1)$. In other words, $\forall \boldsymbol{x}' \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right) \setminus \{\boldsymbol{x}^{(s)}\}. (f_{\boldsymbol{\theta}^*}(\boldsymbol{x}') = 1 \iff R(\boldsymbol{\theta}^*, bin(\boldsymbol{x}')))$. Since $R(\boldsymbol{\theta}^*, \hat{\boldsymbol{y}})$ is false for all choices of $\hat{\boldsymbol{y}}$, $\forall \boldsymbol{x}' \in B_p \left(\boldsymbol{x}^{(s)}, \frac{1}{2} \right) \setminus \{\boldsymbol{x}^{(s)}\}. f_{\boldsymbol{\theta}^*}(\boldsymbol{x}') = 0$. Given the fact that $f_{\boldsymbol{\theta}^*}(\boldsymbol{x}^{(s)}) = 0$, we can conclude that $\boldsymbol{\theta}^*$ satisfies Equation (3).

D.5 PROOF OF COROLLARY 3.2

Similarly to the proof of Corollary 1.3, it follows from the fact that ReLU classifiers are polynomial-time classifiers (w.r.t. the size of the tuple).

E PROOF OF THEOREM 4

There are two cases:

- $\forall \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon). f(\boldsymbol{x}') = f(\boldsymbol{x})$: then the attack fails because $f(\boldsymbol{x}) \notin C(\boldsymbol{x})$;
- $\exists \boldsymbol{x}' \in B_p(\boldsymbol{x}, \varepsilon). f(\boldsymbol{x}') \neq f(\boldsymbol{x})$: then due to the symmetry of the L^p norm $\boldsymbol{x} \in B_p(\boldsymbol{x}', \varepsilon)$. Since $f(\boldsymbol{x}) \neq f(\boldsymbol{x}')$, $\boldsymbol{x}$ is a valid adversarial example for $\boldsymbol{x}'$, which means that $f(\boldsymbol{x}') = \star$. Since $\star \notin C(\boldsymbol{x})$, the attack fails.

E.1 PROOF OF COROLLARY 4.1

Assume that $\forall \boldsymbol{x}. ||\boldsymbol{x}||_r \geq \eta ||\boldsymbol{x}||_p$ and fix $\boldsymbol{x}^{(s)} \in X$. Let $\boldsymbol{x}' \in B_r(\boldsymbol{x}^{(s)}, \eta \varepsilon)$ be an adversarial example. Then $||\boldsymbol{x}' - \boldsymbol{x}^{(s)}||_r \leq \eta \varepsilon$, and thus $\eta ||\boldsymbol{x}' - \boldsymbol{x}^{(s)}||_p \leq \eta \varepsilon$. Dividing by η, we get $||\boldsymbol{x}' - \boldsymbol{x}^{(s)}||_p \leq \varepsilon$, which means that $\boldsymbol{x}^{(s)}$ is a valid adversarial example for $\boldsymbol{x}'$ and thus $\boldsymbol{x}'$ is rejected by p-CA.

We now proceed to find the values of η.

E.1.1 $1 \leq r < p$

We will prove that $||\boldsymbol{x}||_r \geq ||\boldsymbol{x}||_p$.

Case $p < \infty$ Consider $\boldsymbol{e} = \frac{\boldsymbol{x}}{||\boldsymbol{x}||_p}$. $\boldsymbol{e}$ is such that $||\boldsymbol{e}||_p = 1$ and for all i we have $|e_i| \leq 1$. Since $r < p$, for all $0 \leq t \leq 1$ we have $|t|^p \leq |t|^r$. Therefore:

$$||\boldsymbol{e}||_r = \left(\sum_{i=1}^n |e_i|^r \right)^{1/r} \geq \left(\sum_{i=1}^n |e_i|^p \right)^{1/r} = ||\boldsymbol{e}||_p^{p/r} = 1 \tag{36}$$

Then, since $||\boldsymbol{e}||_r \geq 1$:

$$||\boldsymbol{x}||_r = || \, ||\boldsymbol{x}||_p \boldsymbol{e} ||_r = ||\boldsymbol{x}||_p ||\boldsymbol{e}||_r \geq ||\boldsymbol{x}||_p \tag{37}$$

Case $p = \infty$ Since $||\boldsymbol{x}||_r \geq ||\boldsymbol{x}||_p$ for all $r < p$ and since the expressions on both sides of the inequality are compositions of continuous functions, as $p \to \infty$ we get $||\boldsymbol{x}||_r \geq ||\boldsymbol{x}||_\infty$.

E.1.2 $r > p$

We will prove that $||\boldsymbol{x}||_r \geq n^{\frac{1}{r} - \frac{1}{p}} ||\boldsymbol{x}||_p$.

Case $r < \infty$ Hölder's inequality states that, given $\alpha, \beta \geq 1$ such that $\frac{1}{\alpha} + \frac{1}{\beta} = 1$ and given f and g, we have:

$$||fg||_1 \leq ||f||_\alpha ||g||_\beta \tag{38}$$

Setting $\alpha = \frac{r}{r-p}$, $\beta = \frac{r}{p}$, $f = (1, \ldots, 1)$ and $g = (x_1^p, \ldots, x_n^p)$, we know that:

- $||fg||_1 = \sum_{i=1}^{n}(1 \cdot x_i^p) = ||\boldsymbol{x}||_p^p$;
- $||f||_\alpha = \left(\sum_{i=1}^{n} 1\right)^{1/\alpha} = n^{1/\alpha}$;
- $||g||_\beta = \left(\sum_{i} x_i^{pr/p}\right)^{p/r} = \left(\sum_{i} x_i^r\right)^{p/r} = ||\boldsymbol{x}||_r^p$.

Therefore $||\boldsymbol{x}||_p^p \leq n^{1/\alpha} ||\boldsymbol{x}||_r^p$. Raising both sides to the power of $1/p$, we get $||\boldsymbol{x}||_p \leq n^{1/(p\alpha)} ||\boldsymbol{x}||_r$. Therefore:

$$||\boldsymbol{x}||_p \leq n^{(r-p)/(pr)} ||\boldsymbol{x}||_r = n^{\frac{1}{p} - \frac{1}{r}} ||\boldsymbol{x}||_r \tag{39}$$

Dividing by $n^{\frac{1}{p} - \frac{1}{r}}$ we get:

$$n^{\frac{1}{r} - \frac{1}{p}} ||\boldsymbol{x}||_p \leq ||\boldsymbol{x}||_r \tag{40}$$

Case $r = \infty$ Since the expressions on both sides of the inequality are compositions of continuous functions, as $r \to \infty$ we get $||\boldsymbol{x}||_\infty \geq n^{-\frac{1}{p}} ||x||_p$.

F   PROOF OF THEOREM 5

F.1 $CCA_\infty \in \Sigma_2^P$

$CCA_\infty \in \Sigma_2^P$ iff there exists a problem $A \in P$ and a polynomial p such that $\forall \Gamma = \langle \boldsymbol{x}, \varepsilon, \varepsilon', C, f \rangle$:

$$\Gamma \in CCA_\infty \iff \exists \boldsymbol{y}.|\boldsymbol{y}| \leq p\left(|\Gamma|\right) \wedge (\forall \boldsymbol{z}.(|\boldsymbol{z}| \leq p(|\Gamma|) \implies \langle \Gamma, \boldsymbol{y}, \boldsymbol{z} \rangle \in A)) \tag{41}$$

This can be proven by setting $\boldsymbol{y} = \boldsymbol{x}'$, $\boldsymbol{z} = \boldsymbol{x}''$ and A as the set of all triplets $\langle \Gamma, \boldsymbol{x}', \boldsymbol{x}'' \rangle$ such that all of the following are true:

- $||\boldsymbol{x} - \boldsymbol{x}'||_\infty \leq \varepsilon'$
- $f(\boldsymbol{x}') \in C(\boldsymbol{x})$
- $||\boldsymbol{x}'' - \boldsymbol{x}'||_\infty \leq \varepsilon$
- $f(\boldsymbol{x}'') = f(\boldsymbol{x}')$

Since all properties can be checked in polynomial time, $A \in P$.

F.2 CCA_∞ IS Σ_2^P-HARD

We will show that CCA_∞ is Σ_2^P-hard by proving that $co\Pi_2 3SAT \leq CCA_\infty$.

First, suppose that the length of $\hat{\boldsymbol{x}}$ and $\hat{\boldsymbol{y}}$ differ. In that case, we pad the shortest one with additional variables that will not be used.

Let n be the maximum of the lengths of $\hat{\boldsymbol{x}}$ and $\hat{\boldsymbol{y}}$.

Given a set $\boldsymbol{z}$ of 3CNF clauses, we construct the following query $q(\boldsymbol{z})$ for CCA_∞:

$$q(\boldsymbol{z}) = \langle \boldsymbol{x}^{(s)}, \gamma, \frac{1}{2}, C_u, h \rangle \tag{42}$$

where $\frac{1}{4} < \gamma < \frac{1}{2}$ and $\boldsymbol{x}^{(s)} = \left(\frac{1}{2}, \dots, \frac{1}{2}\right)$ is a vector with n elements. Verifying $q(\boldsymbol{z}) \in CCA_\infty$ is equivalent to checking:

$$\exists \boldsymbol{x}' \in B\left(x_s, \frac{1}{2}\right) . \left(h(\boldsymbol{x}') \neq h(\boldsymbol{x}) \wedge \left(\forall \boldsymbol{x}'' \in B\left(\boldsymbol{x}', \frac{1}{4}\right) . h(\boldsymbol{x}'') = h(\boldsymbol{x}')\right)\right) \tag{43}$$

Note that $\boldsymbol{x}' \in [0,1]^n$.

Truth Values We will encode the truth values of $\hat{\boldsymbol{x}}$ and $\hat{\boldsymbol{y}}$ as follows:

$$
\begin{aligned}
x_i'' \in \left(0, \frac{1}{4}\right) &\iff \hat{x}_i = 0 \wedge \hat{y}_i = 0 \\
x_i'' \in \left(\frac{1}{4}, \frac{1}{2}\right) &\iff \hat{x}_i = 0 \wedge \hat{y}_i = 1 \\
x_i'' \in \left(\frac{1}{2}, \frac{3}{4}\right) &\iff \hat{x}_i = 1 \wedge \hat{y}_i = 0 \\
x_i'' \in \left(\frac{3}{4}, 1\right) &\iff \hat{x}_i = 1 \wedge \hat{y}_i = 1
\end{aligned}
\tag{44}
$$

Let $e_{\hat{x}i}(\boldsymbol{x}) = gt\left(x_i, \frac{1}{2}\right)$. Let:

$$e_{\hat{y}i}(\boldsymbol{x}) = or\left(open\left(x_i, \frac{1}{4}, \frac{1}{2}\right), open\left(x_i, \frac{3}{4}, 1\right)\right) \tag{45}$$

Note that $e_{\hat{x}i}(x_i'')$ returns the truth value of $\hat{x}_i$ and $e_{\hat{y}i}(x_i'')$ returns the truth value of $\hat{y}_i$ (as long as the input is within one of the ranges described in Equation (44)).

Invalid Encodings All the encodings other than the ones described in Equation (44) are not valid. We define inv_F as follows:

$$inv_F(\boldsymbol{x}) = or_{i=1,\dots,n} or(out(x_i), edge(x_i)) \tag{46}$$

where $out(x_i) = or(leq(x_i, 0), geq(x_i, 1))$ and

$$edge(x_i) = or\left(eq\left(x_i, \frac{1}{4}\right), eq\left(x_i, \frac{1}{2}\right), eq\left(x_i, \frac{3}{4}\right)\right) \tag{47}$$

On the other hand, we define inv_T as follows:

$$inv_T(\boldsymbol{x}) = or_{i=1,\dots,n} eq\left(x_i, \frac{1}{2}\right) \tag{48}$$

Definition of h Let g be a Boolean formula defined over $e^{(x)}(\boldsymbol{x})$ and $e^{(y)}(\boldsymbol{x})$ that returns the value of R (using the same technique as cnf_3').

We define h as a two-class classifier, where:

$$h_1(\boldsymbol{x}) = or(inv_T(\boldsymbol{x}), and(not(inv_F(\boldsymbol{x})), g(\boldsymbol{x}))) \tag{49}$$

and $h_0(\boldsymbol{x}) = not(h_1(\boldsymbol{x}))$.

Note that:

- If $x_i = \frac{1}{2}$ for some i, the top class is 1; therefore, $h(\boldsymbol{x}^{(s)}) = 1$;
- Otherwise, if $\boldsymbol{x}$ is not a valid encoding, the top class is 0;
- Otherwise, the top class is 1 if $R(e^{(x)}(\boldsymbol{x}), e^{(y)}(\boldsymbol{x}))$ is true and 0 otherwise.

Lemma 5. $\boldsymbol{z} \in co\Pi_2 3SAT \implies q(\boldsymbol{z}) \in CCA_\infty$

Proof. If $\boldsymbol{z} \in co\Pi_2 3SAT$, then there exists a Boolean vector $\boldsymbol{x}^*$ such that $\forall \hat{\boldsymbol{y}}. \neg R(\boldsymbol{x}^*, \hat{\boldsymbol{y}})$.

We now prove that setting $\boldsymbol{x}' = \boldsymbol{x}^*$ satisfies Equation (5). First, note that $h(\boldsymbol{x}^*) = 0$, which satisfies $h(\boldsymbol{x}') \neq h(\boldsymbol{x})$. Then we need to verify that $\forall \boldsymbol{x}'' \in B_\infty(\boldsymbol{x}^*, \gamma). h(\boldsymbol{x}) = 0$.

For every $\boldsymbol{x}'' \in B_\infty(\boldsymbol{x}^*, \gamma)$, we know that $\boldsymbol{x}'' \in ([-\gamma, \gamma] \cup [1 - \gamma, 1 + \gamma])^n$. There are thus two cases:

- $\boldsymbol{x}''$ is not a valid encoding, i.e. $x_i'' \leq 0 \vee x_i'' \geq 1 \vee x_i'' \in \left\{ \frac{1}{4}, \frac{3}{4} \right\}$ for some i. Then $h(\boldsymbol{x}'') = 0$. Note that, since $\gamma < \frac{1}{2}$, $\frac{1}{2} \notin [-\gamma, \gamma] \cup [1 - \gamma, 1 + \gamma]$, so it is not possible for $\boldsymbol{x}''$ to be an invalid encoding that is classified as 1;

- $\boldsymbol{x}''$ is a valid encoding. Then, since $\gamma < \frac{1}{2}$, $e^{(x)}(\boldsymbol{x}'') = \boldsymbol{x}^*$. Since $h(\boldsymbol{x}'') = 1$ iff $R(e^{(x)}(\boldsymbol{x}''), e^{(y)}(\boldsymbol{x}''))$ is true and since $R(\boldsymbol{x}^*, \hat{\boldsymbol{y}})$ is false for all choices of $\hat{\boldsymbol{y}}$, $h(\boldsymbol{x}'') = 0$.

Therefore, $\boldsymbol{x}^*$ satisfies Equation (43) and thus $q(\boldsymbol{z}) \in CCA_\infty$.

$\square$

Lemma 6. $q(\boldsymbol{z}) \in CCA_\infty \implies \boldsymbol{z} \in co\Pi_2 3SAT$

Proof. Since $q(\boldsymbol{z}) \in CCA$, there exists a $\boldsymbol{x}^* \in B\left(\boldsymbol{x}^{(s)}, \frac{1}{2}\right)$ such that $h(\boldsymbol{x}^*) \neq h(\boldsymbol{x}^{(s)})$ and $\forall \boldsymbol{x}'' \in B_\infty(\boldsymbol{x}^*, \gamma). h(\boldsymbol{x}'') = h(\boldsymbol{x}')$. We will prove that $e^{(x)}(\boldsymbol{x}^*)$ is a solution to $co\Pi_2 3SAT$.

Since $h(\boldsymbol{x}^{(s)}) = 1$, $h(\boldsymbol{x}^*) = 0$, which means that $\forall \boldsymbol{x}'' \in B_\infty(\boldsymbol{x}^*, \gamma). h(\boldsymbol{x}'') = 0$.

We know that $\boldsymbol{x}^* \in B_\infty\left(\boldsymbol{x}^{(s)}, \frac{1}{2}\right) = [0, 1]^n$. We first prove by contradiction that $\boldsymbol{x}^* \in \left([0, \frac{1}{2} - \gamma] \cup (\frac{1}{2} + \gamma, 1]\right)^n$. If $x_i^* \in [\frac{1}{2} - \gamma, \frac{1}{2} + \gamma]$ for some i, then the vector $\boldsymbol{x}^{(w)}$ defined as follows:

$$x_j^{(w)} = \begin{cases} \frac{1}{2} & i = j \\ x_i^* & \text{otherwise} \end{cases} \tag{50}$$

is such that $\boldsymbol{x}^{(w)} \in B_\infty(x_i^*, \gamma)$ and $h\left(\boldsymbol{x}^{(w)}\right) = 1$ (since $inv_T\left(\boldsymbol{x}^{(w)}\right) = 1$). This contradicts the fact that $\forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma). h(\boldsymbol{x}) = 0$. Therefore, $\boldsymbol{x}^* \in \left([0, \frac{1}{2} - \gamma] \cup (\frac{1}{2} + \gamma, 1]\right)^n$.

As a consequence, $\forall \boldsymbol{x}'' \in B_\infty(\boldsymbol{x}^*, \gamma). e^{(x)}(\boldsymbol{x}'') = e^{(x)}(\boldsymbol{x}^*)$.

We now prove that $\forall \hat{\boldsymbol{y}}^*. \exists \boldsymbol{x}''^* \in B_\infty(\boldsymbol{x}^*, \gamma)$ such that $e^{(y)}(\boldsymbol{x}''^*) = \hat{\boldsymbol{y}}^*$. We can construct such $\boldsymbol{x}''^*$ as follows. For every i:

- If $e^{(x)}(\boldsymbol{x}^*) = 0$ and $e^{(y)}(\boldsymbol{x}^*) = 0$, set $\boldsymbol{x}_i''^*$ equal to a value in $\left(0, \frac{1}{4}\right)$;

- If $e^{(x)}(\boldsymbol{x}^*) = 0$ and $e^{(y)}(\boldsymbol{x}^*) = 1$, set $\boldsymbol{x}_i''^*$ equal to a value in $\left(\frac{1}{4}, \gamma\right)$;

- If $e^{(x)}(\boldsymbol{x}^*) = 1$ and $e^{(y)}(\boldsymbol{x}^*) = 0$, set $\boldsymbol{x}_i''^*$ equal to a value in $\left(1 - \gamma, \frac{3}{4}\right)$;

- If $e^{(x)}(\boldsymbol{x}^*) = 1$ and $e^{(y)}(\boldsymbol{x}^*) = 1$, set $\boldsymbol{x}_i''^*$ equal to a value in $\left(\frac{3}{4}, 1\right)$.

By doing so, we have obtained a $\boldsymbol{x}''^*$ such that $\boldsymbol{x}''^* \in B_\infty(\boldsymbol{x}^*, \gamma)$ and $e^{(y)}(\boldsymbol{x}''^*) = \hat{\boldsymbol{y}}^*$.

Since:

- $e^{(x)}(\boldsymbol{x}'') = e^{(x)}(\boldsymbol{x}^*)$ for all $\boldsymbol{x}''$;

- $h(\boldsymbol{x}'') = 0$ for all $\boldsymbol{x}''$;

- $h(\boldsymbol{x}'') = 1$ iff $R(e^{(x)}(\boldsymbol{x}'')), e^{(y)}(\boldsymbol{x}''))$ is true;

$R(e^{(x)}(\boldsymbol{x}^*), \hat{\boldsymbol{y}}^*)$ is false for all choices of $\hat{\boldsymbol{y}}^*$. In other words, $\hat{\boldsymbol{x}}^*$ is a solution to Equation (30) and thus $\boldsymbol{z} \in co\Pi_2 3SAT$.

$\square$

Since:

- $q(\boldsymbol{z})$ can be computed in polynomial time;
- $\boldsymbol{z} \in co\Pi_2 3SAT \implies q(\boldsymbol{z}) \in CCA_\infty$;
- $q(\boldsymbol{z}) \in CCA_\infty \implies \boldsymbol{z} \in co\Pi_2 3SAT$;

we can conclude that $co\Pi_2 3SAT \leq CCA$.

F.3 PROOF OF COROLLARY 5.1

The proof of $CCA_p \in \Sigma_2^P$ is the same as the one for Theorem 5.

For the hardness proof, we follow a more involved approach compared to those for Corollaries 1.1 and 3.1.

First, let $\varepsilon_{\rho_{p,n}}$ be the value of epsilon such that $\rho_{p,n}\left(\varepsilon_{\rho_{p,n}}\right) = \frac{1}{2}$. In other words, $B_p(\boldsymbol{x}^{(s)}, \varepsilon_{\rho_{p,n}})$ is an L^p ball that contains $[0,1]^n$, while the intersection of the corresponding L^p sphere and $[0,1]^n$ is the set $\{0,1\}^n$ (for $p < \infty$).

Let $inv'_T(\boldsymbol{x})$ be defined as follows:

$$inv'_T(\boldsymbol{x}) = or_{i=1,\ldots,n}\left(or\left(eq\left(x_i, \frac{1}{2}\right), leq(x_i, 0), geq(x_i, 1)\right)\right) \tag{51}$$

Let $inv'_F(\boldsymbol{x})$ be defined as follows:

$$inv'_F(\boldsymbol{x}) = or_{i=1,\ldots,n}\left(or\left(eq\left(x_i, \frac{1}{4}\right), eq\left(x_i, \frac{3}{4}\right)\right)\right) \tag{52}$$

We define h' as follows:

$$h'_1 = or(inv'_T(\boldsymbol{x}), and(not(inv'_F(\boldsymbol{x})), g(\boldsymbol{x})) \tag{53}$$

with $h'_0(\boldsymbol{x}) = not(h'_1(\boldsymbol{x}))$.

Note that:

- If $x_i \in (-\infty, 0] \cup \{\frac{1}{2}\} \cup [1, \infty)$ for some i, then the top class is 1;
- Otherwise, if $\boldsymbol{x}$ is not a valid encoding, the top class is 0;
- Otherwise, the top class is 1 if $R(e^{(x)}(\boldsymbol{x}), e^{(y)}(\boldsymbol{x}))$ is true and 0 otherwise.

Finally, let $\frac{1}{8} < \gamma' < \frac{1}{4}$. Our query is thus:

$$q(\boldsymbol{z}) = \langle \boldsymbol{x}^{(s)}, \gamma', \frac{1}{2}, C_u, h' \rangle \tag{54}$$

Proof of $\boldsymbol{z} \in co\Pi_2 3SAT \implies q(\boldsymbol{z}) \in CCA_p$ If $\boldsymbol{z} \in co\Pi_2 3SAT$, then $\exists \boldsymbol{x}^*.\forall \hat{\boldsymbol{y}}.\neg R(\boldsymbol{x}^*, \hat{\boldsymbol{y}})$. Let $\boldsymbol{x}^{**}$ be defined as follows:

$$x_i^{**} = \begin{cases} \frac{1}{4} & x_i^* = 0 \\ \frac{3}{4} & x_i^* = 1 \end{cases} \tag{55}$$

Note that:

- $\boldsymbol{x}^{**} \in B_p\left(\boldsymbol{x}^{(s)}, \varepsilon_{\rho_{p,n}}\right)$;
- $e^{(x)}(\boldsymbol{x}^{**}) = \boldsymbol{x}^*$;
- $f(\boldsymbol{x}^{**}) = 0$, since $\boldsymbol{x}^{**} \in \{\frac{1}{4}, \frac{3}{4}\}^n$;
- Since $\gamma' < \frac{1}{4}$, there is no i such that $\exists \boldsymbol{x}'' \in B_p(\boldsymbol{x}^{**}, \gamma').x_i'' \in (-\infty, 0] \cup \{\frac{1}{2}\} \cup [1, \infty)$;
- For all $\boldsymbol{x}'' \in B_p(\boldsymbol{x}^{**}, \gamma')$:
  - If $\boldsymbol{x}''$ is not a valid encoding (i.e. $x_i'' \in \{\frac{1}{4}, \frac{3}{4}\}$ for some i), then $h'(\boldsymbol{x}'') = 0$;
  - Otherwise, $h'(\boldsymbol{x}'') = 1$ iff $R(e^{(x)}(\boldsymbol{x}''), e^{(y)}(\boldsymbol{x}''))$ is true.

Therefore, since $\forall \hat{\boldsymbol{y}}.\neg R(\boldsymbol{x}^*, \hat{\boldsymbol{y}})$, we know that $\forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^{**}, \gamma').f(\boldsymbol{x}'') = 0$. In other words, $\boldsymbol{x}^{**}$ is a solution to Equation (5).

Proof of $q(\boldsymbol{z}) \in CCA_p \implies \boldsymbol{z} \in co\Pi_2 3SAT$ If $q(\boldsymbol{z}) \in CCA_p$, then we know that $\exists \boldsymbol{x}^* \in B_p\left(\boldsymbol{x}^{(s)}, \varepsilon_{\rho_{p,n}}\right).\left(h'(\boldsymbol{x}^*) \neq h(\boldsymbol{x}^{(s)}) \wedge \forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma').h'(\boldsymbol{x}'') = h'(\boldsymbol{x}^*)\right)$. In other words, $\exists \boldsymbol{x}^* \in B_p\left(\boldsymbol{x}^{(s)}, \varepsilon_{\rho_{p,n}}\right).\left(h'(\boldsymbol{x}^*) = 0 \wedge \forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma').h'(\boldsymbol{x}'') = 0\right)$.

We will first prove by contradiction that $\boldsymbol{x}^* \in \left((\gamma', \frac{1}{2} - \gamma') \cup (\frac{1}{2} + \gamma', 1 - \gamma')\right)^n$.

First, suppose that $x_i^* \in (-\infty, 0) \cup (1, \infty)$ for some i. Then $h'(\boldsymbol{x}^*) = 0$ due to the fact that $inv_T(\boldsymbol{x}^*) = 1$.

Second, suppose that $x_i^* \in [0, \gamma'] \cup [1 - \gamma', 1]$ for some i. Then $\boldsymbol{x}^{(w)}$, defined as follows:

$$x_j^{(w)} = \begin{cases} 0 & i = j \wedge x_i^* \in [0, \gamma'] \\ 1 & i = j \wedge x_i^* \in [1 - \gamma', 1] \\ x_j^* & j \neq i \end{cases} \tag{56}$$

is such that $\boldsymbol{x}^{(w)} \in B_p(\boldsymbol{x}^*, \gamma')$ but $h'(\boldsymbol{x}^{(w)}) = 1$.

Finally, suppose that $x_i^* \in [\frac{1}{2} - \gamma, \frac{1}{2} + \gamma]$ for some i. Then $\boldsymbol{x}^{(w)}$, defined as follows:

$$x_j^{(w)} = \begin{cases} \frac{1}{2} & i = j \\ x_j^* & \text{otherwise} \end{cases} \tag{57}$$

is such that $\boldsymbol{x}^{(w)} \in B_p(\boldsymbol{x}^*, \gamma')$ but $h'(\boldsymbol{x}^{(w)}) = 1$.

Therefore, $\boldsymbol{x}^* \in \left((\gamma', \frac{1}{2} - \gamma') \cup (\frac{1}{2} + \gamma', 1 - \gamma')\right)^n$.

As a consequence $\forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma').e^{(x)}(\boldsymbol{x}'') = e^{(x)}(\boldsymbol{x}')$.

From this, due to the fact that $\gamma' > \frac{1}{8}$ and that $p > 0$, we can conclude that for all $\hat{\boldsymbol{y}}$, there exists a $\boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma')$ such that:

$$\begin{aligned} x_i'' &\in \left(0, \frac{1}{4}\right) \text{ for } x_i^* \in \left(\gamma', \frac{1}{2} - \gamma'\right), \hat{y}_i = 0 \\ x_i'' &\in \left(\frac{1}{4}, \frac{1}{2}\right) \text{ for } x_i^* \in \left(\gamma', \frac{1}{2} - \gamma'\right), \hat{y}_i = 1 \\ x_i'' &\in \left(\frac{1}{2}, \frac{3}{4}\right) \text{ for } x_i^* \in \left(\frac{1}{2} + \gamma', 1 - \gamma'\right), \hat{y}_i = 0 \\ x_i'' &\in \left(\frac{3}{4}, 1\right) \text{ for } x_i^* \in \left(\frac{1}{2} + \gamma', 1 - \gamma'\right), \hat{y}_i = 1 \end{aligned} \tag{58}$$

In other words, for all $\hat{\boldsymbol{y}}$ there exists a corresponding $\boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma')$ such that $e^{(y)}(\boldsymbol{x}'') = \hat{\boldsymbol{y}}$.

Therefore, since $h'(\boldsymbol{x}'') = 1$ iff $R(e^{(x)}(\boldsymbol{x}''), e^{(y)}(\boldsymbol{x}''))$ is true and since $\forall \boldsymbol{x}'' \in B_p(\boldsymbol{x}^*, \gamma').h'(\boldsymbol{x}'') = 0$, we can conclude that $\forall \hat{\boldsymbol{y}}.\neg R(e^{(x)}(\boldsymbol{x}^*), \hat{\boldsymbol{y}})$. In other words, $\boldsymbol{z} \in co\Pi_2 3SAT$.

F.4 PROOF OF COROLLARY 5.2

Similarly to the proof of Corollary 1.3, it follows from the fact that ReLU classifiers are polynomial-time classifiers (w.r.t. the size of the tuple).

G FULL EXPERIMENTAL SETUP

All our code is written in Python + PyTorch (Paszke et al., 2019), with the exception of the MIPVerify interface, which is written in Julia.

Models All models were trained using Adam (Kingma & Ba, 2014) and dataset augmentation. We performed a manual hyperparameter and architecture search to find a suitable compromise between accuracy and MIPVerify convergence. The process required approximately 4 months. When

performing adversarial training, following (Madry et al., 2018) we used the final adversarial example found by the Projected Gradient Descent attack, instead of the closest. To maximize uniformity, we used for each configuration the same training and pruning hyperparameters (when applicable), which we report in Table 1. We report the chosen architectures in Tables 2 and 3, while Table 4 outlines their accuracies and parameter counts.

UG100 The first 250 samples of the test set of each dataset were used for hyperparameter tuning and were thus not considered in our analysis. For our G100 dataset, we sampled uniformly across each ground truth label and removed the examples for which MIPVerify crashed. Table 5 details the composition of the dataset by ground truth label.

Attacks For the Basic Iterative Method (BIM), the Fast Gradient Sign Method (FGSM) and the Projected Gradient Descent (PGD) attack, we used the implementations provided by the AdverTorch library (Ding et al., 2019). For the Brendel & Bethge (B&B) attack and the Deepfool (DF) attack, we used the implementations provided by the Foolbox Native library (Rauber et al., 2020). The Carlini & Wagner and the uniform noise attacks were instead implemented by the authors. We modified the attacks that did not return the closest adversarial example found (i.e. BIM, Carlini & Wagner, Deepfool, FGSM and PGD) to do so. For the attacks that accept ε as a parameter (i.e. BIM, FGSM, PGD and uniform noise), for each example we first performed an initial search with a decaying value of ε, followed by a binary search. In order to pick the attack parameters, we first selected the strong set by performing an extensive manual search. The process took approximately 3 months. We then modified the strong set in order to obtain the balanced parameter set. We report the parameters of both sets (as well as the parameters of the binary and ε decay searches) in Table 6.

MIPVerify We ran MIPVerify using the Julia library MIPVerify.jl and Gurobi (Gurobi Optimization, LLC, 2022). Since MIPVerify can be sped up by providing a distance upper bound, we used the same pool of adversarial examples utilized throughout the paper. For CIFAR10 we used the strong parameter set, while for MNIST we used the strong parameter set with some differences (reported in Table 7). Since numerical issues might cause the distance upper bound computed by the heuristic attacks to be slightly different from the one computed by MIPVerify, we ran a series of *exploratory runs*, each with a different correction factor (1.05, 1.25, 1.5, 2), and picked the first factor that caused MIPVerify to find a feasible (but not necessarily optimal) solution. If the solution was not optimal, we then performed a *main run* with a higher computational budget. We provide the parameters of MIPVerify in Table 8. We also report in Table 9 the percentage of tight bounds for each combination.

H QUANTILE-BASED CALIBRATION

The buffer function in CA can be empirically calibrated so as to control the chance of false positives (i.e. inputs wrongly reported as not robust) and false negatives (i.e. non-robust inputs reported as being robust).

Given the strong correlation that we observed between the distance of heuristic adversarial examples and the true decision boundary distance, using a linear model for b_α seems a reasonable choice. Under this assumption, the buffer value depends only on the distance between the original example and the adversarial one, i.e. on $d(x, a_{f,\theta}(x))$. This property allows us to rewrite the main check performed by CA as:

$$||x - a_f(x))||_p - b(x) = \alpha_1 ||x - a_{f,\theta}(x)||_p + \alpha_0 \leq \varepsilon \tag{59}$$

The parameters α_1, α_0 can then be obtained via quantile regression (Koenker & Bassett Jr, 1978) by using the true decision boundary distance (i.e. $d_p^*(x)$) as a target.

The approach provides a simple, interpretable mechanism to control how conservative the detection check should be: with a small quantile, CA will tend to underestimate the decision boundary distance, leading to fewer missed detections, but more false alarms; using a high quantile will lead to the opposite behavior.

We test this type of buffer using 5-fold cross-validation on each configuration. Specifically, we calibrate the model using 1%, 50% and 99% as quantiles. Tables 10 to 13 provide a comparison between the expected quantile and the average true quantile of each configuration on the validation folds. Additionally, we plot in Figures 3 to 8 the mean F_1 score in relation to the choice of ε.

Table 1: Training and pruning hyperparameters.

Parameter Name	Value	
	MNIST	**CIFAR10**
Common Hyperparameters		
Epochs	425	
Learning Rate	1e-4	
Batch Size	32	128
Adam β	(0.9, 0.999)	
Flip %	50%	
Translation Ratio	0.1	
Rotation (deg.)	15°	
Adversarial Hyperparameters (Adversarial and ReLU only)		
Attack	PGD	
Attack #Iterations	200	
Attack Learning Rate	0.1	
Adversarial Ratio	1	
ε	0.05	2/255
ReLU Hyperparameters (ReLU only)		
L1 Regularization Coeff.	2e-5	1e-5
RS Loss Coeff.	1.2e-4	1e-3
Weight Pruning Threshold	1e-3	
ReLU Pruning Threshold	90%	

Table 2: MNIST Architectures.

(a) MNIST A

Input
Flatten
Linear (in = 784, out = 100)
ReLU
Linear (in = 100, out = 10)
Output

(b) MNIST B

Input
Conv2D (in = 1, out = 4, 5x5 kernel, stride = 3, padding = 0)
ReLU
Flatten
Linear (in = 256, out = 10)
Output

(c) MNIST C

Input
Conv2D (in = 1, out = 8, 5x5 kernel, stride = 4, padding = 0)
ReLU
Flatten
Linear (in = 288, out = 10)
Output

Table 3: CIFAR10 architectures.

(a) CIFAR10 A

Input
Conv2D (in = 3, out = 8, 3x3 kernel, stride = 2, padding = 0)
ReLU
Flatten
Linear (in = 1800, out = 10)
Output

(b) CIFAR10 B

Input
Conv2D (in = 3, out = 20, 5x5 kernel, stride = 4, padding = 0)
ReLU
Flatten
Linear (in = 980, out = 10)
Output

(c) CIFAR10 C

Input
Conv2D (in = 3, out = 8, 5x5 kernel, stride = 4, padding = 0)
ReLU
Conv2D (in = 8, out = 8, 3x3 kernel, stride = 2, padding = 0)
ReLU
Flatten
Linear (in = 72, out = 10)
Output

Table 4: Parameter counts and accuracies of trained models.

Architecture	#Parameters	Training	Accuracy
MNIST A	79510	Standard	95.87%
		Adversarial	94.24%
		ReLU	93.57%
MNIST B	2674	Standard	89.63%
		Adversarial	84.54%
		ReLU	83.69%
MNIST C	3098	Standard	90.71%
		Adversarial	87.35%
		ReLU	85.67%
CIFAR10 A	18234	Standard	53.98%
		Adversarial	50.77%
		ReLU	32.85%
CIFAR10 B	11330	Standard	55.81%
		Adversarial	51.35%
		ReLU	37.33%
CIFAR10 C	1922	Standard	47.85%
		Adversarial	45.19%
		ReLU	32.27%

Figure 3: F_1 scores in relation to ε for MNIST A for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

Figure 4: F_1 scores in relation to ε for MNIST B for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

(a) MNIST C Standard Strong

(b) MNIST C Standard Balanced

(c) MNIST C Adversarial Strong

(d) MNIST C Adversarial Balanced

(e) MNIST C ReLU Strong

(f) MNIST C ReLU Balanced

Figure 5: F_1 scores in relation to ε for MNIST C for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

Figure 6: F_1 scores in relation to ε for CIFAR10 A for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

(a) CIFAR10 B Standard Strong

(b) CIFAR10 B Standard Balanced

(c) CIFAR10 B Adversarial Strong

(d) CIFAR10 B Adversarial Balanced

(e) CIFAR10 B ReLU Strong

(f) CIFAR10 B ReLU Balanced

Figure 7: F_1 scores in relation to ε for CIFAR10 B for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

Figure 8: F_1 scores in relation to ε for CIFAR10 C for each considered percentile. For ease of visualization, we set the graph cutoff at $F_1 = 0.8$. We also mark 8/255 (a common choice for ε) with a dotted line.

Table 5: Ground truth labels of the UG100 dataset.

(a) MNIST

Ground Truth	Count	%
0	219	9.77%
1	228	10.17%
2	225	10.04%
3	225	10.04%
4	225	10.04%
5	220	9.82%
6	227	10.13%
7	221	9.86%
8	225	10.04%
9	226	10.08%

(b) CIFAR10

Ground Truth	Count	%
Airplane	228	10.05%
Automobile	227	10.00%
Bird	228	10.05%
Cat	228	10.05%
Deer	226	9.96%
Dog	227	10.00%
Frog	227	10.00%
Horse	227	10.00%
Ship	225	9.92%
Truck	226	9.96%

I ADDITIONAL RESULTS

Tables 14 to 17 detail the performance of the various attack sets on every combination, while Figures 9 to 14 showcase the relation between the true and estimated decision boundary distances.

J ABLATION STUDY

We outline the best attack pools by size in Tables 18 to 21. Additionally, we report the performance of pools composed of individual attacks in Tables 22 to 25. Finally, we detail the performance of dropping a specific attack in Tables 26 to 29.

K FAST PARAMETER SET TESTS

We list the chosen parameter sets for Fast-100, Fast-1k and Fast-10k in Table 30. We plot the difference between the distance of the closest adversarial examples and the true decision boundary distance in Figures 15 to 23, while we plot the R^2 values in Figures 24 to 32. Note that, for attacks that do not have the a 100% success rate, the mean adversarial example distance can increase with the number of steps as new adversarial examples (for inputs for which there were previously no successful adversarial examples) are added.

L RESULTS FOR ATTACKS AGAINST CA

We report the parameters for the variant of our attack in Table 31, while we report its success rate in Table 32. Note that, since Deepfool is a deterministic attack, no measures against randomizations were taken.

Table 6: Parameters of heuristic attacks.

Attack	Parameter Name	MNIST		CIFAR10	
		Strong	Balanced	Strong	Balanced
BIM	Initial Search Factor			0.75	
	Initial Search Steps			30	
	Initial Search Factor			0.75	
	Binary Search Steps			20	
	#Iterations	2k	200	5k	200
	Learning Rate	1e-3	1e-2	1e-5	1e-3
Brendel & Bethge	Initial Attack			Blended Noise	
	Overshoot			1.1	
	LR Decay			0.75	
	LR Decay Every n Steps			50	
	#Iterations	5k	200	5k	200
	Learning Rate	1e-3	1e-3	1e-5	1e-3
	Momentum			0.8	
	Initial Directions			1000	
	Init Steps			1000	
Carlini & Wagner	Minimum τ			1e-5	
	Initial τ			1	
	τ Factor	0.95	0.9	0.99	0.9
	Initial Const			1e-5	
	Const Factor			2	
	Maximum Const			20	
	Reduce Const			False	
	Warm Start			True	
	Abort Early			True	
	Learning Rate	1e-2	1e-2	1e-5	1e-4
	Max Iterations	1k	100	5k	100
	τ Check Every n Steps			1	
	Const Check Every n Steps			5	
	Iter. Check Every n Steps			Disabled	
Deepfool	#Iterations			5k	
	Candidates			10	
	Overshoot			1e-5	
	Loss			Logits	
FGSM	Initial Search Factor			0.75	
	Initial Search Steps			30	
	Initial Search Factor			0.75	
	Binary Search Steps			20	
	Starting ε			1	
PGD	Initial Search Factor			0.75	
	Initial Search Steps			30	
	Initial Search Factor			0.75	
	Binary Search Steps			20	
	#Iterations	5k	200	5k	200
	Learning Rate	1e-4	1e-3	1e-4	1e-3
	Random Initialization			True	
Uniform Noise	Initial Search Factor			0.75	
	Initial Search Steps			30	
	Initial Search Factor			0.75	
	Binary Search Steps			20	
	Runs	8k	200	8k	200

Table 7: Parameter set used to initialize MIPVerify for MNIST. All other parameters are identical to the strong MNIST attack parameter set.

Attack Name	Parameter Name	Value
BIM	#Iterations	5k
	Learning Rate	1e-5
Brendel & Bethge	Learning Rate	1e-3
Carlini & Wagner	Tau Factor	0.99
	Learning Rate	1e-3
	#Iterations	5k

Table 8: Parameters of MIPVerify.

Parameter Name	Value	
	Exploration	Main
Absolute Tolerance	1e-5	
Relative Tolerance	1e-10	
Threads	1	
Timeout (s)	120	7200
Tightening Absolute Tolerance	1e-4	
Tightening Relative Tolerance	1e-10	
Tightening Timeout (s)	20	240
Tightening Threads	1	

Table 9: MIPVerify bound tightness statistics.

Architecture	Training	% Tight
MNIST A	Standard	95.40%
	Adversarial	99.60%
	ReLU	82.46%
MNIST B	Standard	74.61%
	Adversarial	85.68%
	ReLU	75.55%
MNIST C	Standard	86.21%
	Adversarial	97.28%
	ReLU	95.63%
CIFAR10 A	Standard	81.18%
	Adversarial	82.50%
	ReLU	92.73%
CIFAR10 B	Standard	56.32%
	Adversarial	58.88%
	ReLU	81.67%
CIFAR10 C	Standard	100.00%
	Adversarial	100.00%
	ReLU	100.00%

Table 10: Expected vs true quantile for MNIST strong with 5-fold cross validation.

Architecture	Training	Expected Quantile	True Quantile
A	Standard	1.00%
50.00%
99.00%	0.99±1.02%
49.93±2.35%
95.60±3.77%
	Adversarial	1.00%
50.00%
99.00%	1.11±0.53%
50.25±1.58%
89.84±6.42%
	ReLU	1.00%
50.00%
99.00%	1.11±0.45%
50.02±1.72%
91.95±5.64%
B	Standard	1.00%
50.00%
99.00%	1.07±0.48%
49.80±0.76%
97.76±0.71%
	Adversarial	1.00%
50.00%
99.00%	1.22±1.01%
49.88±4.63%
98.10±0.36%
	ReLU	1.00%
50.00%
99.00%	1.04±0.77%
49.98±3.17%
97.69±1.41%
C	Standard	1.00%
50.00%
99.00%	1.07±0.37%
50.17±1.64%
98.73±0.42%
	Adversarial	1.00%
50.00%
99.00%	1.05±0.29%
49.87±3.58%
99.00±0.47%
	ReLU	1.00%
50.00%
99.00%	1.06±0.67%
50.02±1.85%
93.99±3.51%

Table 11: Expected vs true quantile for MNIST balanced with 5-fold cross validation.

Architecture	Training	Expected Quantile	True Quantile
A	Standard	1.00%	1.30±0.79%
		50.00%	49.98±3.10%
		99.00%	93.99±2.59%
	Adversarial	1.00%	0.97±0.40%
		50.00%	50.12±1.14%
		99.00%	90.44±1.90%
	ReLU	1.00%	1.02±0.31%
		50.00%	50.02±1.05%
		99.00%	95.10±2.82%
B	Standard	1.00%	1.03±0.36%
		50.00%	49.98±0.70%
		99.00%	98.88±0.45%
	Adversarial	1.00%	1.17±0.97%
		50.00%	50.17±4.54%
		99.00%	98.69±0.59%
	ReLU	1.00%	1.04±0.49%
		50.00%	50.34±2.49%
		99.00%	98.73±0.53%
C	Standard	1.00%	1.07±0.33%
		50.00%	49.98±0.91%
		99.00%	98.88±0.55%
	Adversarial	1.00%	1.10±0.37%
		50.00%	50.12±4.15%
		99.00%	99.00±0.35%
	ReLU	1.00%	1.06±0.67%
		50.00%	50.12±2.67%
		99.00%	98.62±0.50%

Table 12: Expected vs true quantile for CIFAR10 strong with 5-fold cross validation.

Architecture	Training	Expected Quantile	True Quantile
A	Standard	1.00%
50.00%
99.00%	1.09±0.86%
50.09±1.84%
98.82±0.63%
	Adversarial	1.00%
50.00%
99.00%	1.05±0.23%
49.86±3.59%
98.90±0.62%
	ReLU	1.00%
50.00%
99.00%	0.97±0.41%
49.93±3.42%
97.66±1.35%
B	Standard	1.00%
50.00%
99.00%	0.98±0.18%
49.91±1.18%
98.84±0.56%
	Adversarial	1.00%
50.00%
99.00%	0.91±0.48%
50.00±3.58%
98.69±0.72%
	ReLU	1.00%
50.00%
99.00%	1.10±0.72%
49.98±2.21%
98.85±0.61%
C	Standard	1.00%
50.00%
99.00%	0.93±0.60%
50.00±1.86%
98.71±0.71%
	Adversarial	1.00%
50.00%
99.00%	1.09±0.17%
50.14±2.63%
98.27±0.81%
	ReLU	1.00%
50.00%
99.00%	1.01±0.62%
50.02±2.09%
96.17±2.40%

Table 13: Expected vs true quantile for CIFAR10 balanced with 5-fold cross validation.

Architecture	Training	Expected Quantile	True Quantile
A	Standard	1.00%
50.00%
99.00%	0.95±0.61%
50.32±2.38%
98.87±0.59%
	Adversarial	1.00%
50.00%
99.00%	1.05±0.23%
50.23±2.65%
98.81±0.96%
	ReLU	1.00%
50.00%
99.00%	4.14±5.32%
50.37±1.02%
94.62±2.87%
B	Standard	1.00%
50.00%
99.00%	1.07±0.46%
49.91±2.78%
98.93±0.73%
	Adversarial	1.00%
50.00%
99.00%	1.13±0.57%
50.18±2.05%
98.82±0.71%
	ReLU	1.00%
50.00%
99.00%	1.23±0.38%
50.11±0.38%
98.77±0.51%
C	Standard	1.00%
50.00%
99.00%	0.98±0.50%
50.09±2.21%
98.85±0.43%
	Adversarial	1.00%
50.00%
99.00%	1.09±0.26%
49.96±2.72%
98.86±0.32%
	ReLU	1.00%
50.00%
99.00%	1.01±0.36%
49.93±1.60%
97.93±0.63%

Table 14: Performance of the strong attack set on MNIST.

Architecture	Training	Success Rate	Difference	% Below 1/255	R^2
MNIST A	Standard	100.00%	1.51%	98.16%	0.996
	Adversarial	100.00%	2.48%	81.43%	0.994
	ReLU	100.00%	2.14%	84.33%	0.995
MNIST B	Standard	100.00%	3.38%	97.36%	0.995
	Adversarial	100.00%	4.34%	75.09%	0.991
	ReLU	100.00%	4.80%	68.02%	0.992
MNIST C	Standard	100.00%	4.52%	96.92%	0.996
	Adversarial	100.00%	8.76%	48.78%	0.981
	ReLU	100.00%	4.84%	68.24%	0.988

Table 15: Performance of the balanced attack set on MNIST.

Architecture	Training	Success Rate	Difference	% Below 1/255	R^2
MNIST A	Standard	100.00%	1.68%	97.94%	0.995
	Adversarial	100.00%	2.87%	77.64%	0.993
	ReLU	100.00%	2.55%	80.86%	0.993
MNIST B	Standard	100.00%	4.09%	96.55%	0.995
	Adversarial	100.00%	4.90%	72.60%	0.988
	ReLU	100.00%	5.53%	62.96%	0.989
MNIST C	Standard	100.00%	5.43%	96.04%	0.995
	Adversarial	100.00%	9.50%	48.43%	0.977
	ReLU	100.00%	5.28%	66.96%	0.986

Table 16: Performance of the strong attack set on CIFAR10.

Architecture	Training	Success Rate	Difference	% Below 1/255	R^2
CIFAR10 A	Standard	100.00%	1.62%	100.00%	0.999
	Adversarial	100.00%	4.42%	95.88%	0.995
	ReLU	100.00%	0.26%	100.00%	1.000
CIFAR10 B	Standard	100.00%	1.44%	100.00%	0.999
	Adversarial	100.00%	3.17%	97.69%	0.997
	ReLU	100.00%	1.38%	98.81%	0.999
CIFAR10 C	Standard	100.00%	2.11%	100.00%	0.999
	Adversarial	100.00%	3.10%	97.14%	0.996
	ReLU	100.00%	2.35%	96.12%	0.990

Table 17: Performance of the balanced attack set on CIFAR10.

Architecture	Training	Success Rate	Difference	% Below 1/255	R^2
CIFAR10 A	Standard	100.00%	1.71%	100.00%	0.999
	Adversarial	100.00%	4.18%	96.57%	0.995
	ReLU	100.00%	0.18%	100.00%	1.000
CIFAR10 B	Standard	100.00%	1.53%	100.00%	0.999
	Adversarial	100.00%	2.92%	98.46%	0.996
	ReLU	100.00%	1.19%	98.94%	0.999
CIFAR10 C	Standard	100.00%	2.06%	100.00%	0.999
	Adversarial	100.00%	3.12%	97.28%	0.996
	ReLU	100.00%	1.45%	97.44%	0.995

Table 18: Best pools of a given size by success rate and R^2 for MNIST strong.

n	Attacks	Success Rate	Difference	< 1/255	R^2
1	PGD	100.00±0.00%	10.98±4.41%	51.83±27.78%	0.975±0.010
2	C&W, PGD	100.00±0.00%	7.99±3.31%	60.68±25.43%	0.986±0.005
3	B&B, C&W, PGD	100.00±0.00%	4.71±1.97%	77.97±15.52%	0.989±0.004
4	B&B, C&W, DF, PGD	100.00±0.00%	4.36±2.03%	79.02±15.62%	0.991±0.005
5	No FGSM, Uniform	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005
6	No Uniform	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005
7	All	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005

Figure 9: Decision boundary distances found by the attack pools compared to those found by MIPVerify on MNIST A. The black line represents the theoretical optimum.

Figure 10: Decision boundary distances found by the attack pools compared to those found by MIPVerify on MNIST B. The black line represents the theoretical optimum.

Figure 11: Decision boundary distances found by the attack pools compared to those found by MIPVerify on MNIST C. The black line represents the theoretical optimum.

Figure 12: Decision boundary distances found by the attack pools compared to those found by MIPVerify on CIFAR10 A. The black line represents the theoretical optimum.

Figure 13: Decision boundary distances found by the attack pools compared to those found by MIPVerify on CIFAR10 B. The black line represents the theoretical optimum.

Figure 14: Decision boundary distances found by the attack pools compared to those found by MIPVerify on CIFAR10 C. The black line represents the theoretical optimum.

Table 19: Best pools of a given size by success rate and R^2 for MNIST balanced.

n	Attacks	Success Rate	Difference	< 1/255	R^2
1	BIM	100.00±0.00%	11.72±4.18%	50.92±26.43%	0.965±0.010
2	BIM, B&B	100.00±0.00%	6.11±2.28%	73.23±15.90%	0.980±0.007
3	BIM, B&B, C&W	100.00±0.00%	5.29±2.06%	75.72±16.10%	0.986±0.005
4	BIM, B&B, C&W, DF	100.00±0.00%	4.85±2.10%	77.33±15.85%	0.989±0.005
5	No FGSM, Uniform	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006
6	No Uniform	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006
7	All	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006

Table 20: Best pools of a given size by success rate and R^2 for CIFAR10 strong.

n	Attacks	Success Rate	Difference	< 1/255	R^2
1	DF	100.00±0.00%	6.11±3.49%	95.06±4.81%	0.989±0.011
2	DF, PGD	100.00±0.00%	4.71±2.37%	96.32±3.56%	0.995±0.007
3	C&W, DF, PGD	100.00±0.00%	2.54±1.30%	98.17±2.00%	0.996±0.006
4	B&B, C&W, DF, PGD	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
5	No FGSM, Uniform	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
6	No Uniform	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
7	All	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003

Table 21: Best pools of a given size by success rate and R^2 for CIFAR10 balanced.

n	Attacks	Success Rate	Difference	< 1/255	R^2
1	DF	100.00±0.00%	6.11±3.49%	95.06±4.81%	0.989±0.011
2	B&B, DF	100.00±0.00%	2.52±1.51%	98.23±1.81%	0.995±0.004
3	BIM, B&B, DF	100.00±0.00%	2.21±1.25%	98.53±1.52%	0.997±0.002
4	BIM, B&B, C&W, DF	100.00±0.00%	2.06±1.16%	98.73±1.32%	0.998±0.002
5	No FGSM, Uniform	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002
6	No FGSM	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002
7	All	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002

Table 22: Performance of individual attacks for MNIST strong.

Attack	Success Rate	Difference	< 1/255	R^2
BIM	100.00±0.00%	10.90±4.42%	53.57±28.07%	0.966±0.012
B&B	99.99±0.01%	18.50±7.09%	58.78±9.91%	0.812±0.044
C&W	100.00±0.00%	17.52±2.74%	48.02±21.28%	0.910±0.024
Deepfool	100.00±0.00%	21.59±7.73%	44.15±20.02%	0.923±0.027
FGSM	99.72±0.51%	44.43±15.76%	28.20±17.30%	0.761±0.132
PGD	100.00±0.00%	10.98±4.41%	51.83±27.78%	0.975±0.010
Uniform	99.52±0.91%	414.47±140.54%	0.82±0.55%	0.623±0.138

Table 23: Performance of individual attacks for MNIST balanced.

Attack	Success Rate	Difference	< 1/255	R^2
BIM	100.00±0.00%	11.72±4.18%	50.92±26.43%	0.965±0.010
B&B	99.99±0.03%	18.65±7.29%	58.43±9.61%	0.812±0.039
C&W	100.00±0.00%	22.55±3.83%	38.95±22.49%	0.904±0.025
Deepfool	100.00±0.00%	21.59±7.73%	44.15±20.02%	0.923±0.027
FGSM	99.72±0.51%	44.43±15.76%	28.20±17.30%	0.761±0.132
PGD	100.00±0.00%	16.23±6.59%	48.08±28.88%	0.905±0.070
Uniform	98.66±1.90%	521.61±181.40%	0.57±0.38%	0.484±0.122

Table 24: Performance of individual attacks for CIFAR10 strong.

Attack	Success Rate	Difference	< 1/255	R^2
BIM	91.96±7.40%	19.97±5.95%	80.32±12.97%	0.934±0.041
B&B	100.00±0.00%	508.66±196.37%	42.74±7.85%	0.174±0.074
C&W	99.98±0.02%	10.67±3.64%	90.09±5.51%	0.926±0.030
Deepfool	100.00±0.00%	6.11±3.49%	95.06±4.81%	0.989±0.011
FGSM	100.00±0.00%	31.80±11.12%	69.20±17.72%	0.847±0.123
PGD	100.00±0.00%	19.36±5.99%	77.23±15.89%	0.952±0.027
Uniform	99.99±0.02%	1206.79±277.68%	2.48±0.88%	0.910±0.044

Table 25: Performance of individual attacks for CIFAR10 balanced.

Attack	Success Rate	Difference	< 1/255	R^2
BIM	100.00±0.00%	19.23±5.92%	77.33±15.89%	0.954±0.025
B&B	100.00±0.00%	50.64±52.17%	81.20±10.68%	0.615±0.349
C&W	99.89±0.09%	17.44±4.01%	84.82±8.51%	0.923±0.026
Deepfool	100.00±0.00%	6.11±3.49%	95.06±4.81%	0.989±0.011
FGSM	100.00±0.00%	31.80±11.12%	69.20±17.72%	0.847±0.123
PGD	100.00±0.00%	20.18±6.56%	76.97±16.07%	0.947±0.031
Uniform	99.85±0.26%	1617.74±390.50%	1.80±0.67%	0.853±0.068

Table 26: Performance of pools without a specific attack for MNIST strong.

Dropped Attack	Success Rate	Difference	< 1/255	R^2
None	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005
BIM	100.00±0.00%	4.35±2.03%	79.02±15.62%	0.991±0.005
B&B	100.00±0.00%	6.76±3.31%	64.46±25.01%	0.990±0.005
C&W	100.00±0.00%	4.65±2.20%	77.70±16.02%	0.989±0.006
Deepfool	100.00±0.00%	4.33±1.97%	79.04±15.75%	0.990±0.004
FGSM	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005
PGD	100.00±0.00%	4.26±1.99%	79.36±15.59%	0.991±0.004
Uniform	100.00±0.00%	4.09±2.02%	79.81±15.70%	0.992±0.005

Table 27: Performance of pools without a specific attack for MNIST balanced.

Dropped Attack	Success Rate	Difference	< 1/255	R^2
None	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006
BIM	100.00±0.00%	5.13±2.27%	76.14±15.98%	0.988±0.007
B&B	100.00±0.00%	7.93±3.69%	60.79±25.99%	0.987±0.006
C&W	100.00±0.00%	4.93±2.22%	77.05±15.96%	0.988±0.006
Deepfool	100.00±0.00%	5.03±2.14%	76.34±16.36%	0.988±0.005
FGSM	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006
PGD	100.00±0.00%	4.85±2.10%	77.33±15.85%	0.989±0.005
Uniform	100.00±0.00%	4.65±2.16%	77.78±16.08%	0.990±0.006

Table 28: Performance of pools without a specific attack for CIFAR10 strong.

Dropped Attack	Success Rate	Difference	< 1/255	R^2
None	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
BIM	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
B&B	100.00±0.00%	2.54±1.30%	98.17±2.00%	0.996±0.006
C&W	100.00±0.00%	3.83±2.06%	96.84±3.12%	0.996±0.004
Deepfool	100.00±0.00%	4.02±1.19%	95.65±3.10%	0.992±0.005
FGSM	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003
PGD	100.00±0.00%	2.50±1.48%	98.11±1.93%	0.995±0.005
Uniform	100.00±0.00%	2.21±1.16%	98.40±1.63%	0.997±0.003

Table 29: Performance of pools without a specific attack for CIFAR10 balanced.

Dropped Attack	Success Rate	Difference	< 1/255	R^2
None	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002
BIM	100.00±0.00%	2.07±1.15%	98.72±1.31%	0.998±0.002
B&B	100.00±0.00%	4.08±1.95%	97.26±2.70%	0.996±0.006
C&W	100.00±0.00%	2.18±1.22%	98.54±1.50%	0.997±0.002
Deepfool	100.00±0.00%	4.00±0.99%	95.89±3.13%	0.993±0.003
FGSM	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002
PGD	100.00±0.00%	2.06±1.16%	98.73±1.32%	0.998±0.002
Uniform	100.00±0.00%	2.04±1.13%	98.74±1.29%	0.998±0.002

Table 30: Parameters for the Fast-100, Fast-1k and Fast-10k sets.

Attack	Parameter Name	MNIST			CIFAR10		
		100	1k	10k	100	1k	10k
BIM	Initial Search Factor			N/A			
	Initial Search Steps			N/A			
	Binary Search Steps	10	20	20	10	20	20
	Starting ε		0.5			0.1	
	#Iterations	10	50	500	10	50	500
	Learning Rate	0.1	0.01	1e-3	0.01	1e-3	1e-3
Deepfool	#Iterations	100	500	500		500	
	Candidates			10			
	Overshoot	0.1	1e-5	1e-5		1e-4	
	Loss			Logits			
FGSM	Initial Search Factor		0.75			0.5	
	Initial Search Steps		30			10	
	Binary Search Steps			20			
	Starting ε		1			0.1	
PGD	Initial Search Factor	N/A	0.5	0.5	N/A	0.5	0.75
	Initial Search Steps	N/A	10	10	N/A	10	30
	Binary Search Steps		10		10	10	20
	Starting ε		0.1		0.1	0.1	1
	#Iterations	10	50	500	10	50	200
	Learning Rate	0.1	0.01	1e-3	0.01	1e-3	1e-3
	Random Initialization			True			
Uniform Noise	Initial Search Factor		0.75		0.75	0.75	0.25
	Initial Search Steps		30		30	30	5
	Binary Search Steps		20		20	20	15
	Starting ε		1		1	1	0.5
	Runs	200	500	200	10	50	500

Figure 15: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 A Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 16: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 A Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 17: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 A ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 18: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 B Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 19: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 B Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 20: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 B ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 21: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 C Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 22: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 C Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

(a) MNIST C ReLU Fast-100   (b) CIFAR10 C ReLU Fast-100

(c) MNIST C ReLU Fast-1k   (d) CIFAR10 C ReLU Fast-1k

(e) MNIST C ReLU Fast-10k   (f) CIFAR10 C ReLU Fast-10k

Figure 23: Mean difference between the distance of the closest adversarial examples and the exact decision boundary distance for MNIST & CIFAR10 C ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. Both axes are logarithmic.

Figure 24: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 A Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 25: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 A Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 26: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 A ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 27: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 B Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 28: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 B Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 29: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 B ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 30: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 C Standard. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 31: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 C Adversarial. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Figure 32: R^2 of linear model for the heuristic adversarial distances given the exact decision boundary distances for MNIST & CIFAR10 C ReLU. A dashed line means that the attack found adversarial examples (of any distance) for only some inputs, while the absence of a line means that the attack did not find any adversarial examples. The loosely and densely dotted black lines respectively represent the balanced and strong attack pools. The y axis is logarithmic.

Table 31: Parameters for the variant of the PGD attack.

Parameter	Value
λ	$\{10^{-4}, 10^{-2}, 1, 10^2, 10^4\}$
NES Estimation Samples	200
NES Estimation ε	10^{-4}
PGD Iterations	400
PGD ε	10^{-3}

Table 32: Success rate of the pool composed of the anti-CA variant of PGD and uniform noise for the A architectures.

ε	ε' **Multiplier**			
	1x	**2x**	**5x**	**10x**
0.025	0%	23%	95%	100%
0.05	3%	41%	97%	100%
0.1	2%	50%	96%	100%

(a) MNIST A Standard

ε	ε' **Multiplier**			
	1x	**2x**	**5x**	**10x**
2/255	0%	34%	96%	100%
4/255	1%	50%	100%	100%
8/255	1%	58%	100%	100%

(b) CIFAR10 A Standard