Can LLM understand the implicit meaning of language? Discussion of LLM's ability to generate metaphorical samples

Abstract

Metaphor generation is both an attractive and challenging problem in the field of natural language processing. Previous research has focused on paraphrase generation, i.e., generating literal paraphrases of target words in specific contexts, or on component generation, i.e., generating metaphor triples. However, these approaches do not address the generation of complete metaphor samples, which requires more sophisticated semantic understanding and text generation capabilities. Therefore, this paper explores the capabilities of large language models (LLMs) in metaphor sample generation. We first design LLMs metaphorical reasoning experiments and propose two prompt enhancement methods based on definitions and multi-word meanings. The former introduces metaphor definitions, while the latter requires LLMs to generate corresponding metaphorical or literal samples based on each lexical meaning of the target word. Experimental results show that our proposed SPE method performs slightly lower than manually labeled samples after fine-tuning, but its cost is only 1/25000 of manual labeling. Finally, we delve deeper into the differences between the four generation methods through manual evaluation, automatic evaluation, and example analysis. The results show that although LLM demonstrates some capability in metaphorical reasoning, it still faces significant challenges in generating diversity and accuracy.

1 Introduction

Data annotation is a time-consuming and labor-intensive task. The average cost of labeling each instance on a crowdsourcing platform is $0.11 (Wang et al., 2021a). This high cost has become a constraint for further development of many studies. In contrast, generating samples using LLMs (e.g., ChatGPT) becomes a more cost-effective alternative, with a cost of $0.05 per 1M tokens input and $0.15 per 1M tokens output, respectively. Therefore, it is important and valuable to guide LLMs to generate high-quality sample data. Specifically, (1) mitigating the labor and time overhead of manual annotation. (2) improving the performance of LLMs in low-resource scenarios by transferring the rich world knowledge in LLMs. (3) generating high-quality samples using LLMs that can be used for fine-tuning of the lightweight model. (4) research on generating metaphorical samples that can allow LLMs to better understand and generate content that contains complex semantics.

Metaphor generation tasks in the past have been divided into two main categories: paraphrase generation and component generation. Metaphor paraphrase generation (Shutova, 2010; Mao et al., 2018, 2022) aims to generate literal paraphrases of target words in a particular context. For example:

- The project was a **piece of cake** for our team.

- The project was **very easy** for our team.

Where "piece of cake" is recognized as a metaphorical expression and the model replaces it with the corresponding literal meaning "very easy". This process involves detecting the metaphor and replacing it with a literal expression that fits the context.

Metaphor component generation Wachowiak and Gromann (2023) and Song et al. (2020) aims at generating the metaphor triad, i.e., tenor (or target domain), vehicle (or source domain), and ground (or attribute). In the past research, Wachowiak and Gromann (2023) uses GPT-3 to generate the corresponding source domain through the target domain, but does not explicitly model the semantic association between the two. In contrast, Song et al. (2020) constructs a knowledge graph using metaphor triads for metaphor paraphrase derivation and generating noun metaphors. However, neither of these has achieved the generation of complete metaphor samples. Generating complete metaphor samples requires more sophisticated semantic understanding and text generation capabilities than simple word substitution or triad generation.

Figure 1: The four sample generation methods explored in this paper.

With the development of LLMs, especially the excellent performance of ChatGPT in zero-shot and few-shot NLP tasks (Meng et al., 2022; Yoo et al., 2021), this paper explores the ability of LLMs to generate complex metaphor samples. We design metaphorical reasoning experiments using LLMs to generate metaphorical interpretations and manually score the generated results to assess the model's comprehension ability. Table 6 shows the scoring results, indicating that LLMs have some potential for metaphor comprehension. We propose two knowledge injection methods: definition-based prompt enhancement (DPE) and semantics-based prompt enhancement (SPE). DPE generates through metaphor definitions, while SPE introduces polysemous information from WordNet or oxford dictionary, treats the first two meanings as literal meanings and the rest as metaphor. In addition, we introduce LLMs direct generation (DG) and example-based prompt enhancement (EPE) methods as control experiments, test three LLMs, ChatGPT, LLaMA and Mixtral. The evaluation uses a combination of automated and manual methods to deeply analyze the similarities and differences between samples generated by LLMs and manually labeled samples with examples. Our contributions include:

1. To the best of our knowledge, it is the first study to apply LLMs to metaphor sample generation, which involves more complex semantic modeling and contextual understanding.

2. We propose two prompt enhancement methods DPE and SPE. Results show that these two methods perform well on different LLMs.

3. Analyzed the LLMs generation samples, and summarized three types of problems in the generation process: traditional meaning misinterpretation, metaphorical evolution neglect, and polysemic confusion.

2 Related Work

2.1 Metaphor Generation

Metaphor generation tasks in the past can be broadly categorized into two types, one for metaphor paraphrase generation and the other for metaphor component generation. Metaphor paraphrase generation aims to generate literal words that correspond to target words in a given context. Shutova (2010) uses syntactic dependencies to filter verb-direct object and subject-verb pairs from the context, which are then filtered and sorted by selection preferences. Mao et al. (2018) assumes that the literal meanings of words occur more frequently in the corpus than their metaphorical meanings, then uses synonyms and superlatives in WordNet as candidate literal meanings for target words. Mao et al. (2022) uses the words with the highest probability of occurrence in the BERT context as replacements for the target words. In contrast to generative paraphrasing, several studies have discussed supervised (Chakrabarty et al., 2021; Shou et al., 2024) or unsupervised methods (Stowe et al., 2021) for converting literals to metaphors.

Metaphor component generation aims to generate the tenor, vehicle and ground. Wachowiak and Gromann (2023) uses GPT-3 to generate a source domain based on a target domain. Shao et al. (2024) creates a Chinese metaphor dataset containing grounds and firstly proposes to introduce Chain-of-Thought (CoT) into metaphor generation. Wang et al. (2024) proposes a multi-stage generative heuristic enhancement prompt framework that improved the ability of LLMs in identifying the

Figure 2: SPE and DPE methods prompt design. w_k denotes the target word and y_k is the label. In DPE, $n_{k,i}$ is the number of samples to be generated for the target word w_k, and $i = 0$ or 1 corresponds to the target word being used literally, metaphorically, respectively. For SPE, v_j denotes the jth lexical sense of the target word w_k. $n_{k,i,j}$ is the number of samples to be generated for the jth meaning of the target word w_k.

tenor, vehicle and ground in Chinese metaphors, whereas Song et al. (2020) introduces a new approach based on knowledge graph embedding, using the metaphor triad (target, attribute, source) to represent the conceptual mapping of metaphorical attribute dependencies, but the task mainly involves the processing of noun metaphors. In addition, Li et al. (2022) and Yang et al. (2023) propose a controlled Chinese simile generation task.

2.2 Metaphor Detection

Metaphor detection aims to determine whether the target words are used in metaphor. Compared to tasks such as sentiment labeling and question and answer, metaphor detection requires the model to understand the implicit meaning of the text more deeply. And this challenge has typically been addressed in prior research by injecting domain knowledge. In prior work, researchers have used a variety of knowledge injection strategies. Among them, Le et al. (2020), Song et al. (2021) and Feng and Ma (2022) use dependency tree knowledge to direct the model to focus on specific syntactic structures. Besides, Mao and Li (2021), Choi et al. (2021) and Su et al. (2020) combine a lexical annotation task (POS), where the POS is considered as a separate subtask in Mao and Li (2021). In addition, Gong et al. (2020), Klebanov et al. (2016) and Zhang and Liu (2023) introduce the WordNet database. Gong et al. (2020) and Klebanov et al. (2016) classify words into fifteen categories based

on semantic features, while Zhang and Liu (2023) constructs a dichotomous subtask by directly using the most common definitions of words in WordNet as literals. Li et al. (2023) utilises FrameNet embeddings to capture concept-level metaphors of words. More recently, Jia and Li (2024b) improves the MIP and SPV structures and proposes a framework for course learning. Jia and Li (2024a) combines prompt learning and knowledge distillation techniques for metaphor detection.

3 Method

This section describes four sample generation methods: the DG, EPE, DPE, and SPE. prompt designs for the DG and EPE methods are shown in Appendix 13.1 and 13.2, respectively. the DPE and SPE methods will be described next.

Definition-based Prompt Enhancement. The DPE approach aims at injecting metaphorical definitions as knowledge into LLMs. This paper uses the definition given by Lakoff and Johnson (2008): extracting familiar concepts in the source domain to understand vague and abstract concepts in the target domain.

Semantics-based Prompt Enhancement. The SPE approach aims to inject the lexical knowledge of the target word into the LLMs. This paper use multiple word sense information from wordnet (Miller, 1995; Fellbaum, 1998) and the oxford dictionary. Among them, wordnet has been shown to help improve metaphor recognition performance

(Gong et al., 2020; Klebanov et al., 2016; Zhang and Liu, 2023). For any target word w_k, as well as the verb meaning sets $\mathcal{V}_k$ retrieved from wordnet ($\mathcal{V}_k$ is sorted by frequency of use), we consider the first two common meanings as literal meanings, and the rest as metaphorical meanings. That is, for any lexical meaning $v_j \in \mathcal{V}_k$:

$$v_j \in \begin{cases} \mathcal{V}_{k,l} & 0 < j \leq 2 \text{ and } y_k = 0 \\ \mathcal{V}_{k,m} & j > 2 \text{ and } y_k = 1, \end{cases} \quad (1)$$

where $\mathcal{V}_{k,l}$ and $\mathcal{V}_{k,m}$ denote the literal and metaphorical lexical sense sets of the target word w_k, respectively. The label $y_k = 0$ indicates that w_k is used non-metaphorically, while $y_k = 1$ indicates that w_k is used metaphorically.

Prompt Construction. The prompt design of DPE and SPE is shown in Fig.2. For the input (w_k, y_k), we first specify the target word $word = w_k$. Then, based on the value of y_k, the model is asked to generate $n_{k,i}$ literal or metaphorical sentences, where $i = 0$ or 1 corresponds to $y_k = 0$, $y_k = 1$, respectively. For DPE, we add the metaphorical definition at the beginning. For SPE, we consider the literal lexical sense set $\mathcal{V}_{k,l}$ and the metaphorical lexical sense set $\mathcal{V}_{k,m}$ for the target word w_k. Specifically, we first divide based on the number of samples to be generated, for $y_k = 1$ there are:

$$n_{k,1,j} = \text{ceil}(\frac{n_{k,1}}{|\mathcal{V}_{k,m}|}), \quad (2)$$

where ceil is an upward rounding function, $|\mathcal{V}_{k,m}|$ denotes the number of metaphorical lexical senses, $n_{k,1,j}$ denotes the target word of the kth metaphorical usage, and the number of samples to be generated for the jth lexical meaning. For example, for the first metaphorical lexical meaning $v_3 \in \mathcal{V}_{k,m}$ and its required number of generated samples $n_{k,1}$. We specify the values of the variables in the prompt: $n = n_{k,1,j}, meaning = v_3$, bootstrap ChatGPT to generate the metaphor samples. The next metaphorical meaning v_4 is then given until $n_{k,1}$ samples have been generated.

4 Fine-tuning Model Experiments

4.1 Experimental Setup

Experiment 1. The experiment is designed to fine-tune the mini-model using the LLM-generated samples as a training set and to test it on three metaphorical datasets, VUAverb, TroFi, and MOH-X (see Appendix 12 for a detailed description of

the datasets). The purpose of the experiment is: (1) verify whether the samples generated by LLMs contain sufficient metaphorical knowledge. Higher quality samples tend to allow the fine-tuned model to achieve higher performance on the metaphor test set. (2) Compare the differences in the samples generated by different LLMs. (3) Discuss how different metaphorical knowledge injection methods affect the quality of sample data generated by LLMs. The experiments include four types of DG (no external knowledge), EPE (metaphorical example knowledge), DPE (metaphorical definition knowledge), and SPE (metaphorical knowledge with multiple word meanings). We use three LLMs for sample generation (see Appendix 14 for descriptions). For fine-tuning, we use RoBERTa (Liu et al., 2019), initialized by the weight parameters of Huggingface (Wolf et al., 2019). The output of the model adopts part of the model idea devised in Choi et al. (2021), i.e., the hidden layer output corresponding to the CLS and the target word is used for classification. Specifically, we first let RoBERTa be trained on DG, EPE, DPE, and SPE samples, respectively, and then validated on the test set. We perform the test set on the entire VUAverb test, TroFi and MOH-X with samples 5875, 3739 and 649, respectively.

Experiment 2. Experiment 2 compares the SPE method for generating samples with manually labeled samples (i.e., the VUAverb training set) in terms of fine-tuning performance and cost. Since SPE introduces metaphorical knowledge of multi-word meanings, in addition to wordnet, oxford dictionary also contains multi-word meanings. We denote the wordnet- and oxford dictionary-based SPE methods as SPE-w and SPE-o, respectively. On fine-tuning, the model fine-tuning method is the same as that of Experiment 1. For cost analysis, we use the manual annotation cost recorded in Wang et al. (2021a) (i.e., \$0.11/per sample). For SPE-generated samples, we tokenize them using the methods provided by RoBERTa (Liu et al., 2019) and record the total number of sample tokens for each method separately. We record the token price given in the official OpenAI website as the automatic labeling cost. The input is \$0.5 per 1M tokens and the output is \$1.5 per 1M tokens.

4.2 Results

Experiment 1. The experimental results are presented in Table 1. Our proposed methods achieve

Method	VUAverb			TroFi			MOH-X		
	P	**R**	**F1**	**P**	**R**	**F1**	**P**	**R**	**F1**
Mixtral-DG	0.516	0.261	0.347	0.531	0.175	0.263	1.000	0.038	0.073
Mixtral-EPE	0.412	0.039	0.071	0.586	0.036	0.067	0.529	0.057	0.103
Mixtral-DPE	0.448	0.375	**0.408**	0.538	0.297	0.383	0.813	0.289	**0.426**
Mixtral-SPE	0.348	0.454	0.394	0.461	0.342	**0.392**	0.551	0.311	0.398
LLaMA3-DG	0.547	0.166	0.254	0.558	0.146	0.231	0.900	0.171	0.288
LLaMA3-EPE	0.440	0.086	0.144	0.442	0.101	0.164	0.545	0.038	0.071
LLaMA3-DPE	0.552	0.277	**0.368**	0.565	0.242	**0.338**	0.858	0.384	**0.531**
LLaMA3-SPE	0.325	0.338	0.332	0.420	0.248	0.312	0.559	0.359	0.446
ChatGPT-DG	0.541	0.136	0.217	0.506	0.084	0.144	0.870	0.171	0.286
ChatGPT-EPE	0.450	0.294	0.356	0.564	0.266	0.361	0.516	0.316	0.392
ChatGPT-DPE	0.507	0.298	0.376	0.549	0.237	0.330	0.836	0.324	0.467
ChatGPT-SPE	0.302	0.794	**0.438**	0.439	0.910	**0.593**	0.497	0.470	**0.483**

Table 1: LLM generated samples on three metaphorical datasets to fine-tune performance. Experiments is binary classification. **F1** scores are core metrics indicating the weighted average of precision (**P**) and recall (**R**).

Method	Fine-tuning performance									Labeling costs		
	VUAverb			TroFi			MOH-X					
	P	**R**	**F1**	**P**	**R**	**F1**	**P**	**R**	**F1**	**Input**	**Output**	**Avg**
GT	0.479	0.646	0.550	0.509	0.731	0.600	0.738	0.768	0.753	-	-	869$
SPE-w	0.302	0.794	0.438	0.439	0.910	0.593	0.497	0.470	0.483	0087$	0.252$	0.339$
SPE-o	0.356	0.842	**0.501**	0.453	0.895	0.601	0.609	0.806	**0.694**	**0.068$**	0.280$	0.348$
DPE+SPE-o	0.311	0.861	0.457	0.444	0.958	**0.607**	0.497	0.981	0.660	0.090$	**0.177$**	**0.267$**

Table 2: Comparison of the SPE method with manually labeled samples in terms of fine-tuning performance (left) and labeling cost (right). **Input**: cost of input for the prompt design; **Output**: cost of ChatGPT output data; **Avg**: average of inputs and outputs

the best F1 performance on all three LLMs and all three datasets (e.g., on VUAverb, SPE 0.438 vs. EPE 0.356 on ChatGPT and DPE 0.368 vs. DG 0.254 on LLaMA3 and DPE 0.408 vs. DG 0.347 on Mixtral). This shows that the DPE and SPE methods somewhat balance the accuracy of detecting metaphorical and literal samples.

For the EPE method introduced as an example, while its performance is better for samples generated using ChatGPT, we observe a larger performance degradation when using the open-source Mixtral and LLaMA3 models (e.g., on F1, Chat-GPT 0.356 vs. LLaMA3 0.144 on VUAverb and ChatGPT 0.361 vs. LLaMA3 0.164 on TroFi and ChatGPT 0.392 vs. Mixtral 0.103 on MOH-X). On the one hand, it shows that example knowledge can be counterproductive if the model is unable to understand or misinterprets the introduced example information. On the other hand, it also shows that compared to closed-source ChatGPT, current open-source LLM models often do not understand the metaphorical information in the examples well, which leads to a drastic decrease in the recall of the EPE method (e.g., on VUAverb, EPE 0.039 on Mixtral and EPE 0.086 on LLaMA3).

For our proposed DPE method, the low recall of DG or EPE is improved without decreasing precision (e.g., on VUAverb, DPE 0.277 vs. EPE 0.086 on LLaMA and DPE 0.375 vs. EPE 0.039 on Mixtral). This suggests that introducing metaphor definitions works better than introducing metaphor examples when modeling capabilities are weak. For ChatGPT with some degree of metaphor comprehension, the difference in recall between the

Method	Clarity			Relevance			Diversity		
	Literal	Metaphor	Avg	Literal	Metaphor	Avg	Literal	Metaphor	Avg
GT	4.054	3.828	3.941	4.075	3.387	3.731	**4.086**	**3.785**	**3.935**
DG	4.677	4.355	4.516	**4.151**	**3.699**	**3.925**	3.753	3.419	3.586
EPE	4.505	4.312	4.409	3.430	3.344	3.387	3.796	3.505	3.651
DPE	**4.710**	**4.473**	**4.591**	4.108	3.237	3.672	3.892	3.376	3.634
SPE	4.602	4.333	4.468	4.097	3.301	3.699	3.946	3.634	3.790

Table 3: Results of manual evaluation of ChatGPT generated samples and manually labeled samples. Clarity, relevance, and diversity are formulated in Appendix 15.1. **Literal**: literal sample scores; **Metaphor**: metaphorical sample scores; **Avg**: average of Literal and Metaphor samples.

two is not significant when definitions or examples are introduced (e.g., DPE 0.298 vs. EPE 0.294 on VUAverb and DPE 0.237 vs. EPE 0.266 on TroFi and DPE 0.324 vs. EPE 0.316 on MOH-X).

In addition, DG, EPE and DPE tend to have higher precision than recall. It shows a stronger ability to recognize non-metaphorical samples. In particular, the DG method is the most prominent among the three (e.g., on MOH-X, DG 1 on Mixtral and DG 0.9 on LLaMA3 and DG 0.870 on ChatGPT). Since DG tend to use simple instruction descriptions, whereas EPE and DPE methods introduce partial external knowledge. This suggests that unguided LLM output knowledge tends to be non-metaphorical. This is manifested in the fine-tuning model with its low recall (i.e., weak recognition of metaphorical samples). In contrast, our proposed alternative SPE approach based on multiple lexical meanings has a more balanced precision and recall on all three LLMs, and even higher recall (e.g., on ChatGPT, precision 0.302 vs. recall 0.794 on VUAverb and precision 0.439 vs. recall 0.910 on TroFi and precision 0.497 vs. recall 0.470 on MOH-X). This suggests that injecting metaphorical knowledge in the form of multiple lexical meanings is superior to introducing metaphorical examples or definitions directly.

Experiment 2. As seen from the results in Table 2, the SPE-o method outperforms the SPE-w method in fine-tuning on all three metaphor datasets. Compared to wordnet, Oxford dictionaries tend to contain richer and more current lexical information. As a result, the SPE-oxford method generates higher quality, as evidenced by further improvements in precision and recall (e.g., on VUAverb SPE-Oxford 0.356 vs. SPE-wordnet 0.302 on Pre and SPE-Oxford 0.842 vs. SPE-wordnet 0.794 on Rec). While SPE-o is lower

than the manually labelled samples on VUAverb and MOH-X (i.e., on F1, -0.049 on VUAverb and -0.059 on MOH-X), it is slightly higher on TroFi (i.e., on F1, + 0.001 on TroFi). Overall, although the SPE-o method slightly underperforms the real samples in terms of fine-tuning performance, it requires only about 1/25000 of the cost of manual labelling. This proves the superiority of our proposed method. In addition, the F1 values of the combined DPE+SPE-o method on VUAverb and MOX instead show a decrease (e.g., SPE-o 0.501 vs. DPE+SPE-o 0.457 on VUAverb and SPE-o 0.694 vs. DPE+SPE-o 0.660). Since the SPE approach is based on multiple lexical meanings, it inherently contains metaphorical knowledge. Therefore, giving both definition-based and lexical meaning-based metaphorical knowledge may introduce noise that affects the quality of the metaphorical samples that the model ultimately generates.

5 Manual Evaluation

The manual evaluation aims to compare the similarities and differences between the samples generated by ChatGPT and the manually labelled real samples. The evaluation is conducted in groups (e.g., the target word "abandon" with the label "1"). We randomly select 50 target word groups containing both literal and metaphorical usage. The sample size for each method is approximately 1000, or 14% of the total. We invite three volunteers to conduct the assessment, using clarity, relevance, and variety as assessment metrics, and redefine these metrics based on the characteristics of the metaphorical task (see Appendix 15.1 for specific definitions). Ratings ranged from 1 to 5, and the final result is the average of the three ratings.

Results. The results of the manual evaluation are

Types	DG	EPE	DPE	SPE
MCM	The account manager was responsible for maintaining relationships ⋯	Taking into account the increasing number of car accidents ⋯	I will need to account for all the expenses before submitting the budget report.	The meticulous accountant carefully accounted for every penny ⋯
NME	The sun rose, painting the sky with yellow, as if expecting a glorious day ahead.	The sunflower, reaching for the sky, expects a warm embrace from the sun.	She found that exceeding expectations was not as difficult as she had anticipated.	It's natural to expect professionalism and competence from our employees ⋯
PC	Being the winner entitled him to a cash prize.	⋯ as the ancient philosophers entitled them.	The painting was entitled "Starry Night" by Vincent ⋯	⋯ entitles you to receive a certificate of achievement.

Table 4: Common Errors Showcase. **MCM** stands for misinterpretation of conventional meaning. **NME** stands for neglect of metaphorical evolution. **PC** stands for polysemy confusion. the example of MCM requires ChatGPT to generate the literal usage of "account", and the examples of NWE and PC require the metaphorical usage of "expect" and the literal usage of "entitle", respectively.

shown in Table 3. Compared to the real sample (GT), the clarity scores of the samples generated using ChatGPT are higher (e.g., on avg, DG +0.623 and EPE +0.451 and DPE +0.656 and SPE +0.548). This suggests that the generated samples are easier to understand. Similarly, DG performs best on relevance (e.g., +0.194 on GT and +0.226 on SPE). This suggests that prompt without external knowledge makes LLMs less disturbed compared to the introduction of metaphorical knowledge generation methods, thus ensuring to some extent that LLMs generate samples with better accuracy.

However, the understandability and accuracy of the generated samples do not enhance the performance of the fine-tuned model (comp. GT, DG +0.575 on clarity and DG +0.194 on relevance, but DG -0.333 on VUAverb-F1). Instead, there is a correlation between diversity and model fine-tuning performance (e.g., on ChatGPT and VUAverb, GT-avg 3.935 vs. GT-F1 0.550 and SPE-avg 3.790 vs. SPE-F1 0.438 and DG-avg 3.586 vs. DG-F1 0.217). This suggests that the richness of metaphorical usage can inject more metaphorical knowledge into the fine-tuned model, thus improving the quality of the metaphorical samples. In addition, we notice that EPE scores on relevance are relatively weak (e.g., on avg, -0.538 on EPE and -0.285 on DPE). This suggests that LLMs have difficulty understanding the metaphorical knowledge in the ex-

amples. Finally, the overall ratings of the different method-generated samples on non-metaphor are always higher than those of the metaphor samples (e.g., on GT, Literal 4.054 vs. Metaphor 3.828 on Clarity and Literal 4.075 vs. Metaphor 3.387 on Relevance). This also reflects the relative weakness of ChatGPT in its ability to generate metaphor samples.

6 Automatic Evaluation

Method	Automatic Evaluation			
	Bleu	**Rouge**	**Meteor**	**Avg**
DG to GT	0.111	0.149	0.305	0.188
EPE to GT	**0.194**	**0.212**	**0.348**	**0.251**
DPE to GT	0.115	0.156	0.313	0.195
SPE to GT	0.131	0.142	0.275	0.183

Table 5: The result of the automatic evaluation. Bleu and Rouge are Bleu-1 and Rouge-1, respectively. The automatic evaluations are all referenced to the manually labeled samples.

This experiment uses automatic evaluation to explore the similarity between ChatGPT-generated samples and manually labeled samples. We use three automatic evaluation metrics, Bleu, Rouge,

and Meteor, to measure the degree of similarity between LLM-generated and manually labeled samples (see Appendix 15.2 for a detailed description). **Result.** The results of the experiments are presented in Table 5. EPE reached its maximum values on three metrics (e.g., EPE 0.194 vs. SPE 0.131 on Bleu and EPE 0.212 vs. DPE 0.156 on Rouge and EPE 0.251 vs. DPE 0.195 on Meteor). This suggests that the method of introducing the examples was able to guide ChatGPT to generate samples similar to the examples, but similarity does not mean that the metaphor was understood (see the manual evaluation analysis). Additionally, we have observed that direct generation was more similar to using the defined DPE approach on three metrics (i.e., DPE 0.115 vs. DG 0.111 on Bleu and DPE 0.156 vs. DG 0.149 on Rouge and DPE 0.313 vs. DG 0.305 on Meteor). This suggests that the direct definition-giving approach minimizes the disturbance of external knowledge while improving the metaphor comprehension of ChatGPT. Comparatively, the EPE and SPE methods are more variable.

7 Case Study

Despite the huge cost advantage of the ChatGPT method, there are still some problems with the samples it generates, which can be summarized into three categories: the misinterpretation of conventional meaning (MCM), the neglect of metaphorical evolution (NME) and polysemy confusion (PC). Examples of problems in these three categories are listed in Table 4.

MCM states that ChatGPT incorrectly interprets the conventional meaning as a literal use. For example, the literal use of "account", which originally meant "counting", evolved into "customer or client having an account" or "statement answering for conduct". However, due to the customized meaning of "having an account", ChatGPT misinterprets it as literal. In the MCM example, EPE and DPE generated accurately, interpreting it as "counting"; DG misinterpreted "having an account" as literal, and SPE directly generated "accounting".

NME states that ChatGPT often creates metaphors by anthropomorphizing elements of nature, while ignoring the evolution of metaphors. Take the metaphorical usage of "expect" as an example, its initial meaning is "long for, anticipate", which is later extended to mean "the expected changes in the economy and stock market". In the NME example, DG and EPE ignore the evolution of metaphors and construct inappropriate metaphors (e.g., "sun expects", "sunflower expects") through anthropomorphism. There are many such examples generated by the DG method. Differently, DPE and SPE did not find metaphorical meanings, and misidentified "long for, anticipate" as metaphorical.

PC indicates that too many lexical variations led to confusion in the understanding of metaphors in ChatGPT. Take the literal usage of "entitle" as an example, its original meaning is "to give a title to a chapter, book" or "give a title or name to". which is later extended to "bestow an office" or "give (someone) property". Entitle obviously has more literal and derived meanings than other words. In the PC example, DG and SPE generate the wrong interpretation of "have the right to", while EPE correctly translates it as "give a title or name to" due to the use of manually labeled samples as examples. DPE was also correctly interpreted as "give a title or name to".

8 Conclusion

This work deeply investigates the capability of LLMs in generating metaphor samples and propose two prompt enhancement methods: definition-based prompt enhancement (DPE) and semantics-based prompt enhancement (SPE). The experimental results show that our methods exhibit excellent performance with different LLMs as generators. In particular, when using the oxford dictionary as a multi-syntactic knowledge source, the SPE method's fine-tuning performance approaches that of manually labeled samples at 1/25000 of the cost of manual labeling. Through metaphorical reasoning experiments, manual and automated evaluations, and example analyses, we find that current LLMs are capable of understanding and interpreting metaphors to a certain extent, but they still face significant challenges in generating accurate and diversified metaphor samples. significant challenges.

9 Limitations

This paper investigates the problem of how to generate a metaphorical dataset using ChatGPT and proposes a semantics-based prompt enhancement (SPE). The method relies on the knowledge of word meanings in wordnet, which brings some overhead. Example analysis reveals that there are still a number of problems with the current samples generated using ChatGPT, which are broadly classified into three categories: the misinterpretation of conventional meaning (MCM), the neglect of metaphorical evolution (NME), and the polysemy confusion (PC). Addressing these issues still requires improvements in generating sources (ChatGPT) as well as prompt design methods. In future work, we will aim to explore ways to minimize the reliance on manual annotation or the use of external databases, and to ensure the quality of metaphorical sample generation.

10 Ethics Statement

In this paper, we detail how ChatGPT is utilized to generate the metaphorical dataset. The datasets used and the research papers cited are obtained from publicly available sources, and we strictly adhere to academic and research ethics guidelines to ensure the legitimacy and transparency of the research process. We place particular emphasis on transparency and openness of information, and are committed to providing clear methodological descriptions and experimental details so that other researchers can understand and reproduce our research. We encourage other researchers in our academic community to conduct responsible research and adhere to best practices in knowledge sharing to advance the continued development of the field. Through open information sharing, we expect to foster broader collaboration and deeper understanding of the metaphor detection task.

References

Julia Birke and Anoop Sarkar. 2006. A clustering approach for nearly unsupervised recognition of nonliteral language. In *11th Conference of the European Chapter of the Association for Computational Linguistics*, pages 329–336.

Tuhin Chakrabarty, Xurui Zhang, Smaranda Muresan, and Nanyun Peng. 2021. Mermaid: Metaphor generation with symbolism and discriminative decoding. *arXiv preprint arXiv:2103.06779*.

Eugene Charniak, Don Blaheta, Niyu Ge, Keith Hall, John Hale, and Mark Johnson. 2000. Bllip 1987-89 wsj corpus release 1. *Linguistic Data Consortium, Philadelphia*, 36.

Minjin Choi, Sunkyung Lee, Eunseong Choi, Heesoo Park, Junhyuk Lee, Dongwon Lee, and Jongwuk Lee. 2021. Melbert: Metaphor detection via contextualized late interaction using metaphorical identification theories. *arXiv preprint arXiv:2104.13615*.

B Edition, BNC Baby, and BNC Sampler. British national corpus.

Christiane Fellbaum. 1998. *WordNet: An electronic lexical database*. MIT press.

Huawen Feng and Qianli Ma. 2022. It's better to teach fishing than giving a fish: An auto-augmented structure-aware generative model for metaphor detection. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 656–667.

Hongyu Gong, Kshitij Gupta, Akriti Jain, and Suma Bhat. 2020. Illinimet: Illinois system for metaphor detection with contextual and linguistic information. In *Proceedings of the Second Workshop on Figurative Language Processing*, pages 146–153.

Kaidi Jia and Rongsheng Li. 2024a. Enhancing metaphor detection through soft labels and target word prediction.

Kaidi Jia and Rongsheng Li. 2024b. Metaphor detection with context enhancement and curriculum learning. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 2726–2737.

Beata Beigman Klebanov, Chee Wee Leong, E Dario Gutierrez, Ekaterina Shutova, and Michael Flor. 2016. Semantic classifications for detection of verb metaphors. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 101–106.

George Lakoff and Mark Johnson. 2008. *Metaphors we live by*. University of Chicago press.

Duong Le, My Thai, and Thien Nguyen. 2020. Multitask learning for metaphor detection with graph convolutional neural networks and word sense disambiguation. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 8139–8146.

Chee Wee Leong, Beata Beigman Klebanov, Chris Hamill, Egon Stemle, Rutuja Ubale, and Xianyang Chen. 2020. A report on the 2020 vua and toefl metaphor detection shared task. In *Proceedings of the second workshop on figurative language processing*, pages 18–29.

Chee Wee Leong, Beata Beigman Klebanov, and Ekaterina Shutova. 2018. A report on the 2018 vua metaphor detection shared task. In *Proceedings of*

the *Workshop on Figurative Language Processing*, pages 56–66.

Yucheng Li, Chenghua Lin, and Frank Guerin. 2022. Cm-gen: A neural framework for chinese metaphor generation with explicit context modelling. In *Proceedings of the 29th international conference on computational linguistics*, pages 6468–6479.

Yucheng Li, Shun Wang, Chenghua Lin, and Guerin Frank. 2023. Metaphor detection via explicit basic meanings modelling. *arXiv preprint arXiv:2305.17268*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Edward Loper and Steven Bird. 2002. Nltk: The natural language toolkit. *arXiv preprint cs/0205028*.

Rui Mao and Xiao Li. 2021. Bridging towers of multi-task learning with a gating mechanism for aspect-based sentiment analysis and sequential metaphor identification. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 13534–13542.

Rui Mao, Xiao Li, Mengshi Ge, and Erik Cambria. 2022. Metapro: A computational metaphor processing model for text pre-processing. *Information Fusion*, 86:30–43.

Rui Mao, Chenghua Lin, and Frank Guerin. 2018. Word embedding and wordnet based metaphor identification and interpretation. In *Proceedings of the 56th annual meeting of the association for computational linguistics*. Association for Computational Linguistics (ACL).

Yu Meng, Jiaxin Huang, Yu Zhang, and Jiawei Han. 2022. Generating training data with language models: Towards zero-shot language understanding. *Advances in Neural Information Processing Systems*, 35:462–477.

George A Miller. 1995. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11):39–41.

Saif Mohammad, Ekaterina Shutova, and Peter Turney. 2016. Metaphor as a medium for emotion: An empirical study. In *Proceedings of the Fifth Joint Conference on Lexical and Computational Semantics*, pages 23–33.

Yujie Shao, Xinrong Yao, Xingwei Qu, Chenghua Lin, Shi Wang, Stephen W Huang, Ge Zhang, and Jie Fu. 2024. Cmdag: A chinese metaphor dataset with annotated grounds as cot for boosting metaphor generation. *arXiv preprint arXiv:2402.13145*.

Xincheng Shou, Xiaoxi Huang, and Wenlong Xi. 2024. Conceptual metaphor theory guides gans for generating metaphors and interpretations. *IEEE Access*.

Ekaterina Shutova. 2010. Automatic metaphor interpretation as a paraphrasing task. In *Human language technologies: the 2010 annual conference of the North American chapter of the association for computational linguistics*, pages 1029–1037.

Ekaterina Shutova, Douwe Kiela, and Jean Maillard. 2016. Black holes and white rabbits: Metaphor identification with visual features. In *Proceedings of the 2016 conference of the North American chapter of the association for computational linguistics: Human language technologies*, pages 160–170.

Wei Song, Jingjin Guo, Ruiji Fu, Ting Liu, and Lizhen Liu. 2020. A knowledge graph embedding approach for metaphor processing. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:406–420.

Wei Song, Shuhui Zhou, Ruiji Fu, Ting Liu, and Lizhen Liu. 2021. Verb metaphor detection via contextual relation learning. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 4240–4251.

Gerard Steen, Aletta G Dorst, J Berenike Herrmann, Anna Kaal, Tina Krennmayr, Trijntje Pasma, et al. 2010. A method for linguistic metaphor identification. *Amsterdam: Benjamins*.

Kevin Stowe, Tuhin Chakrabarty, Nanyun Peng, Smaranda Muresan, and Iryna Gurevych. 2021. Metaphor generation with conceptual mappings. *arXiv preprint arXiv:2106.01228*.

Chuandong Su, Fumiyo Fukumoto, Xiaoxi Huang, Jiyi Li, Rongbo Wang, and Zhiqun Chen. 2020. Deepmet: A reading comprehension paradigm for token-level metaphor detection. In *Proceedings of the second workshop on figurative language processing*, pages 30–39.

Lennart Wachowiak and Dagmar Gromann. 2023. Does gpt-3 grasp metaphors? identifying metaphor mappings with generative language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1018–1032.

Jie Wang, Jin Wang, and Xuejie Zhang. 2024. Chinese metaphor recognition using a multi-stage prompting large language model. *arXiv preprint arXiv:2408.09177*.

Shuohang Wang, Yang Liu, Yichong Xu, Chenguang Zhu, and Michael Zeng. 2021a. Want to reduce labeling cost? gpt-3 can help. *arXiv preprint arXiv:2108.13487*.

Zirui Wang, Adams Wei Yu, Orhan Firat, and Yuan Cao. 2021b. Towards zero-label language learning. *arXiv preprint arXiv:2109.09193*.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, M Funtowicz, et al. 2019. Huggingface's transformers: State-of-the-art natural language processing. arxiv. *arXiv preprint arXiv:1910.03771*.

Kexin Yang, Dayiheng Liu, Wenqiang Lei, Baosong Yang, Xiangpeng Wei, Zhengyuan Liu, and Jun Xie. 2023. Fantastic expressions and where to find them: Chinese simile generation with multiple constraints. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 468–486.

Kang Min Yoo, Dongju Park, Jaewook Kang, Sang-Woo Lee, and Woomyeong Park. 2021. Gpt3mix: Leveraging large-scale language models for text augmentation. *arXiv preprint arXiv:2104.08826*.

Shenglong Zhang and Ying Liu. 2023. Adversarial multi-task learning for end-to-end metaphor detection. *arXiv preprint arXiv:2305.16638*.

11 Metaphorical Reasoning

To explore the ability of LLM in understanding metaphorical connotations, we conduct a metaphorical reasoning study. We use LLM to generate metaphorical interpretations for specific metaphor samples, and manually rated these interpretations on a scale of 1 to 5. The following shows the results of the manually generated and LLM-generated interpretations of the metaphor example "I attacked the problem as soon as I got out of bed":

- **Human:** metaphor. It implies an aggressive approach, urgency, and determination to solve the problem immediately. (scores: 5)

- **ChatGPT:** metaphor. No physical violence is implied, and "attack" means to tackle or confront vigorously. (score: 4)

- **LLaMA3.** metaphor. The problem is not a physical entity that can be physically attacked. (score: 4)

Model	VUAPOS	TroFi	MOH-X
ChatGPT3.5	3.83	**3.97**	3.88
LLaMA3-70B	**3.90**	3.85	**3.94**

Table 6: Results of manual evaluation of LLM metaphorical reasoning. The experimental results show that LLM has some degree of metaphor comprehension ability.

12 Fine-tuning Datasets

Among the fine-tuning experiments, we use the metaphor samples generated by LLMs as the training set to fine-tune RoBERTa. and then test them on three metaphor datasets, VUAverb, TroFi and MOH-X, respectively.

VUAverb. The VU Amsterdam Metaphor Corpus (VUAMC) (Steen et al., 2010) metaphorically annotates each lexical unit in a subset of the British National Corpus (Edition et al.), and the annotation was done using the MIPVU program. Based on VUAMC, several different variants of the VUA corpus have emerged, among which VUAverb is the verb version of the VUA corpus. This paper uses the VUAverb dataset mentioned in the metaphor detection shared task (Leong et al., 2018, 2020), which contains 15516 training samples and 5873 test samples.

VUAverb Cuts. VUAverb has the problem of

long-tailed distribution. for example, the target words "say" and "go" contain 509 and 506 samples respectively, while the number of most verbs is very small. According to statistics, among the 1875 verbs in the VUAverb training set, there are only 257 verbs with number greater than 10 (13.7% of the total), while there are 781 verbs with number equal to 1 (41.7% of the total). To mitigate the long-tailed distribution, we trim the VUAverb train. Specifically, we first filter out the target word categories with sample sizes larger than 10, and then randomly select 10 of them as the final samples of the category. After such processing, we finally obtain 7,900 pieces of data, which will be used as crowdsourced annotations (CA) data for subsequent experiments.

TroFi. TroFi (Birke and Sarkar, 2006) is a verb-target focused dataset containing the literal and metaphorical usage of 50 English verbs from the 1987-1989 Wall Street Journal corpus (Charniak et al., 2000). We use the same version of TroFi as Choi et al. (2021) and Zhang and Liu (2023), which contains a total of 3739 samples. These samples cover rich verb instances and provide diverse contextual information.

MOH-X. The MOH dataset is created by Mohammad et al. (2016), and its construction methodology involves first extracting polysemous verb samples from wordnet, and then metaphorically labeling the sentences via a crowdsourcing platform. To ensure the quality of the dataset annotation, Mohammad et al. (2016) adopted a 70% annotation consistency criterion. A subset of MOH, MOH-X (Shutova et al., 2016), contains 649 samples and is a commonly used dataset in mainstream metaphor detection systems (Choi et al., 2021; Zhang and Liu, 2023). This subset excludes instances with pronouns, dependent subjects or objects. Therefore, we use MOH-X for model evaluation.

13 Prompt Designs

13.1 Direct Generation Method

The DG approach aims to direct ChatGPT to generate samples of a specified type without using external knowledge content. For input, $w_k, y_k, n_{k,i}$ represent the target word, label, and the number of samples to be generated, respectively. ($n_{k,i}$ is the same as the number of samples in the same group in VUAverb cut). $i = 0$ or 1 corresponds to $y_k = 0$, $y_k = 1$, respectively, indicating that the target word is literal, metaphorical usage. The specific prompt

---

| **Prompt:** |
| Generate $\mathbf{n_{k,i}}$ sentences in different styles containing the specified verb based on the explanation, where the verb are used **metaphorically**. |
| word: $\mathbf{w_k}$ |
| s-1: |
| ...... |

Table 7: DG prompt.

design is shown in Table 7.

13.2 Example-based Prompt Enhancement Method

| **Prompt:** |
| Generate $\mathbf{n_{k,i}}$ sentences in different styles containing the specified verb based on the explanation, where the verb are used **metaphorically**. |
| word: $\mathbf{w_k}$ |
| example: $\mathbf{d_{k,i}}$ |
| s-1: |
| ...... |

Table 8: EPE prompt.

Example-based prompt enhancement (EPE) methods are commonly used techniques for prompt learning. For example, Yoo et al. (2021); Wang et al. (2021b) provide one or more examples and category labels for each category of a particular task. Inspired by the above, this paper introduces the EPE method and adapts it for metaphorical features. First, we notate the sample set of all available examples (i.e., the VUAverb cut) as $\mathcal{D} = (x_i, w_i, y_i) | 1 \leq i \leq N$, where x_i, w_i, and y_i are the text, the target word, and the corresponding labels, respectively. In then, we classify $\mathcal{D}$ into subsets $\mathcal{D}_{ki}$ based on the target word w_k and the corresponding label y_k, where $i = 0$ or 1 denotes the literal, metaphorical usage, respectively. For each category $\mathcal{D}_{k,i}$, we randomly select a sample $d_{k,i}$ as an example. Finally, $d_{k,i}$ will be used as a prompt message in the prompt.

14 LLM Introduction

In the fine-tuning experiments, we introduced three LLMs as metaphorical sample generators, which are:

- **Mixtral**: Mixtral is an open source generative sparse expert mixture model provided by Mistral AI[1]. We use Mixtral-8x7B-Instruct-v0.1 version, whose weight parameters are derived from huggingface[2].

- **LLaMA3**: LLaMA3 is a parametric large language model released by Meta AI on April 18, 2024, including 8B and 70B. We use the version Llama-3-70B-Instruct, its weights can be obtained from the official website[3].

- **ChatGPT**: ChatGPT is a closed-source model developed by OpenAI, which is available for paid use through API[4]. This paper, the version gpt-3.5-turbo-0125 is used.

15 Evaluation Metrics

15.1 Manual Evaluation Metrics

In the manual evaluation experiments on ChatGPT generated samples, we used clarity, relevance, and diversity as evaluation metrics, and their specific meanings are:

- **Clarity**: the ease with which a metaphor can be understood. The greater the number of samples in the same sample set where it is easier to judge the metaphor, the higher the clarity.

- **Relevance**: whether the category (metaphorical or literal) in which the sample is labeled matches the actual usage of the sample. The greater the number of matching samples in the same sample group, the greater the correlation.

- **Diversity**: whether the usage of the sample metaphors (often expressed in different word meanings) is diverse within the same group. For example, "catch" is "to win someone's affection or love" in "catch someone's heart" and "to attract someone's attention" in "catch someone's eye".

15.2 Automatic Evaluation Metrics

In the automated evaluation experiments on ChatGPT generated samples, we used Bleu, Rouge and Meteor as evaluation metrics, and their specific meanings are:

- **Bleu**: Bleu calculates how well the LLM output matches the real samples on n-grams of different lengths. We use the nltk (Loper and Bird, 2002) tool to calculate Bleu-1 for generated samples and manually labeled samples separately.

- **Rouge**: Rouge is similar to Bleu and also uses the n-gram computation method, but turns precision into recall. In this paper, we use the ROUGE_score library function in python to calculate ROUGE-1.

- **Meteor**: Meteor is an improved version of Bleu, which performs finer-grained matching by taking into account lexical variations (e.g., roots, synonyms) and word order. Again the nltk (Loper and Bird, 2002) tool was used for the computation.

16 Sample Fusion Experiment

This experiment explores the effects of three methods, DG, EPE and SPE, on the performance of the test set after gradually introducing manually labeled samples (GT). We designed six experiments to examine different combinations of generated and GT samples with different percentages: 100% generated samples + 0% GT samples, 80% generated samples + 20% GT samples, 60% generated samples + 40% GT samples, 40% generated samples + 60% GT samples, 20% generated samples + 80% GT samples, and 0% generated samples + 100% GT samples. In the experiments, we randomly selected percentages in terms of target word categories (target word + label), and if the number of group samples was less than the number of samples to be extracted, the method of repeated extraction was used.

results. On both VUAverb and TroFi (see Figure 3 a,b), the introduction of the original sample at the beginning leads to a decrease in accuracy. This suggests that the difference in the distribution of the generated samples and the original samples affects the model's ability to learn metaphorical information, which leads to the opposite effect. In contrast, compared to DG and SPE, EPE has an early turning point in the decline of VUAverb-Acc, and its

---

[1]https://mistral.ai/news/mixtral-of-experts/
[2]https://huggingface.co/mistralai/Mixtral-8x7B-Instruct-v0.1/tree/main
[3]https://llama.meta.com/llama-downloads
[4]https://platform.openai.com/

Figure 3: Plot of the results of the sample fusion experiment. The experiment aims to investigate the impact of the performance of the three methods DG, EPE and SPE on the test set after the gradual introduction of manually labeled samples. The top, bottom graphs show the relationship between accuracy, F1 score and the percentage of manually labeled samples, respectively.

performance starts to increase after 20%. This is due to the fact that the examples of the EPE method are derived from VUAverb. However, Acc is also able to improve as the original data share continues to increase. Moreover, the F1 values of the three methods in each dataset also show a general upward trend (see Figure 3 d,e,f). This indicates that the introduction of the original sample can improve the ability of the model model to capture metaphorical information.

In addition, since the DG method has a low performance, the introduction of a small number of proto-samples can achieve a high F1 performance improvement (e.g., 100% DG + 0% GT 0.299 vs. 80% DG + 20% GT 0.465 on VUAverb and 100% DG + 0% GT 0.272 vs. 80% DG + 20% GT 0.569 on TroFi). The EPE and SPE originally had not-so-low F1 values, so the introduction of a small number of original samples yielded little in terms of performance improvement.

Overall, the introduction of manually labeled data on top of the ChatGPT generated data is related to the performance of the generated data on the test set. On the one hand, researchers may not be able to construct prompts that are suitable for certain general tasks. therefore, they often generate samples directly using ChatGPT. This situation makes it possible to introduce partially manually labeled data, and by paying a small portion of the cost of manual labeling, the samples can quickly catch up in performance with the performance of the samples generated by the customized prompt.

On the other hand, if the researcher is able to design a reasonable prompt based on a specific task (e.g., the SPE method proposed in this paper). As it performs well on the test set. Therefore, the introduction of some of the original sample data may lead to performance degradation due to factors such as distribution mismatch, or yield little results. In this regard, the second case is not used to introduce manually labeled samples.