Hierarchical Few-Shot Imitation with Skill Transition Models

Abstract

A desirable property of autonomous agents is the ability to both solve long-horizon problems and generalize to unseen tasks. Recent advances in data-driven skill learning have shown that extracting behavioral priors from offline data can enable agents to solve challenging long-horizon tasks with reinforcement learning. However, generalization to tasks unseen during behavioral prior training remains an outstanding challenge. To this end, we present Few-shot Imitation with Skill Transition Models (FIST), an algorithm that extracts skills from offline data and utilizes them to generalize to unseen tasks given a few demonstrations at test-time. FIST learns an inverse skill dynamics model, a distance function, and utilizes a semi-parametric approach for imitation. We show that FIST is capable of generalizing to new tasks and substantially outperforms prior baselines in navigation experiments requiring traversing unseen parts of a large maze and 7-DoF robotic arm experiments requiring manipulating previously unseen objects in a kitchen.

1. Introduction

We are interested in developing control algorithms that enable robots to solve complex and practical tasks such as operating kitchens or assisting humans with everyday chores at home. There are two general characteristics of real-world tasks – long-horizon planning and generalizability. Practical tasks are often long-horizon in the sense that they require a robot to complete a sequence of subtasks. For example, to cook a meal a robot might need to prepare ingredients, place them in a pot, and operate the stove before the full meal is ready. Additionally, in the real world many tasks we wish our robot to solve may differ from tasks the robot has completed in the past but require a similar skillset. For example, if a robot learned to open the top cabinet drawer it

should be able to quickly adapt that skill to open the bottom cabinet drawer. These considerations motivate our research question: *how can we learn skills that enable robots to generalize to new long-horizon downstream tasks?*

Recently, learning data-driven behavioral priors has become a promising approach to solving long-horizon tasks. Given a large unlabeled offline dataset of robotic demonstrations solving a diverse set of tasks this family of approaches (Singh et al., 2021; Pertsch et al., 2020; Ajay et al., 2021) extract behavioral priors by fitting maximum likelihood expectation latent variable models to the offline dataset. The behavioral priors are then used to guide a Reinforcement Learning (RL) algorithm to solve downstream tasks. By selecting skills from the behavioral prior, the RL algorithm is able to explore in a structured manner and can solve long-horizon navigation and manipulation tasks. However, the generalization capabilities of RL with behavioral priors are limited since a different RL algorithm needs to be trained for each downstream task and training each RL algorithm often requires millions of environment interactions.

On the other hand, few-shot imitation learning has been a promising paradigm for generalization. In the few-shot imitation learning setting, an imitation learning policy is trained on an offline dataset of demonstrations and is then adapted in few-shot to a downstream task (Duan et al., 2017). Few-shot imitation learning has the added advantage over RL in that it is often easier for a human to provide a handful of demonstrations than it is to engineer a new reward function for a downstream task. However, unlike RL with behavioral priors, few-shot imitation learning is most often limited to short-horizon problems. The reason is that imitation learning policies quickly drift away from the demonstrations due to error accumulation (Ross et al., 2011b), and especially so in the few-shot setting when only a handful of test-time demonstrations are provided.

While it is tempting to simply combine data-driven behavioral priors with few-shot imitation learning, it is not obvious how to do so since the two approaches are somewhat orthogonal. Behavioral priors are trained on highly multi-modal datasets such that a given state can correspond to multiple skills. Given a sufficiently large dataset of demonstrations for the downstream task the imitation learning algorithm will learn to select the correct mode. However, in the few-shot setting how do we ensure that during test time

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

Figure 1. In this work we are interested in enabling autonomous robots to solve complex long-horizon tasks that were unseen during training. To do so, we assume access to a large multi-task dataset of demonstrations, extract skills from the offline dataset, and adapt those skills to new tasks that were unseen during training.

we choose the right skill? Additionally, due to the small sample size and long task horizon it is highly likely that a naive imitation learning policy will drift from the few-shot demonstrations. How do we prevent the imitation learning policy from drifting away from demonstrations at test time?

In this paper we introduce Few-Shot Imitation Learning with Skill Transition Models (FIST), a new algorithm for few-shot imitation learning with skills that enables generalization to unseen but semantically similar long-horizon tasks to those seen during training. Our approach addresses the issues with skill selection and drifting in the few-shot setting with two main components. First, we introduce an inverse skill dynamics model that conditions the behavioral prior not only the current state but also a future state, which helps FIST learn uni-modal future conditioned skill distribution that can then be utilized in few-shot. The inverse skill model is then used as a policy to select skills that will take the agent to the desired future state. Second, we train a distance function to condition the inverse skill model during few-shot evaluation. By finding states along the test-time demonstrations that are closest to the current state, FIST prevents the imitation learning policy from drifting. We show that our method results in policies that are able to generalize to new long-horizon downstream tasks in navigation environments and multi-step robotic manipulation tasks in a kitchen environment. To summarize, we list our three main contributions:

1. We introduce FIST - an imitation learning algorithm that learns an inverse skill dynamics model and a distance function that is used for semi-parametric few-shot imitation.

2. We show that FIST can solve long-horizon tasks in both navigation and robotic manipulation settings that were unseen during training and outperforms previous behavioral prior and imitation learning baselines.

3. We provide insight into how different parts of the FIST algorithm contribute to final performance by ablating different components of our method such as future conditioning and fine-tuning at test time.

2. Related Work

Our approach combines ingredients from imitation learning and skill extraction to produce policies that can solve long-horizon tasks and generalize to tasks that are out of distribution but semantically similar to those encountered in the training set. We cover the most closely related work in imitation learning, skill extraction, and few-shot generalization.

Imitation Learning: Imitation learning is a supervised learning problem where an agent extracts a policy from a dataset of demonstrations. The two most common approaches to imitation are Behavior Cloning (Pomerleau, 1988; Ross et al., 2011a) and Inverse Reinforcement Learning (IRL) (Ng & Russell, 2000). BC approaches learn policies $\pi_\theta(a|s)$ that most closely match the state-conditioned action distribution of the demonstration data. IRL approaches learn a reward function from the demonstration data assuming that the demonstrations are near-optimal for a desired task and utilize Reinforcement Learning to produce policies that maximize the reward. A shortcoming of IRL is that the learned skills are not generalizable since they have overfit to the reward function extracted from the training set. In this work, we aim to learn generalizable skills and therefore utilize the BC approach. However, two drawbacks of BC are that the imitation policies require a large number of demonstrations and are prone to drifting away from the demonstration distribution at test time due to error accumulation (Ross et al., 2011b). For this reason, BC policies work best when the time-horizon of the task is short.

Skill Extraction with Behavioral Priors: Methods that leverage behavioral priors utilize offline datasets of demonstrations to bias a policy towards the most likely skills in the datasets. While related closely to imitation learning, behavioral priors have been mostly applied to improve Reinforcement Learning. Behavioral priors learned through maximum likelihood latent variable models have been used for structured exploration in RL (Singh et al., 2021), to solve complex long-horizon tasks from sparse rewards (Pertsch et al., 2020), and regularize offline RL policies (Wu et al., 2019; Peng et al., 2019; Nair et al., 2020). While impressive, RL with data-driven behavioral priors does not generalize to new tasks efficiently, often requiring millions environment

interactions to converge at an optimal policy for a new task.

Few-Shot Learning: Few-shot learning (Wang et al., 2020) has been studied in the context of image recognition (Vinyals et al., 2016; Koch et al., 2015), reinforcement learning (Duan et al., 2016), and imitation learning (Duan et al., 2017). In the context of reinforcement and imitation learning, few-shot learning is often cast as a meta-learning problem (Finn et al., 2017; Duan et al., 2016; 2017). However, there are other means of attaining few-shot generalization that do not require meta-learning. Recently, advances in unsupervised representation learning in natural language processing (Radford et al., 2019; Brown et al., 2020) and vision (He et al., 2020; Chen et al., 2020) have shown how a network pre-trained with a self-supervised objective can be finetuned or adjusted with a linear probe to generalize in few-shot or even zero-shot (Radford et al., 2021) to a downstream task. Our approach to few-shot imitation learning is loosely inspired by the generalization capabilities of networks pre-trained with unsupervised objectives. Our approach first fits a behavioral prior to an offline dataset of demonstrations to extract skills and then fits an imitation learning policy over the previously acquired skills to generalize in few-shot to new tasks. FIST is therefore a hierarchical few-shot imitation learning algorithm.

3. Approach

3.1. Problem Formulation

Few-shot Imitation Learning: We denote a demonstration as a sequence of states and actions:

$$\tau = \{s_1, a_1, s_2, a_2, \ldots, s_T, a_T\}.$$

In a few-shot setting we assume access to a small dataset of M such expert demonstrations $\mathcal{D}^{\text{demo}} = \{\tau_i\}_{i=1}^{i=M}$ that fulfill a specific long horizon task in the environment. For instance a sequence of sub-tasks in a kitchen environment such as moving the kettle, turning on the burner and opening a cabinet door. The goal is to imitate this behavior to automate the task using only a few example trajectories available.

Skill Extraction: In this work we assume access to an unlabeled offline dataset of prior agent interactions with the environment in the form of N un-directed trajectories $\{\tau_i = \{(s_t, a_t)\}_{t=1}^{t=T_i}\}_{i=1}^{i=N}$. We further assume that these trajectories include semantically meaningful skills that are composable to execute long horizon tasks in the environment. This data can be collected from past tasks that have been attempted, or be provided by human-experts through teleoperation (Zhang et al., 2018).

Skill extraction refers to an unsupervised learning approach that utilizes this undirected dataset to learn a skill policy in form of $\pi_\theta(a|s, z)$ where a is action, s is the current state, and z is the skill. Our hypothesis is that by combining

these skill primitives we can solve semantically similar long-horizon tasks that have not directly been seen during the training. In this work we propose a new architecture for skill extraction based on continuous latent variable models that enables a semi-parametric evaluation procedure for few-shot imitation learning.

3.2. Hierarchical Few-Shot Imitation with Skill Transition Models

Our method, shown in Fig. 2, has three components: (i) Skill extraction, (ii) Skill adaptation via fine-tuning on few-shot data, and (iii) Evaluating the skills using a semi-parametric approach to enable few-shot imitation.

(i) Skill Extraction from Offline Data: We define a continuous skill $z_i \in \mathcal{Z}$ as an embedding for a sequence of state-action pairs $\{s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1}\}$ with a fixed length H. This temporal abstraction of skills has proven to be useful in prior work (Pertsch et al., 2020; Ajay et al., 2021), by allowing a hierarchical decomposition of skills to achieve long horizon downstream tasks. To learn the latent space $\mathcal{Z}$ we propose training a continuous latent variable model with the encoder as $q_\phi(z|s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1})$ and the decoder as $\pi_\theta(a|s, z)$. The encoder outputs a distribution over the latent variable z that best explains the variation in the state-action pairs in the sub-trajectory.

The encoder is an LSTM that takes in the sub-trajectory of length H and outputs the parameters of a Gaussian distribution as the variational approximation over the true posterior $p(z|s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1})$. The decoder is a policy that maximizes the log-likelihood of actions of the sub-trajectory conditioned on the current state and the skill. We implement the decoder as a feed-forward network which takes in the current state s_t and the latent vector z and regresses the action vector directly. This architecture resembles prior works on skill extraction (Pertsch et al., 2020).

To learn parameters ϕ and θ, we randomly sample batches of H-step continuous sub-trajectories from the training data $\mathcal{D}$ and maximize the evidence lower bound (ELBO):

$$\log p(a_t|s_t) \geq \mathbb{E}_{\tau \sim \mathcal{D}, z \sim q_\phi(z|\tau)}[\underbrace{\pi_\theta(a_t|s_t, z)}_{\mathcal{L}_{\text{rec}}}$$
$$+ \beta \underbrace{(\log p(z) - \log q_\phi(z|\tau)]}_{\mathcal{L}_{\text{reg}}}$$

where the posterior $q_\phi(z|\tau)$ is regularized by its Kullback-Leibler (KL) divergence from a unit Gaussian prior $p(z) = \mathcal{N}(0, I)$ and β is a parameter that tunes the regularization term.

To enable quick few shot adaptation over skills we learn an

(a) Skill Extraction   (b) Skill Adaptation   (c) Few-shot Imitation

Figure 2. Our algorithm – Few-Shot Imitation Learning with Skill Transition Models (FIST) – is composed of three parts: (a) *Skill extraction:* we fit a skill encoder, decoder, inverse skill dynamics model, and a distance function to the offline dataset; (b) *Skill adaptation:* at test-time, we are given a few demonstrations and adapt the skills learned in (a) by fine-tuning the encoder, decoder, inverse model, and distance function; (c) *Few-shot imitation:* finally, to imitate the test-time demonstrations, we utilize the distance function to perform a look ahead and condition the inverse model nearby waypoints along the demonstration.

inverse skill dynamics model $q_\psi(z|s_t, s_{t+H-1})$ that infers which skills should be used given the current state and a future state that is H steps away. To train the inverse dynamics model we minimize the KL divergence between the approximated skill posterior $q_\phi(z|\tau)$ and the output of the state conditioned skill prior. This will result in minimizing the following loss with respect to the parameters ψ:

$$\mathcal{L}_{\text{prior}}(\psi) = \mathbb{E}_{\tau \sim \mathcal{D}}\left[D_{KL}(q_\phi(z|\tau), q_\psi(z|s_t, s_{t+H-1}))\right]. \quad (1)$$

We use a reverse KL divergence to ensure that our inverse dynamics model has a broader distribution than the approximate posterior to ensure mode coverage (Bishop, 2006). In our implementation we use a feed-forward network that takes in the concatenation of the current and future state and outputs the parameters of a Gaussian distribution over z. Conditioning on the future enables us to make a more informative decision on what skills to execute which is a key enabler to few-shot imitation. We jointly optimize the skill extractions and inverse model with the following loss:

$$\mathcal{L}(\phi, \theta, \psi) = \mathcal{L}_{\text{rec}}(\phi, \theta) + \beta\mathcal{L}_{\text{reg}}(\phi) + \mathcal{L}_{\text{prior}}(\psi) \quad (2)$$

Algorithm 1 FIST: Evaluation Algorithm

1: **Inputs:** Learned inverse skill dynamics model $q_\psi(z|s_t, s_{t+H-1})$, learned skill policy $\pi_\theta(a|s, z)$, learned distance function $d(s, s')$, test-time demonstration $\mathcal{D}^{\text{demo}}$
2: Initialize the environment to s_0
3: **for** each $t = [1 \ldots T]$ **do**
4:    Pick $s_t^{*'} = \text{LookAhead}(\min_{s \in \mathcal{D}^{\text{demo}}} d(s_t, s))$
5:    Sample skill $z \sim q_\psi(z|s_t, s_t^{*'})$
6:    Sample action $a \sim \pi_\theta(a|s_t, z)$
7:    $s_t \leftarrow \text{env.step}(a)$

(ii) Skill Adaption via Fine-tuning at Test-time : To improve the consistency between the unseen downstream demonstrations and the prior over skills, we use the test-time trajectories to fine-tune the parameters of the architecture by taking gradient steps over the loss in Equation 2. In the experiments we ablate the performance of FIST with and without fine-tuning to highlight the differences.

(iii) Semi-parametric Evaluation for Few-shot Imitation Learning: To run the agent, we need to first sample a skill $z \sim q_\psi(z|s_t, s_t^*)$ based on the current state and the future state that it seeks to reach. Then we can use the low-level decoder $\pi(a_t|z, s_t)$ to convert that sampled skill z and the current state s_t to the corresponding action a_t. During evaluation we use the demonstrations $\mathcal{D}^{\text{demo}}$ to decide which state to use as the future state to condition on. For this purpose we use a learned distance function $d(s, s')$ to measure the distance between the current state s_t and every other state in the demonstrated trajectories. Then, from the few-shot data we find the closest state s_t^* to the current state according to the distance metric:

$$s_t^* = \min_{s_{ij} \in \mathcal{D}^{\text{demo}}} d(s_t, s_{ij}) \quad (3)$$

where s_{ij} is the j^{th} state in the i^{th} trajectory in $\mathcal{D}^{\text{demo}}$. We then condition the inverse dynamics model on the current state s_t and the state $s_t^{*'}$, H-steps ahead of s_t^* within the trajectory that s_t^* belongs to. If by adding H steps we reach the end of the trajectory, we use the end state within the trajectory as the target future state. The reason for this look-ahead adjustment is to ensure that the sampled skill always makes progress towards the future states of the demonstration. After the execution of action a_t according to the low-level decoder, the process is repeated until the fulfillment of the task. The procedure is summarized in Algorithm 1.

Figure 3. **Top**: In each environment, we block some part of the environment and collect undirected trajectories for extracting skills. In the kitchen environment, red markers indicate the objects that are excluded. **Bottom**: At test-time, we use 10 expert trajectories that involve unseen parts of the maze or manipulation of unseen objects.

Inspired by prior work on contrastive learning for control (Srinivas et al., 2020; Stooke et al., 2021) and semi-parametric control with distance functions (Savinov et al., 2018; Liu et al., 2020; Emmons et al., 2020) we learn a distance metric by optimizing a contrastive loss such that states that are H steps in the future are close to the current state while all other states are far. To train this contrastive encoder, we sample a batch of sub-trajectories of length H, $\{\tau_i\}_{i=1}^{i=B}$, and then for each trajectory τ_i we use the last state $s_H \in \tau_i$ as the positive sample for the first state $s_1 \in \tau_i$ and the $B-1$ last states from other trajectories within the batch $s_H \in \tau_j, \forall j \neq i$ as the negative samples for $s_1 \in \tau_i$. Using a contrastive loss we will encourage the positive samples to attract and the negative samples to repel one another. Then a euclidean distance on the encoded states can be used to measure the distance between two arbitrary states.

4. Experiments

In the experiments we are interested in answering the following questions: (i) Can our method successfully imitate unseen long-horizon test-time demonstrations? (ii) Is the temporal abstraction obtained from skills necessary for imitating long-horizon trajectories? (iii) Is pretraining and fine-tuning the skill embedding model necessary for achieving high success rate? (iv) Can our method also be used for robust one-shot imitation learning for in-distribution long-horizon tasks?

4.1. Environments

We evaluate the performance of FIST on two simulated navigation environments and a robotic manipulation task from the D4RL benchmark as shown in Figure 3. To ensure generalizability to out-of-distribution tasks we remove some category of trajectories from the offline data. At test-time, we see if the agent can generalize to those unseen trajectories.

PointMaze: In this environment, the task is to navigate a point mass through a maze, from a start to a goal location. The outline of the maze is shown in Figure 3. We train the skills on three different datasets, each blocking one side of the maze. To test the method's ability to generalize to unseen long-horizon tasks, we use 10 expert demonstrations that start from random places in maze, but end at a goal within the blocked region. This ensures that our test-time trajectories are out of distribution compared to training data. We evaluate the performance by measuring the episode length and the success rate in reaching the demonstrated goals.

AntMaze: The task is to control a quadruped ant to run to different parts of the maze. The layout of the maze is similar to PointMaze, and the same sides are blocked off. The demonstrations are taken directly from the D4RL (Fu et al., 2020) dataset, by removing the trajectories passing through the blocked regions. The expert demonstrations for test-time few-shot learning are randomly sampled for each of the removed trajectories. Similar to PointMaze we measure the episode length and success rate as our evaluation metric.

Kitchen: The task is to use a 7-DoF robotic arm to manipulate different parts of a kitchen environment in a specific

order (e.g. open a microwave door or move the kettle). During skill extraction we pre-process the offline data to exclude interactions with certain objects in the environment (e.g. we exclude interactions with the kettle). However, for the demonstrations we pick four sub-tasks one of which includes the objects that were excluded from the skill dataset (e.g. if the kettle was excluded, we pick the task to be to open the microwave, move the kettle, turn the top burner, and slide the cabinet door). In evaluation, for completion of each sub-task in the order consistent with the test-time demonstrations, the agent is awarded with a reward of 1.0 for a total max reward of 4.0 per episode.

4.2. Results

We use the following approaches for comparison: **BC+FT**: Trains a behavioral cloning agent (i.e. $\pi_\theta(a|s)$) on the offline dataset $\mathcal{D}$ and fine-tunes to the test time dataset $\mathcal{D}^{\text{demo}}$. **SPiRL**: This is an extension of the existing skill extraction methods to imitation learning over skill space (Ajay et al., 2021; Pertsch et al., 2020). SPiRL (Pertsch et al., 2020) is very similar to our skill extraction method, but instead of conditioning the skill prior on the future state it only uses the current state. We extract skills from $\mathcal{D}$ using SPiRL, fine-tune the module on the test-time demonstrations $\mathcal{D}^{\text{demo}}$, and then execute the skill prior for evaluation. **FIST (ours)**: This runs our semi-parametric approach after learning the future conditioned skill prior. After extracting skills from $\mathcal{D}$ we fine-tune the parameters on the downstream demonstration data $\mathcal{D}^{\text{demo}}$ and perform the proposed semi-parametric approach for evaluation.

For details on the implementation and example videos of the experiments we refer the reader to supplementary materials. Our results are summarized in Table 1 and 2. Each row indicates an experiment where a specific test-time task was excluded from the offline data $\mathcal{D}$. We provide a summary of our key findings:

(i) In the PointMaze environment, FIST consistently succeeds in navigating the point mass into all three goal locations. The skills learned by SPiRL fail to generalize when the point mass falls outside training distribution, causing it to get stuck in corners. While BC+FT also solves the task frequently in the Left and Bottom goal location, the motion of the point mass is sub-optimal, resulting in longer completion times.

(ii) In the AntMaze environment, FIST achieves the best performance compared to the baselines. SPiRL and BC+FT make no progress in navigating the agent towards the goal while FIST is able to frequently reach the goal demonstrated during test-time trajectories. We believe that the low success rate numbers in this experiment is due to the low quality of demonstrations that exist in the offline dataset $\mathcal{D}$. In the dataset, we see many episodes with ant falling over, and

FIST's failure cases also demonstrate the same behavior, hence resulting in a low success rate. We hypothesize that with a better skill dataset FIST will be able reach to a higher success rate number.

		FIST (Ours)		SPiRL		BC+FT	
Blocked Region	Environment	Episode Length	Success Rate	Episode Length	Success Rate	Episode Length	Success Rate
Left	PointMaze	**363.87 ± 18.73**	0.99 ± 0.03	1966.7 ± 32.54	0.02 ± 0.04	1089.76 ± 173.74	0.74 ± 0.11
Right	PointMaze	**571.21 ± 38.82**	0.91 ± 0.07	2000 ± 0	0.0 ± 0.0	1918.99 ± 43.65	0.07 ± 0.06
Bottom	PointMaze	**359.82 ± 3.62**	1.0 ± 0.0	2000 ± 0	0.0 ± 0.0	1127.47 ± 148.24	0.87 ± 0.10
Left	AntMaze	**764.36 ± 8.93**	0.32 ± 0.04	1000 ± 0	0.0 ± 0.0	1000 ± 0	0.0 ± 0.0
Right	AntMaze	**903.98 ± 12.01**	0.22 ± 0.12	1000 ± 0	0.0 ± 0.0	1000 ± 0	0.0 ± 0.0
Bottom	AntMaze	**923.22 ± 6.36**	0.21 ± 0.07	957.85 ± 8.62	0.12 ± 0.07	1000 ± 0	0.0 ± 0.0

Table 1. Comparison of our approach to other baselines on the Maze environments. For each experiment we report the average episode length from 10 fixed starting positions with the standard error across 10 evaluation runs (*lower* is better). We also report success rate its standard deviation. The maximum episode length for PointMaze and AntMaze are 2000 and 1000, respectively.

(iii) In the kitchen environment, we see that FIST significantly outperforms SPiRL and BC+FT. FIST can successfully complete **3 out of 4** long-horizon object manipulation tasks in this environment. In one of these long-horizon tasks all algorithms perform similarly poor. We believe that such behavior is due to the fact that fine-tuning the agent on the given task may cause it to forget some part of previous skills (e.g. Sliding the cabinet door). As future work, we plan to explore how different fine-tuning mechanisms (e.g. gradual layer unfreezing) could help avoid forgetting of prior skills.

Task (Unseen)	Environment	FIST (Ours)	SPiRL	BC+FT
Microwave, Kettle, **Top Burner**, Light Switch	KitchenRobot	**3.6 ± 0.16**	2.1 ± 0.48	0.0 ± 0.0
Microwave, Kettle, Slide Cabinet, Hinge Cabinet	KitchenRobot	**2.3 ± 0.5**	2.3 ± 0.5	2.3 ± 0.28
Microwave, **Kettle**, Slide Cabinet, Hinge Cabinet	KitchenRobot	**3.5 ± 0.3**	0.0 ± 0.0	1.3 ± 0.47
Microwave, Kettle, **Slide Cabinet**, Hinge Cabinet	KitchenRobot	**4.0 ± 0.0**	3.3 ± 0.38	1.0 ± 0.32

Table 2. Comparison of average episode reward for our approach against other baselines on the KitchenRobot environment. The average episode reward (with a max. of 4) along with its standard error is measured across 10 evaluation runs (*higher* is better). Each bolded keyword indicates the task that was excluded during skill data collection.

4.3. Ablation Studies

In this section we study different components of the FIST algorithm to provide insight on the contribution of each part. In particular we are interested in performing the following ablations:

Imitation Learning over skills vs. atomic actions: The FIST algorithm is comprised of two coupled pieces that are both critical for robust performance: - the inverse dynamics model over skills and the non-parametric evaluation algorithm. In this experiment we measure the influence of inverse skill dynamics model $q_\psi(z|s_t, s_{t+H-1})$.

An alternative baseline to learning skill dynamics model is to learn an inverse dynamics model on atomic actions $q_\psi(a_t|s_t, s_{t+H-1})$ and perform goal-conditioned behavioral cloning. This model outputs the first action a_t required

for transitioning from s_t to s_{t+H-1} over H steps. We can combine this model with FIST's non-parametric module to determine the s_{t+H-1} to condition on during evaluation of the policy. As shown in Table 3, temporal abstraction obtained in learning an inverse skill dynamics model is a critical factor in the performance of FIST.

Task (Unseen)	FIST (ours)	Goal-BC	BC
Microwave, Kettle, **Top Burner**, Light Switch	**3.6 ± 0.16**	0.0 ± 0.0	0.0 ± 0.0
Microwave, Kettle, Slide Cabinet, Hinge Cabinet	**2.3 ± 0.5**	2.2 ± 0.28	2.3 ± 0.28
Microwave, **Kettle**, Slide Cabinet, Hinge Cabinet	**3.5 ± 0.3**	1.8 ± 0.44	1.3 ± 0.47
Microwave, Kettle, **Slide Cabinet**, Hinge Cabinet	**4.0 ± 0.0**	0.9 ± 0.1	1.0 ± 0.32

Table 3. We ablate the use of our inverse skill dynamics model by replacing it with an inverse dynamics model on atomic actions. The baseline ablations only succeed on one out of the four tasks. BC learns an inverse dynamics model that takes in state as input and outputs a distribution over atomic actions. Goal-BC uses both state and the goal (sub-task) as input.

The effect of skill pre-training and fine-tuning on FIST: In order to adjust the skill-set to out-of-distribution tasks (e.g. moving the kettle while kettle is excluded from the skill dataset) FIST requires fine-tuning on the test-time demonstrations. We hypothesize that without fine-tuning, the agent should be able to perfectly imitate the test-time sub-trajectories that it has seen during training, but should start drifting away when encountered with an out-of-distribution skill. We also hypothesise that pre-training on a large dataset, even if it does not include the test-time demonstration, is crucial for the good performance seen on FIST. Intuitively, pre-training provides a behavioral prior that is easier to adapt to unseen tasks than a random initialization.

To examine the impact of fine-tuning, we compare FIST with *FIST-no-FT* which directly evaluates the semi-parameteric approach with the model parameters trained on the skill dataset without fine-tuning on the test-time trajectories. For pre-training, we compare FIST with *FIST-no-pretrain* which is not pre-trained on the skill dataset. Instead, we directly train the latent variable and inverse skill dynamics model on the test-time data and perform the semi-parametric evaluation of the FIST algorithm.

From the results in Table 4, we observe that fine-tuning is a critical component for out-of-distribution task. The scores on *FIST-no-FT* suggests that the agent is capable of fulfilling the sub-tasks seen during skill training without fine-tuning but cannot progress onto unseen tasks. We also find that the pre-training on a rich dataset, even when the downstream task is directly excluded, provides sufficient prior knowledge about the dynamics of the environment and can immensely help with generalization to unseen tasks via fine-tuning.

One-shot Imitation Learning: The FIST algorithm can be directly evaluated on one-shot in-distribution downstream tasks without any fine-tuning. In this experiment, we want to

Task (Unseen)	FIST (ours)	FIST-no-FT	FIST-no-pretrain
Microwave, Kettle, **Top Burner**, Light Switch	**3.6 ± 0.16**	2.0 ± 0.0	0.1 ± 0.13
Microwave, Kettle, Slide Cabinet, Hinge Cabinet	**2.3 ± 0.5**	0.0 ± 0.0	0.1 ± 0.13
Microwave, **Kettle**, Slide Cabinet, Hinge Cabinet	**3.5 ± 0.3**	1.0 ± 0.0	0.1 ± 0.13
Microwave, Kettle, **Slide Cabinet**, Hinge Cabinet	**4.0 ± 0.0**	2.0 ± 0.0	0.8 ± 0.13

Table 4. We ablate the use of pre-training on offline data, as well as fine-tuning on test-time demonstrations. FIST-no-FT removes the fine-tuning on test-time demonstration step in FIST, while FIST-no-pretrain trains the skills purely from the given test-time data. Without seeing the subtask, FIST-no-FT is unable to solve the test-time subtask. Trained on only test-time data, FIST-no-pretrain is unable to properly manipulate the robot.

see if the agent can pick up the right mode within its skill-set by with only one demonstration for fulfilling a long-horizon task in the kitchen environment. The difference between this experiment and our main result is that the down-stream task is within the distribution of its pre-trained skill-set. This is still a challenging task since the agent needs to correctly identify the desired mode of skills.

Our hypothesis is that in SPiRL, the skill prior is only conditioned on the current state and therefore is, by definition, a multi-modal distribution and would require more data to adapt to a specific long-horizon trajectory. For instance, in the kitchen environment, after opening the microwave door, the interaction with any other objects in the environment is a possible choice of skills that can be invoked. However, in FIST, by conditioning the skill prior on the future states, we fit a uni-modal distribution over skills. In principle, there should be no need for fine-tuning for invoking those skills within the distribution of the pre-trained skill set.

We compare our approach to SPiRL (Section 4.2) as a baseline. In addition, we can provide supervision on which skills to invoke to fulfill the long-horizon task by fine-tuning SPiRL (hence *SPiRL-FT*) for a few epochs on the test-time demonstration. As summarized in Table 5, FIST can fulfill all the long-horizon tasks listed with almost no drift from the expert demonstration. We also see that it is tricky to fine-tune SPiRL in a one-shot setting, as fine-tuning only on one demonstration may cause over-fitting and degradation of performance.

Order of tasks (seen in the skill dataset)	FIST (ours)	SPiRL-FT	SPiRL-no-FT
Kettle, Bottom Burner, Slide Cabinet, Hinge Cabinet	**4.0 ± 0.0**	0.8 ± 0.19	2.4 ± 0.35
Kettle, Top Burner, Light Switch, Slide Cabinet	**3.8 ± 0.19**	0.5 ± 0.16	1.1 ± 0.22
Microwave, Kettle, Slide Cabinet, Hinge Cabinet	**4.0 ± 0.0**	1.1 ± 0.22	1.0 ± 0.37
Top Burner, Bottom Burner, Slide Cabinet, Hinge Cabinet	**4.0 ± 0.0**	0.1 ± 0.1	0.6 ± 0.25

Table 5. With all subtasks seen in the skill dataset, FIST is able to imitate a long-horizon task in the kitchen environment. We compare to a baseline method, SPiRL, which fails to follow the single demo.

Environment	Episode Length	Success Rate
PointMaze	621.02 ± 69.87	1.0 ± 0.0
AntMaze	1000 ± 0	0.0 ± 0.0

Table 6. We evaluate FIST on the maze environment with goal at the bottom when the inverse skill model is trained on an extremely noisy dataset. In this case, FIST achieves sub-optimal performance, or is unable to imitate the test time demonstration.

5. Broader Impacts and Limitations

Limitations As with all imitation learning methods, the performance of FIST is related to the quality of the provided demonstrations. Concretely, when the skill training demonstrations are poor, we expect the extracted skills to be also sub-optimal, thus, hurting test-time imitation performance. To better understand this limitation, we analyze two extremely noisy versions of the PointMaze and AntMaze datasets and use them for skill extraction. In both cases we find that the agent's policy is substantially worse than FIST trained on expert data. For more details regarding this experiment, we refer the reader to the appendix. Learning structured skills from noisy offline data is an exciting direction for future research.

Broader Impacts The ability to extract skills from offline data and adapt them to solve new challenging tasks in few-shot could be impactful in domains where large offline datasets are available but control is challenging and cannot be manually scripted. Examples of such domains include autonomous vehicle navigation, warehouse robotics, digital assistants and perhaps in the future home robots. However, there are also negative potential consequences. First, since in real-world settings offline data will be collected from users at scale there will likely be privacy concerns, especially for video data collected from users' cars or homes. Additionally, since FIST extracts skills without labels data quality for large datasets becomes increasingly opaque and if there are harmful skills or behavior present in the dataset FIST may extract those and use them during deployment which could have unintended consequences. A promising direction for future work is to include a human in the loop for skill verification.

6. Conclusion

We present FIST, a semi-parametric algorithm for few-shot imitation learning for long-horizon tasks that are unseen during training. We use previously collected trajectories of the agent interacting with the environment to learn a set of skills along with an inverse dynamics model that is then combined with a non-parametric approach to keep the agent from drifting away from the test-time demonstrations. Our approach is able to solve long-horizon challenging tasks in

both one and few-shot settings where other methods fail.

References

Ajay, A., Kumar, A., Agrawal, P., Levine, S., and Nachum, O. {OPAL}: Offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=V69LGwJ0lIN.

Bishop, C. M. *Pattern recognition and machine learning*. springer, 2006.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, 2020.

Duan, Y., Schulman, J., Chen, X., Bartlett, P. L., Sutskever, I., and Abbeel, P. Rl^2: Fast reinforcement learning via slow reinforcement learning. *arXiv:1611.02779*, 2016.

Duan, Y., Andrychowicz, M., Stadie, B. C., Ho, J., Schneider, J., Sutskever, I., Abbeel, P., and Zaremba, W. One-shot imitation learning. In Guyon, I., von Luxburg, U., Bengio, S., Wallach, H. M., Fergus, R., Vishwanathan, S. V. N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 1087–1098, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/ba3866600c3540f67c1e9575e213be0a-Abstract.html.

Emmons, S., Jain, A., Laskin, M., Kurutach, T., Abbeel, P., and Pathak, D. Sparse graphical memory for robust planning. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/385822e359afa26d52b5b286226f2cea-Abstract.html.

Finn, C., Yu, T., Zhang, T., Abbeel, P., and Levine, S. One-shot visual imitation learning via meta-learning. In *1st Annual Conference on Robot Learning, CoRL 2017, Mountain View, California, USA, November 13-15, 2017, Proceedings*, volume 78 of *Proceedings*

of Machine Learning Research, pp. 357–368. PMLR, 2017. URL http://proceedings.mlr.press/v78/finn17a.html.

Fu, J., Kumar, A., Nachum, O., Tucker, G., and Levine, S. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

He, K., Fan, H., Wu, Y., Xie, S., and Girshick, R. Momentum contrast for unsupervised visual representation learning. In *Conference on Computer Vision and Pattern Recognition*, 2020.

Koch, G., Zemel, R., and Salakhutdinov, R. Siamese neural networks for one-shot image recognition. 2015.

Liu, K., Kurutach, T., Tung, C., Abbeel, P., and Tamar, A. Hallucinative topological memory for zero-shot visual planning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6259–6270. PMLR, 2020. URL http://proceedings.mlr.press/v119/liu20h.html.

Nair, A., Gupta, A., Dalal, M., and Levine, S. Awac: Accelerating online reinforcement learning with offline datasets, 2020.

Ng, A. Y. and Russell, S. J. Algorithms for inverse reinforcement learning. In Langley, P. (ed.), *Proceedings of the Seventeenth International Conference on Machine Learning (ICML 2000), Stanford University, Stanford, CA, USA, June 29 - July 2, 2000*, pp. 663–670. Morgan Kaufmann, 2000.

Peng, X. B., Kumar, A., Zhang, G., and Levine, S. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *CoRR*, abs/1910.00177, 2019. URL http://arxiv.org/abs/1910.00177.

Pertsch, K., Lee, Y., and Lim, J. J. Accelerating reinforcement learning with learned skill priors. In *Conference on Robot Learning (CoRL)*, 2020.

Pomerleau, D. ALVINN: an autonomous land vehicle in a neural network. In Touretzky, D. S. (ed.), *Advances in Neural Information Processing Systems 1, [NIPS Conference, Denver, Colorado, USA, 1988]*, pp. 305–313. Morgan Kaufmann, 1988. URL http://papers.nips.cc/paper/95-alvinn-an-autonomous-land-vehicle-in-a-neural-network.

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., and Sutskever, I. Language models are unsupervised multitask learners. 2019.

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., and Sutskever, I. Learning transferable visual models from natural language supervision, 2021.

Ross, S., Gordon, G. J., and Bagnell, D. A reduction of imitation learning and structured prediction to no-regret online learning. In Gordon, G. J., Dunson, D. B., and Dudík, M. (eds.), *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, volume 15 of *JMLR Proceedings*, pp. 627–635. JMLR.org, 2011a. URL http://proceedings.mlr.press/v15/ross11a/ross11a.pdf.

Ross, S., Gordon, G. J., and Bagnell, D. A reduction of imitation learning and structured prediction to no-regret online learning. In Gordon, G. J., Dunson, D. B., and Dudík, M. (eds.), *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, volume 15 of *JMLR Proceedings*, pp. 627–635. JMLR.org, 2011b. URL http://proceedings.mlr.press/v15/ross11a/ross11a.pdf.

Savinov, N., Dosovitskiy, A., and Koltun, V. Semiparametric topological memory for navigation. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=SygwwGbRW.

Singh, A., Liu, H., Zhou, G., Yu, A., Rhinehart, N., and Levine, S. Parrot: Data-driven behavioral priors for reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=Ysuv-WOFeKR.

Srinivas, A., Laskin, M., and Abbeel, P. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, 2020.

Stooke, A., Lee, K., Abbeel, P., and Laskin, M. Decoupling representation learning from reinforcement learning. In *International Conference on Learning Representations*, 2021.

Vinyals, O., Blundell, C., Lillicrap, T., Kavukcuoglu, K., and Wierstra, D. Matching networks for one shot learning. In Lee, D. D., Sugiyama, M., von Luxburg, U., Guyon, I., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 3630–3638, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/

90e1357833654983612fb05e3ec9148c-Abstract.
html.

Wang, Y., Yao, Q., Kwok, J. T., and Ni, L. M. Generalizing from a few examples: A survey on few-shot learning. *ACM Comput. Surv.*, 53(3):63:1–63:34, 2020. doi: 10.1145/3386252. URL https://doi.org/10.1145/3386252.

Wu, Y., Tucker, G., and Nachum, O. Behavior regularized offline reinforcement learning. *CoRR*, abs/1911.11361, 2019. URL http://arxiv.org/abs/1911.11361.

Zhang, T., McCarthy, Z., Jow, O., Lee, D., Chen, X., Goldberg, K., and Abbeel, P. Deep imitation learning for complex manipulation tasks from virtual reality tele-operation. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pp. 1–8. IEEE, 2018. doi: 10.1109/ICRA.2018.8461249. URL https://doi.org/10.1109/ICRA.2018.8461249.