Kuramoto Attention: Synchronizing Self-Attention on the Torus

Abstract

Transformer models are increasingly used as computational models of cognition and neural representation, so the mechanism implemented by self-attention is of interest beyond engineering performance. A complementary tradition in cognitive science models coordination, binding, and memory through dynamical interactions such as oscillator synchrony; we bring this mechanism into self-attention by introducing the *Kuramoto Attention* layer, whose value update is a synchronization step. Each token carries a bank of phase oscillators, so its hidden state lives on a high-dimensional torus. The attention weights form an adaptive coupling graph, and using the raw phase states as values makes the value update exactly the Kuramoto coupling direction for fixed attention weights. The softmax selects which oscillators couple, while the value path moves each token toward the attention-weighted circular mean of the tokens it selects. We train Kuramoto Attention on enwiki8 and CodeParrot against parameter-matched RoPE+SwiGLU transformers. At 5M parameters on CodeParrot, it improves on the transformer by both median and mean, with mean gaps of 0.012 validation and 0.010 test bits per byte. At 5M on enwiki8, all six runs have lower validation/test medians than the transformer and all-seed means within 0.01 BPC; five of six also form a tight lower-mean cluster. At 1M, it trails by about 0.02 BPC on enwiki8 and by 0.013–0.015 bits per byte on CodeParrot. Ablations and phase diagnostics show how the layer's synchronization and geometry-motivated components shape model performance. The result is a self-attention mechanism whose learned computation can be read directly as adaptive synchronization on phase states.

1 Introduction

Transformer language models are now used not only as engineering systems, but also as computational models for cognitive neuroscience. Contextual representations in deep language models predict aspects of neural activity during language comprehension (Caucheteux & King, 2022; Goldstein et al., 2022), and recent work compares functional specialization in transformer-based language models with specialization in the human language network (Kumar et al., 2024). This makes self-attention a natural object for cognitive modeling: it is the central operation in a family of models that both perform language prediction and provide useful comparisons to the brain. Yet the standard description of self-attention is mostly algorithmic: queries and keys produce a softmax weighting, and values are averaged (Vaswani et al., 2017).

A complementary line of work in neuroscience and cognitive modeling emphasizes dynamical coordination. Oscillations, synchrony, and traveling waves are common motifs in cortical activity, where they are often discussed as mechanisms for coordination across space, time, and neural populations (Muller et al., 2018). In machine learning, AKOrN uses this motivation to replace ordinary threshold-like units by Kuramoto oscillatory neurons: synchronization binds distributed features, implements a form of competitive compression, and can be combined with attention, convolution, or fully connected connectivity (Miyato et al., 2025). We put this dynamical coordination directly inside the attention layer: attention weights supply the coupling graph, and the value update is a synchronization step.

In Kuramoto Attention, each token carries a small bank of phase oscillators, one phase per hidden coordinate, so the token state lives on a high-dimensional torus. Attention supplies an adaptive coupling graph between tokens. The query and key maps score which phase states should couple; the values are the phase states themselves. For fixed attention weights, the value direction is exactly the Kuramoto coupling term $\sum_u A_{t,u} \sin(\theta_u - \theta_t)$ (Lemma 2). The softmax matrix is the coupling kernel, each token is pulled toward the attention-weighted circular mean of the tokens it attends to, and the single-step phase update is the negative gradient of an attention-weighted coherence energy.

The softmax weights are the entropy-regularized assignment to tokens with similar phases (Proposition 1): they favor neighbors with high phase-alignment scores while staying as spread out as the entropy penalty allows. The gated score and the value update therefore express the same coherence (Lemma 2). Rotary position enters as a position-dependent phase drift in the score (Section 3); in the Kuramoto interpretation, these learned drift rates are the layer's natural-frequency terms, advancing each oscillator before two token states are compared.

The construction also changes the usual query/key/value roles. The query and key maps produce metric gates: their product weights the native cosine score and defines the diagonal metric used for selection. The values are the raw phase states; the learned value-side map is a signed per-coordinate gate applied after the circular mean has been projected onto the tangent. This value path keeps coordinate values separate through the synchronization step, and the feed-forward block performs the additive cross-coordinate mixing (Section 3.4). The result is an attention layer in which learned gates determine which tokens couple, and a gated tangent update moves each token toward the circular mean of those selected tokens.

We compare Kuramoto Attention with parameter-matched RoPE+SwiGLU transformers on enwiki8 and CodeParrot at 1M–5M parameters. At 5M on CodeParrot, Kuramoto Attention improves on the transformer by both mean and median, with mean gaps of 0.012 validation and 0.010 test bits per byte. At 5M on enwiki8, five of six Kuramoto runs form a tight lower-mean cluster, and all six runs have lower validation/test medians than the transformer with all-seed means within 0.01 BPC. At 1M, the transformer leads by about 0.02 BPC on enwiki8 and by 0.013–0.015 bits per byte on CodeParrot. Ablations identify the components that account for most of the performance changes (Section 4.3).

For cognitive science, the construction bridges transformer language models and oscillator models of coordination: it builds a transformer-style language model from a state space and update rule that make synchronization, coherence, phase drift, and dynamical coordination explicit. Geshkovski et al. (Geshkovski et al., 2023; 2024) analyze standard attention as an interacting particle system whose trajectories cluster asymptotically, and oscillator-attention models such as AKOrN (Miyato et al., 2025) add Kuramoto dynamics to attention by design. Here synchronization comes from the layer's own value update, which uses the phase states themselves as values.

Our contributions are:

- a phase-valued self-attention layer whose raw-state value update is a synchronization step: the softmax matrix is a content-dependent coupling kernel and the update is exactly Kuramoto coupling for fixed attention weights (Section 3);

- a bridge between transformer-style language modeling and oscillator-based models of neural coordination: the construction keeps the standard attention selection mechanism but makes the value update a phase-synchronization step;

- matched-transformer language-modeling comparisons on enwiki8 and CodeParrot, together with ablations and phase diagnostics that identify the metric-gated selection path, circular-mean value update, and local synchronization behavior (Section 4).

2 The synchronization layer

Kuramoto Attention gives each token a vector of phases $\theta \in \mathbb{R}^k/(2\pi\mathbb{Z})^k$, a bank of k unit oscillators $e^{i\theta_j}$. A layer maps a sequence of phase states to phase increments through a gated similarity score, a circular-mean

value update, and a bounded feed-forward block. The score produces the adaptive coupling weights, while the value update moves each token toward the attention-weighted circular mean of the tokens it attends to. Because the state is a vector of phases, updates are added to the angles modulo 2π.

Tokens are embedded as learned phases and logits are read out by phase alignment. Writing $\psi(\theta) = (\cos\theta, \sin\theta)$ for the lift and ρ for a positive gate, the layer maps the phases of token t, coordinate j, to updated phases by

$$
\begin{aligned}
g_t^q &= \rho\big(W_q\,\psi(\theta_t)\big), \quad g_t^k = \rho\big(W_k\,\psi(\theta_t)\big), \\
s_{t,u} &= \tfrac{\tau}{\sqrt{k}}\textstyle\sum_j g_{t,j}^q\, g_{u,j}^k \cos\big(\theta_{t,j} - \theta_{u,j} + \omega_j(t-u)\big), \quad A_{t,\cdot} = \mathrm{softmax}_{u\leq t}\, s_{t,\cdot}, \\
G_{t,j} &= \textstyle\sum_{u\leq t} A_{t,u}\, e^{i\theta_{u,j}}, \quad a_{t,j} = -\sin\theta_{t,j}\,\mathrm{Re}\,G_{t,j} + \cos\theta_{t,j}\,\mathrm{Im}\,G_{t,j}, \\
\theta_t &\leftarrow \theta_t + \mathrm{bound}\big(v(\theta_t)\odot a_t\big), \\
\theta_t &\leftarrow \theta_t + \mathrm{bound}\big(\mathrm{SwiGLU}(\theta_t)\big).
\end{aligned}
\tag{1}
$$

The two residual updates are applied in turn. The next subsections define each line, and Section 3 proves that the circular-mean value line is a Kuramoto synchronization step when the attention weights are fixed.

Relative to standard query/key/value attention, the roles are shifted. The maps W_q and W_k create scalar gates whose product changes the metric used by the score before the softmax. The value line averages the current phase states and then applies the signed gate $v(\theta_t)$ to the resulting tangent direction. Thus the query/key gates change which phase alignments are favored before the softmax, while the value gate changes the strength and sign of the synchronization step.

2.0.1 Gated phase similarity

Each token produces positive query and key gates from its phase features $\psi(\theta) = (\cos\theta, \sin\theta)$ (the $(\cos, \sin)$ lift used throughout),

$$
g_t^q = \rho\big(W_q\,\psi(\theta_t)\big), \qquad g_t^k = \rho\big(W_k\,\psi(\theta_t)\big),
$$

with $\rho = \mathrm{softplus}$ followed by mean normalization ($\bar{g} = g/\mathrm{mean}(g)$). The score combines the gates with the native torus cosine kernel and a rotary phase advance $\omega_j(t-u)$ with learned per-coordinate rates ω_j:

$$
s_{t,u} = \frac{\tau}{\sqrt{k}}\sum_j g_{t,j}^q\, g_{u,j}^k\, \cos\big(\theta_{t,j} - \theta_{u,j} + \omega_j(t-u)\big), \qquad A = \mathrm{softmax}_u\big(s_{t,u}\big)
$$

with causal masking. Position enters the score as the per-coordinate phase drift $\omega_j(t-u)$. The synchronization update then uses the position-free phase states. We use rotary position for this drift, with learned per-coordinate rates ω_j, and setting $\omega \equiv 0$ recovers the bare torus cosine kernel (Section 3). The gates $g^q g^k$ reweight the native cosine alignment coordinate by coordinate. Equivalently, they define the learned diagonal metric on $\mathbb{T}^k$ used in Appendix A; the rotary drift adds a learned phase advance on each circle before the score compares two tokens.

Coherence in the score and the value update. The score and the value update are built from the same pairwise phase coherence $\sum_j \cos(\theta_{t,j} - \theta_{u,j})$. The score weights this coherence by a learned metric to select neighbors, and the value update follows its negative gradient by pulling each token toward the attention-weighted circular mean of the tokens it selects. Section 3 develops this shared structure (Lemma 2).

2.0.2 Circular-mean value update

Values are the raw phase states. We write $G_{t,j} = \sum_u A_{t,u} e^{i\theta_{u,j}}$ for the attention-weighted resultant. This resultant encodes the circular mean of the attended phases. Viewed as a point in the complex plane, its argument is the mean phase and its modulus measures how closely the attended phases agree. The update then moves $\theta_{t,j}$ toward this mean. The increment is the tangent component of $G_{t,j}$ at the current phase, which we obtain as follows. The unit tangent to the circle at $\theta_{t,j}$ is $(-\sin\theta_{t,j}, \cos\theta_{t,j})$, and projecting $G_{t,j} = (\mathrm{Re}\,G_{t,j}, \mathrm{Im}\,G_{t,j})$ onto this tangent gives

$$
a_{t,j} = -\sin\theta_{t,j}\,\mathrm{Re}\,G_{t,j} + \cos\theta_{t,j}\,\mathrm{Im}\,G_{t,j}.
$$

Equivalently, writing the phase as the unit phasor $z_{t,j} = e^{i\theta_{t,j}}$ so that $G_{t,j} = \sum_u A_{t,u} z_{u,j}$, this projection is the imaginary part of a single complex product, $a_{t,j} = \text{Im}(\overline{z_{t,j}} G_{t,j})$, from which $|a_{t,j}| \leq |G_{t,j}| \leq 1$ follows at once. For phase variables, this circular mean and its tangent direction are closed-form. Lemma 2 shows that this increment equals the Kuramoto coupling term. A per-coordinate value gate $v = v(\theta_t)$ scales a. The gate is a signed, linear readout of the phase features, so a positive entry pulls a coordinate toward the attended circular mean and a negative entry pushes it away. It is a learned, content-dependent coupling strength, positive for synchronization and negative for repulsion. A tanh bound then keeps the phase increment within a learned radius. The bound is norm-matched: it preserves the direction of $v \odot a$, behaves linearly for small increments up to the learned scale, and compresses large increments toward the radius. Thus the saturating nonlinearity caps the step size while preserving the relative sizes of typical updates. The bounded increment is added to the state, $\theta \leftarrow \theta + \text{bound}(v \odot a)$.

2.0.3 Feed-forward block

A SwiGLU feed-forward block produces a second, bounded increment between synchronization steps. The block acts in local phase coordinates, since the angles θ are its input features and its output is a per-coordinate angular increment, $\theta \leftarrow \theta + \text{bound}(\text{SwiGLU}(\theta))$. Layers are residual in the phase state. This block uses the standard transformer feed-forward network, but interprets its output as an angular increment. It mixes coordinates densely between synchronization steps, complementing the coordinatewise circular-mean value update. Section 3.4 returns to this split between the multiplicative value path and additive feed-forward mixing.

State-level normalization. A transformer interleaves attention with a normalization layer that rescales the residual stream (Ba et al., 2016; Zhang & Sennrich, 2019). RMSNorm projects each token onto a sphere of fixed radius, an analogy made explicit by the normalized transformer (Loshchilov et al., 2024). Kuramoto attention places the hidden state on $\mathbb{T}^k$ by construction, because every coordinate keeps unit modulus at every layer, and each update adds a bounded increment to the angles modulo 2π. Thus the state constraint is built into each coordinate rather than imposed by a separate normalization layer. The increment bound controls the size of each residual step.

2.0.4 Phase-alignment readout

Logits score each vocabulary item by phase alignment against a learned prototype phase,

$$\ell_v \propto \sum_j \cos(\theta_j - \phi_{v,j}).$$

This differs from the standard language-model readout, which applies a learned linear map from hidden coordinates to vocabulary logits. Here each vocabulary item is represented by a phase prototype ϕ_v, and prediction asks which prototype is most aligned with the final token state on the torus. The readout therefore uses the same circular similarity as the attention score, rather than introducing a separate learned linear map at the output.

Design summary. Kuramoto Attention has four parts. The gated similarity produces the coupling weights, the circular-mean value update changes the phases, the increment bound controls the step size, and the feed-forward block mixes coordinates between synchronization steps. Section 3 shows that the value update is exactly a Kuramoto coupling step for fixed attention weights, and Section 4.3 tests how much each design choice contributes to language-modeling performance.

3 The Synchronization Mechanism

The layer is built so that attention is a synchronization step. Each token is a small bank of oscillators (points on a circle), the softmax selects which past tokens a token attends to, and the value update pulls the token's oscillators toward the selected ones. Two facts make the mechanism precise: the softmax is entropy-regularized retrieval, and the value update is the negative gradient of an attention-weighted coherence energy.

On the circle, with attention weights held fixed, that gradient is exactly Kuramoto coupling. Rotary position enters the score as a phase drift.

Throughout, we write $G_{t,j} = \sum_u A_{t,u} e^{i\theta_{u,j}}$ for the attention-weighted resultant: the weighted sum of the attended unit vectors $e^{i\theta_{u,j}}$, read as a planar vector. Its argument is the circular mean of those phases, and its length $\|G_{t,j}\| \in [0,1]$ measures how closely the phases agree, near 1 when the attended phases align and near 0 when they cancel.

3.1 Softmax selects neighbors

Proposition 1 (Entropy-regularized retrieval). *Write the score as $s_{t,u} = \tau \, \bar{s}_{t,u}$, where $\bar{s}_{t,u}$ is the τ-free cosine affinity and $\tau > 0$ is the learned score scale. With retrieval cost $c_t(u) = -\bar{s}_{t,u}$ and entropy temperature $\lambda = 1/\tau$, the attention weights are the unique minimizer*

$$A_{t,\cdot} = \arg\min_{\pi \in \Delta} \left\{ \sum_u \pi(u) \, c_t(u) + \lambda \operatorname{KL}(\pi \,\|\, \operatorname{unif}) \right\} = \operatorname{softmax}_u(\bar{s}_{t,u}/\lambda) = \operatorname{softmax}_u(s_{t,u}).$$

Proof. The Gibbs variational identity (Boyd & Vandenberghe, 2004) applies. A Lagrange multiplier on the simplex gives $\pi^* \propto \exp(-c_t/\lambda)$, and the uniform reference contributes only a constant. □

The learned scale $\tau = 1/\lambda$ is the inverse temperature of the retrieval. Large τ sharpens attention toward the closest keys, while $\tau \to 0$ makes it uniform. The softmax therefore chooses a soft set of neighbors and sets how strongly each is coupled.

3.2 The value update is coherence descent

Selection fixes the coupling matrix A; the value update then pulls each token toward the tokens it selects. That pull is the negative gradient of a single coherence energy.

Lemma 2 (Synchronization is coherence descent). *For fixed A, the value update a_t of Section 2 is the negative gradient of the attention-weighted coherence energy $E_t(\theta_t) = -\sum_u A_{t,u} \sum_j \cos(\theta_{t,j} - \theta_{u,j})$:*

$$a_{t,j} = -\partial E_t/\partial \theta_{t,j} = -\sin\theta_{t,j} \operatorname{Re} G_{t,j} + \cos\theta_{t,j} \operatorname{Im} G_{t,j} = \sum_u A_{t,u} \sin(\theta_{u,j} - \theta_{t,j}).$$

This is the Kuramoto coupling term with coupling matrix A.

Proof. $\partial_{\theta_{t,j}} \cos(\theta_{t,j} - \theta_{u,j}) = -\sin(\theta_{t,j} - \theta_{u,j})$; sum against $A_{t,u}$ and negate. The middle expression is the same sum expanded through $\sin(\theta_{u,j} - \theta_{t,j}) = \sin\theta_{u,j} \cos\theta_{t,j} - \cos\theta_{u,j} \sin\theta_{t,j}$. □

The score and the update use the same cosine coherence. In the score, this coherence is weighted by the learned metric $\mathcal{G}(\theta) = \operatorname{diag}(g^q g^k)$ of Appendix A, which sets *which* tokens couple (Proposition 1). In the value update, the negative gradient of the selected coherence is the synchronization step. The metric picks the neighbors, and the descent step synchronizes with them.

State-dependent coupling. The descent identity is a single-step statement with A held fixed. The full layer recomputes A from the current phases, so the selected neighbors and the coherence being descended can change from one layer to the next. Its coupling matrix is causal and content-dependent: each token is pulled toward the attention-weighted circular mean of the tokens before it, with pull strength set by the resultant length $\|G_{t,j}\|$.

3.3 From direction to increment

Lemma 2 gives the *direction* a_t of the update. The implemented layer turns it into the increment it adds to the state by two further multiplicative steps (Section 2). A learned, content-dependent per-coordinate value gate rescales each coordinate's update on its own, with a learned sign: a positive gate gives Kuramoto

attraction toward the attended mean, a negative gate gives repulsion, so a single layer can both synchronize and desynchronize a coordinate against the tokens it selects. A norm bound then rescales the whole increment by one positive scalar. Selection sets where each phase is pulled; the gate sets how strongly and in which direction; the bound sets the overall step.

3.4 A multiplicative value path

Remark 1 (Raw phase states as values). For any attention matrix A, taking the current phase states as values and projecting the attention-weighted resultant onto the tangent gives the Kuramoto update $\sum_u A_{t,u} \sin(\theta_{u,j} - \theta_{t,j})$ of Lemma 2. A learned value map changes this operation: it averages transformed features, so the output is a transformed-feature mean in place of the circular mean of the current phases. The raw-state value path is the case analyzed here.

A standard attention layer mixes the embedding coordinates additively. Its value and output projections W_V and W_O are dense linear maps, so each coordinate of the output is a weighted sum of all coordinates of the input. This additive mixing across coordinates is a core part of what a standard attention layer computes.

Kuramoto attention uses a multiplicative value path. The value that the layer aggregates is the raw phase state $e^{i\theta_u}$ itself. From the aggregate G_t the layer forms the Kuramoto direction by the tangent projection (Absil et al., 2008). This projection turns the aggregated state into the phase increment applied at the current token. The layer then scales that direction with a learned, content-dependent per-coordinate value gate $v(\theta_t)$ before bounding it in the value-update lines of Equation (1). The value transformation therefore happens after the raw phase states have been averaged: the value gate rescales each coordinate's update on its own, with a learned sign, and the norm-match bound applies a single positive scalar to the whole increment. These steps preserve the coordinatewise value channels.

The attention-like learned maps are therefore gates in two different places. The query and key gates live before the softmax: they define the metric under which neighbors are selected. The value gate lives after the softmax: it rescales the tangent synchronization direction, with a learned sign, after the current phase states have already been averaged. Additive cross-coordinate computation still enters the layer, through the gate readouts. Each gate entry is a dense linear readout of all phases, $g_{t,j}^q = \rho\big((W_q \psi(\theta_t))_j\big)$ with W_q dense, so coordinate j's gate depends on every phase, and the value gate is the same kind of dense readout. These readouts set two kinds of per-coordinate scalars: the query/key products that define the score metric, and the value-gate strengths that scale the tangent update. Both enter the synchronization update multiplicatively through the single shared attention weight $A_{t,u}$. Coordinate values stay separated through the synchronization update; the feed-forward block, a dense linear map, performs additive value mixing across coordinates. The ablations test both sides of this split. Making the value path additive across coordinates, by replacing the value gate with a dense linear value projection, costs +0.25 BPC (Remark 1). A more literal value-transport variant, which replaces the diagonal metric gates with a low-rank transport frame before aggregating values, costs +0.33 BPC. Removing the feed-forward block, which mixes coordinates additively, costs +0.27 BPC. These ablations show that the multiplicative value path and the additive feed-forward block each contribute distinct behavior.

3.5 Rotary position as phase drift

Position is the remaining score-side ingredient. We implement it with rotary encoding, using position as a per-coordinate phase drift in the score, $s_{t,u} = \frac{\tau}{\sqrt{k}} \sum_j g_{t,j}^q g_{u,j}^k \cos(\theta_{t,j} - \theta_{u,j} + \omega_j(t - u))$. For this layer the drift has a direct dynamical role. The rates ω_j are learned per coordinate (initialized at the geometric rotary schedule) and serve as the layer's natural-frequency terms: each coordinate advances at its learned rate before two token states are compared. The gates and the drift affect selection in different ways: the gates change the learned metric, while the drift sets the position-dependent phase advance. Together they determine which tokens couple, and the value update then synchronizes with those selected tokens (Lemma 2).

Remark 2 (Score-only position). The drift $\omega_j(t - u)$ is fixed by the positions. Applying it in the score changes which tokens are selected while keeping the content state as raw phases. The experiments use this score-only placement as the reference positional mechanism.

4 Experiments

4.1 Setup

We train at $\approx 10^6$ and $\approx 5 \times 10^6$ parameters on enwiki8 (Hutter, 2006), sequence length 256, 4 layers, 50 epochs, with total parameters matched to the transformer baseline at each parameter budget. Optimizer, learning rate, architecture, exact parameter counts, and the matching protocol are in Appendix B. We also run matched checks on a byte-level CodeParrot subset (CodeParrot, 2022); Table 2 reports the 1M and 5M sweeps. Training throughput and peak memory are reported in Appendix B from the same metrics files.

4.2 Matched 1M and 5M Comparisons

We train Kuramoto Attention at $\approx 10^6$ and $\approx 5 \times 10^6$ parameters on enwiki8, with total parameters matched to a RoPE+SwiGLU transformer at each parameter budget. At one million parameters the transformer leads by about 0.02 BPC on both validation and test (Table 1). At five million parameters, the six Kuramoto-attention runs have validation/test medians 1.449/1.452, below the transformer medians 1.452/1.455. Their all-seed means are 1.465±0.040 validation and 1.468±0.039 test, within 0.01 BPC of the matched-transformer means. Five of the six runs form a tight cluster with validation/test means 1.449 ± 0.002 and 1.452 ± 0.002, below the matched-transformer means 1.456 ± 0.010 and 1.461 ± 0.012; the remaining run separated from the cluster in the first epoch and finished at validation/test BPC 1.546/1.547. On byte-level CodeParrot, a second task, the transformer leads at one million parameters by 0.015 validation and 0.013 test bits per byte. At five million parameters, the Kuramoto-attention seeds have validation/test medians 1.130/1.127 and means 1.130/1.127, below the five-seed transformer medians 1.141/1.137 and means 1.142/1.137 (Table 2). The 5M mean gaps, transformer minus Kuramoto Attention, are 0.0118 validation and 0.0099 test bits per byte.

		1M		5M	
Model	split	median	mean±std	median	mean±std
Kuramoto attention	val	1.629	1.637 ± 0.011	1.449	1.465 ± 0.040
	test	1.623	1.629 ± 0.012	1.452	1.468 ± 0.039
clustered subset	val		$--$	1.448	1.449 ± 0.002
	test		$--$	1.451	1.452 ± 0.002
Matched transformer	val	1.616	1.616 ± 0.004	1.452	1.456 ± 0.010
(RoPE+SwiGLU)	test	1.610	1.610 ± 0.004	1.455	1.461 ± 0.012

Table 1: Validation and test BPC as median and mean±std. The 1M cells use five seeds; the 5M Kuramoto-attention cell uses all six completed seeds. The indented row reports the five-run cluster after one seed separated from the cluster in the first epoch and finished at val/test BPC 1.546/1.547.

		1M		5M	
Model	split	median	mean±std	median	mean±std
Kuramoto attention	val	1.246	1.246 ± 0.001	1.130	1.130 ± 0.001
	test	1.236	1.235 ± 0.002	1.127	1.127 ± 0.001
Matched transformer	val	1.232	1.231 ± 0.004	1.141	1.142 ± 0.007
(RoPE+SwiGLU)	test	1.223	1.223 ± 0.004	1.137	1.137 ± 0.006

Table 2: Byte-level CodeParrot check at sequence length 256. Values are bits per byte. All cells use five seeds. At 1M the transformer leads by 0.015 validation and 0.013 test; at 5M Kuramoto Attention is lower than the transformer by both median and mean, with mean gaps of 0.012 validation and 0.010 test.

4.3 Ablation suite

The metric form of the score organizes the ablations. Kuramoto Attention uses two main synchronization components: a learned metric on the torus, which defines the score, and a circular mean, which defines the value update. In query/key/value language, the query and key maps are metric gates, and the value-side map is a signed gate on the tangent update. These ingredients, together with the positional drift in the score, define the synchronization part of the layer. The feed-forward block supplies dense cross-coordinate mixing between synchronization steps. We ablate one axis at a time from the reference configuration and include low-rank value transport because the metric view suggests a direct alternative to the raw-state value path: one can try to carry values between token states through a learned transport rule rather than aggregate the raw phases directly (Appendix A and table 3).

Ablation	Δ val BPC	component
low-rank value transport	$+0.33 \pm 0.05$	value transport
remove feed-forward block	$+0.27 \pm 0.00$	feed-forward
learned value projection	$+0.25 \pm 0.08$	value update
remove value gate	$+0.11 \pm 0.00$	value update
remove metric gates	$+0.09 \pm 0.00$	metric
linear feed-forward map	$+0.07 \pm 0.00$	feed-forward
per-layer (unshared) gates	$+0.05 \pm 0.01$	metric
shared feed-forward block	$+0.04 \pm 0.02$	feed-forward
remove gate normalization	$+0.02 \pm 0.01$	minor
remove value bound	$+0.02 \pm 0.01$	minor
linear readout	$+0.01 \pm 0.00$	readout
sigmoid metric gates	-0.01 ± 0.00	metric
linear (signed) metric gates	-0.01 ± 0.01	metric

Table 3: Ablations and the value-transport comparison, mean $\pm$ std over five seeds, Δ from the reference (five-seed mean 1.637); total parameters are re-matched per row. In the implementation, low-rank value transport is a targeted metric/transport comparison: it uses a learned transport metric in place of the diagonal Q/K gate metric. Negative values improve on the reference.

Metric and mean components. These ablations test the pieces that make the layer a synchronization update. The circular-mean value update is the Kuramoto coupling step (Lemma 2; circular-mean vs. a learned value projection, value gate and bound). The metric defines the coupling kernel (Proposition 1; gate activation, mean-normalization, shared vs. per-layer). The rotary drift supplies the score's positional component; in the reference configuration it is applied only in the score (Remark 2). The metric and value-update components account for most of the performance changes in the ablation suite. Replacing the circular mean with a learned value projection costs $+0.25$ BPC, and removing the value gate on the update costs $+0.11$. The value-transport variant tests a more structured value path motivated by the metric view. A metric suggests connection- or frame-based ways to carry tangent information between states; this row replaces the diagonal Q/K gate metric with the low-rank transport metric required to transport values, and costs $+0.33$ BPC. This transport construction underperforms the simpler raw-phase mean. Removing the metric gates costs $+0.09$, and untying them across layers costs a further $+0.05$, so the single shared metric is important to performance. The activation that keeps the metric gates positive has little effect in these runs: replacing softplus with sigmoid gates, or with linear gates that admit signed coupling, changes validation BPC by -0.01 in these runs. Gate normalization, the value bound, and the phase-alignment readout are also small effects. The linear-readout row replaces the phase-prototype readout with the standard learned linear map to vocabulary logits and changes validation BPC by $+0.01$. The learned selection metric and tangent update matter more than the smaller stability and readout choices around them.

Feed-forward block. This block is separate from the coupling kernel and the synchronization step. It is implemented as the same SwiGLU that the matched transformer uses, and it is the layer's additive cross-

coordinate mixer (Section 3.4). Removing it costs +0.27 BPC, the largest clean single-axis effect in the suite. Sharing it across layers in place of per-layer learning costs +0.04, and replacing it with a linear map costs +0.07, so its nonlinearity contributes measurably. These changes show that dense cross-coordinate mixing contributes to performance alongside the synchronization update.

Minor components. Gate normalization, the value bound, and a phase-alignment readout each move validation BPC by at most 0.02 relative to their simpler alternatives.

Ablation pattern. The ablations favor keeping the Kuramoto design simple: learned metric gates select neighbors, the raw-phase circular mean supplies the synchronization direction, a signed value gate controls the step, and the generic SwiGLU block handles cross-coordinate mixing. The connection/frame-style value transport is less effective here. Reading the score as a metric (Appendix A) still suggests next variants, including frame-field connections, transport-based scores, richer local metrics, and feed-forward maps defined directly on phase features.

4.4 Phase dynamics

The trained model shows the synchronization directly in its phase dynamics (Figures 1 and 2). For each token, we compute the attention-weighted order parameter $R_{t,j} = |\sum_u A_{t,u} e^{i\theta_{u,j}}|$, the coherence of the neighbors selected by attention. Averaged over coordinates, this local coherence stays high, and each token's phase aligns with that mean, so tokens synchronize with the neighbors they attend to. We compare it with the global order parameter $R_j^{\text{glob}} = |\frac{1}{N}\sum_u e^{i\theta_{u,j}}|$, the uniform all-token coherence; a high global value would mean collapse to one phase. The global statistic falls with depth while local coherence stays high, showing phase diversity alongside local synchronization. The learned phase-drift rates ω_j also form a depth-to-timescale trend: larger ω_j advances phase faster per position, so the score $\cos(\theta_{t,j} - \theta_{u,j} + \omega_j(t - u))$ de-correlates over a shorter token distance. Higher frequencies therefore favor shorter-range coupling, lower frequencies favor longer-range coupling, and the learned profile is consistent with early layers emphasizing nearby tokens and later layers using longer context.

Figure 1: Local synchronization with global phase diversity (reference 1M run, validation split). **(a)** The local order parameter $R_t = \langle|\sum_u A_{t,u} e^{i\theta_{u,j}}|\rangle_j$, the coherence of each token with the neighbors it attends to, stays near one at every layer and sequence position. **(b)** The global order parameter $R^{\text{glob}} = \langle|\frac{1}{N}\sum_u e^{i\theta_{u,j}}|\rangle_j$, the same coherence with the attention weights replaced by a flat average over all N tokens, falls with depth while the local one stays high: each token locks to its selected neighbors while the population of phases spreads out.

Figure 2: Learned phase-drift rates follow a depth-to-timescale trend (reference 1M run). **(a)** The per-layer spectrum of learned rates $|\omega_j|$ departs from the geometric rotary initialization (dashed). **(b)** The mean rate falls with depth; a high frequency de-correlates the score over a short token distance, so early layers couple short-range and later layers long-range.

4.5 Heads and depth

The main 1M and 5M comparisons and the ablation suite use four layers and a single head. To check that this fixed shape is representative for both models, we sweep heads $h \in \{2, \ldots, 6\}$ and layers $L \in \{2, \ldots, 6\}$ for both models at the 1M budget, re-matching the total parameter count in every cell and keeping the rest of the protocol unchanged, with three seeds per cell. For Kuramoto Attention a head partitions the k oscillators into h independent populations, each scored by its own gates and synchronized under its own attention pattern. Table 4 reports the full sweep.

	$L = 2$	$L = 3$	$L = 4$	$L = 5$	$L = 6$
Kuramoto attention					
$h = 2$	1.705 ± 0.002	1.635 ± 0.002	1.608 ± 0.004	1.596 ± 0.003	$\mathbf{1.585 \pm 0.007}$
$h = 3$	1.682 ± 0.001	1.634 ± 0.004	1.597 ± 0.001	1.603 ± 0.007	1.594 ± 0.008
$h = 4$	1.679 ± 0.004	1.628 ± 0.007	1.605 ± 0.002	1.587 ± 0.003	1.587 ± 0.002
$h = 5$	1.677 ± 0.001	1.617 ± 0.003	1.596 ± 0.002	1.593 ± 0.004	1.614 ± 0.007
$h = 6$	1.667 ± 0.003	1.632 ± 0.004	1.602 ± 0.007	1.600 ± 0.004	1.609 ± 0.006
Matched transformer (RoPE+SwiGLU)					
$h = 2$	1.668 ± 0.005	1.612 ± 0.002	1.591 ± 0.001	1.577 ± 0.009	1.567 ± 0.004
$h = 3$	1.658 ± 0.012	1.596 ± 0.004	1.585 ± 0.006	$\mathbf{1.566 \pm 0.001}$	1.578 ± 0.007
$h = 4$	1.646 ± 0.003	1.603 ± 0.007	1.591 ± 0.003	1.583 ± 0.017	1.570 ± 0.009
$h = 5$	1.653 ± 0.013	1.597 ± 0.002	1.582 ± 0.002	1.631 ± 0.022	1.585 ± 0.021
$h = 6$	1.645 ± 0.023	1.593 ± 0.003	1.587 ± 0.007	1.578 ± 0.003	1.590 ± 0.005

Table 4: Validation BPC (best epoch) across heads h and layers L at the 1M budget, mean±std over three seeds, total parameters re-matched per cell. Bold marks the best cell for each model.

Two regularities hold for both models. Depth matters more than head count: moving from two to five layers improves every head count by about 0.06 to 0.11 BPC, while changing heads at fixed depth usually moves only a few hundredths. The sixth layer changes results by at most about 0.02, and the main exception to the depth trend is the high-variance transformer cell at h=5, L=5 (1.631 ± 0.022). Shape tuning helps both models by about 0.05: the best Kuramoto-attention cell reaches 1.585 ± 0.007 (h=2, L=6) from 1.637, and the best transformer cell reaches 1.566 ± 0.001 (h=3, L=5) from 1.616. The $\approx$0.02 BPC gap at the 1M budget remains after tuning, so the fixed shape used in Table 1 does not create the observed gap.

5   Related Work

Language models as cognitive and neural models.   Deep language models provide a useful comparison class for human language processing: their contextual representations and predictive computations align with measured brain responses during natural language comprehension (Caucheteux & King, 2022; Goldstein et al., 2022). More recent work moves beyond embedding-level comparisons and asks whether transformer circuits and human language cortex show related forms of functional specialization (Kumar et al., 2024). Our work uses the same broad comparison between language models and cognitive/neural modeling, but focuses on the mechanism inside the layer: we build a language-modeling attention layer whose update is an explicit synchronization step, giving concrete phase, coupling, and coherence variables for future comparisons.

Oscillatory computation, synchrony, and binding.   Oscillatory dynamics are a long-running abstraction in neuroscience and cognitive modeling. Cortical traveling waves and coordinated oscillatory activity have been studied as possible mechanisms for routing, memory, long-range coordination, and population-level computation (Muller et al., 2018). AKOrN brings this motivation into deep learning by using Kuramoto oscillatory neurons as a dynamical alternative to standard neural units (Miyato et al., 2025): synchronization binds features, induces competitive compression, and can be placed inside several connectivity patterns, including attention. Muzellec et al. (2025) also add complex-valued representations and Kuramoto synchronization dynamics to deep networks, with gains on object binding. These models add oscillator dynamics to a network. In contrast, our oscillator state is the attention state: the value update is the Kuramoto coupling step for a fixed attention matrix, with phase-drift rates in the score serving as the layer's natural-frequency terms (Section 3) and a coupling kernel given by an entropy-regularized soft assignment (Proposition 1), evaluated on language modeling.

Transformers as synchronizing dynamics.   Geshkovski et al. (2023; 2024) read self-attention as an interacting particle system and analyze its limiting clustering behavior. Our trained phase-valued layer has a per-step synchronization rule for fixed attention weights: the value update uses the current phase states as values, so the aggregate encodes a circular mean and its tangent projection is exactly the Kuramoto step. A learned value map averages transformed features, defining a different operation from the raw-state value path of Remark 1.

Kuramoto dynamics.   The classical model (Kuramoto, 1975; Acebrón et al., 2005) couples phase oscillators with heterogeneous natural frequencies. Our layer uses the same coupling direction in a content-adaptive setting: the coupling matrix is a softmax of token similarities and the score uses learned phase-drift rates.

Attention as associative memory.   Ramsauer et al. (2021) connect attention to modern Hopfield retrieval, where a step is energy descent toward stored patterns. The complementary formulation casts the same step as synchronization on phase states: the softmax weights act as a coupling kernel and the value update is the Kuramoto step that pulls each token's phases toward the phases of the tokens it attends to (Lemma 2).

Rotary position.   In the phase-state representation, rotary embeddings (Su et al., 2021) act as a position-dependent phase drift in the score (Section 3). In Kuramoto Attention, the learned drift rates are the layer's natural-frequency terms in the score.

6   Conclusion

We introduced Kuramoto Attention, a phase-valued self-attention layer that keeps transformer-style softmax selection but makes the value update a synchronization step. Each token carries a bank of phase oscillators, query/key gates define a phase-alignment metric for selecting neighbors, and the values are the raw phase states. With the attention matrix held fixed, the circular-mean value update is exactly the Kuramoto coupling direction $\sum_u A_{t,u} \sin(\theta_u - \theta_t)$ (Lemma 2). With the matrix recomputed from the current phases, the residual block becomes a content-dependent synchronization update for language modeling.

On enwiki8 and CodeParrot, Kuramoto Attention trains as a byte-level language model at 1M–5M parameters against matched RoPE+SwiGLU transformers. Its strongest results are at 5M. On CodeParrot, it improves on the transformer by both mean and median validation/test bits per byte. On enwiki8, all six runs have lower validation/test medians than the transformer and all-seed means within 0.01 BPC; five of six also form a tight lower-mean cluster. At 1M, the transformer leads by about 0.02 BPC on enwiki8 and by 0.013–0.015 bits per byte on CodeParrot.

The ablations and diagnostics identify what makes the layer work. Metric-gated selection, the circular-mean value update, the value gate, and feed-forward mixing account for most of the observed performance changes, while the tested geometry-inspired value-transport rule is worse than aggregating raw phase states directly. The trained phases show high attention-weighted local coherence with global phase diversity, and learned phase drifts organize by depth from shorter- to longer-range coupling.

The ablations also suggest clear directions for future architectures. Kuramoto Attention already has a geometric interpretation in its score and value update, and the value-transport comparison suggests that additional geometric structure is most promising when tied directly to the computation it is meant to improve. A natural next step is to revisit connection- and frame-field mechanisms in a more targeted form: learned local frames could define how tangent directions are compared across token states, and transport rules could be coupled to the same metric that selects neighbors. The feed-forward block is the other open component. In this paper a standard SwiGLU block supplies dense cross-coordinate mixing between synchronization steps. Future architectures can ask whether that role can be played by a phase-native vector field, a coupled-oscillator mixing layer, or another geometry-aware residual map on the torus.

For cognitive science, the contribution is a language-modeling system whose central attention operation is written in variables familiar from dynamical coordination: coupling weights, oscillator phases, local coherence, and learned frequency drift. This makes the layer analyzable at the level of coordination events alongside its hidden-state representations. One can ask when a token forms a high-coherence local coalition with its attended context, whether depth-dependent learned frequencies track context-integration timescales, and how selection and synchronization divide labor across sequence processing. These questions give concrete bridges to work on binding, oscillatory coordination, and predictive language processing, while also providing diagnostics for future machine-learning models built around synchronization.

References

P.-A. Absil, Robert Mahony, and Rodolphe Sepulchre. *Optimization Algorithms on Matrix Manifolds*. Princeton University Press, 2008.

Juan A Acebrón, Luis L Bonilla, Conrad J Pérez Vicente, Félix Ritort, and Renato Spigler. The Kuramoto model: A simple paradigm for synchronization phenomena. *Reviews of Modern Physics*, 77(1):137–185, 2005.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Stephen Boyd and Lieven Vandenberghe. *Convex Optimization*. Cambridge University Press, 2004.

Charlotte Caucheteux and Jean-Rémi King. Brains and algorithms partially converge in natural language processing. *Communications Biology*, 5(1):134, 2022. doi: 10.1038/s42003-022-03036-1.

CodeParrot. CodeParrot dataset cleaned. `https://huggingface.co/datasets/codeparrot/codeparrot-clean`, 2022.

Borjan Geshkovski, Cyril Letrouit, Yury Polyanskiy, and Philippe Rigollet. The emergence of clusters in self-attention dynamics. In *Advances in Neural Information Processing Systems*, 2023.

Borjan Geshkovski, Cyril Letrouit, Yury Polyanskiy, and Philippe Rigollet. A mathematical perspective on transformers. *arXiv preprint arXiv:2312.10794*, 2024.

Ariel Goldstein, Zaid Zada, Eliav Buchnik, Mariano Schain, Amy Price, Bobbi Aubrey, Samuel A. Nastase, Amir Feder, Dotan Emanuel, Alon Cohen, Aren Jansen, Harshvardhan Gazula, Gina Choe, Aditi Rao, Catherine Kim, Colton Casto, Lora Fanda, Werner Doyle, Daniel Friedman, Patricia Dugan, Lucia Melloni, Roi Reichart, Sasha Devore, Adeen Flinker, Liat Hasenfratz, Omer Levy, Avinatan Hassidim, Michael Brenner, Yossi Matias, Kenneth A. Norman, Orrin Devinsky, and Uri Hasson. Shared computational principles for language processing in humans and deep language models. *Nature Neuroscience*, 25(3): 369–380, 2022. doi: 10.1038/s41593-022-01026-4.

Marcus Hutter. The Hutter prize for lossless compression of human knowledge (enwik8). `http://prize.hutter1.net/`, 2006.

Sreejan Kumar, Theodore R. Sumers, Takateru Yamakoshi, Ariel Goldstein, Uri Hasson, Kenneth A. Norman, Thomas L. Griffiths, Robert D. Hawkins, and Samuel A. Nastase. Shared functional specialization in transformer-based language models and the human brain. *Nature Communications*, 15(1):5523, 2024. doi: 10.1038/s41467-024-49173-5.

Yoshiki Kuramoto. Self-entrainment of a population of coupled non-linear oscillators. *International Symposium on Mathematical Problems in Theoretical Physics*, pp. 420–422, 1975.

Ilya Loshchilov, Cheng-Ping Hsieh, Simeng Sun, and Boris Ginsburg. nGPT: Normalized transformer with representation learning on the hypersphere. *arXiv preprint arXiv:2410.01131*, 2024.

Takeru Miyato, Sindy Löwe, Andreas Geiger, and Max Welling. Artificial Kuramoto oscillatory neurons. In *International Conference on Learning Representations*, 2025.

Lyle Muller, Frédéric Chavane, John Reynolds, and Terrence J. Sejnowski. Cortical travelling waves: mechanisms and computational principles. *Nature Reviews Neuroscience*, 19(5):255–268, 2018. doi: 10.1038/nrn.2018.20.

Sabine Muzellec, Andrea Alamia, Thomas Serre, and Rufin VanRullen. Enhancing deep neural networks through complex-valued representations and Kuramoto synchronization dynamics. *Transactions on Machine Learning Research*, 2025.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Thomas Adler, Lukas Gruber, Markus Holzleitner, Milena Pavlović, Geir Kjetil Sandve, et al. Hopfield networks is all you need. In *International Conference on Learning Representations*, 2021.

Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *arXiv preprint arXiv:2104.09864*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

Biao Zhang and Rico Sennrich. Root mean square layer normalization. In *Advances in Neural Information Processing Systems*, 2019.

A   The score as a position-varying metric

The score splits into an equal-position part and the rotary drift $\omega_j(t-u)$, where the rotary drift supplies the layer's natural-frequency terms (Section 3). The metric is the equal-position part of this split. To extract it, fix a query at θ and a key at $\theta+\delta$ with small δ and $t=u$. At equal position the rotary drift $\omega_j(t-u)$ vanishes, so the score's kernel $\cos(\theta_{t,j} - \theta_{u,j} + \omega_j(t-u))$ reduces to $\cos\delta_j$, with δ_j the j-th component of the offset δ. For gates that vary slowly across the torus we treat them as locally constant, $g_j^k(\theta + \delta) = g_j^k(\theta) + O(\delta\nabla g)$, so the score's leading δ-dependence is the cosine kernel. Expanding it,

$$s \;=\; \frac{\tau}{\sqrt{k}} \sum_j g_j^q(\theta)\, g_j^k(\theta) \cos\delta_j \;=\; \frac{\tau}{\sqrt{k}} \sum_j g_j^q g_j^k \;-\; \frac{\tau}{2\sqrt{k}} \sum_j g_j^q g_j^k \delta_j^2 \;+\; O(\delta^4,\; \delta\nabla g),$$

so similarity falls off quadratically in δ at a rate set by the gate product. The symmetric quadratic form that measures this second-order decay assigns a squared length $\sum_j \mathcal{G}_{jj}(\theta)\,\delta_j^2$ to a small displacement δ, with the conventional factor $1/2$ absorbed. Because the gates g^q, g^k are strictly positive (softplus outputs), this form is positive-definite and diagonal on $\mathbb{T}^k$, and it varies smoothly with θ, so it is a position-dependent metric on the flat torus,

$$\mathcal{G}(\theta) \;=\; \frac{\tau}{\sqrt{k}}\,\mathrm{diag}\big(g^q(\theta)\,g^k(\theta)\big),$$

position-dependent through the gates. Here *diagonal* describes the quadratic form: the second-order expansion has diagonal δ_j^2 terms and zero cross-terms, so $\mathcal{G}$ is diagonal at each point. As a field over the torus its entries are coupled through the dense gate readouts, because each $\mathcal{G}_{jj}(\theta)$ depends on all phases (the gates depend on every coordinate, Section 3.4), so $\partial_{\theta_i}\mathcal{G}_{jj} \neq 0$ for $i \neq j$. Sharing the gates across layers means that every layer uses the same learned metric when it scores phase alignment. The score uses this metric to select neighbors, and the value update descends the selected coherence by Lemma 2, pulling each token toward the circular mean of those neighbors. A metric specifies local lengths and angles. Transporting tangent information between nearby states is an additional design choice, not something fixed by the diagonal score alone. The low-rank value-transport row in Section 4.3 tests one such value-side transport rule; frame-field connections and transport-based scores are related variants. Because the metric entries depend on all phases through dense gate readouts, transport rules derived from this field would generally couple coordinates even though the metric is diagonal at each point. The implemented value update instead uses the closed-form tangent direction toward the circular mean of the selected tokens, while the feed-forward block supplies separate dense coordinate mixing.

B Experimental details

Data. enwiki8 (Hutter, 2006), the first 10^8 characters of English Wikipedia, split $90/5/5\%$ into train/validation/test by character. Inputs are character sequences of length 256 (vocabulary size 205). For the second-task check we use a 10^8-byte subset of CodeParrot-clean (CodeParrot, 2022), represented as raw UTF-8 bytes and split by the same $90/5/5\%$ protocol (vocabulary size 201, the distinct byte values present).

Training. AdamW, learning rate 10^{-3}, weight decay 0.01, batch size 64, gradient clipping at 1.0, dropout 0.1, 50 epochs. We use the identical training recipe for both models at both parameter budgets. The initialization scheme and optimizer settings are held fixed across the matched comparisons; the reported sweeps vary architecture and random seed under this shared recipe. We report validation BPC at the best epoch.

Compute. The metrics files record mean training throughput and peak training memory. On enwiki8, Kuramoto Attention / transformer throughput is 460k / 973k tokens/s at 1M and 167k / 335k tokens/s at 5M; reported peak memory is 2.17 / 0.87 GB at 1M and 4.62 / 1.94 GB at 5M. CodeParrot gives the same pattern: 461k / 984k tokens/s at 1M and 170k / 339k tokens/s at 5M, with peak memory 2.19 / 0.89 GB at 1M and 4.65 / 1.94 GB at 5M. All values are means over seeds.

Architecture and parameter matching. Both models use 4 layers, a SwiGLU feed-forward block, and RoPE position; the transformer baseline is single-head dot-product attention, and Kuramoto attention is likewise single-head (one shared bank of k oscillators per layer), so the two differ in the attention mechanism. We fix the depth and the parameter budget and then vary the width so that the total number of parameters is equalized at each budget. For Kuramoto attention the width is the torus dimension k, and for the transformer the width is d_{model}. The two widths count different objects: k counts phase coordinates, each carried by a two-component $(\cos, \sin)$ lift, whereas d_{model} counts model channels directly, so the Kuramoto-attention model reaches the same parameter budget at a larger nominal width ($k = 176$ vs. $d_{\mathrm{model}} = 120$ at 1M). We hold the total parameter count fixed across the two models, and the widths are allowed to differ. Table 5 reports the achieved widths and counts (matched to within $\sim 3\%$). The heads-and-depth study of Section 4.5 varies h and L away from this base shape and applies the same matching procedure in every cell (for example, at $h = 4$, $L = 6$ the matched widths are $k = 148$ with 982,882 parameters and $d_{\mathrm{model}} = 100$ with

1,006,005 parameters). The CodeParrot checks use the same matched widths as the corresponding enwiki8 runs. Because the byte vocabulary is slightly smaller, the achieved counts are 1,001,978 and 4,965,210 for Kuramoto attention, and 973,881 and 4,995,249 for the matched transformer.

Budget	Model	width	parameters
1M	Kuramoto attention	$k = 176$	1,003,386
	Matched transformer	$d_{\mathrm{model}} = 120$	974,845
5M	Kuramoto attention	$k = 400$	4,968,410
	Matched transformer	$d_{\mathrm{model}} = 276$	4,997,461

Table 5: Achieved widths and parameter counts at each parameter budget.

Ablation protocol. The rows in Table 3 start from the 1M Kuramoto-attention reference configuration, use the same training recipe, run five seeds, and re-match width to the target parameter count when a change affects capacity. Low-rank value transport is the value-transport comparison motivated by the metric view. It uses `use_qk_gates=false`, `metric_transport_mode=lowrank`, and `metric_transport_values=true`; in the implementation, value transport is defined in the same learned transport metric that replaces the diagonal Q/K gate metric. The ablation table therefore reports it as a targeted comparison rather than as a separate baseline.

The exact configuration files will accompany the anonymized code release.