SKILL-DISCO: Distilling and Compiling Agent Traces into Reusable Procedural Skills

Abstract

Agents often repeatedly solve similar task instances from scratch, leading to unnecessary reasoning cost and long execution traces. Prior work has explored workflow reuse and executable skill induction, but it remains unclear which task scenarios admit procedural skills and how the shared procedural structure should be represented across successful traces. We study this problem in FSM-defined scenarios, where successful traces can be viewed as paths in an unknown transition graph, and formulate procedural skills as reusable parameterized control-flow subgraphs. Based on this view, we introduce SKILL-DISCO, a distillation-and-compilation framework that distills reusable PFSM subgraphs from successful traces and compiles them into callable, executable, and verifiable procedural skills. Experiments on ALFWorld and WebArena show that SKILL-DISCO improves success rates and reduces agent turns across benchmarks and model scales, demonstrating the benefits of representing shared experience as reusable execution structures.

1 Introduction

LLM agents are increasingly used for interactive tasks that require many reasoning and acting steps (Yao et al., 2023; Shinn et al., 2023; Wang et al., 2024b; Yang et al., 2024). Yet even with stronger action representations such as Code-Act (Wang et al., 2024b), agents often solve each task independently, repeatedly rediscovering low-level action patterns shared across related tasks (Figure 1). This increases reasoning cost, execution length, and generalization brittleness (Wang et al., 2024c, 2025). Recent work on experience reuse addresses this issue by extracting reusable workflows from trajectories (Wang et al., 2024c) or inducing executable skills that improve verifiability and composability (Wang et al., 2025). These results suggest that agents should accumulate reusable procedures rather than solve each task from scratch.

However, the foundations of procedural skill discovery remain under-specified. Reusable skills are meaningful when tasks share stable execution patterns, but become ill-defined for open-ended, instance-specific generation. Existing methods often synthesize skills directly from successful traces using LLMs. Without an explicit notion of shared structure, the resulting libraries can become fragmented and redundant toward trace-specific surface patterns rather than reusable procedural logic.

We make the scope of procedural skill discovery explicit by focusing on *FSM-defined scenarios*, where execution dynamics are described by finite states, admissible actions, and deterministic transitions. In such scenarios, successful traces are paths in an unknown transition graph, and procedural skills correspond to repeated transition structures that help reach goal states. If this graph were known, task completion would reduce to graph search. In realistic agent settings, however, the graph is unavailable, and the agent only observes successful traces.

To capture shared structure across traces, we formalize procedural skills through a *Parameterized Finite-State Machine* (PFSM) view. A PFSM abstracts concrete states and actions into parameterized states and operators, so traces with different objects, states, or lengths can instantiate the same execution pattern. Under this view, each successful trace can be lifted into a parameterized trace graph, and a procedural skill is a reusable PFSM subgraph matched across traces under parameter binding. Thus, a skill is not merely a textual routine or an LLM-generated script, but a structurally grounded abstraction of shared execution logic.

This formulation does not assume that the latent PFSM is directly observable. In realistic agent environments, neither the full transition graph nor the lifting function from raw traces to PFSM subgraphs

Figure 1: SKILL-DISCO distills environment-adaptive PFSM skills that branch on observations, transfer across episodes and model scales without re-induction.

is given. SKILL-DISCO therefore approximates PFSM-based skill discovery by recovering reusable parameterized control-flow patterns from successful traces and validating them through skill compilation. This yields a distillation-and-compilation framework. Distillation discovers compact, high-coverage PFSM subgraphs that favor reusable structures over trace-specific routines. Compilation turns each discovered structure into a callable, executable, and verifiable skill through explicit specification and execution-grounded verification.

Our contributions are as follows:

(C1) We make explicit the scope of procedural skill discovery by focusing on FSM-defined scenarios, where successful traces are paths in an unknown transition graph and reusable skills have well-defined transition semantics.

(C2) We formulate procedural skills as reusable parameterized control-flow subgraphs that can match multiple successful traces under parameter binding. This provides structural targets for skill discovery, rather than treating each successful trace as an independent routine.

(C3) We introduce SKILL-DISCO, a distillation-and-compilation framework that approximates these structural targets and compiles them into verified and executable procedural skills.

(C4) Extensive experiments show that SKILL-DISCO improves both success rate and efficiency across different benchmarks and model scales. Further analysis shows that compact compiled skills reduce library redundancy, improve execution reliability, and transfer procedural knowledge from stronger induction models to smaller execution models.

2 Preliminaries

2.1 FSM-Defined Scenarios

In this paper, we focus on scenarios whose execution dynamics can be formulated as finite-state machines. Such scenarios have a finite state space, a finite action space, and deterministic transitions: given a state $s \in \mathcal{S}$ and an action $a \in \mathcal{A}$, the next state is uniquely determined by $\delta(s, a)$. We refer to such scenarios as *FSM-defined scenarios*.

Definition 1 (FSM-Defined Scenario) *A scenario is called an FSM-defined scenario if its execution dynamics can be represented as a finite-state machine*

$$\mathcal{M} = (\mathcal{S}, \mathcal{A}, \delta, \mathcal{S}_0, \mathcal{S}_{\text{goal}}),$$

where $\mathcal{S}$ is a finite set of states, $\mathcal{A}$ is a finite set of actions, $\delta : \mathcal{S} \times \mathcal{A} \to \mathcal{S}$ is a deterministic transition function, $\mathcal{S}_0 \subseteq \mathcal{S}$ is the set of possible initial states, and $\mathcal{S}_{\text{goal}} \subseteq \mathcal{S}$ is the set of goal states. The corresponding transition graph is defined as $G^* = (V^*, E^*)$, where $V^* = \mathcal{S}$ and $E^* = \{(s, a, s') \mid s, s' \in \mathcal{S}, a \in \mathcal{A}, \delta(s, a) = s'\}$.

For an FSM-defined scenario, if the complete transition graph G^* and the goal states are known, task completion can be reduced to finding a path from an initial state to a goal state on G^*. However, the complete transition graph is unavailable in many agent settings. Thus, we aim to infer reusable transition structures from past successful traces.

Definition 2 (Primitive Operator) *A primitive operator is a tuple*

$$op = (\mathcal{X}, \mathcal{Y}, \text{Pre}, \text{Post}),$$

, where $\mathcal{X}$ is the input space, $\mathcal{Y}$ is the output space, $\text{Pre} : \mathcal{X} \to \{0, 1\}$ is a pre-condition pred-

icate, and $\text{Post} : \mathcal{X} \times \mathcal{Y} \to \{0,1\}$ *is a post-evaluation predicate. For any input $x \in \mathcal{X}$ satisfying* $\text{Pre}(x) = 1$, *executing op produces a unique output* $y = op(x) \in \mathcal{Y}$ *such that* $\text{Post}(x,y) = 1$.

Definition 3 (Successful Trace) *Given an FSM-defined scenario* $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \delta, \mathcal{S}_0, \mathcal{S}_{\text{goal}})$, *an agent trace is a finite execution record* $\tau = (o_0, a_0, o_1, a_1, \ldots, a_{T-1}, o_T)$, *where* o_t *denotes the observation received by the agent at step t and* $a_t \in \mathcal{A}$ *is the action executed by the agent.*

The trace is induced by an underlying state trajectory $(s_0, a_0, s_1, a_1, \ldots, a_{T-1}, s_T)$, *such that* $s_{t+1} = \delta(s_t, a_t)$, *and each observation o_t is generated from the underlying state s_t. We call τ a successful agent trace if the underlying execution starts from a valid initial state and reaches a goal state, i.e. $s_0 \in \mathcal{S}_0$ and $s_T \in \mathcal{S}_{\text{goal}}$.*

Note that every action $a \in \mathcal{A}$ in an FSM-defined scenario is treated as a *Primitive Operator*, i.e. actions in a *Successful Trace* are all primitive operators. For clarity, we will simply refer to such primitive operators as actions throughout the paper.

2.2 PFSM-Based Procedural Skill Discovery

A standard FSM represents task completion as a concrete path from an initial state to a goal state. Such a path precisely records one execution, but is often too instance-specific because each transition is grounded in concrete states and actions. As a result, executions with the same control logic may appear as different paths when they involve different objects, locations, or intermediate states.

To capture reusable execution patterns, we introduce the notion of a *Parameterized Finite State Machine* (PFSM). A PFSM abstracts concrete states and actions with parameters, allowing multiple concrete FSM paths to be represented by the same parameterized control-flow structure.

Definition 4 (Parameterized FSM (PFSM)) *A Parameterized Finite State Machine is defined as*
$$\widetilde{\mathcal{M}} = (\widetilde{\mathcal{S}}, \widetilde{\mathcal{A}}, \Theta, \widetilde{\delta}, \widetilde{\mathcal{S}}_0, \widetilde{\mathcal{S}}_{\text{goal}}),$$
where $\widetilde{\mathcal{S}}$ is a finite set of parameterized states, $\widetilde{\mathcal{A}}$ is a finite set of parameterized actions, Θ is the parameter space, and $\widetilde{\delta} : \widetilde{\mathcal{S}} \times \widetilde{\mathcal{A}} \times \Theta \to \widetilde{\mathcal{S}}$ is a deterministic parameterized transition function. Each parameter assignment $\theta \in \Theta$ instantiates a parameterized transition into a concrete FSM transition. Here, a parameterized state $\tilde{s} \in \widetilde{\mathcal{S}}$ represents an abstract execution state rather than a fully grounded environment state. A parameterized

action $\tilde{a} \in \widetilde{\mathcal{A}}$ *represents an action schema whose arguments are instantiated by parameters.*

Example 1. Consider two successful traces for finding and taking a target object:

τ_1: `go_to(drawer1)` $\to$ `open(drawer1)` $\to$ `go_to(drawer2)` $\to$ `open(drawer2)` $\to$ `go_to(desk1)` $\to$ `go_to(bed)` $\to$ `take(book)` $\to$ `end`.

τ_2: `go_to(shelf1)` $\to$ `go_to(shelf2)` $\to$ `go_to(drawer1)` $\to$ `open(drawer1)` $\to$ `go_to(drawer2)` $\to$ `open(drawer2)` $\to$ `take(mug)` $\to$ `end`.

In a standard FSM, these two traces correspond to different concrete paths, because they visit different numbers of locations. However, they share the same parameterized control-flow pattern:

repeat	`go_to`(l)
	if `can_open`(l) **then** `open`(l)
	`check_target`(l, o)
until	`found`(o)
then	`take`(o).

This pattern can be represented as a PFSM with parameterized actions such as `go_to`(l) and `take`(o), where l is a location parameter and o is an object parameter. The loop over candidate locations abstracts away the number and identity of concrete locations, while preserving the reusable control logic needed to complete the task.

Given a set of successful traces, each trace can be lifted from a concrete FSM path to a subgraph of the PFSM transition graph. Such a subgraph captures the parameterized execution structure of a successful trace, including its abstract states, parameterized actions, and control-flow relations. We refer to this lifted subgraph as a *parameterized trace graph*. Since the underlying PFSM is unavailable, the lifting function $\phi : \tau_i \mapsto \widetilde{G}_i$ does not admit a closed-form definition. We approximate it via a multi-stage pipeline described in Section 3.

Our goal is to discover procedural skills from successful traces. Intuitively, a procedural skill corresponds to a PFSM subgraph that is shared by many successful traces. Such a subgraph captures a recurring control-flow structure that helps the agent reach a goal across different concrete instantiations.

Problem 1 (Procedural Skill Discovery) *Given a set of successful traces* $\mathcal{T}^+ = \{\tau_1, \tau_2, \ldots, \tau_N\}$ *and a lifting function $\phi : \tau_i \mapsto \widetilde{G}_i$ that maps each trace to a parameterized trace graph, the goal is to discover a set of procedural skills*

$\mathcal{K} = \{K_1, K_2, \ldots, K_m\}$, *where each skill K_j is a parameterized control-flow subgraph that matches a subset of $\{\widetilde{G}_i\}_{i=1}^N$ under parameter binding, i.e. $K_j \preceq \widetilde{G}_i$ for i in some index set.*

Intuitively, a desirable skill set $\mathcal{K}$ should satisfy three properties: *(i) Coverage*, where each skill is supported by multiple successful traces rather than a single execution, *(ii) Utility*, where skills capture control-flow structures that help reach goal states, and *(iii) Compactness*, where skills are neither overly specific nor trivially generic. In realistic agent settings, neither the full PFSM $\widetilde{\mathcal{M}}$ nor the lifting function ϕ is analytically available. SKILL-DISCO approximates both from successful traces through the pipeline in Section 3.

3 The SKILL-DISCO Framework

Section 2 formulates procedural skill discovery as identifying reusable PFSM subgraphs from successful agent traces. Solving this problem directly is challenging because the complete PFSM $\widetilde{\mathcal{M}}$ is unavailable, the lifting function ϕ from raw traces to parameterized trace graphs must be inferred, and exact subgraph matching under parameter binding is costly and noise-sensitive. To address these challenges, SKILL-DISCO discovers procedural skills through distillation and compilation.

3.1 Framework Overview

Figure 2 shows an overview of the SKILL-DISCO framework. The input to SKILL-DISCO is a set of successful traces $\mathcal{T}^+ = \{\tau_1, \tau_2, \ldots, \tau_N\}$, where N denotes the number of successful traces. The output is a skill library $\mathcal{K} = \{K_1, K_2, \ldots, K_m\}$, which contains the m procedural skills.

SKILL-DISCO contains two phases. The distillation phase approximates the latent lifting function from traces to reusable PFSM subgraphs. It first normalizes each raw trace into an executable intermediate program, then segments the program into subgoal-level operations, and finally clusters fragments that share parameterized control-flow structure. Each cluster is treated as an approximate PFSM subgraph and becomes a skill candidate.

The compilation phase turns each candidate structure into an executable artifact. It first constructs a skill specification with a signature, description, behavioral requirements, and metadata. It then synthesizes Python code and verifies it on held-out tasks; only skills that pass verification are included in the final callable library.

3.2 The Distillation Phase

The distillation phase consists of three stages that jointly approximate the latent lifting function $\phi : \tau_i \mapsto \widetilde{G}_i$ and discover reusable PFSM subgraphs from successful traces. As described in Section 2, each raw execution trace is first abstracted into a concrete trace graph over the FSM. This concrete trace graph is then lifted into a PFSM graph, where repeated action patterns are represented as parameterized, code-like control-flow structures with branches. Finally, reusable subgraphs are identified from the resulting PFSM graphs and extracted as procedural skills. Therefore, the lifting function ϕ is not implemented as a single monolithic step. Instead, it is decomposed into three successive transformations, each corresponding to one stage of the distillation phase.

Stage 1: Trace Normalization. Trace normalization converts each successful raw trace into a structured, executable intermediate representation. Raw agent logs interleave reasoning text, tool calls, observations, and action histories, but do not expose the control-flow structure needed for PFSM-based skill discovery. SKILL-DISCO therefore normalizes each trace into a program p_i that preserves primitive operators and observations while making loops, branches, and parameterized entities explicit.

Each normalized program has three components: primitive environment calls paired with observations, symbolic variables for task-specific entities such as objects or web elements, and code-level control flow for repeated action patterns and observation-conditioned decisions. For example, a trace that visits candidate locations until an object is found can become a loop whose guard depends on the current observation.

In our implementation, an LLM extracts all executed actions and observations, preserves their order, replaces concrete entities with typed variables when possible, and emits a Python-like program. This program is not the final skill; it is an intermediate representation from which reusable subgoal-level operations are extracted.

Stage 2: Subgoal-level Operation Extraction. The goal of Stage 2 is to decompose each normalized program into subgoal-level operations that can serve as candidate procedural skills. A complete trace often contains multiple reusable parts. For example, a single household task may include searching for an object, retrieving it, navigating to an

Figure 2: Overview of SKILL-DISCO. *Distillation* phase turns successful traces into reusable PFSM subgraphs; *Compilation* phase converts them into executable and verified skills.

appliance, and applying the appliance. Treating the whole trace as one skill would make the induced routine too specific, while treating each primitive operator as a skill would lose the benefit of procedural reuse. SKILL-DISCO therefore extracts intermediate-granularity operators that correspond to coherent subgoals.

Given a normalized program p_i, the operator extractor emits $\mathcal{O}_i = \{o_1^{(i)}, \ldots, o_{m_i}^{(i)}\}$, where each operator is represented as $o = (\nu, \sigma, \mathbf{u}, c)$. Here, ν is an action-oriented identifier, σ is a natural-language summary, $\mathbf{u} = (u_1, \ldots, u_{|o|})$ is the primitive operator sequence, and c is the corresponding code fragment. We discard unit-length fragments with $|o| = 1$, since they correspond to primitive operators rather than reusable procedural structure. The remaining multi-step operators are collected as $\mathcal{O}_{\text{multi}} = \bigcup_i \{o \in \mathcal{O}_i : |o| \geq 2\}$.

Stage 3: Procedural Skill Consolidation. Stage 3 consolidates procedural skills by clustering subgoal-level operations that approximate the same reusable PFSM subgraph. Intuitively, a useful procedural skill should be supported by multiple successful traces, rather than being an incidental pattern that appears in only one execution.

In SKILL-DISCO, subgoal-level operations are grouped together when they share the same underlying parameterized execution structure, even if their concrete objects, locations, or action lengths differ. For example, the two traces in Example 1 differ in their concrete locations, objects, and path lengths, but share the same parameterized search-and-take control flow.

Each cluster approximates a reusable PFSM subgraph and receives a reusability score:

$$r_k \approx \frac{1}{N} \sum_{i=1}^{N} \mathbb{I}[K_k \preceq \widetilde{G}_i],$$

where $K_k \preceq \widetilde{G}_i$ indicates that the PFSM subgraph approximated by cluster c_k can be matched to the lifted trace graph $\widetilde{G}_i$ under some parameter binding. The score is estimated from trace coverage and operation statistics. For each high-coverage cluster, SKILL-DISCO abstracts the shared subgoal-level operation as a procedural skill.

3.3 The Compilation Phase

The distillation phase abstracts high-coverage clusters into procedural skills representing reusable PFSM subgraphs. However, a PFSM subgraph is only a structural artifact, i.e. it does not define a callable interface, runtime grounding rules, return protocol, or failure handling. The compilation phase turns each procedural skill into a callable, executable, and verifiable version. In SKILL-DISCO, the compilation phase consists of two stages: *skill specification* and *skill synthesis and verification*.

Stage 4: Skill Specification. Stage 4 augments discovered procedural skills with explicit specifications. For each skill abstracted from a high-coverage cluster, SKILL-DISCO creates a skill definition that captures how the skill should be invoked and what behavior it should satisfy before any concrete implementation is generated. Each skill definition contains: (i) a *signature*, including an action-oriented skill name, typed parameters with default values, and a structured return type (ii) a *description*, serving as both a machine-readable docstring and LLM-facing guidance (iii) *behavioral requirements*, including preconditions, postconditions, and declared side effects and (iv) *metadata*, including the skill abstraction level, expected primitive actions amortized per invocation, and a confidence score inherited from r_k.

The explicit specification guides implementation synthesis and provides concrete criteria for verification, while giving the deployed agent a domain-agnostic vocabulary for selecting skills during task

execution.

Stage 5: Synthesis and Verification. Stage 5 turns each skill specification into a verified executable skill through a synthesis and verification loop. Given a skill definition, SKILL-DISCO first synthesizes a Python program that realizes the specified behavior using the primitive actions. During execution, f_k interacts with the workload environment and returns a structured output that provides execution information to the caller.

On a held-out set, verification checks runtime correctness, postcondition satisfaction, and action savings. Skills that fail are re-synthesized with feedback for up to R retries; any remaining failures are discarded.

The result is a verified executable skill library: each skill exposes a documented signature that agents can inspect, select, and call during task execution.

4 Experiments

We evaluate whether SKILL-DISCO can distill reusable procedural skills from successful traces and deploy them as reliable skills for interactive agents. Our experiments are organized around four questions: *RQ1.* Does SKILL-DISCO improve end-to-end task success rate and turn efficiency compared with base agents and prior skill-induction methods? (§4.2) *RQ2.* Do the procedural skills transfer across model families, scales, and reasoning modes? (§4.3) *RQ3.* How are the learned skills invoked and executed at inference time? (§4.4) *RQ4.* Do all components of SKILL-DISCO contribute to the observed gains? (§4.5)

4.1 Experimental Setup

Datasets. We evaluate on two interactive agent datasets with different execution structures: *(1) ALFWorld* (Shridhar et al., 2021) consists of text-based household tasks that require navigation, search, and object manipulation. *(2) WebArena* (Zhou et al., 2024) consists of realistic web-navigation tasks over self-hosted websites.

Splits. For each dataset, we use a strict *induction/evaluation* split: skills are derived only from the induction split and evaluated only on held-out tasks. For *ALFWorld*, the induction split consists of 200 tasks sampled from the official `train` set, and the evaluation split is the official unseen split with 134 tasks. For WebArena, which has no canonical induction split, we split the 812 tasks in half: the

Table 1: End-to-end results on ALFWorld and WebArena. Parentheses show relative changes over the base agent; **bold** marks the best result and underlining marks the second-best.

Method	SR (%) ↑	Avg. Turns ↓
(a) ALFWorld		
ReAct	82.0	19.3
CodeAct	96.3	3.6
AWMoffline	54.5	11.3
ASIoffline	47.0	11.4
SKILL-DISCO + **ReAct**	92.4 $_{(+12.7\%)}$	8.8 $_{(-54.5\%)}$
SKILL-DISCO + **CodeAct**	**99.3** $_{(+3.1\%)}$	**3.2** $_{(-11.3\%)}$
(b) WebArena		
ReAct	23.9	5.9
CodeAct	20.0	10.9
AWMoffline	21.2	5.9
ASIoffline	24.6	5.7
SKILL-DISCO + **ReAct**	**29.1** $_{(+21.6\%)}$	**5.1** $_{(-13.1\%)}$
SKILL-DISCO + **CodeAct**	22.9 $_{(+14.8\%)}$	8.5 $_{(-22.0\%)}$

first 406 tasks for induction and the remaining 406 for evaluation. All baselines use the same splits as SKILL-DISCO.

Baselines. We compare against two categories of baselines. The first category contains base agents without skill augmentation: ReAct (Yao et al., 2023) using the AgentBench implementation (Liu et al., 2023), and CodeAct (Wang et al., 2024b). The second group consists of offline workflow- and skill-induction methods: AWMoffline (Wang et al., 2024c) and the offline variant of ASI, ASIoffline (Wang et al., 2025). For all skill-augmented variants, each skill's signature and description are appended in agents' prompts to instruct LLMs to decide whether and how to invoke a skill or emit a primitive action.

Metrics. We report *success rate* (SR) and *average agent turns* (Avg. Turns) per episode. Full per-episode token usage and inference cost are reported in Appendix A.3.

4.2 End-to-End Performance

We first evaluate whether SKILL-DISCO improves complete task execution when added to existing interactive agents. Table 1 compares SKILL-DISCO with base agents and prior offline skill-induction methods using GPT-4o. SKILL-DISCO also uses GPT-4o to induce the skill library.

Higher task success rate. SKILL-DISCO achieves the highest SR on all benchmarks under our evaluation setting. On *ALFWorld*, SKILL-DISCO + CodeAct improves over the strong Code-

Table 2: Skill transfer across target models on ALF-World and WebArena. Δ denotes relative change over the vanilla setting; **bold** marks the best result.

	SR (%) ↑		Avg. Turns ↓	
Model	**Van.**	**+Sk. (Δ)**	**Van.**	**+Sk. (Δ)**
(a) ALFWorld				
Qwen3.5-4B	61.2	91.0 $_{(+48.8\%)}$	9.0	5.0 $_{(-44.4\%)}$
Qwen3.5-9B	54.5	98.5 $_{(+80.8\%)}$	10.8	3.4 $_{(-68.2\%)}$
GPT-4o	96.3	**99.3** $_{(+3.1\%)}$	3.6	3.2 $_{(-11.3\%)}$
GPT-4o-mini	71.6	94.8 $_{(+32.3\%)}$	7.1	4.4 $_{(-38.0\%)}$
GPT-5-chat	91.0	98.5 $_{(+8.2\%)}$	4.7	**3.0** $_{(-34.6\%)}$
GPT-5-mini	91.8	98.5 $_{(+7.3\%)}$	4.9	3.3 $_{(-33.3\%)}$
(b) WebArena				
Qwen3.5-4B	10.1	18.7 $_{(+85.3\%)}$	8.6	6.8 $_{(-20.4\%)}$
Qwen3.5-9B	21.2	23.9 $_{(+12.8\%)}$	6.8	6.0 $_{(-12.0\%)}$
GPT-4o	23.9	29.1 $_{(+21.6\%)}$	5.9	5.1 $_{(-13.1\%)}$
GPT-4o-mini	18.0	18.0 $_{(\pm0.0\%)}$	7.7	7.1 $_{(-7.7\%)}$
GPT-5-chat	32.5	**37.0** $_{(+13.7\%)}$	5.3	**4.8** $_{(-8.6\%)}$
GPT-5-mini	32.5	33.7 $_{(+3.8\%)}$	5.4	4.8 $_{(-10.1\%)}$

Act from 96.3% to 99.3%. On WebArena, SKILL-DISCO + ReAct improves ReAct from 23.9% to 29.1%, outperforming ASI$_{offline}$ by 4.5 absolute points. Since all offline skill-induction methods use the same induction and evaluation splits, these gains reflect the quality of the induced skills by SKILL-DISCO.

Consistent reduction in agent turns. SKILL-DISCO also reduces average turns across all settings: $-54.5\%/-11.3\%$ (ReAct/CodeAct) on *ALF-World* and $-13.1\%/-22.0\%$ on WebArena. By delegating repeated low-level action sequences to the reliable procedural skills, agents solve each task with fewer decisions.

Complementary to different agents. Table 1 shows that the same library improves both ReAct (natural-language reasoning) and CodeAct (code-emitting) across all benchmarks, indicating that SKILL-DISCO acts as an agent-agnostic augmentation layer by providing reusable procedural skills, rather than being tied to a specific agent.

4.3 Cross-Model Skill Transferability

We next test whether the skill library induced by SKILL-DISCO with GPT-4o can transfer to other models. We deploy the same skill library *without modification* across multiple target models: Qwen3.5-4B, Qwen3.5-9B, GPT-4o, GPT-4o-mini, GPT-5-chat, and GPT-5-mini. Based on Table 1, we use the skill library induced from the stronger SKILL-DISCO configuration on each benchmark: CodeAct for *ALFWorld* and ReAct for *WebArena*.

Skills transfer across target models. With the same skill library, every target model benefits: average turns drop in every cell (-7.7% to -68.2%), while SR improves by $+3.1\%$ to $+80.8\%$ on *ALF-World* and by up to $+85.3\%$ on WebArena with no decreases. These results show that the induced skills are robust across model families and scales.

Weaker models can benefit substantially from skill transfer. Although gains are not strictly monotone in capacity, the largest jumps occur on the smaller open-source backbones: Qwen3.5-9B gains $+80.8\%$ on *ALFWorld* and Qwen3.5-4B gains $+85.3\%$ on WebArena, versus only $+3.1\%$–$+7.3\%$ for GPT-4o/GPT-5-mini. Strikingly, Qwen3.5-9B with the GPT-4o-induced library reaches 98.5% on *ALFWorld*, surpassing its inducer (96.3%) at a fraction of the cost. This shows that SKILL-DISCO serves as a form of *procedural-knowledge distillation and transfer*, allowing smaller models to benefit from skills compiled by a stronger inducer.

4.4 Skill Usage and Execution Reliability

We analyze how much of an episode the agent delegates to its skill library and how reliably those skill calls execute. Following the settings in Table 1 (CodeAct on *ALFWorld* and ReAct on WebArena), we report aggregate skill-usage statistics in Table 3 and compare SKILL-DISCO with ASI$_{offline}$.

SKILL-DISCO learns compact, high-coverage skills. SKILL-DISCO uses far fewer skills than ASI (5 vs. 110 on *ALFWorld*; 20 vs. 146 on *WebArena*) while each call covers more prim. steps (5.6 vs. 0.2 on *ALFWorld*; 2.8 vs. 2.5 on *WebArena*) and larger maximum step compression (33/36 vs. 10/8). Thus, SKILL-DISCO distills compact skills that encode reusable procedures rather than shallow fragments.

Verified skills execute more reliably. SKILL-DISCO makes skill calls less error-prone, reducing execution errors from 75.3% to 0.0% on *ALFWorld* and from 33.9% to 21.5% on *WebArena*. Thus, its gains come not only from invoking skills, but from invoking skills that execute reliably; together with higher step compression, this explains the SR and turn improvements in Table 1.

4.5 Ablation Study

We evaluate the contribution of the two main phases of SKILL-DISCO, distillation and compilation, through ablations on ALFWorld using CodeAct with GPT-4o (Table 4).

Distillation is the main driver of success. Removing distillation and inducing skills per success-

Table 3: Skill-usage statistics. #Sk is the number of induced skills; Turns and Sk. turns are average total and skill-invoking turns; Avg./Max prim. steps are primitive steps collapsed per skill call; Err. is execution-error rate.

Bench	Method	#Sk	Turns ↓	Sk. turns	Avg. prim. steps	Max prim. steps	Err. (%) ↓
ALFWorld	ASI$_{offline}$	110	11.4	1.4	0.2	10	75.3
	SKILL-DISCO	5	**3.2**	2.6	5.6	33	**0.0**
WebArena	ASI$_{offline}$	146	5.5	1.3	2.5	8	33.9
	SKILL-DISCO	20	**5.1**	1.0	2.8	36	**21.5**

Table 4: Pipeline ablations. #Sk = skill library size; Relative SR Δ vs. the full pipeline in parentheses.

Configuration	#Sk	SR (%)	Turns
A1: no distill	43	53.0 (−46.6%)	11.5
A2: no compile	NA	97.0 (−2.3%)	3.6
Full SKILL-DISCO	5	**99.3**	3.2

ful trace yields a larger 43-skill library but reduces SR from 99.3% to 53.0% and increases turns from 3.2 to 11.5. Without cross-trace consolidation the library is dominated by overlapping, trace-specific variants, making skill selection harder and causing wrong-variant invocations or fallback to long open-loop executions.

Compilation mainly improves execution compactness. Removing compilation and shipping the output of Stage 3 as natural-language procedure descriptions only modestly reduces SR ($99.3 \rightarrow 97.0\%$), but each episode must keep the full procedure text in context, inflating tokens (Appendix A.3). Compiling skills into callable code externalizes procedural execution from the prompt, yielding both efficiency and a small additional reliability gain.

5 Related Work

LLM-Based Agents. ReAct (Yao et al., 2023) interleaves reasoning with actions; CodeAct (Wang et al., 2024b), PAL (Gao et al., 2023), and Code as Policies (Liang et al., 2023) show executable code improves compositional reasoning (Wei et al., 2022). Yet procedural knowledge in successful traces remains ephemeral and rarely reused.

Reusing Agent Experience as Behavioral Imitation. A common line keeps the model fixed and reuses experience as *token-level context*: Reflexion (Shinn et al., 2023) prompts self-reflection; AWM (Wang et al., 2024c) induces textual workflows; Trace2Skill (Ni et al., 2026) writes structured skill documents. All store knowledge in *natural language*—unverifiable before deployment and

re-interpreted at inference. SKILL-DISCO instead compiles procedural knowledge into external executable code, verifiable offline and reusable across models.

Synthesizing Executable Tools, Workflows, and Skills. *(1) Tool and workflow generation.* LATM (Cai et al., 2023), CREATOR (Qian et al., 2023), and ToolGen (Wang et al., 2024a) synthesize or unify tools per task; AgentDistill (Qiu et al., 2025) produces MCP modules for training-free transfer. At the system level, ADAS (Hu et al., 2024), AgentSquare (Shang et al., 2024), AFlow (Zhang et al., 2024), and MaAS (Zhang et al., 2025) automate agentic-system or workflow design. All start from *explicit task specifications*; SKILL-DISCO mines a *corpus of execution traces*, grounding skills in recurring behavior. *(2) Skill induction from agent experience.* Voyager (Wang et al., 2023) commits one JavaScript function per successful task, leaving near-duplicate variants unconsolidated. SkillWeaver (Zheng et al., 2025) derives APIs from website affordances, not workload traces. ASI (Wang et al., 2025) shows programs beat free-form text as skill representations but still operates per-trajectory. SKILL-DISCO is an offline *corpus-level compiler*: semantic clustering merges equivalent operations into verified executable skills, so library size scales with distinct behaviors, not episode count.

6 Conclusion

This paper studies procedural skill discovery by making shared execution structure across successful traces explicit. We formulate skills as reusable PFSM subgraphs under parameter binding, and introduce SKILL-DISCO which distills compact, high-coverage structures from traces and compiles them into executable, and verifiable skills. Experiments on *ALFWorld* and *WebArena* show that these structurally grounded skills improve success rate and turn efficiency, supporting more reliable and transferable agent experience reuse.

Limitations

Procedural tasks only. SkillDisCo compiles programmatic skills from interaction traces and is effective for tasks with reusable procedural structure (navigation, web automation, tool use). It offers no benefit for pure NLP tasks such as text generation or reading comprehension, where success depends on linguistic understanding rather than executable procedures.

Pipeline quality depends on model capability. SkillDisCo's pipeline relies on the compiler LLM's reasoning and code-generation ability. Insufficient model capability yields incorrect or overly specific skills, and output quality degrades as model capability decreases..

Requires successful traces. Only successful episodes contribute distillation signal. In domains where even frontier models succeed rarely, the corpus may be too sparse for reliable corpus-level skill extraction.

References

Tianle Cai, Xuezhi Wang, Tengyu Ma, Xinyun Chen, and Denny Zhou. 2023. Large language models as tool makers. *arXiv preprint arXiv:2305.17126*.

Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. 2023. PAL: Program-aided language models. *arXiv preprint arXiv:2211.10435*.

Shengran Hu, Cong Lu, and Jeff Clune. 2024. Automated design of agentic systems (ADAS). *arXiv preprint arXiv:2408.08435*.

Jacky Liang, Wenlong Huang, Fei Xia, Peng Xu, Karol Hausman, Brian Ichter, Pete Florence, and Andy Zeng. 2023. Code as policies: Language model programs for embodied control. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 9493–9500.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, and 3 others. 2023. AgentBench: Evaluating LLMs as agents. *arXiv preprint arXiv:2308.03688*.

Jingwei Ni, Yihao Liu, Xinpeng Liu, Yutao Sun, Mengyu Zhou, Pengyu Cheng, Dexin Wang, Erchao Zhao, Xiaoxi Jiang, and Guanjun Jiang. 2026. Trace2Skill: Distill trajectory-local lessons into transferable agent skills. *arXiv preprint arXiv:2603.25158*. Work in progress.

Cheng Qian, Chi Han, Yi R. Fung, Yujia Qin, Zhiyuan Liu, and Heng Ji. 2023. CREATOR: Tool creation for disentangling abstract and concrete reasoning of large language models. *arXiv preprint arXiv:2305.14318*.

Jieyi Qiu, Xiang Juan, Yan Wang, Lei Yang, Xin Qi, Tao Zhang, Jun Guo, Yun Lu, Zheng Yao, Mei Wang, and 1 others. 2025. AgentDistill: Training-free agent distillation with generalizable MCP boxes. *arXiv preprint arXiv:2506.14728*.

Yu Shang, Yu Li, Keyu Zhao, Likai Ma, Jiahe Liu, Fengli Xu, and Yong Li. 2024. AgentSquare: Automatic LLM agent search in modular design space. *arXiv preprint arXiv:2410.06153*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. 2021. ALFWorld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations*.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2023. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*.

Renxi Wang, Xudong Han, Lei Ji, Shu Wang, Timothy Baldwin, and Haonan Li. 2024a. ToolGen: Unified tool retrieval and calling via generation. *arXiv preprint arXiv:2410.03439*.

Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. 2024b. Executable code actions elicit better llm agents. In *ICML*.

Zora Zhiruo Wang, Apurva Gandhi, Graham Neubig, and Daniel Fried. 2025. Inducing programmatic skills for agentic tasks. *arXiv preprint arXiv:2504.06821*.

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2024c. Agent workflow memory. *arXiv preprint arXiv:2409.07429*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35.

John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik R Narasimhan, and Ofir Press. 2024. SWE-agent: Agent-computer interfaces enable automated software engineering. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*.

Guibin Zhang, Luyang Niu, Junfeng Fang, Kun Wang, Lei Bai, and Xiang Wang. 2025. Multi-agent architecture search via agentic supernet. *arXiv preprint arXiv:2502.04180*.

Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, Xionghui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, and 1 others. 2024. AFlow: Automating agentic workflow generation. *arXiv preprint arXiv:2410.10762*.

Boyuan Zheng, Michael Y. Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, and 1 others. 2025. Skill-Weaver: Web agents can self-improve by discovering and honing skills. *arXiv preprint arXiv:2504.07079*.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2024. WebArena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations*.

A Full Results: Token Usage and Inference Cost

A.1 API Pricing Assumptions

All per-episode inference costs reported in the paper are computed from provider-published token prices, retrieved from Artificial Analysis[1] on 23 May 2026 (on-demand rates). Cached input tokens (returned inside a context-caching session) are billed at $1/10$ of the regular input rate; output tokens are billed at the full output rate. No batch-API discounts are applied.

A.2 Full Baseline Comparison with Token and Cost Statistics

Table 5 reproduces Table 1 from the main paper with the three token/cost columns restored.

A.3 Per-Episode Token and Cost Breakdown

Tables 6 expand the aggregate "Avg. In-Tok. (Cached) / Avg. Out-Tok. / Avg. Cost" figures from Table ?? with the full numerical detail for every model-setting pair.

A.4 Full Ablation Breakdown

Table 7 expands the two-row ablation summary in Table 4 (§4.5) with the no-skill baseline and per-episode token and cost statistics.

---

[1] https://artificialanalysis.ai/models#pricing

B Pipeline Stage Prompts

We summarize the LLM prompts that drive each pipeline stage (latest_pipeline/skill_mining/). For brevity each listing keeps the system message's role, key directives, and the JSON output schema; long motivating examples, repeated rationale, and formatting boilerplate from the source files are elided with "...". Placeholders in {braces} are Python f-string slots filled at runtime. A few slots in Stages 4 and 5 are specialized per benchmark (benchmark_prompts.py) – we leave them as placeholders here and omit the benchmark-specific fills for brevity.

B.1 Stage 1 — Trace → Program Transpilation

Listing 1: Stage 1 prompt (trace normalization, from prompt/trace_converter.md).

```
1  [System]
2  You are a Senior AI Systems Architect
      . Convert a raw ReAct trace
3  (alternating THOUGHT / ACTION
      messages and environment
      observations)
4  into a structured Python program that
      preserves the reasoning while
5  making control flow explicit and
      logically stable.
6
7  Each reasoning block must follow the
      Unified Reasoning Template:
8    # A. Deterministic (logic-
      controlled)
9    if "<condition>" in observation:
10       action = "<derived action>"
11       context.append((observation,
          None, action))
12       observation, available_actions
          = env.step(action)
13   # B. Cognitive (LLM-driven, for
      adaptive / uncertain steps)
14   thinking, action = llm(task,
      context, observation,
      available_actions)
15   context.append((observation,
      thinking, action))
16   observation, available_actions =
      env.step(action)
17
18 Rules: (i) use deterministic control
      flow (if/for/while) for
      repetitive
19 or stabilized reasoning; (ii) reserve
       llm() for adaptive decisions;
20 (iii) update `context` and call `env.
      step()` after every action;
21 (iv) preserve every ACTION from the
      trace -- never drop mistakes or
22 recovery steps; (v) copy real
      observation/thinking/action
      strings as
```

Table 5: Full comparison against prior baselines with a GPT-4o backbone, including per-episode token usage and inference cost. "In-Tok. (Cached)" = avg. input tokens per episode with the prompt-cached portion in parentheses (cached tokens are billed at $1/10$ of the regular input rate). Same convention used in all subsequent tables.

Method	SR (%) ↑	Avg. Turns ↓	In-Tok. (Cached)	Out-Tok.	Cost ($)
(a) ALFWorld					
ReAct	82.00	19.29	35,600 (22,200)	626	0.0450
CodeAct	96.27	3.63	7,721 (6,232)	562	0.0109
AWM$_{offline}$	54.48	11.34	38,908 (22,923)	275	0.0484
ASI$_{offline}$	47.01	11.43	68,945 (54,175)	286	0.0533
SKILL-DISCO + ReAct	**92.40** (+12.7%)	**8.78** (−54.5%)	**22,100 (11,300)** (−37.9%)	**607** (−3.0%)	**0.0360** (−20.0%)
SKILL-DISCO + CodeAct	**99.25** (+3.1%)	**3.22** (−11.3%)	**8,468 (6,303)** (+9.7%)	**368** (−34.5%)	**0.0107** (−1.8%)
(b) WebArena					
ReAct	23.89	5.88	50,914 (8,605)	728	0.1152
CodeAct	19.95	10.86	75,962 (24,202)	806	0.1435
AWM$_{offline}$	21.18	5.92	**49,025 (11,748)**	564	**0.1018**
ASI$_{offline}$	24.63	5.71	56,662 (9,247)	603	0.1269
SKILL-DISCO + ReAct	**29.06** (+21.6%)	**5.11** (−13.1%)	51,068 (8,582) (+0.3%)	**561** (−22.9%)	0.1215 (+5.5%)
SKILL-DISCO + CodeAct	22.91 (+14.8%)	8.47 (−22.0%)	85,649 (27,078) (+12.8%)	736 (−8.7%)	0.1606 (+11.9%)

Parenthesized values give relative Δ vs. the matching base agent (ReAct or CodeAct). **Best** and second-best per column highlighted; our rows in **bold**.

Table 6: Per-episode token usage and inference cost on ALFWorld (CodeAct backbone, 134 unseen tasks). "Δ" is the relative change vs. the same model's Vanilla setting (applied to In-Tok.).

Model	In-Tok. (Cached)			Out-Tok.			Cost ($)		
	Vanilla	+Skill	Δ	Vanilla	+Skill	Δ	Vanilla	+Skill	Δ
Qwen3.5-4B	28,010 (24,566)	19,608 (14,505)	−30.0%	2,095	1,391	−33.6%	0.00049	0.00041	−16.3%
Qwen3.5-4B-Thinking	25,687 (22,521)	18,511 (13,742)	−27.9%	2,098	1,436	−31.6%	0.00048	0.00040	−16.7%
Qwen3.5-9B	27,754 (24,939)	10,152 (7,292)	−63.4%	1,382	610	−55.9%	0.00061	0.00036	−41.0%
Qwen3.5-9B-Thinking	29,183 (26,193)	13,768 (10,465)	−52.8%	1,486	844	−43.2%	0.00052	0.00034	−34.6%
GPT-4o	7,721 (6,232)	8,468 (6,303)	+9.7%	562	368	−34.5%	0.01090	0.01067	−2.1%
GPT-4o-mini	17,620 (16,020)	13,686 (11,271)	−22.3%	891	485	−45.6%	0.00102	0.00082	−19.6%
GPT-5-chat	10,606 (8,517)	7,728 (5,496)	−27.1%	677	391	−42.2%	0.01040	0.00739	−28.9%
GPT-5-mini	11,046 (6,979)	8,561 (6,189)	−22.5%	871	492	−43.5%	0.00293	0.00173	−41.0%

```
23  inline `# ...` comments.
24
25  [User]
26  Please convert the following agent
       trace history to Python code:
27  {raw_history}
```

B.2 Stage 2 — Semantic Operation Extraction

Listing 2: Stage 2 prompt.

```
1   [System]
2   You are an expert at analyzing agent
       traces represented as Python code
       .
3   Extract semantic operations: groups
       of consecutive steps that
       together
4   accomplish one coherent sub-goal and
       whose internal relationship can
5   be expressed as control flow (if/for/
       while or fixed sequence).
6   A good operation has clear boundaries
       , locality, and reusability.
7
8   For each operation emit:
9     name         : snake_case verb_noun
10    description  : the sub-goal
11    env_steps    : every (action,
         observation) pair -- prefer the
12                   authoritative env-
                     step log over
                     the code, which
                     may
13                   have dropped actions
                      during
                     conversion
14    code_snippet : the complete code
         block (no truncation)
15    succeeded    : true iff the final
         observation confirms the sub-
         goal
16                   (e.g., "Nothing
                     happens." =>
                     false)
17
18  Output JSON: {"task_summary": "...",
       "operations": [ ... ]}
19
20  [User]
21  ## Code to Analyze
```

Table 7: Full ablation breakdown on ALFWorld (CodeAct + GPT-4o).

Configuration	#Sk	SR (%)	Turns	In-Tok. (Cached)	Out-Tok.	Cost ($)
Vanilla (no skills)	0	96.27	3.63	7,720 (6,231)	561	0.01090
A1: no distill	43	52.99	11.51	107,528 (97,901)	994	0.05849
A2: no compile	0	97.01	3.59	19,083 (17,393)	559	0.01417
Full SKILL-DISCO	5	**99.25**	**3.22**	8,468 (6,302)	368	**0.01067**

```python
22  ```python
23  {trace.code}
24  ```
25  {env_log_section}
26  Please extract all semantic
        operations. The env-step log is
27  authoritative -- group its entries by
        the code's structure but
28  include ALL actions from the log.
```

B.3 Stage 3 — Operation Clustering (Two Passes)

Stage 3 first runs a *grouping pass* over mini-batches that proposes candidate reusable patterns, then a *consolidation pass* that merges overlapping proposals into a minimal cluster set.

Listing 3: Stage 3a prompt – grouping.

```
1   [System]
2   You are identifying reusable
        operation patterns. Partition the
        input
3   operations into non-overlapping
        groups whose members share the
        largest
4   reusable action/observation pattern
        and semantic goal -- transferring
5   across different objects, locations,
        pages, or task instances.
6
7   Rules: use `env_steps` to decide
        membership (not names); ignore
8   incidental differences; split only
        when the action pattern or goal
9   differs; ignore operations that did
        not change state; prefer fewer,
10  larger, uniform groups -- when in
        doubt, MERGE.
11
12  Output JSON: {"groups": [{"group_name
        ", "description",
13  "representative_operations": [{"
        operation_id","name"}]}]}
14
15  [User]
16  ## Operations to Analyze ({len(batch)
        } operations)
17  ```json
18  {json.dumps(batch, indent=2)}
19  ```
```

Listing 4: Stage 3b prompt – consolidation.

```
1   [System]
```

```
2   Merge the candidate operation groups
        into a minimal, non-redundant
3   skill set. Assign every input group `
        index` to exactly one final
4   cluster (no overlap, no missing index
        ).
5
6   Merge groups whose reusable skill,
        goal, or induced state change is
7   similar, even if the wording, objects
        , locations, or appliances
8   differ. Proceed in three steps: (1)
        draft candidate clusters,
9   (2) merge duplicates/overlaps, (3)
        emit the final JSON as the LAST
10  fenced `json` block in your response.
11
12  Output JSON: {"clusters": [{"name", "
        description",
13  "indices": [0,3,7]}, ...]}
14
15  [User]
16  ## Groups to Consolidate ({len(groups
        )} groups)
17  ```json
18  {json.dumps(group_summaries, indent
        =2)}
19  ```
```

B.4 Stage 4 — Skill Contract Definition

Stage 4 turns each cluster into a typed skill contract. The base prompt is built by `build_stage4_prompt(bench_cfg)` and contains two benchmark slots, {action_construction_note} and {action_seq_example}, that are filled per benchmark.

Listing 5: Stage 4 prompt (benchmark slots left as placeholders).

```
1   [System]
2   You design reusable skill APIs for
        LLM agents. Skills are Python
3   functions of the form
4       def skill_name(param1, param2,
        ...):
5   `env` is a global -- never a
        parameter -- and is used as
6       observation, available_actions =
            env.step(action: str)
7   After a skill returns, the caller LLM
        sees ONLY the returned Dict;
8   it must always include at least `
        success`, the latest `observation
```

```
9    and `available_actions`, and a
         process trace of (action,
         observation).
10
11   Design principles: (1) generalize --
         parameterize object names,
12   location lists, and action templates;
         (2) single responsibility --
13   one goal per skill; (3) action
         SELECTION not construction --
14   {action_construction_note}
15   (4) declare every state change in `
         side_effects` and reflect it in
16   `canonical_action_sequence`; (5)
         compose freely -- assume no
17   prerequisite from the caller.
18
19   Output JSON contract:
20     {"skill_name", "description", "
         docstring",
21     "parameters": [{"name","type","
         description","required","
         default"}],
22     "return_type": "Dict",
23     "preconditions", "postconditions",
         "side_effects",
24     "canonical_action_sequence": [
25       "Ordered action templates with
           {param} placeholders.",
26       {action_seq_example}
27       "Derive ONLY from SUCCEEDED
           traces; prefer the
           shortest
28        successful sequence; copy the
           exact action syntax."
29     ],
30     "abstraction_level": "primitive|
         composite|workflow",
31     "estimated_actions_saved": <int>,
         "confidence_score": <float>}
32
33   [User]
34   ## Operation Group
35   - Name / Description / #operations /
         #traces / avg_actions /
36     reusability_score: {cluster fields}
37
38   ## Representative Operations (real
         env.step() patterns)
39   ```json
40   {json.dumps(examples, indent=2)}
41   ```
42   Define a general, reusable skill that
         abstracts this pattern.
```

B.5 Stage 5 — Skill Synthesis

Stage 5 synthesises a self-contained Python implementation from the Stage 4 contract. The base prompt is built by `build_stage5_prompt(bench_cfg)` and contains two benchmark slots, `{first_action_rule}` (how to obtain the first vs. later actions) and `{identifier_note}` (an env-specific gotcha).

Listing 6: Stage 5 prompt (benchmark slots left as placeholders).

```
1    [System]
2    You synthesise the Python body of a
         skill defined by the Stage 4
3    contract. `env` is global; signature
         contains only domain parameters.
4
5    Critical rules:
6    1. Use ONLY `env.step()` and the
         Python stdlib -- no helper
7       functions, no simulation, no
         fabricated observations.
8    2. {first_action_rule}
9    3. Match the trace's action syntax
         exactly; when constructing,
10      reproduce the verb / preposition /
         argument pattern from the
11      reference traces.
12   4. Branch on the LATEST `observation
         `, not on a self-computed flag.
13   5. Honour every parameter; implement
         every step in
14      `canonical_action_sequence` and
         only those plus declared
15      side effects.
16   6. Append every (action, observation)
         pair to `process_trace`.
17   7. Return a Dict including at least `
         success`, latest `observation`,
18      latest `available_actions`, and `
         process_trace` (plus any extra
19      keys the caller needs).
20
21   Environment note: {identifier_note}
22
23   Output JSON: {"implementation": "def
         skill_name(...): \\n  ...",
24              "example_usage": "
                 result = skill_name
                 (...) ..."}
25
26   [User]
27   ## Skill Definition
28   {skill.skill_name / description /
         parameters / pre & postconditions
         }
29
30   ## Representative Code Examples (
         ground truth env.step() patterns)
31   ```json
32   {json.dumps(examples, indent=2)}
33   ```
34   Synthesise the implementation. Select
         actions from
35   `available_actions`, follow the
         code_snippet patterns exactly,
         and
36   return the Dict so the caller can
         continue without blind spots.
```

C Skill Library Examples

We show one representative skill for each benchmark, reproduced verbatim from the final compiled skill catalogs. Listing 7 is the highest-coverage skill in the ALFWorld library: it iterates over a list

of candidate locations, opens any closed containers, and returns as soon as the target item is observed. Listing 8 is a representative WebArena skill that drives the multi-step submission workflow on a Reddit clone (open form → fill URL / title / body → select forum → submit), with every action selected by content-based matching against the live admissible-action set via find_bid(...).

Listing 7: ALFWorld skill: systematic_search_locations.

```python
def systematic_search_locations(
    locations, target):
    """Systematically search through
    a list of locations to find a
    specific target item. The skill
    navigates to each location,
    opens
    it if necessary, and examines its
    contents to locate the
    target.

    Args:
        locations: A list of location
            names to search through.
        target: The name of the item
            to search for.
    """
    process_trace = []
    found_in = None

    for location in locations:
        # Step 1: Go to the location
        action = f"go to {location}"
        observation,
            available_actions = env.
            step(action)
        process_trace.append((action,
            observation))

        # Step 2: Check if the
            location is closed and
            open it if necessary
        if "closed" in observation:
            action = next(
                (a for a in
                    available_actions
                    if "open" in a.lower
                    () and location
                    in a.lower()),
                f"open {location}",
            )
            observation,
                available_actions =
                env.step(action)
            process_trace.append((
                action, observation))

        # Step 3: Inspect the
            contents of the location
        if target in observation:
            found_in = location
            return {
                "success": True,
                "found_in": found_in,
                "observation":
                    observation,
                "available_actions":
                    available_actions
                    ,
                "process_trace":
                    process_trace,
            }

    # If the target is not found in
        any location
    return {
        "success": False,
        "found_in": None,
        "observation": observation,
        "available_actions":
            available_actions,
        "process_trace":
            process_trace,
    }
```

Listing 8: WebArena skill: create_submission_workflow (Reddit site).

```python
def create_submission_workflow(
    title: str,
    body: str,
    forum_name: str,
    url: Optional[str] = None):

    """Complete workflow for creating
        a new submission/post.
        Navigates
    to the submission form, fills in
        required fields (URL if
        present,
    title, body), selects the target
        forum, and submits the form.
    Flow: click Submit -> fill fields
        -> select forum -> click
        Create.

    Args:
        title: Title of the
            submission to post.
        body: Main content/body of
            the submission.
        forum_name: Target forum/
            subreddit label to select
            .
        url: Optional URL to include
            if the form has a URL
            field.
    """
    process_trace = []
    matched_elements = []
    failure_reason = None

    observation = env.step('noop(0)')

    # Step 1: Click "Submit" to open
        the submission form
    submit_bid = find_bid('Submit',
        observation)
    if not submit_bid:
        return {'success': False, '
            observation': observation
            ,
            'process_trace':
                process_trace,
            'matched_elements':
                matched_elements,
```

```
                          'failure_reason': "
                              Submit button not
                              found."}
31    observation = env.step(f"click('{
          submit_bid}')")
32    process_trace.append((f"click('{
          submit_bid}')", observation))
33    matched_elements.append('Submit')
34
35    # Step 2: Optionally fill URL
          field
36    if url:
37        url_bid = find_bid('URL',
              observation)
38        if url_bid:
39            act = f"fill({url_bid!r},
                  {str(url)!r})"
40            observation = env.step(
                  act)
41            process_trace.append((act
                  , observation))
42            matched_elements.append('
                  URL')
43
44    # Step 3: Fill Title field
45    title_bid = find_bid('Title',
          observation)
46    if not title_bid:
47        return {'success': False, '
              observation': observation
              ,
48                'process_trace':
                    process_trace,
49                'matched_elements':
                    matched_elements,
50                'failure_reason': "
                    Title field not
                    found."}
51    act = f"fill({title_bid!r}, {str(
          title)!r})"
52    observation = env.step(act)
53    process_trace.append((act,
          observation))
54    matched_elements.append('Title')
55
56    # Step 4: Open forum-selection
          dropdown and pick the target
          forum
57    combobox_bid = find_bid('Choose
          one', observation) \
58                    or find_bid('Forum
                        ', observation
                        )
59    if not combobox_bid:
60        return {'success': False, '
              observation': observation
              ,
61                'process_trace':
                    process_trace,
62                'matched_elements':
                    matched_elements,
63                'failure_reason': "
                    Forum selection
                    combobox not
                    found."}
64    observation = env.step(f"click('{
          combobox_bid}')")
65    process_trace.append((f"click('{
          combobox_bid}')", observation
          ))

66    forum_bid = find_bid(forum_name,
          observation)
67    if not forum_bid:
68        return {'success': False, '
              observation': observation
              ,
69                'process_trace':
                    process_trace,
70                'matched_elements':
                    matched_elements,
71                'failure_reason': f"
                    Forum '{
                    forum_name}' not
                    found."}
72    observation = env.step(f"click('{
          forum_bid}')")
73    process_trace.append((f"click('{
          forum_bid}')", observation))
74    matched_elements.append(
          forum_name)

76    # Step 5: Fill Body field
77    body_bid = find_bid('Body',
          observation)
78    if not body_bid:
79        return {'success': False, '
              observation': observation
              ,
80                'process_trace':
                    process_trace,
81                'matched_elements':
                    matched_elements,
82                'failure_reason': "
                    Body field not
                    found."}
83    act = f"fill({body_bid!r}, {str(
          body)!r})"
84    observation = env.step(act)
85    process_trace.append((act,
          observation))
86    matched_elements.append('Body')

88    # Step 6: Click "Create
          submission" to finalize
89    create_bid = find_bid('Create
          submission', observation) \
90                    or find_bid('Submit'
                        , observation)
91    if not create_bid:
92        return {'success': False, '
              observation': observation
              ,
93                'process_trace':
                    process_trace,
94                'matched_elements':
                    matched_elements,
95                'failure_reason': "
                    Create-submission
                    button not found
                    ."}
96    observation = env.step(f"click('{
          create_bid}')")
97    process_trace.append((f"click('{
          create_bid}')", observation))
98    matched_elements.append('Create
          submission')

100   success = 'submitted' in
          observation.lower() \
101               or 'created' in
```

```
                        observation.lower()
102         return {
103             'success': success,
104             'observation': observation,
105             'process_trace':
                    process_trace,
106             'matched_elements':
                    matched_elements,
107             'failure_reason': None
108                 if success
109                 else 'No success
                        confirmation detected
                        .',
110         }
```