Decomposed Prompting: Unveiling Multilingual Linguistic Structure Knowledge in English-Centric Large Language Models

Abstract

Despite the predominance of English in their training, English-centric Large Language Models (LLMs) like GPT-3 and LLaMA display a remarkable ability to perform multilingual tasks, raising questions about the depth and nature of their cross-lingual capabilities. This paper introduces a novel *decomposed prompting* approach to probe the linguistic structure understanding of these LLMs within sequence labeling tasks. Diverging from the single text-to-text prompt, our method breaks down the input sentence into individual prompts for each token, seeking its linguistic label. We assess our method on the Universal Dependencies part-of-speech tagging dataset for 38 languages, utilizing both English-centric and multilingual LLMs. Our findings show that *decomposed prompting* surpasses the *iterative prompting* baseline in efficacy and efficiency under zero- and few-shot settings. Further analysis reveals the influence of evaluation methods and instructional prompt use. Our study offers insights into the multilingual transferability of English-centric LLMs, contributing to the understanding of their multilingual linguistic knowledge.

1 Introduction

Current Large Language Models (LLMs), such as GPT-3, GPT-4, PaLM, and LLaMA (Brown et al., 2020; Chowdhery et al., 2023; Touvron et al., 2023a), have demonstrated remarkable capabilities in in-context learning, also known as prompting, across a broad spectrum of language understanding and generation tasks (Zhao et al., 2023; Zhang et al., 2023; Ziyu et al., 2023). These models are predominantly trained on massive amounts of English text data, with limited exposure to other languages. For instance, LLaMA2's pretraining corpus comprises over 89% English content (Touvron et al., 2023b). Yet, these English-centric LLMs [1] still

Figure 1: Comparison of different prompting methods for sequence labeling.

exhibit effective performance in multilingual evaluations (Lai et al., 2023). In a multilingual prompting scenario designed for zero-shot transfer with LLMs, the model executes tasks by directly generating outputs based on a task description and/or a few examples provided in a pivot language (typically English), along with input in another target language (Ahuja et al., 2023). However, the extent and nature of their cross-lingual capabilities remain underexplored (Ye et al., 2023). This raises a critical question: *Does the mutilinguality of these models stem from a deep, generalizable multilingual linguistic understanding, or merely from the superficial alignment of lexical patterns across languages?*

Given the demonstrated proficiency of English-centric LLMs in multilingual tasks that demand profound language understanding (Deng et al., 2023; Wang et al., 2023b), we hypothesize that these models harbor substantial multilingual knowledge.

---

[1] In this paper, we regard a model pretrained primarily on English text as English-centric.

This knowledge, particularly relating to linguistic structure, is commonly conceptualized through sequence tagging tasks (Jurafsky, 2000). However, the current prompting strategies designed for sequence labeling in LLMs exhibit limitations in effectively testing this hypothesis. For instance, behavioral probing methods (Belinkov et al., 2020), aimed at measuring knowledge stored in language models, struggle to adapt to tasks predicting more complex structures. Additionally, text-to-text prompting methods (Asai et al., 2023), which rely on a predefined output template, face challenges in maintaining control over the output format. In response to these challenges, a novel *iterative prompting* strategy for structured prediction has been introduced, addressing the aforementioned limitations (Blevins et al., 2023). Despite its advantages, this method presents its own set of challenges, including inefficiency due to prolonged times in the iterative inference.

To overcome the challenges identified in probing the multilingual knowledge of linguistic structure in LLMs, we introduce a novel approach termed *decomposed prompting*. This approach is designed to probe English-centric LLMs for their understanding of token-level linguistic structure framed as sequence labeling tasks. As shown in Figure 1, instead of employing a single text-to-text prompt for labeling an entire sequence within one step, our method decomposes this process into multiple discrete prompts. More precisely, we first deconstruct the input sentence into tokens. Subsequently, for each token, we formulate an individual prompt that inquires about its linguistic label.

We evaluate our approach on the Universal Dependency (UD) part-of-speech (POS) tagging dataset (Nivre et al., 2020) covering 38 languages with 3 English-centric LLMs and 2 multilingual LLMs. Our approach outperforms the iterative prompting baseline in both zero- and few-shot settings in terms of accuracy and efficiency. We investigate the nuanced impact of evaluation methods and the usage of task instruction within prompts on the performance of decomposed prompting, followed by an empirical comparative study of decomposed and iterative prompting. Moreover, our analysis of multilingual efficacy of English-centric LLMs yields valuable insights into the transferability in multilingual prompting from linguistic perspectives.

2 Background and Related Work

English-Centric LLMs English-centric LLMs are primarily pretrained on large English text data. Despite this focus, these models are also exposed to a limited amount of multilingual data. LLaMA (Touvron et al., 2023a), for example, is pretrained on an extensive scale of corpora comprising over 1.4 trillion tokens, of which less than 4.5% constitutes multilingual data across 20 languages. LLaMA 2 (Touvron et al., 2023b) expands this linguistic diversity, featuring 27 languages each representing more than 0.005% of the pertaining data. Mistral 7B (Jiang et al., 2023), a cutting-edge English-centric LLM, achieves superior performance and efficiency through the adoption of advanced attention techniques such as Sliding Window Attention (SWA) (Child et al., 2019), facilitating faster inference. To enhance the robustness of multilingual processing, the Byte-level Byte-Pair-Encoding (BBPE) algorithm (Sennrich et al., 2016; Wang et al., 2020) is commonly used for tokenization in LLMs. This approach is able to decompose UTF-8 characters, which are outside the scope of the model vocabulary, into their constituent bytes. Consequently, BBPE tokenization equips LLMs with the versatility to handle scripts from any language, theoretically, even those not encountered during training. These two factors—limited exposure to non-English data and byte-level encoding capability—jointly contribute to the robust multilingual abilities observed in English-centric LLMs.

Multilingual LLMs and Instruction Tuning LLMs are typically instruction-tuned models, including multilingual LLMs, as exemplified by models like BLOOMZ (Muennighoff et al., 2023), which is derived from BLOOM (Workshop et al., 2022), and mTk (Wang et al., 2022) which is based on mT5 (Xue et al., 2021). Instruction tuning is a widely utilized method to improve the task understanding and interactivity of LLMs (Zhang et al., 2023). Recent studies have been directed towards augmenting the multilingual capabilities of LLMs by applying the multilingual instruction tuning (Kew et al., 2023; Chen et al., 2023; Shaham et al., 2024). Additionally, there has been a focus on developing multilingual LLMs tailored for specific language clusters, such as SeaLLMs for Southeast Asian Languages (Nguyen et al., 2023). In this work, we utilize instruction-tuned English-centric and multilingual LLMs for our experiments.

Prompting for Sequence Labeling Prompting methods are infrequently applied to sequence labeling tasks. However, some studies have explored the use of prompt-based fine-tuning to address these tasks. Cui et al. (2021) have implemented template-based prompting techniques with the BART model for Named Entity Recognition (NER) tasks. Ma et al. (2022) introduced a template-free prompting strategy for few-shot NER, termed entity-oriented LM fine-tuning. Similar to our approach, Ma et al. (2024) utilized a decomposition-based prompting method to fine-tune multilingual encoder models for cross-lingual sequence labeling. Contrary to these studies, which all operate within a fine-tuning framework, our research is distinctively focused on facilitating multilingual in-context learning in LLMs without the necessity for parameter updates. Prompting LLMs for sequence labeling tasks remains a challenge (Ahuja et al., 2023). While text-to-text prompting is widely adopted across various benchmarking tasks for LLMs (Lai et al., 2023), their application to sequence labeling is hindered by the intricate requirements of output templates (Asai et al., 2023), which may not accurately capture the full capabilities of LLMs. Iterative structured promoting, specifically designed for sequence labeling, has been introduced recently (Blevins et al., 2023). In this approach, at each step t, the model decodes a label for the word at position t in the sequence. This predicted label, along with the next word, is then input back into the model to predict the next label. The dependency of each token's prediction on the preceding one substantially slows down the inference process. In contrast, our proposed decomposed prompting method offers improvements in both efficacy and efficiency.

3 Decomposed Prompting for LLMs

In this study, we introduce a novel approach for conducting sequence labeling with LLMs through in-context learning, termed *decomposed prompting*.

3.1 Intuition

This method draws inspiration from the step-by-step thinking process humans employ when annotating linguistic features within a sentence. Typically, humans approach such tasks incrementally, addressing each token individually. Mirroring this intuitive strategy, our method first decomposes an input sentence into tokens. Subsequently, we generate a distinct prompt for each token, thereby transforming the sequence labeling task into a series of focused, manageable prompts.

Figure 2: An example of how *decomposed prompting* is implemented for sequence labeling.

3.2 Problem Formulation

Given a test sequence set $\mathcal{X}_{test}$, a label set L, and an LLM M, we approach the task of sequence labeling as follows: for an input sequence $X \in \mathcal{X}_{test}$ of length n, $X = x_1, \cdots, x_n$, the model M is expected to produce a corresponding sequence of labels $\hat{Y} = \hat{y}_1, \cdots, \hat{y}_n$, where each label $\hat{y}_i \in L$ is associated with the linguistic feature of the token x_i.

$T(X, x_i) =$ "Sentence: X. In the sentence, the part-of-speech tag of 'x_i' is a kind of"

$T(X, x_i, y_i) =$ "Sentence: X. In the sentence, the part-of-speech tag of 'x_i' is a kind of y_i."

In decomposed prompting, we design a prompt template function $T(\cdot)$ that crafts a specific prompt for each token. The function T accepts the entire input sequence X and an individual token x_i to formulate a prompt aimed at making a prediction. The true label y_i can be optionally included as an argument to T; if included, T utilizes y_i to provide a demonstration. An example of such a template function is illustrated above. $C = c_1, \cdots, c_m$ is a sample from the training set. For a few-shot learning scenario, k examples in the tuple format of (C_j, c_j, l_j) are given along with the input sequence X as well, where c_j is a token in C_j, and $l_j \in L$ the label for c_j. The demonstration D of a input

sequence X is formulated as:

$$D = I \circ T(C_1, c_1, l_1) \circ \cdots \circ T(C_k, c_k, l_k) \quad (1)$$

where I denotes an optional instruction in natural language, $\circ$ denotes the string concatenation operation. Finally, we use a prompt generator function $G(\cdot)$ to generate the set of decomposed prompts for an input sequence X:

$$G(X, D) = \{D \circ T(X, x_1), \cdots, D \circ T(X, x_m)\} \quad (2)$$

The predicted label $\hat{y}_i$ of token x_i can then be calculated by

$$\hat{y}_i = \operatorname*{argmax}_{y \in L} P_M(l | D \circ T(X, x_i)) \quad (3)$$

We derive the probability distribution of the next token prediction over the label set and select the label with the highest probability as the predicted label.

Figure 2 illustrates the generation of prompts for an input sentence for sequence labeling through the implementation of *decomposed prompting*.

4 Experimental Setup

4.1 Datasets and Languages

In our study, we focus on evaluating the multilingual linguistic structure knowledge of English-centric models through the multilingual part-of-speech tagging tasks, employing our proposed decomposed prompting method. We utilize a subset of the Universal Dependency treebanks (UD-POS) (Nivre et al., 2020) for this purpose. The UDPOS dataset adopts a universal POS tag set consisting of 17 tags (Appendix A.1). Our chosen subset, derived from the XTREME multilingual benchmark (Hu et al., 2020), comprises 38 languages with diverse language family distributions (Appendix A.2). Due to computational constraints, we randomly sample 200 instances from test sets for languages containing over 200 samples used for evaluation.

4.2 Models

To investigate the variances in multilingual understanding across LLMs varying in their degree of multilinguality and base capabilities, our study select a diversity array of LLMs, including three English-centric LLMs and two multilingual LLMs. All LLMs in this experiment are instruction-tuned versions accessible through the HuggingFace framework (Wolf et al., 2020).

English-centric LLMs **LLaMA2** represents an advanced iteration of the LLaMA foundation models developed by Meta AI (Touvron et al., 2023a,b), trained on publicly available corpus predominantly in English. We consider two sizes of the LLaMA2 model: the 7B and 13B versions, in our experiments. **Mistral 7B** (Jiang et al., 2023) enhances LLaMA series models in terms of both performance and inference efficiency, achieved through meticulous engineering in language model design and training. For our experiments, we utilize the instruction-tuned version of Mistral 7B, which has been fine-tuned on the OpenHermes 2.5 dataset [2].

Multilingual LLMs **BLOOMZ** (Muennighoff et al., 2023) is a multi-task fine-tuned variant of the BLOOM model (Workshop et al., 2022), which is trained on 46 languages. We employ its 7B version in our experiment. **mTk-Instruct** (Wang et al., 2022) is a multilingual encoder-decoder model, fine-tuned on instruction-following datasets. It is built upon the mT5 model (Xue et al., 2021), which is pretrained on the corpora of over 100 languages. It comprises approximately 13 billion parameters.

4.3 Baselines and Settings

Iterative Prompting (*Iter*) Blevins et al. (2023) introduced a structured prompting approach that *iteratively* labels an entire sentence by appending each predicted label to the context along with the subsequent word Figure 1. This method is employed as a strong baseline in our study.

Decomposed Prompting (*Decom*) To assess our proposed approach, we employ the prompt template outlined in §3.2 to decompose the entire sequence into a set of individual prompts for prediction. In our experiments, we use the 17 POS tags themselves as the label words, i.e., we expect the model to directly generate the tags as shown in Appendix A.1 by selecting the one with the highest logit.

Zero- and Few-Shot Prompting We devised two experimental scenarios for multilingual prompting—zero-shot and few-shot—to evaluate the performance of both baselines under different conditions. In the zero-shot setting, only an English *task instruction* is provided alongside the input in the target language. The text in Appendix A.1, which outlines the tag set information, serves as

---

[2] https://huggingface.co/datasets/teknium/OpenHermes-2.5

	Zero-shot		Few-shot		Avg.
	en	**mult.**	**en**	**mult.**	
LLaMA2-7B					
Iter (prob.)	33.1	27.2	68.0	48.6	44.2
Decom (prob.)	**58.2**	**43.2**	**74.7**	**50.5**	**56.7**
Decom (gen.)	53.8	40.4	62.1	45.8	50.5
LLaMA2-13B					
Iter (prob.)	47.6	37.4	68.0	52.6	51.4
Decom (prob.)	**67.3**	**54.7**	**77.3**	**54.5**	**63.5**
Decom (gen.)	59.2	48.7	65.3	48.3	55.4
Mistral-7B					
Iter (prob.)	**65.2**	54.3	80.2	58.9	64.7
Decom (prob.)	63.6	**61.8**	**85.0**	**64.4**	**68.7**
Decom (gen.)	45.3	48.7	81.4	63.0	59.6

Table 1: Overall results of iterative and decomposed prompting methods on POS tagging tasks in zero- and few-shot settings, with F1 score reported. *prob.* denotes probability-based evaluation, while *gen.* signifies generation-based evaluation. **en** indicates the results for English, and **mult.** represents the average F1 score across other 37 languages. The best performance in each setting is highlighted in **bold**.

the instruction in our experiments. In few-shot prompting, we supplement the prompt with a few English demonstrations, structured according to the prompt template of each baseline method. For the *Decom* baseline, we randomly select an example for each tag type from the English training set to create a demonstration. For a fair comparison, the same number of demonstrations are used for the *Iter* baseline. Refer to Appendix B for the details of prompts used in the experiments.

Evaluation Methods We contrast two evaluation methodologies for prompting in our experiments. *Probability-based* method leverages the model's output logits to retrieve the probability distribution over the tag set, subsequently identifying the label with the highest probability. In case the label word is tokenized into subtokens, we use the first subtoken to serve as the label word, following previous work (Zhao et al., 2021; Wang et al., 2023a). *Generation-based* method directly compares the content generated by the LLM with the gold label.

In our work, we present F1 score as the metric of evaluation. All experiments were conducted on a server equipped with 4 A100-SXM4-80GB GPUs.

5 Results and Analysis

We evaluate the performance of iterative and decomposed prompting for POS tag labeling tasks in both English and multilingual languages under zero- and few-shot settings. Our goal is (1) to validate the benefits of decomposed prompting by comparison with the baseline method (§5), and (2) to explore the extent to which decomposed prompting can capture multilingual linguistic structure knowledge from the English-centric LLMs (§6).

	BLOOMZ	LLaMA2	Mistral	Avg.
zero-shot	3.2×	2.5×	1.4×	2.4×
few-shot	9.2×	7.9×	3.1×	6.7×

Table 2: The ratio by which the inference is accelerated for *Decom* promoting compared to *Iter* prompting.

5.1 Main Findings

The overall results for English-centric LLMs, as detailed in Table 1, demonstrate that our proposed decomposed prompting obviously outperforms the iterative prompting baseline across both zero- and few-shot settings, in both English and multilingual evaluations. This trend holds true for all three English-centric models tested, with the sole exception in the zero-shot setting for the English evaluation with the Mistral-7B model, where *Decom* slightly lags behind *Iter*. (63.6 vs. 65.2). In addition to superior performance, decomposed prompting offers enhanced efficiency during inference, especially under the few-shot prompting. As demonstrated in Table 2, our proposed method achieves, on average, a 2.4-fold increase in speed compared to the baseline in the zero-shot prompting setting and a 6.7-fold increase in the few-shot setting. The efficiency advantage is less obvious with Mistral, owing to Mistral's implementation of a modified attention mechanism designed to enhance inference efficiency.

5.2 Ablation Study

Figure 3 presents the outcomes of our ablation study, which investigates two significant factors: evaluation methods and the role of instructional prompts within various model architectures and experimental settings.

Probability-Based vs. Generation-Based In the context of method evaluation, we observe from Figure 3(a) that across both the 7B and 13B versions of LLaMA2, as well as the Mistral-7B model, the probability-based approach consistently outperforms the generation-based method. This trend is evident in both the English and multilingual tasks,

(a) Effect of evaluation type

(b) Effect of instruction

Figure 3: Results from the ablation study examing the impact of generation-based evaluation method and the inclusion of instruction in prompts across various models and settings. "w/o" denotes the absence of instruction, while "w." signifies the usage of instruction.

under zero-shot and few-shot conditions. Generally, the performance in few-shot conditions is better than in zero-shot conditions. Notably, in the Mistral-7B model, the gap between the probability-based and generation-based methods narrows in the few-shot condition.

Effect of Instruction Figure 3(b) shows that the inclusion of instruction in prompts has a variable impact across different models and evaluation methods. In probability-based evaluation, the presence of instruction leads to a noticeable decrease in F1 scores for all models in both English and multilingual tasks. In generation-based evaluation, there is also some performance decrease in most cases. This suggests that the LLMs might understand the linguistic structure task better from the demonstrations than task descriptions in natural language.

5.3 Case Study

The case study presented in Table 3 offers a revealing comparative analysis of the iterative and decom-

posed prompting methods, using selected German examples processed with the Mistral model.

Case 1
Input: Die Lage mitten im Niederdorf , wo Abends am meisten los ist , ist wirklich sensationel .
Gloss: the location middle in Niederdorf , where evenings at most happening is , is really sensational .
True: DET NOUN ADV ADP PROPN PUNCT ADV ADV ADP PRON ADV VERB PUNCT AUX ADV ADJ PUNCT
Iter: DET NOUN ADV ADP PROPN PUNCT PRON PROPN ADP ADP NOUN AUX PUNCT VERB ADP ADJ PUNCT
Decom: DET NOUN ADV ADP PROPN PUNCT ADV PROPN ADP ADP ADV VERB PUNCT PRON ADP ADJ PUNCT

Case 2
Input: Damit bestätigten die beiden Konzerne Gerüchte , die seit gestern weltweit die Börsianer in Unruhe versetzten .
Gloss: thus confirmed the both corporations rumors , which since yesterday worldwide the stock-participants in unrest put .
True: ADV VERB DET ADJ NOUN NOUN PUNCT PRON ADP ADV ADJ DET NOUN ADP NOUN VERB PUNCT
Iter: ADP VERB PRON ADJ PROPN NOUN PUNCT PRON ADP ADP ADP PRON PROPN ADP NOUN VERB PUNCT
Decom: ADV VERB PRON PRON NOUN NOUN PUNCT PRON ADP ADV ADV PRON NOUN ADP NOUN VERB PUNCT

Table 3: Comparative analysis of the outputs from *iterative* and *decomposed* prompting methods using selected German examples (**de**) with Mistral. Key tokens and tags are highlighted in red.

In Case 1, we observe the cascading effect of error propagation in the iterative prompting method. The iterative approach incorrectly tags the word "los" as a noun, which subsequently appears to affect the tagging of "ist" as an auxiliary verb rather than the correct tag (VERB), as the tag of copula verb "ist" depends on the constituent linked to it. This illustrates a fundamental weakness of the iterative method: a single misprediction can adversely influence subsequent predictions, potentially leading to a series of compounded errors.

Case 2 reveals a limitation inherent to the decomposed prompting, specifically when a single word appears multiple times within a sentence with varying syntactic functions. Take the word "die" in the given case as an example. This word alternates between a definite article and a relative pronoun. The current design of decomposed prompting lacks the sophistication to discern the distinct grammatical roles that a recurring word can play, consequently assigning the tag PRON for all instances of "die". Notably, iterative prompting does not resolve this issue in the given example either. This observation underscores the challenge of developing a prompting mechanism capable of context-sensitive discrimination, an area where both decomposed and iterative prompting methods are yet to evolve.

6 Multilinguality Investigation

6.1 Multilingual Performance

Figure 4 provides a stratified view of decomposed prompting performance, segmented by language family and script, under both zero- and few-shot settings on the Mistral model. The results indicate that Indo-European languages generally achieve higher F1 scores compared to their non-Indo-European counterparts. Notably, the presence of few-shot

(a) Language Family

(b) Script

Figure 4: Analysis of decomposed promoting performance grouped by language family (a) and script type (b) under zero- and few-shot settings on Mistral. "IE" refers to the Indo-European language family. "L" (Low) represents languages that constitute less than 0.005% of the pertaining corpus, while "H" (High) denotes all other languages.

examples consistently improves the overall performance across all categories, but the box plot also indicates some languages are negatively impacted by the use of English demonstrations. As discussed in §2, English-centric LLMs are adept at tokenizing words from Latin or Cyrillic scripts into subtokens. In contrast, for scripts less familiar to these models, they often default to breaking down the text into UTF-8 encodings, which may lead to suboptimal representations for languages using these less common scripts. Thus, to capture a more nuanced understanding of LLM performance across linguistic varieties, we categorize languages not only by family but also by script type. Figure 4(b) illustrates that, in both few-shot and zero-shot settings, languages with known scripts tend to yield better performance than unknown scripts. An exception to this trend is observed among the language group with smaller corpora in the zero-shot setting.

(a) Few-shot

(b) Performance Difference between few- and zero-shot

Figure 5: Panorama of Mistral model's per-language performance. Each node symbolizes a distinct language. (a) shows the few-shot performance and (b) shows the difference between few- and zero-shot performance for each language.

To further understand the impact of English demonstrations on languages with varied properties in multilingual prompting, we delve deeper into the cross-lingual transferability of English-centric LLMs and conduct a detailed analysis of individual language performance. We begin by quantifying the linguistic proximity of each tested language to English. This was achieved by calculating the cosine similarity between language vectors that incorporate syntactic, phylogenetic, and geographic attributes, among others (Littell et al., 2017), following Nie et al. (2023) and Ma et al. (2023). Further information on the computation of language similarity is available in Appendix A.3. From Figure 5, we observe that the performance gain from few-shot prompting is more substantial for languages that are linguistically closer to English, as indicated by the upward trend on the right side of the plot. Remarkably, languages distant from English may even experience a decline in performance when using English demonstrations.

6.2 English-Centric vs. Multilingual LLMs

	Zero-shot		Few-shot		Avg.
	en	mult.	en	mult.	
LLaMA2-7B	58.2	43.2	74.7	50.5	56.7
BLOOMZ-7B	20.6	17.6	44.1	36.2	29.6
LLaMA2-13B	59.2	48.7	65.3	48.3	55.4
mTk-13B	47.6	43.1	57.3	44.7	48.2

Table 4: Performance Comparison of English-Centric and Multilingual LLMs. The results of 7B model group are from settings *Decom+prob.*, while the results of 13B model group are from settings *Decom+gen.*

Table 4[3] shows that English-centric LLMs outperform their multilingual counterparts of comparable size by a considerable margin. This superiority, however, is primarily attributed to their proficiency with English linguistic structures knowledge. For languages distant to English and hardly encountered by the English-centric LLMs, such as el,ta,te,yo, BLOOMZ and mTk surpass their English-centric counterparts, with mTk exhibiting enhanced performance across as many as 11 linguistically distant languages. Full results are provided in Appendix C. The observations suggest that multilingual LLMs may possess more robust cross-lingual transferability, but are constrained by their inherent base capabilities.

7 Discussion

Access to LLM Internal Representations Our ablation study empirically proves that the probability-based evaluation method more accurately reflects the multilingual understanding ability of LLMs compared to the generation-based method, which merely relies on the output text. This method's efficacy, however, hinges on the availability of model output logits, a requirement readily met by open-source LLMs. This accessibility to LLMs' internal representations lays the groundwork for intriguing research avenues, for instance, the interpretability of LLM behavior (Saha et al., 2023) and the application of LLMs for Bayesian inference (Li et al., 2023). Hu and Levy (2023) have underscored the irreplaceability of direct probability measurement in the context of prompting studies. To foster a more transparent

and collaborative research environment, more open access to the internal workings of LLMs is essential.

LLM's Path to Multilinguality This work analyzed the nuances of multilingual performance across different types of LLMs. The exploration of the multilinguality in English-centric LLMs holds significant practical values, particularly when encountering scenarios that demand a model equipped with robust multilingual skills for tasks like reasoning and commonsense understanding. This investigation is pivotal in guiding the decision-making process regarding the foundational model selection for such tasks. The critical question is whether it is more advantageous to commence with an English-centric LLM, which may offer superior understanding abilities in English, and then endeavor to extend these capabilities to additional languages, or to opt for a multilingual LLM that boasts broader language coverage and enhanced multilingual transferability, albeit potentially at the expense of more refined English understanding abilities. Our work sheds light on the importance of careful consideration of the trade-offs between linguistic breadth and depth of language understanding.

8 Conclusion

In conclusion, our investigation into the multilingual capabilities of English-centric LLMs through the lens of decomposed prompting has yielded significant findings. By systematically dissecting the sequence labeling process into discrete, token-level prompts, we have demonstrated that these models possess a considerable understanding of linguistic structure that extends beyond their predominant English training. Our method outperforms existing iterative prompting techniques in both zero- and few-shot settings, highlighting the efficiency and accuracy of decomposed prompting. The empirical evidence suggests that while English-centric LLMs can effectively engage in multilingual tasks, their performance is nuanced and influenced by the linguistic proximity to English and the design of the prompting strategy. This work not only advances the field of NLP by enhancing our understanding of LLMs' cross-lingual transfer capabilities but also opens avenues for future research to further improve the inclusivity and adaptability of language models for a diverse range of languages and tasks.

---

[3]As an LLM of encoder-decoder structure, mTk is not amenable to direct application of our *prob.* evaluation designed for decoder-only models; thus, we resort to *gen.* instead.

Limitations

As discussed in the analysis part, our proposed *decomposed prompting* struggle with multi-label words occurring several times in a sentence. Besides, the efficiency of decomposed prompting might be challenged as the length of the input sequence and the complexity of the task increase. Our study focuses on utilizing decomposed prompting methods for the part-of-speech (POS) tagging task as a means to evaluate the multilingual structural knowledge of English-centric Large Language Models (LLMs). This provides a foundational assessment of the models' capabilities. Nevertheless, the scope for extending this methodology to probe more intricate aspects of linguistic structure is substantial. Future research could beneficially apply decomposed prompting to the analysis of complex linguistic phenomena, including sentence chunking and syntactic parsing, to gain a deeper understanding of the nuanced capabilities of LLMs in processing and understanding language.

References

Kabir Ahuja, Harshita Diddee, Rishav Hada, Millicent Ochieng, Krithika Ramesh, Prachi Jain, Akshay Nambi, Tanuja Ganu, Sameer Segal, Mohamed Ahmed, Kalika Bali, and Sunayana Sitaram. 2023. MEGA: Multilingual evaluation of generative AI. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4232–4267, Singapore. Association for Computational Linguistics.

Akari Asai, Sneha Kudugunta, Xinyan Velocity Yu, Terra Blevins, Hila Gonen, Machel Reid, Yulia Tsvetkov, Sebastian Ruder, and Hannaneh Hajishirzi. 2023. Buffet: Benchmarking large language models for few-shot cross-lingual transfer. *arXiv preprint arXiv:2305.14857*.

Yonatan Belinkov, Sebastian Gehrmann, and Ellie Pavlick. 2020. Interpretability and analysis in neural NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: Tutorial Abstracts*, pages 1–5, Online. Association for Computational Linguistics.

Terra Blevins, Hila Gonen, and Luke Zettlemoyer. 2023. Prompting language models for linguistic structure. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6649–6663, Toronto, Canada. Association for Computational Linguistics.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Pinzhen Chen, Shaoxiong Ji, Nikolay Bogoychev, Barry Haddow, and Kenneth Heafield. 2023. Monolingual or multilingual instruction tuning: Which makes a better alpaca. *arXiv preprint arXiv:2309.08958*.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. 2019. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113.

Leyang Cui, Yu Wu, Jian Liu, Sen Yang, and Yue Zhang. 2021. Template-based named entity recognition using BART. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 1835–1845, Online. Association for Computational Linguistics.

Yue Deng, Wenxuan Zhang, Sinno Jialin Pan, and Lidong Bing. 2023. Multilingual jailbreak challenges in large language models. *arXiv preprint arXiv:2310.06474*.

Jennifer Hu and Roger Levy. 2023. Prompting is not a substitute for probability measurements in large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5040–5060, Singapore. Association for Computational Linguistics.

Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. 2020. Xtreme: A massively multilingual multi-task benchmark for evaluating cross-lingual generalisation. In *International Conference on Machine Learning*, pages 4411–4421. PMLR.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.

Dan Jurafsky. 2000. *Speech & language processing*. Pearson Education India.

Tannon Kew, Florian Schottmann, and Rico Sennrich. 2023. Turning english-centric llms into polyglots: How much multilinguality is needed? *arXiv preprint arXiv:2312.12683*.

Viet Lai, Nghia Ngo, Amir Pouran Ben Veyseh, Hieu Man, Franck Dernoncourt, Trung Bui, and Thien Nguyen. 2023. ChatGPT beyond English: Towards a comprehensive evaluation of large language models in multilingual learning. In *Findings of the Association for Computational Linguistics: EMNLP*

2023, pages 13171–13189, Singapore. Association for Computational Linguistics.

Belinda Z Li, William Chen, Pratyusha Sharma, and Jacob Andreas. 2023. Lampp: Language models as probabilistic priors for perception and action. *arXiv e-prints*, pages arXiv–2302.

Patrick Littell, David R. Mortensen, Ke Lin, Katherine Kairis, Carlisle Turner, and Lori Levin. 2017. URIEL and lang2vec: Representing languages as typological, geographical, and phylogenetic vectors. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 8–14, Valencia, Spain. Association for Computational Linguistics.

Bolei Ma, Ercong Nie, Helmut Schmid, and Hinrich Schütze. 2023. Is prompt-based finetuning always better than vanilla finetuning? insights from cross-lingual language understanding.

Bolei Ma, Ercong Nie, Shuzhou Yuan, Helmut Schmid, Michael Färber, Frauke Kreuter, and Hinrich Schütze. 2024. Topro: Token-level prompt decomposition for cross-lingual sequence labeling tasks. *arXiv preprint arXiv:2401.16589*.

Ruotian Ma, Xin Zhou, Tao Gui, Yiding Tan, Linyang Li, Qi Zhang, and Xuanjing Huang. 2022. Template-free prompt tuning for few-shot NER. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5721–5732, Seattle, United States. Association for Computational Linguistics.

Chaitanya Malaviya, Graham Neubig, and Patrick Littell. 2017. Learning language representations for typology prediction. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 2529–2535, Copenhagen, Denmark. Association for Computational Linguistics.

Niklas Muennighoff, Thomas Wang, Lintang Sutawika, Adam Roberts, Stella Biderman, Teven Le Scao, M Saiful Bari, Sheng Shen, Zheng Xin Yong, Hailey Schoelkopf, Xiangru Tang, Dragomir Radev, Alham Fikri Aji, Khalid Almubarak, Samuel Albanie, Zaid Alyafeai, Albert Webson, Edward Raff, and Colin Raffel. 2023. Crosslingual generalization through multitask finetuning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15991–16111, Toronto, Canada. Association for Computational Linguistics.

Xuan-Phi Nguyen, Wenxuan Zhang, Xin Li, Mahani Aljunied, Qingyu Tan, Liying Cheng, Guanzheng Chen, Yue Deng, Sen Yang, Chaoqun Liu, et al. 2023. Seallms–large language models for southeast asia. *arXiv preprint arXiv:2312.00738*.

Ercong Nie, Sheng Liang, Helmut Schmid, and Hinrich Schütze. 2023. Cross-lingual retrieval augmented prompt for low-resource languages. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 8320–8340, Toronto, Canada. Association for Computational Linguistics.

Joakim Nivre, Marie-Catherine de Marneffe, Filip Ginter, Jan Hajič, Christopher D. Manning, Sampo Pyysalo, Sebastian Schuster, Francis Tyers, and Daniel Zeman. 2020. Universal Dependencies v2: An evergrowing multilingual treebank collection. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 4034–4043, Marseille, France. European Language Resources Association.

Tulika Saha, Debasis Ganguly, Sriparna Saha, and Prasenjit Mitra. 2023. Workshop on large language models' interpretability and trustworthiness (llmit). In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 5290–5293.

Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.

Uri Shaham, Jonathan Herzig, Roee Aharoni, Idan Szpektor, Reut Tsarfaty, and Matan Eyal. 2024. Multilingual instruction tuning with just a pinch of multilinguality. *arXiv preprint arXiv:2401.01854*.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Changhan Wang, Kyunghyun Cho, and Jiatao Gu. 2020. Neural machine translation with byte-level subwords.

Lean Wang, Lei Li, Damai Dai, Deli Chen, Hao Zhou, Fandong Meng, Jie Zhou, and Xu Sun. 2023a. Label words are anchors: An information flow perspective for understanding in-context learning. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9840–9855, Singapore. Association for Computational Linguistics.

Wenxuan Wang, Zhaopeng Tu, Chang Chen, Youliang Yuan, Jen-tse Huang, Wenxiang Jiao, and Michael R Lyu. 2023b. All languages matter: On the multilingual safety of large language models. *arXiv preprint arXiv:2310.00905*.

Yizhong Wang, Swaroop Mishra, Pegah Alipoormolabashi, Yeganeh Kordi, Amirreza Mirzaei, Atharva Naik, Arjun Ashok, Arut Selvan Dhanasekaran, Anjana Arunkumar, David Stap, Eshaan Pathak, Giannis Karamanolakis, Haizhi Lai, Ishan Purohit, Ishani Mondal, Jacob Anderson, Kirby Kuznia, Krima Doshi, Kuntal Kumar Pal, Maitreya Patel, Mehrad Moradshahi, Mihir Parmar, Mirali Purohit, Neeraj Varshney, Phani Rohitha Kaza, Pulkit Verma, Ravsehaj Singh Puri, Rushang Karia, Savan Doshi, Shailaja Keyur Sampat, Siddhartha Mishra, Sujan Reddy A, Sumanta Patro, Tanay Dixit, and Xudong Shen. 2022. Super-NaturalInstructions: Generalization via declarative instructions on 1600+ NLP tasks. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 5085–5109, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

BigScience Workshop, Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, et al. 2022. Bloom: A 176b-parameter open-access multilingual language model. *arXiv preprint arXiv:2211.05100*.

Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2021. mT5: A massively multilingual pre-trained text-to-text transformer. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 483–498, Online. Association for Computational Linguistics.

Jiacheng Ye, Xijia Tao, and Lingpeng Kong. 2023. Language versatilists vs. specialists: An empirical revisiting on multilingual transfer ability. *arXiv preprint arXiv:2306.06688*.

Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, et al. 2023. Instruction tuning for large language models: A survey. *arXiv preprint arXiv:2308.10792*.

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. *arXiv preprint arXiv:2303.18223*.

Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. 2021. Calibrate before use: Improving few-shot performance of language models. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 12697–12706. PMLR.

Zhuang Ziyu, Chen Qiguang, Ma Longxuan, Li Mingda, Han Yi, Qian Yushan, Bai Haopeng, Zhang Weinan, and Ting Liu. 2023. Through the lens of core competency: Survey on evaluation of large language models. In *Proceedings of the 22nd Chinese National Conference on Computational Linguistics (Volume 2: Frontier Forum)*, pages 88–109, Harbin, China. Chinese Information Processing Society of China.

A Dataset and Languages

A.1 POS Tag Set

Figure 6 shows the pos tag set in UD. We also use the text in the box as the task instruction in our experiments.

```
POS tag set: ADJ ADP ADV AUX CCONJ DET INTJ NOUN
NUM PART PRON PROPN PUNCT SCONJ SYM VERB X
```

Figure 6: UD POS tag set.

A.2 Profile of Languages

As Figure 7 shows, our experiment involves 38 languages with diverse language family distributions.

Figure 7: Distribution of languages by language family in the dataset.

A.3 Language Similarity Computation

Malaviya et al. (2017) and Littell et al. (2017) proposed LANG2VEC, language vectors to represent various linguistic features for languages. A language can be represented by five vectors, containing syntactic, phonological, phonetic, phylogenetic,

and geographical features, respectively. Linguistic similarities among different languages with respect to these linguistic features can be calculated through the cosine similarity. In our study, we utilized the language vectors provided by LANG2VEC to calculate the cosine similarity between target languages and English. We used a rank-based similarity score to average the rank of languages in each feature dimension. Table 5 illustrates the computation details.

B Prompt Details

Zero- and few-shot prompts used in this wor are shown in Figure 8 (decomposed prompting) and Figure 9 (iterative prompting).

C Full Results

Full experimental results are displayed in Table 6 (Mistral 7B), Table 7 (LLaMA2 7B), Table 8 (LLaMA 13B), Table 9 (BLOOMZ 7B), and Table 10 (mTk 13B).

	syn.	syn_rank	pho.	pho_rank	inv.	inv_rank	fam.	fam_rank	geo.	geo_rank	rank_score
eng-nld	92.43	37	81.83	18	76.28	36	44.51	35	99.96	37	32.6
eng-deu	90.26	36	80.60	15	78.68	37	54.49	37	99.76	35	32.0
eng-ukr	84.73	32	85.83	32	74.91	33	15.03	30	99.28	26	30.6
eng-por	84.24	31	90.46	35	74.03	28	10.14	22	99.68	33	29.8
eng-ell	78.31	25	95.35	37	74.74	32	15.03	32	98.96	22	29.6
eng-pol	78.64	26	85.83	29	74.09	29	15.03	31	99.63	32	29.4
eng-bul	85.78	35	85.83	30	74.38	30	13.73	27	99.01	23	29.0
eng-ita	85.78	34	85.83	28	72.94	26	11.21	23	99.53	30	28.2
eng-rus	81.18	29	85.83	31	74.63	31	16.80	33	95.81	17	28.2
eng-ron	79.60	27	90.46	34	73.42	27	11.89	24	99.22	25	27.4
eng-spa	82.16	30	85.83	27	72.83	25	9.71	21	99.59	31	26.8
eng-lit	69.33	18	80.42	14	75.58	34	19.39	34	99.44	27	25.4
eng-afr	84.94	33	81.83	17	75.91	35	50.46	36	86.84	6	25.4
eng-fra	81.18	28	75.28	7	72.24	24	9.71	20	99.93	36	23.0
eng-est	77.35	24	85.83	25	70.81	19	0.23	15	99.45	28	22.2
eng-hun	69.40	19	85.83	24	70.66	18	0.33	18	99.46	29	21.6
eng-fin	71.08	21	87.05	33	70.00	17	0.19	13	99.19	24	21.6
eng-eus	62.36	13	85.29	21	70.00	16	3.33	19	99.76	34	20.6
eng-urd	61.63	12	85.83	26	71.98	23	12.71	25	92.54	13	19.8
eng-mar	56.50	8	80.42	13	71.57	22	13.73	28	89.80	11	16.4
eng-wol	63.92	14	85.83	23	69.73	15	0.17	10	96.24	18	16.0
eng-hin	61.63	11	78.35	10	70.91	20	12.71	26	91.10	12	15.8
eng-fas	50.03	3	78.35	11	70.94	21	13.73	29	94.23	14	15.6
eng-ind	72.66	22	90.92	36	67.09	12	0.12	4	79.16	1	15.0
eng-heb	75.15	23	72.55	5	69.10	14	0.13	6	97.16	20	13.6
eng-ara	65.11	16	70.09	3	68.38	13	0.15	9	97.04	19	12.0
eng-tur	50.68	4	81.83	16	67.09	11	0.14	7	98.25	21	11.8
eng-zho	71.08	20	72.55	4	66.94	10	0.33	16	88.42	9	11.8
eng-kaz	44.77	1	83.64	19	66.59	9	0.14	8	95.22	16	10.6
eng-vie	66.04	17	78.35	9	65.81	8	0.19	11	85.25	3	9.6
eng-tel	52.07	6	80.42	12	64.76	4	0.19	14	89.18	10	9.2
eng-tgl	60.89	10	85.83	22	64.76	5	0.13	5	82.15	2	8.8
eng-tam	51.36	5	85.29	20	64.37	3	0.11	3	87.95	8	7.8
eng-kor	55.29	7	74.65	6	63.83	2	0.33	17	86.93	7	7.8
eng-tha	63.95	15	78.35	8	65.40	7	0.11	2	85.25	4	7.2
eng-yor	60.04	9	66.77	2	65.29	6	0.10	1	94.98	15	6.6
eng-jpn	50.03	2	66.77	1	56.88	1	0.19	12	85.65	5	4.2

Table 5: Details of language similarity computation.

Zero-shot prompt

```
POS tag set: ADJ ADP ADV AUX CCONJ DET INTJ NOUN NUM PART PRON PROPN PUNCT SCONJ SYM VERB X
Sentence: Viel Erfolg !
In the sentence, the part-of-speech tag of 'Viel' is a kind of
```

Few-shot prompt (w/o Instruction)

```
Sentence: And if you send me a story , that would be great !
In the sentence, the part-of-speech tag of 'if' is a kind of SCONJ.
Sentence: I 'll admit I was n't expecting much from this place , but they really did do a good job .
In the sentence, the part-of-speech tag of 'good' is a kind of ADJ.
Sentence: I do n't know . The girl shrugged once again . In the sentence, the part-of-speech tag of
'girl' is a kind of NOUN.
Sentence: The dancers were falling back round a Polish agriculturalist who was teaching a gangling
Englishman and two young Africans an Eastern European peasant dance .
In the sentence, the part-of-speech tag of 'around' is a kind of ADP.
Sentence: Antigua was awesome .
In the sentence, the part-of-speech tag of 'was' is a kind of AUX.
Sentence: The food is fresh and taste great .
In the sentence, the part-of-speech tag of 'the' is a kind of DET. Sentence: Now I have wife and son
.
In the sentence, the part-of-speech tag of 'Now' is a kind of ADV.
Sentence: However , this fruitful period was short-lived , as Greece suffered badly under the Ottoman
Empire , only to recover in the 19th century as the capital of independent Greece .
In the sentence, the part-of-speech tag of 'suffered' is a kind of VERB.
Sentence: I survived it without a problem .
In the sentence, the part-of-speech tag of '.' is a kind of PUNCT. Sentence: The food is fresh and
taste great .
In the sentence, the part-of-speech tag of 'and' is a kind of CCONJ.
Sentence: you can view at dresscod.com
In the sentence, the part-of-speech tag of 'dresscod.com' is a kind of X.
Sentence: I do n't know . The girl shrugged once again .
In the sentence, the part-of-speech tag of 'I' is a kind of PRON.
Sentence: I 'll admit I was n't expecting much from this place , but they really did do a good job .
In the sentence, the part-of-speech tag of 'n't' is a kind of PART.
Sentence: Antigua was awesome .
In the sentence, the part-of-speech tag of 'Antigua' is a kind of PROPN.
Sentence: The dancers were falling back round a Polish agriculturalist who was teaching a gangling
Englishman and two young Africans an Eastern European peasant dance .
In the sentence, the part-of-speech tag of 'two' is a kind of NUM. Sentence: Yes , the Cyclone is
almost certain to lose strength as it surges over land .
In the sentence, the part-of-speech tag of 'Yes' is a kind of INTJ.
Sentence: —-== Posted via Newsfeed.Com - Unlimited - Uncensored - Secure Usenet News ==—-
In the sentence, the part-of-speech tag of '—-== ' is a kind of SYM.
Sentence: Viel Erfolg ! In the sentence, the part-of-speech tag of 'Viel' is a kind of
```

Figure 8: Prompt design of decomposed prompting.

Zero-shot prompt

```
POS tag set: ADJ ADP ADV AUX CCONJ DET INTJ NOUN NUM PART PRON PROPN PUNCT SCONJ SYM VERB X
Sentence: Viel Erfolg !
Viel_
```

Few-shot prompt (w/o Instruction)

```
Context: Chahine said her immediate family spent about $ 20,000 to return to Detroit via Syria and
Jordan .
Tagged:  Chahine_PROPN  said_VERB  her_PRON  immediate_ADJ  family_NOUN  spent_VERB  about_ADV  $_SYM
20,000_NUM  to_PART  return_VERB  to_ADP  Detroit_PROPN  via_ADP  Syria_PROPN  and_CCONJ  Jordan_PROPN
._PUNCT
Context: Welcome Darin !
Tagged: Welcome_INTJ Darin_PROPN !_PUNCT
Context: you can view at dresscod.com
Tagged: you_PRON can_AUX view_VERB at_ADP dresscod.com_X
...
Context: They work on Wall Street , after all , so when they hear a company who's stated goals
include " Do n't be evil , " they imagine a company who's eventually history will be " Do n't be
profitable . "
Tagged: They_PRON work_VERB on_ADP Wall_PROPN Street_PROPN ,_PUNCT after_ADV all_ADV ,_PUNCT so_ADV
when_ADV they_PRON hear_VERB a_DET company_NOUN who's_PRON stated_VERB goals_NOUN include_VERB
"_PUNCT Do_AUX n't_PART be_AUX evil_ADJ ,_PUNCT "_PUNCT they_PRON imagine_VERB a_DET company_NOUN
who's_PRON eventually_ADJ history_NOUN will_AUX be_VERB "_PUNCT Do_AUX n't_PART be_AUX profitable_ADJ
._PUNCT "_PUNCT
Context: It 's not quite as freewheeling an environment as you 'd imagine : Sergey Brin has actually
created a mathematical ' proof ' that the company 's self - driven research strategy , which gives
employees one day a week to do research projects on their own , is a good , respectable idea .
Tagged: It_PRON 's_AUX not_PART quite_ADV as_ADV freewheeling_ADJ an_DET environment_NOUN as_SCONJ
you_PRON 'd_AUX imagine_VERB :_PUNCT Sergey_PROPN Brin_PROPN has_AUX actually_ADV created_VERB a_DET
mathematical_ADJ '_PUNCT proof_NOUN '_PUNCT that_SCONJ the_DET company_NOUN 's_PART self_NOUN -_PUNCT
driven_VERB research_NOUN strategy_NOUN ,_PUNCT which_PRON gives_VERB employees_NOUN one_NUM day_NOUN
a_DET week_NOUN to_PART do_VERB research_NOUN projects_NOUN on_ADP their_PRON own_ADJ ,_PUNCT is_AUX
a_DET good_ADJ ,_PUNCT respectable_ADJ idea_NOUN ._PUNCT
Context: Read the entire article ; there 's a punchline , too .
Tagged: Read_VERB the_DET entire_ADJ article_NOUN ;_PUNCT there_PRON 's_VERB a_DET punchline_NOUN
,_PUNCT too_ADV ._PUNCT
Context: My opinion piece on the implications of Arafat 's passing for al - Qaeda has appeared at
Newsday .
Tagged: My_PRON opinion_NOUN piece_NOUN on_ADP the_DET implications_NOUN of_ADP Arafat_PROPN 's_PART
passing_NOUN for_ADP al_PROPN -_PUNCT Qaeda_PROPN has_AUX appeared_VERB at_ADP Newsday_PROPN ._PUNCT
Context: Viel Erfolg ! Tagged: Viel_
```

Figure 9: Prompt design of iterative prompting.

	language	en	af	ar	bg	de	el	es	et	eu	fa	fi	fr	he
zero-shot	Iter	65.2	67.8	57.2	68.6	65.0	55.0	64.8	49.4	35.6	58.3	50.2	65.4	51.5
	Decom (prob.)	63.6	66.0	67.8	74.4	68.6	62.7	68.6	58.0	54.1	68.5	60.2	63.5	66.4
	Decom (gen.)	45.3	43.8	49.6	50.5	49.0	50.7	43.3	53.6	50.7	56.0	55.5	40.5	55.6
few-shot	Iter	80.2	66.4	65.0	77.3	66.9	56.4	70.8	53.7	50.7	57.4	63.9	67.7	66.4
	Decom (prob.)	85.0	76.9	48.1	82.4	78.3	52.3	82.7	65.2	48.8	57.3	64.4	76.9	66.6
	Decom (gen.)	81.4	74.8	44.3	80.4	77.0	46.3	82.0	64.0	48.1	54.1	63.6	76.4	64.9
	Decom (prob.) + I	83.4	77.9	42.4	76.9	77.8	33.6	77.6	64.6	57.4	42.9	67.6	74.8	58.5
	Decom (gen.) + I	78.7	75.8	34.0	74.9	76.6	24.7	76.4	62.6	56.8	34.4	64.5	73.4	54.5

	language	hi	hu	id	it	ja	kk	ko	lt	mr	nl	pl	pt	ro
zero-shot	Iter	61.3	50.6	54.7	64.0	42.2	36.7	39.9	52.8	39.1	60.4	66.5	63.9	66.2
	Decom (prob.)	37.1	58.6	61.0	68.6	56.3	57.8	47.4	68.2	61.0	69.4	73.5	68.4	68.5
	Decom (gen.)	35.6	46.7	41.8	45.1	48.9	50.2	42.2	60.3	56.7	46.8	59.5	43.1	44.6
few-shot	Iter	65.7	50.4	70.0	67.2	42.0	43.8	42.6	63.2	54.4	66.6	70.9	75.1	65.9
	Decom (prob.)	67.8	71.3	73.9	76.2	59.8	50.0	44.0	67.5	48.9	80.6	78.6	77.8	77.8
	Decom (gen.)	66.2	70.8	73.0	76.0	57.1	50.2	43.4	67.1	48.9	77.2	78.3	76.9	77.0
	Decom (prob.) + I	57.6	66.5	70.4	72.2	54.2	58.4	49.2	69.9	53.1	78.5	76.7	75.0	76.4
	Decom (gen.) + I	55.3	63.9	68.2	70.3	53.1	57.9	48.2	69.5	52.7	76.9	75.7	74.2	75.1

	language	ru	ta	te	th	tl	tr	uk	ur	vi	wo	yo	zh	avg.
zero-shot	Iter	68.2	39.2	51.1	54.1	65.0	47.7	67.0	56.0	41.7	31.5	41.3	58.8	54.3
	Decom (prob.)	74.4	55.2	63.8	63.0	62.9	55.2	74.1	54.2	59.9	39.6	49.7	59.2	61.8
	Decom (gen.)	54.7	52.2	57.4	50.1	51.3	43.2	57.4	40.3	45.9	29.2	43.3	55.7	48.7
few-shot	Iter	74.0	52.0	62.4	57.1	37.3	62.0	68.2	59.6	41.0	25.2	39.0	62.3	58.9
	Decom (prob.)	79.9	37.5	61.4	58.2	73.4	62.7	77.7	51.3	52.6	42.0	47.8	65.8	64.4
	Decom (gen.)	78.0	33.9	61.3	56.9	73.4	62.6	76.2	45.7	52.8	42.0	47.6	64.5	63.0
	Decom (prob.) + I	76.8	35.7	67.0	45.8	74.9	63.7	75.1	40.5	59.4	43.1	49.2	62.9	62.3
	Decom (gen.) + I	73.9	28.0	66.6	42.9	74.9	62.6	73.4	32.9	59.7	43.2	48.6	61.4	59.9

Table 6: Full results on Mistral 7b.

	language	en	af	ar	bg	de	el	es	et	eu	fa	fi	fr	he
zero-shot	Iter	33.1	38.8	30.2	33.2	34.5	38.1	38.9	19.7	11.8	17.7	26.0	37.5	21.3
	Decom (prob.)	58.2	45.1	49.6	55.9	53.3	50.4	44.7	37.7	36.4	40.5	41.3	46.8	39.5
	Decom (gen.)	53.8	46.8	38.5	45.8	57.1	54.3	52.4	28.6	20.2	35.9	39.8	53.1	37.5
few-shot	Iter	68.0	56.1	58.0	63.4	56.9	48.7	55.3	46.5	41.3	51.1	50.5	54.2	54.0
	Decom (prob.)	74.7	60.0	29.9	64.7	63.0	30.6	55.7	53.0	44.4	29.7	62.9	54.4	42.8
	Decom (gen.)	62.1	51.0	25.7	60.3	52.4	23.9	50.3	48.3	42.9	26.0	56.8	49.5	37.5
	Decom (prob.) + I	68.2	55.9	23.7	61.6	61.0	20.2	52.5	43.2	40.8	22.7	49.4	54.8	35.4
	Decom (gen.) + I	63.4	53.2	19.0	57.9	56.2	12.0	47.8	39.3	40.0	15.5	46.4	51.2	30.1

	language	hi	hu	id	it	ja	kk	ko	lt	mr	nl	pl	pt	ro
zero-shot	Iter	35.2	29.3	31.1	35.1	28.7	13.6	19.8	24.9	13.2	37.5	37.7	38.4	32.0
	Decom (prob.)	36.9	47.0	46.9	46.7	32.4	39.0	29.0	34.9	45.3	54.9	54.0	48.6	43.6
	Decom (gen.)	34.8	47.4	39.1	45.2	30.9	33.0	33.2	37.7	42.0	51.1	44.1	48.5	42.6
few-shot	Iter	54.0	41.0	51.3	49.6	40.0	43.2	25.0	52.5	50.3	52.2	52.4	52.0	53.8
	Decom (prob.)	45.8	62.6	60.9	56.4	40.2	51.4	48.2	56.3	47.3	58.9	67.2	60.3	63.6
	Decom (gen.)	42.4	57.0	56.5	51.6	34.1	47.5	44.7	51.7	43.5	51.3	64.2	54.5	55.5
	Decom (prob.) + I	30.6	52.3	54.1	51.3	37.3	46.6	41.9	46.5	45.7	64.2	65.4	55.2	56.4
	Decom (gen.) + I	24.1	50.6	49.5	44.1	32.9	46.0	40.7	45.3	34.5	60.2	62.0	51.2	51.8

	language	ru	ta	te	th	tl	tr	uk	ur	vi	wo	yo	zh	avg.
zero-shot	Iter	29.8	19.2	13.8	29.2	28.6	22.2	30.3	20.7	29.7	13.3	13.7	32.2	27.2
	Decom (prob.)	55.8	38.0	34.0	37.5	57.3	48.3	57.4	31.6	39.5	27.6	29.1	42.9	43.2
	Decom (gen.)	48.7	25.5	36.9	34.6	66.3	45.9	48.8	28.4	35.3	18.7	21.8	44.0	40.4
few-shot	Iter	58.2	30.9	54.3	49.4	37.3	34.4	57.7	44.0	46.5	40.7	39.3	52.0	48.6
	Decom (prob.)	67.2	31.7	44.7	36.5	46.8	58.1	62.9	27.1	41.4	39.9	37.1	64.8	50.5
	Decom (gen.)	62.3	25.3	43.5	34.7	45.4	55.9	59.4	23.7	40.7	36.2	35.5	50.9	45.8
	Decom (prob.) + I	59.6	20.3	38.4	20.9	63.1	54.1	59.9	19.3	49.7	32.2	33.8	48.2	45.1
	Decom (gen.) + I	56.9	12.5	34.5	16.7	58.8	52.7	57.5	13.0	47.8	29.7	31.7	44.2	41.0

Table 7: Full results on LLaMA2 7b.

	language	en	af	ar	bg	de	el	es	et	eu	fa	fi	fr	he
zero-shot	Iter	47.6	37.4	43.2	44.5	45.7	38.4	46.8	37.0	26.5	42.0	40.7	45.5	40.0
	Decom (prob.)	67.3	60.1	54.4	62.7	63.6	60.5	55.9	49.9	37.4	59.8	62.6	53.4	55.4
	Decom (gen.)	59.2	54.1	45.0	52.5	57.5	51.3	56.3	37.6	36.7	49.7	50.2	54.7	44.3
few-shot	Iter	68.0	62.3	57.4	69.9	60.3	57.9	66.7	44.8	41.0	49.1	54.2	63.2	59.8
	Decom (prob.)	77.3	67.8	33.2	67.6	67.5	35.0	62.6	58.5	46.9	34.7	62.8	64.8	48.4
	Decom (gen.)	65.3	59.1	25.1	61.3	58.6	24.6	53.5	51.8	45.8	27.4	55.4	55.9	43.9
	Decom (prob.) + I	74.3	67.6	25.9	60.7	70.5	21.5	59.1	51.4	44.1	21.8	59.1	63.1	40.3
	Decom (gen.) + I	68.7	64.4	19.2	58.7	66.2	12.4	53.9	47.9	42.2	15.5	54.0	59.7	35.0

	language	hi	hu	id	it	ja	kk	ko	lt	mr	nl	pl	pt	ro
zero-shot	Iter	45.0	38.8	40.9	41.8	42.8	24.1	29.8	41.2	30.5	36.6	42.2	43.3	43.1
	Decom (prob.)	53.8	57.6	57.4	54.8	48.3	51.8	45.1	54.3	50.2	62.0	66.4	56.6	57.9
	Decom (gen.)	45.4	47.9	48.2	51.3	35.9	48.7	35.3	43.2	48.7	56.9	58.2	51.3	51.4
few-shot	Iter	51.6	46.1	60.8	62.7	46.5	32.0	26.6	50.8	52.7	61.0	64.4	68.9	58.9
	Decom (prob.)	45.4	69.8	62.2	61.2	44.6	52.3	46.1	63.0	49.6	65.4	68.1	62.3	63.6
	Decom (gen.)	37.3	60.5	55.8	54.5	40.7	49.4	42.6	58.4	46.9	54.9	61.4	54.3	54.9
	Decom (prob.) + I	31.4	64.2	55.3	55.3	38.1	51.7	47.1	58.9	52.5	65.4	60.2	56.3	60.4
	Decom (gen.) + I	23.4	60.0	50.2	52.4	35.5	49.0	45.3	56.9	50.8	61.1	58.2	54.1	56.1

	language	ru	ta	te	th	tl	tr	uk	ur	vi	wo	yo	zh	avg.
zero-shot	Iter	42.6	21.8	22.5	45.6	29.3	29.9	39.8	35.1	36.0	24.4	24.1	45.2	37.4
	Decom (prob.)	66.5	49.1	50.8	44.6	66.5	56.9	65.7	47.2	45.3	34.5	47.7	58.7	54.7
	Decom (gen.)	55.2	46.2	54.1	44.2	73.1	52.8	57.3	40.2	45.4	29.9	39.6	52.5	48.7
few-shot	Iter	64.9	33.5	51.5	51.5	60.2	46.3	61.6	45.4	41.8	36.3	31.6	52.1	52.6
	Decom (prob.)	71.0	30.4	54.4	40.1	74.0	54.1	69.0	30.1	47.5	39.4	36.2	66.6	54.5
	Decom (gen.)	63.3	21.9	51.3	33.9	70.9	52.2	61.4	22.1	45.2	38.1	34.8	56.5	48.3
	Decom (prob.) + I	63.3	22.3	52.2	23.5	70.7	53.9	62.4	19.0	48.4	36.9	36.4	56.7	49.4
	Decom (gen.) + I	59.8	14.1	48.4	18.5	70.2	53.2	59.1	12.0	47.1	34.5	34.5	52.7	45.6

Table 8: Full results on LLaMA2 13b.

	language	en	af	ar	bg	de	el	es	et	eu	fa	fi	fr	he
zero-shot	Iter	6.4	7.2	10.9	7.6	9.5	8.4	8.2	12.4	7.5	7.3	9.3	9.0	9.6
	Decom (prob.)	20.6	20.5	14.5	19.7	26.2	18.3	18.2	22.3	19.0	12.8	19.2	19.4	15.2
	Decom (gen.)	28.7	18.3	16.4	22.6	26.8	22.7	24.9	21.2	25.0	11.3	20.9	20.9	21.8
few-shot	Iter	30.9	6.4	14.4	23.8	19.3	7.7	23.2	16.6	28.4	11.1	22.3	25.1	7.5
	Decom (prob.)	44.1	33.1	28.7	35.9	44.0	39.2	33.6	39.0	38.4	25.6	38.5	35.6	34.3
	Decom (gen.)	40.6	31.0	25.5	31.4	39.5	35.8	30.5	36.9	33.8	21.6	36.8	31.0	33.6
	Decom (prob.) + I	33.3	24.7	27.2	35.2	30.0	31.0	30.1	36.5	37.4	24.7	34.4	29.0	29.2
	Decom (gen.) + I	33.3	24.5	27.1	35.0	29.7	30.4	30.0	36.4	37.1	24.5	34.5	28.9	29.1

	language	hi	hu	id	it	ja	kk	ko	lt	mr	nl	pl	pt	ro
zero-shot	Iter	3.9	13.0	10.0	9.1	2.8	4.5	8.5	7.8	0.4	9.1	9.9	8.6	8.8
	Decom (prob.)	12.0	27.0	17.7	23.1	13.5	17.7	19.5	23.6	12.4	18.6	23.6	19.5	19.6
	Decom (gen.)	15.2	21.9	17.3	26.2	26.2	16.8	21.3	23.4	25.8	14.7	23.2	27.8	24.3
few-shot	Iter	20.5	13.4	30.5	19.0	6.3	17.0	5.9	15.0	35.2	20.8	17.9	27.4	13.4
	Decom (prob.)	27.0	38.2	43.8	33.9	25.9	45.6	35.0	40.3	39.6	39.8	39.7	34.4	33.3
	Decom (gen.)	24.8	36.9	41.2	31.1	22.5	43.8	32.7	39.5	28.0	36.5	36.5	31.7	32.0
	Decom (prob.) + I	25.6	32.3	36.0	30.7	25.3	45.2	27.7	41.0	44.5	29.0	34.7	30.4	32.5
	Decom (gen.) + I	25.6	32.2	35.9	30.6	25.1	45.1	27.7	41.0	43.7	28.6	34.6	30.3	32.5

	language	ru	ta	te	th	tl	tr	uk	ur	vi	wo	yo	zh	avg.
zero-shot	Iter	6.8	5.0	5.1	6.8	3.9	9.0	5.2	6.6	4.2	1.4	7.2	7.6	7.4
	Decom (prob.)	26.1	15.0	7.9	8.7	7.8	15.5	23.7	8.1	14.4	11.0	18.9	21.7	17.6
	Decom (gen.)	27.9	20.7	12.8	2.7	1.9	17.4	28.1	12.8	25.7	21.1	28.3	26.0	20.6
few-shot	Iter	20.3	24.3	47.0	3.1	22.5	20.9	20.9	15.5	18.3	16.5	16.9	20.7	18.8
	Decom (prob.)	41.9	36.5	48.2	25.0	41.9	37.9	39.6	26.2	26.9	34.1	39.2	40.8	36.2
	Decom (gen.)	36.8	33.5	41.7	23.1	41.9	36.4	37.0	24.7	24.5	33.2	36.5	35.7	33.2
	Decom (prob.) + I	37.0	34.1	39.0	13.7	57.8	38.0	35.8	26.4	34.0	30.3	33.3	32.8	32.9
	Decom (gen.) + I	36.9	33.9	38.8	13.6	57.8	38.0	35.4	26.4	33.9	30.3	33.3	32.6	32.7

Table 9: Full results on BLOOMZ 7b.

	language	en	af	ar	bg	de	el	es	et	eu	fa	fi	fr	he
zero-shot	Decom (gen.)	47.6	45.7	37.8	48.9	48.9	45.8	40.0	45.3	41.5	44.2	46.8	42.6	42.6
few-shot	Decom (gen.)	49.0	41.0	16.2	37.6	43.9	31.0	37.2	34.8	33.9	33.4	32.1	38.5	34.1
	Decom (gen.) + I	57.3	51.9	27.4	47.2	55.4	40.1	50.1	41.2	43.6	48.1	42.4	49.9	45.6
	language	hi	hu	id	it	ja	kk	ko	lt	mr	nl	pl	pt	ro
zero-shot	Decom (gen.)	40.6	38.7	39.3	39.3	32.9	46.1	29.2	47.4	47.5	42.8	46.1	40.6	49.4
few-shot	Decom (gen.)	23.8	33.5	39.9	36.5	14.3	32.4	17.7	37.5	34.9	42.7	36.1	37.1	35.6
	Decom (gen.) + I	44.7	36.2	51.9	45.7	44.6	45.7	26.7	45.7	48.8	55.3	46.2	48.9	51.5
	language	ru	ta	te	th	tl	tr	uk	ur	vi	wo	yo	zh	avg.
zero-shot	Decom (gen.)	45.9	39.4	51.3	47.1	59.3	46.9	47.4	37.9	48.4	22.3	37.5	42.8	43.1
few-shot	Decom (gen.)	33.5	28.1	50.9	21.9	65.7	34.7	31.2	17.7	33.9	10.5	22.4	17.2	32.5
	Decom (gen.) + I	43.8	38.0	55.3	46.6	70.5	46.0	41.5	36.0	49.0	19.8	38.6	34.5	44.7

Table 10: Full results on mTk 13b.