On Reducing Action Labels in Planning Domains

Abstract

Planning tasks succinctly represent labeled transition systems, with each ground action corresponding to a label. This granularity, however, is not necessary for solving planning tasks and can be harmful, especially for model-free methods. In order to apply such methods, the label sets are often manually reduced. In this work, we propose automating this manual process. We characterize a *valid* label reduction for classical planning tasks and propose an automated way of obtaining such valid reductions by leveraging lifted mutex groups. Our experiments show a significant reduction in the action label space size across a wide collection of planning domains. We demonstrate the benefit of our automated label reduction in two separate use cases: improved sample complexity of model-free reinforcement learning algorithms and speeding up successor generation in lifted planning.

1 Introduction

AI Planning tasks, described in the planning domain description language (PDDL) (McDermott 2000), induce transition graphs with states as nodes and transitions between states as labeled edges. These labeled transition systems (LTS) feature a unique label for each ground action. They identify transitions induced by the same actions on different states with the *same label*. In practice, these labels are primarily used to distinguish *applicable* actions in a given state. So, a much smaller, sufficient set of labels might be attainable. Consider the gripper domain (McDermott 2000) where a robot moves balls between two rooms. Figure 1 depicts the PDDL task in this domain. Consider the schematic operator `pick` and its second parameter `?r:room`. All applicable groundings of the operator `pick` in any given state will have the same value for `?r`, namely the current room the robot is in. Therefore, this parameter is not essential for distinguishing LTS transitions. Note that it does not mean that the parameter can be omitted from the schematic operator, as it is essential for defining operator preconditions. On the labeled transition system, however, all labels of the corresponding grounded actions that differ only in the room parameter can be safely collapsed into one label, achieving a smaller set of labels.

It is no coincidence that discrete action sets of small sizes are also favored by reinforcement learning (RL) approaches. Choosing from a large collection of mostly irrelevant actions

in a state can be detrimental to model-free methods (Huang and Ontañón 2022). Most RL benchmarks have only a small number of actions, e.g., Atari benchmarks have at most 18 actions, representing all possible transition labels (Nelson 2021). When planning problems are cast as Markov Decision Processes (MDPs), great care is taken in defining small label sets (Silver and Chitnis 2020; Fern, Yoon, and Givan 2006; Dzeroski, Raedt, and Driessens 2001). In PDDL-Gym (Silver and Chitnis 2020), the label sets are manually crafted by identifying a subset of lifted schematic operator parameters that are *inessential* for distinguishing two labels in a state. For example, the `?r:room` parameter from our Gripper example is manually identified as inessential.

In this work we propose automating this manual process, exploring ways of automatically reducing action labels in classical planning domains. For that, we characterize a *valid* label reduction for classical planning tasks and propose a way to automatically obtain such a reduction. Focusing on the reduction of operator parameters, we show how *lifted mutex groups* (Fišer 2020) can be leveraged to automatically identify the inessential parameters of the operators effectively, essentially automating the manual process of Silver and Chitnis (2020). Our contributions, however, have a wider scope. We formally define the problem of obtaining a parameter seed set and propose to solve this problem by translating it to a delete-free planning task, proving that the solution obtained is a valid label reduction. Then we empirically evaluate our approach on 14 IPC domains and 10 hard-to-ground domains (Lauer et al. 2021; Haslum 2011; Matloob and Soutchanski 2016) and show that it achieves a significant reduction in action labels. Finally, we demonstrate the benefits of our approach on two use cases, RL and lifted successor generation (Corrêa et al. 2020). We empirically show that the label reduction can help in both cases: it significantly improves the sample efficiency of standard RL agents and speeds up the time to generate applicable actions in lifted successor generation.

2 Preliminaries

In this section, we first introduce the necessary classical planning notations and describe lifted mutex groups that we use in our proposed approach. Then we provide a brief overview of how a PDDL task is cast as an MDP as well as lifted successor generation, the two possible use cases of our

(a)

```
Gripper task Π = ⟨L, O, I, G⟩.
• Language L includes:
    objects B : r1, r2, b1, b2, g1, g2
    types T : room, ball, gripper
    variables V : ?r, ?b, ?g, ?f, ?t
    predicates P : at_robby, at, free, carry
• Initial state I is: {at(b1,r1), at(b2,r1),
    at_robby(r1), free(g1), free(g2)}
• Goal G is: {at(b2,r2)}
• Schematic operators O consists of:
  move  : params {?f : room, ?t : room}
        : pre {at_robby(?f)}
        : add {at_robby(?t)}
        : del {at_robby(?f)}
  pick  : params {?b : ball, ?r : room, ?g : gripper}
        : pre {at(?b,?r), at_robby(?r), free(?g)}
        : add {carry(?b,?g)}
        : del {at(?b,?r), free(?g)}
  drop  : params {?b : ball, ?r : room, ?g : gripper}
        : pre {carry(?b,?g), at_robby(?r)}
        : add {at(?b,?r), free(?g))}
        : del {carry(?b,?g)}
```

(b)

Figure 1: A running example of Gripper task, (a) an initial state with b1, b2, and robot in room r1, and (b) a normalized PDDL task.

approach.

PDDL task We consider normalized PDDL tasks without axioms and conditional effects (Helmert 2009). A *normalized PDDL task* $\Pi = \langle \mathcal{L}, \mathcal{O}, I, G \rangle$ is defined over a first-order language $\mathcal{L}$, a finite set of *schematic operators* $\mathcal{O}$, an *initial state specification* I, and a *goal specification* G. We often use the terms operator and action interchangeably.

A *first-order language* $\mathcal{L} = \langle \mathcal{B}, \mathcal{T}, \mathcal{V}, \mathcal{P} \rangle$ consists of a finite number of objects ($\mathcal{B}$), types ($\mathcal{T}$), variables ($\mathcal{V}$), and fluent predicates ($\mathcal{P}$). The association between types and objects is defined by a function $\mathcal{D} : \mathcal{T} \to 2^{\mathcal{B}}$. $\mathcal{T}$ contains a special default type t_0. Every object is associated with this default type such that $\mathcal{D}(t_0) = \mathcal{B}$. Every pair of types $t_i, t_j \in \mathcal{T}$ satisfy one of the following conditions, either $\mathcal{D}(t_i) \subseteq \mathcal{D}(t_j)$ or $\mathcal{D}(t_i) \supseteq \mathcal{D}(t_j)$ or $\mathcal{D}(t_i) \cap \mathcal{D}(t_j) = \emptyset$. $\mathcal{V}$ is a finite set of variable symbols such that each variable is associated with a type in $\mathcal{T}$. All variables are represented with a prefix "?", for example, ?v. A pair of object and variable (o,?v) are *compatible* if o $\in \mathcal{D}(t_v)$, where t_v is the type of variable v. A predicate in $\mathcal{P}$ has fixed arity and each argument is associated with a type in $\mathcal{T}$. An *atom* is a predicate symbol followed by a parenthesized list of arguments, predicate(term$_1$, term$_2$, $\cdots$). For an atom α, $free(\alpha) \in \mathcal{V}$ denotes a set of variables in the atom. If $free(\alpha) = \emptyset$ then α is called ground atom; otherwise it is called lifted atom. A lifted atom is grounded by replacing every variable with a compatible object. If lifted atoms α and α' have the same predicate and the types of all the terms in α are subsets of types of respective terms in α', we say that α is a *subset* of α'. That is, $p(?a, ?b) \sqsubseteq p(?a', ?b')$, if $\mathcal{D}(t_a) \subseteq \mathcal{D}(t_{a'})$ and $\mathcal{D}(t_b) \subseteq \mathcal{D}(t_{b'})$.

The initial state specification I is a conjunction of ground atoms with fluent predicates. The goal specification G is a conjunction of ground atoms or their negations. A *schematic operator* $o = \langle head, pre, add, del \rangle$ in $\mathcal{O}$ consists of the atom $head(o)$, indicating the name and the parameters of the operator, the preconditions $pre(o)$, the add-effects $add(o)$, and the delete-effects $del(o)$, each is a conjunction of literals over $\mathcal{L}$. For each operator o, the set of operator parameters $params(o)$ is defined as $free(pre(o)) \cup free(add(o)) \cup free(del(o))$. Operators with empty parameter sets are called *ground* operators. Otherwise, an operator can be grounded by replacing parameters with compatible objects in the domain.

The set of all ground operators is denoted by $\mathcal{O}_\downarrow$. By $o_\downarrow(P/\theta)$ we denote a set of ground operators induced by assigning objects θ to parameter subset P and grounding the remaining parameters with all the compatible objects. In the gripper example, the ground operator set of the schematic operator $o=$pick(?b,?r,?g) induced by the assignment {?b/b1, ?g/g1} is $o_\downarrow(\{?b/b1, ?g/g1\}) = \{$pick(b1,r1,g1), pick(b1,r2,g1)$\}$, where the parameters ?b and ?g are replaced with the objects mentioned in the assignment but the parameter ?r is replaced with all room objects, {r1, r2}.

A *state* s assigns values TRUE and FALSE to all ground atoms with *fluent* predicates. The *initial state* s_0 of the task assigns value TRUE to all atoms occurring in I, and FALSE to all other fluent ground atoms. A ground operator o is *applicable* in state s if $s \models pre(o)$, that is, the preconditions of o are satisfied in the state s. A ground atom α is TRUE in the successor state if and only if either it has been TRUE in s and $\alpha \notin del(o)$ or $\alpha \in add(o)$. A *plan* for the task is a sequence of ground operators whose subsequent application leads from s_0 to some state s_* with $s_* \models G$.

Lifted Mutex Groups A *mutex group* is a set of mutually exclusive ground atoms M, of which at any given (reachable from I) state s at most one can be TRUE. That is $\forall s, |M \cap s| \leq 1$ or equivalently $\forall s, |\{\alpha \mid s \models \alpha, \alpha \in M\}| \leq 1$. For example, in the gripper domain, {at(b1,r1), at(b1,r2)} is a mutex group as, in any given state, ball b1 can only be in one of the rooms. Any subset of a mutex group is also a mutex group. A **lifted mutex group** (LMG) is a set of lifted atoms that produces a mutex group when grounded. Formally, a lifted mutex group is defined using an *invariant candidate*.

An **invariant candidate** is a tuple $c = \langle v^f, v^c, \rangle$ where $v^f(c)$ is a finite set of fixed variables, $v^c(c)$ is a finite set of counted variables, and (c) is a finite set of atoms such that all the variables of the atoms are present in either $v^f(c)$ or $v^c(c)$, i.e. $free((c)) = v^f(c) \cup v^c(c)$ and $v^f(c) \cap v^c(c) = \emptyset$. For example, consider an invariant candidate $c = \langle \{?b\}, \{?r\}, \{at(?b, ?r)\} \rangle$. Different groundings of fixed variables $v^f(c) = \{?b\}$ gener-

ate different sets of ground atoms and different grounding of counted variable $v^c(c) = \{?r\}$ generates ground atoms within each set. We denote the ground atom set with down arrow $_\downarrow$. One of the ground atom sets for $\{?b/b1\}$ is $c_\downarrow(?b/b1) = \{\texttt{at(b1,r1)}, \texttt{at(b1,r2)}\}$ and another ground set for $\{?b/b2\}$ is $c_\downarrow(?b/b2) = \{\texttt{at(b2,r1)}, \texttt{at(b2,r2)}\}$.

An invariant candidate is called a **lifted mutex group** if all of its ground atom sets are mutex groups, that is, $\forall x, s, |\{a \mid s \models a, a \in c_\downarrow(v^f(c)/x)\}| \leq 1$. An LMG with no fixed variable can only generate one ground mutex group. For example, $\langle \emptyset, ?r, \{\texttt{at\_robby(?r)}\}\rangle$ only induces ground atoms set $\{\texttt{at\_robby(r1)}, \texttt{at\_robby(r2)}\}$. Fišer (2020) provides a method to identify the set of LMGs for a PDDL task. Since an LMG with multiple atoms can be split into multiple LMGs with a single atom each, for simplicity, in this paper we assume each LMG has only one atom.

PDDL task as MDP An MDP $= \langle S, A, P, R\rangle$ contains a set of states S, a set of actions A, a transition probability distribution $P : S \times S \times A \mapsto [0,1]$, and a reward function $R : S \mapsto \mathbb{R}$. When a PDDL task Π is cast as an MDP , the states $S \in$ are defined as the set of all states reachable from I of Π, the action set $A \in$ is defined as the set of labels L that is composed of a unique label for each of the ground operators, the probability distribution P is defined to respect the state-transition in the PDDL operators, and the reward function R is defined as some positive integer when $s \models G$. In practice, for each of the ground operators, the head of the ground operator $head(o)$ is assigned as the unique label.

Lifted Successor Generation While planning tasks are often represented in PDDL, using first-order representations, most planners use a propositional or a multi-valued grounded representation (Bäckström and Nebel 1995). The lifted successor generator by Corrêa et al. (2020) works directly on a lifted level to generate successor states using database techniques (Ullman 1989). A state is represented as a database. Each predicate has a table with the number of columns according to the predicate arity. Each fact in the state forms a row in the table. With this state representation, the task of identifying the applicable actions is equivalent to a join query evaluation. Consider a planning task $\Pi = \langle \mathcal{L}, \mathcal{O}, I, G\rangle$ over a first-order language $\mathcal{L} = \langle \mathcal{B}, \mathcal{T}, \mathcal{V}, \mathcal{P}\rangle$. A state s is a database $D(s) = \langle \mathcal{B}, \{R_{P,s} | P \in \mathcal{P}\}\rangle$ with objects $\mathcal{B}$ as domain and finite set of relations over these objects. The relation $R_{P,s}$ contains all ground atoms of predicate P in state s as tuples. The set of actions applicable in s for a schematic operator $o \in \mathcal{O}$ is identified by the conjunctive query

$$Q(params(o)) := R_{P_1,s}, \cdots, R_{P_n,s} \text{ where } P_i \in pre(o).$$

3 Label Reduction

A planning task can be represented as a labeled transition system, where labels are actions that can be executed in states. These transition labels are identified by the $head(o)$ for the grounded operator. For example, $\texttt{pick(b1,r1,g1)}$ is a label for the operator that picks the ball $\texttt{b1}$ from room $\texttt{r1}$ in the gripper $\texttt{g1}$. *A label set L consists of a unique label for each grounded operator in $\mathcal{O}_\downarrow$.* The label set size increases exponentially in the number of objects. This work aims to reduce the size of the label set L. We do so by identifying an assignment of labels to planning operators such that it generates a smaller label set L' while producing an equivalent transition system. We capture this requirement by specifying the criteria for a *valid label reduction*. A label reduction is *valid* if it assigns distinct labels to any two ground operators that can be applied in the same reachable state. For example, operators $\texttt{pick(b1,r1,g1)}$ and $\texttt{pick(b2,r2,g1)}$ cannot be applied in the same state as the gripper $\texttt{g1}$ cannot be in two different rooms in the same state. Thus, assigning the same label to both would be valid. But $\texttt{pick(b1,r1,g1)}$ and $\texttt{pick(b2,r1,g2)}$ can be applied in the same state, and hence cannot be assigned the same action label.

Definition 1 *A label reduction function $\psi : L \mapsto L'$ is **valid** if any two distinct ground operator labels $head(o_1), head(o_2) \in L$ that are applicable in the same reachable state $(s \models pre(o_1) \wedge s \models pre(o_2))$ are assigned distinct labels, that is $\psi(head(o_1)) \neq \psi(head(o_2))$.*

This definition ensures that any two operators that are applicable in the same state are distinguishable. For each reduced label, the set of corresponding operators must include at most one applicable operator for each reachable state. Noticing the resemblance to predicate mutex groups, we call such operator sets *applicable operator mutex groups*.

Definition 2 *A set of ground operators $\mathcal{O}'$ is an **applicable operator mutex group** (AOMG) if for any reachable state s, $|\{o \mid s \models pre(o), o \in \mathcal{O}'\}| \leq 1$.*

Naturally, any subset of an AOMG is also an AOMG, and any set of operators of size 1 is an AOMG. A partitioning of operators into AOMGs defines a valid label reduction, and vice versa, a valid label reduction defines a partitioning of operators into AOMGs. While one can seek to find the smallest possible valid label reduction, that might require generating the set of all ground operators. To avoid the tedious grounding process, we focus on finding AOMGs for (lifted) schematic operators.

We find AOMGs for each schematic operator separately, by reducing its parameters. For example, consider a schematic operator $o = \texttt{pick(?b,?r,?g)}$, as a robot can only be in one specific room in any state, only one specific assignment to $\texttt{?r}$ is satisfiable in any state. So one possible set of AOMGs can be obtained by defining partial grounding of operator o on the subset of parameters obtained after removing $\texttt{?r}$. That is $o_\downarrow(\{?b/b, ?g/g\}) | \forall b, g = \{\{\texttt{pick(b1,r1,g1)}, \texttt{pick(b1,r2,g1)}\}, \{\texttt{pick(b1,r1,g2)}, \texttt{pick(b1,r2,g2)}\}, ...\}$.

A partial grounding of parameter subset $(X \subseteq params(o))$ of a schematic operator o induces sets of ground operators where each set corresponds to a particular assignment of objects to parameter subset X. Thus, we want to identify a *subset of parameters* (X) such that any assignment (c) to this subset results in the ground operator set $(o_\downarrow(X/c))$ being an AOMG (like the subset $\{?b, ?g\}$ in the

above example). Note that LMGs have a similar property. Any assignment to their fixed variables results in a ground atom set being a mutex group. Next, we show how LMGs can be used to identify the required parameter subset.

Theorem 1 *Given a schematic operator o and a lifted mutex group $l = \langle v^f(l), v^c(l), \{\alpha\} \rangle$, if $p \sqsubseteq \alpha$ for some $p \in pre(o)$, then any assignment c to $X = params(o) \setminus v^c(l)$[1] results in $o_\downarrow(X/c)$ being an AOMG.*

Proof: Given an assignment $v^f(l)/c$, any state s can only satisfy at most one of the ground atoms from the mutex group $l_\downarrow(v^f/c)$ (from the definition of LMG). Consequently, as $p \in pre(o)$ and $p \sqsubseteq \alpha$, the state can satisfy at most one of the preconditions of the ground operators in the set $o_\downarrow(X/c)$. Hence, $o_\downarrow(X/c)$ is an AOMG. ∎

We call an LMG l *relevant* to a schematic operator if an atom p in the precondition satisfies $p \sqsubseteq \alpha$, where $\alpha \in (l)$. The parameters from set $v^c(l)$ of a relevant LMG need not be included in X. Given the assignment to $v^f(l) \subseteq params(o)$ the LMG l guarantees a unique assignment to parameters $v^c(l)$. Once the assignment to these parameters $(v^f(l) \cup v^c(l) \subseteq params(o))$ are identified, another LMG l' could now be used to identify the assignment to parameters $v^c(l')$ and hence $v^c(l')$ can also be removed from X. Essentially, we can leverage multiple LMGs to further reduce the subset X. Refer to Appendix B for an example. Formally, this corresponds to the following problem, which we call *parameter seed set*:

Input: A schematic operator o with parameters $params(o)$ and a set of *relevant* lifted mutex groups L.
Find: A subset $X \subseteq params(o)$ of parameters s.t. $\exists X_1, \ldots X_k$ with (i) $X = X_1 \subseteq X_2 \subseteq \ldots \subseteq X_k = params(o)$, and (ii) $X_{i+1} = X_i \cup v^c(l)$ for some $l \in L$ s.t. $v^f(l) \subseteq X_i$.

Any assignment of objects to the parameter seed set X will result in a unique assignment to all the remaining parameters of o for any reachable state.

Theorem 2 *Let o be a schematic operator over parameters $params(o)$ and X be a solution to the parameter seed set problem above. Any assignment c of objects to X results in $o_\downarrow(X/c)$ being an AOMG.*

Proof: Let $X_1 \subseteq X_2 \subseteq \ldots \subseteq X_k = params(o)$ and let $l_1 \ldots l_{k-1}$ be lifted mutex groups such that $v^f(l_i) \in X_i$ and $X_{i+1} = X_i \cup v^c(l_i)$. Then, each X_i is a solution to the parameter seed set problem. We prove the claim by induction over the number of lifted mutex groups starting from k. The base claim of $o_\downarrow(X_k/x)$ (one lifted mutex group) is AOMG results from Theorem 1. We assume that $o_\downarrow(X_{i+1}/\hat{c})$ is an AOMG for any assignment $\hat{c}$ to X_{i+1} and prove that $o_\downarrow(X_i/\tilde{c})$ is an AOMG for any assignment $\tilde{c}$ to X_i. Since $l_i = \langle v^f(l_i), v^c(l_i), (l_i) \rangle$ is a lifted mutex group with $v^f(l_i) \subseteq X_i$, we have that $l_{i\downarrow}(X_i/\tilde{c})$ is a mutex group. Let o_1, o_2 be two ground operators in $o_\downarrow(X_i/\tilde{c})$. If both o_1

and o_2 belong to $o_\downarrow(X_{i+1}/\hat{c})$, we are done. Otherwise, assume o_1 in $o_\downarrow(X_{i+1}/c_1)$ and o_2 in $o_\downarrow(X_{i+1}/c_2)$, where c_1 and c_2 agree on X_i but differ on $X_{i+1} \setminus X_i$. However, since $X_{i+1} = X_i \cup v^c(l_i)$, we have $X_{i+1} \setminus X_i \subseteq v^c(l_i)$, making c_1 and c_2 mutually exclusive. Thus, $o_\downarrow(X_i/\tilde{c})$ is an AOMG. ∎

Different parameter seed sets X correspond to different AOMGs. To find the smallest possible label set L', we want to minimize the number of AOMGs and therefore we are looking for a seed set X with a minimum possible total number of assignments. This can be expressed as

$$\underset{X}{\operatorname{argmin}} \prod_{x \in X} |\mathcal{D}(x)|.$$

As the objective is not linear, we can use an equivalent one instead: $\underset{X}{\operatorname{argmin}} \sum_{x \in X} \log(|\mathcal{D}(x)|)$.

The parameter seed set problem is NP-Complete. For the lack of space, the proof, by reducing the bounded parameter seed set decision problem to a seed set decision problem (Gefen and Brafman 2011), is deferred to Appendix A. To solve the parameter seed set problem, we cast it as a (delete-free) STRIPS planning task with action costs. We first find a set L of relevant LMGs. Then, for each schematic operator o we define a separate planning task $\Pi_o = \langle \mathcal{L}_o, \mathcal{O}_o, I_o, G_o \rangle$, where

- Language $\mathcal{L}_o$ contains a single predicate mark and an object for each parameter in $params(o)$.
- The set $\mathcal{O}_o$ consists of two types of operators
  1. seed_x operators are defined for each parameter $x \in params(o)$ as $\text{seed}_x :=$ $\langle \text{seed}_x, \emptyset, \{\text{mark}(x)\}, \emptyset, log(|\mathcal{D}(x)|) \rangle$
  2. get_l operators are defined for each relevant LMG l as $\text{get}_l := \langle get_l, \{\text{mark}(x) \mid x \in v^f(l)\}, \{\text{mark}(y) \mid y \in v^c(l)\}, \emptyset, 0 \rangle$.
- Initial state $I_o = \emptyset$
- Goal state $G_o = \{\text{mark}(x) \mid \forall x \in params(o)\}$.

The operator seed_x marks parameter $x \in params(o)$ as an element of the seed set. Operator get_l indicates that a unique assignment for the parameters $x \in v^c(l)$ can be identified if all parameters $y \in v^f(l)$ are known. Therefore, the parameters $v^c(l)$ can be reduced. A plan for Π_o corresponds to a sequence of seed and get_l operators. The parameters marked by seed operators form the seed set, while others are reduced.

Theorem 3 *For a plan π of Π_o, $X_\pi = \{c \mid \text{seed}_c \in \pi\}$, is a solution to the parameter seed set problem of o.*

Proof: Let π be a plan for Π_o (assume there are no redundant repetitions of operators in π). Since seed operators have no preconditions, assume these operators come before get_l operators, and let $\pi = \pi_s \pi_g$ denote the partition of π into the two sequences of seed and get_l operators, respectively. Let s_1 be the state resulting from applying π_s in the initial state I_o and $s_1, \ldots, s_k$ be the sequence of states along π_g applied to s_1. Then, we have (i) $s_1 \subseteq s_2 \subseteq \ldots \subseteq s_k$ and $s_k = \{\text{mark}(x) \mid x \in params(o)\}$, as well as (ii)

---
[1] We assume that the variables of the LMG l match the ones of the action precondition atom p.

Figure 2: Comparison of label set sizes on (a) 14 IPC STRIPS domains and (b) 7 HTG domains.

$s_{i+1} = s_i \cup add(get_l) = s_i \cup \{\text{mark}(y) \mid y \in v^c(l)\}$ for some get_l with $pre(get_l) = \{\text{mark}(x) \mid x \in v^f(l)\} \subseteq s_i$. Denoting the parameters of o marked in the state s by $\Gamma(s) = \{x \mid \text{mark}(x) \in s\}$, we get that $X_\pi = \Gamma(s_1)$. ∎

The cost of a plan π is $\sum_{\text{seed}_x \in \pi} \log(|\mathcal{D}(x)|)$, and therefore a cost-optimal plan will correspond to a parameter seed set with a minimal possible total number of assignments. To summarize, we find a parameter seed-set X for each schematic operator such that assigning objects to X will result in a set of ground operators that is an AOMG. Hence, all the ground operators in that set can be assigned the same label. This reduces the size of the label set L.

4 Experiments

Our experimental evaluation is split into three parts. First, we check whether our approach is able to reduce the size of the action label set and whether the reduction is substantial. The next two parts evaluate the utility of our approach. We test whether our reduction can translate into improved performance in two use cases: learning reinforcement learning policies and lifted successor generation.

Reduction in action label set We compare the size of label sets, obtained with and without the proposed reduction, on a representative set of 14 STRIPS domains from various IPC (using the typed versions where available) and 10 hard-to-ground (HTG) domains. We use the Fast Downward planning system translator (Helmert 2006) to ground the schematic operators. To infer the lifted mutex groups, we use the implementation by Fišer (2020) and to solve the *parameter seed set* planning task we use the Fast Downward planner. The parameter seed set planning problem described in the previous section uses real-valued costs for the seed operators. However, the Fast downward planner only allows integer costs. So we scale the real-valued costs of the seed operator in our experiments.

Figure 2 compares the size of the label sets L' and L, obtained with and without the reduction resp. Figure 2a presents the reduction on each PDDL problem instance for

Domain	# reduced operators	non-seed parameters	
		max % (#)	mean % (#)
IPC domains			
blocks	3/4	100.0% (1.0)	50.0% (0.75)
barman	11/12	66.67% (3.0)	41.94% (1.92)
driverlog	6/6	66.67% (2.0)	47.22% (1.5)
thoughtful	20/21	100.0% (6.0)	73.03% (3.24)
gripper	3/3	66.67% (2.0)	50.0% (1.33)
pipesworld	6/6	74.57% (6.12)	65.69% (5.26)
pipesworld (no t.)	6/6	71.43% (5.0)	59.81% (3.87)
pipesworld (no s.)	4/4	68.89% (7.6)	65.83% (6.88)
tpp	4/4	69.52% (4.87)	60.48% (3.9)
freecell	10/10	80.0% (5.0)	65.29% (3.3)
logistics	6/6	66.67% (2.0)	55.95% (1.76)
rovers	8.62/9	77.08% (2.88)	46.5% (1.73)
satellite	5/5	68.52% (2.08)	51.99% (1.46)
visitall	1/1	50.0% (1.0)	50.0% (1.0)
depot	5/5	50.0% (2.0)	46.67% (1.8)
zenotravel	5/5	77.5% (4.1)	62.23% (2.68)
HTG Domains			
visitall-3dim	3/3	75.0% (3.0)	75.0% (3.0)
visitall-4dim	4/4	80.0% (4.0)	80.0% (4.0)
visitall-5dim	5/5	83.33% (5.0)	83.33% (5.0)
blocksworld	3/4	100.0% (1.0)	50.0% (0.75)
GED	11/14	100.0% (3.0)	61.9% (1.5)
GED-split	19/21	100.0% (2.0)	73.81% (1.38)
GED-positional	0/3	0.0% (0.0)	0.0% (0.0)
pipesworld (no s.)	4/4	68.0% (7.26)	64.1% (6.68)
rovers	0/9	0.0% (0.0)	0.0% (0.0)
childsnack_parsize1	2.5/4	63.33% (3.17)	27.29% (1.17)
childsnack_parsize2	3/4	77.78% (4.67)	36.11% (1.92)
childsnack_parsize3	3/4	80.95% (5.67)	37.95% (2.42)
childsnack_parsize4	3/4	83.33% (6.67)	39.17% (2.92)
logistics	6/6	83.33% (2.5)	65.97% (2.08)
OS-MIT	15.22/52	44.41% (4.39)	7.91% (0.81)
OS-alkene	12/12	67.36% (7.11)	37.28% (3.81)
OS-original	14.85/52	45.74% (4.65)	7.14% (0.76)

Table 1: Summary of operators reduced by our approach. Column 2 shows the number of reduced/total lifted operators. Columns 3 & 4 present the maximum & mean of the percent (number) of reducible parameters per operator, aggregated over problems in that domain.

IPC domains and Figure 2b on 7 out of 10 HTG domains (the remaining 3 are shown in Appendix C). Both axes are log-scale. Points below the diagonal indicate instances where

Figure 3: Learning curve in (a) ferry, (b) gripper, (c) blocks, and (d) logistics; with and without action label reduction.

Figure 4: Comparison of table sizes before the query is performed. We split HTG domains into two plots for readability.

the reduced label set is smaller than the original one. The distance from the diagonal indicates the significance of the reduction. Gray dashed lines below the diagonal represent the order of magnitude of the reduction. *Our experimental results show a substantial reduction of the label set in most problem instances, going up to 2 orders of magnitude on IPC problems and up to 10 orders of magnitude on hard-to-ground domains.*

Table 1 summarizes the number of schematic operators that were reduced by our approach. It also presents the mean and max number of non-seed parameters found in the schematic operators, i.e., $|params(o)| - |X|$. Each row of the table represents a domain, aggregating results over the instances of that domain. We were able to find non-seed parameters in all 14 IPC domains and all but 2 HTG domains. The largest reduction, in terms of the max number of non-seed parameters, is observed in *thoughtful, pipesworld, tpp, freecell, zenotravel, visit all, childsnack,* and *OS-alkene* domains. Each having > 3 parameters reduced for some schematic operators. 2 IPC domains and 3 HTG domains have operators with 100% reduction, that is all the parameters of some operators were deemed inessential. Note that the number of reduced parameters (in Table 1) is not necessarily proportional to the number of reduced actions (in Figure 2). Nevertheless, the number of reduced parameters indicates the importance of parameter reduction. The com-

putation time was between 0.25 and 1.73 seconds for the IPC domains and between 0.26 and 4.69 seconds for the HTG domains. Refer to Appendix C for details on the computation time for each domain.

Learning RL policies To evaluate the advantage of reducing the label set size in planning as RL, we cast the PDDL task as an MDP with either the regular (all ground actions) or the reduced label set and learn an RL policy. We focus on 4 classical planning domains, *Ferry, Gripper, Blocks,* and *Logistics.* Since our aim is to evaluate the advantage of reducing the action space, and not the generalization of policies, we fix the number of objects in each domain. We generate 500 unique pairs of initial and goal states in each domain. Of these, 250 pairs were used in training and the remaining were set aside for evaluation. Inspired by the work of Gehring et al. (2022), we use domain-independent planning heuristic, h^{FF}, as a dense reward function and use their code to convert PDDL problem to an RL environment. We employ the Double DQN implementation from the ACME RL library (Hoffman et al. 2020) to learn a state-action value function and apply a greedy policy $\pi(s) = \max_a Q(s, a)$ in our evaluation. Refer to Appendix C for more details about the environment and hyperparameters.

Figure 3 shows learning curves aggregated over 5 runs with random seeds. For Ferry and Gripper domains (Figure 3

a and b), the reduction of action labels improves sample efficiency by as many as $300,000$ steps. In Blocks and Logistics domains (Figure 3 c and d), the baseline without the label reduction was not able to learn a policy. With a reduced label set, the training becomes feasible. It is clear from these plots that reducing the action label sets yields significant gains in terms of sample efficiency. One possible reason that explains these results is the reduction of invalid actions achieved in these environments. As our approach reduces the action labels while maintaining all the valid actions, the number of invalid actions is reduced. Appendix C presents the amount of reduction in each environment. This phenomenon of deep RL agents showing performance improvement upon reduction of invalid actions is studied in Huang and Ontañón (2022). Well aware of this phenomenon, researchers invest significant effort to manually identify small action spaces in planning domains (Silver and Chitnis 2020; Fern, Yoon, and Givan 2006; Dzeroski, Raedt, and Driessens 2001) and code state-dependent action functions in RL (Boutilier et al. 2018; Huang and Ontañón 2022; Bamford and Ovalle 2021). With our approach, this manual process can be automated for planning domains.

Our results show that even in small-scale problems (with 4–7 objects) action label reduction is beneficial. In large problems (with many objects) our approach can provide tremendous leverage for training RL algorithms, reducing action set by orders of magnitude.

Lifted successor generation Lifted successor generation (Corrêa et al. 2020) finds a set of applicable ground actions in the given state by treating the state as a database and formulating a query from lifted action preconditions. The query result provides tuples of object assignments to the action parameters, which define the ground actions that are applicable in the state. There are several possible ways of exploiting the additional information of the seed parameters for speeding up join computation. The complexity of the query evaluation is measured in terms of the input and output size of the query. With our reduced set of parameters (seed set), the input and the output of the query can be modified and improvement can be achieved in computation time. To modify the output, one can query only for the seed parameters and derive the assignments for non-seed parameters using the sequence of lifted mutex groups.

In our preliminary experiment, we modify the procedure of Powerlifted planner (Corrêa et al. 2020) by preprocessing the tables, hence modifying the input size. We pre-join the precondition tables with the corresponding lifted mutex group table, over non-seed parameters. This allows us to reduce the size of the tables in the query. Figure 4 shows the difference in the size of the tables before the query is performed. The X-axis presents the size of the table in powerlifted and the y-axis presents the size of the table in powerlifted with seeds. So, a point below the diagonal indicates reduced sizes. There are 4914, out of 36097 tables, that undergo size reduction, and often a significant one. In 478 out of 811 problems where the join is performed, at least one table is reduced in size. As known from database literature, reducing the size of the tables can help improve join performance (Ullman 1989). Our initial results, comparing the time taken to perform the join and to generate applicable actions are presented in Appendix C. Rovers domain is skipped as no reduction was obtained in that domain. Note that we do not modify the existing query evaluation process. Optimizing the join query using the cardinality of the relations can potentially further improve the processing time. However, query optimization is out of the scope of the current work. Further research is needed into additional variants of improving the lifted successor generation to make it beneficial in other domains.

5 Related Work

Various approaches have been studied in RL to reduce the action space. Stochastic action sets (Boutilier et al. 2018) and invalid action masking (Huang and Ontañón 2022; Bamford and Ovalle 2021; Kanervisto, Scheller, and Hautamäki 2020) restricts the action selected by an agent to a small subset of actions that are feasible in the given state. This is done by assigning zero probability (or -inf score) to invalid actions. While the stochastic action sets and invalid action masking define a state-dependent subset of feasible actions, our action reduction is independent of the current state.

Another approach to manage a large number of actions in an MDP is by using factored action spaces (Pazis and Lagoudakis 2011; Geißer, Speck, and Keller 2020; Guestrin, Lagoudakis, and Parr 2002). With factored action space, an action is decomposed into multiple components and represented as either a decision tree or a vector. It is straightforward to convert predicate action space (for example, gripper actions $\{\texttt{drop(b1, r2, g1), pick(b2, r1, g2),...}\}$) to a factored action space $(a_0, a_1, \ldots, a_n)$ with a_0 denoting the action identifier (for example, $\texttt{drop}$ or $\texttt{pick}$) and $a_1, \ldots, a_n$, denoting the parameters. Our approach of identifying the parameter seed set can be used to reduce the number of factors in the factored action spaces.

In planning literature, label reduction techniques are used to reduce the number of transition labels in an abstract transition graph (Helmert et al. 2014; Sievers, Wehrle, and Helmert 2014), with the aim to simplify the transition system by creating an equivalence between labeled transitions. Here, the purpose is different: labels of operators that are never applicable together are reduced to the same label while allowing to differentiate between applicable operators in a given state.

6 Discussion and Future Work

In this work, we have introduced definitions of a valid label reduction and applicable operator mutex groups and have shown the connection between the two. We have presented a method for automatically deriving operator label reductions for planning tasks based on operator parameter reduction. For that, a parameter seed set problem was introduced, and a solution to the problem was suggested by translating it to delete-free planning. Our experimental evaluation shows a significant reduction in operator labels when using our approach, across all tested planning domains. This reduction

translates both into improved sample efficiency of standard RL agents and into reduced computation time of identifying applicable ground actions in lifted planning, the two example use cases.

Our method, however, does not guarantee the optimality of the valid reduction size, even for the restricted case considered in this work. Finding provably minimal size reductions is an interesting topic for future research. Further, we barely touched on the possible benefits of operator parameter reduction for classical planning. We have not explored other methods of speeding up successor computation. Finally, exploring the possible benefits of the operator parameter reduction for lifted heuristic computation (Corrêa et al. 2021; Lauer et al. 2021) is of great promise for lifted planning.

References

Bäckström, C.; and Nebel, B. 1995. Complexity Results for SAS$^+$ Planning. *Comput. Intell.*, 11(4): 625–655.

Bamford, C.; and Ovalle, A. 2021. Generalising Discrete Action Spaces with Conditional Action Trees. In *2021 IEEE Conference on Games (CoG)*, 1–8.

Boutilier, C.; Cohen, A.; Hassidim, A.; Mansour, Y.; Meshi, O.; Mladenov, M.; and Schuurmans, D. 2018. Planning and Learning with Stochastic Action Sets. In *IJCAI*, 4674–4682.

Corrêa, A. B.; Francès, G.; Pommerening, F.; and Helmert, M. 2021. Delete-Relaxation Heuristics for Lifted Classical Planning. In *ICAPS*, 94–102.

Corrêa, A. B.; Pommerening, F.; Helmert, M.; and Francès, G. 2020. Lifted Successor Generation using Query Optimization Techniques. In *ICAPS*, 80–89.

Dzeroski, S.; Raedt, L. D.; and Driessens, K. 2001. Relational Reinforcement Learning. *ML*, 43(1/2): 7–52.

Fern, A.; Yoon, S. W.; and Givan, R. 2006. Approximate Policy Iteration with a Policy Language Bias: Solving Relational Markov Decision Processes. *JAIR*, 25: 75–118.

Fišer, D. 2020. Lifted Fact-Alternating Mutex Groups and Pruned Grounding of Classical Planning Problems. In *AAAI*, 9835–9842.

Gefen, A.; and Brafman, R. I. 2011. The Minimal Seed Set Problem. In *ICAPS*. AAAI.

Gehring, C.; Asai, M.; Chitnis, R.; Silver, T.; Kaelbling, L. P.; Sohrabi, S.; and Katz, M. 2022. Reinforcement Learning for Classical Planning: Viewing Heuristics as Dense Reward Generators. In *ICAPS*, 588–596.

Geißer, F.; Speck, D.; and Keller, T. 2020. Trial-Based Heuristic Tree Search for MDPs with Factored Action Spaces. In *SOCS*, 38–47.

Guestrin, C.; Lagoudakis, M. G.; and Parr, R. 2002. Coordinated Reinforcement Learning. In *ICML*, 227–234.

Haslum, P. 2011. Computing Genome Edit Distances using Domain-Independent Planning. In *ICAPS 2011 Scheduling and Planning Applications woRKshop*, 45–51.

Helmert, M. 2006. The Fast Downward Planning System. *JAIR*, 26: 191–246.

Helmert, M. 2009. Concise Finite-Domain Representations for PDDL Planning Tasks. *Artificial Intelligence*, 173: 503–535.

Helmert, M.; Haslum, P.; Hoffmann, J.; and Nissim, R. 2014. Merge-and-Shrink Abstraction: A Method for Generating Lower Bounds in Factored State Spaces. *Journal of the ACM*, 61(3): 16:1–63.

Hoffman, M.; Shahriari, B.; Aslanides, J.; Barth-Maron, G.; et al. 2020. Acme: A Research Framework for Distributed Reinforcement Learning. *CoRR*, abs/2006.00979.

Huang, S.; and Ontañón, S. 2022. A Closer Look at Invalid Action Masking in Policy Gradient Algorithms. In *FLAIRS*.

Kanervisto, A.; Scheller, C.; and Hautamäki, V. 2020. Action Space Shaping in Deep Reinforcement Learning. In *2020 IEEE Conference on Games (CoG)*, 479–486.

Lauer, P.; Torralba, Á.; Fišer, D.; Höller, D.; Wichlacz, J.; and Hoffmann, J. 2021. Polynomial-Time in PDDL Input Size: Making the Delete Relaxation Feasible for Lifted Planning. In *IJCAI*, 4119–4126.

Matloob, R.; and Soutchanski, M. 2016. Exploring organic synthesis with state-of-the-art planning techniques. In *Scheduling and Planning Applications woRKshop SPARK at ICAPS*, 52–61.

McDermott, D. V. 2000. The 1998 AI Planning Systems Competition. *AI Mag.*, 21(2): 35–55.

Nelson, M. J. 2021. Estimates for the Branching Factors of Atari Games. In *CoG*, 1–5. IEEE.

Pazis, J.; and Lagoudakis, M. G. 2011. Reinforcement learning in multidimensional continuous action spaces. In *IEEE Symposium on Adaptive Dynamic Programming And Reinforcement*, 97–104.

Sievers, S.; Wehrle, M.; and Helmert, M. 2014. Generalized Label Reduction for Merge-and-Shrink Heuristics. In *AAAI*, 2358–2366.

Silver, T.; and Chitnis, R. 2020. PDDLGym: Gym Environments from PDDL Problems. *CoRR*, abs/2002.06432.

Ullman, J. D. 1989. *Principles of Database and Knowledge-Base Systems, Volume II*. Computer Science Press.