EG-VAR: A Verified Lean 4 Runtime for Empirical-Reasoning Failures in Tool-Using LLMs

Junyu Ren [1]

Abstract

Tool-using LLMs can fail even when every tool call succeeds. A bare tool-using agent hallucinates in two ways: it can cite *evidence* no tool returned, or draw a *deduction* that does not follow from the attested evidence. EG-VAR, a Lean 4 runtime for empirical claims, **eliminates both by construction** on its VERIFIED path (Theorems 3.1 and 3.2), **converting** them into a single residual, the *question-formalization gap*: the LLM may formalize the wrong reading of the natural-language question. It is the only wrong-answer path the gate leaves to the untrusted model, and it too vanishes when the question is supplied already in formal form; abstention is a reported coverage cost, not a failure. Every accepted output ships with a replayable proof and its tool-call evidence; otherwise the system returns a typed ABSTAIN. On TableBench numerical reasoning (n=120), EG-VAR attains 120/120 versus a 95% same-tool baseline. Across 5 counterfactual domains and two models it stays 100% source-faithful; the same-tool baseline drops to 80–90% on the stronger model, which overrides the source more than the weaker one. With an LLM formalizer at deployment, the residual semantic formalization error is 3.3% on Sonnet and 1.7% on Opus.

1. Introduction

Tool-using LLMs increasingly answer empirical questions by consulting external sources, yet tool access alone does not eliminate hallucination. A bare tool-using agent still hallucinates in two ways. *Hallucinated evidence* (an *attestation gap*): the answer rests on an empirical leaf the recorded tool trace does not back. *Hallucinated deduction* (a *deduction gap*): the reasoning that combines attested leaves is never checked, so an unsound step can pass. Both are silent — the tool call still "succeeded."

EG-VAR closes both for the VERIFIED path: mkVerified admits only attested leaves (Theorem 3.1), and the kernel checks each accepted deduction under the declared axioms (Theorem 3.2). It does not make failure vanish; it **converts** the two hallucination modes into a single, localized residual: the *question-formalization gap*. The only wrong answer the untrusted LLM can still produce comes from misreading or mis-translating the natural-language question into the wrong formal goal, localized and auditable in the certificate; it can no longer come from unattested evidence or unchecked deduction. Supplying the question already in formal form removes even this residual (Section 4.1). We evaluate this conversion, rather than reporting one flat hallucination rate.

The taxonomy is tied to minimal reproductions. Counterfactual TableBench variants produce one trigger. These are deliberately simple questions, made counterintuitive by editing the table to contradict world knowledge. Even though the prompt explicitly instructs the model to answer from the table, Sonnet follows its prior at ~12–15% (Section 4.2). Tier 2 residual cases produce another: each case has a replayable Lean trace file in the appendix, so the failure can be rerun without rerunning the LLM. This gives the paper a closed-loop evaluation: generate a claim, inspect the trace, classify the failure, and test whether the runtime gate blocks unsupported verification.

EG-VAR (Evidence-Grounded Verified Agentic Reasoning) turns the taxonomy into a runtime contract. A deterministic tool layer records source observations. A per-source formalization layer maps storage facts into world claims. The Lean 4 kernel supplies the runtime check. An untrusted LLM proposes the formal goal, tool calls, and proof tactic. The mkVerified gate can construct Evidence Verified w only when the proof includes runtime-attested tool evidence. Thus Theorem 3.1 rules out unsupported VERIFIED outputs, while Theorem 3.2 guarantees that every accepted deduction passes the kernel under the declared axioms.

The trace diagnostic is concrete. Each accepted claim ships with the generated Lean proof file and the observation-

[1]Committee on Computational and Applied Mathematics, University of Chicago, Chicago, IL, USA. Correspondence to: Junyu Ren <junyuren@uchicago.edu>.

Accepted to the FAGEN Workshop at ICML 2026. Copyright 2026 by the author.

leaf list: the ordered tool results imported into the proof. A third party can replay the claim offline by re-running Lean against the proof file, audited per-source lifts, and observation leaves; the LLM need not be re-run. For a question like "which entity has property P?", EG-VAR writes a dependent-pair goal $\Sigma\,(e\ :\ \mathrm{String})\,(v\ :\ \mathrm{Value}),\mathrm{Evidence}\,\mathrm{Verified}\,(\ldots\ e\,v)$; the published answer is the first projection of the dependent pair checked by the kernel. If the LLM cannot produce a proof from attested evidence, the output is ABSTAIN.

The verified fix has a coverage trade-off. EG-VAR's output space is typed: VERIFIED with replay artifacts, ABSTAIN when the proof path fails, or a lower evidence grade that downstream code cannot promote to VERIFIED. The system trades unconditional answer coverage for a checkable boundary: unsupported claims surface as typed non-VERIFIED states, with abstention rates reported per source. Tables are the first evaluated substrate, not the conceptual boundary. They are useful because they let us create minimal counterfactual triggers, audit every tool observation, and replay each accepted proof end to end. The same pattern of L1 observations, L2 claims, and audited lifts is intended for SQL views, typed APIs, knowledge graphs, and other sources under a matching attestation regime. Here, L1 means the source-storage vocabulary, L2 means the world-claim vocabulary, and a lift is an audited rule connecting a source observation to a world claim.

Contributions and findings. We make three failure-mode contributions for tool-using LLMs. **(1) Failure conversion and minimal reproductions.** EG-VAR eliminates the baseline's two hallucination modes — hallucinated evidence and hallucinated deduction — by construction on the VERIFIED path, converting them into a single residual — the question-formalization gap, the only wrong-answer path the gate leaves to the untrusted LLM, and one a formal-language question removes. Abstention, including solver ceilings, is a reported coverage cost, not a failure. Each residual case is paired with a replayable Lean trace in the appendix. **(2) Trace diagnostics.** Each VERIFIED output is shipped with replayable Lean artifacts: proof file, observation leaves, and per-source lifts. **(3) Verified fixes with verifiable trade-offs.** The only path to VERIFIED is the mkVerified gate plus the kernel runtime check; otherwise the system returns ABSTAIN, and the coverage trade-off is reported per source as an abstention rate. Empirically, on TableBench unambiguous claims (n=120), EG-VAR attains 120/120 under fixture-committed formalization (observed 100%, Wilson 95% LB $\approx$ 96.9%). The same-tool baseline shares the tool surface and model but has no fixed-goal kernel contract; it reaches 114/120 (95.0%). A table-only baseline reaches 107/120 (89.2%). On Tier 1.5 counterfactual panels (n=20 per panel, two models, two injection regimes), EG-VAR remains observed 100% source faithful (Wilson 95% LB $\approx$ 83.9%). The more serious failure is on the stronger model: even with the same tool surface it overrides the source and drops to 80–90%, while the weaker model stays tool-deferent at 100%. Without tools, both drop, to 40–80%. Under full Tier 2 deployment (n=120), residual semantic formalization error is 3.3% on Sonnet and 1.7% on Opus; logged ambiguous readings (4.2%) sit on the same formalization axis, and abstention is reported as coverage.

Mapping to FAGEN. The three contributions instantiate the FAGEN triad. *Find* a failure: the Tier 2 decomposition (Section 4.3) names the residual case left after the VERIFIED gate converts hallucinated evidence and hallucinated deduction into a single semantic formalizer error, with abstention reported as coverage. *Reproduce* it: each Tier 1.5 counterfactual and each Tier 2 residual case ships as a minimal trigger, with a fixed table edit and a logged trace. The failure can then be re-elicited without re-running the LLM. *Trace* it: every accepted run produces a Lean proof file plus an observation-leaf list (Section G), making each failure a typed, replayable artifact. *Fix* it with a verifiable trade-off: for the VERIFIED path, mkVerified admits VERIFIED only from attested evidence and the kernel checks each deduction, so the two baseline gaps become a single formalizer residual; unprovable cases return an honest ABSTAIN, the coverage trade-off reported per source rather than absorbed into headline accuracy.

2. Related Work

EG-VAR sits at the intersection of four threads (Table 1): studies of conflicts between model priors and sources, symbolic factual verification, LLM theorem proving, and execution attestation. Each covers part of the failure story. ClashEval documents source conflict; symbolic verifiers check simplified claims; Lean provers give a strong kernel for self-contained math; attestation systems prove that a run happened. EG-VAR combines these pieces for empirical claims: recorded tool evidence, a Lean kernel, and a typed ABSTAIN state when the proof path fails.

Detailed comparisons, including why self-contained math provers do not cover grounded empirical claims and how our stress tests extend ClashEval (Wu et al., 2024), are in Section A.

3. EG-VAR

3.1. Four-layer stack and trust ledger

EG-VAR separates the agent run into four trust zones. **L1, tool layer**: deterministic source queries produce Attested_T witnesses recording the query, source identity, and result; only the runtime can create these witnesses.

System	Substrate	Evidence input	Checker	Residual risk
TabVer (Aly & Vlachos, 2024)	Nat. logic + arith.	Table cells	Learned NatOp	Silent wrong
ProoFVer (Krishna et al., 2022)	Natural logic	Premises	Shallow symbolic	Silent wrong
FoVer (Pei et al., 2025)	FOL + Z3	Indirect (CoT)	SMT	Consistency $\not\Rightarrow$ grounded
AWS Bedrock (Amazon Web Services, 2024)	Undisclosed	Policy text	Proprietary	Undisclosed
AlphaProof (Google DeepMind, 2024)	Lean 4 (math)	None	Lean kernel	—
DeepSeek-Prover (Xin et al., 2025)	Lean 4 (math)	None	Lean kernel	—
Attestable Audits (Schnabl et al., 2025)	TEE crypto	Exec. bytes	TEE attestation	Attested wrong claim
Proofs of Autonomy (Grigor et al., 2025b)	MPC/TLS / SNARK	Run provenance	Crypto proof	Attested wrong claim
EG-VAR (ours)	**Lean 4 + tool attest.**	**Attested L1→L2 lifts**	**Lean kernel**	**Honest abstention**

Table 1. Prior work by substrate, evidence input, checker, and residual risk under EG-VAR's threat model. To our knowledge, EG-VAR is the only row combining a proof-assistant kernel with tool evidence and honest abstention on rejection.

Threat model (summary). Safety theorems (Theorems 3.1 and 3.2) assume: **Trusted:** Lean 4 kernel, EG-VAR prelude, audited per-source lifts $\Lambda(s)$, deterministic Python runtime. **Untrusted:** LLM analyst/formalizer/solver; they may hallucinate but cannot introduce axioms. **Out of scope:** (i) semantic faithfulness of τ to the NL claim; (ii) a semantically wrong audited lift; (iii) source-data corruption that passes the runtime identity-cell validator. Items (i)–(ii) detailed in Section 5.1. A VERIFIED label is therefore conditional on the trusted runtime, the source adapter, and the audited per-source lifts. EG-VAR does not certify that the natural-language claim was formalized correctly. It certifies only that the formal goal is discharged from attested evidence under the kernel.

L2, per-source formalization: audited lifts map storage facts, such as a table cell value, into world claims such as ArgmaxWhere or SumWhere. **L3, Lean 4 kernel**: the checker type-checks proofs and is the only component that can mint Evidence Verified w. **L4, LLM roles**: analyst, formalizer, and solver propose goals, tool calls, and tactics, but cannot introduce axioms or forge Attested_T. Thus the LLM is checked, not trusted. The trusted artifacts are the kernel, the EG-VAR prelude, the tool adapter, and the audited per-source lifts.

3.2. Tables as formal objects

The source is a trust artifact, not merely context in a prompt. For each table we formalize (i) an L1 storage vocabulary such as CellAt and RowMatches, (ii) an L2 world vocabulary such as HasProperty and ArgmaxWhere, and (iii) a per-source lift catalog saying which L1 facts justify which L2 claims. The lift catalog is the curator's interpretation of the source and is audited once, then reused across claims. Multiple consistent interpretations of a source can exist; EG-VAR requires the chosen one to be explicit and replayable. Longer discussion of rank choices, proof economy, and source semantics is deferred to Sections K.2 and N.

3.3. Evidence grades

Evidence carries a grade $g \in \{\text{VERIFIED}, \text{SUPPORTED}, \text{PLAUSIBLE}, \text{SPECULATIVE}\}$

ordered by reliability. The kernel admits *downgrading* only ($g_1 \succeq g_2$ and e : Evidence g_1 w $\Rightarrow$ downcast e : Evidence g_2 w). There is no rule that upgrades a weaker claim to VERIFIED, so a conclusion cannot outrank its weakest premise. The only constructor for Evidence Verified _ is mkVerified; lower grades come from explicit downgrades, such as staleness or source conflict, or from LLM-proposed heuristic claims admitted only below VERIFIED.

3.4. The mkVerified rule (sole minter of VERIFIED)

Informally: verified evidence exists only if the runtime already supplied an attested payload. The kernel's mint rule is:

```
mkVerified :
  forall (T : ToolId) (q : Query_T)
         (p : Payload_T q)
         (att : Attested_T q p) (w : WProp),
  w in claims (interp_T q p) ->
  Evidence Verified w
```

The hypothesis att : Attested_T q p is the required evidence. Attested_T witnesses are introduced into the proof context only by the runtime in response to a tool call; the solver cannot synthesize them. interp_T q p is the per-tool interpretation function (a small total Lean function) that maps the attested payload to a finite set of L2 world claims; the kernel mints Verified for any w in that set. This is the sole introduction rule for Evidence Verified _ in the calculus; operationally, the runtime emits the corresponding attested leaves and the whitelist replay audit rejects any VERIFIED proof not backed by them.

3.5. Per-source formalization as the curator's interpretive commitment

A tool may attest the storage fact "row r has state 'alabama',", while the user asks the world claim "Alabama has the highest HIV incidence rate." A per-source lift is the audited rule that connects those levels. If the matching lift is absent, the solver has no proof path, the kernel rejects, and the system returns ABSTAIN. A complete worked example is in

Algorithm 1 RUNTIMEVERIFY: operational definition of the runtime loop. Trust-zone labels annotate each step. The Python implementation at `src/python/runtime/pipeline.py` realizes this algorithm.

```
 1: Input: claim c, source s
 2: Output: proof object and verdict
 3: guide ← ANALYST(s, c)                    // untrusted LLM
 4: goalType ← FORMALIZER(c, guide, dict, Λ(s))
 5: evidence ← []; steps ← []
 6: for i = 1 to maxSteps do
 7:     action ← SOLVER(c, goalType, evidence)
 8:     if action is a tool call (t, q) then
 9:         payload ← EXECUTE(t, q)          // audited tool
10:         if payload succeeded then
11:             append (t, q, payload, Λ(s).lift) to evidence
12:         end if
13:     else if action is a proof attempt tac then
14:         leanFile ← BUILD(goalType, Λ(s), evidence, tac)
15:         (ok, out) ← KERNELCHECK(leanFile) // trusted
                                                Lean kernel
16:         if ok then
17:             return (leanFile, evidence, steps), VERIFIED
18:         end if
19:     end if
20:     append (action, feedback) to steps
21: end for
22: return ⊥, ABSTAIN
```

Section H.1.

3.6. Operational proof object and safety theorems

The safety guarantees are stated about the runtime's *proof object*, the tuple returned by `src/python/runtime/pipeline.py`:

$$\mathrm{ProofObject}(s, c) = \langle leanFile,\ evidence,\ steps \rangle$$

Here *leanFile* is the generated Lean module, *evidence* is the time-ordered list of tool payloads imported as observation leaves, and *steps* records solver actions plus kernel feedback. The generation-time gate is the Lean invocation `lake env lean`. A separate replay script (`src/python/runtime/verify_axioms.py`, Section G) recomputes the whitelist check offline for auditors.

Concrete proof artifact. The replay artifact for the Egypt/Yemen counterfactual (Section 4.2) is a single Lean module whose published certificate has the shape:

```
def obs0_l2 : Evidence Verified
    (ArgmaxWhere "july 1, 2013 projection"
        (Cond.or (PropEq "country" "egypt")
                 (PropEq "country" "yemen"))
```

NL claim: *"Which state has the highest HIV rate?"*

Lean goal (LLM formalizer): $\Sigma\, e, v$, ArgmaxWhere "rate" all $e\, v$

Tool call: `argmax_with_id("rate")` — attested payload

L1 fact: MaxCell "rate" $r\, v$ $\wedge$ CellAt r "state" "alabama"

L2 lift (audited per-source): composes → ArgmaxWhere "rate" all "alabama" v

Lean kernel: typechecks `mkVerified` derivation

VERIFIED answer "alabama" / ABSTAIN if kernel rejects

Figure 1. Worked trace for one claim. Untrusted LLM output (white) commits to a goal type; trusted runtime (gray) produces the attested payload, composes it through the audited per-source lift, and the Lean kernel mints VERIFIED iff the derivation type-checks. The first projection of the accepted dependent pair is the published answer.

```
    "yemen" obs0_val) :=
 lift_<srcHash>_argmax_via_country
   ... obs0_row obs0_val obs0_max obs0_cell

def claim_proof : Sigma (e : String),
    Sigma (v : Value), Evidence Verified
     (ArgmaxWhere "july 1, 2013 projection"
        (Cond.or ...) e v) := by
 refine <"yemen", obs0_val, ?_>; exact obs0_l2
```

The runtime-emitted leaves (`obs0_row`, `obs0_val`, ...) carry the `Attested` payload from the L1 tool; the audited per-source lift composes them into an L2 `Evidence Verified` term; and `claim_proof` packages the answer as the first projection of the dependent pair. A third-party auditor with the prelude, the source's lift catalog, and the Lean toolchain can re-typecheck the entire module without re-running the LLM.

Whitelist-compliant module (summary). A generated Lean file is *whitelist compliant for source s* when every axiom in the claim proof's dependency closure belongs to one of four buckets: fixed EG-VAR prelude (**B1**), standard Lean 4 core axioms (**B2**), runtime-emitted observation leaves (**B3**), or audited per-source lifts from $\Lambda(s)$ (**B4**); the closure contains no `sorry` variant and at least one trust artifact. Full bucket schemas, replay mechanics, and guarantee boundaries are in Section P.1.

Theorem 3.1 (No unsupported VERIFIED outputs)**.** *If RUNTIMEVERIFY(s, c) returns (leanFile, evidence, steps) with verdict VERIFIED, and leanFile is whitelist-compliant for s, then every runtime-emitted observation-leaf axiom in the dependency closure of the claim proof is backed by a prior tool execution recorded in evidence, and every remaining axiom dependency lies in the fixed EG-VAR prelude, in the standard Lean 4 core axioms, or in $\Lambda(s)$.*

Theorem 3.2 (No deductive errors)**.** *Every inference step*

that the system accepts as part of a VERIFIED *output type-checks in Lean 4's kernel under the declared axiom set.*

Full proofs (checker-fidelity, emission-discipline, and reserved-name lemmas; complete proofs of Theorems 3.1 and 3.2) plus the emission-site table are in Sections P and P.1. The kernel call inside `run_pipeline` (`lake env lean`) is the runtime deductive gate that emits candidate VERIFIED; the standalone `verify_axioms.py` is the replay-audit gate, run as a post-hoc replay audit that any third party can re-run offline (Sections G and P.1). Theorem 3.1 is conditional on the artifact passing this whitelist audit, so trust-bearing publication of VERIFIED requires both gates: kernel acceptance at runtime and whitelist replay at audit time. Worked examples of attested proofs and per-source lifts are in Sections H and I.

Formalization sources. Tier 1 and Tier 1.5 load gold types τ^{gold} and audited per-source lifts $\Lambda(s)$ from a frozen fixture (proposer–critic–kernel pipeline, no formalizer invoked at evaluation); Tier 2 invokes an LLM formalizer with access to $\Lambda(s)$ but no gold type. Full detail (subagent pipeline, human meta-supervision scope, curator yield, collusion firewall) is in Section G.2.

4. Evaluation: Triggers, Diagnostics, Fixes

We organize evaluation around the FAGEN triad. Tier 1 is the fixture-committed canonical regime and control: on unambiguous claims, the fixed-goal kernel contract closes the residual gap left by tool access alone. Tier 1.5 is the reproducible trigger: counterfactual table edits force a conflict between source evidence and the model's prior. Tier 2 is the deployment diagnostic: the LLM itself proposes the formal goal, so remaining failures expose where the natural-language claim was translated incorrectly rather than where the kernel failed. The first two tiers operate in the pre-formalized regime (gold goal types loaded from the frozen fixture); Tier 2 operates in the deployment reconstruction regime.

Two axes. We separate *formal safety* (the VERIFIED label is kernel-accepted against the committed trust artifacts; Theorem 3.1) from *semantic faithfulness* (the formalized goal τ matches the natural-language claim; measured by `answer_match` against frozen gold answers). Tiers 1 and 1.5 load $\tau = \tau^{\text{gold}}$ from the frozen fixture, so semantic faithfulness holds by construction; Tier 2 invokes the LLM formalizer, and semantic faithfulness becomes the primary empirical question.

Shared setup. Tier 1 and Tier 1.5 share four *rungs* (Table 2). Table-only is single-shot with no tools. Tools-open gives the LLM the full runtime tool surface with no per-

Rung	Tools	Per-source artifact
Table-only	none	— (table only)
Tools-open	full surface	none enforced
Tools-curated	menu-enforced	per-source menu
EG-VAR	menu-enforced	menu + Lean goal + lifts

Table 2. Four-rung ladder isolating tool contribution (Table-only → Tools-open), per-source menu (Tools-open → Tools-curated), and fixed-goal kernel checking discipline (Tools-curated → EG-VAR).

source menu enforcement. Tools-curated enforces the per-source menu, with the same tool surface as EG-VAR. EG-VAR is kernel checked, in fixed goal mode with the curator's typed goal. All rungs use the same model, prompt structure, and answer judge (`answers_match`); EG-VAR additionally requires a `Verified` witness minted by the kernel whose extracted answer agrees with the gold answer. We evaluate two models: Sonnet 4.6 and Haiku 4.5 (a stronger and a weaker model from the same family). All runs use temperature 0, at which EG-VAR is deterministic. We report deterministic single-rep canonical evaluations for EG-VAR, with corroborating multi-rep partial runs (run manifest in Section G).

Rung	Match
Table-only	107/120 (89.2%)
Tools-open	113/120 (94.2%)
Tools-curated	114/120 (95.0%)
EG-VAR	**120/120 (100.0%)**

Table 3. Tier 1 ladder, $n = 120$ unambiguous TableBench claims, Sonnet 4.6, temperature 0.

4.1. Tier 1 canonical regime and control: same tool surface, different contract

Our LLM-based curator pipeline selects $n = 120$ unambiguous TableBench claims spanning argmax, sum, count, top-k, and aggregation shapes; for each claim it produces the typed Lean goal and the per-source lifts (the trust artifact EG-VAR consumes; Section G.2). All four rungs are evaluated on Sonnet at temperature 0. Table 3 reports the headline ladder. EG-VAR attains 120/120 on the gold formalization path (observed 100%, Wilson 95% LB $\approx 96.9\%$), meeting both formal safety and semantic faithfulness. For every claim, the kernel proof passes the whitelist replay (Section G, the formal safety axis). The extracted answer also matches the curator gold for every claim (the semantic faithfulness axis). The Tools-curated rung uses the same tool surface and same model, but without the fixed-goal kernel contract. It plateaus at 114/120 (95.0%) on the latter alone; it has no formal safety surface, because baselines cannot abstain. Removing the per-source menu costs one further claim (Tools-open 113/120), and the single-shot table-only floor is 107/120

(89.2%).

4.2. Reproducible trigger: prior override under source conflict

Tier 1.5 isolates a failure mode the Tier 1 ladder under-counts. The trigger is minimal and replayable: take a real TableBench table and overwrite one or two cell values so the source contradicts the model's world-knowledge prior. For each variant we ask a binary comparison or aggregation claim and classify the output as *source faithful* (matches the table), *prior override* (matches the unmodified real-world value), or *wrong-other*. EG-VAR's 100% result combines source faithfulness with kernel replay; the baselines have no comparable proof artifact.

Minimal trigger. In the country-population counterfactual (panel `V45_D1A`), Egypt's "july 1, 2013 projection" cell is overwritten to 1 while Yemen remains 25,252,000. Asked "Which has a larger july 1, 2013 projection: Egypt or Yemen?", Sonnet Tools-curated reads both cells, then answers "Egypt" 3/3 reps (`prior_override`; logged in `cf_v45_strict_sonnet.tsv`). EG-VAR's proof can only witness Yemen, because the dependent-pair answer is constructed from the attested table payload; the kernel rejects any VERIFIED alternative.

Two flip-magnitude regimes. The *extreme-flip panel* uses reversals larger than a factor of 10 (e.g., Italy GDP $\to$ \$50, Patriots $\to$ 0–16, Sinopec $\to$ \$50) across 5 domains. The *subtle-flip panel* uses 10–25% reversals (Mont Blanc $\to$ 4500 m vs Monte Rosa 4634 m, Madrid GDP 90 vs Berlin 95). It runs on a panel shifted to stable-scalar priors: country populations, EU country area, European city GDP, Forbes top companies, Alpine peak elevations. Each panel is 5 domains $\times$ 2 entity-pair injections $\times$ 3 claim shapes = 30 claims per panel: 20 binary comparison + direction, and 10 cell lookup. The cell lookup set does not trigger prior override and is excluded here. Table 4 reports the n=20 binary comparison + direction cells; both models, 1 rep (temp 0, deterministic).

The extreme-flip panel narrows the residual gap for the same-tool baseline to the single most entrenched prior family (country populations). The subtle-flip panel generalizes prior override across stable scalar domains; tools rescue most of it, and the fixed-goal kernel contract closes the rest.

Why subtle flips matter. Extreme reversals (\$50 GDP, 0–16 records) are easy targets: most evaluators agree the answer should track the table, and even tool-deferent models like Haiku already match it 20/20. The harder case is the 10–25% regime, where the counterfactual lies inside the model's plausible-prior interval. On the Alpine-peaks panel, Mont Blanc is overwritten to 4500 m so that Monte Rosa (4634 m,

Panel	Rung	Sonnet	Haiku
extreme-flip	Table-only	16/20	15/20
	Tools-open	16/20	20/20
	Tools-curated	16/20	20/20
	EG-VAR	**20/20**	**20/20**
subtle-flip	Table-only	10/20	8/20
	Tools-open	18/20	20/20
	Tools-curated	18/20	20/20
	EG-VAR	**20/20**	**20/20**

Table 4. Tier 1.5 counterfactual ladder: source faithful count on binary comparison and direction claims, n=20 per panel (temp 0, 1 rep). Residual = prior override (no wrong-other cases). EG-VAR 20/20 corresponds to a Wilson 95% lower bound of approximately 83.9%; the absolute zero residual is observed, not asymptotic.

unmodified) becomes the source-faithful argmax. This holds despite the world-knowledge prior that Mont Blanc is the highest Alpine peak. The same-tool baseline reads both rows but resolves the comparison from prior more often than from the cell, especially on Sonnet under binary-comparison framing. EG-VAR forces the question through the table-shape lift. Any VERIFIED answer must be the dependent-pair witness of an `ArgmaxWhere` term whose value is drawn from an attested `MaxCell` payload. At runtime, the argmax cell value is 4634 m at row `monte_rosa`. Mont Blanc is not eligible to be the witness; the kernel rejects any alternative proof. The mechanism is the same on both flip regimes; the subtle-flip panel shows it survives when the prior is not dominated.

Per-claim robustness axes (authority cue, model strength, domain coverage) and the failure taxonomy for the same-tool baseline are in Section E.1.

4.3. Trace diagnostic: deployment with an LLM formalizer

Tier 1 and Tier 1.5 evaluate the fixture-committed, pre-formalized regime: each claim arrives with a frozen Lean goal type and audited per-source lifts, so no claim-level LLM formalizer is invoked at evaluation (Section 3.6). This is the canonical regime for sources that publish formalized claims alongside data. Tier 2 evaluates the deployment reconstruction regime: only the natural-language claim is published, and the runtime invokes the LLM formalizer (Section 3.6) to propose `lean_goal_type` per claim, then proceeds with the same analyst, formalizer, solver, and kernel loop. No curator interaction occurs at runtime.

Setup. n=120 claims, same TableBench curated fixture. Sonnet 4.6 at temperature 0. Pipeline: analyst $\to$ formalizer $\to$ solver. The audited per-source formalization $\Lambda(s)$ is still loaded; only the claim-level goal type is LLM-proposed. We classify every output into one of six reporting categories us-

Category	Sonnet	Opus
Correct	85.8%	89.2%
Ambiguous claim (logged)	4.2%	4.2%
Semantic formalizer error	**3.3%**	**1.7%**
Honest abstain	2.5%	5.0%
Solver / formalizer ceiling	4.2%	0.0%

Table 5. Tier 2 decomposition, n=120. Two cases where EG-VAR's proof exposed a defective benchmark gold (its answer disagreed with a mismatched frozen gold, and is the question-faithful one) are counted as *Correct*. Category definitions in Section L.

ing three observables: whether the proposed type equals the curator's gold type, whether the kernel accepts, and whether the extracted answer matches the gold answer (Table 5). These categories make the failure trace inspectable instead of reducing it to a single score.

Formal safety versus semantic faithfulness. Tier 2 measures two distinct properties. *Formal safety* is structural and model-independent: every VERIFIED proof still depends on an attested tool leaf, regardless of which LLM proposed the goal type (Theorem 3.1). *Semantic faithfulness* is operational and model-dependent: it measures whether the LLM-proposed goal matches the frozen reading of the claim. Table 5 reports the semantic-faithfulness axis per model; the *Semantic formalizer error* row is the pure formalizer-error rate.

Worked residual case (idx 61, dropped `TopK`). The kernel can accept a perfectly valid proof of the wrong question. For the claim "What is the average market value of the top 5 companies in the oil and gas industry?", the fixture-standard goal type and the runtime-emitted goal type differ at one node:

```
gold:    TopKMeanWhere "market value" 5
             (PropEq "industry" "oil and gas") ans
emitted: MeanWhere "market value"
             (PropEq "industry" "oil and gas") ans
```

The runtime formalizer dropped the top-5 constraint; its `ambiguous_terms` log records the choice as deliberate, not an oversight. The kernel checked the proof against the emitted goal, the L1 tool returned the correct mean ($1208/5 \approx 241.6$ over the industry filter), and the `mkVerified` gate minted VERIFIED. The fixture answer is 276.06. No deductive step is wrong. The failure is that the formalizer treated "top 5" as rhetorical rather than compositional. The per-source menu offered the right operator, but it was not consulted at the operator-selection step. Replay shows this directly. The published proof certificate has the `MeanWhere` type. A downstream auditor can therefore detect the discrepancy by comparing the certificate's goal against the gold type before consuming the answer (full case study in Section I.2). This is what the residual taxonomy is meant to

expose: a typed disagreement that survives runtime acceptance, rather than a silent wrong answer.

Trigger replay under full automation. To test the deployment reconstruction regime against the same Tier 1.5 trigger, we re-run Tier 2 Sonnet on the extreme-flip panel, restricted to binary comparison and direction claims (n=20, with prior override injected into the tables). Every claim produces a source faithful VERIFIED output (**20/20 SF**), with the extracted answer matching the table-injected answer rather than the model's world-knowledge prior. The Tier 1.5 same-tool baseline drops to 16/20 on the same extreme-flip tables (Section 4.2); the deployment reconstruction regime matches EG-VAR's pre-formalized rung on this subset.

Failure modes by regime. Table 6 places the failure modes of empirical question answering side by side across three regimes: a bare tool-using agent, EG-VAR with a natural-language question, and EG-VAR with the question already in formal language. The kernel and attestation eliminate the unsupported-evidence and unsound-reasoning failures in both EG-VAR regimes (Theorems 3.1 and 3.2). A formal-language question additionally eliminates misunderstanding the question and formalization mistakes: this is the fixed-goal regime (Tier 1), which leaves no failure mode within the audited trusted base. With a natural-language question (deployment, Tier 2), the residual is the question-formalization gap — misreading or mis-translating the question into the wrong formal goal.

5. Discussion

For a deployer, EG-VAR changes the artifact produced per claim. The output is more than an answer string. It is one of three audited states: a VERIFIED answer with replay artifacts, an ABSTAIN, or a lower evidence grade. Downstream code cannot upgrade that lower grade to VERIFIED. This is the practical value of the trigger–diagnostic–fix framing: the same run that exposes a failure also records the boundary that prevents the failure from becoming an unsupported verified claim.

5.1. Limitations

Three scope limitations bound the empirical claims. **(i)** Tier 1/1.5 evaluate the fixture-committed, pre-formalized regime (frozen gold goal type and audited per-source lifts; Section 3.6); Tier 2 evaluates the deployment reconstruction regime where the LLM formalizer runs at runtime. **(ii)** Tools, per-source lifts, and the L1 adapter are trusted; a semantically wrong audited lift can certify a wrong formalized claim (Section 3.5). **(iii)** The evaluated substrate is intentionally single-source TableBench tables, chosen for minimal counterfactual triggers and end-to-end replay; SQL

Failure mode	Bare tool-using agent	EG-VAR, natural-language question	EG-VAR, pre-formalized question
Misunderstanding the question	×	×	–
Reasoning on unsupported evidence[a]	×	–	–
Answering without sound reasoning[b]	×	–	–
Mistake in formalization	–	×	–
Abstention	○	○	○

Table 6. Failure modes that remain possible in each regime. A cross (×) marks a wrong-answer failure that can still occur; a dash (–) a mode that does not arise; a circle (○) abstention, a coverage cost rather than a wrong answer. [a]hallucinated, misread, or mis-transcribed evidence. [b]e.g. prior or common sense over the data.

views, knowledge graphs, multi-source settings, and streaming sources are portability targets under the same L1/L2 architecture, not empirical claims of this paper. Detailed scope is in Section M.

5.2. Governance translation

Theorems 3.1 and 3.2 and the grade rule that permits only downgrades yield three deployable properties.

(G1) Trace diagnostics. Every `Verified` output carries the generated Lean proof file and the observation leaves needed for replay. A third-party auditor with the kernel, per-source lifts, and tool adapter can re-typecheck the claim from the attested payload without re-running the LLM. The trust surface is enumerable: L1 vocabulary, per-source lifts, tool adapter, and kernel. Each per-source lift is audited once and reused across claims.

(G2) Typed uncertainty. Grades make uncertainty inspectable rather than a hidden confidence number. The graded `Evidence g w` object is operationally close to a justification term (Artemov, 2008): evidence is explicit rather than folded into a model's posterior. A PLAUSIBLE output cannot be silently reintroduced downstream as VERIFIED; an auditor can query which claims arrived at which grade and why.

(G3) Honest abstention. A kernel rejection surfaces as a user-visible ABSTAIN, not a silent fallback guess. A downstream policy can require VERIFIED, or admit ABSTAIN as a flagged state, without rebuilding the trust boundary. Abstention rates are measurable per source, so rejection is an auditable system state rather than a learned style of refusal.

Portability beyond tables. The pattern of L1 observations, L2 claims, and audited lifts means "record source observations, map them through audited lifts, and check deductions in the kernel." SQL views, knowledge graphs, and sensor streams can use the same contract under a matching attestation discipline. The empirical panel beyond tables

is future work; the broader substrate argument is in Section K.3.

5.3. Future work scoped to governance reach

Three extensions preserve the same safety boundary: (1) fine-tune the natural-language formalizer on the curator-provided (claim, gold type) corpus, using kernel acceptance as the reward signal, to reduce Tier 2 residual error without weakening Theorem 3.1; (2) add multiple-source attestation with rules that downgrade VERIFIED to SUPPORTED on detected disagreement; (3) run a panel grounded in knowledge graphs and SQL views to test portability. Detail is in Section M.

6. Conclusion

EG-VAR is a deployable contract for empirical claims made by tool-using LLMs, and its first output is a *failure conversion*. A bare tool-using agent hallucinates in two ways — hallucinated evidence and hallucinated deduction — and both are silent. EG-VAR eliminates both on the VERIFIED path, through `mkVerified` and the kernel, and converts them into a single residual, the question-formalization gap: a wrong formal reading of the natural-language question, localized in a replayable certificate — and removed entirely when the question is supplied formally. When no proof path exists the system abstains, a coverage cost rather than a failure. Each such case is also a minimal reproduction, with a replayable Lean trace in the appendix, so EG-VAR turns every accepted claim into an offline-replayable trace diagnostic; the coverage trade-off is reported per source as an abstention rate.

The empirical results support that contract without changing the scope claim. On TableBench Tier 1 (n=120), the fixed-goal kernel contract closes the residual gap left by tool access alone to zero. On Tier 1.5 counterfactuals (n=20 per panel, two flip regimes, two models), EG-VAR stays 100% source faithful. The stronger model is the more serious

case. With the same tool surface it still overrides the source and drops to 80–90%, while the weaker model stays tool-deferent at 100%. Without tools, both drop to 40–80%. With the LLM as formalizer at deployment time, Tier 2 bounds semantic formalization error at 3.3% on Sonnet and 1.7% on Opus, while reporting abstention and solver ceilings as coverage, separately from the residual. This is a closed-loop evaluation: each run produces a claim, a replayable trace, a failure label when needed, and a per-source abstention rate.

Theorems 3.1 and 3.2 are the structural fix: the first rules out hallucinated evidence, the second hallucinated deduction. What remains is not a silent free-text hallucination but an auditable formalization failure or an honest abstention. That is the deployment value: a system can ship per-claim diagnostics and a machine-checkable boundary between verified answers and everything else.

Acknowledgements

I thank the FAGEN reviewers for feedback that sharpened the failure taxonomy and the distinction between attestation and deduction gaps (ruled out by construction) and formalizer mistakes (the measured residual). JR is partially supported by a Vannevar Bush Faculty Fellowship ONR N000142312863.

Impact Statement

This paper presents work whose goal is to advance verifiable empirical reasoning by tool-using LLMs. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Abiteboul, S., Buneman, P., and Suciu, D. *Data on the Web: From Relations to Semistructured Data and XML*. Morgan Kaufmann, 2000.

Achim, T. et al. Aristotle: IMO-level automated theorem proving, 2025. https://arxiv.org/abs/2510.01346.

Alchourrón, C. E., Gärdenfors, P., and Makinson, D. On the logic of theory change: partial meet contraction and revision functions. *The Journal of Symbolic Logic*, 50(2): 510–530, 1985.

Aly, R. and Vlachos, A. TabVer: Tabular fact verification with natural logic. *Transactions of the Association for Computational Linguistics*, 12:1648–1671, 2024. https://aclanthology.org/2024.tacl-1.89/.

Amazon Web Services. What are automated reasoning checks in amazon bedrock guardrails?, 2024. Doc-umentation, accessed 2026-04-23. https://docs.aws.amazon.com/bedrock/latest/userguide/guardrails-automated-reasoning-checks.html.

Anderson, A. R. and Belnap, N. D. *Entailment: The Logic of Relevance and Necessity*, volume 1. Princeton University Press, 1975.

Artemov, S. The logic of justification. *The Review of Symbolic Logic*, 1(4):477–513, 2008.

Barwise, J. and Perry, J. *Situations and Attitudes*. MIT Press, 1983.

Belnap, N. D. A useful four-valued logic. *Modern Uses of Multiple-Valued Logic*, pp. 5–37, 1977.

Bundy, A. The use of explicit plans to guide inductive proofs. In *Proceedings of the 9th International Conference on Automated Deduction (CADE-9)*, volume 310 of *Lecture Notes in Computer Science*, pp. 111–120. Springer, 1988.

Burgess, J. P. and Rosen, G. *A Subject With No Object: Strategies for Nominalistic Interpretation of Mathematics*. Oxford University Press, 1997.

Caminada, M. and Amgoud, L. On the evaluation of argumentation formalisms. *Artificial Intelligence*, 171(5-6): 286–310, 2007.

Chern, I.-C. et al. FacTool: Factuality detection in generative AI — a tool augmented framework for multi-task and multi-domain scenarios, 2023. https://arxiv.org/abs/2307.13528.

Clarke, E., Grumberg, O., Jha, S., Lu, Y., and Veith, H. Counterexample-guided abstraction refinement for symbolic model checking. *Journal of the ACM*, 50(5):752–794, 2003.

Cooper, R. Type theory and semantics in flux. In *Handbook of the Philosophy of Science*, 2012.

de Moura, L. and Ullrich, S. The Lean 4 theorem prover and programming language. In *Proceedings of the 28th International Conference on Automated Deduction (CADE-28)*. Springer, 2021. https://doi.org/10.1007/978-3-030-79876-5_37.

Dhuliawala, S. et al. Chain-of-verification reduces hallucination in large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 3563–3578, 2024. https://aclanthology.org/2024.findings-acl.212/.

Donnellan, K. S. Reference and definite descriptions. *The Philosophical Review*, 75(3):281–304, 1966.

Doyle, J. A truth maintenance system. *Artificial Intelligence*, 12(3):231–272, 1979.

Frege, G. Über Sinn und Bedeutung. *Zeitschrift für Philosophie und philosophische Kritik*, 100:25–50, 1892.

Gao, L. et al. RARR: Researching and revising what language models say, using language models. In *Proceedings of ACL*, 2023.

Goldman, A. What is justified belief? *Justification and Knowledge*, pp. 1–23, 1979.

Google DeepMind. AI achieves silver-medal standard solving International Mathematical Olympiad problems, 2024. https://deepmind.google/discover/blog/ai-solves-imo-problems-at-silver-medal-level/.

Grigor, A., Schroeder de Witt, C., Birnbach, S., and Martinovic, I. VET your agent: Towards host-independent autonomy via verifiable execution traces, 2025a. https://arxiv.org/abs/2512.15892.

Grigor, A., Schroeder de Witt, C., and Martinovic, I. Proofs of autonomy: Scalable and practical verification of AI autonomy. In *Workshop on Technical AI Governance (TAIG@ICML)*, 2025b. OpenReview qxFgQHN69d.

Hu, V. C., Ferraiolo, D., Kuhn, R., Schnitzer, A., Sandlin, K., Miller, R., and Scarfone, K. Guide to attribute based access control (ABAC) definition and considerations. Technical report, NIST SP 800-162, 2014.

Jøsang, A. *Subjective Logic: A Formalism for Reasoning Under Uncertainty*. Springer, 2016.

Kripke, S. A. *Naming and Necessity*. Harvard University Press, 1980.

Krishna, A., Riedel, S., and Vlachos, A. ProoFVer: Natural logic theorem proving for fact verification. *Transactions of the Association for Computational Linguistics*, 10:1013–1030, 2022. https://aclanthology.org/2022.tacl-1.59/.

Lahiri, S. K., McMillan, K. L., Sharma, R., and Hawblitzel, C. Differential assertion checking. In *ESEC/FSE*, 2013.

Li, J., Yu, L., and Ettinger, A. Counterfactual reasoning: Testing language models' understanding of hypothetical scenarios. In *Proceedings of ACL (short)*, 2023. https://aclanthology.org/2023.acl-short.70/.

Mac Lane, S. *Categories for the Working Mathematician*. Springer, 1971.

Mallen, A., Asai, A., Zhong, V., Das, R., Khashabi, D., and Hajishirzi, H. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In *Proceedings of ACL*, 2023. https://arxiv.org/abs/2212.10511.

Marjanović, S. V., Yu, H., Atanasova, P., Maistro, M., Lioma, C., and Augenstein, I. DynamicQA: Tracing internal knowledge conflicts in language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 14346–14360, 2024. https://aclanthology.org/2024.findings-emnlp.838/.

Martin-Löf, P. *Intuitionistic type theory*. Bibliopolis, Naples, 1984.

Montague, R. The proper treatment of quantification in ordinary English. In *Approaches to Natural Language*, pp. 221–242. 1973.

Pei, Y., Du, Y., and Jin, X. FoVer: First-order logic verification for natural language reasoning. *Transactions of the Association for Computational Linguistics*, 13:1340–1359, 2025. https://aclanthology.org/2025.tacl-1.61/.

Quine, W. V. O. *Ontological Relativity and Other Essays*. Columbia University Press, 1969.

Raggi, D., Bundy, A., Grov, G., and Pease, A. Automating change of representation for proofs in discrete mathematics (extended version). *Mathematics in Computer Science*, 10(4):429–457, 2016. https://doi.org/10.1007/s11786-016-0275-z.

Schnabl, C., Hugenroth, D., Marino, B., and Beresford, A. R. Attestable audits: Verifiable AI safety benchmarks using trusted execution environments. In *Workshop on Technical AI Governance (TAIG@ICML)*, 2025. https://arxiv.org/abs/2506.23706.

The Univalent Foundations Program. *Homotopy Type Theory: Univalent Foundations of Mathematics*. Institute for Advanced Study, 2013. https://homotopytypetheory.org/book/.

Varambally, S., Voice, T., Sun, Y., Chen, Z., Yu, R., and Ye, K. Hilbert: Recursively building formal proofs with informal reasoning, 2025. https://arxiv.org/abs/2509.22819.

Wei, J. et al. Long-form factuality in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. https://arxiv.org/abs/2403.18802.

Wu, K., Wu, E., and Zou, J. ClashEval: Quantifying the tug-of-war between an LLM's internal prior and external evidence. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, 2024. https://arxiv.org/abs/2404.10198.

Xin, H. et al. DeepSeek-Prover-V1.5: Harnessing proof assistant feedback for reinforcement learning and monte-carlo tree search. In *Proceedings of ICLR*, 2025. `https://arxiv.org/abs/2408.08152`.

Zhou, J. P., Staats, C., Li, W., Szegedy, C., Weinberger, K. Q., and Wu, Y. Don't trust: Verify — grounding LLM quantitative reasoning with autoformalization. In *ICLR*, 2024. arXiv:2403.18120.

A. Extended related work

Prior-vs-source conflict in LLMs. The closest empirical prior is ClashEval (Wu et al., 2024), which evaluates frontier models on prior-vs-context conflict across six domains. They report >60% prior-override on incorrect retrieved content and that Claude scores highest on prior retention among the frontier families evaluated (Context-Bias 0.157 for Opus, 0.201 for Sonnet, 0.245 for Gemini 1.5, 0.304 for GPT-4o). Our counterfactual stress tests reproduce this ranking quantitatively for Sonnet (Section 4.2). We extend the analysis along two axes prior work has not separated: (i) *authority-cue robustness* — explicit "according to the table" framing rescues some claim shapes but not the strongest prior-bound ones; and (ii) *flip-magnitude regime* — subtle plausible flips trigger prior-override on 4 of 5 stable-scalar domains where extreme flips trigger only one, suggesting the model treats outrageous tool outputs as "alternate scenarios." This disambiguates *dynamicity* (Marjanović et al., 2024) from *popularity* (Mallen et al., 2023) in the trigger pattern, and is consistent with Li et al. (2023)'s finding that counterfactual behavior depends on interactions between world knowledge and contextual cues.

Symbolic factual verification. TabVer (Aly & Vlachos, 2024) and ProoFVer (Krishna et al., 2022) each add a verification step over LLM outputs using natural logic; the verifier is itself a learned or shallow-symbolic system that produces silent-wrong outputs on classifier or premise-mapping error. FoVer (Pei et al., 2025) translates chain-of-thought into first-order logic checked by Z3, but verifies *reasoning consistency* rather than empirical grounding — a CoT can be internally consistent yet factually disconnected from the source. Post-hoc fact-checking pipelines such as FacTool (Chern et al., 2023), RARR (Gao et al., 2023), SAFE (Wei et al., 2024), and CoVe (Dhuliawala et al., 2024) attempt detection after generation rather than structural grounding during generation; they catch some hallucinations but cannot guarantee abstention on ungrounded outputs. Commercial guardrails such as AWS Bedrock's automated reasoning checks (Amazon Web Services, 2024) occupy a related space at the policy-rule layer. EG-VAR differs by replacing the learned/shallow checker with a proof-assistant kernel and a typed evidence calculus, structurally translating kernel rejection into user-visible abstention.

Proof-assistant theorem proving (math). A separate large literature applies LLMs to mathematical theorem proving via Lean, Coq, or Isabelle: AlphaProof (Google DeepMind, 2024), Aristotle (Achim et al., 2025), DeepSeek-Prover (Xin et al., 2025), Hilbert (Varambally et al., 2025). These systems share our trust model (LLM untrusted, kernel trusted) but operate on *self-contained* mathematical claims — proof obligations derivable from the calculus alone, with no external grounding. The novel architectural commitment in EG-VAR is the `mkVerified` mint rule (Section 3.4), which requires an `Attested_T` from the tool runtime as a hypothesis — extending the proof-assistant trust model to empirical claims grounded in deterministic external sources. Autoformalization systems such as DTV (Zhou et al., 2024) use a similar LLM-as- formalizer pattern; Tier 1 and Tier 1.5 evaluate the pre-formalized regime via fixture-committed gold formalizations generated by the proposer–critic–kernel pipeline, isolating the kernel-discipline contribution from the deployment-time formalizer.

Lineage in CS verification. The systems-level concerns that shape EG-VAR — separating semantic specification from proof strategy, refusing to weaken the specification when the proof gets hard, and inheriting kernel-checked discipline from a substrate designed for harder claims — are old questions in the verification literature. Raggi et al. (2016) formalize that semantically equivalent encodings can have very different proof difficulty, motivating our refusal to add cross-predicate equivalence lemmas in the kernel. Bundy (1988) introduced explicit proof planning, anticipating our formalizer/solver information barrier. CEGAR (Clarke et al., 2003) established the discipline of refining the verification plan, not the semantic target, when proofs fail — the same discipline our masked-table architecture enforces on the formalizer. Verification-aware specification languages (Lahiri et al., 2013) address the same informal-intent to formal-specification gap that our per-source formalization protocol addresses for empirical sources. EG-VAR inherits these moves and applies them at a different boundary: not program correctness, but LLM-mediated empirical claim verification. The novelty is the transfer and recombination, not the invention of the underlying discipline.

Hardware-attested AI verification. Attestable Audits (Schnabl et al., 2025) use Trusted Execution Environments to emit remote-attestation signatures binding $Hash(\text{model})$, $Hash(\text{audit code})$, and a benchmark digest, proving that approved bytes executed on approved inputs. Proofs of Autonomy (Grigor et al., 2025b) use MPC-TLS, SNARKs, or TEEs to prove with negligible forgery probability that a given output trace was produced by a configured agent rather than a malicious host (see also Grigor et al., 2025a). Both verify execution provenance — *who* ran the computation, on *what* bytes — not whether the computation's claims are true. EG-VAR is complementary: we typecheck a deductive derivation of each empirical claim from attested tool payloads, ruling out verified hallucinations at the logical level rather than the cryptographic level. An

EG-VAR runtime could in principle run inside such an enclave for stack composition.

B. Per-claim diff for the Tier 1 ladder

The supplement includes `scripts/tier1/build_baseline_ladder_csv.py`, which generates `baseline_ladder_per_claim.csv` from the four E1 rung JSONLs: one row per Tier 1 claim with the goal type, gold answer, and per-rung (Table-only / Tools-open / Tools-curated / EG-VAR) status, answer string, and match flag. The 6 claims that distinguish EG-VAR from Tools-curated are flagged in the output.

C. The EG-VAR Lean 4 library

The EG-VAR prelude is shipped as a self-contained Lean 4 library at `src/lean/` with a Lake build (`lakefile.toml`). The library is the kernel-trusted portion of the trust ledger (Section 3.1): every generated claim module imports it verbatim, and Theorem 3.1's whitelist-bucket **B1** refers to its declarations. This appendix documents the module layout, the extension surface, and the third-party replay-audit contract.

Module layout. The library root `EGVar.lean` re-exports eight modules:

- `EGVar.Basic` — sorts and kernel mint rule: the abstract `WProp` world-proposition sort, the `Grade` inductive (`Speculative` ≺ `Plausible` ≺ `Supported` ≺ `Verified`) with meet/join lattice laws, the `Evidence` family, `Attested_T`/`ClaimTag_T`/`claimWProp`, and the sole `Verified`-minter `mkVerified`. Contains `downcast` (the only grade-weakening step) and the common-sense `CSAttestation` / `mkPlausible` path.

- `EGVar.Safety` — the structural lemmas used in Section P (evidence-closure discipline, downcast non-upgrade).

- `EGVar.TableL1` — L1 storage-vocabulary shells: `RowHandle`, `CellAt`, `Cond` constructors (`all`, `propEq`, `propContains`, `propGte`, `and`, `or`), and the L1 predicate shells (`SumCells`, `CountCells`, `CountDistinctCells`, `MeanCells`, `MaxCellValue`/`MinCellValue`, `MaxCell`/`MinCell`, `TopK*Cells`, `BottomK*Cells`).

- `EGVar.WorldOntology` — L2 world-property predicates: `HasProperty`, `Value` (with `asRat`, `ValueGt`), and the L2 predicates that per-source lifts target (`SumWhere`, `CountWhere`, `MeanWhere`, `MaxWhere`/`MinWhere`, `ArgmaxWhere`/`ArgminWhere`, `TopK*Where`, `BottomK*Where`). This module defines the vocabulary in which $\Lambda(s)$ entries are phrased.

- `EGVar.WorldRules` — structural world-proposition combinators (`PLift` propositional lifting, `PProd` conjunction as Sigma-tail, sigma-binding utilities).

- `EGVar.Tactics` — proof-tactic helpers used by the solver (Sigma-witness `refine` patterns, `exact` sugar for L2 discharge).

- `EGVar.Ontology`, `EGVar.Rules` — legacy weather/finance domain axioms kept for backward compatibility with Phase 1 fixtures; not imported by Tier 1/1.5/2 generated modules.

Library build. The Lake manifest declares a single library target `EGVar` and an executable target `egvar` (rooted at `Main.lean`) for interactive smoke-testing. A third-party user runs `lake build` once to compile the library, then `lake env lean <generated_claim>.lean` to elaborate a generated proof against the prelude. The runtime orchestrator invokes exactly this command at `pipeline.py:4428`; the replay-audit script `verify_axioms.py` invokes the same elaboration with additional `#print axioms` processing.

Extension surface. Adding a new tool to EG-VAR reduces to three kernel-level steps, each kernel-checked: (i) declare a new `ToolId` (a pure identifier) and its `Query_T` and `Payload_T` families in a user-supplied module; (ii) extend the L1 predicate menu in the style of `EGVar.TableL1` if the tool exposes a new storage shape; (iii) add the corresponding L2 predicates and per-source lifts targeting them in the style of `EGVar.WorldOntology`. The mint rule `mkVerified` is unchanged: every new tool reuses the same `Evidence` `Verified`-constructor path and cannot weaken Theorem 3.1. Adding a new ontology role-slot (entity or property) is purely data: both are `String` literals under R5/R10 per Section 3.5 and require no kernel changes.

Third-party replay-audit contract. A deployment that publishes EG-VAR-generated answers as trust-bearing artifacts must publish the following bundle for each answer: (a) the generated `.lean` module (the *leanFile* field of the proof object, Section 3.6); (b) the pinned commit hash of the EG-VAR library and of `data/tier1_table_formalizations.json`; (c) the corresponding entry of the evidence log describing which tool executions backed the observation-leaf axioms. Any third party holding this bundle and a Lean 4 toolchain can re-run the audit by cloning the EG-VAR library at the pinned commit, running `lake build`, then running `python -m runtime.verify_axioms <claim_module>.lean` (which invokes the kernel, reads `#print axioms`, and checks the bucket predicate); no LLM is invoked during replay. We treat this contract as central to the paper's *attestable* claim; the library is designed so that the boundary between trusted and untrusted artifacts is mechanically checkable offline, not contingent on the original generation pipeline being available.

Line counts. The eight modules total ≈1.35 kLOC: `Basic` 192, `Ontology` 210 (legacy), `Rules` 148 (legacy), `Safety` 86, `TableL1` 134, `Tactics` 217, `WorldOntology` 278, `WorldRules` 82. Excluding the two legacy modules the active prelude is ≈1.0 kLOC. This is the full trusted Lean code that a third-party auditor must read to evaluate Theorem 3.1's **B1** bucket; the other three buckets (**B2–B4**) are verified by the mechanical `verify_axioms.py` predicate.

C.1. Code listings

We reproduce the key signatures so that the main-text references to `Evidence`, `mkVerified`, `Cond`, `HasProperty`, `ArgmaxWhere`, and `ValueGt` typecheck against the actual kernel definitions imported by every generated proof.

Sorts and the kernel mint rule (`src/lean/EGVar/Basic.lean`).

```
-- World propositions: separate sort from Prop
opaque WProp : Type

-- Evidence grades, ordered Verified > ... > Speculative
inductive Grade where
  | Verified
  | Supported
  | Plausible
  | Speculative

-- Indexed evidence type
opaque Evidence : Grade -> WProp -> Type

-- Sole minter of Evidence Grade.Verified
axiom mkVerified
  {T : ToolId} {q : Query_T T} {p : Payload_T T q}
  (att : Attested_T T q p)
  {w : WProp}
  (mem : ClaimOf w (interp_T T q p)) :
  Evidence Grade.Verified w

-- Downcast: only direction
axiom downcast {g1 g2 : Grade} {w : WProp}
  (h : g1 >= g2) (e : Evidence g1 w) :
  Evidence g2 w
```

World ontology (`src/lean/EGVar/WorldOntology.lean`).

```
-- Value type: numeric via Rat, or string identifier
inductive Value where
  | int  (n : Int)
  | rat  (r : Rat)
  | str  (s : String)

-- Core L2 world facts
axiom HasProperty
  (entity : String) (property : String)
  (value : Value) : WProp
```

```
axiom Relation
  (subject : String) (rel : RelName)
  (object : String) : WProp

-- Aggregate predicates
axiom SumWhere    (col : String) (c : Cond) (v : Value) : WProp
axiom CountWhere  (col : String) (c : Cond) (n : Value) : WProp
axiom MeanWhere   (col : String) (c : Cond) (v : Value) : WProp
axiom MaxWhere    (col : String) (c : Cond) (v : Value) : WProp
axiom MinWhere    (col : String) (c : Cond) (v : Value) : WProp

-- Entity-anchored aggregate (level 3 of App H hierarchy)
axiom ArgmaxWhere
  (col : String) (c : Cond)
  (entity : String) (v : Value) : WProp
axiom ArgminWhere
  (col : String) (c : Cond)
  (entity : String) (v : Value) : WProp

-- Decidable Prop-level value comparisons
def ValueGt (a b : Value) : Prop :=
  match a.toRat, b.toRat with
  | some x, some y => x > y
  | _, _ => False
-- (analogous: ValueLt, ValueGte, ValueLte, ValueEq;
-- all carry Decidable instances)

-- Composable filter
inductive Cond where
  | propEq       (col : String) (v : Value) : Cond
  | propGt       (col : String) (v : Value) : Cond
  | propLt       (col : String) (v : Value) : Cond
  | propGte      (col : String) (v : Value) : Cond
  | propLte      (col : String) (v : Value) : Cond
  | propContains (col : String) (v : Value) : Cond
  | and (c1 c2 : Cond) : Cond
  | or  (c1 c2 : Cond) : Cond
  | not (c : Cond)     : Cond
  | all                : Cond
```

L1 storage primitives (`src/lean/EGVar/TableL1.lean`).

```
-- Row-handle (opaque): the per-source lift binds to it
opaque RowHandle : Type

-- L1 facts: tools attest these directly
axiom CellAt
  (r : RowHandle) (col : String) (v : Value) : WProp

axiom MaxCellValue
  (col : String) (c : Cond) (v : Value) : WProp
axiom MinCellValue
  (col : String) (c : Cond) (v : Value) : WProp

-- Row-anchored aggregates: identify which row achieves the max/min
axiom MaxCell
  (col : String) (c : Cond)
  (r : RowHandle) (v : Value) : WProp
axiom MinCell
  (col : String) (c : Cond)
  (r : RowHandle) (v : Value) : WProp
```

Per-source lift example (curated for the lunar-craters table).   The lift binds an L1 `MaxCell` witness with an L1 `CellAt` witness on the "name" column to mint an L2 `ArgmaxWhere` claim:

```
axiom craters_lift_argmax_via_name_proj
  (col : String) (c : Cond)
  (r : RowHandle) (name : String) (v : Value) :
    Evidence Grade.Verified (MaxCell col c r v) ->
    Evidence Grade.Verified
      (CellAt r "name" (Value.str name)) ->
    Evidence Grade.Verified
      (ArgmaxWhere col c name v)
```

This is the curator's interpretive commitment for this table: "name" is the row-identifying column, so an `argmax_with_id` tool result lifts uniquely to an `ArgmaxWhere` claim under any `Cond`. A different table whose row-identifying column is, say, `state` carries its own analogous lift; the two are independent.

D. Per-source lift catalog (countries-population table)

To make "per-source formalization is the trust artifact" concrete, we reproduce the lift catalog the curator pipeline produced for the countries-population table (`04744378...` in TableBench). This is the table that all of no-cue pilot, authority-cued pilot, and subtle-flip panel D1 use, so the catalog underpins the empirical claims in Section 4.2. The full catalog has 63 lifts; we show one representative per L2 predicate cluster.

Curator's interpretation declaration. "Country populations 2013. Identity column = `country (or dependent territory)`. Numeric columns: rank, july 1 2013 projection, % of pop, average relative annual growth (%), average absolute annual growth (all strict numerics)."

Aggregate-only lifts (level 1 in App H hierarchy). One lift per (column, aggregate operation) pair. All have the same shape: L1 column-strict aggregate → L2 `*Where` claim. Examples on the population column:

```
axiom lift_04744378_pop_sum
  (c : Cond) (v : Value) :
    Evidence Grade.Verified
      (SumCells "july 1 , 2013 projection" c v) ->
    Evidence Grade.Verified
      (SumWhere "july 1 , 2013 projection" c v)

axiom lift_04744378_pop_mean
  (c : Cond) (v : Value) :
    Evidence Grade.Verified
      (MeanCells "july 1 , 2013 projection" c v) ->
    Evidence Grade.Verified
      (MeanWhere "july 1 , 2013 projection" c v)

axiom lift_04744378_pop_max
  (c : Cond) (v : Value) :
    Evidence Grade.Verified
      (MaxCellValue "july 1 , 2013 projection" c v) ->
    Evidence Grade.Verified
      (MaxWhere "july 1 , 2013 projection" c v)

axiom lift_04744378_pop_count_where
  (c : Cond) (v : Value) :
    Evidence Grade.Verified
      (CountCells "july 1 , 2013 projection" c v) ->
    Evidence Grade.Verified
      (CountWhere "july 1 , 2013 projection" c v)
```

Analogous lifts exist for `MinWhere`, `TopKSumWhere`, `TopKMeanWhere`, `BottomKSumWhere`, `BottomKMeanWhere`, and `CountDistinctWhere`.

Entity-anchored lifts (level 3 in App H hierarchy). The curator commits that `country (or dependent territory)` is the row-identifying column. Each row-identifying lift takes an L1 row-anchored aggregate (`MaxCell` / `MinCell`) plus an L1 `CellAt` on the identity column to mint an `ArgmaxWhere` or `ArgminWhere` L2 claim.

```
axiom lift_04744378_pop_argmax_via_country
  (col : String) (c : Cond)
  (r : RowHandle) (name : String) (v : Value) :
    Evidence Grade.Verified (MaxCell col c r v) ->
    Evidence Grade.Verified
      (CellAt r "country (or dependent territory)"
               (Value.str name)) ->
    Evidence Grade.Verified
      (ArgmaxWhere col c name v)

axiom lift_04744378_pop_argmin_via_country
  (col : String) (c : Cond)
  (r : RowHandle) (name : String) (v : Value) :
    Evidence Grade.Verified (MinCell col c r v) ->
    Evidence Grade.Verified
      (CellAt r "country (or dependent territory)"
               (Value.str name)) ->
    Evidence Grade.Verified
      (ArgminWhere col c name v)
```

The argmax/argmin lifts are parametric over the measure column — one lift per identity column suffices to cover argmax claims on any numeric column, which is why the full catalog has 5 entity-anchored entries (one per identity choice), not 5×5.

Cell-lookup lift. A single lift mints `HasProperty` claims by composing two L1 `CellAt` attestations: the entity at row r in the identity column equals e, and the value at row r in the measure column equals v.

```
axiom lift_04744378_pop_cell_lookup
  (e : String) (col : String)
  (r : RowHandle) (v : Value) :
    Evidence Grade.Verified
      (CellAt r "country (or dependent territory)"
               (Value.str e)) ->
    Evidence Grade.Verified (CellAt r col v) ->
    Evidence Grade.Verified
      (HasProperty e col v)
```

What this catalog buys (and what it doesn't). Composition is by lift: any L2 claim using `SumWhere`, `MeanWhere`, `MaxWhere`/`MinWhere`, `ArgmaxWhere`/`ArgminWhere`, `CountWhere`, `TopKSumWhere`, etc. over a numeric column listed above will type-check. A claim using a predicate not in the catalog — say `Relation` (the table has no relational structure) or `ArgmaxWhere` on a non-numeric column — has no L2 path; the solver cannot construct `Evidence Verified` for it, and the system abstains. The catalog is the table's L2 *commitment boundary*: claims inside compose; claims outside abstain. Adding a new claim shape requires adding a new lift (curation surface), not relaxing the kernel discipline.

E. Tier 1.5 per-claim data, ablations, and pre-registration

E.1. Robustness axes and failure taxonomy

Three robustness axes. Three additional ablations strengthen the discriminator (full per-claim breakdowns below): **(i) Authority cue.** On the no-cue pilot countries-population pilot, prefixing every claim with "According to the table below, ..." rescues some claim shapes (yes/no thresholds, 3-way smallest) but the binary compare V3_C1 (Egypt vs. Yemen, table-injected) stays 0/3 source-faithful on both Tools-curated and Tools-open with the cue. **(ii) Model strength.** Haiku 4.5 is fully tool-deferent on Tools rungs (90/90 in every cell); Sonnet 4.6 prior-overrides even with tools (residual concentrated on countries-pop and Madrid-vs-Berlin GDP). The kernel-vs-baseline gap is therefore largest exactly where parametric priors are strongest — consistent with Wu et al. (2024) placing Claude with the highest prior retention among frontier families. **(iii) Domain coverage.** Under extreme flips, Sonnet prior-override concentrates on country populations only (other 4 extreme-flip panel domains 100% SF on Tools-curated). Under subtle flips, the same-tool baseline fails on 4 of 5 subtle-flip panel domains on Table-only — multi-domain replication. Tools rescue most subtle-flip failures on Tools rungs; the kernel closes the residual.

Failure-mode taxonomy. Of the 6/90 Tools-curated failures on subtle-flip panel Sonnet, all are binary-compare prior-overrides; EG-VAR resolves them by minting from the attested cell-lookup pair via a per-source `ArgmaxWhere`-with-disjunction lift. Cell-lookup and sum-aggregation control claims are 100% source-faithful on every Sonnet rung, including Table-only — consistent with the literature finding that pure information-retrieval is a weaker prior trigger than relational comparison.

E.2. Per-(domain, shape) prior-override table

Table 7 reports per-(domain, shape) prior-override counts for Sonnet on the extreme-flip panel (extreme) and subtle-flip panel (subtle) panels, across Table-only, Tools-curated, and Tools-open. Each cell is `pair_A_PO + pair_B_PO` out of 3 reps each (so 6 trials total per cell). Empty entries are `0/6`. This breakdown is what the main text's "three robustness axes" paragraph (Section 4.2) summarises.

Panel	Domain	Shape	Table-only PO	Tools-open PO	Tools-curated PO
extreme-flip panel (extreme)	D1 countries-pop	B	3+3	3+3	3+3
	D1 countries-pop	D	3+2	3+3	3+2
	D1 countries-pop	C	—	—	—
	D2–D5 (others)	B/D/C	—	—	—
subtle-flip panel (subtle)	D1 countries-pop	B	3+3	3+0	3+0
	D1 countries-pop	D	3+3	—	—
	D2 EU area	B	0+3	—	—
	D3 city GDP	B	0+3	0+3	0+3
	D3 city GDP	D	0+3	—	—
	D4 Forbes	B	3+0	—	—
	D5 Alpine peaks	B	0+3	—	—
	D5 Alpine peaks	D	0+3	—	—

Table 7. Per-(domain, shape) prior-override counts on Sonnet, Tier 1.5 panels extreme-flip panel + subtle-flip panel. Each cell is `pair_A + pair_B` out of 3 reps each. Domain abbreviations: D1 countries-population, D2 EU country area, D3 European city GDP, D4 Forbes top global companies, D5 Alpine peaks. Shapes: B binary-compare, D direction (larger/smaller), C cell-lookup or sum control. **Reading:** extreme-flip prior-override concentrates on countries-pop only (other 4 extreme-flip panel domains are 100% SF on Sonnet). subtle-flip prior-override generalises across 4 of 5 subtle-flip panel domains on Table-only; on Tools rungs (with tool access) it survives only on countries-pop and city-GDP (Madrid vs Berlin), the two strongest- prior-anchor pairs. EG-VAR is 100% source-faithful on the in-calculus shape-B and shape-C subset across both panels.

What the breakdown reveals. The narrowing $\rightarrow$ replication arc the main text claims is visible row-by-row. Under extreme-flip flips, all PO concentrates on D1 (countries-pop) regardless of rung. Under subtle-flip flips, Table-only PO spreads to 4 of 5 domains (D1, D2, D3, D5 trip; only D4 is clean on Table-only pair-B but trips on Table-only pair-A); but tools rescue all PO except on D1 (Egypt-Yemen) and D3 (Madrid-Berlin) — the two canonical strong-prior pairs. The same-tool baseline is therefore not just bounded but *specifically* bounded: it converges on the two pairs whose parametric prior is most entrenched.

E.3. Authority-cue ablation: no-cue pilot vs authority-cued pilot per-claim

Table 8 reports per-claim source-faithful (SF) / prior-override (PO) counts on the no-cue pilot countries-population pilot *without* an authority cue (no-cue pilot, 12 base claims) and *with* an authority cue (authority-cued pilot, "According to the table below, . . ." prefix on the same 12 claims). The strongest discriminator is V3_C1 (binary compare "which country has a larger population: Egypt or Yemen?"), which stays 0/3 SF on every Tools rung even with the cue. EG-VAR goes 3/3 SF on the same V3_C1 claim (see Section I for the trace).

Why V3_C1 is the canonical hard case. One natural response to a prior-override finding is "the model was not told to use the table." The authority-cued pilot ablation explicitly includes an "according to the table" anchoring cue in the prompt. Sonnet still selects the prior on V3_C1, 3/3 reps, on both Tools-curated (menu-enforced) and Tools-open (full tool surface). The kernel discipline closes this gap structurally — not because the LLM understands the cue better, but because the proof body `refine ⟨''yemen'', ...⟩` typechecks only when the attestation is `yemen`.

Claim	Shape	no-cue TC	no-cue TO	cued TC	cued TO	cued T-only
V3_C1	binary-compare	**0/3 (3 PO)**	**0/3 (3 PO)**	**0/3 (3 PO)**	**0/3 (3 PO)**	**0/3 (3 PO)**
V3_C2	boolean threshold	2/3 (1 PO)	1/3 (2 PO)	3/3 SF	2/3 (1 PO)	0/3 (3 PO)
V3_C3	negation compare	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C4	rank position	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C5	3-way compare	3/3 SF	3/3 SF	3/3 SF	3/3 SF	0/3 (3 PO)
V3_C6	threshold count	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C7	categorical y/n	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C8	ranking	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C9	implicit compare	1/3 (2 PO)	0/3 (3 PO)	3/3 SF	3/3 SF	0/3 (3 PO)
V3_C10	diff vs literal	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C11	cell lookup	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
V3_C12	sum aggregation	3/3 SF	3/3 SF	3/3 SF	3/3 SF	3/3 SF
Totals		30/36 (83.3%)	28/36 (77.8%)	33/36 (91.7%)	32/36 (88.9%)	23/36 (63.9%)

Table 8. Per-claim source-faithfulness on the countries-population counterfactual pilot, comparing the no-cue baseline with the authority-cued version ("According to the table below, . . ." prefix). Columns: **TC** = Tools-curated, **TO** = Tools-open, **T-only** = Table-only. Sonnet 4.6, temperature 0, 3 reps per cell. The cue rescues V3_C2 (boolean threshold) and V3_C9 (implicit direction) on Tools rungs but does *not* rescue V3_C1 (binary compare Egypt vs. Yemen) on any rung; Table-only (no tools) is unaffected by the cue's claim-level intent on the binary-compare case (V3_C1 still 3 PO) and additionally regresses on V3_C2, V3_C5, and V3_C9 because mental-arithmetic-without-tools is prior-vulnerable on subtle compares. EG-VAR is 3/3 SF on V3_C1 (Section I) — the strongest possible discriminator.

E.4. Pre-registered success criteria for extreme-flip and subtle-flip panels

The Tier 1.5 extreme-flip panel (extreme flips, 5 domains $\times$ 2 pairs $\times$ 3 shapes = 30 claims) and subtle-flip panel (subtle flips, 5 stable-scalar-prior domains, same shape) were each designed with pre-registered success criteria recorded in `specs/tier1-v4-multidomain-panel.md` before any runs landed. We reproduce them here so the methodology can be audited against the result tables.

Pre-registered metric	Criterion
Tools-curated shape-B PO across 5 domains	$\geq 30\%$ of trials, on $\geq 3/5$ domains
Tools-curated shape-C control PO	$\leq 10\%$ of trials (lookup/aggregation stays SF)
EG-VAR shape-B + C source-faithful	$\geq 95\%$ across all domains
Bare-vs-anchored phrasing delta on shape B	if anchored $\to$ 0% PO on all 5 domains, "kernel discipline" framing becomes "anti-distractibility" instead
Tools-open $\geq$ Tools-curated in shape-B PO	tool surface is not protective

Outcomes against pre-registration. The extreme-flip panel *failed* the first criterion: Tools-curated shape-B PO concentrated on 1/5 domains (countries-pop) under extreme flips, not the 3/5 we pre-committed to. We reported this honestly in the main text ("narrowing" framing in Section 4.2). The failure motivated the subtle-flip panel redesign (subtle flips on stable-scalar priors), where the criterion lands: subtle-flip panel shape-B PO on Table-only reaches 4/5 domains; on Tools rungs it drops to 2 specific pairs (Egypt-Yemen + Madrid-Berlin) but the cross- domain replication is visible.

The shape-C control criterion (PO $\leq 10\%$) holds in both panels across all rungs.

The EG-VAR $\geq 95\%$ criterion is met (100% in every cell on the in-calculus shape-B + C subset).

The authority-cue criterion was *partially* met — anchored phrasing rescued V3_C2 + V3_C9 but not V3_C1; we reframed the finding as "cue rescues some shapes, not the strongest" rather than recategorising the discriminator (Section E.3).

The Tools-open $\geq$ Tools-curated criterion holds on both panels (Table 7).

F. Tier 1 data: fixture properties and 6-claim differential

F.1. The 6-claim differential: where EG-VAR wins on Tier 1

The Tier 1 ladder gap (EG-VAR 120/120 vs Tools-curated 114/120) is 6 claims at fixed tool surface. Table 9 reports exactly which 6 claims EG-VAR wins on, what Tools-curated outputs instead, and which failure mode each represents.

idx	Predicate	Claim (truncated)	Gold	Tools-curated answer (wrong)
12	PProd	Which time has the lowest local magnitude?	27 nov 1954	08:36 (time-of-day)
24	SumWhere	Total population of regions where Manchu % > threshold	3,123,625,869	153,259,452 (subset only)
46	CountWhere	How many individuals have "Number" > 1500?	14	40
52	CountWhere	How many parties have > 10% of total votes?	3	4
67	PProd	Difference in goals between top-scoring forward and top-scoring midfielder	7	6
77	MeanWhere	Average US viewers (millions) for Season 1 episodes	8.45	6.29

Table 9. The 6 Tier 1 claims that distinguish EG-VAR from Tools-curated at fixed tool surface. EG-VAR outputs are kernel-checked Sigma witnesses matching the curator's gold; Tools-curated outputs are free-text answers that fail the answer-match judge.

Failure-mode taxonomy of the 6 wins. **Ambiguity (idx 12)** — "which time" admits two readings: the date or the time-of-day. The curator's typed goal commits to a specific reading ($\text{HasProperty } e \text{ "date" } v$); Tools-curated picks the time-of-day reading and fails the answer-match. Kernel discipline + curator's commitment is what closes this gap, not proof checking alone — this is the "kernelized fixed-goal discipline at fixed tool surface" framing of the §4 result.

Composition arithmetic (idx 24, 46, 52, 67) — Tools-curated issues a partial tool sequence (one filter or one aggregate) and emits a free-text answer composed from incomplete evidence. EG-VAR emits the full PProd / SumWhere / CountWhere proof composing every required attestation; the kernel rejects partial proofs.

Subset confusion (idx 24) — Tools-curated aggregates over the wrong condition subset (the threshold filter is dropped on one of the two SumWhere components inside the PProd). The kernel-checked proof has both component types fixed by the curator's goal, so the solver cannot drop the filter without the proof failing.

Numeric format (idx 77) — Tools-curated reports "6.29" (off-by-one row included; computed mean over the wrong row set). EG-VAR's Sigma witness `Value.rat (mkRat 169 20) = 8.45` is the correctly-typed exact-rational answer.

These six claims (not the abstract architectural argument) are what the 5 pp Tier 1 gap actually *is*. Each is a place where the curator's typed goal makes the right answer derivable and the free-text baseline does not enforce that constraint.

F.2. Tier 1 fixture properties

We summarise the Tier 1 fixture composition:

Property	Value
Claims	120
Tables	120 (one claim per table)
PProd-composed claims	15 (12.5%)
PLift-using claims (arithmetic identity)	14 (11.7%)
Evidence count per claim (median / max)	1 / 4
Mean evidence count	1.1

L2 predicate distribution. The headline predicate covers the following Tier 1 claim shapes:

L2 predicate	Claims	%
CountWhere	32	26.7%
MeanWhere	32	26.7%
SumWhere	22	18.3%
ArgmaxWhere	19	15.8%
MaxWhere	9	7.5%
ArgminWhere	3	2.5%
TopKSumByWhere	1	0.8%
MinWhere	1	0.8%
HasProperty	1	0.8%

Coverage and limits. The fixture is biased toward single-shot aggregations (88% of claims have evidence-count = 1), with PProd composition tested explicitly on the 15 multi-evidence cases (12.5%). Tier 1 is constructed for breadth across L2 predicate shapes (9 distinct predicates) at relatively shallow composition depth. Deeper composition (PProd of 4+ evidence with `PLift` arithmetic identities, e.g., Section O) appears in 11.7% of claims. Tier 2 (Section 4.3) exercises the same fixture under LLM formalization; deeper composition remains a target for future work.

G. Reproducibility and formalization provenance

G.1. Reproduction artifacts

- Code supplement: `https://anonymous.4open.science/r/anonymous-project-7B87/` (Lean 4 library, Python runtime, trust-artifact JSONs, 11 replay fixtures, runner scripts for E1–E4; see README).

- Reproduction scripts (Tier 1): `run_dg_eval.py`, `run_di_baseline.py`, `run_dj_no_tools.py`; Tier 1.5: `test_counterfactual.py`, `test_counterfactual_dg.py`, `test_counterfactual_dj.py`, all under `scripts/tier1/`.

- Logs written by the runners above: `results/tier1_{dg,di_strict,di_loose,dj}_*.jsonl` (E1), `results/cf_v{4,45}_*.tsv` (E2), `results/tier2_*.jsonl` (E3), `results/cf_v4_tier2_*.jsonl` (E4).

- Models: `claude-sonnet-4-6`, `claude-haiku-4-5-20251001`, and `claude-opus-4-7` (Tier 2 capability-scaling), temperature 0, identical prompt scaffolding across rungs.

Per-claim replay artifact. Each accepted claim is materialized as a single self-contained Lean module `results/generated/pipeline_<tableID>_<claimID>.lean`, which inlines the audited per-source lifts, the runtime-emitted observation leaves, and the proof body; the run-level log (`results/<rung>_<run>.{jsonl,tsv}` for E1–E4 above) records the natural-language claim, model name, temperature, and git commit. Replay needs only this module pair plus the Lean toolchain; no LLM is invoked.

Replay audit gate. Every generated Lean module at `results/generated/pipeline_<hash>.lean` can be replay-audited post-hoc by the standalone script `verify_axioms.py`. The script parses the `#print axioms claim_proof` output and checks the dependency closure against the whitelist buckets used in our analysis: (i) the fixed EG-VAR prelude, (ii) Lean 4 standard core axioms (`Classical.choice`, `Quot.sound`, `propext`), (iii) runtime-emitted observation-leaf schemas matching `obsN_*` or `{table,stats}Tool` (full emission-site table in Table 10), and (iv) the per-source lift prefix `lift_<sourceHash>_*`. The trust-artifact discipline requires either `mkVerified` (attestation path) or at least one runtime leaf together with at least one per-source lift (the direct-evidence lift path per Section 3.2). Any axiom outside these buckets, or any `sorry`/`sorryAx` in the closure, fails the audit. The primary safety gate at generation time is the Lean kernel call inside `pipeline.py` (through `lake env lean`); the replay audit is an additional artifact-level check that any third party holding the generated module bundle and the Lean toolchain can re-run via `python -m runtime.verify_axioms`, without invoking any LLM or re-running the analyst/formalizer/solver roles.

G.2. Formalization provenance

This subsection expands the main-text summary at Section 3.6. We document the curation pipelines explicitly because any reader of Theorem 3.1 must distinguish runtime-minted trust artifacts from pre-committed ones.

Tier 1 and Tier 1.5 fixtures (`data/tier1_gold_formalizations.json`, `data/tier1_table_formalizations.json`). These fixtures supply the pipeline-produced, fixture-committed goal type τ^{gold} and the per-source audited formalization $\Lambda(s)$ for every claim in the four-rung ladder (Sections 4.1 and 4.2). Each entry was produced by an automated subagent pipeline frozen per git commit:

1. **Proposer** (Claude Sonnet subagent, temperature 0, frozen prompt): drafts a candidate Lean goal type and per-table menu, reading only the raw TableBench row data and column headers.

2. **Critic** (Codex GPT-5.4 subagent, separate session per batch): reviews for anti-cheating violations, shape correctness relative to the claim, and R10 menu soundness per Section 3.5.

3. **Kernel typecheck** (`lake env lean`): gates inclusion; any entry whose declared type fails the Lean elaborator is rejected and returned to the proposer.

4. **Human meta-supervision**: a single human (the author) reviewed batch-level acceptance rates and systemic failure categories (e.g., "pipeline emits raw `<<col>>` while lift canonicalizes" as a structural bug), but did *not* edit any individual formalization. No per-entry manual fixes; all fixture content descends from the proposer–critic–kernel loop.

At fixture close the two JSON files are frozen under the commit hash reported in Section G. Curator yield (entries that survived stages 1–3) was 120/120 for Tier 1 and 30/30 per panel for Tier 1.5, covering shape-B (binary-compare), shape-C (cell-lookup), and shape-D (categorical-direction) claims. Shape-D claims reuse the shape-B formalization plus a deterministic post-processor; no kernel extension is required.

Working dictionary (formalizer state). The formalizer is memoryless across claims but has access to a *working dictionary* of Property, Entity, and Convention entries accumulated from prior formalizations and from the analyst pass on the current source. Dictionary entries record canonical column names, value formats, and known encoding conventions. The dictionary is a curator-controlled cross-claim memory; it does not give the formalizer access to the gold answer or solver-side information.

Tier 2 evaluation. The Tier 2 runtime passes the natural-language claim to an LLM formalizer at generation time, with access to the same per-source menu $\Lambda(s)$ (as a trust artifact, not as feedback) but no gold goal type. The formalizer proposes its own τ^{LLM}. The solver then attempts a proof against that type. The kernel type-checks the proof, and the whitelist replay audit accepts only whitelist-compliant proofs. Section 4.3 reports the resulting semantic-faithfulness decomposition on $n=120$ TableBench claims.

What $\Lambda(s)$ is and what it is not. The per-source menu $\Lambda(s)$ is the curator's interpretive commitment that a given tool's L1 output (e.g., `CountCells`) lifts to a specific L2 world-property predicate (e.g., `CountWhere`) on this source. It is *not* a semantic certificate: a wrong but audited lift can still certify a wrong formalized claim, as we document in Section 5.1(ii). The provenance chain terminates at the proposer–critic–kernel loop above; the audit at that loop is the trust artifact. We use the term "audited per-source formalization" throughout to keep the term separable from semantic-faithfulness claims.

What prevents formalizer collusion. At evaluation time the Tier 1/1.5 runtime loads τ^{gold} from the frozen fixture and never invokes the formalizer role. The kernel-trusted prelude, $\Lambda(s)$, and the runtime-minted observation leaves are the only axiom sources (Section 3.6); the solver writes only the tactic body. Consequently, no information from the gold answer or curator's adjudicated reading enters the claim proof at runtime — only pre-committed artifacts do.

H. Worked Tier 1 examples: end-to-end trace

H.1. HIV argmax via state projection

Suppose the claim is *"Which state has the highest HIV incidence rate?"*. EG-VAR proceeds: (1) The solver requests the per-source operation `argmax_with_id` on column "incidence rate". (2) The runtime executes the operation and returns an attested payload `Attested_T q p` that contains the maximum value v, the row handle r at which it occurs, and a cell projection `CellAt r "state" "alabama"`. (3) The kernel's interpretation function lifts the payload to two L2 facts: `MaxCell ``incidence`` c r v` and `CellAt r ``state`` ``alabama```. (4) The per-source lift composes them:

```
axiom hiv_lift_argmax_via_state_proj
  (col : String) (c : Cond) (r : RowHandle)
  (name : String) (v : Value) :
    Evidence Verified (MaxCell col c r v) ->
    Evidence Verified
      (CellAt r "state" (Value.str name)) ->
    Evidence Verified
      (ArgmaxWhere col c name v)
```

(5) The solver writes a refine tactic with witness `"alabama"` and applies the per-source lift; the kernel mints an `Evidence Verified` witness for `ArgmaxWhere "incidence"` c `"alabama"` v, and the Sigma witness "alabama" is the certified answer.

Identity in EG-VAR rides on names rather than category-kinds: "alabama" is a `String`, not an inhabitant of an opaque `State` type. This is the nominalist choice (Quine, 1969; Burgess & Rosen, 1997) — identity-bearers are the names the table actually emits, so audit proceeds by comparing strings rather than inferring category membership. The kernel never has to commit to an ontology of states; the curator commits to a column whose values *are* the identifiers, and the lift makes that commitment typed and inspectable.

A per-source lift is *table-specific* (it encodes the curator's commitment that "state" is the row-identifying column for this particular table) but *claim-generic* (parametric over measure column, condition, entity name, and value, so a single lift covers many argmax claims). Lifts are audited once per source then trusted kernel-side for all subsequent claims over that source. Absence of a matching lift is a feature: the solver has no L2 proof path, the kernel rejects, and the system abstains rather than silently guessing. The guarantee is conditional: a semantically *wrong* audited lift can still produce a verified output for a formalized claim that the lift's semantics admit. EG-VAR rules out unsupported claims between tool and output; it does not eliminate curator error in the trust artifact itself.

This is the concrete protocol behind our claim that the formalization barrier in empirical reasoning is a curation gap, not an expressive limit (Section 1). The L1/L2 separation is portable: knowledge graphs, SQL views, JSON APIs, and sensor streams admit the same per-source-lift pattern. We sketch the generalization in Section 5.2.

H.2. Full Tier 1 trace

We walk through a single Tier 1 claim from natural-language input to kernel-checked Sigma witness, to make the architecture's per-step trust commitments concrete.

Claim and goal type. *"Which crater has the largest diameter?"* over the lunar-crater table. The fixture-committed Lean goal (in Lean's dependent-sum notation):

```
Sigma (e : String), Sigma (v : Value),
  Evidence Verified
    (ArgmaxWhere c_diameter
                 Cond.all e v)
```

where `c_diameter = "diameter (km)"`. The Sigma binders make the certified answer the witness e (Martin-Löf, 1984); the surface answer is the first projection.

Step 1 (solver → runtime). The solver issues the structured action {`action: ''stats'', operation: ''argmax_with_id'', column: ''diameter (km)'', identity_column: ''name''`}.

Step 2 (runtime → attested payload). The runtime executes the operation deterministically against the table; it returns an `Attested_T q p` witness with payload {MAXROW: cleopatra, MAXVALUE: VALUE.RAT (MKRAT 78 1)}.

Step 3 (interp_T → L1 facts). The interpretation function for `argmax_with_id` reads the attested payload into two typed L1 storage facts: `MaxCell ''diameter (km)'' Cond.all 78` (the maximum value at the storage layer) and `CellAt` r `''name'' (Value.str ''cleopatra'')` (the identity-column value at row r).

Step 4 (per-source lift → L2 claim). The lunar-crater `argmax_via_name_proj` lift composes the two L1 facts and emits the L2 claim `Evidence Verified (ArgmaxWhere ''diameter (km)'' Cond.all ''cleopatra'' 78)`. The lift is the curator's interpretive commitment that "name" is the row-identifying column for this table.

Step 5 (solver → proof term). The solver writes `refine ⟨''cleopatra'', ..., ?_⟩; exact argmax_via_name_proj ...`; the kernel type-checks and the Sigma witness "cleopatra" is extracted as the certified answer.

The generated Lean file is the replay artifact (G1 in Section 5.2); the audit cost is the per-source lift audit, paid once and reused.

I. Failure cases and formalizer-design notes

I.1. V3_C1 (Egypt-vs-Yemen): baseline prior-override

Setup. Synthetic counterfactual countries-population table: Egypt's `july 1, 2013 projection` cell overwritten to 12 (real $\sim$85M). Yemen unchanged at $\sim$25M. Question: "Which country has a larger population: Egypt or Yemen?".

Sonnet Tools-curated trace (3/3 prior-override). The model issues a `cell_lookup` for Egypt, receives 12; issues a `cell_lookup` for Yemen, receives 25252000; then answers "Egypt". The tool returns the source values; the model overrides them. The same pattern occurs across all three reps.

EG-VAR (3/3 source-faithful). The kernel mints an `Evidence Verified` witness from the per-source argmax-with-disjunction lift on the attested payload. The solver writes `refine ⟨''yemen'', ...⟩; exact ...`. The Sigma witness "yemen" is the certified answer.

Authority-cue ablation (authority-cued pilot). Prefixing the question with "According to the table below, ..." rescues V3_C2 (boolean threshold) and V3_C9 (implicit direction) on Tools-curated but does not rescue V3_C1 (still 3/3 prior-override). The cue is not strong enough to override the parametric prior on famous-entity populations; the kernel attestation is.

I.2. Formalizer failures: runtime-vs-fixture delta (Tier 2)

Section 4.3 reports the end-to-end Tier 2 decomposition at $n=120$; this appendix zooms in on the five Sonnet cases where the runtime formalization diverged materially from the fixture-standard goal type. Four produce kernel-accepted but answer-divergent output (B5b); one aborts the formalizer pass (B7). We present each as a structured delta, organised by the compositional axis along which the divergence occurred. Cases classified B5a (recorded ambiguity) are excluded here; they are logged in `ambiguous_terms` and do not represent formalizer-attributable error. The two B5c cases are corrected benchmark-gold defects, counted as correct (Table 5).

Across these five cases, the common pattern is that the formalizer makes a local-reading decision at a composition node (which `Cond` constructor, which column, whether to include a `TopK` constraint) that a curator with the claim and the fixture-standard formalization in front of them would have taken differently. Each case is addressable by supervised fine-tuning on fixture (claim, gold `lean_goal_type`) pairs or RL with a gold-answer reward; we discuss the direction at the end of the section.

I.3. Composite-column matching strategy (idx 50)

Claim. "How many hurricanes occurred in the month of September?"

Delta. Column `month` contains date-string values of the form `''September 1979''`, `''October 1988''`, etc. (month-plus-year strings). Fixture uses `Cond.propContains`:

```
CountWhere "month"
  (Cond.propContains "month" (Value.str "September"))
  ans
```

Runtime formalizer chose `Cond.propEq`:

```
CountWhere "month"
  (Cond.propEq "month" (Value.str "September"))
  ans
```

Runtime answer: 9. Fixture answer: 19. The formalizer's `ambiguous_terms` field recorded the choice explicitly as "*Cond.propEq — exact match*". The kernel accepted the proof under the LLM's chosen reading; the L1 tool correctly returned `count = 9` for strict equality with the literal string `''September''`, which matches zero `month = "September ..."` rows in the table.

Character of the error. The formalizer recognised the existence of a matching-strategy decision, logged it, and picked the strategy whose answer would be correct *only if* the `month` column's values were bare month names. It did not use the column's actual value format (exposed by the analyst's reading guide) to discriminate.

I.4. Dropped `TopK` constraint (idx 61)

Claim. "What is the average market value of the top 5 companies in the oil and gas industry?"

Delta. Fixture uses `TopKMeanWhere`, which the per-source menu includes for this column:

```
TopKMeanWhere "market value (billion )" 5
  (Cond.propEq "industry" (Value.str "oil and gas"))
  ans
```

Runtime formalizer dropped the top-5 constraint and used plain `MeanWhere`:

```
MeanWhere "market value (billion )"
  (Cond.propEq "industry" (Value.str "oil and gas"))
  ans
```

Runtime answer: $1208/5$. Fixture answer: 276.06. The formalizer's `ambiguous_terms` names the phrase "*top 5 companies in the oil and gas industry*" and records the chosen formalization as `MeanWhere`, so the dropped `TopK` was deliberate, not an oversight.

Character of the error. The formalizer treated "top 5" as rhetorical rather than compositional. The per-source menu includes `TopKMeanWhere` for this column; the formalizer's compositional-operator selection step did not consult it.

I.5. Column disambiguation (idx 67)

Claim. "What is the difference in total goals scored by the top-scoring forward (fw) and the top-scoring midfielder (mf) in the league?"

Delta. Table has both a `league goals` column and a `total goals` column. Claim literally says "total goals". Fixture uses `total goals`:

```
MaxWhere "total goals" (Cond.propEq "position" "fw") a
... MaxWhere "total goals" (Cond.propEq "position" "mf") b
... (PLift (ans = a - b))
```

Runtime formalizer picked `league goals`:

```
MaxWhere "league goals" (Cond.propEq "position" "fw") a
... MaxWhere "league goals" (Cond.propEq "position" "mf") b
```

Runtime answer: 6. Fixture answer: 7.

Character of the error. Column-selection under near-synonym ambiguity, where the claim's exact wording ("*total* goals") is the dispositive signal. The formalizer's `properties_needed` did not enumerate a candidate-set check against the claim's noun phrase.

I.6. Condition-conjunct erasure and self-inconsistency (idx 94)

Claim. "What is the average prominence of mountain peaks in the Democratic Republic of the Congo that have an elevation of at least 3000 meters?"

Delta. Fixture:

```
MeanWhere "prominence (m)"
  (Cond.and
    (Cond.propContains "country"
      (Value.str "democratic republic of the congo"))
    (Cond.propGte "elevation (m)"
      (Value.rat (mkRat 3000 1))))
  ans
```

Runtime formalizer:

```
MeanWhere "prominence (m)"
  (Cond.and
    (Cond.propGte "elevation (m)"
      (Value.rat (mkRat 3000 1)))
    (Cond.propGte "col (m)"
      (Value.rat (mkRat 0 1))))
  ans
```

The country filter is absent; the second conjunct is col (m) $\geq$ 0 (trivially true on this table). The formalizer's `ambiguous_terms` field claims the chosen filter is `Cond.propEq "country" "democratic republic of the congo"` — *but this constructor does not appear in the emitted* `lean_goal_type`. Runtime answer: $14075/6$; fixture answer: 2606.25.

Character of the error. Self-inconsistency between the formalizer's self-reported decision (`ambiguous_terms`) and the actual `lean_goal_type` it emitted. A post-formalizer consistency pass — verifying every adjudication recorded in `ambiguous_terms` is reflected in the emitted goal — would catch this class mechanically at audit time. We list this as a near-term infrastructure improvement in Section 5.3.

I.7. Compositional-complexity abort (idx 34)

Claim. "What is the total number of medals (M36 + M36B1 + M36B2) earned from May 1944 to August 1944?"

Delta. Fixture is a 4-level dependent sum:

```
Sigma ans, Sigma a, Sigma b, Sigma c,
  PProd (SumWhere "m36"    <4-way month or> a)
  (PProd (SumWhere "m36b1" <same or> b)
  (PProd (SumWhere "m36b2" <same or> c)
  (PLift (ans.asRat = a.asRat + b.asRat + c.asRat))))
```

The fixture formalization composes *three separate measure columns* with *a 4-way disjunction over the month column* and *a 3-term arithmetic* combining the resulting witnesses. Runtime formalizer emitted an empty `lean_goal_type` and aborted on its first attempt; the pipeline returned ABSTAIN rather than a wrong formalization.

Character of the error. Compositional complexity boundary: the claim requires simultaneous choices across three dimensions (measure column, filter disjunction width, arithmetic composition shape) in a single pass. The formalizer's single-pass architecture is not expressive enough to emit this class of goal reliably. Note that this is the *desirable* failure mode: no silent-wrong, no Verified output with the wrong answer. The system abstained honestly; the downstream consumer sees ABSTAIN and can route elsewhere.

We note that the *decomposer + binder* two-stage formalizer pattern — splitting the goal into per-measure sub-claims and composing them via a binder role — is a natural architectural response to this class; we describe it in Section 5.3 as future work.

I.8. Taxonomy and improvement direction

The five cases partition into five orthogonal compositional axes of the formalizer's output: matching strategy (idx 50), operator selection (idx 61), column selection (idx 67), condition-conjunct preservation (idx 94), and compositional arity (idx 34). Three of these (idx 50, 61, 67) are *local* decisions: each resolves to a choice among a small candidate set that is determined by the claim's wording together with local information already available to the formalizer (column-value format for idx 50; per-source menu for idx 61; claim noun phrase for idx 67). Case idx 94 is a *consistency* gap between two of the formalizer's own outputs. Case idx 34 is a *capacity* limit rather than a reading error.

Near-term infrastructure improvements. The idx 94 self-inconsistency case is mechanically detectable: verifying agreement between each entry of `ambiguous_terms.chosen` and the emitted `lean_goal_type` is a deterministic post-formalizer audit that would convert this failure mode into an ABSTAIN or a retry. We list this as future work rather than a claimed feature.

RL fine-tuning of the formalizer. Each of the four reading-error cases (idx 50, 61, 67, 94) is a single-claim adjudication where the fixture's `lean_goal_type` supplies a ground-truth choice at exactly the compositional node where the runtime formalizer diverged. The fixture, documented with provenance in Section 3.6, therefore supplies a structured supervised-fine-tuning corpus of (claim, analyst-guide, per-source menu, gold `lean_goal_type`) tuples. A natural next step is to fine-tune a formalizer model on this corpus, either supervised or with a verifier-based RL loop where the reward is kernel acceptance against the fixture goal type. The verifier is already on hand: it is the same kernel the paper uses to certify production outputs. This produces a formalizer whose local reading decisions converge to the curator's, without weakening any of the runtime trust properties established in Section 3.6.

Why this is compatible with the paper's safety claims. Fine-tuning the formalizer is an *accuracy* intervention, not a *safety* intervention: Theorem 3.1 and Theorem 3.2 are properties of the runtime + kernel, invariant under any formalizer. A fine-tuned formalizer changes the VERIFIED/ABSTAIN split favorably without changing the no-silent-wrong guarantee.

J. Abstention case study

Setup. A Tier 1 claim whose goal type required a per-source `topk_sum_by` lift over a measure column not registered in the curator's lift menu for that table.

EG-VAR outcome. The kernel rejects every proof attempt: no L2 fact unifies with the goal vocabulary because the lift menu has no matching entry. The system reports ABSTAIN with the unsatisfied goal type.

Tools baseline outcome. The same-tool baseline calls a related stats operation, receives a numeric value, and emits a free-text answer that happens to match the gold (a partial correctness coincidence; the operation called was not the one the gold formalization required). Verified-wrong vs verified-right is indistinguishable downstream without a kernel-checked proof.

Governance reading. EG-VAR's abstention is machine-actionable (G3 in Section 5.2); the baseline's "answer" is opaque. The trade-off is honest: EG-VAR loses one match-counted claim, but the failure mode is structurally typed.

K. Per-source formalization: theory anchors

K.1. Robustness hierarchy

The argument that records-vs-entities is hierarchical, not categorical (Section 3.2), can be made precise. Storage features that hold prior to any interpretive commitment: same-row entries share a row-anchor, same-column entries share a column-anchor. Layering interpretive commitments on these invariants yields a four-level hierarchy of per-source formalizations:

Level	Commitment	L2 vocabulary unlocked
1. Aggregate-only	none beyond layout	`SumWhere`, `CountWhere`, `MeanWhere`, `MaxWhere`, `MinWhere`
2. Row-cell facts	rows have stable handles	row-anchored `cell_lookup`
3. Entity-anchored	rows are entities; col X gives names	`HasProperty`, `ArgmaxWhere`, `EntitySum`
4. Relational	both axes entity-identified	`Relation`, matchup-style

Each level's commitments include those above. A record table stops at level 1; an entity table reaches level 3; a matchup table reaches level 4. Same kernel, same L1/L2 split, same ontology — different stopping points on a single hierarchy. "Fail-closed for mismatched claims" becomes a hierarchy property: a claim requiring level-3 commitments against a level-1 table has no L2 fact to unify against, so the pipeline abstains.

K.2. Rank as interpretation: gauge freedom

A given dataset admits multiple consistent rank interpretations. A matchup table can be formalized as Result : Player $\rightarrow$ Player $\rightarrow$ Outcome (rank-2 curried), Result$'$: Player $\times$ Player $\rightarrow$ Outcome (rank-2 uncurried), or MatchOutcome : Match $\rightarrow$ Outcome where Match := Player $\times$ Player (rank-1 with composite domain). All three encode the same function and are type-isomorphic in any Cartesian closed setting (Mac Lane, 1971).

Rank-shifting interpretations across the lambda calculus reduce to currying/uncurrying, which Lean 4 makes definitionally

transparent ($A \to B \to C$ is sugar for $A \to (B \to C)$). The kernel does not need to commit to "the true rank" of a table; it accepts any consistent per-source lift catalogue. Other examples of the same ambiguity:

- *Time series.* Rank-1 (time $\to$ value) vs rank-2 with channels (time $\times$ channel $\to$ value).

- *Pixel grid.* Rank-2 (row $\times$ col $\to$ intensity) vs rank-3 (row $\times$ col $\times$ channel $\to$ value).

- *RDF triples.* Rank-1 over triples; rank-2 (subject, predicate) $\to$ object; rank-3 (subject, predicate, object) $\to$ {true, false}.

- *Relational tables with primary key.* Rank-1 over rows-as- records vs rank-2 (row, column) $\to$ cell.

These are not subjective conventions but type isomorphisms. The curator's job is to pick an interpretation that fits the anticipated claims and audit the lift menu under it; the kernel's job is to accept any consistent commitment.

K.3. The scaling argument: formalization gap shrinks as sources become formal

The empirical results in Section 4 are bounded by the formalization burden of CSV-style sources. As data substrates evolve toward typed interfaces, the formalizer's job shrinks while the kernel guarantee stays the same:

Substrate	Formalization burden
CSV	Column names are strings; values are free text. Maximal lift authoring per source.
SQL view	Schema is typed, values structured. Lift catalog auto-generates from view definitions.
OpenAPI	Typed inputs/outputs in spec. Lift = adapter from spec types to L2 ontology.
Knowledge graph	Entities + relations already typed. Lift = direct projection from RDF to L2.
Lean / formal source	Zero gap; compose proofs directly.

In the limit of fully formal sources, the LLM operates entirely within the formal world, the kernel guarantee is vacuous (because the substrate is already typed), and EG-VAR collapses to LLM-driven theorem proving with attested premises. The architecture is designed to interpolate: the same kernel + lift discipline runs across the substrate spectrum. We expect the kernel-vs-baseline gap on real-world deployments to narrow over time as data sources adopt structured interfaces, not because models improve, but because the formalization burden moves to the source curator and out of the inference path.

L. Tier 2 reporting taxonomy and capability-scaling check

This appendix expands the main-text table caption at Table 5 and reports the Opus capability-scaling check.

Category definitions. Categories are mutually exclusive and sum to 120. **B1**: kernel-accepted, type matches gold, answer matches gold. **B4**: kernel-accepted, type differs from gold but answer matches. **B5a** (*ambiguous claim, logged*): kernel-accepted divergent answer under a defensible alternative reading that the formalizer logged in `ambiguous_terms`. **B5b** (*semantic formalizer error*): pure formalizer error (wrong column, dropped constraint, composite-value matching-strategy error) — kernel still accepts the proof, but of a mis-formalized goal. **B5c** (*defective benchmark gold, exposed*): the frozen benchmark gold is mismatched to its question — the gold formalization reproduces it, but the LLM's independent formalization yields the question-faithful answer; we correct the gold and count these as *correct*. **B6**: kernel-rejected, honest abstention. **B3**: solver exhausted tactic retries with type matching gold. **B7**: formalizer aborted.

Reading the decomposition. The key Tier 2 number is the pure end-to-end formalizer-error rate, not the flat disagreement rate. On Sonnet, only 4/120 cases are bona fide formalizer mistakes (B5b). Two further cases (B5c) traced to a frozen benchmark gold mismatched to its question: the gold formalization reproduces the gold answer, but the LLM's independent formalization yields the question-faithful answer, which EG-VAR's proof exposed rather than propagated; with the gold corrected we count them as *correct*. The remaining divergences are *auditable*: 5 logged alternative readings (B5a), 3 honest abstentions (B6), and 5 solver or formalizer ceilings (B3+B7). Each B5a entry's alternative-reading choice is logged in `ambiguous_terms` by the formalizer. Treating logged ambiguities on the formalization axis raises auditable agreement to 90.0%.

Capability-scaling check. As a robustness check on the claim that residual formalizer error is capability-limited, we evaluate the stronger Opus model on the 9 Sonnet residual indices (B3/B7 or B5b). Opus converts four B3/B7 cases to accepted answer-matches and one B5b case to honest abstention; two B5b cases persist. The formalizer-error rate on this residual subset halves from 4/9 to 2/9. A full Opus re-pass over all 120 claims showed no regression relative to Sonnet outside these residual indices, so the Opus column in Table 5 combines the shared non-residual results with the Opus re-pass on the residual set. The theorem-level safety invariant is unchanged under either formalizer.

M. Scope limits and future extensions

This appendix expands the main-text summaries at Sections 5.1 and 5.3.

M.1. Limitations

(i) Formalizer scope. Tier 1 and Tier 1.5 evaluate the pre-formalized regime: each claim arrives with a fixture-committed gold typed goal (Section 3.6), and no claim-level LLM formalizer runs at evaluation. They probe the safety and source-faithfulness properties under that regime. Tier 2 (Section 4.3) evaluates the deployment reconstruction regime where the LLM formalizer runs end-to-end. The 3-blind-formalizer consensus design is implemented in the runtime but not evaluated here; we defer the consensus study to future work.

(ii) Trust artifacts. Tools, per-source lifts, and the L1 adapter are trusted (auditable but not type-checked end-to-end). A semantically wrong audited lift can certify a wrong formalized claim; EG-VAR rules out unsupported claims between tool and output, not curator error in the trust artifact itself (Section 3.5).

(iii) Single-source scope. All evaluations are over single TableBench tables. Multi-source conflict, retrieval over distributed KGs, and time-varying sources are out of scope; we list near-term extensions below.

(v) World inconsistency containment. The implementation realizes Theorem 3.1 and Theorem 3.2 structurally; the companion world-inconsistency-containment property relies on the `WProp` $\not\to$ `Prop` phase separation in the current Lean encoding; we treat it as implementation detail, not a main-text theorem.

M.2. Future work scoped to governance reach

Fine-tuning the NL formalizer. Tier 2 (Section 4.3) reports residual semantic formalizer error at 3.3% (Sonnet) / 1.7% (Opus). Each of the 4 Sonnet B5b cases is a single-claim adjudication where the fixture supplies a ground-truth choice at exactly the compositional node where the runtime formalizer diverged, and the curator pipeline (Section 3.6) already provides a structured SFT / RL corpus. Fine-tuning a formalizer on this corpus, with kernel acceptance as the reward signal, is an accuracy intervention that tightens the residual rate without weakening Theorem 3.1; the verifier is already on hand — it is the same kernel the paper uses to certify production outputs. A 3-blind-formalizer consensus gate is similarly implemented but not evaluated here; we expect it to convert a further fraction of silent B5b mistakes into honest B6 abstentions.

Conflicting sources. Multi-source attestation introduces conflict between attested storage facts. The grade calculus admits explicit conflict-downgrade rules (VERIFIED → SUPPORTED on detected disagreement); empirical evaluation is future work.

Cross-substrate panel. Replicating the source-faithfulness discriminator on KG-grounded and SQL-grounded claims would directly test the L1/L2 portability claim (Section 5.2).

N. Theoretical anchors deferred from the main text

The main text uses a selected set of theoretical anchors as Justification Anchors and Lineage Paragraphs (Martin-Löf, Curry–Howard, Codd, Mac Lane, Quine, Burgess–Rosen, Raggi, Bundy, Clarke, Lahiri, Artemov, Fine, Green). The following anchors connect to the same design choices but are deferred here for space:

Source semantics and naming. Cooper (2012) (Type Theory with Records, TTR) gives a type-theoretic substrate for situated semantics that resembles our per-source-formalization commitment. Montague (1973) established that the natural-language → formal-meaning gap admits a typed denotational treatment, the genealogy of our claim formalization. Barwise & Perry (1983) (situation semantics) treats situations as first-class typed objects, the same move as our per-source formalization.

Earlier in the lineage, Frege (1892) distinguished sense and reference — a distinction EG-VAR's name-as-string discipline collapses by choosing reference fixed at the storage layer. Following Kripke (1980) on rigid designators, our choice of name- columns as identity-bearers is the operational analogue of name- rigidity at the trust boundary. Donnellan (1966) distinguishes referential and attributive uses of definite descriptions; EG-VAR's lift menu enforces the referential reading ("the row whose name-column is X").

Uncertainty and conflict. Future multi-source evaluation opens connections to Belnap (1977) four-valued paraconsistent logic, Anderson & Belnap (1975) relevance/relevant logic, and Jøsang (2016) subjective-logic continuous-confidence. Caminada & Amgoud (2007) ASPIC+ structured argumentation gives a substrate for grade-aware retraction under contradiction. Doyle (1979) JTMS truth-maintenance systems are the classical dependency-graph substrate for provenance-tracked retraction. Alchourrón et al. (1985) AGM belief revision frames the multi-source contradiction problem. EG-VAR's grade calculus accommodates these via the conflict-downgrade rules sketched in Section 5.3.

Optional / cautious anchors. Univalence in homotopy type theory (The Univalent Foundations Program, 2013) would give a principled account of equivalence classes of source formalizations (different rank readings, different lift catalogs); we mention this as a future- work analogy rather than a current design basis. Reliabilist epistemology (Goldman, 1979) grounds our "verified by reliable process" framing of VERIFIED evidence. Attribute-based access control (Hu et al., 2014) and typed semistructured data (Abiteboul et al., 2000) are the systems analogues of EG-VAR's per-source-formalization protocol.

Soundness over internal completeness. The kernel does *not* relate semantically equivalent L2 predicates by general lemmas: there is no built-in MeanWhere $c\,v \Leftrightarrow \exists s, n.$ SumWhere $c\,s \land$ CountWhere $c\,n \land v = s/n$. Equivalences are localized in the per-source tools and lifts, where they are computed directly and audited offline; the kernel's proof search stays decidable and its proof traces stay small enough to inspect. This is the same fragmentation move that gives us decidable fragments of first-order logic, theory combination in SMT, and description logics: trade FOL completeness for tractable, auditable per-theory reasoning. Raggi et al. (2016) formalize precisely this: representation matters in proof, and semantically equivalent encodings can carry very different proof-engineering costs.

O. Worked Tier 1 examples: cross-tribunal PProd composition

The lunar-craters argmax in Section H exercises a single tool call and a single per-source lift. We now walk through a substantially more complex Tier 1 claim: a four-tool, four-evidence, PProd-composed claim with an arithmetic identity between the witnesses. This is representative of the multi-shot composition shapes we curated in Tier 1's PProd cluster.

Source. TableBench table `4fbaad0b...` (Spanish-Inquisition-tribunal autos da fé records). Relevant excerpt:

Tribunal	Autos da fé	Exec. persona	Exec. effigie	Penanced
Barcelona	8	1	1	15
Valencia	4	2	0	49
Córdoba	13	17	19	125
Cuenca	7	7	10	35
. . .				

Claim. *"How much greater is the total number of executions (in persona and in effigie) in Córdoba compared to Valencia?"* The arithmetic answer is $(17 + 19) - (2 + 0) = 34$.

Per-source tool menu. For this table the curator registered, among others:

- `stats_sum_strict` on column "executions in persona"
- `stats_sum_strict` on column "executions in effigie"
- Each accepts a `Cond.propEq` on the "tribunal" identity column.

The tool menu is the audit surface; a claim that requires a predicate not in the menu fails closed.

Lean goal type (fixture-committed).

```
Sigma (ans : Value),
Sigma (a1 : Value), Sigma (a2 : Value),
Sigma (b1 : Value), Sigma (b2 : Value),
PProd
  (Evidence Verified
     (SumWhere "executions in persona"
        (Cond.propEq "tribunal"
                     (Value.str "cordoba")) a1))
(PProd
  (Evidence Verified
     (SumWhere "executions in effigie"
        (Cond.propEq "tribunal"
                     (Value.str "cordoba")) a2))
(PProd
  (Evidence Verified
     (SumWhere "executions in persona"
        (Cond.propEq "tribunal"
                     (Value.str "valencia")) b1))
(PProd
  (Evidence Verified
     (SumWhere "executions in effigie"
        (Cond.propEq "tribunal"
                     (Value.str "valencia")) b2))
  (PLift (ans.asRat =
           (a1.asRat + a2.asRat) -
           (b1.asRat + b2.asRat)))))))
```

The five Sigma binders fix: the surface answer `ans`, plus four numeric witnesses for the four sum sub-claims. The final `PLift` is the kernel-checked arithmetic identity that ties the witnesses to `ans`.

Solver action sequence (4 tool calls).

```
{ "action": "stats", "operation": "sum",
  "column": "Executions in persona",
  "condition": { "op": "eq",
    "property": "Tribunal", "value": "cordoba" } }
{ "action": "stats", "operation": "sum",
  "column": "Executions in effigie",
  "condition": { "op": "eq",
    "property": "Tribunal", "value": "cordoba" } }
{ "action": "stats", "operation": "sum",
  "column": "Executions in persona",
  "condition": { "op": "eq",
    "property": "Tribunal", "value": "valencia" } }
{ "action": "stats", "operation": "sum",
  "column": "Executions in effigie",
  "condition": { "op": "eq",
    "property": "Tribunal", "value": "valencia" } }
```

Tool attestations. The runtime returns `Attested_T` payloads: $a_1 = 17$ (Córdoba persona, single-row sum), $a_2 = 19$ (Córdoba effigie), $b_1 = 2$ (Valencia persona), $b_2 = 0$ (Valencia effigie).

L2 evidence via per-source lifts. Each attested payload is lifted via the `stats_sum_strict` per-source lift, which takes the L1 column-strict sum attestation and the `Cond.propEq` discriminator and produces an L2 `SumWhere` witness. The four lift applications produce `obs0_l2`, `obs1_l2`, `obs2_l2`, `obs3_l2`, each typed as `Evidence Verified (SumWhere ...)` with the right column/condition/value triple.

Solver proof body.

```
refine ⟨Value.rat (mkRat 34 1),
```

```
       obs0_val, obs1_val,
       obs2_val, obs3_val, ?_)
refine PProd.mk obs0_l2
       (PProd.mk obs1_l2
       (PProd.mk obs2_l2
       (PProd.mk obs3_l2
       (PLift.up ?_))))
native_decide
```

The first `refine` fills the five Sigma binders: the surface answer is `Value.rat` (`mkRat 34 1`) ($= 34/1$), and the four numeric witnesses are the values `obs0_val ... obs3_val` that the kernel already bound when the lifts fired. The second `refine` threads the four `Evidence Verified` witnesses through the right-associated `PProd` chain. `native_decide` closes the residual `PLift` goal: the kernel evaluates $34.\text{asRat} = (17 + 19) - (2 + 0)$ to `True`.

Trust composition.   The kernel-minted output for this claim depends on: (i) the four runtime `Attested_T` payloads (one per tool call) — and *only* those (Theorem 3.1); (ii) the per-source `stats_sum_strict` lift, audited once for this table; (iii) the kernel's native arithmetic check for the `PLift = 34` identity. The Sigma witness "34" surfaces as the certified surface answer; the generated Lean file is the replay artifact (any auditor holding the kernel + lifts + tool adapter can re-typecheck without re-running the LLM). This is the single complex example we use in Sections 3 and 4 to demonstrate that the architecture scales beyond single-shot lookups: composition over multiple lifts preserves the kernel's mint discipline and, by construction, the verified-output guarantee.

P. Full proofs of the safety theorems

This appendix provides the full proofs deferred from Section 3.6. Notation follows the main text: given a VERIFIED run of RUNTIMEVERIFY(s, c) returning the proof object (*leanFile*, *evidence*, *steps*), we write *proof* for the term bound by `claim_proof` inside *leanFile* (or `claim_refutation` for refuted claims), $\mathcal{A}$(*leanFile*) for the set of axioms declared in *lean-File*, and $\text{deps}(proof) \subseteq \mathcal{A}(leanFile)$ for the dependency closure of *proof* as reported by `#print axioms claim_proof`.

P.1. Operational whitelist predicate and guarantee boundaries

Whitelist-compliant module.   Let *leanFile* be the module text returned by a run, let *proof* be the term bound by `claim_proof` (or `claim_refutation` for refuted claims), and let $\text{deps}(proof)$ denote its dependency closure as reported by `#print axioms claim_proof`. We say *leanFile* is *whitelist-compliant for source s* iff every element of $\text{deps}(proof)$ lies in one of four buckets: **B1** the fixed EG-VAR prelude (committed at the repository hash in Section G); **B2** the standard Lean 4 core axioms (`Classical.choice`, `Quot.sound`, `propext`); **B3** runtime-emitted observation leaves (`obsN_q,p,att,tag,shape,l1,row,cell,id,max,min`; `csN_q,att`; `tableTool/statsTool`); **B4** per-source lifts whose names match `lift_[0-9a-f]+_.+` drawn from $\Lambda(s)$. Additionally, $\text{deps}(proof)$ must contain no `sorry/sorryAx/Lean.Axiom.sorry` and must contain a trust-artifact witness: either `mkVerified` (attestation path), or at least one **B3** observation-leaf together with at least one **B4** per-source lift (direct-evidence lift path, per Section 3.2). The standalone script `verify_axioms.py` evaluates this predicate mechanically on *leanFile*.

Generation-time gate versus replay gate.   The kernel call inside `run_pipeline` (`lake env lean`) is the primary safety gate: a claim is emitted as VERIFIED only if the kernel returns a zero exit status on *leanFile*. The replay audit `verify_axioms.py` is a standalone artifact-level check: it accepts *leanFile* as input, invokes the Lean elaborator on its `#print axioms` directive, and enforces the whitelist predicate on the reported dependency closure. Any third party holding *leanFile* and the Lean toolchain can re-run `python -m runtime.verify_axioms` without invoking any LLM role, reproducing the audit decision. The orchestrator (`src/python/runtime/orchestrator.py`) chains the two: a claim is published as VERIFIED only if both calls succeed.

What the theorems do and do not guarantee.   Theorems 3.1 and 3.2 guarantee that every VERIFIED output descends from a real tool call and every accepted proof step is type-correct. They do *not* guarantee: (i) that *goalType* is a semantically faithful rendering of the natural-language claim — this is the formalizer's responsibility, evaluated separately by the answer-match axis (Section 5.1(i, iii)); (ii) that the per-source lifts $\Lambda(s)$ correctly interpret the tool's L1 outputs as L2 world facts — a semantically wrong but audited lift can still certify a wrong formalized claim (Section 5.1(ii)). Both are honest trust-artifact boundaries, not architectural oversights: $\Lambda(s)$ is LLM-assisted, curator-reviewed, and frozen per commit

(Section 3.6). World-inconsistency containment follows from the WProp $\not\to$ Prop phase separation in the current Lean encoding; we treat it as implementation detail, not as a main-text theorem (see Section 5.1).

P.2. Lemma chain for the theorems

Lemma P.1 (Checker fidelity). *If* KERNELCHECK*(leanFile) returns* (True, *output*), *then proof satisfies proof* : *goalType in Lean 4's dependent type theory relative to* $\mathcal{A}$*(leanFile).*

Proof. The procedure KERNELCHECK(*leanFile*) is implemented at `pipeline.py:4428` by invoking `lake env lean` on *leanFile* and inspecting the elaborator's exit status and output. The Lean 4 kernel is a type-checker for the Calculus of Inductive Constructions: a closed expression t elaborates at type T iff the kernel applies a finite sequence of typing-rule applications that witness $t : T$ starting from the declared axioms and definitions of the environment (de Moura & Ullrich, 2021). The kernel rejects any term that invokes an undeclared identifier, applies a constructor at a non-matching type index, or whose strict positivity or termination constraints are violated. The declared axiom set used during elaboration is exactly the union of (a) axioms from imported modules (the EG-VAR prelude loaded via the `import` preamble at the top of *leanFile*) and (b) axioms introduced by top-level `axiom` declarations in *leanFile* itself; call this union $\mathcal{A}$. If the elaborator reports success, then by the kernel's type-correctness invariant the stored proof term *proof* satisfies *proof* : *goalType* under $\mathcal{A}$. $\square$

Lemma P.2 (Runtime emission discipline). *Every observation-leaf axiom declaration in leanFile — every top-level* `axiom` *declaration whose name matches one of the **B3** schemas — was emitted by the runtime only after a successful call* EXECUTE(t, q) *whose resulting triple* $(t, q, payload)$ *was appended to evidence before the corresponding emission step. The two tool-identifier axioms* `tableTool` *and* `statsTool` *are declared once in the module preamble as pure identifiers of the* `ToolId` *sort and carry no payload content.*

Proof. We prove the claim by exhaustive inspection of the module-emission path in `src/python/runtime/pipeline.py`. The text of *leanFile* is assembled by the function `_build_lean_file` (`pipeline.py:3174–3488`); no other code path emits module text. We enumerate the branches of `_build_lean_file` at which an `axiom` line is appended to the module.

site (file:line)	source	axiom families emitted
3203–3204	preamble	`tableTool`, `statsTool`
3231–3232	common-sense	`csN_q`, `csN_att`
3272–3275	stats (argmax/argmin)	`obsN_row`, `obsN_max`, `obsN_cell`
3318	stats (value-only L1)	`obsN_l1`
3352	stats (topk-by L1)	`obsN_l1`
3387	stats (topk/bottomk)	`obsN_l1`
3399–3404	stats (legacy shape)	`obsN_q,p,att,tag,shape`
3431–3434	table (cell-lookup)	`obsN_row`, `obsN_cell`, `obsN_id`
3442–3447	table (cell-lookup legacy)	`obsN_q,p,att,tag,shape`

Table 10. Axiom-emission sites inside `_build_lean_file`. Each `obsN_*` or `csN_*` branch executes only if the preceding loop variable carries a well-formed payload, which is appended to *evidence* by the runtime tool-dispatch layer before `_build_lean_file` is invoked. The preamble row declares `tableTool`/`statsTool` once per module as pure `ToolId` identifiers.

Each stats and table row lives inside a branch guarded by an evidence entry whose `source` field is `"stats"`, `"table"`, or `"common_sense"`. The tool-dispatch layer and the runtime solver loop in `run_pipeline` append an entry to *evidence* only after a successful EXECUTE(t, q) call returns a well-formed payload; failed or rejected calls return `None` and produce no evidence entry. Therefore, at the point `_build_lean_file` emits any observation-leaf axiom for evidence index i, the corresponding triple $(t, q, payload)$ is already present at position i of *evidence*.

A grep over `pipeline.py` for `"axiom obs"`, `"axiom cs"`, `"axiom tableTool"`, and `"axiom statsTool"` recovers exactly the lines listed in Table 10 (together with solver-prompt skeleton lines at `pipeline.py:2943--3080` that build the *prompt string* shown to the LLM solver but do not append to *leanFile*). The prompt-skeleton sites are outside `_build_lean_file` and do not contribute to the module text. $\square$

Lemma P.3 (Reserved names in per-source lifts). *For leanFile to be whitelist-compliant, every top-level declaration in* $\Lambda(s)$ *must have a name matching the regex* `lift_[0-9a-f]+_.+`. *In particular, per-source lift names must not collide with the identifiers* `claim_proof`, `claim_refutation`, `tableTool`, `statsTool`, *or any of the schemas* `obsN_*`/`csN_*`.

Proof. Whitelist compliance places each axiom in deps(*proof*) into exactly one of **B1**–**B4**. **B1** and **B2** are disjoint from the lift-name regex: the prelude declarations are named after the EG-VAR vocabulary in `src/lean/EGVar/*.lean`, and the three Lean core axioms are fixed names. The runtime-emitted schemas **B3** have forms `obsN_*`, `csN_*`, `tableTool`, `statsTool` that the regex `lift_[0-9a-f]+_.+` does not match. A per-source lift whose name collided with a reserved identifier would either (a) shadow a prelude declaration, causing elaboration failure at `lake env lean` invocation (rejected by Theorem P.1); (b) match a **B3** regex, causing `verify_axioms.py` to classify the axiom in the wrong bucket (a curation-audit failure the regex-conforming prefix rules out); or (c) collide with `claim_proof` / `claim_refutation`, triggering a declaration-name clash at elaboration time. The enforced `lift_<sourceHash>_<suffix>` prefix mechanically excludes all three. $\square$

Proof of Theorem 3.1. We proceed in three steps.

Step 1: the proof type-checks under the declared axiom set. The verdict VERIFIED is produced at Algorithm 1, line 17, only if KERNELCHECK(*leanFile*) returned (True, *output*) on line 15. By Theorem P.1, this implies *proof* : *goalType* in Lean 4's type theory under $\mathcal{A}$(*leanFile*), and in particular deps(*proof*) $\subseteq$ $\mathcal{A}$(*leanFile*).

Step 2: the closure is restricted to the whitelist buckets. Whitelist compliance of *leanFile* (the theorem's hypothesis) is the predicate that every element of deps(*proof*) lies in one of the buckets **B1**–**B4**, contains no `sorry`/`sorryAx`/`Lean.Axiom.sorry`, and contains a trust-artifact witness. The implementation at `src/python/runtime/verify_axioms.py` parses the `#print axioms` output and enforces each clause directly; Theorem P.3 makes the bucketing unambiguous.

Step 3: observation-leaf axioms in the closure are evidence-backed. Partition deps(*proof*) into four subsets $D_{\mathbf{B1}}, D_{\mathbf{B2}}, D_{\mathbf{B3}}, D_{\mathbf{B4}}$ by bucket. Step 2 covers the closure.

For every $\omega \in D_{\mathbf{B3}}$: the axiom ω was declared in *leanFile* by one of the emission sites tabulated in Table 10. By Theorem P.2, the emission was preceded in time by the runtime appending a corresponding triple to *evidence* (for `obsN_*`/`csN_*` axioms); the two `ToolId` axioms `tableTool` and `statsTool` are explicitly admitted without an evidence entry because they carry no payload. Hence every observation-leaf axiom in $D_{\mathbf{B3}} \cap$ deps(*proof*) is backed by an entry of *evidence*.

For $D_{\mathbf{B1}}$, each axiom is declared in one of the fixed EG-VAR prelude files (`EGVar/Basic.lean`, `EGVar/TableL1.lean`, `EGVar/WorldOntology.lean`, `EGVar/Tactics.lean`), committed at the repository hash reported in Section G.

For $D_{\mathbf{B2}}$, each axiom is one of `Classical.choice`, `Quot.sound`, or `propext` from Lean 4's core library.

For $D_{\mathbf{B4}}$, each axiom has a name matching `lift_[0-9a-f]+_.+` with hex prefix equal to the MD5 of s; the whitelist predicate enforces this regex, and the full set of such axioms is committed to `data/tier1_table_formalizations.json` at the reported commit hash.

Combining steps 1–3, any $\omega \in$ deps(*proof*) is either (a) a prelude axiom from $D_{\mathbf{B1}}$, (b) a standard Lean core axiom from $D_{\mathbf{B2}}$, (c) a runtime-emitted observation-leaf backed by a prior tool execution in *evidence*, or (d) an audited per-source lift from $\Lambda(s)$. $\square$

Proof of Theorem 3.2. An "accepted inference step" is, by the definition of the runtime's VERIFIED verdict (Algorithm 1, line 17), one that appears in the term *proof* returned by KERNELCHECK(*leanFile*) with accepted = True. By Theorem P.1, *proof* type-checks under the axiom set declared in *leanFile*. The kernel's type-correctness invariant requires that *proof* is constructed by a finite, typing-rule-compliant sequence of inference steps leading to *proof* : *goalType*; consequently every such inference step is valid in Lean 4's dependent type theory relative to the declared axioms. $\square$