Isometric Transformation Invariant and Equivariant Graph Convolutional Networks

Abstract

Graphs are one of the most important data structures for representing pairwise relations between objects. Specifically, a graph embedded in a Euclidean space is essential to solving real problems, such as physical simulation. A crucial requirement to applying a graph in a Euclidean space to physical simulations is learning and inferring the isometric transformation invariant and equivariant features in a computationally efficient manner. In the present paper, we propose a set of transformation invariant and equivariant models based on graph convolutional networks, called IsoGCNs. We demonstrate that the proposed model has competitive performance against state-of-the-art methods on tasks related with geometrical and physical simulation data. Moreover, the proposed model can scale up to the graphs with 1M vertices and conduct an inference faster than a conventional finite element analysis, which the existing equvariant models cannot achieve.

1 Introduction

Graph-structured data embedded in a Euclidean space can be utilized in many different fields such as object detection, structural chemistry analysis, and physical simulation. Graph neural networks (GNNs) have been introduced to deal with such data. Crucial properties of a GNN include its permutation invariance and equivariance. In addition to permutations, isometric transformation invariance and equivariance must be addressed when considering the graphs in a Euclidean space because many properties of objects in the Euclidean space do not change under translation and rotation. Due to these invariance and equivariance, 1) interpretation of the model can be easier; 2) the output of the model can be stable and predictable; and 3) training can be efficient by eliminating the necessity of data augmentation as discussed in literatures (Thomas et al., 2018; Weiler et al., 2018; Fuchs et al., 2020).

Especially for applications to physical simulations, isometric transformation invariance and equivariance are inevitable because every physical quantity and physical law is either invariant or equivariant to such a transformation. Another essential requirement for that application is computational efficiency because the primal objective to learn physical simulation is to replace a computationally expensive simulation method with a machine learning model.

In the present paper, we propose *IsoGCNs*, a set of simple yet powerful models providing computationally-efficient isometric transformation invariance and equivariance based on graph convolutional networks (GCNs) (Kipf & Welling, 2017). Specifically, by simply tweaking the definition of an adjacency matrix, the proposed model is sufficiently simple for realizing isometric transformation invariance. Because the proposed approach relies on graphs, it can deal with complex shapes, which are usually presented in mesh or point cloud data structures. Besides, a specific form of the IsoGCN layer can be regarded as a spatial differential operator, which is essential to describe physical laws. Also, we have shown that the proposed approach is computationally efficient in terms of processing the graphs with up to 1M vertices, which are often presented in physical simulations corresponding to realistic problems. Moreover, the proposed model showed faster inference compared to a conventional finite element analysis approach at the same level of accuracy. Therefore, IsoGCN is suitable to replace physical simulations in terms of both expressive power of physical law and faster, scalable computation.

The main contributions of the present paper can be summarized as follows:

- We construct isometric invariant and equivariant GCNs, called IsoGCNs for the specified input and output tensor ranks.

- We demonstrate that an IsoGCN model has competitive performance against state-of-the-art baseline models on the considered tasks related to physical simulations.

- We confirm that IsoGCN is computationally efficient to scale up to graphs with 1M vertices and achieves inference considerably faster than a conventional finite element analysis.

2 RELATED WORK

Graph neural networks. The concept of a GNN was first proposed by Baskin et al. (1997); Sperduti & Starita (1997) and then improved by (Gori et al., 2005; Scarselli et al., 2008). Although many variants of GNNs have been proposed, these models have been unified under the concept of message passing neural networks (Gilmer et al., 2017). Generally, message passing is computed with nonlinear neural networks, which can lead to tremendous computational cost. By contrast, GCN developed by Kipf & Welling (2017) is a considerable simplification of a GNN, using a linear message passing scheme expressed as

$$\boldsymbol{H}_{\text{out}} = \sigma(\hat{\boldsymbol{A}}\boldsymbol{H}_{\text{in}}\boldsymbol{W}), \tag{1}$$

where $\boldsymbol{H}_{\text{in}}$ ($\boldsymbol{H}_{\text{out}}$) is an input (output) feature of the lth layer, $\hat{\boldsymbol{A}}$ is a renormalized adjacency matrix with self-loops, and $\boldsymbol{W}$ is a trainable weight. Among variants of GNNs, the use of a GCN is essential to the present study, because the proposed model is based on GCNs for computational efficiency.

Invariant and equivariant neural networks. A function $f : X \rightarrow Y$ is said to be equivariant to a group G when $f(g \cdot x) = g \cdot f(x)$ for all $g \in G$ and $x \in X$, assuming the group G acts on both X and Y. In particular, when $f(g \cdot x) = f(x)$, f is said to be invariant to the group G. Group equivariant convolutional neural networks were first proposed by Cohen & Welling (2016) for discrete groups. Subsequent studies have categorized such networks into continuous groups (Cohen et al., 2018), three-dimensional data (Weiler et al., 2018), and general manifolds (Cohen et al., 2019). These methods are based on CNN; thus, they cannot handle mesh or point cloud data structures as is. Specifically, 3D steerable CNNs (Weiler et al., 2018) uses voxels (regular grids), which are relatively easy to handle but not efficient because it represents both occupied and non-occupied parts of an object (Ahmed et al., 2018). Besides, a voxelized object tends to lose the smoothness of its shape, which can lead to drastically different behavior in a physical simulation, as typically observed in structural analysis and computational fluid dynamics.

Thomas et al. (2018); Kondor (2018) discussed the way to provide rotation equivariance to point clouds. Specifically, the tensor field network (TFN) (Thomas et al., 2018) is a point cloud based rotation and translation equivariant neural networks whose layer can be written as

$$\tilde{\mathbf{H}}_{\text{out},i}^{(l)} = w^{ll}\,\tilde{\mathbf{H}}_{\text{in},i}^{(l)} + \sum_{k \geq 0}\sum_{j \neq i}\boldsymbol{W}^{lk}(\boldsymbol{x}_j - \boldsymbol{x}_i)\,\tilde{\mathbf{H}}_{\text{in},i}^{(k)}, \tag{2}$$

$$\boldsymbol{W}^{lk}(\boldsymbol{x}) = \sum_{J=|k-l|}^{k+l}\phi_J^{lk}(\|\boldsymbol{x}\|)\sum_{m=-J}^{J}Y_{Jm}(\boldsymbol{x}/\|\boldsymbol{x}\|)\boldsymbol{Q}_{Jm}^{lk}, \tag{3}$$

where $\tilde{\mathbf{H}}_{\text{in},i}^{(l)}$ ($\tilde{\mathbf{H}}_{\text{out},i}^{(l)}$) is a type-$l$ input (output) feature at the ith vertex, $\phi_J^{lk} : \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}$ is a trainable function, Y_{Jm} is the mth component of the Jth spherical harmonics, and $\boldsymbol{Q}_{Jm}^{lk}$ is the Clebsch-Cordan coefficient. SE(3)-Transformer (Fuchs et al., 2020) is a variant of the TFN with self-attention. These models achieve a high expressibility based on spherical harmonics and message passing with nonlinear neural networks; however, for this reason, a considerable amount of computational resources are required. By contrast, the present study allows a significant reduction in the computational costs because it eliminates spherical harmonics and nonlinear message passing. From this point of view, IsoGCN is also regarded as a simplification of TFN, as seen in equation 14.

Physical simulations using GNNs. Several related studies, including those by Sanchez-Gonzalez et al. (2018; 2019); Alet et al. (2019); Chang & Cheng (2020) were focused on applying GNNs to learn physical simulations. These approaches allowed introducing the physical information into

GNNs; however, addressing isometric transformation invariance and equivariance was out of the scope of their research.

In the present study, we incorporate isometric transformation invariance and equivariance into GCNs, thereby ensuring the stability of the training and inference under an isometric transformation. Moreover, the proposed approach is efficient in processing large graphs with up to 1M vertices that have a sufficient number of degrees of freedom to express complex shapes.

3 ISOMETRIC TRANSFORMATION INVARIANT AND EQUIVARIANT GRAPH CONVOLUTIONAL LAYERS

In this section, we discuss a way to construct IsoGCN layers that correspond to the isometric invariant and equivariant GCN layers. To formulate a model, we assume: 1) only attributes associated with vertices and not edges; and 2) graphs do not contain self-loops. Here, $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ denotes a graph and d denotes the dimension of a Euclidean space. In this paper, we refer to tensor as geometric tensors, and we consider a (discrete) rank-p tensor field $\mathbf{H}^{(p)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d^p}$, where $|\mathcal{V}|$ denotes the number of vertices and $f \in \mathbb{Z}^+$ ($\mathbb{Z}^+$ denotes the positive integers). Here, f denotes the number of features (channels) of $\mathbf{H}^{(p)}$, as shown in figure 1 (a). With indices, we denote $H^{(p)}_{i;g;k_1 k_2 \ldots k_p}$, where i permutes under permutation of vertices and $k_1, \ldots, k_p$ refers to Euclidean representation. Thus, under permutation, $\pi : H^{(p)}_{i;g;k_1 k_2 \ldots k_p} \mapsto H^{(p)}_{\pi(i);g;k_1 k_2 \ldots k_p}$ and under orthogonal transformation, $\boldsymbol{U} : H^{(p)}_{i;g;k_1 k_2 \ldots k_p} \mapsto \sum_{l_1, l_2, \ldots, l_p} U_{k_1 l_1} U_{k_2 l_2} \ldots U_{k_p l_p} H^{(p)}_{i;g;l_1 l_2 \ldots l_p}$.

3.1 CONSTRUCTION OF AN ISOMETRIC ADJACENCY MATRIX

Before constructing an IsoGCN, we need to define an **isometric adjacency matrix** (IsoAM), which is at the core of the IsoGCN concept. The proof of each proposition can be found in Appendix B.

An IsoAM $\mathbf{G} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}| \times d}$ is defined as:

$$\mathbb{R}^d \ni \mathbf{G}_{ij;;:} := \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{T}_{ijkl}(\boldsymbol{x}_k - \boldsymbol{x}_l), \quad (4)$$

where $\mathbf{G}_{ij;;:}$ is a slice in the spatial index of $\mathbf{G}$, $\boldsymbol{x}_i \in \mathbb{R}^d$ is the position of the ith vertex (rank-1 tensor), and $\boldsymbol{T}_{ijkl} \in \mathbb{R}^{d \times d}$ is an untrainable transformation invariant and orthogonal transformation equivariant rank-2 tensor. Note that we denote $\mathbf{G}_{ij;;k}$ to be consistent with the no-

Figure 1: Schematic diagrams of (a) rank-1 tensor field $\mathbf{H}^{(1)}$ with the number of features equal to 2 and (b) the simplest case of $\mathbf{G}_{ij;;:} = \delta_{il}\delta_{jk}A_{ij}\boldsymbol{I}(\boldsymbol{x}_k - \boldsymbol{x}_l) = A_{ij}(\boldsymbol{x}_j - \boldsymbol{x}_i)$.

tation of $H^{(p)}_{i;g;k_1 k_2 \ldots k_p}$ because i and j permutes under vertex permutation and k represents spatial index while the number of feature is always 1. The IsoAM can be viewed as weighted adjacency matrix for each direction, thus it can reflect spatial information while an usual weighted adjacency matrix cannot have it because one graph has only one adjacency matrix. If the size of the set $\{G_{ij;;:} \neq \boldsymbol{0}\}_j$ is greater than or equal to d, then it can be deemed as a frame, which is a generalization of a basis. For the simplest case, one can define $\boldsymbol{T}_{ijkl} = \delta_{il}\delta_{jk}A_{ij}\boldsymbol{I}$ (figure 1 (b)), where δ_{ij} is the Kronecker delta, $\boldsymbol{A}$ is an adjacency matrix of the graph, and $\boldsymbol{I}$ is the identity matrix that is the simplest rank-2 tensor. For another case, $\boldsymbol{T}_{ijkl}$ can be determined from the geometry of a graph, as defined in equation 16. Nevertheless, in the majority of this section, we remain $\boldsymbol{T}_{ijkl}$ general to cover various forms of interaction, such as position-aware GNN (You et al., 2019). Here, $\mathbf{G}$ is composed of only untrainable parameters, and thus it can be determined prior to training.

Proposition 3.1. *IsoAM defined in equation 4 is both translation invariant and orthogonal transformation equivariant, i.e., for any isometric transformation $\forall \boldsymbol{t} \in \mathbb{R}^3, \boldsymbol{U} \in \mathrm{O}(d), T : \boldsymbol{x} \mapsto \boldsymbol{U}\boldsymbol{x} + \boldsymbol{t}$,*

$$T : \boldsymbol{G}_{ij;;k} \mapsto \sum_l U_{kl} \boldsymbol{G}_{ij;;l}. \quad (5)$$

Based on the definition of the GCN layer in the equation 1, let $\mathbf{G} * \mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d}$ denote the **convolution** between $\mathbf{G}$ and the rank-0 tensor field $\mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f}$ ($f \in \mathbb{Z}^+$) as follows:

$$(\mathbf{G} * \mathbf{H}^{(0)})_{i;g;k} := \sum_j \mathbf{G}_{ij;;k} H^{(0)}_{j;g;}. \tag{6}$$

With $\mathbf{G}$ and let $\mathbf{H}^{(1)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d}$, $\mathbf{G} \odot \mathbf{H}^{(1)} \in \mathbb{R}^{|\mathcal{V}| \times f}$ and $\mathbf{G} \odot \mathbf{G} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$ denote the **contractions** which are defined as follows:

$$(\mathbf{G} \odot \mathbf{H}^{(1)})_{i;g;} := \sum_{j,k} G_{ij;;k} H^{(1)}_{j;g;k}, \quad (\mathbf{G} \odot \mathbf{G})_{il;;} := \sum_{j,k} G_{ij;;k} G_{jl;k}. \tag{7}$$

The contraction of IsoAMs $\mathbf{G} \odot \mathbf{G}$ can be interpreted as the inner product of each component in the IsoAMs. Thus, the subsequent proposition follows.

Proposition 3.2. *The contraction of IsoAMs $\mathbf{G} \odot \mathbf{G}$ is isometric transformation invariant, i.e., for any isometric transformation $\forall \boldsymbol{t} \in \mathbb{R}^3, \boldsymbol{U} \in \mathrm{O}(d), T : \boldsymbol{x} \mapsto \boldsymbol{U}\boldsymbol{x} + \boldsymbol{t}, \mathbf{G} \odot \mathbf{G} \mapsto \mathbf{G} \odot \mathbf{G}$.*

With a rank-p tensor field $\mathbf{H}^{(p)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d^p}$, let $\mathbf{G} \otimes \mathbf{H}^{(p)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d^{1+p}}$ and $\mathbf{G} \otimes \mathbf{G} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}| \times d^2}$ denote the **tensor products** defined as follows:

$$(\mathbf{G} \otimes \mathbf{H}^{(p)})_{i;g;km_1m_2...m_p} := \sum_j \mathbf{G}_{ij;;k} H^{(p)}_{j;g;m_1m_2...m^p}, \tag{8}$$

$$(\mathbf{G} \otimes \mathbf{G})_{il;;k_1k_2} := \sum_j \mathbf{G}_{ij;;k_1} \mathbf{G}_{jl;;k_2} \tag{9}$$

The tensor product of IsoAMs $\mathbf{G} \otimes \mathbf{G}$ can be interpreted as the tensor product of each component in the IsoAMs. Thus, the subsequent proposition follows:

Proposition 3.3. *The tensor product of IsoAMs $\mathbf{G} \otimes \mathbf{G}$ is isometric transformation equivariant in terms of rank-2 tensor, i.e., for any isometric transformation $\forall \boldsymbol{t} \in \mathbb{R}^3, \boldsymbol{U} \in \mathrm{O}(d), T : \boldsymbol{x} \mapsto \boldsymbol{U}\boldsymbol{x} + \boldsymbol{t}$ and $\forall i, j \in 1, \ldots, |\mathcal{V}|, (\mathbf{G} \otimes \mathbf{G})_{ij;;k_1k_2} \mapsto \boldsymbol{U}_{k_1l_1} \boldsymbol{U}_{k_2l_2} (\mathbf{G} \otimes \mathbf{G})_{ij;;l_1l_2}$.*

It is possible to easily generalize this proposition to the tensors of higher ranks by defining the pth tensor power of $\mathbf{G}$ as follows: $\bigotimes^0 \mathbf{G} = 1$, $\bigotimes^1 \mathbf{G} = \mathbf{G}$, and $\bigotimes^p \mathbf{G} = \bigotimes^{p-1} \mathbf{G} \otimes \mathbf{G}$. Namely, $\bigotimes^p \mathbf{G}$ is isometric transformation equivariant in terms of rank-p tensor. Therefore, one can see that $(\bigotimes^p \mathbf{G}) \otimes \mathbf{H}^{(q)} = (\bigotimes^{p-1} \mathbf{G}) \otimes (\mathbf{G} \otimes \mathbf{H}^{(q)})$. Moreover, the convolution can be generalized for $\bigotimes^p \mathbf{G}$ and rank-0 tensor field $\mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f}$ as follows:

$$\left[\left(\bigotimes^p \mathbf{G} \right) * \mathbf{H}^{(0)} \right]_{i;g;k_1k_2...k_p} = \sum_j \left(\bigotimes^p \mathbf{G} \right)_{ij;;k_1k_2...k_p} H^{(0)}_{j;g;}. \tag{10}$$

The contraction can be generalized for $\bigotimes^p \mathbf{G}$ and the rank-q tensor field $\mathbf{H}^{(q)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d^q}$ ($p \geq q$) as specified below:

$$\left[\left(\bigotimes^p \mathbf{G} \right) \odot \mathbf{H}^{(q)} \right]_{i;g;k_1k_2...k_{p-q}} = \sum_{j,m_1,m_2,...,m_q} \left(\bigotimes^p \mathbf{G} \right)_{ij;;k_1k_2...k_{p-q}m_1m_2...m_q} H^{(q)}_{j;g;m_1m_2...m_q}. \tag{11}$$

For the case $p < q$, the contraction can be defined similarly.

3.2 CONSTRUCTION OF ISOGCN

An IsoGCN utilizes an IsoAM to realize the isometric transformation invariant and equivariant layers. Using the operations defined above, we can construct IsoGCN layers, which take the tensor field of any rank as input, and output the tensor field of any rank, which can differ from those of the input. In addition, one can show these layers are also equivariant under vertex permutation, as discussed in Maron et al. (2018).

3.2.1 ISOMETRIC TRANSFORMATION INVARIANT LAYER

As it can be seen in Proposition 3.1, the contraction of IsoAMs is isometric transformation invariant. Therefore, for the isometric transformation invariant layer with a rank-0 input tensor field $f : \mathbb{R}^{|\mathcal{V}| \times f_{\text{in}}} \ni \boldsymbol{H}_{\text{in}} \mapsto \boldsymbol{H}_{\text{out}} \in \mathbb{R}^{|\mathcal{V}| \times f_{\text{out}}}$ ($f_{\text{in}}, f_{\text{out}} \in \mathbb{Z}^+$), the activation function σ, and the trainable parameter matrix $W \in \mathbb{R}^{f_{\text{in}} \times f_{\text{out}}}$ can be constructed as $\boldsymbol{H}_{\text{out}} = \sigma\left((\mathbf{G} \odot \mathbf{G}) \boldsymbol{H}_{\text{in}} \boldsymbol{W}\right)$. By defining $\boldsymbol{L} := \mathbf{G} \odot \mathbf{G} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$, it can be simplified as $\boldsymbol{H}_{\text{out}} = \sigma\left(\boldsymbol{L} \boldsymbol{H}_{\text{in}} \boldsymbol{W}\right)$, which has the same form as a GCN (equation 1), with the exception that $\hat{A}$ is replaced with $\boldsymbol{L}$.

An isometric transformation invariant layer with the rank-p input tensor field $\mathbf{H}_{\text{in}}^{(p)} \in \mathbb{R}^{|\mathcal{V}| \times f_{\text{in}} \times d^p}$ can be formulated as $\boldsymbol{H}_{\text{out}} = F_{p \to 0}(\mathbf{H}^{(p)}) = \sigma\left([\bigotimes^p \mathbf{G} \odot \mathbf{H}_{\text{in}}^p] \boldsymbol{W}\right)$. If $p = 1$, such approaches utilize the inner products of the vectors in $\mathbb{R}^d$, these operations correspond to the extractions of a relative distance and an angle of each pair of vertices, which are employed in Klicpera et al. (2020).

3.2.2 ISOMETRIC TRANSFORMATION EQUIVARIANT LAYER

To construct an isometric transformation equivariant layer, one can use linear transformation, convolution and tensor product to the input tensors. If both the input and the output tensor ranks are greater than 0, one can apply neither nonlinear activation nor bias addition because these operations will cause an inappropriate distortion of the isometry, because isometric transformation does not commute with them in general. However, conversion using only linear transformation, convolution, and tensor product does not have nonlinearity, which limit the predictive performance of the model. To add nonlinearity to such a conversion, we can first convert the input tensors to rank-0 ones, apply nonlinear activations, and then multiply them to the higher rank tensors.

For instance, the nonlinear isometric transformation equivariant layer with the rank-m input tensor field $\mathbf{H}_{\text{in}}^{(m)} \in \mathbb{R}^{|\mathcal{V}| \times f_{\text{in}} \times d^m}$ and the rank-l ($m \leq l$) output tensor $\mathbf{H}_{\text{out}}^{(l)} \in \mathbb{R}^{|\mathcal{V}| \times f_{\text{out}} \times d^l}$ can be defined as:

$$\mathbf{H}_{\text{out}}^{(l)} = F_{m \to 0}\left(\mathbf{H}_{\text{in}}^{(m)}\right) \times \mathbf{F}_{m \to l}\left(\mathbf{H}_{\text{in}}^{(m)}\right), \quad \mathbf{F}_{m \to l}\left(\mathbf{H}_{\text{in}}^{(m)}\right) = \left[\overset{l-m}{\bigotimes} \mathbf{G}\right] \otimes \mathbf{H}_{\text{in}}^{(m)} \boldsymbol{W}^{ml}, \quad (12)$$

where $\times$ denotes the multiplication with broadcasting. and $\boldsymbol{W}^{ml} \in \mathbb{R}^{f_{\text{in}} \times f_{\text{out}}}$ are trainable weight matrices multiplied in the feature direction. If $m = 0$, regard $\mathbf{G} \otimes \mathbf{H}^{(0)}$ as $\mathbf{G} * \mathbf{H}^{(0)}$. If $m = l$, one can add the residual connection (He et al., 2016) in the equation 12. If $m > l$,

$$\mathbf{H}_{\text{out}}^{(l)} = F_{m \to 0}\left(\mathbf{H}_{\text{in}}^{(m)}\right) \times \mathbf{F}_{m \to l}\left(\mathbf{H}_{\text{in}}^{(m)}\right), \quad \mathbf{F}_{m \to l}\left(\mathbf{H}_{\text{in}}^{(m)}\right) = \left[\overset{m-l}{\bigotimes} \mathbf{G}\right] \odot \mathbf{H}_{\text{in}}^{(m)} \boldsymbol{W}^{ml}. \quad (13)$$

In general, the nonlinear isometric transformation equivariant layer with the rank-0 to rank-M input tensor field $\{\mathbf{H}_{\text{in}}^{(m)}\}_{m=0}^{M}$ and the rank-l output tensor field $\mathbf{H}_{\text{out}}^{(l)}$ can be defined as:

$$\mathbf{H}_{\text{out}}^{(l)} = \mathbf{H}_{\text{in}}^{(l)} \boldsymbol{W} + \sum_{m=0}^{M} f_{\text{gather}}\left(\left\{F_{k \to 0}(\mathbf{H}_{\text{in}}^{(k)})\right\}_{k=0}^{M}\right) \times \mathbf{F}_{m \to l}\left(\mathbf{H}_{\text{in}}^{(m)}\right) \quad (14)$$

where f_{gather} denotes a function such as summation, product and concatenation in the feature direction. One can see that this layer is similar to that in TFN (equation 2), while this IsoGCN layer has no spherical harmonics and trainable message passing.

To be exact, the output of the layer defined above is translation invariant. To output translation equivariant variable such as the vertex positions after deformation (which change accordingly with the translation of the input graph), one can first define the reference vertex position $\boldsymbol{x}_{\text{ref}}$ for each graph, then compute translation invariant output using the equation 14, and finally add $\boldsymbol{x}_{\text{ref}}$ to the output. For more detailed information of IsoGCN modeling, see Appendix D.

3.3 EXAMPLE OF ISOAM

The IsoGCN $\mathbf{G}$ is defined in a general form, so that the propositions can work with various classes of graph. In this section, we concretize the concept of the IsoAM to apply IsoGCN

to mesh structured data. Here, a mesh is regarded as a graph with regarding the points in the mesh as vertices of the graph and assuming two vertices are connected when they share the same cell. A concrete instance of IsoAM $\tilde{\mathbf{D}}, \mathbf{D} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}| \times d}$ is defined as follows:

$$\tilde{D}_{ij;;k} = D_{ijk} - \delta_{ij} \sum_l D_{ilk}, \tag{15}$$

$$D_{ij;;;} = \boldsymbol{M}_i^{-1} \frac{\boldsymbol{x}_j - \boldsymbol{x}_i}{\|\boldsymbol{x}_j - \boldsymbol{x}_i\|^2} w_{ij} A_{ij}(m), \tag{16}$$

$$\boldsymbol{M}_i = \sum_l \frac{\boldsymbol{x}_l - \boldsymbol{x}_i}{\|\boldsymbol{x}_l - \boldsymbol{x}_i\|} \otimes \frac{\boldsymbol{x}_l - \boldsymbol{x}_i}{\|\boldsymbol{x}_l - \boldsymbol{x}_i\|} w_{il} A_{il}(m), \tag{17}$$

where $\mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|} \ni \boldsymbol{A}(m) := \min(\sum_{k=1}^m \boldsymbol{A}^k, 1)$ is an adjacency matrix up to m hops and $w_{ij} \in \mathbb{R}$ is an untrainable weight between the ith and jth vertices determined depending on the tasks[1]. By regarding $\boldsymbol{T}_{ijkl} =$

Table 1: Correspondence between the differential operators and the expressions using the IsoAM $\tilde{\mathbf{D}}$.

Differential op.	Expression
Gradient	$\tilde{\mathbf{D}} * \mathbf{H}^{(0)}$
Divergence	$\tilde{\mathbf{D}} \odot \mathbf{H}^{(1)}$
Laplacian	$\tilde{\mathbf{D}} \odot \tilde{\mathbf{D}}\mathbf{H}^{(0)}$
Jacobian	$\tilde{\mathbf{D}} \otimes \mathbf{H}^{(1)}$
Hessian	$\tilde{\mathbf{D}} \otimes \tilde{\mathbf{D}} * \mathbf{H}^{(0)}$

$\delta_{il} \delta_{jk} \boldsymbol{M}_i^{-1} w_{ij} \boldsymbol{A}_{ij}(m)/\|\boldsymbol{x}_j - \boldsymbol{x}_i\|^2$ in equation 4, one can see that $\mathbf{D}$ is qualified as an IsoAM. Because a linear combination of IsoAMs is also an IsoAM, $\tilde{\mathbf{D}}$ is an IsoAM. Thus, they provide both translation invariance and orthogonal transformation equivariance. $\tilde{\mathbf{D}}$ can be obtained only from mesh geometry information, thus can be computed in the preprocessing step.

Here, $\tilde{\mathbf{D}}$ is designed such that it corresponds to the gradient operator model used in physical simulations (Tamai & Koshizuka, 2014; Swartz & Wendroff, 1969). As presented in Table 1 and Appendix C, $\tilde{\mathbf{D}}$ is closely related to many differential operators such as gradient, divergence, Laplacian, Jacobian, and Hessian ones. Therefore, the considered IsoAM plays an essential role in constructing the neural network models that are capable of learning differential equations.

4 EXPERIMENT

To test the applicability of the proposed model, we composed the following two datasets: 1) a differential operator dataset of grid meshes; and 2) an anisotropic nonlinear heat equation dataset of meshes generated from CAD data. In this section, we discuss our machine learning model, the definition of the problem, and the results for each dataset.

Using $\tilde{\mathbf{D}}$ defined in Section 3.3, we constructed a neural network model considering an encode-process-decode configuration (Battaglia et al., 2018). The encoder and decoder comprised component-wise MLPs and tensor operations. For each task, we tested $m = 2, 5$ in equation 15 to investigate the effect of the number of hops considered. In addition to GCN (Kipf & Welling, 2017), we chose GIN (Xu et al., 2018), SGCN (Wu et al., 2019), Cluster-GCN (Chiang et al., 2019), and GCNII (Chen et al., 2020) as GCN variant baseline models. For equivariant models, we chose TFN (Thomas et al., 2018), SE(3)-Transformer (Fuchs et al., 2020) as baseline. We implemented these models using PyTorch 1.6.0 (Paszke et al., 2019) and PyTorch Geometric 1.6.1 (Fey & Lenssen, 2019). For both TFN and SE(3)-Transformer, we used implementation of Fuchs et al. (2020) [2] because the computation of TFN is considerably faster than the original implementation, as claimed in Fuchs et al. (2020). For each experiment, we minimized the mean squared loss using the Adam optimizer (Kingma & Ba, 2014). The corresponding implementation and the dataset will be made available online. The details of the experiments can be found in Appendix E and F.

4.1 DIFFERENTIAL OPERATOR DATASET

To demonstrate the expressive power of IsoGCN, we created a dataset to learn the differential operators. We first generate a pseudo-2D grid mesh randomly, which has only one cell in the Z direction and 10 to 100 cells in the X and Y directions. We then generated scalar fields on the grid meshes,

---

[1] $\boldsymbol{M}_i$ is invertible when the number of independent vectors in $\{\boldsymbol{x}_l - \boldsymbol{x}_i\}_l$ is greater than or equal to the space dimension d, which is true for common meshes, e.g., solid mesh in the 3D Euclidean space.

[2] https://github.com/FabianFuchsML/se3-transformer-public

Figure 2: (Top) the gradient field and (bottom) the error vector between the prediction and the ground truth of a test data sample. The error vectors are exaggerated by a factor of 2 for a clear visualization.

Table 2: Summary of the test losses (mean squared error $\pm$ the standard error of the mean, in the original scale) of the differential operator dataset: $0 \to 1$ (the scalar field to the gradient field), $0 \to 2$ (the scalar field to the Hessian field), $1 \to 0$ (the gradient field to the Laplacian field), and $1 \to 2$ (the gradient field to the Hessian field). Here, if "x" is "Yes", it means x is also in the input feature. We show only the best setting for each method except for the equivariant models. For a full table, see Appendix E. OOM denotes the out-of-memory on the applied GPU (32 GiB).

Method	# hops	x	Loss of $0 \to 1$ $\times 10^{-5}$	Loss of $0 \to 2$ $\times 10^{-6}$	Loss of $1 \to 0$ $\times 10^{-6}$	Loss of $1 \to 2$ $\times 10^{-6}$
GIN	5	Yes	147.07 ± 0.51	47.35 ± 0.35	404.92 ± 1.74	46.18 ± 0.39
GCNII	5	Yes	151.13 ± 0.53	31.87 ± 0.22	280.61 ± 1.30	39.38 ± 0.34
SGCN	5	Yes	151.16 ± 0.53	55.08 ± 0.42	127.21 ± 0.63	56.97 ± 0.44
GCN	5	Yes	151.14 ± 0.53	48.50 ± 0.35	542.30 ± 2.14	25.37 ± 0.28
Cluster-GCN	5	Yes	146.91 ± 0.51	26.60 ± 0.19	185.21 ± 0.99	18.18 ± 0.20
TFN	2	No	2.47 ± 0.02	OOM	26.69 ± 0.24	OOM
	5	No	OOM	OOM	OOM	OOM
SE(3)-Trans.	2	No	$\mathbf{1.79} \pm 0.02$	$\mathbf{3.50} \pm 0.04$	$\mathbf{2.52} \pm 0.02$	OOM
	5	No	2.12 ± 0.02	OOM	7.66 ± 0.05	OOM
IsoGCN (Ours)	2	No	2.67 ± 0.02	6.37 ± 0.07	7.18 ± 0.06	$\mathbf{1.44} \pm 0.02$
	5	No	14.19 ± 0.10	21.72 ± 0.25	34.09 ± 0.19	8.32 ± 0.09

and then calculated the gradient, Laplacian, and Hessian fields analytically. We generated 100 samples for each train, validation, and test dataset. For simplicity, we set $w_{ij} = 1$ in equation 15 for all $(i, j) \in \mathcal{E}$. To compare the performance with the GCN models, we simply replaced an IsoGCN layer with a GCN or its variant layers while keeping the number of hops m the same to enable a fair comparison. For equivariant models, we adjusted the hyperparameters in the models to make the number of parameters in each model almost the same as that in the IsoGCN model. For more details regarding the model architecture, see Appendix E. We conducted the experiments using the following settings: 1) inputting the scalar field and predicting the gradient field (rank-0 $\to$ rank-1 tensor); 2) inputting the scalar field and predicting the Hessian field (rank-0 $\to$ rank-2 tensor); 3) inputting the gradient field and predicting the Laplacian field (rank-1 $\to$ rank-0 tensor); and 4) inputting the gradient field and predicting the Hessian field (rank-1 $\to$ rank-2 tensor).

Figure 2 and Table 2 present a visualization and comparison of predictive performance, respectively. The results show that an IsoGCN outperforms other GCN models for all settings. This is because IsoGCN has the information on the relative position of the adjacency vertices, and thus understands the direction of the gradient, whereas the other GCN models cannot distinguish where the adjacencies are, making it nearly impossible to predict the gradient directions. Adding the vertex positions to the input feature to other GCN models showed performance improvement, however as the vertex position was not a translation invariant feature, it could degrade the predictive performance of models. Thus, we did not input x as a vertex feature to the IsoGCN model or other equivariant models to keep isometric transformation invariant and equivariant nature of them. Compared to other equivari-

ant models, IsoGCN has competitive performance with shorter inference time as shown in Table 7. As mentioned in Section 3.3, $\tilde{\mathbf{D}}$ corresponds to the gradient operator, which is now confirmed in practice.

4.2 ANISOTROPIC NONLINEAR HEAT EQUATION DATASET

To apply the proposed model to a real problem, we adopted the anisotropic nonlinear heat equation. We considered the task of predicting the time evolution of the temperature field based on the initial temperature field, material property, and mesh geometry information as inputs. We selected 82 CAD shapes by randomly considering the first 200 shapes of the ABC dataset (Koch et al., 2019), generate first-order tetrahedral meshes using a mesher program Gmsh (Geuzaine & Remacle, 2009), randomly set the initial temperature and anisotropic thermal conductivity, and finally conducted a finite element analysis (FEA) using the FEA program FrontISTR[3] (Morita et al., 2016; Ihara et al., 2017).

For this task, we set $w_{ij} = V_j^{\text{effective}}/V_i^{\text{effective}}$, where $V_i^{\text{effective}}$ denotes the effective volume of the ith vertex (equation 46.) Similar to the differential operator dataset, we tested the number of hops $m = 2, 5$. However, because we put four IsoAM operations in one model, the number of hops visible from the model is 8 ($m = 2$) or 20 ($m = 5$). As is the case with the differential operator dataset, we replaced an IsoGCN layer accordingly for GCN or its variant models. For equivariant models, in the case of $k = 2$, we made the number of parameters in each models smaller than that in the IsoGCN model, because the models did not fit into the memory of the GPU (NVIDIA Tesla V100 with 32 GiB memory) with the same level of the number of parameters. In the case of $k = 5$, both TFN and SE(3)-Transformer did not fit into the memory of the GPU even with the number of parameters equal to 10. For more details about the used dataset and the model, see Appendix F.

Figure 3 and Table 3 present the results of the qualitative and quantitative comparisons for the test dataset. It can be seen that IsoGCN outperforms all other baseline models. Moreover, owing to the computationally efficient and isometric transformation invariant nature of IsoGCN, it also achieved a high prediction performance for the meshes that had a significantly larger graph than those considered in the training dataset. IsoGCN can scales up to 1M vertices (figure 7), which is a practical scale and considerably greater than that reported in Sanchez-Gonzalez et al. (2020). Therefore, we conclude that the IsoGCN models could be trained on a relatively smaller meshes[4] to save the training time and then used to apply an inference of larger meshes without observing significant performance deterioration.

Figure 3: (Top) the temperature field of the ground truth and inference results and (bottom) the error between the prediction and the ground truth of a test data sample. The error is exaggerated by a factor of 2 for a clear visualization.

---

[3]https://github.com/FrontISTR/FrontISTR. We applied a private update to FrontISTR to deal with anisotropic heat problem, which will be also made available online.

[4]However, it should be also sufficiently large in order to express sample shapes and fields.

Table 4 reports the computation time of preprocessing and inference using the equivariant models with $m = 2$ as the number of hops and FEA using FrontISTR 5.0.0. For the FEA computation, we varied the time step ($\Delta t = 1.0, 0.5$) to compute $t = 1.0$ time evolution, thus resulting in the different computation time and error compared to an FEA with $\Delta t = 0.01$, which were considered as the ground truth. It can be seen that IsoGCN is 3- to 5- times faster than the FEA with the same level of accuracy, while other equivariant models has almost the same speed as FrontISTR with $\Delta t = 0.5$.

5 CONCLUSION

In the present study, we proposed the GCN-based isometric transformation invariant and equivariant models called *IsoGCN*. We discussed an example of an isometric adjacency matrix (IsoAM) that was closely related to the essential differential operators. The experiment results confirmed that the proposed model leveraged the spatial structures and can deal with large-scale graphs. The computation time of the IsoGCN model is significantly shorter than FEA, which other equivariant models cannot achieve. Therefore, IsoGCN must be the first choice to learn physical simulations because of its computational efficiency and isometric transformation invariance and equivariance. Our demonstrations were conducted on the mesh structured dataset based on the FEA results. However, we expect IsoGCN to be applicable to various domains, such as object detection, molecular properties prediction, and physical simulations using particles.

Table 3: Summary of the test losses (mean squared error $\pm$ the standard error of the mean, in the original scale) of the anisotropic nonlinear heat dataset. Here, if "$\boldsymbol{x}$" is "Yes", it means $\boldsymbol{x}$ is also in the input feature. We show only the best setting for each method except for the equivariant models. For the full table, see Appendix E. OOM denotes the out-of-memory on the applied GPU (32 GiB).

Method	# hops	$\boldsymbol{x}$	Loss $\times 10^{-3}$
GIN	2	No	16.921 ± 0.040
GCN	2	No	10.427 ± 0.028
GCNII	5	No	8.377 ± 0.024
Gluster-GCN	2	No	7.266 ± 0.021
SGCN	5	No	6.426 ± 0.018
TFN	2	No	15.661 ± 0.019
	5	No	OOM
SE(3)-Trans.	2	No	14.164 ± 0.018
	5	No	OOM
IsoGCN (Ours)	2	No	4.674 ± 0.014
	5	No	$\mathbf{2.470} \pm 0.008$

Table 4: Comparison of computation time. To generate the test data, we sampled CAD data from the test dataset and then generated the mesh such that the graph gets large with keeping the element volume sizes almost the same. The initial temperature field and the material properties are set randomly using the same methodology as the dataset sample generation. For a fair comparison, each computation were run on the same CPU (Intel Xeon E5-2695 v2@2.40GHz) using one core, and we excluded file I/O time from the measured time. OOM denotes the out-of-memory (500 GiB).

Method	$|\mathcal{V}| = 21,289$		$|\mathcal{V}| = 155,019$		$|\mathcal{V}| = 1,011,301$	
	Loss $\times 10^{-4}$	Time [s]	Loss $\times 10^{-4}$	Time [s]	Loss $\times 10^{-4}$	Time [s]
FrontISTR ($\Delta t = 1.0$)	10.9	16.7	6.1	181.7	2.9	1656.5
FrontISTR ($\Delta t = 0.5$)	0.8	30.5	0.4	288.0	0.2	2884.2
TFN	77.9	46.1	30.1	400.9	OOM	OOM
SE(3)-Transformer	111.4	31.2	80.3	271.1	OOM	OOM
IsoGCN (Ours)	8.1	**7.4**	4.9	**84.1**	3.9	**648.4**

REFERENCES

Eman Ahmed, Alexandre Saint, Abd El Rahman Shabayek, Kseniya Cherenkova, Rig Das, Gleb Gusev, Djamila Aouada, and Bjorn Ottersten. A survey on deep learning advances on different 3d data representations. *arXiv preprint arXiv:1808.01462*, 2018.

Ferran Alet, Adarsh Keshav Jeewajee, Maria Bauza Villalonga, Alberto Rodriguez, Tomas Lozano-Perez, and Leslie Kaelbling. Graph element networks: adaptive, structured computation and memory. In *ICML*, 2019.

Igor I Baskin, Vladimir A Palyulin, and Nikolai S Zefirov. A neural device for searching direct correlations between structures and properties of chemical compounds. *Journal of chemical information and computer sciences*, 37(4):715–721, 1997.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Kai-Hung Chang and Chin-Yi Cheng. Learning to simulate and design for structural engineering. *arXiv preprint arXiv:2003.09103*, 2020.

Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. *arXiv preprint arXiv:2007.02133*, 2020.

Wei-Lin Chiang, Xuanqing Liu, Si Si, Yang Li, Samy Bengio, and Cho-Jui Hsieh. Cluster-gcn: An efficient algorithm for training deep and large graph convolutional networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 257–266, 2019.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *7nternational conference on machine learning*, pp. 2990–2999, 2016.

Taco S Cohen, Mario Geiger, Jonas Köhler, and Max Welling. Spherical cnns. In *ICLR*, 2018.

Taco S Cohen, Maurice Weiler, Berkay Kicanaoglu, and Max Welling. Gauge equivariant convolutional networks and the icosahedral cnn. *ICML*, 2019.

Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.

Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d rototranslation equivariant attention networks. *Advances in Neural Information Processing Systems*, 33, 2020.

Christophe Geuzaine and Jean-François Remacle. Gmsh: a three-dimensional finite element mesh generator with built-in pre- and post-processing facilities. *International Journal for Numerical Methods in Engineering*, 79(11):1309–1331, 2009.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1263–1272. JMLR. org, 2017.

Marco Gori, Gabriele Monfardini, and Franco Scarselli. A new model for learning in graph domains. In *Proceedings. 2005 IEEE International Joint Conference on Neural Networks, 2005.*, volume 2, pp. 729–734. IEEE, 2005.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Yu Ihara, Gaku Hashimoto, and Hiroshi Okuda. Web-based integrated cloud cae platform for large-scale finite element analysis. *Mechanical Engineering Letters*, 3:17–00520, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

Johannes Klicpera, Janek Groß, and Stephan Günnemann. Directional message passing for molecular graphs. In *ICLR*, 2020.

Sebastian Koch, Albert Matveev, Zhongshi Jiang, Francis Williams, Alexey Artemov, Evgeny Burnaev, Marc Alexa, Denis Zorin, and Daniele Panozzo. Abc: A big cad model dataset for geometric deep learning. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Risi Kondor. N-body networks: a covariant hierarchical neural network architecture for learning atomic potentials. *arXiv preprint arXiv:1803.01588*, 2018.

Haggai Maron, Heli Ben-Hamu, Nadav Shamir, and Yaron Lipman. Invariant and equivariant graph networks. *arXiv preprint arXiv:1812.09902*, 2018.

Naoki Morita, Kazuo Yonekura, Ichiro Yasuzumi, Mitsuyoshi Tsunori, Gaku Hashimoto, and Hiroshi Okuda. Development of 3×3 dof blocking structural elements to enhance the computational intensity of iterative linear solver. *Mechanical Engineering Letters*, 2:16–00082, 2016.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th international conference on machine learning (ICML-10)*, pp. 807–814, 2010.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin Riedmiller, Raia Hadsell, and Peter Battaglia. Graph networks as learnable physics engines for inference and control. *arXiv preprint arXiv:1806.01242*, 2018.

Alvaro Sanchez-Gonzalez, Victor Bapst, Kyle Cranmer, and Peter Battaglia. Hamiltonian graph networks with ode integrators. *arXiv preprint arXiv:1909.12790*, 2019.

Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter W Battaglia. Learning to simulate complex physics with graph networks. *arXiv preprint arXiv:2002.09405*, 2020.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2008.

Alessandro Sperduti and Antonina Starita. Supervised neural networks for the classification of structures. *IEEE Transactions on Neural Networks*, 8(3):714–735, 1997.

Blair Swartz and Burton Wendroff. Generalized finite-difference schemes. *Mathematics of Computation*, 23(105):37–49, 1969.

Tasuku Tamai and Seiichi Koshizuka. Least squares moving particle semi-implicit method. *Computational Particle Mechanics*, 1(3):277–305, 2014.

Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

Maurice Weiler, Mario Geiger, Max Welling, Wouter Boomsma, and Taco S Cohen. 3d steerable cnns: Learning rotationally equivariant features in volumetric data. In *NeurIPS*, pp. 10381–10392, 2018.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *ICML*, pp. 6861–6871. PMLR, 2019.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

Jiaxuan You, Rex Ying, and Jure Leskovec. Position-aware graph neural networks. *arXiv preprint arXiv:1906.04817*, 2019.

A NOTATION

$\mathcal{G}$	A graph
$\mathcal{V}$	A vertex set
$|\mathcal{V}|$	The number of vertices
$\mathcal{E}$	An edge set
$\mathbb{Z}^+$	The positive integers
d	The dimension of the Euclidean space
$\boldsymbol{x}_i$	The position of the ith vertex
x_{ik}	Element k of $\boldsymbol{x}_i$
$\mathbf{G} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}| \times d}$	The isometric adjacency matrix (IsoAM) (equation 4)
$\mathbf{G}_{ij;:} \in \mathbb{R}^d$	Slice of $\mathbf{G}$ in the spatial index (equation 4)
$\mathbf{G}_{ij;:k} \in \mathbb{R}$	Element (i, j, k) of $\mathbf{G}$
$\mathbf{H}^{(p)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d^p}$	A rank-p tensor field tensor ($f, p \in \mathbb{Z}^+$)
$H^{(p)}_{i;g;k_1 k_2 \ldots k_p}$	Element $(i; g; k_1, k_2, \ldots, k_p)$ of $\mathbf{H}^{(p)}$. i refers to the permutation representation, $k_1, \ldots k_p$ refer to the Euclidean representation, and g denotes the feature index (See section 3).
$\left[\bigotimes^{p} \mathbf{G} \right] * \mathbf{H}^{(0)}$	Convolution of the pth power of $\mathbf{G}$ and rank-0 tensor field $\mathbf{H}^{(0)}$ (equation 6, equation 10)
$\left[\bigotimes^{p} \mathbf{G} \right] \odot \mathbf{H}^{(q)}$	Contraction of the pth power of $\mathbf{G}$ and rank-q tensor fields (equation 7, equation 11)
$\left[\bigotimes^{p} \mathbf{G} \right] \otimes \mathbf{H}^{(q)}$	Tensor product of the pth power of $\mathbf{G}$ and rank-q tensor fields $\mathbf{H}^{(q)}$ (equation 8)
$\mathbf{H}^{(p)}_{\text{in}}$	The rank-p input tensor field of the considered layer
$\mathbf{H}^{(p)}_{\text{out}}$	The rank-p output tensor field of the considered layer
σ	The activation function
$\boldsymbol{W}$	The trainable parameter matrix
$\boldsymbol{A} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$	An adjacency matrix
δ_{ij}	The Kronecker delta
$V_i^{\text{effective}}$	The effective volume of the ith vertex (equation 46)
V_i^{mean}	The mean volume of the ith vertex (equation 47)
$\tilde{\mathbf{D}} \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$	An IsoAM (equation 15)

B   Proofs of propositions

In this section, we present the proofs of the propositions described in Section 3. Let $\mathbb{R}^3 \ni \boldsymbol{g}(\boldsymbol{x}_l, \boldsymbol{x}_k) = (\boldsymbol{x}_k - \boldsymbol{x}_l)$. Note that $\mathbf{G}$ is expressed using $\boldsymbol{g}(\boldsymbol{x}_i, \boldsymbol{x}_j)$ as $\mathbf{G}_{ij;;:} = \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{T}_{ijkl} \boldsymbol{g}(\boldsymbol{x}_l, \boldsymbol{x}_k)$.

B.1   Proof of Proposition 3.1

Proof. First, we demonstrate the invariance with respect to the translation with $\forall \boldsymbol{t} \in \mathbb{R}^d$. $\boldsymbol{g}(\boldsymbol{x}_i, \boldsymbol{x}_j)$ is transformed invariantly as follows under translation:

$$\begin{aligned} \boldsymbol{g}(\boldsymbol{x}_i + \boldsymbol{t}, \boldsymbol{x}_j + \boldsymbol{t}) &= [\boldsymbol{x}_j + \boldsymbol{t} - (\boldsymbol{x}_i + \boldsymbol{t})] \\ &= (\boldsymbol{x}_j - \boldsymbol{x}_i) \\ &= \boldsymbol{g}(\boldsymbol{x}_i, \boldsymbol{x}_j). \end{aligned} \tag{18}$$

By definition, $\boldsymbol{T}_{ijkl}$ is also translation invariant. Thus,

$$\begin{aligned} \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{T}_{ijkl} \boldsymbol{g}(\boldsymbol{x}_l + \boldsymbol{t}, \boldsymbol{x}_k + \boldsymbol{t}) &= \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{T}_{ijkl} \boldsymbol{g}(\boldsymbol{x}_l, \boldsymbol{x}_k) \\ &= \mathbf{G}_{ij;;:}. \end{aligned} \tag{19}$$

We then show an equivariance with respect to the orthogonal transformation with $\forall \boldsymbol{U} \in \mathrm{O}(d)$. $\boldsymbol{g}(\boldsymbol{x}_i, \boldsymbol{x}_j)$ is transformed as follows under an orthogonal transformation:

$$\begin{aligned} \boldsymbol{g}(\boldsymbol{U}\boldsymbol{x}_i, \boldsymbol{U}\boldsymbol{x}_j) &= \boldsymbol{U}\boldsymbol{x}_j - \boldsymbol{U}\boldsymbol{x}_i \\ &= \boldsymbol{U}(\boldsymbol{x}_j - \boldsymbol{x}_i) \\ &= \boldsymbol{U}\boldsymbol{g}(\boldsymbol{x}_i, \boldsymbol{x}_j). \end{aligned} \tag{20}$$

By definition, $\boldsymbol{T}_{ijkl}$ is transformed to $\boldsymbol{U}\boldsymbol{T}_{ijkl}\boldsymbol{U}^{-1}$ under orthogonal transformation. Thus,

$$\begin{aligned} \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{U}\boldsymbol{T}_{ijkl}\boldsymbol{U}^{-1}\boldsymbol{g}(\boldsymbol{U}\boldsymbol{x}_l, \boldsymbol{U}\boldsymbol{x}_k) &= \sum_{k,l \in \mathcal{V}, k \neq l} \boldsymbol{U}\boldsymbol{T}_{ijkl}\boldsymbol{U}^{-1}\boldsymbol{U}\boldsymbol{g}(\boldsymbol{x}_l, \boldsymbol{x}_k) \\ &= \boldsymbol{U}\mathbf{G}_{ij;;:}. \end{aligned} \tag{21}$$

Therefore, $\mathbf{G}$ is both translation invariant and orthogonal transformation equivariant. $\square$

B.2   Proof of Proposition 3.2

Proof. Here, $\mathbf{G} \odot \mathbf{G}$ is translation invariant because $\mathbf{G}$ is translation invariant. We prove rotation invariance under an orthogonal transformation $\forall \boldsymbol{U} \in \mathrm{O}(n)$. In addition, $\mathbf{G} \odot \mathbf{G}$ is transformed under the $\boldsymbol{U}$ as follows:

$$\begin{aligned} \sum_{j,k} \mathbf{G}_{ij;;k} \mathbf{G}_{jl;;k} &\mapsto \sum_{j,k,m,n} \boldsymbol{U}_{km} \mathbf{G}_{ij;;m} \boldsymbol{U}_{kn} \mathbf{G}_{jl;;n} \\ &= \sum_{j,k,m,n} \boldsymbol{U}_{km} \boldsymbol{U}_{kn} \mathbf{G}_{ij;;m} \mathbf{G}_{jl;;n} \\ &= \sum_{j,k,m,n} \boldsymbol{U}_{mk}^T \boldsymbol{U}_{kn} \mathbf{G}_{ij;;m} \mathbf{G}_{jl;;n} \\ &= \sum_{j,m,n} \delta_{mn} \mathbf{G}_{ij;;m} \mathbf{G}_{jl;;n} \qquad (\because \text{property of the orthogonal matrix}) \\ &= \sum_{j} \mathbf{G}_{ij;;m} \mathbf{G}_{jl;;m} \\ &= \sum_{j,k} \mathbf{G}_{ij;;k} \mathbf{G}_{jl;;k}. \qquad (\because \text{Change the dummy index } m \to k) \end{aligned} \tag{22}$$

Therefore, $\mathbf{G} \odot \mathbf{G}$ is isometric transformation invariant. $\square$

B.3 Proof of Proposition 3.3

Proof. $\mathbf{G} \otimes \mathbf{G}$ is transformed under $\forall \boldsymbol{U} \in \mathrm{O}(n)$ as follows:

$$
\sum_j \boldsymbol{G}_{ij;;k} \boldsymbol{G}_{jl;;m} \mapsto \sum_{n,o} \boldsymbol{U}_{kn} \boldsymbol{G}_{ij;;n} \boldsymbol{U}_{mo} \boldsymbol{G}_{jl;;o}
$$
$$
= \sum_{n,o} \boldsymbol{U}_{kn} \boldsymbol{G}_{ij;;n} \boldsymbol{G}_{jl;;o} \boldsymbol{U}_{om}^T. \tag{23}
$$

By regarding $\boldsymbol{G}_{ij;;n} \boldsymbol{G}_{jl;;o}$ as one matrix H_{no}, it follows the coordinate transformation of rank-2 tensor $\boldsymbol{U} \boldsymbol{H} \boldsymbol{U}^T$ for each i, j and l. $\qquad \square$

C Physical intuition of $\tilde{\mathbf{D}}$

In this section, we discuss the connection between the concrete example of IsoAM $\tilde{\mathbf{D}}$ and the differential operators such as the gradient, the divergence, the Laplacian, the Jacobian, and the Hessian operators.

Let $\phi_i \in \mathbb{R}$ denote a rank-0 tensor (scalar) ath the ith vertex. Let us assume a partial derivative model of a rank-0 tensor ϕ at the ith vertex regarding the kth axis $(\partial \phi / \partial x_k)_i \in \mathbb{R}$ ($k \in \{1, \ldots, d\}$), that is based on the gradient model in the least squares moving particle semi-implicit method (Tamai & Koshizuka, 2014).

$$
\left(\frac{\partial \phi}{\partial x_k} \right)_i := \boldsymbol{M}_i^{-1} \sum_j \frac{\phi_j - \phi_i}{\|\boldsymbol{x}_{jk} - \boldsymbol{x}_{ik}\|} \frac{x_{jk} - x_{ik}}{\|\boldsymbol{x}_j - \boldsymbol{x}_i\|} w_{ij} A_{ij}(m) \tag{24}
$$
$$
= \sum_j \boldsymbol{D}_{ijk} (\phi_j - \phi_i), \tag{25}
$$
$$
\boldsymbol{M}_i = \sum_l \frac{\boldsymbol{x}_l - \boldsymbol{x}_i}{\|\boldsymbol{x}_l - \boldsymbol{x}_i\|} \otimes \frac{\boldsymbol{x}_l - \boldsymbol{x}_i}{\|\boldsymbol{x}_l - \boldsymbol{x}_i\|} w_{il} A_{il}(m). \tag{26}
$$

Although one could define w_{ij} as a function of the distance $\|\boldsymbol{x}_j - \boldsymbol{x}_i\|$, we kept w_{ij} constant with respect to the distance required to maintain the simplicity of the model with fewer hyperparameters.

C.1 Gradient

$\tilde{\mathbf{D}}$ can be viewed as a Laplacian matrix based on $\mathbf{D}$; however, $\tilde{\mathbf{D}} * \mathbf{H}^{(0)}$ can be interpreted as the gradient within the Euclidean space. Let $\nabla \mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f \times d}$ be an approximation of the gradient of $\mathbf{H}^{(0)}$. Using equation 25, the gradient model can be expressed as follows:

$$
\left(\nabla \mathbf{H}^{(0)} \right)_{i;g;k} = \frac{\partial H^{(0)}_{i;g;}}{\partial x_k} \tag{27}
$$
$$
= D_{ijk} (H^{(0)}_{j;g;} - H^{(0)}_{i;g;}). \tag{28}
$$

Using this gradient model, we can confirm that $(\tilde{\mathbf{D}} * \mathbf{H}^{(0)})_{i;g;k} = (\nabla \mathbf{H}^{(0)})_{i;glk}$ because

$$
\begin{aligned}
\left(\tilde{\mathbf{D}} * \mathbf{H}^{(0)}\right)_{i;g;} &= \sum_j \tilde{D}_{ij;;k} H^{(0)}_{j;g;} & (29) \\
&= \sum_j (D_{ij;;k} - \delta_{ij} \sum_l D_{il;;k}) H^{(0)}_{j;g;} \\
&= \sum_j D_{ij;;k} H^{(0)}_{j;g;} - \sum_{j,l} \delta_{ij} D_{il;;k} H^{(0)}_{j;g;} \\
&= \sum_j D_{ij;;k} H^{(0)}_{j;g;} - \sum_l D_{il;;k} H^{(0)}_{i;g;} \\
&= \sum_j D_{ij;;k} H^{(0)}_{j;g;} - \sum_j D_{ij;;k} H^{(0)}_{i;g;} & (\because \text{Change the dummy index } l \to j) \\
&= \sum_j D_{ij;;k} (H^{(0)}_{j;g;} - H^{(0)}_{i;g;}) \\
&= \left(\nabla \mathbf{H}^{(0)}\right)_{i;g;k}. & (30)
\end{aligned}
$$

Therefore, $\tilde{\mathbf{D}}*$ can be interpreted as the gradient operator within a Euclidean space.

C.2   DIVERGENCE

We show that $\tilde{\mathbf{D}} \odot \mathbf{H}^{(1)}$ corresponds to the divergence. Using $\mathbf{D}$, the divergence model $\nabla \cdot \mathbf{H}^{(1)} \in \mathbb{R}^{|\mathcal{V}| \times f}$ is expressed as follows:

$$
\begin{aligned}
\left(\nabla \cdot \mathbf{H}^{(1)}\right)_{i;g;} &= \left(\sum_k \frac{\partial \mathbf{H}^{(1)}}{\partial x_k}\right)_{i;g;} & (31) \\
&= \sum_{j,k} D_{ij;;k} (H^{(1)}_{j;g;k} - H^{(1)}_{i;g;k}). & (32)
\end{aligned}
$$

Then, $\tilde{\mathbf{D}} \odot \mathbf{H}^{(1)}$ is

$$
\begin{aligned}
(\tilde{\mathbf{D}} \odot \mathbf{H}^{(1)})_{i;g;} &= \sum_{j,k} \tilde{\mathbf{D}}_{ij;;k} H^{(1)}_{i;g;k} \\
&= \sum_{j,k} \left(\mathbf{D}_{ij;;k} - \delta_{ij} \sum_l \mathbf{D}\right) H^{(1)}_{i;g;k} \\
&= \sum_{j,k} \mathbf{D}_{ij;;k} \mathbf{H}^{(1)}_{j;g;k} - \sum_{l,k} \mathbf{D}_{il;;k} \mathbf{H}^{(1)}_{i;g;k} \\
&= \sum_{j,k} D_{ij;;k} (H^{(1)}_{j;g;k} - H^{(1)}_{i;g;k}) & (\because \text{Change the dummy index } l \to j) \\
&= (\nabla \cdot \mathbf{H}^{(1)})_{i;g;}. & (33)
\end{aligned}
$$

C.3   LAPLACIAN OPERATOR

We prove that $\tilde{\mathbf{D}} \odot \tilde{\mathbf{D}}$ corresponds to the Laplacian operator within a Euclidean space.

Using equation 25, the Laplacian model $\nabla^2 \mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f}$ can be expressed as follows:

$$
\begin{aligned}
\left(\nabla^2 \mathbf{H}^{(0)}\right)_{i;g;} &:= \sum_k \left[\frac{\partial}{\partial x_k} \left(\frac{\partial \mathbf{H}}{\partial x_k} \right)_i \right]_{i;g;} \\
&= \sum_{j,k} D_{ij;;k} \left[\left(\frac{\partial \mathbf{H}}{\partial x_k} \right)_{j;g;} - \left(\frac{\partial \mathbf{H}}{\partial x_k} \right)_{i;g;} \right] \\
&= \sum_{j,k} D_{ij;;k} \left[\sum_l D_{jl;;k}(H^{(0)}_{l;g;} - H^{(0)}_{j;g;}) - \sum_l D_{il;;k}(H^{(0)}_{l;g;} - H^{(0)}_{i;g;}) \right] \\
&= \sum_{j,k,l} D_{ij;;k}(D_{jl;;k} - D_{il;;k})(H^{(0)}_{l;g;} - H^{(0)}_{j;g;}).
\end{aligned}
\tag{34}
$$

Then, $(\tilde{\mathbf{D}} \odot \tilde{\mathbf{D}})\mathbf{H}^{(0)}$ is

$$
\begin{aligned}
((\tilde{\mathbf{D}} \odot \tilde{\mathbf{D}})\mathbf{H}^{(0)})_{i;g;} &= \sum_{j,k,l} \tilde{D}_{ij;;k}\tilde{D}_{jl;;k}H^{(0)}_{l;g;} \\
&= \sum_{j,k,l} \left(D_{ij;;k} - \delta_{ij}\sum_m D_{im;;k} \right) \left(D_{jl;;k} - \delta_{jl}\sum_n D_{jn;;k} \right) H^{(0)}_{l;g;} \\
&= \sum_{j,k,l} D_{ij;;k}D_{jl;;k}H^{(0)}_{l;g;} - \sum_{j,k,n} D_{ij;;k}D_{jn;;k}H^{(0)}_{j;g;} \\
&\quad - \sum_{k,l,m} D_{im;;k}D_{il;;k}H^{(0)}_{l;g;} + \sum_{k,m,n} D_{im;;k}D_{in;;k}H^{(0)}_{i;g;} \\
&= \sum_{j,k,l} D_{ij;;k}D_{jl;;k}H^{(0)}_{l;g;} - \sum_{j,k,n} D_{ij;;k}D_{jn;;k}H^{(0)}_{j;g;} \\
&\quad - \sum_{k,l,j} D_{ij;;k}D_{il;;k}H^{(0)}_{l;g;} + \sum_{k,j,n} D_{ij;;k}D_{in;;k}H^{(0)}_{i;g;} \\
&\qquad (\because \text{Change the dummy index } m \to j \text{ for the third and fourth terms}) \\
&= \sum_{j,k,l} D_{ij;;k}(D_{jl;;k} - D_{il;;k})(H^{(0)}_{l;g;} - H^{(0)}_{j;g;}) \\
&\qquad (\because \text{Change the dummy index } n \to l \text{ for the second and fourth terms}) \\
&= \left(\nabla^2 \mathbf{H}^{(0)}\right)_{i;g;}.
\end{aligned}
\tag{35}
$$

C.4 JACOBIAN AND HESSIAN OPERATORS

Considering a similar discussion, we can show the following dependences. For the Jacobian model, $\boldsymbol{J}[\mathbf{H}^{(1)}] \in \mathbb{R}^{|\mathcal{V}| \times f \times d \times d}$,

$$
\begin{aligned}
\left(\boldsymbol{J}[\mathbf{H}^{(1)}]\right)_{i;g;kl} &= \left(\frac{\partial \mathbf{H}^{(1)}}{\partial x_l} \right)_{i;g;k} \tag{36} \\
&= \sum_j D_{ij;;l}(H^{(1)}_{j;g;k} - H^{(1)}_{i;g;k}) \tag{37} \\
&= (\tilde{D} \otimes \mathbf{H}^{(1)})_{i;g;lk}. \tag{38}
\end{aligned}
$$

For the Hessian model, $\mathrm{Hess}[\mathbf{H}^{(0)}] \in \mathbb{R}^{|\mathcal{V}| \times f \times d \times d}$,

$$\left(\mathrm{Hess}[\mathbf{H}^{(0)}] \right)_{i;g;kl} = \left(\frac{\partial}{\partial x_k} \frac{\partial}{\partial x_l} \mathbf{H}^{(0)} \right)_{i;g;} \tag{39}$$

$$= \sum_{j,m} D_{ij;;k}[D_{jm;;l}(H^{(0)}_{m;g;} - H^{(0)}_{l;g;}) - D_{im;;l}(H^{(0)}_{m;g;} - H^{(0)}_{i;g;})] \tag{40}$$

$$= \left[(\tilde{\mathbf{D}} \otimes \tilde{\mathbf{D}}) * \mathbf{H}^{(0)} \right]_{i;g;kl}. \tag{41}$$

D IsoGCN MODELING DETAILS

To achieve isometric transformation invariance and equivariance, there are several rules to follow. Thus, here we describe where to focus when constructing an IsoGCN model. In this section, a rank-p tensor denotes a tensor whose rank is $p \geq 1$ and σ denotes a nonlinear activation function. $\boldsymbol{W}$ and $\boldsymbol{b}$ are a trainable weight matrix and a trainable bias.

D.1 ACTIVATION AND BIAS

As nonlinear activation function is not isometric transformation equivariant, one cannot apply non-linear activation to rank-p tensors, while one can apply any activation to rank-0 tensors. In addition, adding bias is also not isometric transformation equivariant, one cannot add bias when performing an affin transformation to rank-p tensors. Again, one can add bias to rank-0 tensors.

Thus, for instance, if one perform conversion from rank-0 tensors $\mathbf{H}^{(0)}$ to rank-1 tensors using IsoAM $\mathbf{G}$, $\mathbf{G} * \sigma(\mathbf{H}^{(0)}\boldsymbol{W} + \boldsymbol{b})$ and $(\mathbf{G} * \sigma(\mathbf{H}^{(0)}))\boldsymbol{W}$ are isometric equivariant functions, however $(\mathbf{G} * \mathbf{H}^{(0)})\boldsymbol{W} + \boldsymbol{b}$ and $\sigma\left((\mathbf{G} * \sigma(\mathbf{H}^{(0)}))\boldsymbol{W} \right)$ is not due to the bias and the nonlinear activation, respectively. Likewise, regarding a conversion from rank-1 tensors $\mathbf{H}^{(1)}$ to rank-0 tensors, $\sigma\left((\mathbf{G} \odot \mathbf{H}^{(1)})\boldsymbol{W} + \boldsymbol{b} \right)$ and $\sigma\left(\mathbf{G} \odot (\mathbf{H}^{(1)}\boldsymbol{W}) \right)$ are isometric transformation invariant functions, however $\mathbf{G} \odot (\mathbf{H}^{(1)}\boldsymbol{W} + \boldsymbol{b})$ and $(\mathbf{G} \odot \sigma(\mathbf{H}^{(1)}))\boldsymbol{W} + \boldsymbol{b}$ are not.

To convert rank-p tensors to rank-q tensors ($q \geq 1$), one can apply neither bias nor nonlinear activation. To add nonlinearity to such a conversion, we can multiply the converted rank-0 tensors $\sigma((\bigotimes^p \mathbf{G} \odot \mathbf{H}^{(p)})\boldsymbol{W} + \boldsymbol{b})$ to the input tensors $\mathbf{H}^{(p)}$ or the output tensors $\mathbf{H}^{(q)}$.

D.2 PREPROCESSING OF INPUT FEATURE

Similar to the discussion regarding the biases, we have to take care of the preprocessing of rank-p tensors to keep isometric transformation invariance because adding a constant array and component-wise scaling could distort the tensors, resulting in broken isometric transformation equivariance.

For instance, $\mathbf{H}^{(p)}/\mathrm{Std}_{\mathrm{all}}\left[\mathbf{H}^{(p)}\right]$ is a valid transformation to keep isometric transformation equivariance, assuming $\mathrm{Std}_{\mathrm{all}}\left[\mathbf{H}^{(p)}\right] \in \mathbb{R}$ is a standard deviation of all components of $\mathbf{H}^{(p)}$. However, conversion such as $\mathbf{H}^{(p)}/\mathrm{Std}_{\mathrm{component}}\left[\mathbf{H}^{(p)}\right]$ and $\mathbf{H}^{(p)} - \mathrm{Mean}\left[\mathbf{H}^{(p)}\right]$ are not isometric transformation equivariant, assuming $\mathrm{Std}_{\mathrm{component}}\left[\mathbf{H}^{(p)}\right] \in \mathbb{R}^{d^p}$ is a component-wise standard deviation.

D.3 SCALING

Because the concrete instance of IsoAM $\tilde{\mathbf{D}}$ corresponds to the differential operator, the scale of the output after operations regarding $\tilde{D}$ can be considerably huge. Thus, we rescale $\tilde{\mathbf{D}}$ using the scaling factor $\left[\mathrm{Mean}_{\mathrm{sample},i}(\tilde{D}^2_{ii;;1} + \tilde{D}^2_{ii;;2} + \tilde{D}^2_{ii;;3}) \right]^{1/2}$, where $\mathrm{Mean}_{\mathrm{sample},i}$ denotes mean over samples and vertices.

D.4 IMPLEMANTATION

Because an adjacency matrix $\boldsymbol{A}$ is usually a sparse matrix for a regular mesh, $\boldsymbol{A}(m)$ in equation 16 is also a sparse matrix for a sufficiently small m. Thus, we can leverage sparse matrix multiplication in the IsoGCN computation. This is one major reason why IsoGCN can computer fast. If one need to compute multiplication (tensor product or contraction) of IsoAMs multiple times, one can utilize associative property of the IsoAM.

For instance, one can see that $\left[\bigotimes^k \mathbf{G}\right] * \mathbf{H}^{(0)} = \mathbf{G} \otimes (\mathbf{G} \otimes \ldots (\mathbf{G} * \mathbf{H}^{(0)}))$. Assuming the number of nonzero elements in $\boldsymbol{A}(m)$ equals to n and $\mathbf{H}^{(0)} \in \mathbb{R}^{|\mathcal{V}| \times f}$, then the computational comprexity of the right hand side is $\mathcal{O}(n|\mathcal{V}|f d^k)$. This is an exponential order regarding d. However, d and k are usually small number (typically $d = 3$ and $k \leq 4$). Therefore one can compute IsoGCN layer in a fast and memory efficient way with the realistic spatial dimension d and tensor rank k. In our implementation, both sparse matrix operation and associative property are utilized to realize fast computation.

E EXPERIMENTS DETAILS: DIFFERENTIAL OPERATOR DATASET

E.1 MODEL ARCHITECTURES

Figure 4: The IsoGCN model used for (a) the scalar field to the gradient field, (b) the scalar field to the Hessian field, (c) the gradient field to the Laplacian field, (d) the gradient field to the Hessian field of the gradient operator dataset. The numbers in each box denote the number of units. Below the unit numbers, the activation function used for each layer is also shown. $\otimes$ denotes multiplication in the feature direction.

Figure 4 represents the IsoGCN model used for the differential operator dataset. We used the $\mathtt{tanh}$ activation function as a nonlinear activation function because we expect the target temperature field is smooth. Therefore, we avoid using non-differentiable activation functions such as the rectified linear unit (ReLU) (Nair & Hinton, 2010). For GCN and its variants, we simply replaced the IsoGCN

Table 5: Summary of the hyperparameter setting for both TFN and SE(3)-Transformer. For the parameters not written in the table, we used the default setting in the implementation of `https://github.com/FabianFuchsML/se3-transformer-public`.

	$0 \rightarrow 1$	$0 \rightarrow 2$	$1 \rightarrow 0$	$1 \rightarrow 2$
# hidden layers	1	1	1	1
# NL layers in the self-interaction	1	1	1	1
# channels	24	20	24	24
# maximum rank of the hidden layers	1	2	1	2
# nodes in the radial function	16	8	16	22

Table 6: Summary of the test losses (mean squared error $\pm$ the standard error of the mean, in the original scale) of the differential operator dataset: $0 \rightarrow 1$ (the scalar field to the gradient field), $0 \rightarrow 2$ (the scalar field to the Hessian field), $1 \rightarrow 0$ (the gradient field to the Laplacian field), and $1 \rightarrow 2$ (the gradient field to the Hessian field). Here, if "$\boldsymbol{x}$" is "Yes", it means $\boldsymbol{x}$ is also in the input feature.

Method	# hops	$\boldsymbol{x}$	Loss of $0 \rightarrow 1$ $\times 10^{-5}$	Loss of $0 \rightarrow 2$ $\times 10^{-6}$	Loss of $1 \rightarrow 0$ $\times 10^{-6}$	Loss of $1 \rightarrow 2$ $\times 10^{-6}$
GIN	2	No	151.19 ± 0.53	49.10 ± 0.36	542.52 ± 2.14	59.65 ± 0.46
	2	Yes	147.10 ± 0.51	47.56 ± 0.35	463.79 ± 2.08	50.73 ± 0.40
	5	No	151.18 ± 0.53	48.99 ± 0.36	542.54 ± 2.14	59.64 ± 0.46
	5	Yes	147.07 ± 0.51	47.35 ± 0.35	404.92 ± 1.74	46.18 ± 0.39
GCNII	2	No	151.18 ± 0.53	43.08 ± 0.31	542.74 ± 2.14	59.65 ± 0.46
	2	Yes	151.14 ± 0.53	40.72 ± 0.29	194.65 ± 1.00	45.43 ± 0.36
	5	No	151.11 ± 0.53	32.85 ± 0.23	542.65 ± 2.14	59.66 ± 0.46
	5	Yes	151.13 ± 0.53	31.87 ± 0.22	280.61 ± 1.30	39.38 ± 0.34
SGCN	2	No	151.17 ± 0.53	50.26 ± 0.38	542.90 ± 2.14	59.65 ± 0.46
	2	Yes	151.12 ± 0.53	49.96 ± 0.37	353.29 ± 1.49	59.61 ± 0.46
	5	No	151.12 ± 0.53	55.02 ± 0.42	542.73 ± 2.14	59.64 ± 0.46
	5	Yes	151.16 ± 0.53	55.08 ± 0.42	127.21 ± 0.63	56.97 ± 0.44
GCN	2	No	151.23 ± 0.53	49.59 ± 0.37	542.54 ± 2.14	59.64 ± 0.46
	2	Yes	151.14 ± 0.53	47.91 ± 0.35	542.68 ± 2.14	59.60 ± 0.46
	5	No	151.18 ± 0.53	50.58 ± 0.38	542.53 ± 2.14	59.64 ± 0.46
	5	Yes	151.14 ± 0.53	48.50 ± 0.35	542.30 ± 2.14	25.37 ± 0.28
Cluster-GCN	2	No	151.19 ± 0.53	33.39 ± 0.24	542.54 ± 2.14	59.66 ± 0.46
	2	Yes	147.23 ± 0.51	32.29 ± 0.24	167.73 ± 0.83	17.72 ± 0.17
	5	No	151.15 ± 0.53	28.79 ± 0.21	542.51 ± 2.14	59.66 ± 0.46
	5	Yes	146.91 ± 0.51	26.60 ± 0.19	185.21 ± 0.99	18.18 ± 0.20
TFN	2	No	2.47 ± 0.02	OOM	26.69 ± 0.24	OOM
	5	No	OOM	OOM	OOM	OOM
SE(3)-Trans.	2	No	$\mathbf{1.79} \pm 0.02$	$\mathbf{3.50} \pm 0.04$	$\mathbf{2.52} \pm 0.02$	OOM
	5	No	2.12 ± 0.02	OOM	7.66 ± 0.05	OOM
IsoGCN (Ours)	2	No	2.67 ± 0.02	6.37 ± 0.07	7.18 ± 0.06	$\mathbf{1.44} \pm 0.02$
	5	No	14.19 ± 0.10	21.72 ± 0.25	34.09 ± 0.19	8.32 ± 0.09

layers to the corresponding ones. We stacked $m(=2,5)$ layers for GCN, GIN, GCNII, Cluster-GCN. We used m hop adjacency matrix for SGCN.

For TFN and SE(3)-Transformer, we set hyperparameters to have the number of parameters almost the same as that in the IsoGCN model. The setting of hyperparameters are shown in Table 5.

E.2 RESULT DETAILS

Table 6 represents the detailed comparison of training results. The results show that an IsoGCN outperforms other GCN models for all settings. Compared to other equiv- ariant models, IsoGCN has competitive performance compared to equivariant models with shorter inference time as shown in Table 7. Therefore, it can be found out the proposed model has a strong expressive power to express differential regarding space with less computation resources compared to TFN and SE(3)-Transformer.

Table 7: Summary of the inference time on the test dataset. $0 \to 1$ corresponds to the scalar field to the gradient field, and $0 \to 2$ corresponds to the scalar field to the Hessian field. Each computation were run on the same GPU (NVIDIA Tesla V100 with 32 GiB memory). OOM denotes the out-of-memory of the GPU.

| Method | $0 \to 1$ | | $0 \to 2$ | |
	# parameters	Inference time [s]	# parameters	Inference time [s]
TFN	5264	3.8	5220	OOM
SE(3)-Trans.	5392	4.0	5265	9.2
IsoGCN (Ours)	4816	0.4	4816	0.7

F EXPERIMENTS DETAILS: ANISOTROPIC NONLINEAR HEAT EQUATION DATASET

F.1 DATASET

The purpose of the conducted experiment is to solve the anisotropic nonlinear heat diffusion under an adiabatic boundary condition. The governing equation is defined as follows:

$$\Omega \subset \mathbb{R}^3, \tag{42}$$

$$\frac{\partial T(\boldsymbol{x}, t)}{\partial t} = \nabla \cdot \boldsymbol{C}(T(\boldsymbol{x}, t)) \nabla T(\boldsymbol{x}, t), \text{in } \Omega, \tag{43}$$

$$T(\boldsymbol{x}, t = 0) = T_{0.0}(\boldsymbol{x}), \text{in } \Omega, \tag{44}$$

$$\nabla T(\boldsymbol{x}, t)|_{\boldsymbol{x} = \boldsymbol{x}_b} \cdot \boldsymbol{n}(\boldsymbol{x}_b) = 0, \text{on } \partial\Omega, \tag{45}$$

where T is the temperature field, $T_{0.0}$ is the initial temperature field, $\boldsymbol{C} \in \mathbb{R}^{d \times d}$ is an anisotropic diffusion tensor, and $\boldsymbol{n}(\boldsymbol{x}_b)$ is the normal vector at $\boldsymbol{x}_b \in \partial\Omega$. Here, $\boldsymbol{C}$ depends on temperature thus the equation is nonlinear. We randomly generate $\boldsymbol{C}(T = -1)$ such that it is positive semidefinite symmetric tensor whose eigenvalues varies from 0.0 to 0.02. Then we defined linear temperature dependency whose slope is $-\boldsymbol{C}(T = -1)/4$. The function of the anisotropic diffusion tensor is uniform for each one sample. The task is defined to predict temperature field at $t = 0.2, 0.4, 0.6, 1.0$ ($T_{0.2}, T_{0.4}, T_{0.6}, T_{0.8}, T_{1.0}$) from the given initial temperature field, material property, and mesh geometry. However, the performance is evaluated only with $T_{1.0}$ to focus on predictive performance. We put other output fearues just to stabilize the trainings. Accordingly, the diffusion number of this problem is $\boldsymbol{C}\Delta t/(\Delta x)^2 \simeq 10.0^4$ with assuming $\Delta x \simeq 10.0^{-3}$.

Figure 5 represents the process of generating the dataset. We generated up to 9 FEA results for each CAD shape. To avoid data leakage in terms of the CAD shapes, we first split them into training, validation, and test datasets, and then applied the following process.

Using one CAD shape, we generated up to three meshes using clscale (a control parameter of the mesh characteristic lengths) = 0.20, 0.25, and 0.30. To facilitate the training process, we scaled the meshes to fit into a cube with an edge length equal to 1.

Using one mesh, we generated three initial conditions rondomly using a Fourier series of the 2nd to 10th orders. We then applied an FEA for each initial condition and material property determinded rondomly as described above. We applied an implicit method to solve time evolutions and a direct method to solve the linear equations. The time step of the FEA was set equal to 0.01.

During this process, some of the meshes or FEA results might not be available owing to an excessive computation time or non-convergence. Therefore, the size of the dataset was not exactly equal to the number multiplied by 9. Finally, we obtained 439 FEA results for the training dataset, 143 FEA results for the validation dataset, and 140 FEA results for the test dataset.

Figure 5: The process of generating the dataset. A smaller clscale parameter generates smaller meshes.

F.2 INPUT FEATURES

To express the geometry information, we extracted the effective volume of the ith vertex $V_i^{\text{effective}}$ and the mean volume of the ith vertex V_i^{mean}, which are defined as follows:

$$V_i^{\text{effective}} = \sum_{e \in \mathcal{N}_i^e} \frac{1}{4} V_e, \tag{46}$$

$$V_i^{\text{mean}} = \frac{\sum_{e \in \mathcal{N}_i^e} V_e}{|\mathcal{N}_i^e|}, \tag{47}$$

where $\mathcal{N}_i^e$ is the set of elements including the ith vertex.

For GCN or its variant models, we tested several combinations of input vertex features $T_{0.0}$, $\boldsymbol{C}$, $V^{\text{effective}}$, V^{mean}, and $\boldsymbol{x}$ (Table 9). For the IsoGCN model, inputs were $T_{0.0}$, $\boldsymbol{C}$, $V^{\text{effective}}$, and V^{mean}.

F.3 MODEL ARCHITECTURES

Figure 6 represents the IsoGCN model used for the anisotropic nonlinear heat equation dataset. We used the $\tanh$ activation function as a nonlinear activation function because we expect the target temperature field is smooth. Therefore, we avoid using non-differentiable activation functions such as the rectified linear unit (ReLU) (Nair & Hinton, 2010). Although the model looks complicated, one propagation block corresponds to the first-order Taylor expansion $T(t + \Delta t) \simeq \nabla \boldsymbol{C} \odot \nabla T(t) + T(t)$ because the propagation block is expressed as $\tilde{\mathbf{D}} \odot \boldsymbol{C} \odot \text{MLP}(T)\tilde{\mathbf{D}} * T + T$, where T denotes

Figure 6: The IsoGCN model used for the anisotropic nonlinear heat equation dataset. The numbers in each box denote the number of units. Below the unit numbers, the activation function used for each layer is also shown. $\otimes$ denotes multiplication in the feature direction, $\odot$ denotes contraction, and $\oplus$ denotes the addition in the feature direction.

Table 8: Summary of the hyperparameter setting for both TFN and SE(3)-Transformer. For the parameters not written in the table, we used the default setting in the implementation of `https://github.com/FabianFuchsML/se3-transformer-public`.

# hidden layers	1
# NL layers in the self-interaction	1
# channels	16
# maximum rank of the hidden layers	2
# nodes in the radial function	32

the rank-0 tensor input to the propagation block. By stacking this propagation block p times, one can approximate the pth order Taylor expansion of the anisotropic nonlinear heat equation.

For GCN and its variants, we simply replaced the IsoGCN layers to the corresponding ones. We stacked $m(=2, 5)$ layers for GCN, GIN, GCNII, Cluster-GCN. We used m hop adjacency matrix for SGCN.

For TFN and SE(3)-Transformer, we set hyperparameters to have as many parameters as possible to fit on the GPU we used because TFN and SE(3)-Transformer with the almost the same number of parameters did not fit on the GPU. The setting of hyperparameters are shown in Table 8.

F.4 RESULT DETAILS

Table 9 shows a detailed comparison of the training results. Including x in the input features of the baseline models did not improve the performance. In addition, if x is included in the input features, it might lead to a loss of the generalization capacity for larger shapes compared to the training dataset, as it extrapolates. The proposed model achieved the best performance compared with the considered baseline models considered. Therefore, we concluded that the essential features regarding the mesh shapes are included in $\tilde{\mathbf{D}}$. Besides, IsoGCN can scale up to meshes with 1M vertices as shown in Figure 7.

Table 9: Summary of the test losses (mean squared error $\pm$ the standard error of the mean, in the original scale) of the anisotropic nonlinear heat dataset. Here, if "x" is "Yes", it means x is also in the input feature. OOM denotes the out-of-memory on the applied GPU (32 GiB).

Method	# hops	x	Loss $\times 10^{-3}$
GIN	2	No	16.921 ± 0.040
	2	Yes	18.483 ± 0.025
	5	No	22.961 ± 0.056
	5	Yes	17.637 ± 0.046
GCN	2	No	10.427 ± 0.028
	2	Yes	11.610 ± 0.032
	5	No	12.139 ± 0.031
	5	Yes	11.404 ± 0.032
GCNII	2	No	9.595 ± 0.026
	2	Yes	9.789 ± 0.028
	5	No	8.377 ± 0.024
	5	Yes	9.172 ± 0.028
Cluster-GCN	2	No	7.266 ± 0.021
	2	Yes	8.532 ± 0.023
	5	No	8.680 ± 0.024
	5	Yes	10.712 ± 0.030
SGCN	2	No	7.317 ± 0.021
	2	Yes	9.083 ± 0.026
	5	No	6.426 ± 0.018
	5	Yes	6.519 ± 0.020
TFN	2	No	15.661 ± 0.019
	5	No	OOM
SE(3)-Trans.	2	No	14.164 ± 0.018
	5	No	OOM
IsoGCN (Ours)	2	No	4.674 ± 0.014
	5	No	$\mathbf{2.470} \pm 0.008$

Figure 7: Comparison between (left) samples in the training dataset, (center) ground truth computed through FEA, and (right) IsoGCN inference result. For both the ground truth and inference result, $|\mathcal{V}| = 1,011,301$. One can see that IsoGCN can predict the temperature field for a mesh, which is much larger than these in the training dataset.