TactileVAD: Geometric Aliasing-Aware Dynamics for High-Resolution Tactile Control

Abstract: Control through touch is a promising approach to dexterous manipulation. However, existing tactile control methods often overlook tactile geometric aliasing which can compromise control performance and reliability. This type of aliasing occurs when different physical configurations yield similar tactile signatures. To address this, we propose TactileVAD, a generative decoder-only linear latent dynamics formulation compatible with standard control methods that is capable of resolving geometric aliasing. We evaluate TactileVAD on two mechanically-distinct tactile sensors, SoftBubbles (pointcloud data) and Gelslim 3.0 (RGB data), showcasing its effectiveness in handling different sensing modalities. Additionally, we introduce the tactile cartpole, a novel benchmarking setup to evaluate the stability of tool grasping control under external perturbations. Comparative evaluations against baselines demonstrate the efficacy of our method in achieving desired tactile configurations, poses, and generalization.

Keywords: Manipulation, tactile control, high-resolution tactile sensors

1 Introduction

Tactile sensing is a key enabler for dexterous robotic manipulation, allowing robots to perceive the objects they interact with and control their behavior. The ability to sense and respond to external forces and changes in grasped object poses during manipulation is essential for a broad range of tasks including grasping, pushing, sliding, and tool-use. These tactile perception-action loops provide accuracy and robustness in the face of uncertainty while complementing vision by providing feedback despite occlusions from the robot or environment.

In recent years, there has been a growing interest in developing high-resolution, vision-based, and collocated tactile sensors for robotic manipulation [1, 2, 3, 4, 5]. These sensors convert tactile signatures to visual formats (e.g., RGB or point clouds) and have enabled a variety of perception tasks including in-hand pose estimation [6, 7, 8], object identification [9, 10, 11, 12], and slip detection [13, 14]. However, these high-resolution tactile sensors,

Figure 1: **Tactile Cartpole:** Our proposed benchmark task evaluates the robustness of tool grasping control subject to disturbances applied by the cart.

by virtue of their mechanical structure, introduce complex dynamics between the robot, grasped object, and the environment that must be accounted for in the control of the robot [15]. Current state-of-the-art tactile control methods rely on black-box modeling of the sensor-object-environment interaction coupled with sample-based control [16, 17, 18] or reinforcement learning [19, 20].

While these approaches have shown promise in leveraging tactile feedback for control, they often overlook a critical factor: tactile geometric aliasing. This aliasing occurs when different config-

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

urations or contact geometries produces indistinguishable tactile signals, leading to ambiguity in interpreting the underlying interactions. Neglecting this effect can hinder planning and control performance, as we show in this paper. To address these limitations, we introduce a tactile representation and controller that is able to disambiguate geometric aliasing. Our contributions are:

- TactileVAD, a generative decoder-only linear latent dynamics formulation for tactile control with high-resolution sensors that is robust to geometric aliasing,
- Demonstration of this formulation for two mechanically-distinct tactile sensors with different sensing modalities: SoftBubbles [1] (point cloud data) and Gelslim 3.0 [2] (RGB data),
- Tactile cartpole, a novel benchmarking setup for evaluating the stability of tool grasping control in the presence of external perturbations.

2   Related Work

Tactile Control In recent years, there has been a growing interest in the application of tactile sensors for various robotic manipulation tasks, including insertion [21], cloth manipulation [22], cable manipulation She et al. [18], or tool manipulation [23, 15]. Tactile sensors provide valuable information for controlling the interaction between the robot and a grasped object. Some existing methods focus on learning the dynamics of sensor-object interactions [16, 3] to utilize them for model-based control. However, the high dimensionality of the tactile signals poses a challenge in modeling these dynamics and using them for controls. To address this, a common approach is to project them into a lower-dimensional space [15, 19]. Despite the potential shown by these approaches, they frequently neglect the presence of ambiguity in tactile signals arising from geometric aliasing. In our work, we address this issue by constructing latent spaces capable of disambiguating aliased observations.

Latent-Space Dynamics The identification of system dynamics from raw observations plays a crucial role in the development of effective control strategies. Brunton et al. [24] proposed to identify the underlying dynamics of a non-linear system through sparse regression. Since observations are often high-dimensional, it is common to represent the system dynamics in a lower-dimensional space [25]. Many of these approaches employ encoder-decoder architectures, and one notable framework is Embed-to-Control (E2C) [26]. E2C formulates the latent as a Variational Auto-encoder with locally-linear latent space dynamics over conditional distributions. This work inspired subsequent research efforts. Jaques et al. [27] explored a more constrained parametrization of the latent dynamics, resulting in improved learning of the latent space for PD control laws. Furthermore, Okumura et al. [28] extended this approach to incorporate tactile sensing by learning a latent space projection for both tactile and visual inputs. Despite the success of encoder-decoder architectures, they can introduce aliasing in the latent space when faced with aliased observations. To overcome this limitation, our approach employs a decoder-only architecture and updates the latent space through back-propagation, effectively mitigating the adverse effects of aliasing.

Decoder-Only Architectures Decoder-only models have gained attention as an alternative to traditional encoder-decoder architectures. These models eliminate the need for an encoder by leveraging gradient-based optimization to infer the latent space representation directly from the observations [29]. Decoder-only architectures have exhibited promising results in learning structured latent spaces for high-dimensional data generation [30, 31, 32, 33]. A notable example of this is the Variational Auto-decoder (VAD) [34], which extends the well-known Variational Auto-encoder (VAE) [35] formulation to a decoder-only scenario. VAD incorporates a codebook that stores conditional latent distribution parameters, which are jointly optimized along with the decoder weights. This formulation regularizes and encourages a more structured and smooth latent space. In our work, we extend the VAD formulation by introducing dynamics through linear transitions in the latent space. Our proposed approach, TactileVAD, enables the generation of temporal trajectories of states.

3   Problem Formulation

In this paper, we consider the problem of controlling a system with unknown dynamics of the form $\mathbf{s}_{t+1} = f_{\text{dyn}}(\mathbf{s}_t, \mathbf{u}_t)$. Here, $\mathbf{s}_t \in \mathcal{S} \subset \mathbb{R}^{n_s}$ represents the system state at time t consisting of both robot and environment configurations. The control actions $\mathbf{u}_t \in \mathcal{U} \subset \mathbb{R}^{n_a}$ correspond to the robot's

Figure 2: **Geometric Aliasing** (Left) illustrates the geometric aliasing problem of the tactile sensor reading while grasping an object with geometric symmetries. Observe that two different states $\mathbf{s}_1$ and $\mathbf{s}_2$ corresponding to different grasping locations result in the same sensor measurement $\mathbf{x}_1 = \mathbf{x}_2$. However, the same action $\mathbf{u}$ applied to both of them results in very different next state observations. (Top Right) As a consequence of the aliasing in the observations, the mapping $\phi : \mathcal{X} \to \mathcal{Z}$ introduces ill-posed latent space. (Bottom Right) modelling only the $\psi : \mathcal{Z} \to \mathcal{X}$ results in better latent spaces.

end-effector motions. We assume that the true system state $\mathbf{s}_t$ is not directly measurable, but we have access to observations $\mathbf{x}_t = \text{obs}(\mathbf{s}_t) \in \mathcal{X} \subset \mathbb{R}^{n_x}$. Specifically, in our study, these observations $\mathbf{x}_t$ are obtained using vision-based-tactile sensors and can take the form of point clouds or RGB images. We further assume that $\mathbf{x}$ may suffer from observation aliasing, where different system states $\mathbf{s}_1, \mathbf{s}_2 \in \mathbb{R}^{n_s}$, $\mathbf{s}_1 \neq \mathbf{s}_2$ can result in the same observations $\mathbf{x}_1 = \text{obs}(\mathbf{s}_1) = \mathbf{x}_2 = \text{obs}(\mathbf{s}_2)$. This aliasing can occur due to geometric symmetries and limited sensor measurement range. This situation can lead to an ill-posed inference problem, as the indistinguishable observations $\mathbf{x}_1$ and $\mathbf{x}_2$ result in ambiguity in determining the underlying dynamics. Fig. 2 (Left) illustrates this. The goal of this problem is to determine a sequence of actions $\mathbf{u}_1, \ldots, \mathbf{u}_T$ that can drive the system from some initial $\mathbf{s}_0$ to a desired system state $\mathbf{s}_g \in \mathcal{S}$ in the presence of observation aliasing.

4 Methods

4.1 Variational Auto-Decoder Linear Latent Dynamics

The key idea of our method is to learn a model of the underlying system dynamics in a lower-dimensional latent space $\mathcal{Z}$ such that: (i) observations $\mathbf{x}_t$ are reconstructed; (ii) the latent space dynamics are linear, smooth, and structured; and (iii) aliased states are identified and disambiguated.

One common approach is to learn a mapping function $\phi : \mathcal{X} \to \mathcal{Z}$ that projects high-dimensional observations $\mathbf{x} \in \mathbb{R}^{n_x}$ to a lower-dimensional latent space $\mathbf{z} \in \mathbb{R}^{n_z}$ where $n_z \ll n_x$. The dynamics in this latent space are globally-linear and given by $\mathbf{z}_{t+1} = f_{\text{lat\_dyn}}(\mathbf{z}_t, \mathbf{u}_t) = \mathbf{A}\mathbf{z}_t + \mathbf{B}\mathbf{u}_t$ where $\mathbf{A} \in \mathbb{R}^{n_z \times n_z}$, $\mathbf{B} \in \mathbb{R}^{n_z \times n_u}$. This approach typically employs an encoder-decoder architecture [26, 19, 25]. However, we observe that formulating the mapping from observation space to latent space $\phi : \mathcal{X} \to \mathcal{Z}$ introduces ill-defined latent spaces when aliased observations are present in the dynamics. With reference to Fig. 2 (Right), consider two distinct states $\mathbf{s}_1 \neq \mathbf{s}_2$ that result in aliased observations $\mathbf{x}_1 = \text{obs}(\mathbf{s}_1) = \mathbf{x}_2 = \text{obs}(\mathbf{s}_2)$. Additionally, assume the existence of an action $\mathbf{u} \in \mathcal{U}$ that leads to non-aliased states: $\mathbf{s}_3 = f_{\text{dyn}}(\mathbf{s}_1, \mathbf{u})$ and $\mathbf{s}_4 = f_{\text{dyn}}(\mathbf{s}_2, \mathbf{u})$ where $\mathbf{s}_3 \neq \mathbf{s}_4$. Let $\mathbf{x}_3 = \text{obs}(\mathbf{s}_3)$ and $\mathbf{x}_4 = \text{obs}(\mathbf{s}_4)$ be the corresponding observations, such that $\mathbf{x}_3 \neq \mathbf{x}_4$. The resultant latent representations are denoted as $\mathbf{z}_i = \phi(\mathbf{x}_i)$. In such cases, the mapping ϕ will force $\mathbf{z}_1 = \mathbf{z}_2$ since $\mathbf{x}_1 = \mathbf{x}_2$, and therefore they are compelled to produce the same resultant

dynamics $\hat{\mathbf{z}}$: $f_{\text{lat\_dyn}}(\mathbf{z}_1, \mathbf{u}) = f_{\text{lat\_dyn}}(\mathbf{z}_2, \mathbf{u}) = \hat{\mathbf{z}}$. However, the dynamics should yield distinct outcomes: $f_{\text{lat\_dyn}}(\mathbf{z}_1, \mathbf{u}) = \mathbf{z}_3 \neq \mathbf{z}_4 = f_{\text{lat\_dyn}}(\mathbf{x}_2, \mathbf{u})$. This situation leads to an ill-posed problem, as the indistinguishable observations $\mathbf{x}_1$ and $\mathbf{x}_2$ result in ambiguity in determining the underlying dynamics. Figure 2 (Top Right) visualizes this effect.

To address this, we propose an alternative approach that focuses exclusively on modeling the mapping from the latent space to observation space, denoted as $\psi : \mathcal{Z} \to \mathcal{X}$. By adopting this surjective mapping ψ, we can have multiple latent vectors $\mathbf{z}$ mapped to the same observation $\mathbf{x}$. Each of these $\mathbf{z}$ will evolve differently when action $\mathbf{u}$ is taken. Once the corresponding outcomes are perceived, we can use an inference via optimization procedure (Sec. 4.3) to disentangle the aliased observations. Fig. 2 (Bottom Right) provides an illustration of this concept. Our objective is to jointly learn the mapping from latent space to observation space, ψ, and the latent space dynamics $f_{\text{lat\_dyn}}$ from state observation transitions $(\mathbf{x}_1, \mathbf{u}_1, \mathbf{x}_2, \dots, \mathbf{x}_{T-1}, \mathbf{u}_{T-1}, \mathbf{x}_T)$. To this end, we employ a decoder-only architecture. Additionally, we choose to model the latent space as conditional distributions, which leads to more structured and smooth learned latent spaces. Consequently, our model takes the form of a VAD with globally-linear latent dynamics, in contrast to E2C, which is formulated as a VAE. The latent space dynamics are of the form:

$$\mathbf{z}_t \sim Q(Z_t) = \mathcal{N}(\boldsymbol{\mu}_t, \boldsymbol{\Sigma}_t); \quad \mathbf{z}_{t+1} \sim Q(Z_{t+1}|Z_t, \mathbf{u}_t) = \mathcal{N}(\mathbf{A}\boldsymbol{\mu}_t + \mathbf{B}\mathbf{u}_t, \mathbf{A}\boldsymbol{\Sigma}_t\mathbf{A}^\top)$$

We have chosen this parametrization of latent dynamics to ensure compatibility with standard control methods like LQR. Section 4.4 describes our control formulation.

In our method, we eliminate the need for an encoder by maintaining a codebook of distribution parameters $\{\boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i\}_{i=1\dots,N}$. These parameters are optimized jointly with the decoder's, and the dynamics parameters via back-propagation. The training process is described in detail in Section 4.2. During the inference, when mapping from observation space to latent space, we employ an optimization-based approach, as explained in 4.3. This inference procedure enables us to accurately determine the latent space representation based on the observed data. Furthermore, it allows us to generate multiple likely candidates for an aliased observation, providing a more comprehensive understanding of the underlying latent dynamics.

4.2 TactileVAD Training

We train our model from a dataset of N trajectories of T state-action transitions of the form $\mathcal{D} = \{(\mathbf{x}_1, \mathbf{u}_1, \mathbf{x}_2, \dots, \mathbf{x}_T, \mathbf{u}_T, \mathbf{x}_{T+1})\}_{n=1}^N$. Our goal is to jointly optimize the latent space parameters $\{\boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i\}_{i=1\dots,(T+1)N}$, the transition dynamics $\mathbf{A}$ and $\mathbf{B}$, as well as the parameters θ that define the mapping from latent space to observation space f_{dec}. The training procedure is outlined in Algorithm 1. To jointly learn this, we use a loss function composed of four weighted terms:

$$\mathcal{L} = \alpha_{\text{rec}}\mathcal{L}_{\text{rec}}(\mathbf{x}_t, q_t) + \alpha_{\text{pred}}\mathcal{L}_{\text{pred}}(\mathbf{x}_{t+1}, \hat{q}_{t+1}) + \alpha_{\text{cons}}\mathcal{L}_{\text{cons}}(\hat{q}_{t+1}, q_{t+1}) + \alpha_{\text{kl}}l_{\text{kl}}$$

where (i) $\mathcal{L}_{\text{rec}}$ imposes that we are able to reconstruct the current observation from the current latent distribution, (ii) $\mathcal{L}_{\text{pred}}$ imposes that we are able to generate the next observation from the predicted

Figure 3: **VAD Latent Linear Dynamics Model** (Left) TactileVAD for trajectory generation of length T via latent space linear dynamics propagation (Right) single step training with reconstruction, prediction, and latent space consistency.

distribution dynamics given by the control action $\mathbf{u}_t$, (iii) $\mathcal{L}_{\text{cons}}$ imposes that the predicted latent distribution matches the distribution, and (iv) $\mathcal{L}_{\text{kl}}$ imposes a prior distribution on the latent space which regularizes the latent space. Each of the losses is formulated as follows:

$$\mathcal{L}_{\text{rec}}(\mathbf{x}_t, q_t) = \mathbb{E}_{\mathbf{z}_t \sim q_t}[-\log P_\theta(\mathbf{x}_t|\mathbf{z}_t)] \approx \sum_{m=1}^{M} \mathcal{L}_{\text{state}}(\mathbf{x}_t, f_{\text{dec}}(\hat{\mathbf{z}}_t^{(m)})) \tag{1}$$

$$\mathcal{L}_{\text{pred}}(\mathbf{x}_{t+1}, \hat{q}_{t+1}) = \mathbb{E}_{\hat{\mathbf{z}}_{t+1} \sim \hat{q}_{t+1}}[-\log P_\theta(\mathbf{x}_{t+1}|\hat{\mathbf{z}}_{t+1})] \approx \sum_{m=1}^{M} \mathcal{L}_{\text{state}}(\mathbf{x}_{t+1}, f_{\text{dec}}(\hat{\mathbf{z}}_{t+1}^{(m)})) \tag{2}$$

$$\mathcal{L}_{\text{cons}}(\hat{q}_{t+1}, q_{t+1}) = \text{KL}(\hat{q}_{t+1}\|q_{t+1}) \tag{3}$$
$$\mathcal{L}_{\text{kl}}(\hat{q}_t) = \text{KL}(q_t\|\mathcal{N}(\mathbf{0}, \mathbf{I})) \tag{4}$$

See Appendix A.1 for more details about the training.

4.3 Embedding via Inference Search

Decoder-only architectures exclusively model the mapping from latent space to observation space $\psi : \mathcal{Z} \to \mathcal{X}$. Unlike encoder-decoder architectures, which can infer the latent representation $\mathbf{z}_t$ by forward-passing the encoder, decoder-only architectures do not directly model the mapping $\phi : \mathcal{X} \to \mathcal{Z}$. Instead, they employ an inference-based encoding approach to obtain the latent vector corresponding to a given observation. Similar to DeepSDF [30], we infer $\mathbf{z}$ via gradient-based search. During inference, the decoder weights θ are fixed we fixed, and an optimization process is carried out to find the most likely $\mathbf{z}$ that produced $\mathbf{x}$, as shown below:

$$\hat{\mathbf{z}} = \arg\min_{\mathbf{z}} \mathcal{L}_{\text{state}}(f_\theta^{\text{dec}}(\mathbf{z}), \mathbf{x})$$

Although this inference approach is more computationally expensive than a forward encoding pass, it offers two main advantages: (i) better generalization to unseen data and distribution shifts and (ii) generation of multiple candidate latent states that result in the same observation. The ability to generate multiple candidates helps disambiguate aliased observations by capturing the inherent uncertainty in the latent space representation.

4.4 Low-level Control with VAD Dynamics Model

The goal of the controller is to drive the system state $\mathbf{s}_t$ to a desired target state $\mathbf{s}_g$. Given that we only have access to an aliased observations $\mathbf{x}_t$ of the system state $\mathbf{s}_t$, we formulate our controller in the learned latent space $\mathcal{Z}$ since it does not suffer from aliasing and has the added convenience of linear transition dynamics. Given a quadratic cost, we formulate a discrete time LQR controller:

$$(\text{P1}) \min_{\mathbf{u}} \quad \sum_{t=1}^{\infty} \bar{\mathbf{z}}_t^\top \mathbf{Q} \bar{\mathbf{z}}_t + \mathbf{u}_t^\top \mathbf{R} \mathbf{u}_t$$
$$\text{s.t.} \quad \bar{\mathbf{z}}_t = \mathbf{z}_t - \mathbf{z}_g \qquad t = 1, \dots, \infty,$$
$$\mathbf{z}_{t+1} = \mathbf{A}\mathbf{z}_t + \mathbf{B}\mathbf{u}_t \quad t = 1, \dots, \infty$$

with $\mathbf{Q} \succeq \mathbf{0}$, $\mathbf{R} \succ \mathbf{0}$. The optimal controller is computed by solving the discrete time algebraic Riccati equation (DARE), yielding $\mathbf{u}_t = -\mathbf{K}\bar{\mathbf{z}}$ [36]. Here, we choose $n_z = n_u$. When $n_z > n_u$, the resulting system dynamics are underactuated and the controller may not have a stable solution. Algorithm 2 summarizes our controller formulation.

5 Experiments and Results

We demonstrate the effectiveness of our proposed approach to tactile control in 4 tasks: (i) an aliased-rich simulation task with discrete states, where many of them exhibit aliasing, (ii) a real-world tactile control for static tool grasping with the Soft Bubbles tactile sensors and (iii) Gelslims 3.0 sensors, and (iv) the tactile cartpole: a novel quasi-dynamic tactile control bench-marking task for tool grasping under external perturbations inspired by the classic cartpole control task.

5.1 Baselines

We benchmark our method with 3 baselines, including 2 encoder-decoder approaches and one decoder-only approach. All methods have linear latent dynamics.

Auto-encoder Dynamics (AE) This baseline is a common approach that uses auto-encoders to shape the latent space [25]. The encoder projects high-dimensional observations into the latent vector space where dynamics are propagated. Predictions are then projected back to the observation space using the decoder. The controller is formulated in the low-dimensional latent space.

Embed to Control (E2C) Embed to control [26] is a popular framework for latent space dynamics that extends the auto-encoder formulation to the variational setting. The resulting latent spaces are distributions over vector spaces and have been shown to perform well for control tasks. For consistent evaluation, we use the global-E2C formation (globally linear dynamics).

Auto-decoder Dynamics (AD) This decoder-only framework optimizes a latent codebook simultaneously with the dynamics parameters and the decoder parameters. The main difference from our proposed approach is in the latent space, which is not a distribution. Here, the optimized codebook is not distribution parameters, but the latent vectors directly.

5.2 Moving Block Control

This task aims to demonstrate the impact of aliasing when modeling the dynamics on an aliased-rich task with discrete states. Fig. 5 provides a visualization of this task. The objective is to control the planar position of the rectangular object (in yellow) from image observations, where the object undergoes 2D translation motions. The states $\mathbf{s}_t$ represent the object's position in the 2D plane, while the observations $\mathbf{x}_t$ capture only a partial view of the full state (depicted as the blue subpart around the center). Fig. 5 also shows an example of observation aliasing, where two different states lead to the same observation due to the small sensed area.

Figure 4: **Moving Block Setup** On the left, two different block location result in the same observation. However, the same action applied to both states resulted in different next states (right).

We benchmark our approach and compare it to the baselines. The goal is to control the block position to reach a desired target location. We evaluate the reconstruction and prediction quality as well as the LQR-controlled performance of the resulting dynamics models. Tab. 1 summarizes the results. We note that the decoder-only models (AD and VAD) result in much lower reconstruction error and prediction errors. This can be explained because the learned latent space from decoder-only models does not suffer from aliasing. In particular, our approach (VAD) consistently obtains the best scores in long-horizon predictions, which suggests that our method results in better-structured latent spaces (Fig. 6). Furthermore, our approach results in better controlled achieved pose (Tab. 1 first column). See Appendix B.2 for more details.

5.3 Tactile Rod Grasping

The goal of this task is to control the relative pose between the robot end-effector and a grasped object from only tactile data. The object being grasped is a 3D-printed rod designed to simulate a tool handle. This rod is fixed in the scene to facilitate easy reset and data collection. It is important to note that the controller does not have access to the robot pose with respect to the grasped object; it solely relies on tactile measurements. The control actions are the changes in position and orientation of the robot end-effector. The control actions are constrained to a box, requiring the robot to perform multiple grasps to achieve a desired relative pose.

Figure 5: **Tactile Rod Grasping** (A) Rod grasping with Soft Bubbles where tactile signatures are encoded as depthmaps. (B) Rod grasping with Gelslims 3.0 where tactile signatures are encoded as RGB images.

We evaluate our methods on two tactile sensors with distinct mechanical properties and sensing modalities [15]: (i) the Soft Bubbles are composed of two inflated membranes that deform when in contact. This sensor exhibits large deformations that are sensed via a depth camera. We also evaluate our methods on the Gelslims 3.0 (ii) which are more rigid than the soft-bubbles and the sensor deformation are sensed via RGB images.

Figure 6: **Moving Block Setup** On the left, two different block location result in the same observation. However, the same action applied to both states resulted in different next states (right).

To train the models, we collect 500 trajectories of robot-rod interactions under random actions for each sensor. The length of these trajectories is 10. The rod used in these interaction has cylindrical dimension of 120mm in length and a diameter of 20mm. In the case of the Soft Bubbles, the observed states are encoded as deformation maps of the sensor, representing the difference between the current sensor depth map and a reference undeformed state. On the other hand, for the Gelslims sensor, the observations are grayscale image differences between the current state and a reference undeformed state.

To assess the performance of the learned methods, we execute 20 trajectories using an LQR controller, starting from random configurations of the robot grasping the rod. The objective is to achieve a specific robot-rod configuration, where the rod is grasped at the center of the sensor and aligned with the end-effector. This goal configuration is provided as a non-aliased tactile observation. The evaluation

Method	LQR Pose Errors		Reconstruction Error ↓	Prediction Error ↓ ($\cdot 10^{-3}$)		
	Mean ↓	Std ↓		1 step	5 step	10 step
AE	2.13	4.36	$2.21 \cdot 10^{-3}$	21.19	318.4	1045.3
E2C	4.01	3.02	$7.07 \cdot 10^{-2}$	102.4	110.6	107.7
AD	2.90	3.22	$\mathbf{2.41 \cdot 10^{-7}}$	2.231	40.57	78.77
VAD (ours)	**0.53**	**2.37**	$1.14 \cdot 10^{-5}$	**0.726**	**30.74**	**62.96**

Table 1: **Moving Block Evaluation:** LQR Pose Errors = error between an unaliased target pose and the pose achieved after 10 control steps following LQR control law. Reconstruction Error and Prediction Error for 500 test data trajectories propagating latent dynamics.

was conducted using three different rods: the same 20mm rod used during training, as well as two novel rods of sizes 15mm and 30mm, to assess the generalization capability of the methods to varying geometries. The pose error between the final achieved configuration and the target configuration was computed as a measure of performance. Detailed information on the metrics computation can be found in Appendix B.3. Tables 2 and 4 present a summary of these metrics. Notably, our method consistently yielded lower errors in achieving the desired tactile configuration and pose, demon-

Method	Bubbles Rod Pose Errors						Gelslim Rod Pose Errors					
	20mm Rod (Train)		15mm Rod		30mm Rod		20mm Rod (Train)		15mm Rod		30mm Rod	
	Mean ↓	Std ↓	Mean ↓	Std ↓	Mean↓	Std↓	Mean ↓	Std ↓	Mean ↓	Std ↓	Mean↓	Std↓
AE	41.79	37.69	27.27	36.92	53.86	52.44	16.77	22.67	27.27	36.92	11.66	16.29
E2C	25.29	31.65	77.11	58.14	31.08	23.82	14.45	15.15	18.22	10.26	16.01	9.69
AD	58.05	36.27	65.46	31.37	62.26	39.04	64.13	18.00	40.61	36.96	80.22	11.74
VAD (ours)	**5.23**	**4.06**	**10.91**	**3.99**	**7.68**	**2.67**	**8.54**	**16.01**	**8.98**	**7.27**	**10.39**	**19.83**

Table 2: **Tactile Rod Grasping Evaluation:** Measuring the error between the planar pose achieved for 20 control steps and the target (rod vertical). For each sensor, we test on the training rod (20mm diameter) as well 2 unseen rods (15mm and 30mm diameter). Statistics are reported over 20 trials per method and rod.

strating its effectiveness for both known and unknown objects, as well as across different sensor modalities.

5.4 Tactile Cartpole

The goal of this task is to demonstrate the utility of our method as a low-level controller for tool manipulation tasks. To this end, we combine our learned tactile low-level controller to correct the relative robot-tool position with a high-level controller that controls tool orientation.

The setup is composed of a cylindrical rod connected via a revolute joint to an actuated cart on a rail. The rod is grasped by the robot and simulates the tool handle. Fig. 1 illustrates this task. By moving the cart, we perturb the grasped tool pose, serving as an automated mechanism. The goal of the robot is to keep the rod vertical and aligned with its end-effector. Therefore, the cartpole motions force the robot to correct and adapt to the resulting perturbed tool pose.

Method	Number of Steps		Rod Angular Mean
	Mean↑	Std ↓	Error [rad] ↓
AE	11.84	7.42	0.2949
E2C	8.12	3.17	0.2682
AD	11.73	7.95	0.2057
VAD (ours)	**73.06**	**23.25**	**0.09267**

Table 3: **Cartpole Control Evaluation:** Reporting the number of perturbations steps without letting the tool slip out of hand or dropping the tool and the rod angle error with respect to the target vertical rod. Statistics are reported over 20 trials per method.

We compare our method with the baselines, all sharing the same high-level controller, differing only on the low-level robot-rod align motion. We evaluate the time the robot is able to keep the rod vertical without dropping it as well as the average angle error, Tab. 3. Our method considerably outperforms the baselines and is able to maintain the tool vertical for longer periods of time and track the desired relative orientation significantly more successfully. This suggests that our approach is able to better generalize to novel tasks.

6 Discussion and Limitations

One limitation of decoder-only architectures is that obtaining the latent representation requires multiple passes through the decoder using inference-via-optimization, which can be slower compared to encoder-decoder architectures that only require a single forward pass. Another limitation of our approach is its limited exposure to cylindrical rods. Since tools can have various handle geometries such as rectangular or curved handles, generalizing the learned model becomes a challenge. To address this, we propose learning separate models for each primitive handle geometry. At runtime, a handle geometry-aware classifier can be used to select the appropriate controller based on the current grasped tool geometry, enabling better adaptability to different handle shapes.

Finally, both the Gelslims and Soft Bubbles tactile sensors are smooth elastomers despite their different mechanical properties. In our approach, we employ decoder architectures based on convolutional neural networks (CNNs) to generate the sensor data. However, it is worth noting that these CNN-based decoders may not fully capture the inherent characteristics of the sensors, like smoothness and continuity. To overcome this limitation, alternative methods can be explored, which specifically incorporate smoothness constraints on the sensor geometry. By adopting such methods that better capture the three-dimensional geometry of the sensors, more accurate predictions can be achieved, thereby improving the overall performance and reliability of the system.

References

[1] A. Alspach, K. Hashimoto, N. Kuppuswamy, and R. Tedrake. Soft-bubble: A highly compliant dense geometry tactile sensor for robot manipulation. In *2019 2nd IEEE International Conference on Soft Robotics (RoboSoft)*, pages 597–604. IEEE, 2019.

[2] I. Taylor, S. Dong, and A. Rodriguez. Gelslim3. 0: High-resolution measurement of shape, force and slip in a compact tactile-sensing finger. *arXiv preprint arXiv:2103.12269*, 2021.

[3] M. Lambeta, P.-W. Chou, S. Tian, B. Yang, B. Maloon, V. R. Most, D. Stroud, R. Santos, A. Byagowi, G. Kammerer, et al. Digit: A novel design for a low-cost compact high-resolution tactile sensor with application to in-hand manipulation. *IEEE Robotics and Automation Letters*, 5(3):3838–3845, 2020.

[4] A. Yamaguchi. Fingervision for tactile behaviors, manipulation, and haptic feedback teleoperation. In *the 4th IEEJ international workshop on Sensing, Actuation, Motion Control, and Optimization (SAM-CON2018)*, 2018.

[5] W. K. Do and M. Kennedy. Densetact: Optical tactile sensor for dense shape reconstruction. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 6188–6194. IEEE, 2022.

[6] M. Bauza, A. Bronars, and A. Rodriguez. Tac2pose: Tactile object pose estimation from the first touch. *arXiv preprint arXiv:2204.11701*, 2022.

[7] N. Kuppuswamy, A. Castro, C. Phillips-Grafflin, A. Alspach, and R. Tedrake. Fast model-based contact patch and pose estimation for highly deformable dense-geometry tactile sensors. *IEEE Robotics and Automation Letters*, 5(2):1811–1818, 2020. doi:10.1109/LRA.2019.2961050.

[8] T. Kelestemur, R. Platt, and T. Padir. Tactile pose estimation and policy learning for unknown object manipulation. *arXiv preprint arXiv:2203.10685*, 2022.

[9] M. Bauza, E. Valls, B. Lim, T. Sechopoulos, and A. Rodriguez. Tactile object pose estimation from the first touch with geometric contact rendering. *arXiv preprint arXiv:2012.05205*, 2020.

[10] J. Kerr, H. Huang, A. Wilcox, R. Hoque, J. Ichnowski, R. Calandra, and K. Goldberg. Learning self-supervised representations from vision and touch for active sliding perception of deformable surfaces. *arXiv preprint arXiv:2209.13042*, 2022.

[11] J. Lin, R. Calandra, and S. Levine. Learning to identify object instances by touch: Tactile recognition via multimodal matching. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3644–3650. IEEE, 2019.

[12] J. Zhao, M. Bauza, and E. H. Adelson. Fingerslam: Closed-loop unknown object localization and reconstruction from visuo-tactile feedback. *arXiv preprint arXiv:2303.07997*, 2023.

[13] S. Dong, W. Yuan, and E. H. Adelson. Improved gelsight tactile sensor for measuring geometry and slip. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 137–144. IEEE, 2017.

[14] S. Dong, D. Ma, E. Donlon, and A. Rodriguez. Maintaining grasps within slipping bounds by monitoring incipient slip. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3818–3824. IEEE, 2019.

[15] M. Oller, M. P. i Lisbona, D. Berenson, and N. Fazeli. Manipulation via membranes: High-resolution and highly deformable tactile sensing and control. In *Conference on Robot Learning*, pages 1850–1859. PMLR, 2023.

[16] S. Tian, F. Ebert, D. Jayaraman, M. Mudigonda, C. Finn, R. Calandra, and S. Levine. Manipulation by feel: Touch-based control with deep predictive models. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 818–824. IEEE, 2019.

[17] C. Wang, S. Wang, B. Romero, F. Veiga, and E. Adelson. Swingbot: Learning physical features from in-hand tactile exploration for dynamic swing-up manipulation. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 5633–5640. IEEE, 2020.

[18] Y. She, S. Wang, S. Dong, N. Sunil, A. Rodriguez, and E. Adelson. Cable manipulation with a tactile-reactive gripper. *The International Journal of Robotics Research*, 40(12-14):1385–1401, 2021.

[19] H. Van Hoof, N. Chen, M. Karl, P. van der Smagt, and J. Peters. Stable reinforcement learning with autoencoders for tactile and visual data. In *2016 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pages 3928–3934. IEEE, 2016.

[20] Y. Zheng, F. F. Veiga, J. Peters, and V. J. Santos. Autonomous learning of page flipping movements via tactile feedback. *IEEE Transactions on Robotics*, 38(5):2734–2749, 2022.

[21] S. Dong, D. K. Jha, D. Romeres, S. Kim, D. Nikovski, and A. Rodriguez. Tactile-rl for insertion: Generalization to objects of unknown geometry. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6437–6443. IEEE, 2021.

[22] N. Sunil, S. Wang, Y. She, E. Adelson, and A. R. Garcia. Visuotactile affordances for cloth manipulation with local control. In *Conference on Robot Learning*, pages 1596–1606. PMLR, 2023.

[23] H. T. Suh, N. Kuppuswamy, T. Pang, P. Mitiguy, A. Alspach, and R. Tedrake. Seed: Series elastic end effectors in 6d for visuotactile tool use. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 4684–4691. IEEE, 2022.

[24] S. L. Brunton, J. L. Proctor, and J. N. Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the national academy of sciences*, 113(15): 3932–3937, 2016.

[25] B. Lusch, J. N. Kutz, and S. L. Brunton. Deep learning for universal linear embeddings of nonlinear dynamics. *Nature communications*, 9(1):4950, 2018.

[26] M. Watter, J. Springenberg, J. Boedecker, and M. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. *Advances in neural information processing systems*, 28, 2015.

[27] M. Jaques, M. Burke, and T. M. Hospedales. Newtonianvae: Proportional control and goal identification from pixels via physical latent spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4454–4463, 2021.

[28] R. Okumura, N. Nishio, and T. Taniguchi. Tactile-sensitive newtonianvae for high-accuracy industrial connector-socket insertion. *arXiv preprint arXiv:2203.05955*, 2022.

[29] S. Tan and M. L. Mayrovouniotis. Reducing data dimensionality through optimizing neural network inputs. *AIChE Journal*, 41(6):1471–1480, 1995.

[30] J. J. Park, P. Florence, J. Straub, R. Newcombe, and S. Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 165–174, 2019.

[31] J. Mu, W. Qiu, A. Kortylewski, A. Yuille, N. Vasconcelos, and X. Wang. A-sdf: Learning disentangled signed distance functions for articulated shape representation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 13001–13011, 2021.

[32] Y. Wi, A. Zeng, P. Florence, and N. Fazeli. Virdo++: Real-world, visuo-tactile dynamics and perception of deformable objects. *arXiv preprint arXiv:2210.03701*, 2022.

[33] M. Van der Merwe, Y. Wi, D. Berenson, and N. Fazeli. Integrated object deformation and contact patch estimation from visuo-tactile feedback. *arXiv preprint arXiv:2305.14470*, 2023.

[34] A. Zadeh, Y.-C. Lim, P. P. Liang, and L.-P. Morency. Variational auto-decoder: A method for neural generative modeling from incomplete data. *arXiv preprint arXiv:1903.00840*, 2019.

[35] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[36] T. Pappas, A. Laub, and N. Sandell. On the numerical solution of the discrete-time algebraic riccati equation. *IEEE Transactions on Automatic Control*, 25(4):631–641, 1980.