Manifold Topology Divergence: a Framework for Comparing Data Manifolds

Abstract

We develop a framework for comparing data manifolds, aimed, in particular, towards the evaluation of deep generative models. We describe a novel tool, Cross-Barcode(P,Q), that, given a pair of distributions in a high-dimensional space, tracks multiscale topology spacial discrepancies between manifolds on which the distributions are concentrated. Based on the Cross-Barcode, we introduce the Manifold Topology Divergence score (MTop-Divergence) and apply it to assess the performance of deep generative models in various domains: images, 3D-shapes, time-series, and on different datasets: MNIST, Fashion MNIST, SVHN, CIFAR10, FFHQ, chest X-ray images, market stock data, ShapeNet. We demonstrate that the MTop-Divergence accurately detects various degrees of mode-dropping, intra-mode collapse, mode invention, and image disturbance. Our algorithm scales well (essentially linearly) with the increase of the dimension of the ambient high-dimensional space. It is one of the first TDA-based practical methodologies that can be applied universally to datasets of different sizes and dimensions, including the ones on which the most recent GANs in the visual domain are trained. The proposed method is domain agnostic and does not rely on pre-trained networks.

1 Introduction

Geometric perspective in working with data distributions has been pervasive in machine learning [2, 5, 10, 7, 21, 18]. Reconstruction of the data from observing only a subset of its points has made a significant step forward since the invention of Generative Adversarial Networks (GANs) [11]. Despite the exceptional success that deep generative models achieved, there still exists a longstanding challenge of good assessment of the generated samples quality and diversity [4].

For images, the Fréchet Inception Distance (FID) [14] is the most popular GAN evaluation measure. However, FID is limited only to 2D images since it relies on pre-trained on ImageNet "Inception" network. FID unrealistically approximates point clouds by Gaussians in embedding space; also, FID is biased [3]. Surprisingly, FID can't be applied to compare adversarial and non-adversarial generative models since it is overly pessimistic to the latter ones [26].

The evaluation of generative models is about comparing two *point clouds*: the true data cloud P_{data} and the model (generated) cloud Q_{model}. In view of the commonly assumed Manifold Hypothesis [2, 10], we develop a topology-based measure for comparing two manifolds: the true data manifold M_{data} and the model manifold M_{model}, by analysing samples $P_{\text{data}} \subset M_{\text{data}}$ and $Q_{\text{model}} \subset M_{\text{model}}$.

Contribution. In this work, we make the following contributions:

1. We introduce a new tool: Cross-Barcode(P, Q). For a pair of point clouds P and Q, the Cross-Barcode(P, Q) records the differences in multiscale topology between two manifolds

35   approximated by the point clouds;

36 2. We propose a new measure for comparing two data manifolds approximated by point clouds:
37   Manifold Topology Divergence (MTop-Div);

38 3. We apply the MTop-Div to evaluate performance of GANs in various domains: 2D images, 3D
39   shapes, time-series. We show that the MTop-Div correlates well with domain-specific measures
40   and can be used for model selection. Also it provides insights about evolution of generated data
41   manifold during training;

42 4. We have compared the MTop-Div against 6 established evaluation methods: FID, discriminative
43   score, MMD, JSD, 1-coverage, and Geometry score and found that MTop-Div is able to capture
44   subtle differences in data geometry;

45 5. We have essentially overcame the known TDA scalability issues and in particular have carried out
46   the MTop-Div calculations on most recent datasets such as FFHQ, with dimensions D up to 10^7.

Related work. GANs try to recover the true data distribution via a min-max game where two players,
typically represented by deep neural networks, called Discriminator and Generator, compete by
optimizing the common objective. Training curves are not informative since generator and dis-
criminator counter each other, thus, the loss values are often meaningless. Several other measures
were introduced to estimate the quality of GANs. However, there is no consensus which of them
best captures strengths and limitations of the models and can be used for the fair model selection.
The likelihood in Parzen window works poorly in high-dimensional spaces and does not correlate
with the visual quality of generated samples [28]. The Inception Score (IS) [27] measures both the
discriminability and diversity of generated samples. It relies on the pre-trained Inception network and
is limited to 2D images domain. While IS correlates with visual image quality, it ignores the true data
distribution, doesn't detect mode dropping and is sensitive to image resolution. The Fréchet Inception
Distance (FID) [14] is a distance between two multivariate Gaussians. These Gaussians approximate
the features of generated and true data extracted from the last hidden layer of the pretrained Inception
network. Similar variant is KID [3] which computes MMD distance between two distributions of
features. The work [12] proposed to use the Duality Gap, a notion from the game theory, as a domain
agnostic measure for GAN evaluation. Another variant of a measure inspired by game theory was
proposed in [25]. Conventional precision and recall measures can be also used [20, 19]. Accurate
calculation of precision and recall is limited to simple datasets from low-dimensional manifolds. The
Geometry Score (GScore) [17] is the L2-distance between mean Relative Living Times (RLT) of
topological features calculated for the model distribution and the true data distribution. The work [33]
uses Wasserstein distance between RLTs for this purpose. The GScore is domain agnostic, does not
involve auxiliary pretrained networks and is not limited to 2D images. However, GScore is not sensi-
tive even to some simple transformations - like constant shift, dilation, or reflection (see our fig. 2, 4).
The barcodes in GScore are calculated approximately, based only on the approximate witness com-
plexes on 64 landmark points sampled from each distribution. That's why the procedure is stochastic
and should be repeated several thousand times for averaging. Thus, the calculation of GScore can be
prohibitively long for large datasets. We also refer reader to the comprehensive survey [4].

2   Cross-Barcode and Manifold Topology Divergence.

2.1   Multiscale simplicial approximation of manifolds.

According to the well-known Manifold Hypothesis [10] the support of the data distribution $\mathcal{P}_{\text{data}}$ is
often concentrated on a low-dimensional manifold M_{data}. We construct a framework for comparing
numerically such distribution $\mathcal{P}_{\text{data}}$ with a similar distribution $\mathcal{Q}_{\text{model}}$ concentrated on a manifold
M_{model}. Such distribution $\mathcal{Q}_{\text{model}}$ is produced in one of applications scenarios, for example, by a
generative deep neural network. The immediate difficulty here is that the manifold M_{data} is unknown
and is described only through discrete sets of samples from the distribution $\mathcal{P}_{\text{data}}$. One standard
approach to resolve this difficulty is to approximate the manifold M_{data} by simplices with vertices
given by the sampled points. The simplices approximating the manifold are picked based on proximity
information given by the pairwise distances between sampled points [2, 23]. The standard approach
is to fix a threshold $r > 0$ and to take the simplices whose edges do not exceed the threshold r. The
choice of threshold is essential here since if it is too small, then only the initial points, i.e., separated
from each other 0-dimensional simplices, are allowed. And if the threshold is too large, then all
possible simplices with sampled points as vertices are included and their union is simply the big blob
representing the convex hull of the sampled points. Instead of trying to guess the right value of the

threshold, the standard recent approach is to study all thresholds at once. This can be achieved thanks to the mathematical tool, called barcode [7], that quantifies the evolution of topological features over multiple scales. For each value of r the barcode describes the topology, namely the numbers of holes or voids of different dimensions, of the union of all simplices included up to the threshold r.

2.2 Measuring the differences in simplicial approximation of two manifolds

However, to estimate numerically the degree of similarity between the manifolds $M_{\text{model}}, M_{\text{data}} \subset \mathbb{R}^D$, it is important not just to know the numbers of topological features across different scales for simplicial complexes approximating $M_{\text{model}}, M_{\text{data}}$, but to be able to verify that the similar topological features are located at similar places and appear at similar scales.

Our method measures the differences in the simplicial approximation of the two manifolds, represented by samples P and Q, by constructing sets of simplices, describing discrepancies between the two manifolds. To construct these sets of simplices we take the edges connecting $P-$points with $Q-$points, and also $P-$points between them, ordered by their length, and start adding these edges one by one, beginning from the smallest edge and gradually increasing the threshold, see Figure 1. We add also the triangles and $k-$simplices at the threshold when all their edges have been added. It is assumed that all edges between $Q-$points were already in the initial set. We track in this process the births and the deaths of topological features, where the topological features are allowed

Figure 1: Edges(red) connecting $P-$points(red) with $Q-$points(blue), and also $P-$points between them, are added for three thresholds: $\alpha = 0.2, 0.4, 0.6$

here to have boundaries on any simplices formed by $Q-$points. The longer the lifespan of the topological feature across the change of threshold the bigger the described by this feature discrepancy between the two manifolds.

Homology is a tool that permits to single out topological features that are similar, and to decompose any topological feature into a sum of basic topological features. More specifically, in our case, a $k-$cycle is a collection of $k-$simplices formed by $P-$ and $Q-$ points, such that their boundaries cancel each other, perhaps except for the boundary simplices formed only by $Q-$points. For example, a cycle of dimension $k = 1$ corresponds to a path connecting a pair of $Q-$points and consisting of edges passing through a set of $P-$points. A cycle which is a boundary of a set of $(k+1)-$simplices is considered trivial. Two cycles are topologically equivalent if they differ by a boundary, and by collection of simplices formed only by $Q-$points. A union of cycles is again a cycle. Each cycle can be represented by a vector in the vector space where each simplex corresponds to a generator. In practice, the vector space over $\{0, 1\}$ is used most often. The union of cycles corresponds to the sum of vectors. The homology vector space H_k is defined as the factor of the vector space of all $k-$cycles modulo the vector space of boundaries and cycles consisting of simplices formed only by $Q-$points. A set of vectors forming a basis in this factor-space corresponds to a set of basic topological features, so that any other topological feature is equivalent to a sum of some basic features.

The homology are also defined for manifolds and for arbitrary topological spaces. This definition is technical and we have to omit it due to limited space, and to refer to e.g. [13, 22] for details. The relevant properties for us are the following. For each topological space X the vector spaces $H_k(X)$, $k = 0, 1 \ldots$, are defined. The dimension of the vector space H_k equals to the number of independent $k-$dimensional topological features (holes,voids etc). An inclusion $Y \subset X$ induces a natural map $H_k(Y) \to H_k(X)$

In terms of homology, we would like to verify that not just the dimensions of homology groups $H_*(M_{\text{model}})$ and $H_*(M_{\text{data}})$ are the same but that more importantly the natural maps:

$$\varphi_r : H_*(M_{\text{model}} \cap M_{\text{data}}) \to H_*(M_{\text{model}}) \tag{1}$$

$$\varphi_p : H_*(M_{\text{model}} \cap M_{\text{data}}) \to H_*(M_{\text{data}}) \tag{2}$$

induced by the embeddings are as close as possible to isomorphisms. The homology of a pair is the tool that measures how far such maps are from isomorphisms. Given a pair of topological spaces $Y \subset X$, the homology of a pair $H_*(X, Y)$ counts the number of independent topological features

142 in X that cannot be deformed to a topological feauture in Y plus independent topological features
143 in Y that, after the embedding to X, become deformable to a point. An equivalent description,
144 the homology of a pair $H_*(X, Y)$ counts the number of independent topological features in the
145 factor-space X/Y, where all points of Y are contracted to a single point. The important fact for us
146 is that the map, induced by the embedding, $H_*(Y) \to H_*(X)$ is an isomorphism if and only if the
147 homology of the pair $H_*(X, Y)$ are trivial. Moreover the embedding of simple simplicial complexes
148 $Y \subset X$ is an equivalence in homotopy category, if and only if the homology of the pair $H_*(X, Y)$
149 are trivial [30].

150 To define the counterpart of this construction for manifolds represented by point clouds, we employ
151 the following strategy. Firstly, we replace the pair $(M_{\text{model}} \cap M_{\text{data}}) \subset M_{\text{model}}$ by the equivalent pair
152 $M_{\text{model}} \subset (M_{\text{data}} \cup M_{\text{model}})$ with the same factor-space. Then, we represent $(M_{\text{data}} \cup M_{\text{model}})$ by
153 the union of point clouds $P \cup Q$, where the point clouds P, Q are sampled from the distributions $\mathcal{P}_{\text{data}}$,
154 $\mathcal{Q}_{\text{model}}$. Our principal claim here is that taking topologically the quotient of $(M_{\text{data}} \cup M_{\text{model}})$ by
155 M_{model} is equivalent in the framework of multiscale analysis of topological features to the following
156 operation on the matrix $m_{P \cup Q}$ of pairwise distances of the cloud $P \cup Q$: **we set to zero all pairwise**
157 **distances within the subcloud Q** $\subset (P \cup Q)$.

2.3 Cross-Barcode (P,Q)

159 Let $P = \{p_i\}$, $Q = \{q_j\}$, $p_i, q_j \in \mathbb{R}^D$ are two point clouds sampled from two distributions $\mathcal{P}$,
160 $\mathcal{Q}$. To define Cross-Barcode(P, Q) we construct first the following filtered simplicial complex. Let
161 $(\Gamma_{P \cup Q}, m_{(P \cup Q)/Q})$ be the metric space defined as the metrized complete graph on the union of point
162 clouds $P \cup Q$ with the distance matrix given by the pairwise distance in $\mathbb{R}^D$ for the pairs of points
163 (p_i, p_j) or (p_i, q_j) and with all pairwise distances within the cloud Q that we set to zero. Our filtered
164 simplicial complex is the Vietoris-Rips complex of $(\Gamma_{P \cup Q}, m_{(P \cup Q)/Q})$.

165 Recall that given such a graph Γ with matrix m of pairwise distances between vertices and a
166 parameter $\alpha > 0$, the Vietoris-Rips complex $R_\alpha(\Gamma, m)$ is the abstract simplicial complex with
167 simplices that correspond to the non-empty subsets of vertices of Γ whose pairwise distances are
168 less than α as measured by m. Increasing parameter α adds more simplices and this gives a nested
169 family of collections of simplices know as filtered simplicial complex. Recall that a **simplicial**
170 **complex** is described by a set of vertices $V = \{v_1, \ldots, v_N\}$, and a collection of $k-$simplices S, i.e.
171 $(k + 1)-$elements subsets of the set of vertices V, $k \geq 0$. The set of simplices S should satisfy the
172 condition that for each simplex $s \in S$ all the $(k - 1)$-simplices obtained by the deletion of a vertex
173 from the subset of vertices of s belong also to S. The **filtered simplicial complexes** is the family of
174 simplicial complexes S_α with nested collections of simplices: for $\alpha_1 < \alpha_2$ all simplices of S_{α_1} are
175 also in S_{α_2}.

176 At the initial moment, $\alpha = 0$, the simplicial complex $R_\alpha(\Gamma_{P \cup Q}, m_{(P \cup Q)/Q})$ has trivial homology
177 H_k for all $k > 0$ since it contains all simplices formed by $Q-$points. The dimension of the $0-$th
178 homology equals at $\alpha = 0$ to the number of $P-$points, since no edge between them or between a
179 $P-$point and a $Q-$point is added at the beginning. As we increase α, some cycles, holes or voids
180 appear in our complex R_α. Then, some combinations of these cycles disappear. The **persistent**
181 **homology** principal theorem [34, 7] states that it is possible to choose the set of generators in the
182 homology of filtered complexes $H_k(R_\alpha)$ across all the scales α such that each generator appears at
183 its specific "birth" time and disappears at its specific "death" time. These sets of "birth" and "deaths"
184 of topological features in R_α are registered in **Barcode** of the filtered complex.

185 **Definition.** The Cross-Barcode$_i(P, Q)$ is the set of intervals recording the "birth" and "deaths" times
186 of $i-$dimensional topological features in the filtered simplicial complex $R_\alpha(\Gamma_{P \cup Q}, m_{(P \cup Q)/Q})$.

187 Topological features with longer "lifespan" are considered essential. The topological features with
188 "birth"="death" are trivial by definition and do not appear in Cross-Barcode$_*(P, Q)$.

2.4 Basic properties of Cross-Barcode$_*$(P,Q).

190 **Proposition 1.** Here is a list of basic properties of Cross-Barcode$_*(P, Q)$:

191 • if the two clouds coincide then Cross-Barcode$_*(P, P) = \varnothing$;
192 • for $Q = \varnothing$, Cross-Barcode$_*(P, \varnothing) = $ Barcode$_*(P)$ the usual barcode of the point cloud P itself;

193 • the norm of Cross-Barcode$_i$$(P,Q)$, $i \geq 0$, is bounded from above by the Hausdorff distance

$$\|\text{Cross-Barcode}_i\,(P,Q)\|_B \leq d_H(P,Q). \tag{3}$$

194 The proof is given in appendix.

2.5 The Manifold Topology Divergence (MTop-Div)

196 The bound from eq.(3) and the equality Cross-Barcode$_*$$(P,P) = \varnothing$ imply that the closeness of
197 Cross-Barcode$_*$$(P,Q)$ to the empty set is a natural measure of discrepancy between $\mathcal{P}$ and $\mathcal{Q}$. Each
198 Cross-Barcode$_i$$(P,Q)$ is a list of intervals describing the persistent homology H_i. To measure the
199 closeness to the empty set, one can use segments' statistics: sum of lengths, sum of squared lengths,
200 number of segments, the maximal length (H_i max) or specific quantile. We assume that various
201 characteristics of different H_i could be useful in various cases, but the cross-barcodes for H_0 and H_1
202 can be calculated relatively fast.

203 Our **MTop-Divergence**$(\mathcal{P}, \mathcal{Q})$ is based on the sum of lengths of segments in Cross-Barcode$_1$$(P,Q)$,
204 see section 2.6 for details. The sum of lengths of segments in Cross-Barcode$_1$$(P,Q)$ has an interesting
205 interpretation via the Earth Mover Distance. Namely, it is easy to prove (see Appendix C) that EM-
206 Distance between the Relative Living Time histogram for Cross-Barcode$_1$$(P,Q)$ and the histogram
207 of the empty barcode, multiplied by the parameter α_{max} from the definition of RLT, see e.g. [17],
208 coincides with the sum of lengths of segments in H_1. This ensures the standard good stability
209 properties of this quantity.

210 Our metrics can be applied in two settings: to a pair of distributions $\mathcal{P}_{\text{data}}$, $\mathcal{Q}_{\text{model}}$, in which case we
211 denote our score MTop-Div(D,M) and to a pair of distributions $\mathcal{Q}_{\text{model}}$, $\mathcal{P}_{\text{data}}$, in which case our score
212 is denoted MTop-Div(M,D). These two variants of the Cross-Barcode, and of the MTop-Divergence
213 are related to the concepts of precision and recall, we leave exploration of this analogy for further
214 research. These two variants could be analyzed separately or combined together, e.g. averaged.

2.6 Algorithm

216 To calculate the score that evaluates the similitude between two distributions, we employ the following
217 algorithm. First, we compute Cross-Barcode$_1$$(P,Q)$ on point clouds P, Q of sizes b_P, b_Q sampled
218 from the two distributions $\mathcal{P}, \mathcal{Q}$. For this we calculate the matrices $m_P, m_{P,Q}$ of pairwise distances
219 within the cloud P and between clouds P and Q. Then the algorithm constructs the Vietoris-Rips
220 filtered simplicial complex from the matrix $m_{(P\cup Q)/Q}$ which is the matrix of pairwise distances in
221 $P \cup Q$ with the pairs of points from cloud Q block replaced by zeroes and with other blocks given
222 by $m_P, m_{P,Q}$. Next step is to calculate the barcode of the constructed filtered simplicial complex.
223 This step and the previous step constructing the filtered complex from the matrix $m_{(P\cup Q)/Q}$ can
224 be done using one of the fast scripts[1], some of them are optimized for GPU acceleration, e.g.[32].
225 The calculation of barcode is based on the persistence algorithm [9]. Next, sum of lengths or one of
226 others numerical characteristcs of Cross-Barcode$_1$$(P,Q)$ is computed. Then this computation is run
227 a sufficient number of times to obtain the mean value of the picked characteristic. In our experiments
228 we have found that for common datasets the number of times from 10 to 100 is generally sufficient.
229 Our method is summarized in the Algorithms 1 and 2.

230 **Complexity.** The Algorithm 1 requires computation of the two matrices of pairwise distances
231 $m[P,P]$, $m[P,Q]$ for a pair of samples $P \in \mathbb{R}^{b_\mathcal{P} \times D}$, $Q \in \mathbb{R}^{b_\mathcal{Q} \times D}$ involving $O(b_\mathcal{P}^2 D)$ and
232 $O(b_\mathcal{P} b_\mathcal{Q} D)$ operations. After that, the complexity of the computation of barcode does not de-
233 pend on the dimension D of the data. Generally the persistence algorithm is at worst cubic in the
234 number of simplices involved. In practice, the boundary matrix is sparse in our case and thanks also
235 to the GPU optimization, the computation of cross-barcode takes similar time as in the previous step
236 on datasets of big dimensionality. Since only the discrepancies in manifold topology are calculated,
237 the results are quite robust and a relatively low number of iterations is needed to obtain accurate
238 results. Since the algorithm scales linearly with D it can be applied to the most recent datasets with
239 D up to 10^7. For example, for $D = 3.15 \times 10^6$, and batch sizes $b_\mathcal{P} = 10^3, b_\mathcal{Q} = 10^4$, on NVIDIA
240 TITAN RTX the time for GPU accelerated calculation of pairwise distances was 15 seconds, and
241 GPU-accelerated calculation of Cross-Barcode$_1$$(P,Q)$ took 30 seconds.

---

[1]Persistent Homology Computation (wiki)

Algorithm 1 Cross-Barcode$_i(P,Q)$	**Algorithm 2** MTop-Divergence$(\mathcal{P},\mathcal{Q})$, see section 2.6 for details, default suggested values: $b_{\mathcal{P}}=1000$, $b_{\mathcal{Q}}=10000$, $n=100$
Input: $m[P,P]$, $m[P,Q]$: matrices of pairwise distances within point cloud P, and between point clouds P and Q
Require: VR(M): function computing filtered complex from pairwise distances matrix M
Require: B(C,i): function computing persistence intervals of filtered complex C in dimension i
$\quad b_Q \leftarrow$ number of columns in matrix $m[P,Q]$
$\quad m[Q,Q] \leftarrow$ zeroes(b_Q, b_Q)
$\quad M \leftarrow \begin{pmatrix} m[P,P] & m[P,Q] \\ m[P,Q] & m[Q,Q] \end{pmatrix}$
$\quad$ Cross-Barcode$_i \leftarrow$ B$($VR$(M),i)$
Return: list of intervals **Cross-Barcode**$_i(P,Q)$ representing "births" and "deaths" of topological discrepancies	**Input:** $X_{\mathcal{P}}$, $X_{\mathcal{Q}}$: $N_{\mathcal{P}} \times D$, $N_{\mathcal{Q}} \times D$ arrays representing datasets
$\quad$ **for** $j=1$ **to** n **do**
$\quad\quad P_j \leftarrow$ random choice$(X_{\mathcal{P}}, b_{\mathcal{P}})$
$\quad\quad Q_j \leftarrow$ random choice$(X_{\mathcal{Q}}, b_{\mathcal{Q}})$
$\quad\quad \mathcal{B}_j \leftarrow$ list of intervals Cross-Barcode$_1(P_j, Q_j)$ calculated by Algorithm1
$\quad\quad mtd_j \leftarrow$ sum of lengths of all intervals in $\mathcal{B}_j$
$\quad$ **end for**
$\quad$ MTop-Divergence$(\mathcal{P},\mathcal{Q}) \leftarrow$ mean(mtd)
Return: number **MTop-Divergence**$(\mathcal{P},\mathcal{Q})$ representing discrepancy between the distributions $\mathcal{P}, \mathcal{Q}$

3 Experiments

We examine the ability of MTop-Div to measure quality of generative models trained on various datasets. Firstly, we illustrate the behaviour of MTop-Div on simple synthetic datasets (rings (Fig.2), disks (Fig. 13)). Secondly, we show that MTop-Div is superior to the GScore, another topology-based GAN quality measure. We carry out experiments with a mixture of Gaussians, MNIST, CIFAR10, X-ray images, FFHQ. The performance of MTop-Div is on par with FID. For images, MTop-Div is always calculated in pixel space without utilizing pre-trained networks. Thirdly, we apply MTop-Div to GANs from non-image domains: 3D shapes and time-series, where FID is not applicable. We show that MTop-Div agrees with domain-specific measures, such as JSD, MMD, Coverage, discriminative score, but MTop-Div better captures evolution of generated data manifold during training.

3.1 Simple synthetic datasets in 2D

Figure 2: MTop-Div and H0 max compared with GScore, for two ring clouds of 1000 points, as function of d =distance between ring centers, the Cross-Barcode$_1(P,Q)$ is shown at $d = 0.5$

As illustrated on Fig. 2 the GScore does not respond to shifts of the distributions' relative position.

3.2 Mode-Droping on Gaussians

One of common tasks to assess GAN's performance is measuring it's ability to uncover the variety of modes in the data distribution. A common benchmark for this problem is a mixture of Gaussians, see fig. 3. We trained two generators with very different performance: original GAN, which managed to capture all 5 modes of the distribution and WGAN-GP, which have only covered poorly two. However, the Geometry score is not sensitive to such a difference since two point clouds have the same RLT histogram. While the MTop-Div is sensitive to such a difference.

Figure 3: Difficulty of the Geometry Score to detect the mode dropping.

3.3 Digit flipping on MNIST

Figure 4 shows an experiment with MNIST dataset. We compare two point clouds: "5"s vs. vertically flipped "5"s (resembling rather "2"s). These two clouds are indistinguishable for Geometry Score, while the MTop-Div(D,M) is sensitive to such flip since it depends on the relative position of the two clouds.

vs Geometry Score = 0.0
MTop-Div = 6154.0

Figure 4: Two point clouds:"5"s from MNIST vs. vertically flipped "5"s from MNIST (resembling rather "2"s). The two clouds are indistinguishable for Geometry Score, while the MTop-Divergence is sensitive to such flip as it depends on the positions of clouds with respect to each other.

3.4 Synthetic modifications of CIFAR10

Figure 5: Experiment with modifications of CIFAR10. The disturbance level rises from zero to a maximum. Ideally, the quality score should monotonically increase with the disturbance level.

We evaluate the proposed MTop-Div(D,M) using a benchmark with the controllable disturbance level. We take CIFAR10 and apply the following modifications. Firstly, we emulate common issues in GAN: mode drop, mode invention and mode collapse by doing class drop, class addition and intra-class collapse (removal of objects within a class). Secondly, we apply two disturbance types: erasure of a random rectangle and a Gaussian noise. As 'real' images we use the test set from CIFAR10, as 'generated' images - a subsample of the train set with applied modifications. The size of the later always equals the test set size. Figure 5 shows the results. Ideally, the quality measure should monotonically increase with the disturbance level. We conclude that Geometry Score is monotone only for 'mode invention' and 'intra-mode collapse' while MTop-Div(D,M) is almost monotone for all the cases. The average Kendall-tau rank correlation between MTop-Div(D,M) and disturbance level is 0.89, while for Geometry Score the rank correlation is only 0.36. FID performs perfectly on this benchmark, not shown on Figure 5 for ease of perception.

3.5 GAN model selection

We trained WGAN and WGAN-GP on various datasets: CIFAR10, SVHN, MNIST, FashionMNIST and evaluated their quality, see Table 1. Experimental data show that the ranking between WGAN and WGAN-GP is consistent for FID and MTop-Div(D, M).

Dataset	FID		MTop-Div(D,M)	
	WGAN	WGAN-GP	WGAN	WGAN-GP
CIFAR10	**154.6**	399.2	**353.1**	1637.4
SVHN	**101.6**	154.7	**332.0**	963.2
MNIST	31.8	**22.0**	2042.8	**1526.1**
FashionMNIST	52.9	**35.1**	919.6	**660.4**

Table 1: MTop-Div is consistent with FID for model selection of GAN's trained on various datasets.

3.6 Experiments with StyleGAN

We evaluated the performance of StyleGAN [15] and StyleGAN2 [16] generators trained on the FFHQ dataset[2]. We generated 20×10^3 samples with two truncation levels: $\psi = 0.7, 1.0$ and compared them with 20×10^3 samples from FFHQ. The truncation trick is known to improve average image quality but decrease image variance. Figure 7 show the results (see also Table 3 in Appendix for more data). Thus, the ranking via MTop-Div(M, D) is consistent with FID. We also tried to calculate Geometry Score but found that it takes a prohibitively long time.

---

[2]`https://github.com/NVlabs/ffhq-dataset` (CC-BY 2.0 License)

Figure 6: Training process of GAN applied to chest X-ray data. **Top**: normalized quality measures FID, MTop-Div, Disc. score vs. epoch. Each measure is divided by it's maximum value: max. FID = 304, max MTop-Div = 21, max. Disc.score = 0.5. Lower is better. Dashed horizontal lines depict comparison of real COVID-positive and COVID-neg. chest X-rays. **Bottom**: PCA projections of real objects (red) and generated objects (green).

Figure 7: Comparison of the quality measures, FID vs MTop-Div, on StyleGAN, StyleGAN2 trained on FFHQ with different truncation levels. MTop-Div(M,D) is monotonically increasing in good correlation with FID.

3.7 Chest X-rays generation for COVID-19 detection

Waheen et al. [29] described how to apply GANs to improve COVID-19 detection from chest X-ray images. Following [29], we trained an ACGAN [24] on a dataset consisting of chest X-rays of COVID-19 positive and healthy patients [3]. Next, we studied the training process of ACGAN. Every 10'th epoch we evaluated the performance of ACGAN by comparing real and generated COVID-19 positive chest X-ray images. That is, we calculated FID, MTop-Div(D,M) and a baseline measure - discriminative score [4] of a CNN trained to distinguish real vs. generated data. The MTop-Div agrees with FID and the discriminative score. PCA projections show that generated data approximates real data well. Figure 18 in Appendix presents real and generated images.

Additionally, we compared real COVID-positive and COVID-negative chest X-ray images, see horizontal dashed lines at fig. 6. Counterintuitively, for FID real COVID-positive images are closer to real COVID-negative ones than to generated COVID-positive images; probably because FID is overly sensitive to textures. At the same time, evaluation by MTop-Div is consistent.

3.8 3D shapes generation

We use the proposed MTop-Div score to analyze the training process of the GAN applied to 3D shapes, represented by 3D point clouds [1]. For training, we used 6778 objects of the "chair" class from ShapeNet [6]. We trained GAN for 1000 epochs and tracked the following standard quality measures: Minimum Matching Distance (MMD), Coverage, and Jensen-Shannon Divergence (JSD) between marginal distributions. To understand the training process in more details, we computed PCA decomposition of real and generated objects (fig. 8, bottom). For computing PCA, each object (3D point cloud) was represented by a vector of point frequencies attached to the 3-dimensional 28^3 grid. Figure 8, top, shows that conventional metrics (MMD, JSD, Coverage) doesn't represent the training process adequately. While these measures steadily improve, the set of generated objects dramatically changes. At epoch 50, the set of generated objects (green) "explodes" and becomes much more diverse, covering a much larger space than real objects (red). Conventional quality measures (MMD, JSD, Coverage) ignore this shift while MTop-Div has a peak at this point. Next, we evaluated the final quality of GAN by training a classifier to distinguish real and generated object. A simple MLP with 3 hidden layers showed accuracy 98%, indicating that the GAN poorly approximates the manifold of

---

[3]We used the ACGAN implementation `https://github.com/clvrai/ACGAN-PyTorch`, (MIT License) and chest X-ray data was from `https://www.kaggle.com/tawsifurrahman/covid19-radiography-database` (Kaggle Data License)

[4]Discriminative score equals accuracy minus 0.5. MTop-Div better correlates with the discriminative score than FID: 0.75 vs. 0.66.

Figure 8: Training process of GAN applied to 3D shapes. **Top, middle**: quality measures MMD, JSD, 1-Coverage, MTop-Div vs. epoch. Each quality measure is normalized, that is, divided by its value at the first epoch. Lower is better. **Bottom**: PCA projection of real objects (red) and generated objects (green). **Vertical red line** (epoch 50) depicts the moment, when the manifold of generated objects "explodes" and becomes much more diverse.

Figure 9: Training dynamics of TimeGAN applied to market stock data. **Top**: discriminative score vs. epoch, MTop-Div vs. epoch. Lower is better. **Bottom**: PCA projection of real time-series (red) and generated time-series (green). **Vertical red line** (epoch 2000) depicts the moment when manifolds of real and generated objects become close.

real objects. This result is consistent with the MTop-Div score: the latter one at epoch 1000 is even larger than at epoch 1.

3.9 Time series generation

Next, we analyze training dynamics of TimeGAN [31] tailored to multivariate time-series generation. We followed the experimental protocol from [31] and used the daily historical market stocks data from 2004 to 2019, including as features the volume, high, low, opening, closing, and adjusted closing prices. The baseline evaluation measure is calculated via a classifer (RNN) trained to distinguish real and generated time-series. Particularly, the *discriminative score* equals to the accuracy of such a classifer minus 0.5. Fig. 9, top, shows the results. We conclude that the behaviour of MTop-Div is consistent with the discriminative score: both of them decrease during training. To illustrate training in more details we did PCA projections of real and generated time-series by flattening the time dimension (fig. 9, bottom). At 2000-th epoch, the point clouds of real (red) and generated (green) time-series became close, which is captured by a drop of MTop-Div score. At the same time, discriminative score is not sensitive enough to this phenomena.

4 Conclusions

We have proposed a tool, Cross-Barcode$_*(P, Q)$, which records multiscale topology discrepancies between two data manifolds approximated by point clouds. Based on the Cross-Barcode$_*(P, Q)$, we have introduced the Manifold Topology Divergence and have applied it to evaluate the performance of GANs in various domains: 2D images, 3D shapes, time-series. We have shown that the MTop-Div correlates well with domain-specific measures and can be used for model selection. Also, it provides insights about the evolution of generated data manifold during training and can be used for early stopping. The MTop-Div score is domain agnostic and does not rely on pre-trained networks. We have compared the MTop-Div against 6 established evaluation methods: FID, discriminative score, MMD, JSD, 1-coverage, and Geometry score and found that MTop-Div outperforms many of them and captures well subtle differences in data manifolds. Our methodology permits to overcome the known TDA scalability issues and to carry out the MTop-Div calculations on the most recent datasets such as FFHQ, with the size of up to 10^5 and the dimension of up to 10^7.

References

[1] Panos Achlioptas, Olga Diamanti, Ioannis Mitliagkas, and Leonidas Guibas. Learning representations and generative models for 3d point clouds. In *International conference on machine learning*, pages 40–49. PMLR, 2018.

[2] Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps and spectral techniques for embedding and clustering. In *Proceedings of the 14th International Conference on Neural Information Processing Systems: Natural and Synthetic*, pages 585–591, 2001.

[3] Mikołaj Bińkowski, Dougal J Sutherland, Michael Arbel, and Arthur Gretton. Demystifying mmd gans. *arXiv preprint arXiv:1801.01401*, 2018.

[4] Ali Borji. Pros and cons of gan evaluation measures. *Computer Vision and Image Understanding*, 179:41–65, 2019.

[5] Michael M. Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: Going beyond euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

[6] Angel X Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

[7] Frédéric Chazal and Bertrand Michel. An introduction to topological data analysis: fundamental and practical aspects for data scientists. *arXiv preprint arXiv:1710.04019*, 2017.

[8] Herbert Edelsbrunner and John Harer. Persistent homology-a survey. *Contemporary mathematics*, 453:257–282, 2008.

[9] Herbert Edelsbrunner and Dmitriy Morozov. Persistent homology: Theory and practice. In *European Congress of Mathematics Kraków, 2–7 July, 2012*, pages 31–50, 2014.

[10] Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.

[11] Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks, 2014.

[12] Paulina Grnarova, Kfir Y Levy, Aurelien Lucchi, Nathanael Perraudin, Ian Goodfellow, Thomas Hofmann, and Andreas Krause. A domain agnostic measure for monitoring and evaluating gans. In *Advances in Neural Information Processing Systems*, pages 12092–12102, 2019.

[13] Allen Hatcher. *Algebraic topology*. 2005.

[14] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pages 6626–6637, 2017.

[15] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4401–4410, 2019.

[16] Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8110–8119, 2020.

[17] Valentin Khrulkov and Ivan Oseledets. Geometry score: A method for comparing generative adversarial networks. In *International Conference on Machine Learning*, pages 2621–2629. PMLR, 2018.

[18] Kwangho Kim, Jisu Kim, Manzil Zaheer, Joon Kim, Frédéric Chazal, and Larry Wasserman. Pllay: Efficient topological layer based on persistence landscapes. In *34th Conference on Neural Information Processing Systems (NeurIPS 2020)*, 2020.

[19] Tuomas Kynkäänniemi, Tero Karras, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Improved precision and recall metric for assessing generative models. *arXiv preprint arXiv:1904.06991*, 2019.

[20] Mario Lucic, Karol Kurach, Marcin Michalski, Sylvain Gelly, and Olivier Bousquet. Are gans created equal? a large-scale study. In *Advances in neural information processing systems*, pages 700–709, 2018.

[21] Michael Moor, Max Horn, Bastian Rieck, and Karsten Borgwardt. Topological autoencoders. In *International Conference on Machine Learning*, pages 7045–7054. PMLR, 2020.

[22] Rodrigo Rojas Moraleda, Nektarios A Valous, Wei Xiong, and Niels Halama. *Computational Topology for Biomedical Image and Data Analysis: Theory and Applications*. CRC Press, 2019.

[23] Partha Niyogi, Stephen Smale, and Shmuel Weinberger. Finding the homology of submanifolds with high confidence from random samples. *Discrete & Computational Geometry*, 39(1-3):419–441, 2008.

[24] Augustus Odena, Christopher Olah, and Jonathon Shlens. Conditional image synthesis with auxiliary classifier gans. In *International conference on machine learning*, pages 2642–2651. PMLR, 2017.

[25] Catherine Olsson, Surya Bhupatiraju, Tom Brown, Augustus Odena, and Ian Goodfellow. Skill rating for generative models. *arXiv preprint arXiv:1808.04888*, 2018.

[26] Suman Ravuri and Oriol Vinyals. Classification accuracy score for conditional generative models. *arXiv preprint arXiv:1905.10887*, 2019.

[27] Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *arXiv preprint arXiv:1606.03498*, 2016.

[28] Lucas Theis, Aäron van den Oord, and Matthias Bethge. A note on the evaluation of generative models. *arXiv preprint arXiv:1511.01844*, 2015.

[29] Abdul Waheed, Muskan Goyal, Deepak Gupta, Ashish Khanna, Fadi Al-Turjman, and Plácido Rogerio Pinheiro. Covidgan: data augmentation using auxiliary classifier gan for improved covid-19 detection. *Ieee Access*, 8:91916–91923, 2020.

[30] George W Whitehead. *Elements of homotopy theory*, volume 61. Springer Science & Business Media, 1968.

[31] Jinsung Yoon, Daniel Jarrett, and Mihaela van der Schaar. Time-series generative adversarial networks. 2019.

[32] Simon Zhang, Mengbai Xiao, and Hao Wang. Gpu-accelerated computation of vietoris-rips persistence barcodes. In *36th International Symposium on Computational Geometry (SoCG 2020)*. Schloss Dagstuhl-Leibniz-Zentrum für Informatik, 2020.

[33] Sharon Zhou, Eric Zelikman, Fred Lu, Andrew Y. Ng, Gunnar Carlsson, and Stefano Ermon. Evaluating the disentanglement of deep generative models through manifold topology. *preprint arXiv:2006.03680*, 2020.

[34] Afra Zomorodian and Gunnar Carlsson. Computing persistent homology. *Discrete & Computational Geometry*, 33(2):249–274, 2005.