Pythagoras-Prover: Advancing Efficient Formal Proving via Augmented Lean Formalisation

Abstract

Modern Lean theorem provers achieve strong performance only with substantial training and inference compute. This cost is driven in part by the scarcity of verified proof data and by the long reasoning traces required for formal proof search, which make both supervised fine-tuning and sampling expensive. We introduce Pythagoras-Prover, a compute-efficient open-source family of Lean theorem provers designed to deliver strong performance under practical compute budgets. The family spans two generation paradigms: two autoregressive models with 4B and 32B parameters, and a first proof-of-concept diffusion-based theorem-proving model (4B), which iteratively refines Lean proofs at inference time. To make training more efficient, we construct a Lean-verified corpus stratified into easy, medium, and hard problems and use it for curriculum supervised fine-tuning, allowing the models to acquire proof skills progressively from shorter and simpler proofs to longer and more difficult ones. During supervised fine-tuning, we further apply a dynamic proof-reasoning filtering scheme that preserves informative proof traces while ensuring each training instance fits within an 8k-token context budget. We further introduce *Augmented Lean Formalisation* (ALF), which expands scarce verified corpora into variants of formal statements; these variants are then populated through self-distillation, providing additional training signal without requiring every mutated instance to be formally verified. By perturbing known problems while preserving their formal character, ALF exposes the model to structured variants of verified problems, reducing reliance on any single statement's surface form. Empirically, Pythagoras-Prover demonstrates strong performance across model scales. Most notably, Pythagoras-Prover-4B surpasses DeepSeek-Prover-V2-671B at pass@32 on MiniF2F-Test $(82.4\% \rightarrow 86.1\%)$, despite using roughly $167\times$ fewer parameters. Scaling to 32B further yields state-of-the-art performance among open-source neural theorem provers, with Pythagoras-Prover-32B attaining 93.0% on MiniF2F-Test and solving 93 of 672 problems on PutnamBench. We additionally release *MiniF2F-ALF*, an ALF-mutated contamination-sensitive perturbation benchmark on which every evaluated model loses accuracy; on this split, Pythagoras-Prover-32B remains the strongest evaluated prover, while Pythagoras-Prover-4B reaches parity with Goedel-Prover-V2-32B, the prior state of the art. Together, these results show that strong Lean theorem proving need not rely exclusively on frontier-scale models.

1 Introduction

Recent progress in mathematical reasoning has made large language models (LLMs) considerably more capable, yet not reliably correct. Although modern LLMs can solve complex problems end-to-end, their reasoning remains susceptible to hallucinations and subtle logical errors that natural-language inspection cannot reliably detect (Leang et al., 2025a; Lyu et al., 2023). Automated Theorem Proving (ATP) addresses this limitation by grounding model outputs in interactive proof assistants such as Lean (de Moura et al., 2015), Isabelle (Paulson, 1994) and Rocq (Coquand & Huet, 1988), whose deterministic type-checkers reject any argument that is not mechanically verifiable. This formal grounding eliminates an entire class of hallucinations and yields reasoning whose correctness can be audited step by step.

Figure 1: Performance comparison across proving tasks. The left and middle panels show results under a limited Pass@32 inference budget on MiniF2F-ALF and PutnamBench, respectively; for PutnamBench we additionally include Pythagoras-Prover at Pass@64, which incurs an inference cost comparable to Goedel-Prover-V2 with self-correction (see §4 for detailed explanation). The right panel plots best-reported MiniF2F-Test pass rate against model size (log scale), with the inference budget for each result shown in parentheses; stars mark our models (Pythagoras-Prover), and "(sc)" denotes self-correction.

In recent years, frontier systems such as DeepMind's AlphaProof and AlphaGeometry (Chervonyi et al., 2025; Hubert et al., 2025) and ByteDance's Seed-Prover (Chen et al., 2025) have demonstrated that AI systems can attain International Mathematical Olympiad (IMO) medal-level performance. In the open-source community, DeepSeek-Prover-V2 (Ren et al., 2025), Kimina-Prover (Wang et al., 2025a), and Goedel-Prover-V2 (Lin et al., 2026) have reported strong results on standard benchmarks including MiniF2F (Zheng et al., 2022) and PutnamBench (Tsoukalas et al., 2024). These successes, however, are typically achieved either through very large models with hundreds of billions of parameters, or through computationally intensive inference that relies on elaborate search procedures, self-correction, or large sampling budgets. State-of-the-art ATP therefore remains largely inaccessible to researchers and practitioners without substantial compute, and a sizeable gap persists between small open-source provers and their largest counterparts.

In this work, we release Pythagoras-Prover, a compute-efficient family of open-source theorem provers for Lean 4 that challenges the assumption that stronger formal reasoning requires frontier-scale models. At 4B parameters, Pythagoras-Prover-4B surpasses DeepSeek-Prover-V2-671B (Ren et al., 2025) at pass@32 on MiniF2F-Test (82.4% → 86.1%), despite being roughly 167× smaller. At 32B parameters, Pythagoras-Prover-32B achieves the strongest reported performance among open-weight neural Lean provers evaluated without self-correction, obtaining the highest pass rate on MiniF2F-Test while relying on standard restart sampling rather than inference-time corrective procedures. Beyond autoregressive proving, the family includes Pythagoras-Prover-Diffusion, to our knowledge the first proof-of-concept diffusion-based theorem-proving model for Lean. Under a matched 4B setting on the same self-distillation corpus and evaluation harness, Pythagoras-Prover-Diffusion trails Pythagoras-Prover-4B in raw pass@32 accuracy but generates proofs 2.58× faster on the same hardware, placing it on the throughput side of an emerging accuracy-efficiency frontier for formal theorem proving.

Underlying all our releases is a compute-frugal data recipe for Lean theorem proving. We first build a Lean-verified seed corpus of roughly 800K instances using predominantly open models with 30B parameters or fewer, with a single 235B model as the only larger component. This verified corpus is stratified into easy, medium, and hard difficulty tiers, which enables curriculum supervised fine-tuning from shorter and simpler proofs to longer and more difficult ones. We then introduce *Augmented Lean Formalisation* (ALF), which takes each verified instance and produces structured formal variants across five mutation types: simplification, generalisation, lemma proposal, proof-step decomposition, and reformulation. Because ALF uses a lightweight sanity check rather than Lean-verifying every mutated instance, it decouples corpus expansion from verifier throughput and allows for the expansion of the seed corpus by roughly 2.5×. These ALF variants are then used in two ways: first, as self-distillation inputs that enrich post-training for both the autoregressive and diffusion provers; and second, as the basis for *MiniF2F-ALF*, where the same mutation operator is applied to

MiniF2F-Test to probe whether performance transfers across nearby formal variants. Contemporary provers degrade substantially on this benchmark, suggesting that strong performance on the original split does not always transfer to structured formal variants. Thus, the 4B and 32B autoregressive provers, the diffusion prover, and the companion benchmark all follow from the same pipeline: verified seed construction enables curriculum learning, ALF expands the seed into structured variants, self-distillation turns those variants into training signal, and the same perturbation mechanism yields a contamination-sensitive perturbation benchmark.

In summary, our contributions are as follows:

- **A compute-efficient family of Lean theorem provers.** We release Pythagoras-Prover, a family of open-source Lean 4 theorem provers spanning two generation paradigms: autoregressive provers at 4B and 32B parameters, and Pythagoras-Prover-Diffusion-4B, to our knowledge the first proof-of-concept diffusion-based theorem-proving model. Pythagoras-Prover-4B surpasses DeepSeek-Prover-V2-671B on MiniF2F-Test at pass@32 ($82.4\% \rightarrow 86.1\%$), despite being roughly $167\times$ smaller, while Pythagoras-Prover-32B achieves the strongest reported performance among open-weight neural Lean provers evaluated without self-correction.

- **A compute-frugal Lean data pipeline.** We construct a Lean-verified corpus of roughly 800K instances stratified into easy, medium, and hard tiers. We then introduce *Augmented Lean Formalisation* (ALF), a structured mutation scheme that expands this corpus by roughly $2.5\times$ using lightweight sanity checks rather than per-instance Lean verification. Applying the same mutation operator to MiniF2F-Test yields *MiniF2F-ALF*, a companion benchmark for probing transfer across nearby formal variants of benchmark statements.

- **An efficient adaptation recipe for Lean-proving.** We combine parameter-efficient supervised fine-tuning, curriculum learning, self-distillation, and reinforcement learning from Lean verification. During supervised fine-tuning, a dynamic proof–reasoning filter preserves informative reasoning traces while keeping each instance within an 8K-token context budget. The same post-training corpus trains both the autoregressive and diffusion provers, allowing a controlled comparison between generation paradigms.

2 Methodology

In this section we present the training pipeline of Pythagoras-Prover in detail. We first describe our framework for generating the Lean-verified *seed* corpus (§2.1). We then present the training algorithm that turns this corpus into our base autoregressive provers (§2.2). Finally, we introduce *Augmented Lean Formalisation* (ALF), a structured mutation operator that scales the corpus beyond what per-instance Lean verification can throughput, and the self-distillation stage built on it (§2.3); the same self-distillation corpus is then used to train a diffusion-based prover (§2.4).

2.1 Synthetic Data Creation

Our training corpus is produced across three difficulty tiers, gated throughout on the Lean type-checker. *Easy* and *medium* instances are autoformalised from general mathematical-reasoning datasets (§2.1.1), while *hard* instances are drawn from competition-level sources (§2.1.2). The tiers are ordered monotonically by construction: *easy* instances are rubric-driven simplifications of medium ones (§2.1.1); *medium* problems are routine multi-step reasoning; and *hard* problems are competition proofs requiring non-routine techniques absent from general maths corpora. A representative example from each tier is given in Appendix A.6. This seed corpus delivers quality at modest scale; §2.3 then scales it via Augmented Lean Formalisation.

2.1.1 The Easy and Medium Tiers

The easy and medium tiers are produced by a three-stage seed pipeline: formal statement synthesis, formal proof verification, and rubric-guided distillation, shown in Figure 2.

Figure 2: The seed synthetic data generation pipeline for *easy* and *medium tier* problems.

Formal statements and formal proofs. Our pipeline is inspired by the theorem prover as a judge pipeline (Leang et al., 2025b), which leverages the deterministic verification of formal proof assistants to filter synthetic training data. While Leang et al. (2025b) operate solely on problems drawn from GSM8K and MATH500 formalised with GPT-4 (OpenAI et al., 2024), we broaden both the difficulty range and the domain coverage of the resulting corpus by sourcing natural-language problems from *DART-Math-Hard* (Tong et al., 2024), *DeepScaleR-Preview* (Luo et al., 2025), and *OpenR1-Math* (Hugging Face, 2025). Each problem is autoformalised into a Lean statement using Goedel-Autoformaliser-v2 (Lin et al., 2026). To mitigate the logical errors introduced by autoformalisation, we then apply *auto-informalisation* (Leang et al., 2025b): each candidate formal statement is translated back into natural language and aligned with its source problem, and instances exhibiting logical discrepancies are discarded.

For every retained formal statement, we synthesise candidate proofs with Goedel-Prover-v2-32B (Lin et al., 2026), an open prover that is orders of magnitude smaller than the GPT-4 model used by Leang et al. (2025b). We draw $n=2$ independent proof attempts per statement and accept the (statement, proof) pair into the training corpus if at least one attempt is verified by the Lean type-checker. This deterministic verification step ensures that every retained training example is verified by Lean, yielding a corpus whose correctness is enforced by the proof assistant.

Rubric-guided distillation. Existing autoformalisers and provers still fail on a substantial fraction of complex mathematical statements (Lin et al., 2026; Ren et al., 2025; Wang et al., 2025a). To characterise these failures, we parse the errors shown by the Lean compiler over all rejected instances and additionally annotate a representative subset manually; we then group the observed errors into seven recurring categories: (i) *invalid projection or field errors*, where the proof references a non-existent field of a mathematical object; (ii) *unsolved goals*, where residual goal states remain after proof execution; (iii) *tactic failures* (e.g. `linarith`, `simp`, `rewrite`), arising when algebraic expressions resist automated simplification; (iv) *type mismatches*, involving domain conflicts such as integers versus natural numbers; (v) *synthesis failures*, where a required type-class property (e.g. finiteness, decidability) cannot be inferred; (vi) *unknown constant or identifier errors*, typically arising from hallucinated theorem names; and (vii) *other errors*, covering miscellaneous technical failures. Further explanation and examples of each error are presented in Appendix A.1.

This taxonomy forms the basis of a rubric (Appendix A.1) that prompts an LLM to generate simplified variants of each failed problem, with each variant targeted at the specific algebraic manipulation or logical step responsible for the failure. Unlike the free-form scaffolded synthesis of prior work (Lin et al., 2026), which prompts for unconstrained simpler or harder variants, our rubric is conditioned on a fine-grained taxonomy of Lean failure modes, so that each generated variant addresses a concrete cause of failure. We synthesise two variants per instance with Qwen3-235B and Qwen3-30B (Qwen Team et al., 2025), pairing a high-capacity generator with a smaller model that tends to yield more diverse, simpler and more effective task-specific

Figure 3: Overview of Pythagoras-Prover pipeline.

outputs (Kim et al., 2025b). Applying the rubric yields a 30% relative improvement in autoformalisation success rate; further analysis and decomposition are provided in §5.1.

2.1.2 The Hard Tier

For the hard tier we draw on Big-Math-RL-Verified (Albalak et al., 2025), restricting our selection to its Olympiads, AIME, AMC, `aops_forum`, and Level 4/5 MATH subsets. This choice is motivated by the difficulty profile of the easy/medium sources, which skews toward routine problems: DART-Math-Hard is rejection-sampled from GSM8K and MATH; DeepScaleR interleaves AIME and AMC problems with Omni-MATH (Gao et al., 2025) and routine contest preparation; and OpenR1-Math is distilled from NuminaMath-CoT (Li et al., 2024), which is itself dominated by lower-difficulty sources such as `cn_k12`. Restricting the hard tier to the subsets above therefore concentrates it on problems that demand multi-step, proof-oriented reasoning over advanced number theory, combinatorics, inequalities, and Euclidean geometry. When an exact or near-duplicate appears in both easy/medium and hard sources, we assign it to the hard tier and remove it from easy/medium to avoid cross-tier contamination.

From each retained problem we synthesise additional question variants with Qwen3.6-27B (Qwen Team, 2026) and pass the variants through the same formal-statement and formal-proof pipeline as Leang et al. (2025b) (step 2 in Figure 2). Only the synthesised variants enter the supervised fine-tuning corpus; the original Big-Math hard problems are held out and reserved exclusively for reinforcement learning. As the hard tier is substantially more challenging, we synthesise $n = 4$ variants per retained problem (versus $n = 2$ for easy/medium) so that the pipeline retains enough verifiable instances after Lean filtering. We deliberately keep these originals at full difficulty so that they retain their value both as a challenging on-policy reward signal and as an unleaked probe of generalisation; we therefore do *not* apply rubric-guided distillation to the hard tier, since its simplification step would convert hard-source failures into local subproblems and leak hard-problem structure into the supervised corpus.

2.2 Training Algorithm

We train Pythagoras-Prover in three stages: supervised fine-tuning on the seed corpus under a difficulty-ordered curriculum, reinforcement learning on held-out hard problems, and a final continued-SFT stage on the ALF self-distillation corpus of §2.3.

Supervised fine-tuning and a three-stage curriculum. We perform supervised fine-tuning with LoRA (Hu et al., 2022) under a context length of 8,192 tokens, chosen to balance training stability against computational cost. To our knowledge, Pythagoras-Prover is the first prover to reach state-of-the-art performance using parameter-efficient supervised fine-tuning, whereas prior open provers rely on full-parameter training (Lin et al., 2026; Ren et al., 2025). We order training by difficulty in a three-stage curriculum that mirrors the tiers of §2.1, training first on easy instances, then medium, and finally hard. Within each stage, a fixed 8K budget is nonetheless restrictive for theorem proving, where reasoning chains are long and discarding them outright degrades performance. We therefore adopt a *dynamic proof-reasoning filtering* scheme governed by three cases: (i) if the reasoning chain and formal proof together fit within the budget, we train on the complete sequence; (ii) if their combined length exceeds the budget, we drop the reasoning chain and retain only the formal proof; and (iii) if the formal proof alone exceeds the budget, the instance is discarded. This scheme improves substantially over both naive truncation and naive instance filtering, recovering performance comparable to full-context fine-tuning at a fraction of the cost (Appendix C.4). More training details are provided in Appendix B.1.

Reinforcement learning. For the reinforcement-learning stage we aggregate three sources: Goedel instances generated without self-correction (Lin et al., 2026), the manually annotated subset of NuminaMath-Lean (Wang et al., 2025b), and the original Big-Math hard problems held out from §2.1.2. We train with GRPO (Shao et al., 2024) with a single epoch using a rollout size of 8 per problem; a rollout receives a reward iff its proof compiles under Lean and aligns with the formal statement, and 0 otherwise. We apply DAPO-style (Yu et al., 2025) dynamic filtering, retaining a problem only when its number of successful rollouts lies in $\{1, \ldots, 5\}$. We further remove the KL-divergence penalty to encourage exploration. Unlike the SFT stage, we use full-parameter fine-tuning here, having found the LoRA-adapted policy unstable under GRPO updates (Qi et al., 2025). We observe that RL yields only modest gains over the curriculum-SFT model. We interpret this not as a shortcoming of RL but as evidence of the quality of our training corpus: because every supervised instance is Lean-verified and presented in difficulty order, the policy already internalises strong proof-search behaviour before RL, leaving limited headroom for on-policy improvement. Appendix C.2 quantifies the contribution of each stage.

2.3 Augmented Lean Formalisation and Self-Distillation

The seed corpus of §2.1 is bounded in size by the throughput of Lean verification: every retained instance has been gated on the type-checker. To scale beyond this bound, we propose *Augmented Lean Formalisation* (ALF), a structured mutation operator that expands the seed via formal variants without requiring per-instance verification. ALF prompts a dedicated mutation model (Qwen3.6-27B) to emit, for each seed instance, exactly one variant in each of five categories: *simplification*, *generalisation*, *lemma proposal*, *proof-step decomposition*, and *reformulation*. Unlike free-form variant generation at test time, ALF is applied offline across the entire seed corpus, yielding balanced coverage over transformation types.

Crucially, ALF dispenses with formal verification of the mutated instances, replacing it with a cheaper consistency check. The pipeline runs in three steps, each using a distinct, deliberately small model where a model is needed. *(i) Statement mutation:* a dedicated mutation model, Qwen3.6-27B, rewrites each seed statement into one formal variant per category, producing mutated *statements* only (no proofs at this stage). *(ii) Proof self-distillation:* each mutated statement is then populated with a proof by the post-RL Pythagoras-Prover of §2.2, which generates a single candidate proof (n=1) per statement; the 4B and 32B models each prove their own mutations. *(iii) Statement-alignment filtering:* in place of Lean verification, we retain a (statement, proof) pair only when the generated proof references its target formal statement.

We stress that step (iii) is a *statement-alignment* check, not a correctness check: it confirms that the generated proof addresses the intended goal, but it never invokes the Lean type-checker and does not certify that the proof is valid. Consequently, unlike the seed corpus, the ALF data is not Lean-verified. Replacing per-instance verification with this single alignment check removes the dominant computational cost of the pipeline, as end-to-end Lean compilation at this scale remains prohibitively expensive. We adopt this choice because prior work shows that unverified self-distilled samples remain beneficial even in domains with an executable correctness signal, such as coding (Zhang et al., 2026); whether the same holds for formal proving is an

empirical question, which we examine in Appendix C.2. As a check, we Lean-verify a random subset of 2,000 ALF instances and find that 87.8% pass, indicating that quality remains high despite the absence of exhaustive verification.

The filtered generations, together with the verified proofs collected during reinforcement learning, form a corpus of approximately 2M instances, roughly $2.5\times$ the size of the seed, which we use both for a continued-SFT stage of Pythagoras-Prover (§2.2) and for training the diffusion-based prover (§2.4).

We complete training with a continued-SFT stage on this corpus, again using LoRA to bound compute. We found cross-model distillation (for example, a 32B generator paired with a 4B trainee) unstable, so no external or larger teacher is used. The same corpus is also used to train the diffusion-based prover of §2.4, so both branches of the Pythagoras-Prover family share a single self-distillation data recipe.

2.4 Pythagoras-Prover-Diffusion

As an alternative use of the self-distillation corpus, we train Pythagoras-Prover-Diffusion, to our knowledge the first diffusion-based theorem prover. We build on a block-diffusion formulation (Arriola et al., 2025) using the `dllm` framework (Zhou et al., 2026), in which the proof is partitioned into blocks generated autoregressively while the tokens within each block are produced by discrete diffusion. The transition from autoregressive to diffusion language models has been reported to destabilise as the target length grows (Kim et al., 2025a); we find that the *dynamic proof-reasoning filtering scheme* of §2.2 carries over to this regime and keeps training stable on long Lean proofs. The remainder of this section describes our central modification to the within-block diffusion: *tactic-based masking*, which corrupts each proof at the granularity of complete Lean tactics so that the denoising objective is aligned with the discrete reasoning steps the prover must commit to at inference time.

Tactic-based masking. We use masked diffusion rather than autoregressive decoding because diffusion models can fill in sequence positions in any order, revisit earlier commitments once later context disambiguates them, and commit several positions per forward pass with a more efficient cost (Sahoo et al., 2024; Nie et al., 2025); in our case the unit of corruption is a Lean tactic rather than a single token. We adopt the discrete masked diffusion formulation of Nie et al. (2025) under the linear schedule $\alpha_t = 1 - t$, so that the diffusion time $t \in [0, 1]$ coincides with the per-unit mask probability. Let $\mathbf{x}_0 = (x_0^1, \ldots, x_0^L)$ denote a clean Lean proof of length L, $\mathbf{x}_t = (x_t^1, \ldots, x_t^L)$ its corrupted counterpart containing the mask symbol [M], and $p_\theta(\cdot \mid \mathbf{x}_t)$ the denoiser that predicts the clean token at every masked position. The theorem statement (header, goal, `:=by`) is treated as a fixed input block on which the denoiser always conditions, and corruption is applied only to positions within the proof body; the diffusion time t is resampled independently for each training sequence. Random per-token masking treats every position as exchangeable, which is mismatched with Lean proofs: the natural unit of reasoning is a complete *tactic*, and we want the denoiser to recover whole tactics rather than isolated tokens that can be guessed from sibling tokens within the same tactic. We therefore change only the unit of corruption. Let $\mathcal{T}(\mathbf{x}_0) = (\tau_1, \ldots, \tau_K)$ be the tactic spans extracted from $\mathbf{x}_0$ by a Lean parser (examples for such a span would be `intro x y z` or `have hnum : x * y * z * (x + y + z) = 36 := by`), each $\tau_k \subseteq \{1, \ldots, L\}$ a contiguous range of token indices. The residual positions $S = \{1, \ldots, L\} \setminus \bigcup_k \tau_k$ are structural (the `by` keyword, indentation, the theorem header) and are never masked: $x_t^i = x_0^i$ for all $i \in S$. The remaining positions are corrupted span-wise:[1]

$$\mathbf{x}_t^{\tau_k} \sim \begin{cases} [\text{M}]^{|\tau_k|} & \text{with probability } t, \\ \mathbf{x}_0^{\tau_k} & \text{with probability } 1 - t, \end{cases} \qquad k = 1, \ldots, K, \tag{1}$$

independently across tactics. A whole tactic is therefore either masked in full or kept intact; partial masking inside a tactic does not occur. The denoiser remains a per-token model, and the training objective replaces the per-position sum of the standard MDLM cross-entropy with a per-span sum that aggregates the per-token

---

[1]For a symbol a, a sequence $\mathbf{x}$ and a set of integers b, we denote by $a^{|b|}$ the symbol repeated $|b|$ times and by $\mathbf{x}^b$ the subsequence indexed by elements of b.

log-probabilities produced by p_θ:

$$\mathcal{L}_{\text{tac}}(\theta) \;=\; -\,\mathbb{E}_{t\sim\mathcal{U}[0,1],\,\mathbf{x}_0,\,\mathbf{x}_t}\left[\frac{1}{t}\sum_{k=1}^{K}\mathbf{1}\Big[\mathbf{x}_t^{\tau_k}=[\text{M}]^{|\tau_k|}\Big]\sum_{i\in\tau_k}\log p_\theta\big(x_0^i\,\big|\,\mathbf{x}_t\big)\right],\tag{2}$$

in which the $1/t$ prefactor compensates the expected mask count so that every noise level contributes equally in expectation to the loss. Setting $\tau_k = \{k\}$ for every k ($K = L$ in that case) reduces Eq. equation 2 to the per-token MDLM objective of Sahoo et al. (2024), so tactic-level masking is a strict generalisation of token-level masking. Because an entire tactic is masked or retained as a unit, the model cannot exploit sibling tokens within the same tactic and must recover the whole proof step from the surrounding context; the expected number of masked positions per sample, $t(L - |S|)$, scales linearly in t, so the $1/t$ weighting yields a constant-in-expectation contribution across noise levels for all tokens within a single example in a batch.

3 Experimental Setup

In this section, we describe the experimental setup used to evaluate Pythagoras-Prover, covering the benchmarks §3.1 and the evaluation protocol §3.2. All design choices are kept consistent across runs unless explicitly stated.

3.1 Benchmarks

We evaluate on three Lean theorem-proving benchmarks spanning a range of difficulty and topical coverage: MiniF2F, PutnamBench, and *MiniF2F-ALF*, a companion benchmark we introduce that reuses the ALF mutation operator of §2.3 as a perturbation on the MiniF2F test set.

MiniF2F. MiniF2F (Zheng et al., 2022) comprises 488 problem statements in Lean (244 validation and 244 test) drawn from high-school level competitions, including the AMC, AIME, and the International Mathematical Olympiad (IMO). We adopt the Kimina-revised release (Wang et al., 2025a) and report results on MiniF2F-Test, in which several erroneous statements from the original release have been corrected.

PutnamBench. PutnamBench (Tsoukalas et al., 2024) targets college-level mathematics through 672 problems sourced from the William Lowell Putnam Mathematical Competition (1962–2023), covering algebra, analysis, number theory, geometry, combinatorics, probability, and set theory.

MiniF2F-ALF. MiniF2F-ALF is a mutated variant of MiniF2F-Test, constructed by applying the ALF mutation scheme of §2.3 to each of the 244 test statements, together with further numerical and variable perturbation inspired by Mirzadeh et al. (2025). It plays a dual role. First, it serves as a *contamination-sensitive perturbation probe*: models that rely heavily on exact benchmark recall should degrade under controlled statement mutations, whereas models with more transferable proof behaviour should retain more performance. Second, it serves as a *transfer probe*, testing whether models trained on ALF-augmented data generalise to ALF-mutated test data. ALF defines five mutation operators, but some produce variants that remain nearly identical to the source statement and provide little signal for either purpose. We therefore generate five candidate mutations per problem with Codex (GPT-5.5) (OpenAI, 2026) and retain the two most divergent under cosine distance in the `Alibaba-NLP/gte-Qwen2-7B-instruct` embedding space, yielding a 488-statement benchmark. We verify that every retained statement is a well-formed Lean theorem and further judge well-formedness using Claude Code (Claude-Opus-4.5 (Anthropic, 2025)). Further details, including the perturbation procedure, are provided in Appendix B.2.

3.2 Evaluation

All experimental results are evaluated with Lean 4.9.0-rc1, using a similar evaluation environment as previous work (Lin et al., 2026; Ren et al., 2025). The model's maximum generation length is set to 30,000 tokens. A proof attempt is judged correct only if (i) it compiles under Lean with no errors and contains no `sorry`, `admit`, or otherwise unproved goals, and (ii) the target formal statement appears verbatim in the generated

Table 1: Pass@N (%) on MiniF2F-Test. "Best (N)" represents each method's highest reported pass rate, with the corresponding sampling budget in parentheses. $\dagger$ marks Kimina-Prover variants, and the highest overall result is highlighted in bold. Results in the upper section are copied from the respective papers. A detailed comparison is provided in Table 4.

Method	#Params	Pass@32	Pass@1024	Best (N)
Goedel-Prover-SFT (Lin et al., 2025b)	7B	57.6	–	62.7 (3200)
STP (Dong & Ma, 2025)	7B	–	–	67.6 (25600)
Kimina-Prover-Preview-72B (Wang et al., 2025a)	72B	68.85	–	80.74 (8192)
DeepSeek-Prover-V2-7B (Ren et al., 2025)	7B	75.6	–	82.0 (8192)
DeepSeek-Prover-V2-671B	671B	82.4	–	88.9 (8192)
Kimina-Prover-8B-Distill† (Wang et al., 2025a)	8B	77.86	–	–
Kimina-Prover-70B†	70B	84.0	87.7	92.2 (TTRL)*
Goedel-Prover-V2-8B (Lin et al., 2026)	8B	84.6	87.9	90.2 (8192)
(+Self Correction)	8B	86.7	89.3	–
Goedel-Prover-V2-32B	32B	88.1	91.8	92.2 (8192)
(+Self Correction)	32B	90.4	92.6	–
Pythagoras-Prover-4B	4B	86.1	88.1	89.8 (2048)
Pythagoras-Prover-32B	32B	89.8	92.6	**93.0** (2048)

*Refers to test-time reinforcement learning.

output, ensuring that the model proves the stated goal rather than a rewritten or weaker one. We report pass@N, the fraction of problems for which at least one of N independently sampled attempts is judged correct.

4 Experimental Results

The evaluation results on MiniF2F-Test, PutnamBench, and MiniF2F-ALF are shown in Tables 1–2 and Figure 4, respectively. Below we summarise and discuss the results: state-of-the-art accuracy at modest scale, the strongest open-source result on PutnamBench under matched effective compute, robustness to statement-level perturbation under MiniF2F-ALF, and a first viable diffusion-based theorem prover trained on the same corpus.

State-of-the-art performance at modest scale. Pythagoras-Prover-32B achieves the highest reported pass rate on MiniF2F-Test, **93.03**% at pass@2048, exceeding the best prior open-source result (Goedel-Prover-V2-32B, 92.2% at pass@8192) while using a quarter of the sampling budget, and doing so without inference-time self-correction or test-time reinforcement learning. Among methods that likewise forgo self-correction, Pythagoras-Prover-32B leads at every budget we evaluate: at pass@32 it attains 89.8%, ahead of Goedel-Prover-V2-32B (88.1%), DeepSeek-Prover-V2-671B (82.4%, roughly 20$\times$ larger), and Kimina-Prover-70B (84.0%). It further matches the self-correction-augmented Goedel-Prover-V2-32B at pass@1024 (92.6% vs. 92.6%) and surpasses it at pass@2048, indicating that the proof-search behaviour internalised during training largely obviates multi-round repair.

Pythagoras-Prover-4B outperforms substantially larger baselines. The efficiency of our recipe is clearest at the 4B scale. Under a matched pass@32 budget, Pythagoras-Prover-4B attains 86.1%, exceeding DeepSeek-Prover-V2-671B (82.4%) by 3.6 points despite being roughly 167$\times$ smaller, and outperforming Kimina-Prover-70B (84.0%), Goedel-Prover-V2-8B (84.6%), and DeepSeek-Prover-V2-7B (75.6%). The advantage persists with budget: at pass@2048 Pythagoras-Prover-4B reaches 89.8%, exceeding DeepSeek-Prover-V2-671B's pass@8192 result (88.9%) at a quarter of the budget. Against the 8B Goedel-Prover-V2, Pythagoras-Prover-4B leads at every shared budget without self-correction (88.1% vs. 87.9% at pass@1024) and stays within 1.2 points even of its self-corrected variant, at half the parameters. The training recipe thus transfers cleanly to the small-model regime, where billion-scale baselines are impractical.

Table 2: PutnamBench leaderboard (problems solved out of 672). Pythagoras-Prover solves 93 problems at pass@2048, the best open-source result, surpassing the previous best (Goedel-Prover-V2, 86 at pass@184 with self-correction).*

#	Model	Num-solved	Open-source	Compute
1	**Pythagoras-Prover**	93	✓	pass@2048
1	**Pythagoras-Prover**	59	✓	pass@64
1	**Pythagoras-Prover**	48	✓	pass@32
2	Goedel-Prover-V2 (self-correction mode)	86	✓	pass@184
2	Goedel-Prover-V2 (self-correction mode)	57	✓	pass@32
2	Goedel-Prover-V2	43	✓	pass@32
3	DeepSeek-Prover-V2	47	✓	pass@1024
3	DeepSeek-Prover-V2	22	✓	pass@32
4	DSP+	23	✓	pass@128
5	Bourbaki	14	✓	pass@512
6	Kimina-Prover-7B-Distill	10	✓	pass@192
7	Self-play Theorem Prover	8	✓	pass@3200
8	Goedel-Prover-SFT	7	✓	pass@512
9	ABEL	7	✗	pass@596

*Seed Prover (Chen et al., 2025), successfully solved 331 problems on PutnamBench. However, the prover is closed-source, and the computational budget at test time remains unclear.

PutnamBench: restart sampling reaches the strongest open-source result. On PutnamBench (Table 2), the comparison is more nuanced. Indeed, self-correction is more sample-efficient at small budgets: Goedel-Prover-V2 with self-correction solves 57 problems at pass@32, compared with Pythagoras-Prover's 48. However, Pythagoras-Prover uses independent *restart* sampling, generating fresh complete proofs and verifying each with Lean. This strategy scales well with the sampling budget: Pythagoras-Prover solves 59 problems at pass@64 and 93 at pass@2048, achieving the *strongest open-source* result on the leaderboard. This exceeds Goedel-Prover-V2's 86 solved problems at pass@184 with self-correction by 7 problems, and nearly doubles DeepSeek-Prover-V2's 47 at pass@1024. This suggests that, although self-correction can be effective at low budgets, it may become brittle when the initial proof attempt contains an early logical error, since subsequent correction rounds often inherit the same mistake and fail to recover (Appendix E). Restart sampling avoids this failure mode by starting each attempt from scratch. As we show next, it is also competitive in terms of *effective* decoding compute.

Raw generated-token counts do not fully capture the decoding cost of self-correction. With KV caching, each newly generated token still attends to the entire prefix available at that step. Hence, under dense attention the work of generating a tokens from a context of length m grows super-linearly. To capture this effect, we define the *effective token complexity*, a worst-case proxy for cumulative attention work:

$$\text{ETC}(m, a) = ma + \frac{a(a+1)}{2},$$

where ma is the cost of attending to the fixed input at every step and $a(a+1)/2$ the cost of the growing generated prefix. ETC counts cumulative query–key interaction under an idealised dense-attention model; it is not a wall-clock measurement, and Appendix F states the assumptions and limitations in full. We note that ETC is size-agnostic: it counts query–key interactions without reference to model width, and so neither credits nor penalises Pythagoras-Prover for its smaller parameter count. We therefore do not read the matched-ETC comparison as a model-size efficiency result; it reflects only the difference in how much context each attempt conditions on: a short prompt for restart sampling versus long accumulated histories for self-correction. Self-correction and restarting differ sharply under this measure: later self-correction rounds condition on long accumulated contexts, whereas each restart conditions only on a short prompt. Table 3 reports the relevant token statistics. Goedel-Prover-V2 runs three self-correction rounds at pass@184, with generation lengths of 18.4K, 21.3K, and 23.0K and roughly 15K of additional proof context across rounds two

Table 3: Average input and generated token counts used for the effective token complexity (ETC) estimate. Goedel-Prover decodes three self-correction rounds per attempt; Pythagoras-Prover draws independent restarts from a short input context.

Method	Pass@	Input context (tokens)	Avg. generated tokens
Goedel-Prover, round 1	184	284.88	18,367.83
Goedel-Prover, round 2	184	7,838.74	21,638.70
Goedel-Prover, round 3	184	8,309.06	23,835.80
Pythagoras-Prover restart	1024	284.88	18,741.80

and three, giving an estimated ETC $\approx 1.95 \times 10^{11}$ (full derivation in Appendix F). Pythagoras-Prover with 1024 independent restarts conditioned on a short (≈ 285-token) prompt with ≈ 18.7K generated tokens each, for ETC $\approx 1.85 \times 10^{11}$. At comparable ETC, Pythagoras-Prover solves 88 problems versus Goedel-Prover-V2's 86, so restart sampling matches or improves on self-correction without incurring the decoding cost of long correction histories.

Pythagoras-Prover is robust under statement-level perturbation. To probe robustness, we re-evaluate DeepSeek-Prover-V2-671B, Goedel-Prover-V2-8B/32B, and Pythagoras-Prover-4B/32B on MiniF2F-ALF, applying our pass criterion uniformly. Figure 4 shows that every model loses accuracy relative to MiniF2F, confirming that ALF mutation induces a non-trivial distribution shift. Pythagoras-Prover-32B retains the highest absolute pass rate of any evaluated model (85.0%); Pythagoras-Prover-4B (83.2%) is almost on par with the $8\times$ larger Goedel-Prover-V2-32B (83.6%) and degrades less under perturbation than that model does (2.9 vs. 4.5 points). Since our training corpus is itself ALF-augmented (§2.3), this is the empirical signature we would expect: models trained on ALF mutations should retain accuracy under ALF-mutated test data more readily than models that have not seen this kind of structural variation, and the robustness gap we observe relative to Goedel-Prover-V2 is consistent with this prediction. MiniF2F-ALF therefore plays two roles simultaneously: it acts as a sharper stress test than the saturated original split, preserving the same problem families while exposing failures under nearby formal variants; and it probes whether the augmentation strategy used during training transfers to the evaluation side. Under both readings, these

Figure 4: Performance of current state-of-the-art provers on MiniF2F-ALF. As MiniF2F-ALF is introduced in this work, all results are evaluated by us under a unified setup.

results do not rule out high-level theorem-family overlap, but they suggest that Pythagoras-Prover is less sensitive than the evaluated baselines to surface-level changes in MiniF2F statements.

Pythagoras-Prover-Diffusion: the corpus transfers across decoding regimes. We additionally train Pythagoras-Prover-Diffusion on the same self-distillation corpus (§2.3) to test whether the data transfers across decoding regimes. To our knowledge, Pythagoras-Prover-Diffusion is the first viable diffusion-based theorem prover; Figure 5 accordingly establishes an initial baseline for this regime. At pass@32 on MiniF2F-Test, Pythagoras-Prover-Diffusion-4B attains 63.25% with a block size of 32, demonstrating that diffusion-style iterative refinement is a viable decoding strategy for Lean proof generation; it trails the autoregressive Pythagoras-Prover-4B (86.1%) by roughly 23 points. We attribute this gap to three constraints that together govern diffusion training for formal mathematics: (i) the random-masking objective, which provides a sparser supervisory signal than next-token prediction; (ii) the limited stable context length of current diffusion language models (Ye et al., 2025; Leang et al., 2026a; Nie et al., 2025) and (iii) the scarcity of diffusion-suitable Lean training data that remain informative while fitting these context limits. We address the first via tactic-based masking (§2.4) and the third via the ALF self-distillation corpus (§2.3); the second remains binding. Under the autoregressive objective, Pythagoras-Prover-4B converges stably at the 8,192-token context used throughout this work, whereas the same setting destabilises diffusion training, producing sustained high gradient norms well

past warm-up (Figure 10); reducing the context budget to 4,096 tokens recovers stable convergence. To isolate this effect, we re-train the autoregressive Pythagoras-Prover-4B at the matched 4,096-token context and observe a large performance drop, indicating that a clear bottleneck is the *context length forced by the diffusion regime.*

A residual gap in favour of the autoregressive variant remains, which we attribute to the relative maturity of autoregressive foundation models: the Qwen backbone has been pretrained and post-trained far more extensively under the AR objective than under any diffusion objective, so the AR initialisation we fine-tune from is itself a stronger prior for Lean than its diffusion counterpart. Since competitive provers rely on test-time scaling (Chen et al., 2025; Lin et al., 2026; Varambally et al., 2026), where long reasoning chains routinely exceeding 4,096 tokens are essential to competitive pass rates, the context limit binds tightly today and caps the proofs Pythagoras-Prover-Diffusion can produce. We therefore present these results as an existence proof rather than a finalised performance number: Pythagoras-Prover-Diffusion is, to our knowledge, the first demonstration that a diffusion language model can be trained from our corpus to verifiably solve Lean theorems at non-trivial rates. Our belief

Figure 5: Comparison on the MiniF2F benchmark. * denotes the setting where training tokens are restricted to 4096 and evaluation is performed solely at 8192 tokens.

is that given long enough context window, diffusion models have the potential to capture long-range dependencies that exist in mathematical formal statements and proofs, ranging from simple syntactic dependencies such as parenthetical agreement to more complex dependencies such as logical dependencies between clauses. Diffusion models enable random access to token generation during decoding, which can potentially build a proof section by section while following dependency relations, rather than as a linear sequence of tokens.

5 Analysis

In this section, we provide a comprehensive analysis of the dataset decomposition (§5.1), followed by a scaling study on MiniF2F (§5.2). We then examine per-instance behaviour on MiniF2F and MiniF2F-ALF (§5.3), and conclude with a comparison between diffusion and autoregressive provers (§5.4).

5.1 Dataset Decomposition

We present a detailed analysis of the Lean-verified seed corpus underlying our training pipeline. The seed is constructed in three difficulty tiers (§2.1), produced by two complementary mechanisms: an initial autoformalisation pass on natural-language problems from existing mathematical-reasoning datasets, which yields the medium and hard tiers (§2.1.1, §2.1.2); and a rubric-guided distillation stage (§2.1.1) that simplifies failed medium instances to produce the easy tier. The ALF augmentation of §2.3 is layered on top of this seed and is treated separately.

5.1.1 The Easy and Medium Tiers

Seed verification (Medium). The seed collection from DART-Math-Hard, OpenR1-Math, and DeepScaleR yields 852,641 instances, of which 239,824 (28.1%) are verified by the Lean type-checker and 612,817 (71.9%) are rejected, as shown by the *Seed* bar in Figure 6a. DART-Math-Hard contributes the majority of verified proofs (199,452; 83.2% of all verified seeds), reflecting both its larger scale and its emphasis on competition-style problems that tend to be more amenable to automated formalisation. OpenR1-Math and DeepScaleR contribute 28,530 (11.9%) and 11,842 (4.9%) respectively. The substantial gap between DART-Math-Hard and the remaining sources motivates the rubric-guided distillation stage below, which targets the harder instances that initial proof synthesis could not resolve.

Error analysis and rubric-guided synthesis. We categorise every type-checker failure on the 612,817 rejected seeds into the seven error classes of §2.1.1; Figure 6b reports the distribution. The dominant failure modes are tactic failures (30.0%, concentrated in `linarith`, `simp`, `ring`, and `omega`), unsolved goals (14.7%),

(a) Accepted and rejected instances across seed, synthetic, and combined data.

(b) Distribution of error categories for rejected pass@2 attempts.

Figure 6: Data filtering and error analysis. Left: accepted and rejected instances across data sources. Right: distribution of error categories among rejected attempts.

invalid projection/field errors (15.2%), and type mismatches (11.6%, typically between $\mathbb{N}$ and $\mathbb{Z}$ or related subtypes); unknown-identifier (10.8%), failed-to-synthesise (8.0%), and a long tail of miscellaneous errors (9.7%) account for the remainder. As these categories are not mutually exclusive at the instance level, our rubric addresses each class with targeted simplification rather than a single monolithic correction. From the rejected pool we retain 258,648 instances with actionable error signatures and have Qwen3-30B and Qwen3-235B each produce $n{=}2$ simplified question variants. After near-duplicate filtering, the two models retain $198,641$ and $132,428$ instances respectively, whose union of $331,069$ forms the easy synthetic pool.

Synthetic verification (Easy) and final composition. As shown by the *Synthetic* bar in Figure 6a, of the 331,069 candidates entering Lean verification, 262,247 (79.2%) pass and 68,822 (20.8%) are rejected, a 51.1-point absolute gain over the seed verification rate (28.1%) that is consistent with the rubric's intent: each easy variant isolates the single manipulation responsible for an original failure and is therefore far more amenable to automated proof synthesis. Combined with the seed corpus, the easy/medium dataset comprises $2.04M$ instances with 502,071 verified proofs. Synthetic augmentation alone contributes 262,247 verified instances on top of the 239,824 seed-verified instances, approximately a 2x increase in verified training data, obtained without any additional human annotation.

5.1.2 The Hard Tier

The hard tier comprises $328,966$ instances drawn from the hardest subset of our seed sources. Unlike the easy and medium tiers, we do *not* apply rubric-guided synthesis here, since the hardest problems admit no faithful simplification. We instead retain the standard generate-and-verify pipeline and raise the per-problem sampling budget to $n{=}4$ to compensate for the increased difficulty, yielding approximately 1.32M candidate instances before Lean filtering. After Lean verification with $n{=}4$ per instance, $338,683$ instances (25.74%) remain. We read this as evidence that the larger sampling budget offsets the difficulty gap, yielding a hard-tier corpus of comparable density without resorting to simplifications that would alter the underlying problems.

5.2 Scaling Analysis

Figure 7 traces the scaling behaviour of Pythagoras-Prover (4B and 32B) across budgets $N \in \{32, \dots, 2048\}$ against Goedel-Prover-V2 (8B and 32B, with and without self-correction) and DeepSeek-Prover-V2 (7B and 671B). The advantage is consistent rather than budget-specific. Among methods without self-correction,

Figure 8: Per-pair outcomes across MiniF2F-Test and its MiniF2F-ALF mutation. ■: both solved; ■: both failed; ■: MiniF2F-Test solved, MiniF2F-ALF failed; ■: MiniF2F-ALF solved, MiniF2F-Test failed.

Pythagoras-Prover-32B leads at every budget and reaches 93.03% at pass@2048; it crosses above the self-correction-augmented Goedel-Prover-V2-32B from roughly pass@256 onwards, indicating that the proof-search behaviour internalised during training substitutes for iterative verifier-guided correction. Pythagoras-Prover-4B is the more striking case: it surpasses DeepSeek-Prover-V2-671B at every shared budget despite being roughly 167× smaller, reaching 89.8% at pass@2048, which exceeds DeepSeek-Prover-V2-671B's pass@8192 result (88.9%), and it tracks or exceeds the twice-larger Goedel-Prover-V2-8B across the full range.

The shape of both curves, high accuracy already at small N with shallow slopes thereafter, shows that Pythagoras-Prover reaches competitive accuracy with far fewer samples than the baselines, which is the property most relevant to compute-constrained deployment. These results indicate that Pythagoras-Prover efficiently internalises proof-search behaviour during training, requiring substantially fewer inference samples to reach competitive accuracy. This is most striking for Pythagoras-Prover-4B: despite its compact size, it surpasses DeepSeek-Prover-V2-671B across every budget examined throughout the sampling range. Such behaviour highlights that the proposed training recipe transfers cleanly to the small-model regime, yielding a prover whose accuracy–compute profile is well suited to memory- or latency-constrained deployment where billion-scale baselines

Figure 7: Scaling behaviour on MiniF2F test split. We compare Pythagoras-Prover with Goedel-Prover-v2, with and without self-correction, and DeepSeek-Prover-v2.

are impractical. The complementary strength of Pythagoras-Prover-32B at the upper end of the Pareto frontier confirms that the same recipe scales upward without modification.

5.3 Analysis towards MiniF2F

The headline pass rates of §4 already suggest that original MiniF2F is approaching saturation under current Lean provers; the clearer indicator is the size and composition of the residual failure set. Taking Pythagoras-Prover-4B, Pythagoras-Prover-32B, Goedel-Prover-V2-8B, and Goedel-Prover-V2-32B[2] as a representative panel, (83.20%) of original MiniF2F problems are solved by *all four* models, leaving only 41/244 (16.80%)

---

[2]Goedel-Prover-V2 outcomes throughout this analysis are obtained by our own replication and may differ slightly from those reported by Lin et al. (2026).

on which at least one system fails and 22/244 (9.02%) on which every system fails. On the bulk of the benchmark, modern provers can no longer be separated; what remains is a small, concentrated tail. That tail is domain-skewed (Figure 9): among at-least-one-wrong instances, AMC accounts for 34.15% and IMO for 31.71%, and the all-model-wrong subset is more lopsided still, with IMO contributing 50.00% and AMC a further 27.27%. Original MiniF2F thus probes a narrow, familiar residual rather than broad reasoning robustness.

MiniF2F-ALF reopens the benchmark and diversifies the failures. MiniF2F-ALF holds each problem family fixed and asks whether models remain correct under controlled mutations of the same statement. Under this evaluation the all-model failure rate rises from 9.02% on the original to 13.93% (68/488), and the at-least-one-wrong set expands to 18.24% (89/488). Critically, the failures *diversify* rather than merely scale: alongside AMC (30.34%) and IMO (24.72%), MathD jumps to 20.22%, with Algebra (7.87%), Number Theory (6.74%), Induction (5.62%), and AIME (4.49%) all carrying non-trivial mass. Mutation therefore surfaces brittleness in categories that should not be difficult under robust reasoning but that the saturated original benchmark is too easy to expose. As the same ALF operator drives both training augmentation (§2.3) and these test mutations, the redistribution is a sharp diagnostic of where structural generalisation breaks down even in well-trained provers.

Figure 9: Domain composition of the at-least-one-model-wrong set on original MiniF2F.

Mutation makes strong systems more distinguishable. The same effect appears in head-to-head comparisons. On original MiniF2F the systems rarely disagree: Pythagoras-Prover-4B solves 7 problems that Goedel-Prover-V2-8B misses while Goedel solves none that Pythagoras-Prover-4B misses, and Pythagoras-Prover-32B solves 8 missed by Goedel-Prover-V2-32B against only 1 in return. Under ALF the systems disagree on far more instances: Pythagoras-Prover-4B solves 6 mutated instances missed by Goedel-Prover-V2-8B with Goedel solving 3 in return (9 disagreements versus 7 on the original), and Pythagoras-Prover-32B solves 12 missed by Goedel-Prover-V2-32B against 5 (17 versus 9). Pythagoras-Prover remains favoured in both directions at both scales, but the central point is diagnostic rather than directional: mutation roughly doubles the number of instances on which strong systems can be told apart, recovering discriminative power that the saturated original benchmark has lost. The per-problem transition in Figure 8 makes this concrete: the orange region (solved on the original but failed after mutation) isolates exactly the brittleness that high MiniF2F pass rates obscure.

5.4 Compute Efficiency: Pythagoras-Prover versus Pythagoras-Prover-Diffusion

We compare Pythagoras-Prover-4B and Pythagoras-Prover-Diffusion-4B under a matched evaluation setting on MiniF2F pass@32: a single 8× H100 node, batch size 4, and an identical harness. The two systems are trained on the same self-distillation corpus (§2.3) and differ only in decoding regime, so the comparison isolates how the same data behaves under autoregressive versus diffusion sampling. On raw accuracy the autoregressive model is clearly ahead, 86.1% versus 63.3%, a gap of 22.7 points. This comparison, however, counts only per-attempt success and ignores the very different cost of producing each attempt. To isolate the context length from architectural capability, we re-train Pythagoras-Prover-4B at the same 4,096-token context used for Pythagoras-Prover-Diffusion-4B and evaluate both models at 8,192 tokens (Figure 5). Under this matched setting the gap shrinks to 11.4% (74.6% vs. 63.2%), roughly half the 22.7% gap observed under mismatched contexts, indicating that context length explains a substantial share of the raw disparity while a smaller architectural gap remains.

Under the harness above, the two systems sustain average generation throughput, calculated as tokens/sec (TPS): $\text{TPS}_{\text{AR}} = 4.10$ and $\text{TPS}_{\text{Diff}} = 10.56$ output tokens per second per GPU worker, so the diffusion sampler is 2.58× faster. The asymmetry is structural: autoregressive decoding is strictly sequential and becomes expensive on the long completions permitted by `max_new_tokens`= 30,000, whereas the diffusion

sampler uses a fixed denoising budget with block-parallel generation and sustains markedly higher throughput on the same hardware.

To weigh accuracy against this cost, we report a throughput-weighted score: $S = \text{accuracy} \times \text{TPS}$, which is proportional to solved proofs per GPU-second *when the two systems generate a comparable number of tokens per attempt.* This gives $S_{\text{AR}} = 0.8607 \times 4.10 = 3.53$ and $S_{\text{Diff}} = 0.6325 \times 10.56 = 6.68$, a $1.89\times$ advantage for the diffusion sampler under this proxy. We read S cautiously: it is a coarse measure whose value at this operating point is dominated by throughput rather than accuracy, so it tracks compute efficiency more than absolute proving capability.

The substantive claim is therefore more limited than the score alone would suggest. For applications that prize per-attempt reliability, the 22.7-point accuracy gap is decisive and the autoregressive model is preferable. Where throughput or wall-clock latency is the binding constraint, however, Pythagoras-Prover-Diffusion is the more compute-efficient option at equal hardware, delivering more verified proofs per GPU-second, and it does so as a first-generation, context-limited prover (§2.4); we expect this efficiency margin to grow as stable diffusion context lengths increase. We currently read Pythagoras-Prover-Diffusion as occupying the throughput side of an accuracy–throughput frontier traced by the same training corpus, rather than as competing on the accuracy frontier itself.

6 Related Work

LLM reasoning. LLM reasoning abilities have advanced significantly on complex mathematical reasoning tasks (Llama Team, 2024), particularly through chain-of-thought (CoT) reasoning (Wei et al., 2022). Large reasoning models (LRMs) (Guo et al., 2025; Qwen Team et al., 2025; Gemma Team, 2025) instead tackle complex problems by generating long CoT traces, and are further enhanced through techniques such as confidence selection (Leang et al., 2026b), iterative refinement (Snell et al., 2025), multi-path exploration (Guan et al., 2025) and others. It is also well established that test-time scaling improves performance in both general reasoning (Muennighoff et al., 2025) and formal reasoning (Varambally et al., 2026). More recently, diffusion models have proven highly capable on mathematical and coding tasks (Bie et al., 2026; Li et al., 2026; Leang et al., 2026a); given this strength, extending diffusion models to formal proving is a natural fit.

Formal theorem proving and autoformalisation. Distinct from general informal reasoning, formal reasoning has emerged as a promising direction for grounding LLM reasoning within formal proofs (Leang et al., 2025b; Zhang et al., 2025b;c). Several works advance formal reasoning (Xin et al., 2024; Ji et al., 2025; Zhang et al., 2025a; Lin et al., 2025b; Xin et al., 2025) through methods such as Monte Carlo Tree Search or breadth-first search, exploring multiple proof trajectories and iteratively assembling valid proofs to improve correctness. There is also recent work that applies formal reasoning beyond mathematics (Meadows et al., 2026; Xu et al., 2026). Recently, Seed-Prover (Chen et al., 2025) uses techniques such as extensive test-time search and refinement to attain IMO medal-level performance; however, such systems rely on either large-scale training over very large base models or substantially higher computational overhead (Chen et al., 2025). Other lines of work explore bootstrapping (Lin et al., 2025a) and self-training (Dong & Ma, 2025). AlphaProof (Hubert et al., 2025) introduces a mutation-based augmentation strategy to mitigate data scarcity in formal theorem proving, but the approach is compute-intensive: each candidate mutation requires Gemini (Gemini Team et al., 2025) to generate an accompanying proof and the Lean kernel to cross-check it before the variant can enter the training corpus. ALF removes this per-mutation overhead by operating at the statement level alone, retaining mutations on the basis of structural validity rather than verified proofs. Pythagoras-Prover aims to mitigate these issues by developing small models without large computational cost, while also addressing the data scarcity that currently bottlenecks formal proving.

7 Limitations and Future Work

While our work makes several contributions, a number of natural extensions remain. (1) *Diffusion-based formal proving.* Although Pythagoras-Prover-Diffusion currently trails its autoregressive counterpart, we believe diffusion models represent a promising research direction due to the mechanism of iterative refinement, and a meaningful architectural shift for LLM reasoning. Scaling the diffusion regime to longer effective

contexts, and hybridising parallel diffusion refinement with autoregressive verification, are natural next steps. (2) *Richer mutation operators.* Our data pipeline uses five mutation operators, which already yields a substantial diagnostic uplift on MiniF2F-ALF. We believe mutation is an efficient route to generating synthetic formal data, and that a broader operator family, including type-driven, lemma-graph, and proof-trace mutations, could further widen the failure surface that future provers must handle. (3) *Beyond MiniF2F.* Our analysis indicates that MiniF2F is approaching saturation under contemporary Lean provers. Existing alternative benchmarks offer only partial substitutes: many are calibrated to a difficulty regime in which strong open-source language models register pass rates in the low single digits, while others have already approached saturation under current systems — in either case providing limited resolution for distinguishing among the strongest provers. We position MiniF2F-ALF as a stronger drop-in variant within the MiniF2F family, but a broader community effort is needed to construct evaluation suites with controlled difficulty stratification across theorem-proving regimes. (4) *Attribution of modest RL gains.* In §2.2 we attribute the modest gains from RL over the curriculum-SFT model to the policy already internalising strong proof-search behaviour before RL. We acknowledge this is not the only plausible explanation: the sparsity of the binary pass/fail reward signal under GRPO is a complementary factor, since a single compile-or-not outcome provides limited gradient signal on long formal proofs. Disentangling these two effects, for instance through denser, process-level reward signals, is a promising direction for future work.

8 Conclusions

We introduced Pythagoras-Prover, a compute-efficient family of open-source Lean 4 theorem provers spanning two generation paradigms: autoregressive provers at 4B and 32B parameters, and Pythagoras-Prover-Diffusion-4B, the first proof-of-concept diffusion-based theorem-proving model for Lean. The results show that strong formal proving need not rely exclusively on frontier-scale models: Pythagoras-Prover-4B outperforms a 671B-parameter prover on MiniF2F-Test despite being roughly $167\times$ smaller, while Pythagoras-Prover-32B achieves state-of-the-art performance on MiniF2F-Test and the strongest open-source result on PutnamBench. Pythagoras-Prover-Diffusion-4B shows that Lean proof generation is possible under a diffusion decoding regime, opening a complementary direction in which theorem provers can be compared not only by accuracy, but also by throughput and proofs per GPU-second.

The main driver of these results is a staged compute-frugal Lean data pipeline. Starting from a Lean-verified corpus we extend it with additional verified instances, and stratify it into easy, medium, and hard problems, which we use to train the models with a curriculum that exposes models progressively to more difficult proof tasks. We then introduce *Augmented Lean Formalisation* (ALF), a structured mutation scheme that expands the verified corpus into diverse formal variants using lightweight sanity checks rather than per-instance Lean verification. The resulting variants serve both as self-distillation data for training and as the basis for *MiniF2F-ALF*, a perturbation-based companion benchmark for evaluating robustness beyond exact benchmark memorisation. The degradation of contemporary provers on MiniF2F-ALF suggests that high accuracy on MiniF2F-Test does not yet imply robust transfer to structured formal variants. Together with parameter-efficient supervised fine-tuning, dynamic proof-reasoning filtering under an 8K context budget, self-distillation, and reinforcement learning from Lean verification, this data pipeline yields strong performance under practical compute budgets.

Overall, our results support the central premise of the paper: careful data construction and efficient training can substitute, in part, for raw model scale in Lean theorem proving.

References

Alon Albalak, Duy Phung, Nathan Lile, Rafael Rafailov, Kanishk Gandhi, Louis Castricato, Anikait Singh, Chase Blagden, Violet Xiang, Dakota Mahan, and Nick Haber. Big-Math: A Large-Scale, High-Quality Math Dataset for Reinforcement Learning in Language Models, 2025. URL https://arxiv.org/abs/2502.17387.

Anthropic. System Card: Claude Opus 4.5. https://anthropic.com/claude-opus-4-5-system-card, 2025.

Anthropic. System Card: Claude Opus 4.6. https://anthropic.com/claude-opus-4-6-system-card, 2026.

Marianne Arriola, Subham Sekhar Sahoo, Aaron Gokaslan, Zhihan Yang, Zhixuan Qi, Jiaqi Han, Justin T Chiu, and Volodymyr Kuleshov. Block Diffusion: Interpolating Between Autoregressive and Diffusion Language Models. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=tyEyYT267x.

Tiwei Bie, Maosong Cao, Xiang Cao, Bingsen Chen, Fuyuan Chen, Kun Chen, Lun Du, Daozhuo Feng, Haibo Feng, Mingliang Gong, Zhuocheng Gong, Yanmei Gu, Jian Guan, Kaiyuan Guan, Hongliang He, Zenan Huang, Juyong Jiang, Zhonghui Jiang, Zhenzhong Lan, Chengxi Li, Jianguo Li, Zehuan Li, Huabin Liu, Lin Liu, Guoshan Lu, Yuan Lu, Yuxin Ma, Xingyu Mou, Zhenxuan Pan, Kaida Qiu, Yuji Ren, Jianfeng Tan, Yiding Tian, Zian Wang, Lanning Wei, Tao Wu, Yipeng Xing, Wentao Ye, Liangyu Zha, Tianze Zhang, Xiaolu Zhang, Junbo Zhao, Da Zheng, Hao Zhong, Wanli Zhong, Jun Zhou, Junlin Zhou, Liwang Zhu, Muzhi Zhu, and Yihong Zhuang. LLaDA2.1: Speeding Up Text Diffusion via Token Editing, 2026. URL https://arxiv.org/abs/2602.08676.

Luoxin Chen, Jinming Gu, Liankai Huang, Wenhao Huang, Zhicheng Jiang, Allan Jie, Xiaoran Jin, Xing Jin, Chenggang Li, Kaijing Ma, Cheng Ren, Jiawei Shen, Wenlei Shi, Tong Sun, He Sun, Jiahui Wang, Siran Wang, Zhihong Wang, Chenrui Wei, Shufa Wei, Yonghui Wu, Yuchen Wu, Yihang Xia, Huajian Xin, Fan Yang, Huaiyuan Ying, Hongyi Yuan, Zheng Yuan, Tianyang Zhan, Chi Zhang, Yue Zhang, Ge Zhang, Tianyun Zhao, Jianqiu Zhao, Yichi Zhou, and Thomas Hanwen Zhu. Seed-Prover: Deep and Broad Reasoning for Automated Theorem Proving, 2025. URL https://arxiv.org/abs/2507.23726.

Yuri Chervonyi, Trieu H. Trinh, Miroslav Olšák, Xiaomeng Yang, Hoang H. Nguyen, Marcelo Menegali, Junehyuk Jung, Junsu Kim, Vikas Verma, Quoc V. Le, and Thang Luong. Gold-medalist Performance in Solving Olympiad Geometry with AlphaGeometry2. *J. Mach. Learn. Res.*, 26:241:1–241:39, 2025. URL https://jmlr.org/papers/v26/25-1654.html.

Thierry Coquand and Gérard Huet. The Calculus of Constructions. *Information and Computation*, 76(2–3): 95–120, 1988. URL https://doi.org/10.1016/0890-5401(88)90005-3.

Leonardo Mendonça de Moura, Soonho Kong, Jeremy Avigad, Floris van Doorn, and Jakob von Raumer. The Lean Theorem Prover (System Description). In Amy P. Felty and Aart Middeldorp (eds.), *Automated Deduction - CADE-25 - 25th International Conference on Automated Deduction, Berlin, Germany, August 1-7, 2015, Proceedings*, Lecture Notes in Computer Science, pp. 378–388. Springer, 2015. doi: 10.1007/978-3-319-21401-6_26. URL https://doi.org/10.1007/978-3-319-21401-6_26.

Kefan Dong and Tengyu Ma. STP: Self-play LLM Theorem Provers with Iterative Conjecturing and Proving. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, Proceedings of Machine Learning Research. PMLR / OpenReview.net, 2025. URL https://proceedings.mlr.press/v267/dong25h.html.

Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. The Faiss Library. *IEEE Transactions on Big Data*, 12 (2):346–361, 2026. doi: 10.1109/TBDATA.2025.3618474. URL https://doi.org/10.1109/TBDATA.2025.3618474.

Bofei Gao, Feifan Song, Zhe Yang, Zefan Cai, Yibo Miao, Qingxiu Dong, Lei Li, Chenghao Ma, Liang Chen, Runxin Xu, Zhengyang Tang, Benyou Wang, Daoguang Zan, Shanghaoran Quan, Ge Zhang, Lei Sha, Yichang Zhang, Xuancheng Ren, Tianyu Liu, and Baobao Chang. Omni-MATH: A Universal Olympiad Level Mathematic Benchmark for Large Language Models. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=yaqPf0KAlN.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: A Family of Highly Capable Multimodal Models, 2025. URL https://arxiv.org/abs/2312.11805.

Gemma Team. Gemma 3 Technical Report, 2025. URL https://arxiv.org/abs/2503.19786.

Xinyu Guan, Li Lyna Zhang, Yifei Liu, Ning Shang, Youran Sun, Yi Zhu, Fan Yang, and Mao Yang. rStar-Math: Small LLMs Can Master Math Reasoning with Self-Evolved Deep Thinking. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, Proceedings of Machine Learning Research. PMLR / OpenReview.net, 2025. URL https://proceedings.mlr.press/v267/guan25f.html.

Daya Guo, Dejian Yang, Haowei Zhang, et al. Deepseek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *Nature*, 645:633–638, 2025. doi: 10.1038/s41586-025-09422-z.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring Mathematical Problem Solving With the MATH Dataset. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021. URL https://openreview.net/forum?id=7Bywt2mQsCe.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Thomas Hubert, Rishi Mehta, Laurent Sartran, Miklós Z. Horváth, Goran Žužić, Eric Wieser, Aja Huang, Julian Schrittwieser, Yannick Schroecker, Hussain Masoom, Ottavia Bertolli, Tom Zahavy, Amol Mandhane, Jessica Yung, Iuliya Beloshapka, Borja Ibarz, Vivek Veeriah, Lei Yu, Oliver Nash, Paul Lezeau, Salvatore Mercuri, Calle Sönne, Bhavik Mehta, Alex Davies, Daniel Zheng, Fabian Pedregosa, Yin Li, Ingrid von Glehn, Mark Rowland, Samuel Albanie, Ameya Velingker, Simon Schmitt, Edward Lockhart, Henryk Michalewski, Nicolas Sonnerat, Demis Hassabis, Pushmeet Kohli, and David Silver. Olympiad-Level Formal Mathematical Reasoning with Reinforcement Learning. *Nature*, 2025. URL https://www.nature.com/articles/s41586-025-09833-y.

Hugging Face. Open R1: A fully open reproduction of DeepSeek-R1, January 2025. URL https://github.com/huggingface/open-r1.

Xingguang Ji, Yahui Liu, Qi Wang, Jingyuan Zhang, Yang Yue, Rui Shi, Chenxi Sun, Fuzheng Zhang, Guorui Zhou, and Kun Gai. Leanabell-Prover-V2: Verifier-integrated Reasoning for Formal Theorem Proving via Reinforcement Learning, 2025. URL https://arxiv.org/abs/2507.08649.

Minseo Kim, Coleman Hooper, Aditya Tomar, Chenfeng Xu, Mehrdad Farajtabar, Michael W. Mahoney, Kurt Keutzer, and Amir Gholami. Beyond Next-Token Prediction: A Performance Characterization of Diffusion versus Autoregressive Language Models, 2025a. URL https://arxiv.org/abs/2510.04146.

Seungone Kim, Juyoung Suk, Xiang Yue, Vijay Viswanathan, Seongyun Lee, Yizhong Wang, Kiril Gashteovski, Carolin Lawrence, Sean Welleck, and Graham Neubig. Evaluating Language Models as Synthetic Data Generators. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6385–6403, Vienna, Austria, July 2025b. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.320. URL https://aclanthology.org/2025.acl-long.320/.

Joshua Ong Jun Leang, Aryo Pradipta Gema, and Shay B Cohen. CoMAT: Chain of Mathematically Annotated Thought Improves Mathematical Reasoning. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 20245–20274, Suzhou, China, November 2025a. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.1024. URL https://aclanthology.org/2025.emnlp-main.1024/.

Joshua Ong Jun Leang, Giwon Hong, Wenda Li, and Shay B Cohen. Theorem Prover as a Judge for Synthetic Data Generation. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar

(eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 29941–29977, Vienna, Austria, July 2025b. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1448. URL https://aclanthology.org/2025.acl-long.1448/.

Joshua Ong Jun Leang, Yu Zhao, Mihaela Cătălina Stoian, Wenda Li, Shay B. Cohen, and Eleonora Giunchiglia. Can I Have Your Order? Monte-Carlo Tree Search for Slot Filling Ordering in Diffusion Language Models, 2026a. URL https://arxiv.org/abs/2602.12586.

Joshua Ong Jun Leang, Zheng Zhao, Aryo Pradipta Gema, Sohee Yang, Wai-Chung Kwan, Xuanli He, Wenda Li, Pasquale Minervini, Eleonora Giunchiglia, and Shay B. Cohen. PiCSAR: Probabilistic Confidence Selection And Ranking for Reasoning Chains, 2026b. URL https://arxiv.org/abs/2508.21787.

Jia Li, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Huang, Kashif Rasul, Longhui Yu, Albert Q Jiang, Ziju Shen, et al. Numinamath: The largest public dataset in ai4maths with 860k pairs of competition math problems and solutions, 2024. URL https://github.com/project-numina/aimo-progress-prize/blob/main/report/numina_dataset.pdf.

Jia-Nan Li, Jian Guan, Wei Wu, and Chongxuan Li. ReFusion: A Diffusion Large Language Model with Parallel Autoregressive Decoding. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=LBtWaUc7FE.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. Towards General Text Embeddings with Multi-stage Contrastive Learning, 2023. URL https://arxiv.org/abs/2308.03281.

Haohan Lin, Zhiqing Sun, Sean Welleck, and Yiming Yang. Lean-STaR: Learning to Interleave Thinking and Proving. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net, 2025a. URL https://openreview.net/forum?id=SOWZ59UyNc.

Yong Lin, Shange Tang, Bohan Lyu, Jiayun Wu, Hongzhou Lin, Kaiyu Yang, Jia LI, Mengzhou Xia, Danqi Chen, Sanjeev Arora, and Chi Jin. Goedel-Prover: A Frontier Model for Open-Source Automated Theorem Proving. In *Second Conference on Language Modeling*, 2025b. URL https://openreview.net/forum?id=x2y9i2HDjD.

Yong Lin, Shange Tang, Bohan Lyu, Ziran Yang, Jui-Hui Chung, Haoyu Zhao, Lai Jiang, Yihan Geng, Jiawei Ge, Jingruo Sun, Jiayun Wu, Jiri Gesi, Ximing Lu, David Acuna, Kaiyu Yang, Hongzhou Lin, Yejin Choi, Danqi Chen, Sanjeev Arora, and Chi Jin. Goedel-Prover-V2: Scaling Formal Theorem Proving with Scaffolded Data Synthesis and Self-Correction. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=j4COnALrgK.

Llama Team. The Llama 3 Herd of Models, 2024. URL https://arxiv.org/abs/2407.21783.

Michael Luo, Sijun Tan, Justin Wong, Xiaoxiang Shi, William Tang, Manan Roongta, Colin Cai, Jeffrey Luo, Tianjun Zhang, Erran Li, Raluca Ada Popa, and Ion Stoica. DeepScaleR: Surpassing O1-Preview with a 1.5B Model by Scaling RL. https://pretty-radio-b75.notion.site/DeepScaleR-Surpassing-O1-Preview-with-a-1-5B-Model-by-Scaling-RL-19681902c1468005bed8ca303013a4e2, 2025. Notion Blog.

Qing Lyu, Shreya Havaldar, Adam Stein, Li Zhang, Delip Rao, Eric Wong, Marianna Apidianaki, and Chris Callison-Burch. Faithful Chain-of-Thought Reasoning. In Jong C. Park, Yuki Arase, Baotian Hu, Wei Lu, Derry Wijaya, Ayu Purwarianti, and Adila Alfa Krisnadhi (eds.), *Proceedings of the 13th International Joint Conference on Natural Language Processing and the 3rd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 305–329, Nusa Dua, Bali, November 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.ijcnlp-main.20. URL https://aclanthology.org/2023.ijcnlp-main.20/.

Jordan Meadows, Lan Zhang, and Andre Freitas. FormalScience: Scalable Human-in-the-Loop Autoformalisation of Science with Agentic Code Generation in Lean, 2026. URL https://arxiv.org/abs/2604.23002.

Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. GSM-Symbolic: Understanding the Limitations of Mathematical Reasoning in Large Language Models. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net, 2025. URL https://openreview.net/forum?id=AjXkRZIvjB.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. s1: Simple test-time scaling. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 20275–20321, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.1025. URL https://aclanthology.org/2025.emnlp-main.1025/.

Shen Nie, Fengqi Zhu, Zebin You, Xiaolu Zhang, Jingyang Ou, Jun Hu, Jun Zhou, Yankai Lin, Ji-Rong Wen, and Chongxuan LI. Large Language Diffusion Models. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, pp. 50608–50646. Curran Associates, Inc., 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/48b383b24230e0e6e649d9c98dae4d8c-Paper-Conference.pdf.

OpenAI. OpenAI GPT-5 System Card, 2026. URL https://arxiv.org/abs/2601.03267.

OpenAI, Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. GPT-4o System Card, 2024. URL https://arxiv.org/abs/2410.21276.

Lawrence C. Paulson. *Isabelle - A Generic Theorem Prover (with a contribution by T. Nipkow)*, volume 828 of *Lecture Notes in Computer Science*. Springer, 1994. ISBN 3-540-58244-4. doi: 10.1007/BFB0030541. URL https://doi.org/10.1007/BFb0030541.

Penghui Qi, Zichen Liu, Xiangxin Zhou, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Defeating the Training-Inference Mismatch via FP16, 2025. URL https://arxiv.org/abs/2510.26788.

Qwen Team. Qwen3.6-27B: Flagship-Level Coding in a 27B Dense Model, April 2026. URL https://qwen.ai/blog?id=qwen3.6-27b.

Qwen Team, An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, et al. Qwen3 Technical Report, 2025. URL https://arxiv.org/abs/2505.09388.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/a85b405ed65c6477a4fe8302b5e06ce7-Abstract-Conference.html.

Z. Z. Ren, Zhihong Shao, Junxiao Song, Huajian Xin, Haocheng Wang, Wanjia Zhao, Liyue Zhang, Zhe Fu, Qihao Zhu, Dejian Yang, Z. F. Wu, Zhibin Gou, Shirong Ma, Hongxuan Tang, Yuxuan Liu, Wenjun Gao, Daya Guo, and Chong Ruan. DeepSeek-Prover-V2: Advancing Formal Mathematical Reasoning via Reinforcement Learning for Subgoal Decomposition, 2025. URL https://arxiv.org/abs/2504.21801.

Subham Sekhar Sahoo, Marianne Arriola, Yair Schiff, Aaron Gokaslan, Edgar Marroquin, Justin T Chiu, Alexander Rush, and Volodymyr Kuleshov. Simple and Effective Masked Diffusion Language Models. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 130136–130184. Curran Associates, Inc., 2024. doi: 10.52202/079017-4135. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/eb0b13cc515724ab8015bc978fdde0ad-Paper-Conference.pdf.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models, 2024. URL https://arxiv.org/abs/2402.03300.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. HybridFlow: A Flexible and Efficient RLHF Framework. *arXiv preprint arXiv: 2409.19256*, 2024.

Charlie Victor Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling LLM Test-Time Compute Optimally Can be More Effective than Scaling Parameters for Reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=4FWAwZtd2n.

Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. DART-Math: Difficulty-Aware Rejection Tuning for Mathematical Problem-Solving. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 7821–7846. Curran Associates, Inc., 2024. doi: 10.52202/079017-0251. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/0ef1afa0daa888d695dcd5e9513bafa3-Paper-Conference.pdf.

George Tsoukalas, Jasper Lee, John Jennings, Jimmy Xin, Michelle Ding, Michael Jennings, Amitayush Thakur, and Swarat Chaudhuri. PutnamBench: Evaluating Neural Theorem-Provers on the Putnam Mathematical Competition. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 11545–11569. Curran Associates, Inc., 2024. doi: 10.52202/079017-0368. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/1582eaf9e0cf349e1e5a6ee453100aa1-Paper-Datasets_and_Benchmarks_Track.pdf.

Sumanth Varambally, Thomas Voice, Yanchao Sun, Zhifeng Chen, Rose Yu, and Ke Ye. Hilbert: Recursively Building Formal Proofs with Informal Reasoning, 2026. URL https://arxiv.org/abs/2509.22819.

Haiming Wang, Mert Unsal, Xiaohan Lin, Mantas Baksys, Junqi Liu, Marco Dos Santos, Flood Sung, Marina Vinyes, Zhenzhe Ying, Zekai Zhu, Jianqiao Lu, Hugues de Saxcé, Bolton Bailey, Chendong Song, Chenjun Xiao, Dehao Zhang, Ebony Zhang, Frederick Pu, Han Zhu, Jiawei Liu, Jonas Bayer, Julien Michel, Longhui Yu, Léo Dreyfus-Schmidt, Lewis Tunstall, Luigi Pagani, Moreira Machado, Pauline Bourigault, Ran Wang, Stanislas Polu, Thibaut Barroyer, Wen-Ding Li, Yazhe Niu, Yann Fleureau, Yangyang Hu, Zhouliang Yu, Zihan Wang, Zhilin Yang, Zhengying Liu, and Jia Li. Kimina-Prover Preview: Towards Large Formal Reasoning Models with Reinforcement Learning, 2025a. URL https://arxiv.org/abs/2504.11354.

Haiming Wang, Mert Unsal, Xiaohan Lin, Mantas Baksys, Junqi Liu, Marco Dos Santos, Flood Sung, Marina Vinyes, Zhenzhe Ying, Zekai Zhu, et al. Kimina-Prover Preview: Towards Large Formal Reasoning Models with Reinforcement Learning, 2025b. URL https://arxiv.org/abs/2504.11354.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 24824–24837. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/9d5609613524ecf4f15af0f7b31abca4-Paper-Conference.pdf.

Huajian Xin, Daya Guo, Zhihong Shao, Zhizhou Ren, Qihao Zhu, Bo Liu, Chong Ruan, Wenda Li, and Xiaodan Liang. DeepSeek-Prover: Advancing Theorem Proving in LLMs through Large-Scale Synthetic Data, 2024. URL https://arxiv.org/abs/2405.14333.

Ran Xin, Chenguang Xi, Jie Yang, Feng Chen, Hang Wu, Xia Xiao, Yifan Sun, Shen Zheng, and Ming Ding. BFS-Prover: Scalable Best-First Tree Search for LLM-based Automatic Theorem Proving. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pp. 32588–32599. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.acl-long.1565/.

Qiyuan Xu, Xiaokun Luan, Renxi Wang, Joshua Ong Jun Leang, Peixin Wang, Haonan Li, Wenda Li, and Conrad Watt. Neural Theorem Proving for Verification Conditions: A Real-World Benchmark. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=MfDyickxQA.

Jiacheng Ye, Zhihui Xie, Lin Zheng, Jiahui Gao, Zirui Wu, Xin Jiang, Zhenguo Li, and Lingpeng Kong. Dream 7B: Diffusion Large Language Models, 2025. URL https://arxiv.org/abs/2508.15487.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, juncai liu, LingJun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Ru Zhang, Wang Zhang, Hang Zhu, Jinhua Zhu, Jiaze Chen, Jiangjie Chen, Chengyi Wang, Hongli Yu, Yuxuan Song, Xiangpeng Wei, Hao Zhou, Jingjing Liu, Wei-Ying Ma, Ya-Qin Zhang, Lin Yan, Yonghui Wu, and Mingxuan Wang. DAPO: An Open-Source LLM Reinforcement Learning System at Scale. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, pp. 113222–113244. Curran Associates, Inc., 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/a4277440d50f1f15d2cb4c14f7e0c0d2-Paper-Conference.pdf.

Jingyuan Zhang, Qi Wang, Xingguang Ji, Yahui Liu, Yang Yue, Fuzheng Zhang, Di Zhang, Guorui Zhou, and Kun Gai. Leanabell-Prover: Posttraining Scaling in Formal Reasoning, 2025a. URL https://arxiv.org/abs/2504.06122.

Lan Zhang, Marco Valentino, and André Freitas. Autoformalization in the Wild: Assessing LLMs on Real-World Mathematical Definitions. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing, EMNLP 2025, Suzhou, China, November 4-9, 2025*, pp. 1720–1738. Association for Computational Linguistics, 2025b. doi: 10.18653/V1/2025.EMNLP-MAIN.90. URL https://doi.org/10.18653/v1/2025.emnlp-main.90.

Lan Zhang, Marco Valentino, and André Freitas. MASA: LLM-Driven Multi-Agent Systems for Auto-formalization. In Ivan Habernal, Peter Schulam, and Jörg Tiedemann (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing, EMNLP 2025 - System Demonstrations, Suzhou, China, November 4-9, 2025*, pp. 615–624. Association for Computational Linguistics, 2025c. doi: 10.18653/V1/2025.EMNLP-DEMOS.44. URL https://doi.org/10.18653/v1/2025.emnlp-demos.44.

Ruixiang Zhang, Richard He Bai, Huangjie Zheng, Navdeep Jaitly, Ronan Collobert, and Yizhe Zhang. Embarrassingly Simple Self-Distillation Improves Code Generation, 2026. URL https://arxiv.org/abs/2604.01193.

Kunhao Zheng, Jesse Michael Han, and Stanislas Polu. MiniF2F: a cross-system benchmark for formal Olympiad-level mathematics. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=9ZPegFuFTFv.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyan Luo, Zhangchi Feng, and Yongqiang Ma. LlamaFactory: Unified Efficient Fine-Tuning of 100+ Language Models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, Bangkok, Thailand, 2024. Association for Computational Linguistics. URL http://arxiv.org/abs/2403.13372.

Zhanhui Zhou, Lingjie Chen, Hanghang Tong, and Dawn Song. dLLM: Simple Diffusion Language Modeling, 2026. URL https://arxiv.org/abs/2602.22661.

Appendix Contents

A   Additional Details on Synthetic Data Generation

A.1   Rubric Distillation Prompt

For our rubric-based distillation stage, we use the prompt shown below to convert each failed Lean proof attempt into a self-contained synthetic mathematics problem with a step-by-step solution. The prompt instructs the generator to identify the root-cause error, classify it under our extraction rubric, and emit a strictly formatted JSON object containing the synthetic question and its solution.

Prompt: ALF Failure-to-Synthetic-Problem Generation

```
You are an expert mathematician and dataset creator. Your task is to
analyze a failed Lean 4 proof attempt, extract the exact mathematical
context where it failed, generate a WHOLE NEW SIMPLER SYNTHETIC, FULLY
SOLVABLE MATH PROBLEM, and provide its complete step-by-step
mathematical solution.

### CORE OBJECTIVE
Analyze a failed Lean 4 proof to identify the exact mathematical step
where the logic or formalization breaks down. Extract the specific
mathematical parameters, formulas, and premises from that step and the
original theorem statement. Use these extracted details to generate a
SIMPLER, SYNTHETIC, FULLY SOLVABLE MATH PROBLEM in pure natural
language, along with its step-by-step mathematical solution. This must
be a standalone mathematical question that contains all the necessary
numbers and context required to calculate the answer from scratch,
without needing to reference the original Lean code.

### ROOT CAUSE
When multiple errors are present, identify all the error by line
position as the root cause. However, ignore downstream errors that
would resolve once the root cause is fixed.
**Determine Failure Level:**
   - **Formalization error:** Malformed theorem statement (wrong
     types/fields). Target the underlying mathematical
     conceptualization of the claim.
   - **Proof error:** Bug inside the tactic block. Target mathematical
     strategy or logic.

### EXTRACTION RUBRIC (Map Error Category to Conceptual Math)
* **Invalid projection/field:** The proof calls a field that doesn't
  exist for that mathematical object. Extract the actual mathematical
  object and generate a problem that requires calculating or properly
  interacting with its true mathematical properties.
* **Unsolved goals:** Extract the exact remaining goal state and the
  available hypotheses. Turn this exact state into a self-contained
  "Prove that..." or "Calculate..." math problem.
* **Tactic failures (linarith, simp, rewrite, etc.):** Extract the
  specific algebraic equation or inequality that failed to simplify.
  Create a synthetic math problem asking the student to manually
  perform that specific algebraic manipulation or simplification.
* **Type mismatch:** Identify expected vs. actual domains (e.g.,
  integers vs. natural numbers, sets vs. finite collections). Create a
  problem that requires converting or mapping between these specific
  domains using the numbers from the theorem.
* **Failed to synthesize:** Missing mathematical property (e.g.,
  finiteness, decidability). Create a problem asking to prove that the
  specific object in the theorem possesses this required property.
* **Unknown constant/identifier:** The LLM hallucinated a theorem.
  Extract the logical step it was trying to make, and create a math
  problem that requires proving that specific logical step from first
  principles.
* **Other errors:** Extract the technical failure and translate it
  into a logic or calculation problem based on the active variables.

### CONSTRAINTS FOR THE SYNTHETIC QUESTION & SOLUTION
1. **COMPLETELY SELF-CONTAINED & SOLVABLE:** The generated question
   MUST include the actual mathematical values, coordinates, formulas,
   or premises involved in the failed step. (e.g., If the error
   involves Point F, you MUST state the exact coordinates of Point F
   in the question). It must be solvable without looking at the Lean
   code.
2. **PURE MATHEMATICS (NO CODE):** The question and solution MUST NOT
   contain Lean 4 code, tactics (`simp`, `rw`), Lean keywords (`let`,
   `have`), or backticks (` `). Frame it purely as a standard math
   competition or textbook problem.
```

```
3. **NO DIAGNOSTIC OR "WHY" QUESTIONS:** Do not ask "Why did this
   fail?" or "What is the correct logical approach?". Ask direct
   mathematical questions like "Calculate X", "Find Y", or "Prove that
   Z is true given [Premises]."
4. **EXPLICIT STEP-BY-STEP SOLUTION:** You must provide a clear,
   logically sound, step-by-step mathematical solution to the
   synthetic question you just generated.

### EXAMPLES (Bad vs. Good)
- **BAD (Diagnostic/Code-heavy):** "Why does the `intro` tactic fail
  when applied to Point F?"
- **GOOD (Synthetic Math Problem):** "Point A is at (0, 0) and Point B
  is at (8/3, 4). If Point F is defined as the midpoint of segment AB,
  calculate the exact sum of the x and y coordinates of Point F."

- **BAD (Diagnostic/Vague):** "What missing logical step is required
  to prove that this sum is strictly positive?"
- **GOOD (Synthetic Math Problem):** "Given that x > 5 and y = -2,
  prove that the sum of x and y is strictly positive."

---
### BEGIN USER PROMPT
PREVIOUS QUERY
{{QUESTION}}

FORMAL STATEMENT:
```lean4
{{FORMAL_STATEMENT}}

FAILED PROOF:

{{MERGED_PROOF}}
ERROR MESSAGE:
{{ERROR_MESSAGE}}
```

A.2 Similarity Filtering for Intra-corpus Deduplication

For the *easy* tier we deduplicate by semantic content rather than surface form, since paraphrase-level duplicates are common in our problem sources and surface methods (exact-match or normalised edit distance) miss variable-renamed or lightly reworded copies. Each statement is encoded with `Alibaba-NLP/gte-Qwen2-7B-instruct` (Li et al., 2023) into a 3,584-dimensional dense embedding. Embeddings are ℓ_2-normalised so that cosine similarity reduces to an inner product, and indexed with FAISS (Douze et al., 2026) using an inner-product index for efficient k-nearest-neighbour search.

Chunked overlapping search. Exhaustive pairwise comparison across the full easy-tier pool is memory-bound, so we partition the embedded instances into chunks of 5,000 items with a 100-instance overlap between consecutive chunks, and run top-k nearest-neighbour retrieval within each chunk. The overlap guarantees that near-duplicates whose embeddings happen to straddle a chunk boundary are still compared in at least one chunk, preventing duplicates from leaking through partitioning.

Filtering rule. A pair (x_i, x_j) with cosine similarity above τ is treated as a near-duplicate, and the lower-priority member is dropped by source-tier priority (curated problems over autoformalised paraphrases; older sources over newer reformulations). We set $\tau = 0.75$ via a small held-out sweep that balances false-positive removal (distinct problems flagged as duplicates) against false-negative retention (near-duplicates passing through).

A.3 Dataset Decontamination Sweep

Beyond intra-corpus deduplication (Appendix A.2), we run a five-stage decontamination sweep against every benchmark we report on (MiniF2F-Valid, MiniF2F-Test, and PutnamBench); a training instance is discarded if any stage triggers a hit. (i) *Surface-form hashing:* we normalise the natural-language statement (lowercase, collapsed whitespace, stripped punctuation, canonicalised numerals) and the Lean statement (α-renamed binders, comments and formatting removed) and compare MD5 hashes. (ii) *n-gram overlap:* we flag any instance sharing an n-gram with a benchmark item, with $n = 10$ on natural language and $n = 5$ on Lean (the shorter window reflects the lower lexical entropy of formal code). (iii) *Embedding similarity:* surviving

candidates are encoded with `gte-Qwen2-7B-instruct` and indexed in FAISS as in Appendix A.2, and removed if their cosine similarity to any benchmark statement exceeds τ_{decon}. (iv) *Structural equivalence:* we compare α-normalised Lean statement trees and remove any instance that elaborates to the same formal theorem as a benchmark item despite a different surface form. (v) *Proof-template overlap:* as a cheaper alternative to retraining-based checks, we strip variable names and constants from both training and benchmark proofs, normalise the residual tactic skeletons, and flag any training instance whose skeleton is near-identical to that of a benchmark proof, catching cases where a benchmark proof is reproduced up to renaming.

Because MiniF2F-ALF is obtained by mutating MiniF2F-Test, any MiniF2F-Test contamination is also an ALF-seed contamination; we additionally run the first three stages against the 488 mutated ALF statements to catch the residual case where a training instance matches a mutated variant rather than the original. The resulting decontaminated set is used for all supervised fine-tuning, self-distillation, and reinforcement-learning runs reported in this paper.

A.4   ALF Self-Distillation

For our ALF Self-Distillation generation, each mutated statement's formal proof is generated by Pythagoras-Prover-Post-RL teacher at temperature $T = 1.2$ and nucleus top-$p = 0.95$, and the completion is used as a training target. Given the scale (2M instances per model), we omit per-sample Lean verification; Zhang et al. (2026) report that this omission does not materially degrade downstream performance in the coding domain, and Appendix C.2 indicates the same holds for formal proving, with self-distillation contributing consistently on top of the SFT baseline at both 4B and 32B.

A.5   Verification of ALF Synthetic Data

Verifying all 2M ALF self-distilled instances with the Lean compiler is computationally prohibitive. We therefore conduct a random audit: sampling 2,000 retained ALF instances uniformly from the final self-distillation corpus and checking each complete generated theorem, including both the mutated formal statement and its proof, under the same Lean environment used for evaluation. Of these audited instances, 87.8% compile successfully, indicating that the quality of the synthetic data remains high and that exhaustive verification is unnecessary for our purposes. We do, however, verify the formal *statement* alongside the formal proof rather than the proof alone: checking only the proof teaches the model to alter the statement to fit a flawed proof, an effect we observe in practice and find necessary to prevent. Full verification of every instance is left out only on grounds of compute. Inspecting the remaining 12.2% (244 of 2,000) non-compiling instances, we find that the failures are overwhelmingly syntax-level (e.g. minor tactic or bracket errors) rather than reasoning-level: the underlying proof strategy still targets the mutated statement correctly, and closely tracks the reasoning chain of the pre-mutation seed proof, which was itself Lean-verified. This is precisely the distinction between the statement-alignment check and full mathematical correctness: alignment certifies that a plausible, on-topic proof strategy is offered, not that every low-level tactic step type-checks. We therefore expect this residual noise to mostly perturb surface syntax rather than corrupt the reasoning signal used for self-distillation, consistent with self-distillation contributing positively on top of the SFT baseline at the full 2M-instance scale (Appendix C.2).

A.5.1   Why Self-Distillation?

After supervised fine-tuning, Pythagoras-Prover already attains a strong pass rate on MiniF2F-Test (Table 5); the remaining headroom is not a question of base capability but of exposing the model to a wider distribution of proof trajectories. Preference-based post-training is poorly matched to this regime: Direct Preference Optimisation (Rafailov et al., 2023) expects a dense preference signal, but the Lean verifier returns only a sparse binary judgement, and the preference pairs we derived from it proved unstable in our runs. GRPO suffers the same scarcity, yielding only marginal gains because the binary success/fail reward leaves little gradient on the long tail of structurally distinct but equally valid proofs. Self-distillation via ALF sidesteps both issues. It supplies dense, full-trajectory supervision: the teacher emits a complete proof for each mutated statement, rather than a single bit of reward. It *expands* rather than refines the training distribution, drawing formally distinct theorem variants from each seed. Self-distillation is therefore the right tool for this regime:

full proof trajectories are more informative than sparse preference signals, and ALF is the mechanism that turns one seed into many.

A.6 Examples of Pythagoras-Prover-Dataset for Each Difficulty

---

Easy tier example. Synthetic, rubric-simplified algebra problem (rectangle perimeter).

Formal statement

```
import Mathlib
import Aesop

set_option maxHeartbeats 0

open BigOperators Real Nat Topology Rat

/-- Let `a` and `b` be positive real numbers
    such that `b = a + 9` and `a * b = 360`.
    Prove that `2 * (a + b) = 78`. -/
theorem my_algebra_theorem
    (a b : R) (ha : a > 0) (hb : b > 0)
    (h1 : b = a + 9) (h2 : a * b = 360) :
    2 * (a + b) = 78 := by
  sorry
```

Formal proof

```
theorem my_algebra_theorem
    (a b : R) (ha : a > 0) (hb : b > 0)
    (h1 : b = a + 9) (h2 : a * b = 360) :
    2 * (a + b) = 78 := by
  have h3 : a * (a + 9) = 360 := by
    rw [← h1]; exact h2
  have ha15 : a = 15 := by
    nlinarith [sq_nonneg (a - 15), sq_nonneg (a + 24), ha]
  have hb24 : b = 24 := by
    rw [h1, ha15]; norm_num
  rw [ha15, hb24]; norm_num
```

Medium tier example. Autoformalised general-reasoning word problem (camper marshmallow count).

```
import Mathlib
import Aesop

set_option maxHeartbeats 0

open BigOperators Real Nat Topology Rat

/-- At camp Wonka there are 96 campers.
    Two-thirds are boys, one-third are girls.
    50% of the boys and 75% of the girls want
    a marshmallow. How many marshmallows are
    needed in total? -/
theorem my_combinatorics_theorem :
    let total_campers      : N := 96
    let boys               : N := (2 * total_campers) / 3
    let girls              : N := total_campers / 3
    let boys_wanting_toast : N := boys / 2
    let girls_wanting_toast : N := (3 * girls) / 4
    let total_marshmallows : N :=
      boys_wanting_toast + girls_wanting_toast
    total_marshmallows = 56 := by
  sorry
```

```
theorem my_combinatorics_theorem :
    let total_campers      : N := 96
    let boys               : N := (2 * total_campers) / 3
    let girls              : N := total_campers / 3
    let boys_wanting_toast : N := boys / 2
    let girls_wanting_toast : N := (3 * girls) / 4
    let total_marshmallows : N :=
      boys_wanting_toast + girls_wanting_toast
    total_marshmallows = 56 := by
  intro total_campers boys girls
        boys_wanting_toast girls_wanting_toast
        total_marshmallows
  have h_boys : boys = 64 := by
    dsimp [boys, total_campers] <;> norm_num <;> rfl
  have h_girls : girls = 32 := by
    dsimp [girls, total_campers] <;> norm_num <;> rfl
  have h_boys_toast : boys_wanting_toast = 32 := by
    dsimp [boys_wanting_toast, boys, total_campers] at *
    <;> norm_num at * <;> rfl
  have h_girls_toast : girls_wanting_toast = 24 := by
    dsimp [girls_wanting_toast, girls, total_campers] at *
    <;> norm_num at * <;> rfl
  have h_total : total_marshmallows = 56 := by
    dsimp [total_marshmallows,
           boys_wanting_toast, girls_wanting_toast] at *
    <;> norm_num [h_boys_toast, h_girls_toast] at *
    <;> rfl
  exact h_total
```

Hard tier example. Competition-style number theory: smallest prime p such that $p^2 + 144$ is a perfect square.

```
import Mathlib
import Aesop

set_option maxHeartbeats 0

open BigOperators Real Nat Topology Rat

/-- Let `p` be the smallest prime such that
    `p^2 + 144` is also a perfect square.
    Determine the value of `p`. -/
theorem my_favorite_prime :
    Nat.Prime 5 and
    (exists k : N, 5^2 + 144 = k^2) and
    (forall p : N, Nat.Prime p → p < 5 →
      ¬exists k : N, p^2 + 144 = k^2) := by
  sorry
```

```
theorem my_favorite_prime :
    Nat.Prime 5 and
    (exists k : N, 5^2 + 144 = k^2) and
    (forall p : N, Nat.Prime p → p < 5 →
      ¬exists k : N, p^2 + 144 = k^2) := by
  have h_prime_5 : Nat.Prime 5 := by decide
  have h_exists_k : exists k : N, 5^2 + 144 = k^2 := by
    refine' ⟨13, _⟩
    norm_num
  have h_no_smaller_prime :
      forall p : N, Nat.Prime p → p < 5 →
        ¬exists k : N, p^2 + 144 = k^2 := by
    intro p hp hlt
    have h1 : p = 2 or p = 3 := by
      have h4 : p ≤ 4 := by linarith
      interval_cases p <;>
        norm_num [Nat.Prime] at hp ⊢ <;> aesop
    rcases h1 with (rfl | rfl)
    · intro h
      rcases h with ⟨k, hk⟩
      have h2 : 2 ^ 2 + 144 = k ^ 2 := by simpa using hk
      have h3 : k ^ 2 = 148 := by linarith
      have h4 : k ≤ 12 := by nlinarith
      have h5 : k >= 13 := by nlinarith
      linarith
    · intro h
      rcases h with ⟨k, hk⟩
      have h2 : 3 ^ 2 + 144 = k ^ 2 := by simpa using hk
      have h3 : k ^ 2 = 153 := by linarith
      have h4 : k ≤ 12 := by nlinarith
      have h5 : k >= 13 := by nlinarith
      linarith
  exact ⟨h_prime_5, h_exists_k, h_no_smaller_prime⟩
```

B Experimental Settings

B.1 Training Details

All models are based on the Qwen3 series (Qwen Team et al., 2025), specifically Qwen3-4B and Qwen3-32B, and are fine-tuned for two epochs using LoRA of rank 64 applied to all linear layers. Our models are trained using LlamaFactory (Zheng et al., 2024) for SFT, and Volcano Engine Reinforcement Learning (verl) (Sheng et al., 2024) for RL. We use learning rates of 3e−4 and 7e−5 for the SFT stages. For self-distillation, we reduce the learning rate to 1e−5, as larger values induced training instability. Lastly, for Pythagoras-Prover-Diffusion we perform full fine-tuning with a learning rate of 3e−5.

B.2 MiniF2F-ALF Creation

MiniF2F-ALF is constructed by applying the ALF mutation scheme of §2.3 to each of the 244 problems in MiniF2F-Test. The design follows GSM-Symbolic (Mirzadeh et al., 2025), which shows that perturbing a problem's variables and numerical values while preserving its underlying structure and difficulty is sufficient to expose memorisation effects on GSM8K; we transfer this principle to formal proving by renaming variables in each statement, reducing reliance on memorised surface forms. For each problem we generate five candidate mutations with Codex (GPT-5.5) and rank them by semantic divergence from the original statement, measured as cosine distance under `Alibaba-NLP/gte-Qwen2-7B-instruct` (Li et al., 2023) (the encoder of Appendix A.2), retaining the two most divergent candidates per problem. Unlike the ALF self-distillation corpus, where per-sample verification is omitted at scale (§2.3), here every retained mutation is verified: we use Claude Opus 4.6 (Anthropic, 2026) as a judge to confirm that it is a well-formed Lean theorem and pass it through the Lean compiler to ensure correctness, so that all 488 statements in the final benchmark are guaranteed valid.

C Extended Results and Ablations

C.1 Full Pass@N Results

Table 4 reports pass@N on MiniF2F-Test across the full sweep of inference budgets we evaluate, covering every open-source baseline both with and without self-correction.

At the 4B scale, Pythagoras-Prover-4B reaches 86.1% at pass@32. This places it ahead of Goedel-Prover-V2-8B without self-correction (84.6%) and at near parity with that model's self-corrected variant (86.7%), despite using half the parameters and no inference-time correction loop. The advantage widens with budget: Pythagoras-Prover-4B attains 88.1% at pass@1024 and 89.8% at pass@2048, the latter already exceeding the pass@8192 result of DeepSeek-Prover-V2-671B (88.9%) at a quarter of the sampling budget and with roughly 167× fewer parameters.

At the 32B scale, Pythagoras-Prover-32B leads Goedel-Prover-V2-32B without self-correction by 1.7 points at pass@32 (89.8% vs. 88.1%), trails its self-corrected counterpart by only 0.6 points at the same budget (89.8% vs. 90.4%), and matches it at pass@1024 (92.6% vs. 92.6%). At pass@2048 it reaches **93.03%**, the strongest reported pass rate on MiniF2F-Test, surpassing the pass@8192 result of Goedel-Prover-V2-32B (92.2%) at a quarter of the budget and without any iterative repair step.

C.2 Decomposition Performance

Table 5 decomposes the contributions of supervised fine-tuning and ALF self-distillation on MiniF2F-Test at pass@32. Supervised fine-tuning on our synthetic-data corpus alone already yields a strong prover (79.10% at 4B and 84.02% at 32B) which we read as direct evidence that the corpus itself carries most of the signal required for competitive formal reasoning, prior to any further training stages. Adding ALF self-distillation lifts the two models to 86.1% and 89.8%, gains of +6.97 and +5.73 points respectively, showing that mutation-driven self-distillation delivers a consistent improvement on top of an already strong SFT baseline rather than substituting for it.

Table 4: Pass@N on MiniF2F-Test across inference budgets N. Results in the top part are copied as reported by the respective papers. Values are percentages; [†] Kimina-Prover variants; best in bold.

Method	Budget (N)	Performance Pass@N
Goedel-Prover-SFT (Lin et al., 2025b)	32	57.6
	3200	62.7
STP (Dong & Ma, 2025)	128	61.2
	3200	65.0
	25600	67.6
Kimina-Prover-Preview-72B (Wang et al., 2025a)	32	68.85
	8192	80.74
DeepSeek-Prover-V2-7B (Ren et al., 2025)	32	75.6
	8192	82.0
DeepSeek-Prover-V2-671B	32	82.4
	8192	88.9
Kimina-Prover-8B[†] (Wang et al., 2025a)	32	78.3
Kimina-Prover-70B[†]	32	84.0
	1024	87.7
w/ Test-Time Reinforcement Learning	–	92.2
Goedel-Prover-V2-8B (Lin et al., 2026)	32	84.6
	1024	87.9
	8192	90.2
w/ Self-Correction	32	86.7
	1024	89.3
Goedel-Prover-V2-32B	32	88.1
	1024	91.8
	8192	92.2
w/ Self-Correction	32	90.4
	1024	92.6
Pythagoras-Prover-4B	32	86.1
	1024	88.1
	2048	89.8
Pythagoras-Prover-32B	32	89.8
	1024	92.6
	2048	**93.0**

Table 5: Ablation of Pythagoras-Prover training components on MiniF2F-Test under a pass@32 inference budget. SFT-only rows isolate the contribution of the synthetic-data supervised fine-tuning stage prior to ALF self-distillation.

Method	Budget	Pass@32 (%)
Pythagoras-Prover-4B (SFT only)	32	79.10
Pythagoras-Prover-4B (SFT + ALF Self-Distillation)	32	86.07
Pythagoras-Prover-32B (SFT only)	32	84.02
Pythagoras-Prover-32B (SFT + ALF Self-Distillation)	32	89.75

(a) Stable training at 4,096-token context: gradient norm settles after warm-up and remains bounded throughout training.

(b) Unstable training at 8,192-token context: gradient norm fails to settle and exhibits sustained spikes well past warm-up.

Figure 10: Gradient-norm dynamics of Pythagoras-Prover-Diffusion-4B under the two context-length settings. The 8,192-token setting that converges cleanly under the autoregressive objective destabilises diffusion training, motivating the reduced 4,096-token budget used for Pythagoras-Prover-Diffusion (§2.4).

C.3 Why Long-Context Diffusion Training Destabilises

The instability illustrated in Figure 10 is not a tuning artefact but a consequence of the variance structure of the MDLM objective. We give the analysis here, and connect it to the design choices reported in prior masked-diffusion LM work.

Variance of the per-sequence loss. For a fixed sequence $\mathbf{x}_0$ of length L and fixed noise level t, the forward process masks each position independently with probability t, so the number of masked positions is $|S| \sim \text{Binomial}(L, t)$. The MDLM stochastic loss for this sample is

$$\widehat{\mathcal{L}}(\theta; \mathbf{x}_0, \mathbf{x}_t, t) \;=\; -\frac{1}{t} \sum_{i=1}^{L} \mathbf{1}\big[x_t^i = [\text{M}]\big] \log p_\theta(x_0^i \mid \mathbf{x}_t). \tag{3}$$

Treating the per-position log-probabilities as bounded by an average magnitude $\bar{\ell}$, the conditional variance over the masking draw is

$$\text{Var}\Big[\widehat{\mathcal{L}}\,\Big|\, t, \mathbf{x}_0\Big] \;\approx\; \bar{\ell}^2 \cdot \frac{L\,(1-t)}{t}. \tag{4}$$

Here $\bar{\ell}$ denotes a representative per-position log-probability magnitude, $\bar{\ell} \approx |\log p_\theta(x_0^i \mid \mathbf{x}_t)|$, treated as roughly constant across positions. We stress that Eq. equation 4 is approximate: collapsing the per-position losses to a single scale $\bar{\ell}$ treats them as independent and omits their cross-position covariance, whereas in practice the $\log p_\theta(x_0^i \mid \mathbf{x}_t)$ are correlated, since all masked positions are predicted from the same partially-masked context. We therefore read Eq. equation 4 as a behavioural scaling, $\text{Var} \propto L(1-t)/t$, rather than an exact variance.

Although Eq. equation 4 is the variance of the loss, the gradient $\nabla_\theta \widehat{\mathcal{L}}$ shares the same $1/t$-reweighted sum-over-masked-positions structure, so its variance carries the same $L(1-t)/t$ scaling; this is the quantity reflected in the gradient-norm spikes of Figure 10b.

Two properties of Eq. 4 matter for stability: (i) the variance is *linear in the sequence length L*, so doubling the context from 4,096 to 8,192 doubles per-step gradient variance at every noise level; and (ii) the variance *diverges as $t \to 0$*, so rare low-t realisations, which are unavoidable under the uniform schedule $t \sim \mathcal{U}[0,1]$ used by LLaDA (Nie et al., 2025) and by Diffusion-Pythagoras-Prover, produce heavy-tailed contributions whose magnitude also scales with L. The compound effect is that long-context training amplifies both the typical gradient variance and the tail mass of large-gradient steps, so even short bursts of low-t samples are enough to push the optimiser past gradient clipping in sustained spikes, which is precisely the pattern visible in Figure 10b.

This effect compounds with the memory budget: doubling the context roughly halves the largest feasible batch size, so the per-sequence variance increase of Eq. equation 4 is averaged over fewer samples per step, further raising the gradient variance the optimiser actually sees.

Extension to tactic-based masking. The analysis above is stated for the token-level objective, whereas Pythagoras-Prover-Diffusion masks whole tactic spans (Eq. equation 2). The same argument transfers with the unit of masking changed from tokens to tactics. Writing K for the number of tactic spans and $\ell_{\tau_k} \approx |\tau_k| \bar{\ell}$ for the summed per-token loss of span τ_k, the per-sequence variance becomes

$$\mathrm{Var}\left[\widehat{\mathcal{L}}_{\mathrm{tac}} \,\Big|\, t, \mathbf{x}_0\right] \;\approx\; \frac{1-t}{t} \sum_{k=1}^{K} \ell_{\tau_k}^2 \;\approx\; \bar{\ell}^{\,2}\, \bar{s}\, \frac{L(1-t)}{t}, \tag{5}$$

where $\bar{s}$ is the mean tactic length (with equality when spans are equal-length; variable span lengths increase the bound further). Tactic-based masking therefore inherits the same L- and t-dependence and amplifies it by roughly $\bar{s}$, so the instability is, if anything, more pronounced for Pythagoras-Prover-Diffusion than for a token-level masked-diffusion model at the same context length.

Contrast with autoregressive training. This variance is specific to the diffusion objective. The autoregressive loss $-\sum_i \log p_\theta(x_0^i \mid \mathbf{x}_0^{<i})$ is a deterministic sum over all L positions, with no masking draw and no $1/t$ reweighting, so it carries none of the $L(1-t)/t$ terms. This is why the same 8,192-token setting that destabilises diffusion converges cleanly under the autoregressive objective (§2.4).

Consistency with prior masked-diffusion LM work. Every existing masked-diffusion LM that scales to large models trains at a relatively short, fixed context window and explicitly engineers around the variance term of Eq. 4. LLaDA (Nie et al., 2025) pretrains at a *fixed* 4,096-token context and reserves 1% of the data for random shorter lengths, with no recipe given for 8,192. MDLM (Sahoo et al., 2024) reduces ELBO variance through a low-discrepancy t-sampler that draws correlated t_i rather than i.i.d.. Block diffusion (Arriola et al., 2025) goes further still, introducing gradient-variance estimators and data-driven noise schedules and decomposing the sequence into smaller blocks so that no single forward pass has to absorb the full $L(1-t)/t$ variance term. The shared pattern across these works is that long-sequence stability in masked diffusion is treated as a *variance-reduction* problem rather than an optimiser-hyperparameter problem, which matches our empirical observation: the only intervention that consistently stabilised Pythagoras-Prover-Diffusion at 8,192 tokens in our preliminary experiments was reducing the context budget, while increased warm-up, lower learning rate, and tighter gradient clipping each only postponed the spike pattern of Figure 10b. We therefore use the 4,096-token budget throughout for Pythagoras-Prover-Diffusion, and leave variance-reduction techniques (low-discrepancy / antithetic t-sampling, block decomposition) to future work.

C.4 Training Performance between full context and dynamic *proof-reasoning filtering*

In this section, we perform an ablation study between full-context training and our full-context dynamic training with proof-reasoning filtering. Both settings share the same model backbone, synthetic-data corpus, optimiser configuration, and SFT recipe; they differ only in whether reasoning traces are filtered on the fly during training. The full-context baseline trains on every reasoning–proof pair extracted from the synthetic corpus, whereas the dynamic-filtering variant prunes each minibatch in real time by discarding pairs whose reasoning trace is inconsistent with its closing tactic sequence, concentrating gradient updates on traces whose chain-of-thought actually supports the discharged theorem.

Table 6 reports pass@32 on MiniF2F-Test under both settings. The dynamic filter delivers a consistent improvement at both scales, +3 solved instances at 4B and +2 instances at 32B, without changing parameter count, training budget, or inference protocol. The gain is meaningful in the near-saturated regime of MiniF2F-Test: the 4B model picks up three additional problems on a benchmark where the four-prover panel of §5.3 leaves only 41/244 at-least-one-wrong cases to contest. The smaller absolute gain at 32B is consistent with the diminishing-returns pattern observed elsewhere in the analysis: the 32B baseline already discharges most reasoning-noisy traces robustly, so filtering shifts mass on a narrower residual.

D Detailed Analysis of MiniF2F

Extending the analysis of §5.3, we examine the domain composition of the residual failure set on original MiniF2F-Test under our four-prover panel (Pythagoras-Prover-4B, Pythagoras-Prover-32B, Goedel-Prover-

Table 6: Ablation of dynamic proof-reasoning filtering against full-context training on MiniF2F-Test at pass@32. Both rows share the SFT recipe and synthetic-data corpus; the only difference is whether reasoning traces are filtered on the fly during training. Values are pass rates (%) with absolute solved counts out of 244 in parentheses.

Training setting	Pythagoras-Prover-4B	Pythagoras-Prover-32B
Full context (no filtering)	80.70	84.02
+ Dynamic proof-reasoning filtering	79.10	83.20
Δ	+1.62	+0.82

(a) Domain composition of the full MiniF2F-Test benchmark (all instances).

(b) Domain composition of the all-model-wrong set on original MiniF2F-Test.

(c) Domain composition of the at-least-one-model-wrong set on MiniF2F-ALF, after applying the ALF mutation scheme to each MiniF2F-Test statement.

Figure 11: Categories are taken directly from MiniF2F. The competition-derived slices comprise *IMO* (International Mathematical Olympiad), *AMC* (American Mathematics Competitions, AMC 8/10/12), and *AIME* (American Invitational Mathematics Examination); *MathD* groups problems imported from the MATH (Hendrycks et al., 2021). The remaining slices are topic-tagged hand-written instances grouped by area: *Algebra*, *Number Theory*, and *Induction*.

V2-8B, Goedel-Prover-V2-32B). Figure 9 shows that the at-least-one-model-wrong subset is dominated by olympiad-level material: AMC and IMO together account for roughly two-thirds of all failures, with the remaining categories forming a thin long tail. The all-model-wrong subset (Figure 11b) is even more skewed: IMO alone accounts for half of all universal failures and AMC for the bulk of the remainder, so the residual difficulty on which contemporary provers can still be separated sits almost entirely at the upper end of the difficulty spectrum. Combined with the headline saturation statistic that 83.20% of MiniF2F-Test is solved by all four systems, this leaves only a narrow band of olympiad instances on which the benchmark can meaningfully discriminate between strong provers. Figure 8 breaks this residual set down per problem, showing for each prover which instances it solves and which it misses, and confirming that disagreement is confined to a smaller, olympiad-heavy tail.

Figure 11c shows the same decomposition after ALF mutation. The distribution shifts substantially: MathD, a small slice of the original failure set, rises to roughly 20% of at-least-one-wrong instances on MiniF2F-ALF, and Algebra, Number Theory, Induction, and AIME each occupy a non-trivial share. The IMO/AMC concentration that characterises the original failure set is broken, with failures redistributing across categories that should not be intrinsically harder than instances the same systems solve on the original split. This redistribution is the empirical signature we look for: rather than amplifying the olympiad tail, ALF surfaces a broader set of structurally simple cases on which strong provers turn out to be brittle, providing discriminative signal across the full difficulty range rather than only at its top.

E   A Failure Mode of Self-Correction

Putnam 1966 A4. Non-square positive integers indexed by closest-square distance.

Formal statement

```
theorem putnam_1966_a4
    (a : N → ℤ)
    (ha1 : a 1 = 2)
    (hai : forall n >= 1, a (n + 1) =
        (if exists m : ℤ, m^2 = a n + 1 = True
        then a n + 2
        else a n + 1)) :
    forall n >= 1, a n = n + round (Real.sqrt n) := by
  sorry
```

Putnam 1966 A4: A self-correction failure mode. A structural induction on n that decomposes the non-square indices into blocks $[k^2 - k + 1,\ k^2 + k]$, with a rounding lemma identifying $\mathrm{round}(\sqrt{n})$ inside each block.

Goedel-Prover-V2 (first round, failed)

```
theorem putnam_1966_a4
(a : N → ℤ)
(ha1 : a 1 = 2)
(hai : forall n >= 1, a (n + 1) = (if exists m : ℤ, m^2 = a n + 1 then a n + 2 else
a n + 1))
: forall n >= 1, a n = n + round (Real.sqrt n) :=
by
  have h_main : forall (n : N), n >= 1 → a n = n + round (Real.sqrt n) := by
    intro n hn
    have h₁ : forall n : N, n >= 1 → a n = n + round (Real.sqrt n) := by
      intro n hn
      induction' hn with n hn IH
      · norm_num [ha1]
        <;> simp [round_eq, Int.floor_eq_iff, Real.le_sqrt, Real.sqrt_lt]
        <;> norm_num
        <;> linarith [Real.sqrt_nonneg 1,
              Real.sq_sqrt (show 0 ≤ (1 : R) by norm_num)]
      · have h₂ : a (n + 1) =
            (if exists m : ℤ, m ^ 2 = a n + 1 then a n + 2 else a n + 1) := by
          apply hai
          <;> omega
        rw [h₂]
        have h₃ : a n = n + round (Real.sqrt n) := IH
        rw [h₃]
        have h₄ : (if exists m : ℤ, m ^ 2 = (n : ℤ) + round (Real.sqrt n) + 1
              then (n : ℤ) + round (Real.sqrt n) + 2
              else (n : ℤ) + round (Real.sqrt n) + 1)
            = (n + 1 : ℤ) + round (Real.sqrt (n + 1)) := by
          split_ifs with h
          · have h₈ : round (Real.sqrt (n + 1 : R))
                  = round (Real.sqrt (n : R)) + 1 := by
              sorry
            sorry
          · have h₈ : round (Real.sqrt (n + 1 : R))
                  = round (Real.sqrt (n : R)) := by
              sorry
            sorry
        rw [h₄]
    exact h₁ n hn
  intro n hn
  exact h_main n hn
```

Self-correction round (failed)

```
import Mathlib
import Aesop

set_option maxHeartbeats 0

open BigOperators Real Nat Topology Rat Filter

theorem putnam_1966_a4
(a : N → ℤ)
(ha1 : a 1 = 2)
(hai : forall n >= 1, a (n + 1) = (if exists m : ℤ, m^2 = a n + 1 then a n + 2 else
a n + 1))
: forall n >= 1, a n = n + round (Real.sqrt n) := by
  have h_main : forall n >= 1, a n = (n : ℤ) + round (Real.sqrt n) := by
    intro n hn
    have h₁ : n ≤ 16 or n > 16 := by omega
    cases h₁ with
    | inl h₁ =>
      interval_cases n
      <;> norm_num [ha1, hai, round_eq, Int.floor_eq_iff,
            Real.sqrt_le_iff, Real.lt_sqrt, Real.sqrt_lt] at *
      <;> (try { nlinarith [Real.sqrt_nonneg 2,
            Real.sq_sqrt (show (0:R) ≤ 2 by norm_num)] })
      <;> (try { nlinarith [Real.sqrt_nonneg 3,
            Real.sq_sqrt (show (0:R) ≤ 3 by norm_num)] })
      <;> (try { nlinarith [Real.sqrt_nonneg 5,
            Real.sq_sqrt (show (0:R) ≤ 5 by norm_num)] })
      <;> (try { aesop }) <;> (try { linarith })
    | inr h₁ =>
      exfalso
      have h₃ : a 1 = 2 := ha1
      have h₄ : a 2 = 3 := by
        have h₅ := hai 1 (by norm_num); norm_num [ha1] at h₅ ⊢
        <;> simp_all [ha1] <;> aesop
      have h₅ : a 3 = 5 := by
        have h₆ := hai 2 (by norm_num); norm_num [h₄] at h₆ ⊢
        <;> simp_all [ha1, h₄] <;> aesop
      have h₆ : a 4 = 6 := by
        have h₇ := hai 3 (by norm_num); norm_num [h₅] at h₇ ⊢
        <;> simp_all [ha1, h₄, h₅] <;> aesop
      have h₇ : a 5 = 7 := by
        have h₈ := hai 4 (by norm_num); norm_num [h₆] at h₈ ⊢
        <;> simp_all [ha1, h₄, h₅, h₆] <;> aesop
      have h₁₈ : a 16 = 20 := by
        have h₁₉ := hai 15 (by norm_num); norm_num [h₁₇] at h₁₉ ⊢
        <;> simp_all [ha1, h₄, h₅, h₆, h₇, h₈, h₉, h₁₀,
              h₁₁, h₁₂, h₁₃, h₁₄, h₁₅, h₁₆, h₁₇]
        <;> aesop
      <;> norm_num <;> aesop
    intro n hn
    have h₁ : a n = (n : ℤ) + round (Real.sqrt n) := h_main n hn
    norm_cast at h₁ ⊢
    <;> simp_all [add_assoc] <;> linarith
```

Putnam 1966 A4: Pythagoras-Prover successful proof.

```
theorem putnam_1966_a4
(a : N → ℤ)
(ha1 : a 1 = 2)
(hai : forall n >= 1, a (n + 1) =
    (if exists m : ℤ, m^2 = a n + 1 = True then a n + 2 else a n + 1))
: forall n >= 1, a n = n + round (Real.sqrt n) := by
  have h_round_of_block : forall (n k : N),
    [TRUNCATE]

  have h_square_branch_of_block : forall (n k : N),
    k * k - k + 1 ≤ n → n ≤ k * k + k →
    (((exists m : ℤ, m ^ 2 = (n : ℤ) + (k : ℤ) + 1) = True) ↔ n = k * k + k) := by
    [TRUNCATE]

  have h_block : forall n : N, n >= 1 → exists k : N,
    a n = (n : ℤ) + (k : ℤ) and
    k * k - k + 1 ≤ n and n ≤ k * k + k := by
    [TRUNCATE]

  intro n hn
    [TRUNCATE]
```

F Effective Token Complexity Calculation

Intuition. Wall-clock cost and pass@N are both misleading proxies for compute when two systems decode under very different regimes: pass@N ignores per-attempt length, and wall-clock conflates batching, hardware, and serving stack. We instead estimate the work the attention mechanism performs under an idealised model. For a single decoded block of a tokens conditioned on an input of m tokens, the generated token at within-block position t attends to the m prompt tokens together with the t tokens produced up to and including itself ($m + t$ keys in total), so the cumulative query–key work over the block is

$$\sum_{t=1}^{a}(m+t) \;=\; \underbrace{m\,a}_{\text{prompt attention}} \;+\; \underbrace{\frac{a(a+1)}{2}}_{\text{self-attention}} \;. \tag{6}$$

We call the quantity in Eq. equation 6 the *effective token complexity* (ETC), denoted by $\mathrm{ETC}(m, a)$. The first term scales linearly with the input context (attending to a fixed prompt across the whole block); the quadratic term is the intra-block self-attention cost, and it dominates whenever a is comparable to or larger than m. For pass@N we multiply the per-attempt ETC by N, summing across rounds for multi-round systems.

Assumptions and scope. ETC is deliberately idealised and should be read as a worst-case, asymptotic proxy rather than an estimate of realised inference cost; three caveats apply. First, it assumes *dense global attention* in every layer, so each step pays a cost proportional to its full context length. This does not hold for models that replace global attention with sparse attention (e.g. the Qwen3 family) or linear or gated delta net attention (e.g. Qwen3.5-Omni) in most layers, for which the per-step context cost is sub-linear and ETC over-counts the linear term. Second, ETC ignores inference-engine optimisations such as KV- and prefix-caching, as well as the memory-bound versus compute-bound trade-off that depends jointly on context length and batch size. Third, it is not a FLOP count: converting it to FLOPs would require architecture-specific factors (model width, head count, attention type), not a single multiplicative constant. What survives these caveats is the *geometric asymmetry* the measure is designed to expose, which holds under any super-linear attention cost: generating many short independent blocks is asymptotically cheaper than conditioning on a long accumulated context. Concretely, k independent blocks of length n cost on the order of $k \cdot n^2/2$ under the self-attention term, against $(kn)^2/2 = k^2 \cdot n^2/2$ for a single block of the same total length, a factor-k saving. Restart sampling realises this saving; multi-round self-correction does not. We therefore use ETC only to characterise this scaling behaviour, and report the per-attempt token statistics in Table 3 so the estimate can be recomputed under any alternative cost model.

Illustrative ETC under the idealised model. We report per-attempt ETC values under the dense-attention idealisation to illustrate the scaling regime, not as an estimate of realised decoding cost; the caveats above (in particular the over-counted linear term under sparse attention) mean the absolute figures should be read as an upper-bound-style illustration rather than a measurement. For Goedel-Prover, summing its three self-correction rounds at pass@184 with the per-round token statistics in Table 3, we obtain

$$\mathrm{ETC}_{\text{Goedel-Prover}} = 184 \left[\underbrace{\mathrm{ETC}(284.88,\, 18367.83)}_{\textit{round 1}} + \underbrace{\mathrm{ETC}(7838.74,\, 21638.70)}_{\textit{round 2}} + \underbrace{\mathrm{ETC}(8309.06,\, 23835.80)}_{\textit{round 3}} \right]$$

$$\approx 184 \left[1.7393 \times 10^8 + 4.0375 \times 10^8 + 4.8214 \times 10^8 \right]$$

$$\approx 1.95 \times 10^{11}.$$

For Pythagoras-Prover, with an input context of 284.88 tokens and an average restart length of 18,741.80 tokens at pass@1024,

$$\mathrm{ETC}_{\text{Pythagoras-Prover}} = 1024 \cdot \mathrm{ETC}(284.88,\, 18741.80)$$

$$\approx 1024 \cdot 1.8098 \times 10^8 \;\approx\; 1.85 \times 10^{11}.$$

Under this idealisation the two estimates are within roughly 5% of one another. We deliberately do *not* read this margin as evidence that either system has lower cost: a 5% difference lies well inside the error introduced

by assuming dense global attention, and because Goedel-Prover's later rounds condition on much larger input contexts m than our restarts, the linear-term over-counting does not cancel between the two systems. Moving off dense attention, to the sparse or linear kernels used in practice, lowers the absolute cost of *both* regimes but does not reverse the direction of the asymmetry established above, since that asymmetry arises from how context grows across attempts rather than from the attention kernel. We therefore treat the two systems as operating at *comparable* effective token complexity, at which Pythagoras-Prover solves more problems (88 vs. 86), and rely on the scaling behaviour rather than the point estimate.