CYCLOPHOBIC REINFORCEMENT LEARNING

ABSTRACT

In environments with sparse rewards finding a good inductive bias for exploration is crucial to the agent's success. However, there are two competing goals: novelty search and systematic exploration. While existing approaches such as curiosity-driven exploration find novelty, they sometimes do not systematically explore the whole state space, akin to depth-first-search vs breadth-first-search. In this paper, we propose a new intrinsic reward that is cyclophobic, i.e. it does not reward novelty, but punishes redundancy by avoiding cycles. Augmenting the cyclophobic intrinsic reward with a sequence of hierarchical representations based on the agent's cropped observations we are able to achieve excellent results in the MiniGrid and MiniHack environments. Both are particularly hard, as they require complex interactions with different objects in order to be solved. Detailed comparisons with previous approaches and thorough ablation studies show that our newly proposed cyclophobic reinforcement learning is vastly more efficient than other state of the art methods.

1 INTRODUCTION

Exploration is one of reinforcement learning's most important problems. Learning success largely depends on whether an agent is able to explore its environment efficiently. Random exploration (e.g. epsilon-greedy with sparse rewards) is exploring all possibilities but at great costs, since it possibly revisits states very often. More efficient approaches use intrinsic rewards based on curiosity to enforce focusing on novelty, which often leads to great results, but at the price of possibly not exploring all corners of the environment systematically. Ideally, we would pursue both goals: novelty search and systematical exploration.

How can we favor novelty while ensuring that the whole environment is systematically explored? To achieve this, we propose *cyclophobic reinforcement learning* which is based on the simple idea of avoiding cycles during exploration. More precisely, we define a negative intrinsic reward that penalizes redundancy in the exploration history. This idea is further pushed by applying it to several hierarchical views of the environment. The notion of redundancy can be defined relative to cropped views of the agent: while cycles in the global view induces cycles in the corresponding narrow view, the converse is not the case. E.g., a MiniGrid agent turning four times to the left produces a cycle in state space that we would like avoid everywhere. This cycle is visible in the global view, but penalizing it does not avoid it in other locations. However, with a hierarchy of views, we record a cycle also in some smaller view, which allows us to transfer this knowledge to any location in the global view and hereby to avoid never experienced cycles. Similarly, encountering a key in a smaller view produces less cycles and thus the probability of picking up the key increases, since other actions possibly produce already seen cycles (e.g. when walking away). Thus, we are defining cycles relative to a hierarchy of view to get a transferable definition of redundancy.

Contributions:

1. We introduce cyclophobic reinforcement learning as a new paradigm for efficient exploration in hard environments (e.g. with sparse rewards). It is based on a new cyclophobic intrinsic reward for systematic exploration applied to a hierarchy of views. Instead rewarding novelty we are avoiding redundancy by penalizing cycles, i.e. repeated state/action pairs in the exploration history. Our approach can be applied to any MDP for which a hierarchy of views can be defined.

2. In the sparse-reward settings of the MiniGrid and MiniHack environments we thoroughly evaluate cyclophobic reinforcement learning and can show that it achieves excellent results compared to existing methods, both for tabula-rasa and transfer learning.

3. In an ablation study we provide deeper insights into the interplay of the cyclophobic intrinsic reward and the hierarchical state representations.

Notation: We define an MDP as a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma)$, where the agent and the environment interact continuously at discrete time steps $t = 0, 1, 2, 3, \ldots$ We define the state an agent receives from the environment as a random variable $S_t \in \mathcal{S}$, where $S_t = s$ is some representation of the state from the set of states $\mathcal{S}$ at timestep t. From that state, we define a random variable for the agent selecting an action $A_t \in \mathcal{A}$ where $A_t = a$ is some action in the possible set of actions $\mathcal{A}$ for the agent at timestep t. This action is selected according to a policy $\pi(a \mid s)$ or $\pi(s)$ if the policy is deterministic. One time step later as a consequence of its action, the agent receives a numerical reward which is a random variable $R_{t+1} \in \mathbb{R}$, where $R_{t+1} = r$ is some numerical reward at timestep $t + 1$. Finally, the agent finds itself in a new state S_{t+1}. Furthermore we define a POMDP $(\mathcal{S}, \mathcal{A}, \mathcal{O}, \mathcal{P}, \mathcal{R}, \mathcal{Z}, \gamma)$ as a generalization of an MDP in the case the true state space $\mathcal{S}$ is unknown. That is, the agent sees the state $s \in \mathcal{S}$ through an observation $o \in \mathcal{O}$, where an observation function $\mathcal{Z} : \mathcal{S} \rightarrow \mathcal{O}$ maps the observation to the true state.

2 BUILDING BLOCKS

We begin by first defining the cyclophobic intrinsic reward and hierarchical state representations as they are the building blocks of our method. Finally, we define a policy which combines the intrinsic and extrinsic rewards together with the hierarchical state representations to form a global policy which the agent acts upon.

2.1 CYCLOPHOBIC INTRINSIC REWARD

For efficient exploration, redundancy must be avoided. A sign for redundancy is when states are repeatedly explored, with other words, when the agent encounters cycles in the state space instead of focusing on novel areas. To guide the exploration, we will penalize cycles using a cycle penalty, which we call cyclophobic intrinsic reward (a negative intrinsic reward). This avoids redundancy such that uninteresting parts of the state-action space are discarded quickly. For instance, if an agents gets stuck in some area, typically, it is facing numerous cycles. In such a situation we would like the agent to assign penalties to the repeating state-action pairs in order to focus on more promising parts of the state space that do not cause immediate repetition.

Formally, let us assume that we have per episode a history of previous state-action pairs $\mathcal{H}_{\text{episodic}} = \{(s_1, a_1), (s_2, a_2), \ldots, (s_t, a_t)\}$ and we are currently at the state-action pair (s_{t+1}, a_{t+1}). We say that we have encountered a cycle if the current state-action pair appeared already in the history, i.e. $(s_{t+1}, a_{t+1}) \in \mathcal{H}_{\text{episodic}}$. For its first repeated occurrence, we will penalize the state-action pair (s_t, a_t) (just before the cycle) by negative one,

$$r_{\text{cycle}}(s, a) = -1. \tag{1}$$

If a cycle is encountered multiple times, e.g. l times, the cycle penalty is $-l$. That is, during exploration the cycle penalty can decrease indefinitely. For pairs (s, a) that have not created a cycle, $r_{\text{cycle}}(s, a) = 0$.

Learning the cycle penalties. In principle, the cycle penalty can be combined with any reinforcement learning algorithm. However, we explain how it can be build into the SARSA update rule, since the latter will propagate the additional penalty across the trajectory. To learn the Q-function, we are employing the standard SARSA update rule,

$$Q(s, a) \leftarrow (1 - \eta) \, Q(s, a) + \eta \big[r(s, a) + \gamma \, Q(s', a') \big] \tag{2}$$

with $(s, a, r_{\text{ex}}, s', a')$ being a transition, η being step size and where the total reward $r(s, a)$ for the state-action pair (s, a) is the sum of the extrinsic reward from the environment r_{ex} and the cyclophobic intrinsic reward $r_{\text{cycle}}(s, a)$ defined above,

$$r(s, a) = r_{\text{ex}} + \rho \, r_{\text{cycle}}(s, a). \tag{3}$$

where ρ trades off extrinsic and intrinsic rewards.

2.2 HIERARCHICAL STATE REPRESENTATIONS

Besides penalizing cycles, the second key idea of this paper is to consider a hierarchy of state representations. For this, we repeatedly crop the agent's observations to induce additional partially observable Markov decision processes (POMDPs). In general, restricting the views leads to ignoring information about the environment. Surprisingly, in combination with the cyclophobic intrinsic reward, we gain additional information about the structure of the environment. The relevant insight is

that on limited views lower down the hierarchy, trajectories can contain cycles that have not been experienced on views higher up the hierarchy. These cycles in the detailed view represent transferable knowledge about the structure of the environment. E.g. in the MiniGrid environment (see Section B.1) encountering a wall in the most detailed view will cause a cycle, capturing that running into a wall is counterproductive. On larger views this knowledge is only available directly, if we tried all walls everywhere. So, the the detailed view captures relevant invariances that also apply to the larger views. In general MDPs it might not be obvious how to define hierarchical state representations. Ideally, the agent has some sort of "location" to allow "cropped" views. Additionally, local properties of the state space that result in cycles are transferable to the whole state space, so that learning to avoid cycles helps for efficient exploration. For grid world-like environments, the hierarchical state representations are easily definable, since the agent has a defined location that can be used to define smaller neighborhoods typically corresponding to limited views of the agent.

(a)   (b)

Figure 1: **Hierarchical views allow us to transfer relevant invariances about the environment.** (a) The three different representations are obtained by cropping the observation for each state-action pair (s, a). V_1 is the full view where the agent sees the whole environment or the largest portion of it. V_2 are intermediate cropped representations of the agent's view that help the agent generalize by reusing familiar observations . V_3 is the most restricted view where the agent only sees what is front. (b) Through the views V_1 to V_k the amount of cycles continuously increases as the observations in the higher views can be mapped multiple times to the same observation in the lower view. This naturally leads to each view being a separate POMDP describing the true MDP.

To discuss the roles of the different views more precisely, let's consider three such cropped views which consist of the global view V_1, the intermediate view V_2 and the smallest possible detail view V_3 (see Figure 1a). Each view gives a new, typically more limited, perspective of the true state. As shown in Figure 1b, each view induces a different set of cycles, for instance a sequence of actions which do not lead to a cycle in the full view V_1, might lead to a cycle in a detailed view V_3, because in the latter, more states are mapped to the same observation. Thus, the different views provide different types of information which are useful for learning and allow the agent to focus on different properties of the environment.

In general, we can have an arbitrary number of views. Each view V_i induces a POMDP

$$\mathcal{V}_i = (\mathcal{S}, \mathcal{A}, \mathcal{O}^{V_i}, \mathcal{P}, \mathcal{R}, \mathcal{Z}^{V_i}, \gamma) \tag{4}$$

each having their own set of observations $\mathcal{O}^{V_i}$ and observation function $\mathcal{Z}^{V_i} : \mathcal{S} \to \mathcal{O}^{V_i}$. All POMDP's $\mathcal{V}_1, \mathcal{V}_2, \ldots$ operate on the same state space $\mathcal{S}$, however they have different sets of observations $\mathcal{O}$ and corresponding observation functions. General POMDPs can have a probabilistic observation function. In our case, the observations are deterministic functions of the full view, e.g. the observations for the ith POMDP of state s is

$$o^{V_i} = \mathcal{Z}^{V_i}(s) \tag{5}$$

which corresponds to the cropping for the view V_i. Hereby we create partial representations of the state space that allow us to identify invariances in the environment by looking at the same true state s through different perspectives.

Note that, POMDPs are normally used to model uncertain observations. That is, they are a generalization of MDPs where the true state is not observable. Here, the POMDP idea is used to model different views of a fully observable state space. Therefore, we do not seek to solve a POMDP problem, but rather we extend a regular MDP to get redundant hierarchical representations.

2.3 A CYCLOPHOBIC POLICY FOR HIERARCHICAL STATE REPRESENTATIONS

In the following, we describe how the cyclophobic intrinsic reward and the hierarchical state representations can be combined into a policy that exploits the cyclophobic inductive bias. For this, we define several Q-functions along the views, and combine them as a weighted sum. The weights are determined by counts of the observations in each observation set $\mathcal{O}^{V_i}$ which we explain next.

Mixing coefficients. Many strategies for defining mixing coefficients are possible. For concreteness, we follow in this paper a simple schema, where we determine the weights from the observation counts, which are obtained from the history of states visited throughout training,

$$\mathcal{H}_{\text{all}} = \{s_1, s_2, \ldots, s_T\}. \tag{6}$$

Note that $\mathcal{H}_{\text{all}}$ contains all states that have been visited in the training so far, which is different from the states in the episodic history $\mathcal{H}_{\text{episodic}}$ that was used in Sec. 2.1 to define cycles. Denoting the corresponding views of the history as $o_t^{V_i} = \mathcal{Z}^{V_i}(s_t)$, the counts for view V_i are

$$N(o_1^{V_i}), N(o_2^{V_i}), \ldots, N(o_T^{V_i}). \tag{7}$$

where N counts the number of times the observation $o_t^{V_i}$ has been encountered. The raw counts are normalized by their maximum (maximum for simplicity, other normalizations are possible), because the smaller views have higher counts than the bigger views. The weights should be large for states that have been seen less often, so we subtract the normalized counts from one,

$$\alpha_*^{V_i}(o_t^{V_i}) = 1 - \frac{N(o_t^{V_i})}{\max(N(o_1^{V_i}), N(o_2^{V_i}), \ldots, N(o_T^{V_i}))}. \tag{8}$$

The previous formula allows us to compute several weights for a single state s_t,

$$\alpha_*(s_t) = [\alpha_*^{V_1}(\mathcal{Z}^{V_1}(s_t)), \ldots, \alpha_*^{V_k}(\mathcal{Z}^{V_k}(s_t))] = [\alpha_*^{V_1}(o_t^{V_1}), \ldots, \alpha_*^{V_k}(o_t^{V_k})] \tag{9}$$

where $\alpha_*(s_t)$ is a vector. Finally, the softmax operator turns these weights into a vector of probabilities,

$$\alpha(s_t) = \text{softmax}(\alpha_*(s_t)) = [\alpha_1(s_t), \ldots, \alpha_k(s_t)]. \tag{10}$$

The entries of this vector are denoted by $\alpha_i(s_t)$ and are used to define the cyclophobic Q-function in the next paragraph. The definition of α can be extended to all state s by setting it to zero for unseen states, i.e. $\alpha(s) = 0$ (zero-vector) for $s \notin \mathcal{H}_{\text{all}}$.

In general, larger views in the hierarchy will have bigger entries in $\alpha(s_t)$ as the observations repeat less often than in the smaller views. Thus $\alpha(s_t)$ gives more weight to the larger views than the smaller ones. However, this is compensated by the cyclophobic intrinsic reward since it is triggered far more in the smaller views than the larger views.

Cyclophobic Q-function. To combine all views into a single global policy we define a mixture over the different Q-functions learned with the cyclophobic intrinsic reward as defined in Section 2.1. For view V_i, we define Q-function as

$$Q(o^{V_i}, a) \leftarrow (1 - \eta) Q(o^{V_i}, a) + \eta \left[r(o^{V_i}, a) + \gamma Q(o'^{V_i}, a') \right]. \tag{11}$$

This follows from our argumentation in Section 2.2, where we replace the state s in Equation 2 by the observations o^{V_i} in their respective views. Then we can define cyclophobic Q-function as the mixture of the Q-functions of each view,

$$Q_{\text{cycle}}(s, a) = \sum_i \alpha_i(s) Q(\mathcal{Z}^{V_i}(s), a) = \sum_i \alpha_i(s) Q(o^{V_i}, a). \tag{12}$$

Note that the mixing coefficients $\alpha_i(s_t)$ are only non-zero for states s_t that appeared in the global history $\mathcal{H}_{\text{all}}$. Thus the cyclophobic Q-function is zero for states $s \notin \mathcal{H}_{\text{all}}$ not encountered.

Cyclophobic policy. Finally, the cyclophobic policy is defined to the greedy action for the cyclophobic Q-function, i.e.

$$\pi(s) = \arg\max_a Q_{\text{cycle}}(s, a) = \arg\max_a \sum_i \alpha_i(s) Q(o^{V_i}, a). \tag{13}$$

Having normalized the counts within each view ensures comparability of the counts. This ensures that Q-values from rare observations i.e. more salient have a larger effect on deciding the action for the policy π. In an ablation study in Section 3 we show that the combination of the cyclophobic intrinsic reward and hierarchical state representations is crucial to the methods success.

3 EXPERIMENTS

Our experiments are inspired by Parisi et al. (2021) and Samvelyan et al. (2021). We test in environments where the causal structure is complex and the binding problem (Greff et al., 2020), (van Steenkiste et al., 2019) arises. That is, where some form of disentangled representation of the environments plays an important role for efficiently finding solutions.

Environments: We test our method on the MiniGrid and MiniHack environments:

- The MiniGrid environment (Chevalier-Boisvert et al., 2018) consists of a series of procedurally generated environments where the agent has to interact with several objects to reach a specific goal. The MiniGrid environments pose currently a benchmark for the sparse reward problem, since a reward is only given when reaching the final goal state.
- The MiniHack environment (Samvelyan et al., 2021) is a graphical version of the NetHack environment (Küttler et al., 2020). We select environments from the *Navigation* and *Skill* tasks. The MiniHack environment has a richer observation space by containing more symbols than the MiniGrid environments and a richer action space with up to 75 different actions. While not necessarily tailored to the sparse reward problem as the MiniGrid environment, the high state-action complexity makes it one of the most difficult environments for exploration.

State encoding: For both environments we choose five croppings of the original full view. The views V_1, V_2, V_3, V_4, V_5 are of grid size 9×9, 7×7, 5×5, 3×3 and 2×1. In principle we could also include the full view. However, in the experiments the performance was much better when we limit ourselves to the partial views. Intuitively, limiting the views allows the agent to ignore irrelevant details that are far away.

Next, the views are mapped to hash codes (we use the open source *xxhash* library). That is, we have a hash function g that maps observation $o_t^{V_i}$ to a hashcode $h_t^{V_i} = g(o_t^{V_i})$. This helps us to quickly check for cycles as we only need to check whether two hash codes are equal.

For the MiniHack environment, a text prompt is an integral part of the current state. So, for MiniHack, the hash code for a state is the concatenation of the hash codes of the observation $o_t^{V_i}$ and the text prompt m_t, where $m_t \in \mathbb{R}^k$ be an encoding of a string of length k, i.e.

$$h_t = g(o_t) + g(m_t). \qquad (\text{"+" denoting concatenation}) \qquad (14)$$

Training setup and baselines: We train each environment for three runs using different seeds for every run. For transfer learning we use "DoorKey" and MultiEnv("MultiRoom-N4-S5", "Key-CorridorS3R3", "BlockedUnlockPickup") for pretraining. We simply save the extrinsic rewards in a separate Q-table and set the values as starting values for the new Q-table at the start of transfer learning. The baselines for the MiniGrid experiments are provided by Parisi et al. (2021) and allow us to compare our method to C-BET (Parisi et al., 2021), Random Network Distillation (Ostrovski et al., 2017), RIDE (Raileanu & Rocktäschel, 2020) and ICM (Pathak et al., 2017). For the MiniHack environment we compare our results to the baselines presented by Samvelyan et al. (2021) which include IMPALA (Espeholt et al., 2018), RIDE (Raileanu & Rocktäschel, 2020) and Random Network Distillation (Burda et al., 2018). For the skill tasks the only available baseline is IMPALA (Espeholt et al., 2018).

Evaluation metric: While during learning the intrinsic reward based on cyclophobia plays the essential role, the ultimate goal is to maximize the extrinsic reward that is provided by the environment. Thus for comparison, we have to plot the extrinsic reward the agent receives for each episode. The reward ranges from 0 to 1. Note that these environments are considered to be solved, if one reaches an average extrinsic reward of at least 0.8.

3.1 MINIGRID

For applying our method to the MiniGrid environment we choose the training setup of Parisi et al. (2021). Figure 2 shows the agent's performance when training from scratch (rows three and six) and when transferring knowledge from pretrained environments (bottom three rows).

- **Learning from scratch** (rows three and six): In three out of six environments, our proposed method converges much faster than the competitors, including C-BET (Parisi et al., 2021). Note that for some environments our x-axis is shorter, since our method converges much faster. Only "KeyCorridorS3R3", "MultiRoom" and "ObstructedMaze-2Dlhb" pose significant challenges to our approach, because our method is tabular and thus can not deal with

Figure 2: **MiniGrid:** We converge faster than C-BET (Parisi et al., 2021) in many MiniGrid environments with and w/o pretraining. The hierarchical state representations and cyclophobic intrinsic reward is extremely quick to converge which shows efficient exploration and the usefulness of the cropped representations. Furthermore we are also able to transfer knowledge by pretraining on other environments.

too many object variations in the environment (e.g. random color changes). Furthermore, the "MultiRoom" environment proves challenging for all environments with only C-BET managing to reach convergence, while we are able to fetch some rewards. This is due to the large amount of observations the different corridors produce. In the Appendix A.1 our approach also excels in the "KeyCorridorS3R3', "ObstructedMaze-2Dlhb" and more difficult environments once we remove the colors, e.g. "KeyCorridorS4R3", "KeyCorridorS5R3", "KeyCorridorS6R3", "ObstructedMaze-1Q".

- **Transferring knowledge** (rows one, two, four and five): Having trained on one environment can we transfer knowledge to a different one? In some environments the transfer even improved the results from the "no transfer" setup (see "Unlock", "Doorkey", "UnlockPickup", "BlockedUnlockPickup", "ObstructedMaze-1Dlh") and never deteriorated performance.

3.2 MINIHACK

To push our approach to its limits, we also tackle some of the MiniHack environments which are diverse in the required skills.

- **Navigation task:** For the simpler navigation tasks show in Figure 3, our method converges quicker than intrinsic curiosity driven methods such as RIDE and RND. Especially, in the "River" environment, only our cyclophobic agent is able to converge and solve the

Figure 3: **MiniHack Navigation:** The agent converges quicker in the *Navigation* task than the intrinsic curiosity baselines such as RIDE (Raileanu & Rocktäschel, 2020) and Random Network Distillation (Burda et al., 2018). This corroborates our hypothesis, that avoiding cycles is essential for quick exploration.

Figure 4: **MiniHack Skill:** We converge quicker than IMPALA (Espeholt et al., 2018) in the *Skill* task. The *Skill* task defines over 75 different actions the agent must learn to use making it one of the most difficult set of environments of the MiniHack suite.

environment. However, of course there are environments such as "RoomUltimate" where our approach fails due to its tabular style, which limits the complexity of the environment.

- **Skill task:** For the *Skill* task the only available baseline is IMPALA which is not based on intrinsic curiosity. Here we are also vastly superior, even collecting extrinsic rewards when the baseline can not ("Wear" and "LockedDoor-Fixed").

3.3 LIMITATIONS

In some environments with a big number of different objects our method struggles to converge. Since our method is tabular, we do not have the observational invariances that methods based on function approximation learn and exploit (e.g. with CNNs). For instance, for these environments learned invariances allow them to handle differently colored objects. While our method does cope with avoiding redundancy through the cyclophobic intrinsic reward and the hierarchical state representations, it does not learn the kind of observational invariances neural networks do, which are sometimes necessary. However, note that we can show that reducing the number of colors for the "KeyCorridor" environment improves our performance as well dramatically (see Appendix A.1). Color reduction can also be seen as a cropped view of the real situation, and hence this experiment falls into our setup. Future work will explore the combination of our approach and neural networks.

Nonetheless, we argue that the above limitation does not lessen the impact of our work, since our method is able to compete with neural network based methods showing that exploration does not seem to rely solely on representation learning, but also on clever avoidance of repetition. Thus, when the number of different objects increases, better performance can be attributed to the learned invariances in a neural network reducing observational complexity, rather than to more efficient exploration. For this reason, intrinsic curiosity methods perform well in the "KeyCorridor" environment due to the large number of changes driving exploration.

3.4 ABLATION STUDY

To show the effectiveness of the cyclophobic intrinsic reward and the hierarchical state representations, we perform an ablation study. Figure 5 shows state counts as a heat map after 10,000 steps of training. We distinguish four cases:

- **epsilon-greedy:** Plain epsilon greedy exploration fails to find the goal in the bottom right.

Figure 5: **MiniGrid ablation study (visitation counts):** The cyclophobic Q-function explores the environment more efficiently than its count based and epsilon-greedy based counterparts. We record state counts for several variations of intrinsic reward and hierarchical state representations. Hierarchical state representations together with the cyclophobic intrinsic reward are the most efficient.

- **hierarchical:** We replace the cyclophobic intrinsic reward in equation (3) with a count-based intrinsic reward defined by $N(o_T^{V_i})^{-\frac{1}{2}}$, for view V_i. This improves the results but still fails.
- **cyclophobic:** Having a cyclophobic intrinsic reward calculated only on the largest view finds the goal.
- **cyclophobic & hierarchical:** The combination of hierarchical views and cyclophobic intrinsic rewards (as explained in Sec. 2.3) explores even more efficiently as can be seen in the left room where fewer steps are needed to leave it.

Figure 6: **MiniGrid ablation study (extrinsic reward):** Hierarchical state representations are crucial to performance in some environments. We see that the cyclophobic intrinsic reward is necessary to reach a successful trajectory at all. Only by using hierarchical state representations we achieve good performance.

In Figure 6 we analyze the impact of the hierarchical state representations on the agent's performance. The "UnlockPickup" environment can only be solved if hierarchical state representations are used. Due to the complexity of the environment and the large number of object variations, the different views allow for knowledge reuse and thus lead to better performance. Similarly, for the MiniHack "Room-Random" environment the cyclophobic intrinsic reward performs well. However adding hierarchical state representations leads to perfectly solving the environment.

4 RELATED WORK

Novelty search, count based and prediction error exploration: Our method combines several ideas from different exploration methods and strategies in reinforcement learning. While our method is based on avoiding redundancy, ultimately by doing this we determine a novel state-action pair. Exploration by determining state novelty is one of the most basic forms of exploration in reinforcement learning. In the simplest form this can be done by counting states i.e. determining a count $N(s, a)$ for each state-action pair (s, a). One way to do this is by approximating the counts via a density model as done by Ostrovski et al. (2017) and Bellemare et al. (2016). The real count $N(s, a)$ is then replaced by a pseudo-count $\hat{N}(s, a)$ which is modeled by some density. An important aspect to our method is the propagation of the cycle penalty, which has been explored by Choshen et al. (2018). They propose to propagate the visitation counts and show that this converges and leads to improved exploration. Savinov et al. (2018) try to incorporate a temporal component into the intrinsic reward by measuring

how far away states are from local memory i.e. buffer of states. Our method may be understood as achieving a similar effect, as propagating the cycle penalty introduces a sense of proximity to redundant states. The intrinsic curiosity module (ICM) by Pathak et al. (2017) and Burda et al. (2018) produces representations that only take into account what the agent can influence directly on a given transition (s, a, r, s', a'). Although our method is not prediction error based, it achieves something similar by cropping the observations to the smallest possible view effectively ignoring everything not immediate to the agent. Burda et al. (2018) produce fixed representations via a neural network with fixed parameters. These fixed representations are then compared to the output of a predictor network, where the resulting prediction error measures novelty. RIDE by Raileanu & Rocktäschel (2020) is a prediction error based method, where the prediction error between subsequent states is used as intrinsic reward. Thus the agent, is biased towards parts of the environment where transitions produce changes. Overall, prediction error methods require a model while our method is model-free.

Exploration by counting changes in observations: Instead of relying on the prediction error to measure state transition change, the changes in the observation space can be counted. Zhang et al. (2020) define an intrinsic reward for a count based approach by calculating the difference of visitation counts between subsequent states. This intrinsic reward pushes the exploration boundary as it provides a positive reward when reaching unexplored states for the first time or no reward otherwise. The mechanism to check novelty is extended through NovelD(Zhang et al., 2021). Interesting Object, Curious Agent by Parisi et al. (2021) is an intrinsic motivation method that splits up learning into a pretraining and transfer stage. It defines a count-based intrinsic reward called C-BET that is based on counting the amount of changes in a state transition (s, a, s'). In contrast, we use state counts to measure novelty in the respective hierarchical views.

Encoding observations to augment intrinsic reward: Encoding observations to either augment the intrinsic reward or to define goals has lead to great improvements in exploration. Language in the form of text prompts that define goals has been used by Mu et al. (2022) to augment the intrinsic reward. Singh Chaplot et al. (2020) build representations that reflect the structure, i.e. geometry of the environment. More generally, Ye et al. (2020) train an A2C (Mnih et al., 2016) agent on different croppings in a grid environment, without an intrinsic reward, with mixed results. Parisi et al. (2021) also augment the input by training on a 360° panoramic to learn task-agnostic changes. Our hierarchical state representations similarly augment the intrinsic reward and reveal structural invariances about the environment which aid exploration.

Generalization and transfer learning: The idea of learning representations of the environment that are reusable and can be transferred to other situations has been explored previously. Learning successor representations (Barreto et al., 2016) requires learning local environment dynamics that can be reused when the environment, i.e. the original distribution, is changed. "Universal Value Function Approximators" (Schaul et al., 2015) use Singular Value Decomposition on the learned action-value function to obtain a canonical representation of the environment which can be transferred to other situations. More recently, Parisi et al. (2021) learn an exploratory policy which is then combined with a task specific policy at transfer time. Our method likewise contains a task-agnostic component given by the cyclophobic intrinsic reward and a task-specific component given by the external reward.

5 CONCLUSION

Avoiding cycles allows the agent to quickly and systematically discard uninteresting state/action pairs which are repeated often. This makes our cyclophobic intrinsic reward a good inductive bias towards novelty that simultaneously encourages systematic exploration.

The ablation studies show that the cyclophobic intrinsic reward just for a single view is already powerful enough to solve complex environments. Adding hierarchical state representations leads to even better performance, as can be seen in the MiniGrid experiments. Moreover, the experiments for MiniGrid confirm the transferability of the learned bias to new environments. Here the hierarchical state representations are crucial, as otherwise in a tabular approach transferability could not be achieved.

Due to the tabular approach, environments with large object variation lead to convergence problems in our method. The more objects are present in a single view, the larger the state space becomes in a tabular setting. Neural networks, on the other hand, learn invariances that reduce the complexity of the state space. To address the convergence problems, future work will therefore focus on incorporating the hierarchical state representations into a neural network based architecture.

REFERENCES

André Barreto, Will Dabney, Rémi Munos, Jonathan J. Hunt, Tom Schaul, Hado van Hasselt, and David Silver. Successor Features for Transfer in Reinforcement Learning. *arXiv e-prints*, art. arXiv:1606.05312, June 2016.

Marc G. Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying Count-Based Exploration and Intrinsic Motivation. *arXiv e-prints*, art. arXiv:1606.01868, June 2016.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by Random Network Distillation. *arXiv e-prints*, art. arXiv:1810.12894, October 2018.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

Leshem Choshen, Lior Fox, and Yonatan Loewenstein. DORA The Explorer: Directed Outreaching Reinforcement Action-Selection. *arXiv e-prints*, art. arXiv:1804.04012, April 2018.

Rachit Dubey, Pulkit Agrawal, Deepak Pathak, Thomas L. Griffiths, and Alexei A. Efros. Investigating Human Priors for Playing Video Games. *arXiv e-prints*, art. arXiv:1802.10217, February 2018.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, Shane Legg, and Koray Kavukcuoglu. IMPALA: Scalable Distributed Deep-RL with Importance Weighted Actor-Learner Architectures. *arXiv e-prints*, art. arXiv:1802.01561, February 2018.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the Binding Problem in Artificial Neural Networks. *arXiv e-prints*, art. arXiv:2012.05208, December 2020.

Heinrich Küttler, Nantas Nardelli, Alexander H. Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The NetHack Learning Environment. *arXiv e-prints*, art. arXiv:2006.13760, June 2020.

Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous Methods for Deep Reinforcement Learning. *arXiv e-prints*, art. arXiv:1602.01783, February 2016.

Jesse Mu, Victor Zhong, Roberta Raileanu, Minqi Jiang, Noah Goodman, Tim Rocktäschel, and Edward Grefenstette. Improving Intrinsic Exploration with Language Abstractions. *arXiv e-prints*, art. arXiv:2202.08938, February 2022.

Georg Ostrovski, Marc G. Bellemare, Aaron van den Oord, and Remi Munos. Count-Based Exploration with Neural Density Models. *arXiv e-prints*, art. arXiv:1703.01310, March 2017.

Simone Parisi, Victoria Dean, Deepak Pathak, and Abhinav Gupta. Interesting Object, Curious Agent: Learning Task-Agnostic Exploration. *arXiv e-prints*, art. arXiv:2111.13119, November 2021.

Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven Exploration by Self-supervised Prediction. *arXiv e-prints*, art. arXiv:1705.05363, May 2017.

Roberta Raileanu and Tim Rocktäschel. RIDE: Rewarding Impact-Driven Exploration for Procedurally-Generated Environments. *arXiv e-prints*, art. arXiv:2002.12292, February 2020.

Mikayel Samvelyan, Robert Kirk, Vitaly Kurin, Jack Parker-Holder, Minqi Jiang, Eric Hambro, Fabio Petroni, Heinrich Küttler, Edward Grefenstette, and Tim Rocktäschel. MiniHack the Planet: A Sandbox for Open-Ended Reinforcement Learning Research. *arXiv e-prints*, art. arXiv:2109.13202, September 2021.

Mikayel Samvelyan, Robert Kirk, Vitaly Kurin, Jack Parker-Holder, Minqi Jiang, Eric Hambro, Fabio Petroni, Heinrich Kuttler, Edward Grefenstette, and Tim Rocktäschel. Minihack the planet: A sandbox for open-ended reinforcement learning research. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021. URL https://openreview.net/forum?id=skFwlyefkWJ.

Nikolay Savinov, Anton Raichuk, Raphaël Marinier, Damien Vincent, Marc Pollefeys, Timothy Lillicrap, and Sylvain Gelly. Episodic Curiosity through Reachability. *arXiv e-prints*, art. arXiv:1810.02274, October 2018.

Tom Schaul, Daniel Horgan, Karol Gregor, and David Silver. Universal value function approximators. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1312–1320, Lille, France, 07–09 Jul 2015. PMLR. URL `https://proceedings.mlr.press/v37/schaul15.html`.

Mathieu Seurin, Florian Strub, Philippe Preux, and Olivier Pietquin. Don't Do What Doesn't Matter: Intrinsic Motivation with Action Usefulness. *arXiv e-prints*, art. arXiv:2105.09992, May 2021.

Devendra Singh Chaplot, Ruslan Salakhutdinov, Abhinav Gupta, and Saurabh Gupta. Neural Topological SLAM for Visual Navigation. *arXiv e-prints*, art. arXiv:2005.12256, May 2020.

Sjoerd van Steenkiste, Klaus Greff, and Jürgen Schmidhuber. A Perspective on Objects and Systematic Generalization in Model-Based RL. *arXiv e-prints*, art. arXiv:1906.01035, June 2019.

Chang Ye, Ahmed Khalifa, Philip Bontrager, and Julian Togelius. Rotation, Translation, and Cropping for Zero-Shot Generalization. *arXiv e-prints*, art. arXiv:2001.09908, January 2020.

Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E. Gonzalez, and Yuandong Tian. BeBold: Exploration Beyond the Boundary of Explored Regions. *arXiv e-prints*, art. arXiv:2012.08621, December 2020.

Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E. Gonzalez, and Yuandong Tian. Noveld: A simple yet effective exploration criterion. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL `https://openreview.net/forum?id=CYUzpnOkFJp`.

A FURTHER ABLATION STUDIES

A.1 OBSERVATIONAL COMPLEXITY - REMOVING COLOR FROM OBSERVATIONS

To test our theory of observational complexity affecting our performance in some environments such as "KeyCorridor" and "ObstructedMaze-2Dlhb", we remove color from objects in the environment such that the underlying task is not affected. In case of "KeyCorridor" and "MultiRoom" colors can be removed from all objects, while in the "ObstructedMaze" environments we only remove color of the key and door. We show the results in figures 7, 8 and 9.

Figure 7: When extracting color from the hierarchical state representations we are able to converge very quickly in the "KeyCorridorS3R3" and "ObstructedMaze-2Dlhb" environments. Doing this for the MultiRoom-N6 environment does not have such a large effect as here the large variation in observation is due to the many different corridors, which our tabular method cannot find observational invariances for as a neural network could.

Figure 7 shows that this has an immediate impact on the performance where the "KeyCorridorS3R3" environment converges instantly while the "ObstructedMaze-2Dlhb" environment needs very few steps to converge in comparison to C-BET. For the MultiRoom-N6 environment, the observational complexity comes from the different types of corridors present throughout training, thus removing color only mitigates the observational complexity to some extent. This corroborates our theory that while our method is very good at exploration, its tabular nature cannot capture the observational invariances that neural networks naturally do.

Figure 8: Our agent can even gather rewards successfully in much larger KeyCorridor environments when removing colors, showing that the exploration mechanism is very strong.

In Figure 8 we test more difficult "KeyCorridor" environments. We can see that the cyclophobic reinforcement learning is also able to explore efficiently in these harder environments when colors are removed.

Figure 9: For the more difficult "ObstructedMaze" environments the agent is able to solve the "1Q" version. The other more larger variants prove too complex even when removing colors.

Finally, we test more complex "ObstructedMaze" environments in Figure 9. While we achieve good performance in the "1Q" variant, the other larger variants remain too complex for the cyclophobic agent.

Note that when training the other methods without colors their performance may improve. However, this ablation study simply illustrates that our method is very good at exploring and is only held back by its tabular nature. In future work we want to find the best way to learn observational invariances with the hierarchical state representations and the cyclophobic intrinsic reward.

B ENVIRONMENT DETAILS

B.1 MINIGRID EXPERIMENTS

Figure 10: An overview of the MiniGrid environments used in this paper.

We test on some of the same environments as Parisi et al. (2021). In the following we describe the environments as Parisi et al. (2021) and add our own comments where relevant.

- **Unlock**: pick up the key and unlock the door. (288 steps per episode)
- **DoorKey-8x8:** pick up the key, unlock the door, and go to green goal (640 steps per episode)
- **KeyCorridorS3R3:** pick up the key, unlock the door, and pick up the ball (only the door before the ball is locked) (270 steps per episode).
- **UnlockPickup:** pick up the key, unlock the door, and open the box (288 steps per episode).
- **BlockedUnlockPickup:** pick up the ball in front of the door, drop it somewhere else, pick up the key, unlock the door, and open the box (576 steps per episode).
- **ObstructedMaze-1Dlh:** open the box to reveal the key, pick it up, unlock the door, and pick up the ball (288 steps per episode).
- **ObstructedMaze-2Dlh:** same as above, but with two doors to unlock (576 steps per episode).
- **ObstructedMaze-2Dlhb:** same as above, but with two balls in front of the doors (like in BlockedUnblockPickup) (576 steps per episode).

- **MultiRoom-N6:** navigate through six rooms of maximum size ten and go to the green goal (all doors are already unlocked) (120 steps per episode).
- **MultiRoom-N12-S10:** navigate through twelve rooms of maximum size ten and go to the green goal (all doors are already unlocked) (120 steps per episode).

B.2 MINIHACK EXPERIMENTS

Figure 11: An overview of the Minihack environments tested in this paper. The top row shows the *Navigation* tasks, while the bottom row shows the *Skill* tasks.

We perform experiments inspired by the baselines from Samvelyan et al. (2021). Here, Samvelyan et al. (2021) define a set of navigation and skill acquisition tasks. The navigation tasks range from requiring the agent to navigate an empty room or maze, up to navigating environments with monsters and hazards. The skill acquisition tasks require the agent to perform a certain set of skills to be able to solve the environments.

B.2.1 NAVIGATION TASKS

In the following we describe the environments used from the navigation task.

- **Room-Random-15x15:** This task is set in a single square room, where the goal is to reach the staircase down. In the random version of this task, the start and goal positions are randomized.
- **Room-Dark-15x15:** Same as Room-Random, but the agent only sees parts of the environment it has already discovered.
- **KeyRoom-S5:** These tasks require an agent to pick up a key, navigate to a door, and use the key to unlock the door, reaching the staircase down within the locked room. The locations of the door, key and starting position are randomized.
- **River:** The river environment requires the agent to cross a river using boulders. When pushed into the water, they create a dry land to walk on, allowing the agent to cross it.

B.2.2 SKILL TASKS

The nature of commands in NetHack requires the agent to perform a sequence of actions so that the initial action, which is meant for interaction with an object, has an effect. The exact sequence of subsequent can be inferred by the in-game message bar prompts. Overall, in each of the following tasks the agent has to perform a sequence of actions that allow the agent to perform the required skill.

- **Eat:** The agent has to navigate and eat an apple. Doing so requires a sequence of actions and confirming a prompt to eat the appe.
- **Pray:** The agent has to pray on an altar. This is more complex than eating an apple as praying requires the agent to confirm more prompts.
- **Wear:** The agent has to wear armor. This is a more difficult task than the previous tasks.

- **LockedDoor-Fixed:** The agent has to kick a locked door.
- **Wand of Death-Easy:** The agent starts with a wand of deatch in its inventory and has to zap it towards a sleeping monster. That is, the agent needs to equip the wand of death walk to the monster and zap it.

In all of these environments the positions of the agent and of the object that has to be interacted with are randomised. Furthermore, the complexity is also increased by the confirmation prompts the agent has to answer in order to perform a certain action.

C EXPERIMENTAL DETAILS

C.1 HYPERPARAMETERS

Common hyperparameters: In the following we present a table with all hyperparameters used for training the environments. In general, our method has very few hyperparameters. In this case the only really tunable hyperparameters are the step size η, the random action selection coefficient ϵ for epsilon-greedy exploration and the discount γ:

η	γ	Num. views
0.2	0.99	5

In our case we determined experimentally that 5 views is a good number of views for training an agent.

Epsilon-greedy parameter ϵ: While learning with the cyclophobic intrinsic reward we still perform random action from time to time by having an epsilon-greedy action selection. That is, the agent samples a value n from a uniform distribution and selects a random action if this $n < \epsilon$. These are the settings for ϵ for the respective environments:

Environments	ϵ
Unlock	0.1
DoorKey	0.1
KeyCorridor	0.1
UnlockPickup	0.3
MultiRoom-N6	0.1
MultiRoom-N12-S10	0.1
BlockedUnlockPickup	0.3
ObstructedMaze-1Dlh	0.3
ObstructedMaze-2Dlh	0.1
ObstructedMaze-2Dlhb	0.3

Intrinsic reward tradeoff ρ: For the "ObstructedMaze-2Dlh" and "BlockedUnlockPickup" environments we set intrinsic reward tradeoff $\rho = 0.2$. This has as effect that the extrinsic reward gets propagated more when the agent encounters it, which is necessary for more complex environments. For all other tested environments we set $\rho = 1$, thus not weighting the intrinsic reward at all.

C.2 PLOT SMOOTHING

For all we show the mean reward and standard deviation smoothed over a sliding window. For our and Samvelyan et al. (2021) we use a sliding window of 50000 steps. On the other hand for the experiments in Parisi et al. (2021) we use a sliding window of 96000 steps as per their experimental setup.