[Reproducibility Report]
Double-Hard Debias: Tailoring Word Embeddings for Gender Bias Mitigation

Reproducibility Summary

Scope of Reproducibility

Our goal was to reproduce the original paper's central claim that projecting away the word-frequency direction(s) in word embeddings improves the debiasing performance of the well-known Hard Debias algorithm. The objectives were to first verify that such word-frequency direction(s) exist and then verify removing these direction(s) decreases bias without significantly affecting the embeddings' utility.

Methodology

We were able to use the author's supplied code and raw data as a starting point, though several modifications and additions were inserted into the code to replicate the author's full data pipeline. Specifically, we needed to insert code to export intermediate data files between Jupyter notebooks. In terms of computational resources, we were able to execute all of the code on our local laptop machines after installing specified software dependencies.

Results

We were able to reproduce the author's findings that suggest the existence of a word-frequency direction. Specifically, we confirmed that with GloVe embeddings, the second principle component corresponds with the word-frequency direction.

However, we were only able to partially show that projecting away the word-frequency direction improved de-biasing. Our de-biased embeddings contained more bias than the embeddings reported in the original paper. A gender classifier trained on our top-100 most biased words reported 66.5% accuracy while the authors reported 51.5%. That said, we verified that the de-biased embeddings preserved semantics and matched these results exactly.

What was easy

The author's provided much of the code required so re-constructing the data pipeline was not very challenging.

What was difficult

The main difficulty involved identifying precisely where our results began to diverge with the authors'. In the end we were able to reproduce the analogy metrics but not the classification accuracy values. Because there was limited logging in the Jupyter notebook it was difficult to determine why our embeddings were more biased.

Communication with original authors

We were in communication with Tianlu, the primary author, on several occasions. Tianlu provided timely responses that confirmed our approach matched the description laid out in the paper. In the end, we were not able to collectively determine the cause behind the divergence in results. However, our findings do reproduce the qualitative finding that a word-frequency direction exists.

1 Introduction

In this reproducibility report, we detail our experience reproducing the paper titled "Double-Hard Debias: Tailoring Word Embeddings for Gender Bias Mitigation", which was published at ACL 2020. The paper's main claim is that the existing, well-known word embedding debiasing technique known as Hard Debias can be improved with an additional pre-processing step that removes the word-frequency direction, hence the naming "Double-Hard Debias". Previous studies have identified that word-embeddings are skewed by the frequency with which words appear in the training data set. Subsequently, the Double-Hard-Debias authors posit that projecting away the word-frequency direction will improve downstream de-baiasing algorithms that identify and remove the gender direction. In their results, the authors demonstrate that their proposed pre-processing technique succeeded in decreasing bias without sacrificing utility.

2 Scope of reproducibility

The findings introduced in the previous section can be categorized into three claims presented in the Double-Hard Debias paper:

1. Word-frequency direction(s) can be identified among the word embeddings' principle components.

2. Hard Debias will achieve better performance once the word-frequency direction(s) have been projected away.

3. Double-Hard debiased embeddings will still perform similarly well as Hard Debiased embeddings on semantic tests.

In reproducing the paper's central claims, we mapped each claim to tables and figures in the original paper. Specifically, claim 1 corresponded to reproducing Figure 2; claim 2 corresponded with Table 3 and Figure 3; and claim 3 corresponded with Tables 2 and 4. At the same time, it is worth mentioning the findings in the paper that were not within the scope of our reproducibility effort. Below, we list the findings that were not within the scope of our replication as well as our reasoning for excluding them:

- We did not reproduce Figure 1 in the original paper, which demonstrates that the gender direction vectors changed significantly after removing the word-frequency direction. We did not reproduce this figure because the code was not provided for the visualization and the findings suggested in this figure can also be uncovered from the classification accuracies.

- The coreference resolution results in Table 1 were also beyond the scope of this report. After consulting with the authors, we discovered that the coreference code exceeded our computing resources. Furthermore, the substantive results can also be shown through the classification ac accuracies.

- The original paper compares Double-Hard Debias embeddings against not just the Hard Debias embeddings but also a handful of other benchmark embeddings. Because the authors did not generate these embeddings themselves, we did not reproduce the metrics associated with these benchmark embeddings. Instead, we focused on comparing the Double-Hard Debiased embeddings against the Hard Debiased embeddings.

3 Methodology

3.1 Code and Data

We were able to reconstruct the majority of the data pipeline by forking the authors' Github repository[1]. In terms of verifying each of the claims, we needed to execute the Jupyter notebook `GloVe_Debias.ipynb` for claim 1 and then `Glove_Eval.ipynb` for claims 2 and 3. The authors also provided the raw GloVe embeddings data through a download link in the README. Of the various data files provided, we downloaded `vectors.txt`, which are simply the raw GloVe embeddings, and placed this file into the `/data` directory.

In order to successfully execute the pipeline end-to-end however, we had to make several minor changes to the provided code. First, the provided code did not save the intermediate de-biased output from `Glove_Debias.ipynb` to a data file. So, we inserted commands to pickle the de-biased embeddings. Second, the Word Embeddings Benchmark dependency required manual setup during the installation process. In addition to modifying the file paths in the dependency code, we downloaded the analogy metadata text files directly from source as we encountered issues with the auto-download feature[2]. Finally, the author's code did not provide all WEAT scores, so we expanded the tests to provide all metrics.

---

[1]`https://github.com/uvavision/Double-Hard-Debias`
[2]Additional details included in our README

Table 1: Comparison WEAT Scores Between Original and Reproduced Embeddings

Embedding	Version	Career (d)	Career (p)	Math (d)	Math (p)	Science (d)	Science (p)
GloVe	Original	1.81	0	0.55	0.14	0.88	0.04
	Reproduced	1.81	0	0.55	0.14	0.88	0.04
Double-Hard	Original	1.53	$2e^{-4}$	0.09	0.57	0.15	0.61
	Reproduced	1.53	$2e^{-4}$	0.09	0.57	0.15	0.61

Table 2: Comparison of Gender Classification Scores for Top-K Gendered Words

Embedding	Version	Top 100	Top 500	Top 1000
GloVe	Original	100	100	100
	Reproduced	100	100	100
Double-Hard	Original	51.5	55.5	59.5
	Reproduced	66.5	74.1	70.4

3.2 Computational requirements

The two Jupyter notebooks executed on the GloVe embeddings were computationally inexpensive. We were able to execute each notebook in under 10 minutes on our Macbook Air laptops. However, it should be noted that the authors did report findings based on Word2Vec in their Supplemental Materials. While these results were not within our reproducibility scope, we found that executing the same notebooks on the Word2Vec embeddings was not feasible on our laptops. Furthermore, the most computationally expensive portion of the data pipeline, in our experience, was executing the analogy tests in the evaluation notebook.

4 Results

We were able to generate Double-Hard debiased word embeddings using code provided. Though our embeddings did not exactly match those that the authors released, they performed qualitatively similarly in terms of removing bias but also performing well on semantic benchmarks. In this section we compare the performance of our reproduced Double-Hard debiased word embeddings against the results reported in the paper. For all experiments, we also reproduced the results the authors reported for raw GloVe embeddings. These results were based on the unmodified, standard GloVe embeddings, so we had a greater expectation that our evaluation metrics would match those in the original paper.

In our efforts to reproduce the Double-Hard debiasing results, we generated word embeddings that were more biased than those reported in the paper. The paper evaluated the debiased word embeddings with two sets of tests: WEAT and classification accuracy. Table 1 contains the WEAT scores reported in the paper as well as score for our reproduced embeddings (green when equal to the original, and red otherwise). When we evaluated the raw GloVe embeddings as well as those we generated with the author's debiasing code, we were able to match the WEAT scores for both sets of embeddings. However, the gender classification scores for our Double-Hard embeddings were higher than those reported in the paper, as shown in Table 2. Regardless of the sample size, our classification accuracy was at least 10 percent greater than the paper's values, indicating the reproduced embeddings were more biased. This finding is supplemented in Figure 1 which shows the t-SNE clustering plots for our reproduced Double-Hard debiased embeddings against the plot in the paper. The t-SNE plots confirm that in our embeddings, the male and female words are much more separable.

There are several possible explanations for why our Double-Hard debiased embeddings are more biased than those described in the paper. Our leading hypothesis is that the authors performed additional PCA projections. In the paper, the authors describe the Double-Hard pre-processing as simply projecting away the second principal component. With the author's code we are able to confirm that the second component is the most optimal component to project away, but the provided code does not show the projection itself.

Interestingly, even though the Double-Hard debiased embeddings that we generated were more biased than those the authors created, the two versions performed exactly the same on the analogy and categorization benchmark tests. Table 3 includes the benchmark scores for our GloVe and Double-Hard debiased embeddings as well as the scores in the paper. Given the fact that the scores match, we can conclude that our embeddings perform just as well on standard word-embedding applications as the authors' embeddings. Of note, we found discrepancies in the evaluation metrics

Table 3: Performance of Original vs. Reproduced Embeddings on Benchmarks

Embedding	Version	Sem	Syn	Total	MSR	AP	ESSLI	Battig	BLESS
GloVe	Original	80.5	62.8	70.8	54.2	55.6	72.7	51.2	81
	Reproduced	80.5	62.8	70.8	54.2	58.9	72.7	49.6	81
Double-Hard	Original	80.9	61.6	70.4	53.8	59.6	72.7	46.7	79.5
	Reproduced	80.9	61.6	70.4	53.8	58.4	75	48.1	80

for the raw GloVe embeddings, specifically on the AP and Battig categorization tests. Our best explanation is that the authors uploaded a newer version of GloVe vectors to their data repository after publishing the paper earlier this year.

5 Discussion

We were able to verify claims 1 and 3 in our original reproducibility roadmap while the experiments for claim 2 did not match precisely. Even though we were not able to match all of the results for claim 2, overall, replicating the results in this paper was made much simpler due to the code and documentation that the authors provided. All of the results were contained within two Jupyter notebooks and the scripts were not computationally expensive. Given further resources, we would aim to reproduce the findings that we excluded from the scope of this report.

5.1 What was easy

The author's provided much of the code required so replicating the data pipeline was not very challenging. It was helpful that most of the code was written in a modular, organized, and efficient way. For this reason, it was not difficult to make simple changes to the code. It was also helpful that the authors specified which dependencies to install.

5.2 What was difficult

The main difficulty involved identifying precisely where our results began to diverge with the authors'. In the end we were able to reproduce the analogy metrics but not the classification accuracy values. Because there was limited logging in the Jupyter notebook it was difficult to determine why our embeddings were more biased.

5.3 Communication with original authors

We were in communication with Tianlu, the primary author, on several occasions. Tianlu provided timely responses that confirmed our approach matched the description laid out in the paper. Tianlu was able to advise us that the coreference results would require significant computational investments, which directed our efforts. In terms of debugging the slight differences we noticed in the classification accuracies we were not able to collectively determine the cause behind the divergence in results. Based on our discussion, we believe that the differences may be due to missing random seeds in the code, or, the most biased words, a crucial subset, differed between the original paper and our replication. However, our findings do reproduce the qualitative finding that a word-frequency direction exists.

(a) Original   (b) Reproduced

Figure 1: Comparing original vs reproduced embedding t-SNE clustering using Double-Hard