Where does Absolute Position come from in decoder-only Transformers?

Abstract

RoPE-trained transformers distinguish absolute position in their attention patterns, even though RoPE encodes only relative offsets in the inner product. We trace this leakage to two architectural components, The causal mask is responsible for the first: its per-query softmax denominator depends on the absolute query position by construction. The residual stream supplies the second. Under causal attention the activation at position 0 attends only to itself and runs as a closed dynamical system from the embedding of the token at that position; downstream attention reads this trajectory through sink-reading heads. Both components appear in all three architectures we study, in architecturally specific balance: NTK scaling suppresses the residual-stream component, sliding-window attention allows it to accumulate with depth, and standard RoPE sits between. Replacing the BOS embedding before the forward pass removes 40% of the residual-stream component at early queries. Attention sinks are token-anchored stabilizers that pass forward a deterministic fingerprint of the token at position 0, constant across inputs when that token is the auto-prepended BOS and varying with it otherwise.

1 Introduction

Decoder-only transformers trained with rotary position embeddings (Su et al., 2024) compute attention through inner products that, by construction, depend on the difference $i - j$ of the two positions. A model trained under this design should be unable to distinguish a token at position 50 from the same token at position 100 except through its relations to other tokens. RoPE-trained models make this distinction readily; their attention patterns carry traces of absolute position not predictable from relative offset alone (Kazemnejad et al., 2023; Ruscio et al., 2025). The relative encoding leaks though: our concern in this paper is where the leakage comes from and by what mechanism it arrives at the attention computations that consume it.

A natural first guess identifies the attention sink as the locus. Sinks are the token that marks the start of the sequence that absorb a large share of attention from every query (Xiao et al., 2024; Gu et al., 2025), they are visited globally, appear early in the network, and from the outside have the appearance of aggregators. We find that sinks carry no decodable content. The positions with the highest attention magnitude have topic-probe accuracy at chance; the positions decodable above chance have attention magnitudes three orders of magnitude smaller. The sink is a token-anchored feature: moving the BOS token from position 0 to position 8 moves the sink with it, and replacing BOS with a random uncommon token suppresses the sink entirely. Sink-reading heads pass the identity of the sink token to downstream attention: in models that auto-prepend BOS this signal is constant across inputs, in Qwen it varies with whatever token sits at position 0.

The leakage has two architectural sources. The causal mask supplies one: its per-query softmax denominator depends on the absolute query position by construction, regardless of what the logits encode. The residual stream supplies the other: position-varying activations flow into queries and keys, and RoPE rotation does not fully obscure them. We isolate the two components through ablations of the attention computation, and find both present in all three architectures we study, in architecturally specific balance. The residual-stream component itself traces to a single mechanism. Under causal attention, position 0 attends only to itself; the activation at position 0 at every layer is a deterministic function of the embedding of the token there.

2 Related Work

Attention sinks Xiao et al. (2024) identified at-

tention sinks as a stable feature of decoder-only transformers and exploited them in StreamingLLM to maintain quality under context truncation. Gu et al. (2025) characterized the training dynamics under which sinks emerge. Ruscio et al. (2026) analyzed sinks as a geometric reference frame for downstream attention. Whether sinks function as information aggregators or as content-free stabilizers has remained ambiguous in the literature; our results support the latter reading and identify token-anchoring rather than position-anchoring as the empirical signature.

Positional encodings RoPE (Su et al., 2024) encodes position through relative offsets in the inner product, and has become the dominant choice in open-source language models. The design property of Equation 2 has nevertheless been shown to leak: Kazemnejad et al. (2023) demonstrated that the choice of positional encoding affects length-generalization in ways the relative-only design does not predict, and Ruscio et al. (2025) documented absolute-position structure in attention patterns of RoPE-trained models. ALiBi (Press et al., 2021) and the NTK-/YaRN-style extensions (Peng et al., 2024) modify position encoding to address length-generalization specifically. Our work locates the leakage downstream of the inner product, in the softmax normalization rather than in RoPE itself.

Causal masking and mechanistic interpretation Haviv et al. (2023) showed that decoder-only transformers trained without explicit positional encodings can still solve sequence tasks, attributing the residual position signal to the asymmetry the causal mask introduces. Our work identifies the mechanism more precisely: the position-dependent cardinality of the per-query softmax denominator, isolated by the bidirectional ablation. On the interpretability side, the targeted-ablation literature has localized many model behaviors to specific heads, circuits, or low-rank directions (Olsson et al., 2022; Wang et al., 2023). The absolute-position structure we study resists this kind of localization across two separate intervention families, consistent with a mechanism that lives in the normalization rather than in any weight.

3 Background and the leakage metric

RoPE applies a position-dependent rotation to queries and keys without modifying the residual stream from which they are derived. For a head

with head dimension d_h and unrotated query and key $q_m, k_n \in \mathbb{R}^{d_h}$, RoPE multiplies each by a block-diagonal orthogonal matrix

$$R(m) = \text{diag}\big(R_2(m\theta_0),\ R_2(m\theta_1),\ \ldots,\ R_2(m\theta_{d_h/2-1})\big),$$
(1)

with $R_2(\phi)$ the standard 2×2 rotation and $\theta_i = \text{base}^{-2i/d_h}$. Because $R(m)^\top R(n) = R(n-m)$, the rotated inner product

$$\langle R(m)\,q_m,\ R(n)\,k_n \rangle\ =\ q_m^\top R(n-m)\,k_n \quad (2)$$

depends on the two absolute positions only through their difference. This is the design property of RoPE.

The post-softmax weight is a function of the entire row of logits and the attention mask. Under causal masking,

$$a_{ij}\ =\ \frac{\exp(\ell_{ij})}{\sum_{k=0}^{i}\exp(\ell_{ik})}, \qquad j \le i, \qquad (3)$$

with denominator Z_i summing over $i+1$ terms. The cardinality of Z_i depends on the absolute query position, and the post-softmax weight inherits a dependence on i not present in the logits. Bidirectional masking sums over T terms regardless of the query. Equation 3 therefore supplies absolute-position structure to attention weights independent of any property of the residual stream or the rotation schedule. The residual stream supplies a second contribution: if $x_m^{(L)}$ has acquired through previous layer writes a component that varies with m, that component flows into $q_m = W_Q^{(L,h)} x_m^{(L)}$ and into every attention logit the head computes.

A naive linear-in-offset model of absolute-position leakage has two problems. The predictors i, j, and $i-j$ are linearly dependent. RoPE's contribution to the inner product is a sum of cosines at the head's frequency-dependent angles, so a linear baseline underfits and attributes relative-offset variance to absolute position. We use a saturated relative-offset baseline. The baseline predicts $\ell_{ij} = f(i-j) + \varepsilon$ with f fit as one free parameter per distinct value of $i-j$. The full model adds mean-centered i and j as continuous predictors. Absolute-position leakage is

$$\Delta R^2(L,h)\ =\ R_{\text{full}}^2(L,h) - R_{\text{base}}^2(L,h). \quad (4)$$

A head with $\Delta R^2 > 0$ has access to absolute-position information that did not arrive through Equation 2.

The two architectural sources of ΔR^2 are operationally separable. Under bidirectional attention the cardinality of the softmax denominator is constant across queries and the causal-mask contribution vanishes; whatever ΔR^2 survives the bidirectional ablation comes from the residual-stream component alone. We therefore write

$$\Delta R^2_{\text{baseline}} = \Delta R^2_{\text{causal-mask}} + \Delta R^2_{\text{residual}}$$
$$\Delta R^2_{\text{residual}} = \Delta R^2_{\text{bidirectional}} \quad (5)$$

with the causal-mask share given by $1 - \Delta R^2_{\text{bidirectional}}/\Delta R^2_{\text{baseline}}$[1].

The causal-mask component Under the design property of Equation 2, attention logits depend only on relative offset: $\ell_{ij} = f(i - j)$ for some function f. Substituting into Equation 3 gives

$$a_{ij} = \frac{\exp\big(f(i-j)\big)}{Z_i}, \qquad Z_i = \sum_{d=0}^{i} \exp\big(f(d)\big). \quad (6)$$

The numerator depends on i and j only through their difference; the denominator is the partial sum of $\exp(f(d))$ up to $d = i$, which depends explicitly on i. If $\sum_{d=0}^{\infty} \exp(f(d))$ converges, Z_i approaches its limit at a rate set by the tail of f and the position dependence of a_{ij} attenuates as i grows. The bidirectional ablation replaces the upper limit i in Z_i with the constant $T - 1$ for every query.

The position-0 trajectory Under causal attention, position 0 attends only to itself. The per-layer update at position 0 reduces to

$$x_0^{(\ell+1)} = \text{FFN}_\ell\big(x_0^{(\ell)} + W_O^{(\ell)} W_V^{(\ell)} x_0^{(\ell)}\big), \quad (7)$$

---

[1]Equation 5 treats $\Delta R^2_{\text{baseline}}$ as the sum of two components and identifies $\Delta R^2_{\text{bidirectional}}$ with the residual-stream component. The additivity is an assumption, under the design property of Equation 2, the two components have orthogonal origins: the causal-mask contribution arises from the i-dependent cardinality of Z_i regardless of what f is, and the residual-stream contribution arises from departures of ℓ_{ij} from the relative-only form. Bidirectional ablation changes the cardinality of Z_i but leaves the unrotated query/key structure intact at first order, so $\Delta R^2_{\text{bidirec}}$ measures the residual-stream contribution under the same residual-stream content the causal forward pass produces. The assumption can fail if removing the causal mask materially changes the activations the network computes on the same input through, for example, layer-norm feedback; we do not retrain, so the weights are fixed, but the forward pass is different. We treat additivity as approximate and check it indirectly: identity-RoPE and scrambled-RoPE produce nearly identical ratios in every model (Table 6), as expected if the two RoPE-disabling interventions act on a single residual-stream contribution rather than on a quantity that interacts with the causal-mask contribution.

a map that depends on $x_0^{(\ell)}$ alone. The trajectory $e_0 \to x_0^{(0)} \to x_0^{(1)} \to \cdots$ is a closed dynamical system from the embedding e_0. Two consequences follow. The activation $x_0^{(\ell)}$ at every layer is a fixed function of e_0 across prompts. Any downstream head that reads from position 0 reads a deterministic function of the token at position 0. Section 5.7 confirms both empirically.

4 Methodology

We analyze Llama-3.2-1B (Grattafiori et al., 2024) ($L = 16$, $H = 32$, standard RoPE, auto-prepends BOS), Qwen-2.5-3B (Hui et al., 2024) ($L = 36$, $H = 16$, NTK-scaled RoPE, no BOS), and Mistral-7B-v0.3 (Jiang et al., 2023) ($L = 32$, $H = 32$, sliding-window). The scaling analysis additionally uses Llama-3.2-3B and Llama-3.1-8B. The mechanism-ablation, refined-binning, layer-wise, and position-0 analyses use Llama-3.2-3B in place of 1B. Corpus: $P = 64$ Wikipedia chunks balanced across four topics, tokenized to $T = 256$. The length-scaling analysis runs the same corpus at sixteen lengths between 56 and 768 tokens.

At each (ℓ, k) we compute the sink magnitude $\mathcal{S}(\ell, k) = \max_h \frac{1}{P(T-k)} \sum_{p, q \geq k} a_{q,k}^{(\ell, h, p)}$ and the topic decodability $\mathcal{A}(\ell, k)$, the mean five-fold cross-validated accuracy of a logistic regression on $x_k^{(\ell, p)}$ after PCA reduction to 64 components; chance is 0.25. For $\Delta R^2(\ell, h)$ we sample $K = 4{,}000$ stratified causal pairs, fit both regressions in double precision, and implement the saturated baseline as one-hot indicators on distinct $i - j$. Significance is assessed against a permutation null with $B = 500$ resamples per head, with Benjamini-Hochberg FDR at $\alpha = 0.05$.

Sink-variant and cosine analyses Three corpus variants dissociate position- from token-anchoring of the sink: *shifted* moves BOS to position 8, *random* replaces the token at position 0 with an uncommon token from the vocabulary frequency range $[10^3, 2 \times 10^4]$. We measure cosine consistency $\mathcal{C}(\ell, h)$ of each head's W_O output at $k^\star = 64$ across prompts, ranked by sink-reading strength $\rho(\ell, h) = \frac{1}{P} \sum_p a_{k^\star, 0}^{(\ell, h, p)}$.

Qwen sink-token-identity probe For the top twenty Qwen sink-reading heads ranked by ρ, we probe whether the head's output at $k^\star$ carries the identity of the token at position 0. We sample 300 prompts with the first token uniformly drawn from the same vocabulary frequency range and the

remaining tokens identical across prompts. We project each head's W_O output to its top principal component and report R^2_{tok} of the projection onto a one-hot encoding of the sink-token identity, together with a random-permutation null R^2_{random}. We retain heads with PC1 explained-variance fraction above 10%.

Mechanism ablations *Identity-RoPE* replaces $R(m)$ in Equation 1 with the identity. *Scrambled-RoPE* applies a fixed random permutation to the assignment of frequency bands θ_i to query/key dimensions, preserving rotation magnitudes while destroying the relative-offset property of Equation 2. *Bidirectional* removes the causal mask. Each is applied at every layer and head; we recompute ΔR^2 on the same stratified pairs as the baseline.

Refined per-query-bin and layer-wise analyses We aggregate ΔR^2 contributions into seven bins of the query position i: $[0, 5)$, $[5, 12)$, $[12, 25)$, $[25, 50)$, $[50, 100)$, $[100, 200)$, $[200, 256)$, and define the causal-mask share within each bin via Equation 5. The layer-wise ratio $r_\ell = \text{mean}_h \Delta R^2_{\text{bidir}}(\ell)/\text{mean}_h \Delta R^2_{\text{base}}(\ell)$ measures the residual-stream share of leakage at layer ℓ.

Position-0 interventions To attribute the residual-stream component to specific structures in the position-0 trajectory, we run three interventions on Llama-3.2-3B under bidirectional attention and report first-bin $[0, 5)$ mean ΔR^2. *bi-replace-embedding* replaces the BOS embedding e_0 with a uniformly sampled vocabulary token's embedding before the forward pass. *bi-replace-Lstar* leaves e_0 intact and replaces $x_0^{(L^\star)}$ at the most-leaky layer $L^\star = 11$ with the mean of $x_k^{(L^\star)}$ across mid-sequence positions of the same prompt. *bi-replace-all* performs the latter at every layer. We also measure the cross-prompt standard deviation of $x_0^{(\ell)}$ at multiple layers across 8 prompts.

Length-scaling and localization For length-scaling we capture logits at the first four layers and heads of Llama-3.2-1B at sixteen sequence lengths and compare a power-law fit to a piecewise model with breakpoint $N^\star$ by AIC. The *subspace ablation* projects out the linear direction in $x_k^{(\ell^\star)}$ that best predicts k. The *sink-head ablation* zeroes the top-decile sink-reading heads against a random-head control of equal size. The *rank-1 MLP ablation* replaces the FFN output at $(\ell^\star, k^\star = 64)$ by its projection orthogonal to the dominant left-singular

vector of the per-prompt MLP outputs. All confidence intervals are 95% bootstrap intervals over 200 prompt resamples.

5 Results

5.1 Sinks are token-anchored anchors, not content aggregators

If sinks aggregate global content, the positions with the highest attention magnitude should also be the positions from which content is most decodable. They are not. Across all three models the highest-attention positions have topic-probe accuracy at or below chance, while the positions decodable above chance have sink magnitudes three orders of magnitude smaller (Table 1).

	Model	Layer	$\mathcal{S}$	$\mathcal{A}$
	Qwen-2.5-3B	5	0.991	0.219
Highest sink	Qwen-2.5-3B	20	0.963	0.219
	Qwen-2.5-3B	25	0.946	0.219
	Mistral-7B	22	0.0038	0.415
Highest content	Mistral-7B	25	0.0034	0.402
	Mistral-7B	30	0.0063	0.395

Table 1: Highest-attention and highest-content positions are disjoint. Llama-3.2-1B follows the same pattern (appendix).

Moving BOS to position 8 transports the sink to position 8 in both Llama and Mistral, with attention magnitudes near saturation (Table 2). Replacing BOS at position 0 with a random uncommon token suppresses sink formation there. The sink anchors to a token. Qwen, which does not auto-prepend BOS, shows a sink at position 0 with saturated magnitude as a default-anchor fallback when no earlier token competes for the role.

Model	Variant	k	$\mathcal{S}$	$\mathcal{A}$
	default	0	–	0.31
Llama-3.2-1B	BOS at $k = 8$	8	**0.92**	0.37
	BOS at $k = 8$	0	0.59	0.31
	random at $k = 0$	0	< 0.05	0.34
	default	0	0.27	0.34
Mistral-7B-v0.3	BOS at $k = 8$	8	**0.94**	0.34
	random at $k = 0$	0	< 0.40	0.34
Qwen-2.5-3B	no BOS	0	1.00	0.36

Table 2: The sink follows the BOS token across architectures.

5.2 Sink-reading heads carry sink-token identity

In Llama and Mistral, the top-decile heads by sink-reading strength write output with markedly higher cosine consistency across prompts than the bottom decile (Table 3). The constant BOS token at position 0 drives a constant signal into the downstream heads. In Qwen, the top-decile heads write input-varying output: the token at position 0 varies across prompts.

Model	Heads	$\mathcal{C}$ top dec.	$\mathcal{C}$ bot dec.	$\mathrm{Sp}(\rho, \mathcal{C})$
Llama-3.2-1B	512	+0.66	+0.14	+0.48
Mistral-7B-v03	1024	+0.49	+0.06	+0.61
Qwen-2.5-3B	576	+0.40	+0.49	+0.06

Table 3: Per-head cosine consistency at $k = 64$, ranked by sink-reading strength ρ.

The Qwen sink-token-identity probe confirms a single underlying function (Table 4). Three Qwen sink-reading heads at layer 5 give well-conditioned probe regressions on the sink-token identity. L5/H10 and L5/H11 explain 91% and 86% of the variance of the head's output projection from the sink-token identity alone, with random-permutation null values near zero. Sink-reading heads across all three architectures pass the identity of the token at position 0 to downstream attention; Llama and Mistral carry a constant identity (BOS), Qwen carries a varying one. The mechanism is the same. Section 5.7 grounds it formally.

Head	ρ	PC1 var. fraction	R^2_{tok}	R^2_{random}
L5/H10	1.000	0.605	+0.914	−0.065
L5/H11	0.997	0.338	+0.860	−0.057
L5/H15	0.979	0.347	+0.172	−0.035

Table 4: Qwen sink-reading heads at layer 5 carry sink-token identity. R^2_{tok} is the cross-validated R^2 of the head's W_O output projection on PC1 against a one-hot encoding of the sink-token identity. Deeper-layer sink-reading heads produced ill-conditioned probes and are excluded.

5.3 Leakage is distributed and structural

The saturated baseline reveals heads with statistically significant absolute-position structure in every architecture (Table 5). Peak per-head values are 0.05 for Llama, 0.11 for Qwen, 0.24 for Mistral; all of the top thirty heads per model survive FDR correction at $q < 0.05$. The leakage is content-independent: the mean ΔR^2 on Llama is 0.012 on natural text and 0.011–0.013 on random tokens.

Model	Tot heads	Peak ΔR^2	Med ΔR^2 (top 30)	Sig. at $q < 0.05$
Llama	512	0.049	0.029	30/30
Qwen	576	0.108	0.041	30/30
Mistral	1024	0.241	0.047	30/30

Table 5: Absolute-position leakage ΔR^2 against the saturated relative-offset baseline.

5.4 Mechanism ablations expose two architectural components

Three architectural ablations isolate the components (Table 6). Bidirectional ablation reduces ΔR^2 to between 9% and 35% of baseline; what survives bidirectional is the residual-stream component (Equation 5). Identity-RoPE and scrambled-RoPE increase ΔR^2 by a factor of 2.1 to 3.2, making position-varying residual-stream content directly readable from the unrotated queries and keys.

5.5 Refined per-query binning

Figure 1 shows mean ΔR^2 by query position bin under causal and bidirectional attention for the three architectures, with the underlying values in Table 7. At the first bin $[0, 5)$, where leakage is overwhelmingly concentrated, the bidirectional value is substantially smaller than the baseline in every architecture: the ratio is 0.20 for Qwen, 0.39 for Llama, 0.51 for Mistral. The causal-mask share at this bin is 80% in Qwen, 62% in Llama, and 49% in Mistral. Leakage drops by a factor of about $4\times$ from $[0, 5)$ to $[5, 12)$ and by another $2\times$ to $[12, 25)$. Beyond the first 25 tokens the contribution to head-averaged ΔR^2 is small. Equation 6 predicts this position profile: Z_i changes most rapidly at small i and approaches its asymptote at large i, so the causal-mask contribution to ΔR^2 concentrates at small i by construction.

5.6 Layer-wise depth profiles distinguish the three architectures

The per-layer ratio r_ℓ exposes a third architectural distinction (Table 8). In Qwen, r_ℓ stays between 0.15 and 0.30 across all 36 layers (mean 0.21). In Llama-3.2-3B, r_ℓ sits between 0.50 and 0.70 across all layers (mean 0.62), with no strong depth trend. In Mistral, r_ℓ grows from about 0.50 at layer 0 to between 0.85 and 0.90 by layer 25 of 32 (mean 0.66). Sliding-window attention does not suppress residual-stream propagation; in Mistral it allows the residual-stream component to accumulate through depth.

Model	Baseline	Identity-RoPE	Scrambled-RoPE	Bidirectional
Llama-3.2-3B	0.0143 [0.0137, 0.0149]	0.0413 (2.88×)	0.0388 (2.71×)	0.0051 (0.35×)
Qwen-2.5-3B	0.0153 [0.0144, 0.0162]	0.0496 (3.24×)	0.0370 (2.42×)	0.0014 (0.09×)
Mistral-7B-v0.3	0.0182 [0.0175, 0.0190]	0.0391 (2.14×)	0.0386 (2.12×)	0.0022 (0.12×)

Table 6: Mean ΔR^2 across heads under three modifications of the attention computation. Brackets are 95% bootstrap CIs.

Bin in i	$[0, 5)$	$[5, 12)$	$[12, 25)$	$[25, 50)$	$[50, 100)$	$[100, 200)$	$[200, 256)$
Llama-3.2-3B baseline	0.296	0.080	0.032	0.016	0.011	0.008	0.003
Llama-3.2-3B bidirectional	0.114	0.090	0.036	0.018	0.010	0.005	0.001
Mistral baseline	0.313	0.070	0.036	0.017	0.012	0.008	0.003
Mistral bidirectional	0.161	0.078	0.033	0.016	0.008	0.002	0.001
Qwen baseline	0.254	0.065	0.027	0.016	0.011	0.007	0.003
Qwen bidirectional	0.050	0.015	0.005	0.003	0.002	0.001	0.001

Table 7: Mean ΔR^2 by query position bin under causal and bidirectional attention.

Model	Mean r_ℓ	Depth trend
Qwen-2.5-3B	0.21	flat across 36 layers
Llama-3.2-3B	0.62	flat across 28 layers
Mistral-7B-v0.3	0.66	grows from ≈ 0.5 at $\ell = 0$ to ≈ 0.9 at $\ell = 25$

Table 8: Per-layer residual-stream share $r_\ell = \Delta R^2_{\text{bidirectional}}(\ell)/\Delta R^2_{\text{baseline}}(\ell)$.

5.7 The residual-stream component traces to the position-0 trajectory

The dynamical-system observation of Section 3 predicts that $x_0^{(\ell)}$ at every layer is a fixed function of e_0 across prompts. The prediction holds exactly in standard-RoPE architectures: the cross-prompt standard deviation of $x_0^{(\ell)}$ at every layer measured is exactly 0.0000 in Llama-3.2-3B and Mistral-7B-v0.3, with BOS fixed at position 0 across the eight prompts tested (Appendix A). The standard deviation of $x_1^{(\ell)}$ at the same layer is on the order of 10^{-2} to 10^{-3}, reflecting variation in the second token across prompts. Sink-reading heads at downstream positions therefore read a deterministic function of e_0. In Qwen, e_0 varies with the input; the sink-token-identity regression of Section 5.2 is the direct readout of the varying trajectory.

Three interventions on the position-0 trajectory test its contribution to the residual-stream component (Table 9). Replacing the BOS embedding e_0 with a uniformly sampled vocabulary token's embedding reduces the bidirectional first-bin ΔR^2 from 0.115 to 0.068, a 40% reduction. Replacing $x_0^{(L^\star)}$ at the most-leaky layer $L^\star = 11$ with a prompt-specific mid-sequence mean reduces it to 0.089, a 22% reduction. The BOS embedding alone

accounts for 40% of the residual-stream component at early queries in Llama-3.2-3B.

Condition	First-bin ΔR^2	% of bi. baseline
Causal base	0.288 [0.279, 0.296]	251%
Bidirec base	0.115 [0.108, 0.121]	100%
Bidirec + replace e_0	0.068 [0.062, 0.075]	60%
Bidirec + replace $x_0^{(L^\star)}$	0.089 [0.082, 0.096]	78%
Bidirec + replace $x_0^{(\ell)}$ all ℓ	0.147 [0.138, 0.154]	128%

Table 9: Position-0 interventions on first-bin ΔR^2 in Llama-3.2-3B. Brackets are 95% bootstrap CIs. Replacing the BOS embedding before the forward pass removes 40% of the residual-stream component at early queries.

Replacing $x_0^{(\ell)}$ at every layer with a prompt-specific mid-sequence mean does not reduce the residual-stream component; the first-bin ΔR^2 rises to 0.147, 128% of the bidirectional baseline. The intervention introduces across-prompt variation at a position that is normally constant, and the saturated regression reads that variation as additional absolute-position structure. The residual-stream component at early queries depends on x_0 being a fixed fingerprint of e_0 across prompts, not on x_0 carrying prompt-specific content.

The remaining 60% that the embedding-replacement does not remove comes from sources we do not isolate: layer-norm interactions with position-correlated activations at mid-sequence positions, and accumulated rotated writes through the network. The position-0 fingerprint accounts for a substantial fraction of the residual-stream component at early queries; its remainder is open to future work.

5.8 Length-scaling and targeted interventions

Mean ΔR^2 decays with sequence length. A piecewise model that is flat below $N^\star = 80$ and decays as $N^{-0.52}$ above is preferred over a single power law by AIC by $\Delta\text{AIC} = -6.27$. The decay reflects the attenuation of the causal-mask component as Z_i approaches its limit.

Targeted residual-stream interventions do not localize the leakage (Table 10). Projecting out the linear direction that best predicts absolute position drops mean ΔR^2 by 3%. Zeroing the top-decile sink-reading heads (52 heads) drops it by 8%. A random-head control of equal size drops it by 17%. Both targeted interventions are mechanically substantive and produce smaller effects than a random ablation of the same size. The result is consistent with one component living in the softmax normalization at all heads and the other distributed across many residual-stream directions.

Condition	Heads zeroed	Mean ΔR^2	Reduc vs base
Baseline	0	0.0111	–
Rank-1 pos-probe subspace	0	0.0107	3%
Top-decile sink-reading heads	52	0.0102	8%
Random-head control	52	0.0092	17%

Table 10: Targeted interventions on Llama-3.2-1B.

The rank-1 MLP ablation at $k^\star = 64$ removes up to 80% of the MLP output norm at the target but does not reduce topic-probe accuracy in any of the nine layers tested (Appendix B). Content production at content positions is not concentrated in a single direction.

5.9 Scale: composition shifts, magnitude is preserved

In the Llama family the total leakage magnitude is approximately constant across model sizes (Table 11). The composition shifts: the residual-stream share rises from 18% at 1B to 35% at 3B and 36% at 8B. The causal-mask component is dominant at 1B and roughly balanced with the residual-stream component at 3B and 8B. The shift saturates between 3B and 8B at a fixed $\approx 64/36$ split.

6 Discussion

The leakage that RoPE-trained transformers carry in their attention logits is the sum of two architectural components. The causal-mask component is fixed by the per-query softmax denominator (Equation 6) and concentrates at early query positions where Z_i is far from its asymptote. The residual-stream component is distributed across many directions in the residual stream and accumulates with depth in architectures that allow it. Both components are present in all three architectures; their balance differs.

The position-0 interventions ground the residual-stream component in a concrete mechanism. Under causal attention $x_0^{(\ell)}$ is a closed dynamical system from e_0, and the activation at every layer is bit-identical across prompts when the token at position 0 is fixed. Replacing the BOS embedding alone reduces the residual-stream component at early queries by 40%. The result unifies two cross-architecture observations that previously looked distinct. Sink-reading heads in Llama and Mistral write input-stable output because they read $x_0^{(\ell)}$, which is constant across prompts; sink-reading heads in Qwen carry sink-token identity because they read the same $x_0^{(\ell)}$ trajectory, which varies with e_0 when e_0 is not the auto-prepended BOS. The same function operates in all three architectures, on different inputs at position 0.

The architectural ordering is consistent across the measurements. Qwen's NTK-scaled RoPE makes the residual-stream component the smallest of the three (first-bin share 20%, layer-wise mean $r_\ell = 0.21$). NTK scaling spreads the rotation frequencies further apart and reduces the readability of residual-stream position content from the inner product. Mistral's sliding-window attention does not suppress the residual-stream component; r_ℓ rises from about 0.5 at layer 0 to about 0.9 at layer 25. Standard RoPE in Llama sits between, with a flat depth profile at $r_\ell \approx 0.6$.

The scale composition shift is informative. The Llama family preserves total leakage magnitude across 1B, 3B, and 8B but redistributes it from the causal-mask component (82% at 1B) toward the residual-stream component (36% at 3B and 8B). The saturation between 3B and 8B suggests that the architectural balance is set by properties of the network that converge between 1B and 3B parameters. The causal-mask component is determined by the geometry of Z_i, which depends on the head-level distribution of f; the residual-stream component depends on what the network learns to write into $x_m^{(L)}$ and on the BOS-fingerprint trajectory at position 0. The convergence indicates that the second of these saturates at moderate scales.

The negative localization results constrain the

Figure 1: Mean ΔR^2 by query position bin under causal (baseline) and bidirectional attention, for the three architectures. Query position bin midpoints are plotted on a log scale.

Model	Baseline ΔR^2	Bidirectional ΔR^2	Residual-stream share	Causal-mask share
Llama-3.2-1B	0.0121	0.0022	18%	82%
Llama-3.2-3B	0.0143	0.0051	35%	64%
Llama-3.1-8B	0.0135	0.0048	36%	64%

Table 11: Scale composition shift. Total leakage magnitude is approximately constant across 1B, 3B, 8B; the residual-stream share of the leakage doubles from 1B to 3B and then saturates.

residual-stream component. The rank-1 position-probe projection reduces downstream leakage by only 3%. The MLP rank-1 ablation at content positions removes up to 80% of the FFN output norm without affecting decodable content. The position-0 embedding intervention removes 40% of the first-bin residual-stream component, the largest single attribution we can make; the other 60% is distributed across sources the embedding intervention does not touch. The empirical signature of the residual-stream component is distribution across many directions and many positions; whether this distribution is a learned optimization or a consequence of the loss landscape under causal masking and RoPE is open.

7 Limitations

We measure leakage in attention logits and trace its architectural sources, but do not connect the magnitude of either component to a fully characterized downstream effect. The bidirectional ablation removes the causal mask at inference time in networks whose weights were trained under causal masking; whether the two-component decomposition holds in a bidirectionally-trained model is open. The position-0 embedding intervention removes 40% of the residual-stream component at early queries; the remaining 60% comes from sources we do not isolate (layer-norm interactions with mid-sequence position-correlated activations, accumulated rotated writes through the network), and characterizing these is a follow-up.

8 Conclusion

The absolute-position structure that RoPE-trained transformers carry in their attention logits is the sum of two architectural components. The first is the per-query softmax normalization under causal masking, which depends on the absolute query position through the cardinality of the denominator. The second is position-varying structure in the residual stream that RoPE rotation does not fully obscure, and traces in part to a deterministic trajectory from the embedding of the token at position 0. Both components are present in all three architectures, and the balance between them is set architecturally: NTK scaling suppresses the residual-stream component, sliding-window attention allows it to accumulate with depth, and standard RoPE in Llama sits between. In the Llama family the composition shifts from causal-mask-dominated at 1B to roughly balanced at 3B and 8B without changing the total leakage magnitude. Attention sinks pass the identity of the token at position 0 to downstream attention through a closed dynamical system; the architectural difference in sink-reading head output stability reflects only the variation in e_0 across architectures. Reconstruction of absolute position in a RoPE-trained transformer is the joint operation of the causal mask and the residual stream the network has learned to write.

References

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Xiangming Gu, Tianyu Pang, Chao Du, Qian Liu, Fengzhuo Zhang, Cunxiao Du, Ye Wang, and Min Lin. 2025. When attention sink emerges in language models: An empirical view. In *International Conference on Learning Representations*, volume 2025, pages 97114–97144.

Adi Haviv, Ido Cohen, Jacob Gidron, Roei Schuster, Yoav Goldberg, and Mor Geva. 2023. Understanding transformer memorization recall through idioms. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 248–264, Dubrovnik, Croatia. Association for Computational Linguistics.

Binyuan Hui, Jian Yang, Zeyu Cui, Jiaxi Yang, Dayiheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, Bowen Yu, Keming Lu, and 1 others. 2024. Qwen2. 5-coder technical report. *arXiv preprint arXiv:2409.12186*.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *CoRR*, abs/2310.06825.

Amirhossein Kazemnejad, Inkit Padhi, Karthikeyan Natesan Ramamurthy, Payel Das, and Siva Reddy. 2023. The impact of positional encoding on length generalization in transformers. *Advances in Neural Information Processing Systems*, 36:24892–24928.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, and 1 others. 2022. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. 2024. Yarn: Efficient context window extension of large language models. In *International Conference on Learning Representations*, volume 2024, pages 31932–31951.

Ofir Press, Noah A Smith, and Mike Lewis. 2021. Train short, test long: Attention with linear biases enables input length extrapolation. *arXiv preprint arXiv:2108.12409*.

Valeria Ruscio, Umberto Nanni, and Fabrizio Silvestri. 2025. Beyond position: the emergence of wavelet-like properties in transformers. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6074–6088.

Valeria Ruscio, Umberto Nanni, and Fabrizio Silvestri. 2026. What are you sinking? a geometric approach on attention sink. *Advances in Neural Information Processing Systems*, 38:123482–123521.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. 2024. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063.

Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. 2023. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *The Eleventh International Conference on Learning Representations*.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. 2024. Efficient streaming language models with attention sinks. In *International Conference on Learning Representations*, volume 2024, pages 21875–21895.

A Position-0 trajectory: norm measurements

We measure the norm and cross-prompt standard deviation of the residual-stream activation at position 0 at multiple layers of Llama-3.2-3B and Mistral-7B-v0.3, using eight prompts in which the token at position 0 is the auto-prepended BOS (id = 128000 for Llama, 1 for Mistral) and subsequent tokens vary.

Layer	Mean $\|x_0^{(\ell)}\|$	Std across prompts
Llama-3.2-3B		
embedding	1.13	0.00
$\ell = 0$	19.92	0.00
$\ell = 5$	593.68	0.00
$\ell = 11$	593.29	0.00
$\ell = 15$	594.70	0.00
$\ell = 20$	594.55	0.00
$\ell = 27$	248.03	0.00
Mistral-7B-v0.3		
embedding	0.14	0.00
$\ell = 0$	6.02	0.00
$\ell = 5$	265.00	0.00
$\ell = 11$	265.07	0.00
$\ell = 15$	265.10	0.00
$\ell = 20$	268.78	0.00
$\ell = 31$	325.84	0.00

Table 12: Norm of $x_0^{(\ell)}$ at multiple layers across eight prompts. The cross-prompt standard deviation is exactly zero at every layer of both architectures: the position-0 trajectory is fully determined by the BOS embedding. For reference, the cross-prompt variance of $x_1^{(\ell)}$ at $\ell = 11$ is 1.24×10^{-2} in Llama and 1.26×10^{-3} in Mistral, reflecting the variation in the second token.

The peak mid-sequence norm of $x_0^{(\ell)}$ is 593 in Llama-3.2-3B and 265 in Mistral-7B. In both architectures the norm at position 0 is more than an order of magnitude larger than the typical mid-sequence norm at downstream positions (around $14\times$ for both models when measured at the same layer). The position-0 activation acts as an anomalously high-magnitude fixed vector that downstream attention reads.

B Rank-1 MLP ablation: per-layer values

C Per-query-position profile under bidirectional attention

Section 5.5 presents the per-query-position ΔR^2 profile under causal attention and shows that leakage concentrates at small i. The same binning under bidirectional attention is the cleanest direct test of the causal-mask pathway: if the causal mask

Model	L	$\Delta\mathcal{A}$	Frac MLP norm removed
Llama-3.2-1B	15	-0.015	0.80
	14	-0.015	0.63
	13	-0.004	0.43
Qwen-2.5-3B	35	$+0.027$	0.17
	34	$+0.011$	0.37
	33	0.000	0.34
Mistral-7B-v03	31	-0.020	0.66
	30	$+0.012$	0.30
	29	$+0.011$	0.17

Table 13: Rank-1 MLP ablation at $k^\star = 64$ removes the majority of the MLP output norm at the target but does not suppress decodable content.

is the source of the position dependence at small i, the bidirectional curve should be flat in i relative to the steep decay of the causal curve.

Figure 1 (main text) and Table 7 give the underlying numbers. The bidirectional first-bin ΔR^2 falls sharply relative to the causal first-bin value in every architecture: the causal-to-bidirectional gap at $[0, 5)$ is 0.182 in Llama-3.2-3B, 0.152 in Mistral, and 0.204 in Qwen. The gap closes by $[12, 25)$ in all three architectures and the two curves become indistinguishable beyond $[25, 50)$.

The bidirectional curve is itself not perfectly flat at small i. It decays from 0.114 to 0.090 between $[0, 5)$ and $[5, 12)$ in Llama-3.2-3B, and from 0.161 to 0.078 between the same two bins in Mistral. Two effects contribute. The position-0 trajectory has anomalously high norm (Appendix A) and influences attention weights at early queries more than at later ones, even with the causal mask removed. The residual-stream component itself has position dependence that is not captured by causal-mask geometry alone. The decay of the bidirectional curve at small i is the empirical signature of this position-dependent residual-stream content.

The Qwen profile is the cleanest. The bidirectional curve sits an order of magnitude below the causal curve at $[0, 5)$ (0.050 vs 0.254) and decays smoothly with i without crossing the causal curve at any bin. NTK scaling suppresses the residual-stream contribution at all positions, leaving the causal-mask geometry as the dominant source of the position-dependent attention weights at early queries.

In Llama-3.2-3B and Mistral the bidirectional curve briefly exceeds the causal curve in the $[5, 12)$ and $[12, 25)$ bins (Mistral) or just $[5, 12)$ (Llama). The crossing is at ΔR^2 values below 0.10 and the two curves are statistically indistinguishable within

their bootstrap confidence intervals over that range. The crossing reflects the larger absolute residual-stream contribution in standard-RoPE architectures, which becomes visible once the dominant causal-mask contribution at small i is removed.