Deep Generative model with Hierarchical Latent Factors for Timeseries Anomaly Detection

Abstract

In this paper, we propose a Generative model for multivariate time-series anomaly detection, which generates windows from a novel hierarchical latent factor representation (DGHL). This novel hierarchical factors exploit time-series dynamics to encode information efficiently. DGHL does not rely on an encoder network; instead, it infers and samples latent vectors from the posterior distribution directly with Langevin Dynamics. Despite relying on posterior sampling, our approach is computationally more efficient than RNN based models, with up to 10x shorter training times. DGHL achieved state-of-the-art performance on four popular benchmark datasets, outperforming current reconstruction-based and generative models. With IoT, settings with corrupted or missing data have increasing relevance. The proposed model has superior robustness to incomplete data, which we demonstrate with novel occlusion experiments in this literature.

1 Introduction

Multivariate time-series anomaly detection has become an active area of research in recent years. Advancements in Deep Learning such as Recurrent Neural Networks (RNN), Temporal Convolution Networks (TCN) and Graph Networks (GN) have been successfully incorporated by recent models to outperform previous approaches such as out-of-limits, clustering-based, distance-based, and dimensionality reduction. [2] [13] present comprehensive reviews of current state-of-the-art methods for time-series anomaly detection.

In this work, we propose DGHL, a novel Deep Generative model based on a top-down Convolution Network (ConvNet), which maps multivariate time-series windows to a novel hierarchical latent space. The model is trained by maximizing the observed likelihood directly with the Alternating Back-Propagation algorithm, so it does not rely on auxiliary networks such as encoders or discriminators as VAEs and GANs do. DGHL, therefore, comprehends a separate family of generative models, previously unexplored for time-series anomaly detection. We perform experiments on several popular datasets and show the proposed model outperforms the recent state-of-the-arts while reducing training times against previous reconstruction-based and generative models.

With IoT, we believe that settings with corrupted or missing data have increasing relevance. For example, faulty sensors can cause missing values, privacy issues on consumer electronics devices, or heterogeneous hardware can lead to variable features. We present the first extensive analysis on the robustness of current state-of-the-art models on datasets with missing inputs and variable features with novel occlusion experiments. DGHL achieved superior performance on this setting, maintaining state-of-the-art performance with up to 90% of missing data, without modification to the architecture or training procedure.

We perform additional qualitative experiments of our model to assess desirable properties of lower-dimensional representations such as continuity and extrapolation capabilities. Finally, we show how DGHL can be used as a forecasting model, demonstrating its versatility on various time-series tasks.

The main **contributions** of our paper are:

- **Hierarchical latent factors**. We present a novel hierarchical latent space representation to generate windows of arbitrary length. We demonstrate with ablation studies how DGHL achieves state-of-the-art performance by leveraging this representation on four benchmark datasets.

- **Langevin Dynamics**. First time-series anomaly detection generative model based on short-run MCMC for estimating posterior of latent variables and inferring latent vectors. In particular, first application of Alternating Back-Propagation algorithm for learning generative model for time-series data.

- **Robustness to missing data**. We present the first experiments on robustness to missing inputs of state-of-the-art anomaly detection models, and demonstrate DGHL achieves superior performance in this setting.

The rest of the paper is structured as follows. Section 2 reviews current state-of-the-art models and presents the Alternating Back-Propagation algorithm, Section 3 introduces DGHL, Section 4 contains the empirical findings. Finally in Section 5 we wrap up and conclude.

2 Related Work

2.1 Reconstruction-based models

Reconstruction-based models learn representations for the time-series by reconstructing the input based on latent variables. The reconstruction error or the likelihood are commonly used as anomaly scores. Among these models, variational auto-encoders (VAE) are the most popular. The LSTM-VAE, proposed in [12], uses LSTM both as encoders and decoders and models the reconstruction error with support vector regression (SVR) to have a dynamic threshold based on the latent space vector. OmniAnomaly [16] improves on the LSTM-VAE by adding normalizing planar flows to increase the expressivity and including a dynamic model for the latent space.

Generative Adversarial Networks (GANs) were also adapted for anomaly detection as alternatives to VAE, with models such as AnoGAN [14], MAD-Li [6], and MAD-GAN [7]. For instance, in MAD-GAN, a GAN is used to generate short windows of time-series with LSTM Generator and Discriminator networks. The anomaly score considers both the reconstruction error of the reconstructed window by the Generator network and the score of the Discriminator network.

Most recent models propose to detect anomalies directly on the latent representation and embeddings. THOC [15] proposed to use one-class classifiers based on multiple hyperspheres on the representations on all intermediate layers of a dilated RNN. NCAD [1] uses a TCN to map context windows and suspect windows into a neural representation and detect anomalies in the suspect window on the latent space with a contextual hypersphere loss.

Virtually all current models, including our proposed approach, rely on mapping the original time-series input into embeddings or a lower-dimensional latent space. DGHL, however, is trained with the Alternating Back-Propagation (ABP) algorithm, presented in [4]. ABP maximizes the observed likelihood directly; it does therefore not rely on variational inference approximations or auxiliar networks such as discriminators. Instead, our approach uses MCMC sampling methods to sample from the true posterior to approximate the likelihood gradient. Several generative models which rely on MCMC sampling, and in particular Langevin Dynamics, have shown state-of-the-art performance on computer vision [10] and NLP [11] tasks. To our knowledge, this algorithm has not been used for time-series forecasting and time-series anomaly detection. We present the ABP algorithm in the next subsection.

2.2 Alternating back-propagation

Let $\mathbf{y} \in \mathbb{R}^D$ be a data vector such as a time-series window or an image, and $\mathbf{z} \in \mathbb{R}^d$ a latent vector. Let $\{\mathbf{y}^{(i)}, i = 1, ..., n\}$ be a training set. Consider the following generative model,

$$\mathbf{y} = f(\mathbf{z}, \boldsymbol{\theta}) + \boldsymbol{\epsilon} \tag{1}$$

with $\mathbf{z} \sim N(0, \boldsymbol{I}_d)$, $\boldsymbol{\epsilon} \sim N(0, \sigma^2 \boldsymbol{I}_D)$, $D > d$ and $\boldsymbol{\theta}$ the learnable parameters of the Generator model f. For instance, the classic factor analysis model corresponds to $f = \boldsymbol{\theta}\mathbf{z}$. In this work, we consider top-down Convolution Networks (ConvNet), however, this framework allows for other types of Generator functions such as fully-connected networks (MLP) or Recurrent Neural Networks (RNN). The proposed Alternating Back-Propagation algorithm learns parameters $\boldsymbol{\theta}$ by maximizing the observed log-likelihood directly, given by,

$$L(\boldsymbol{\theta}) = \sum_{i=1}^n \log p_{\boldsymbol{\theta}}(\mathbf{y}^{(i)}) = \sum_{i=1}^n \log \int p_{\boldsymbol{\theta}}(\mathbf{y}^{(i)}, \mathbf{z}^{(i)})d\mathbf{z}^{(i)} \tag{2}$$

The observed likelihood $L(\boldsymbol{\theta})$ is analytically intractable. However, the gradients $L'(\boldsymbol{\theta})$ can be simplified to,

$$\begin{aligned}
\frac{\partial}{\partial \boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{y}) &= \frac{1}{p_{\boldsymbol{\theta}}(\mathbf{y})} \frac{\partial}{\partial \boldsymbol{\theta}} \int p_{\boldsymbol{\theta}}(\mathbf{y}, \mathbf{z})d\mathbf{z} \\
&= \mathbb{E}_{p_{\boldsymbol{\theta}}(\mathbf{z}|\mathbf{y})} \left[\frac{\partial}{\partial \boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{y}, \mathbf{z}) \right]
\end{aligned} \tag{3}$$

where $p_{\boldsymbol{\theta}}(\mathbf{z}|\mathbf{y}) = p_{\boldsymbol{\theta}}(\mathbf{y}, \mathbf{z})/p_{\boldsymbol{\theta}}(\mathbf{z})$ is the posterior. The expectation in the previous equation can be approximated with the Monte Carlo average by taking samples using MCMC. In particular, Alternating Back-Propagation takes a single sample of the posterior using Langevin Dynamics [8], a Hamiltonian Monte Carlo algorithm, which iterates,

$$\begin{aligned}
\mathbf{z}_{t+1} &= \mathbf{z}_t + \frac{s}{\sigma_z} \frac{\partial}{\partial \mathbf{z}} \log p_{\boldsymbol{\theta}}(\mathbf{z}_t|\mathbf{y}) + \sqrt{2s}\boldsymbol{\epsilon_t} \\
&= \mathbf{z}_t + \frac{s}{\sigma_z} \left[(\mathbf{y} - f(\mathbf{z}_t, \boldsymbol{\theta}) \frac{\partial}{\partial \mathbf{z}} f(\mathbf{z}_t, \boldsymbol{\theta}) - \mathbf{z}_t \right] + \sqrt{2s}\boldsymbol{\epsilon_t}
\end{aligned} \tag{4}$$

where $\boldsymbol{\epsilon_t} \sim N(0, \boldsymbol{I}_D)$, t is the time step of the dynamics, s is the step size, and σ controls the relative size of the injected noise. This iteration is an explain-away process where latent factors are chosen such that the current residual on the reconstruction, $\mathbf{y} - f(\mathbf{z}_t, \boldsymbol{\theta})$, is minimized. With large values of σ_z, the posterior will be close to the prior, while small σ_z allows for a richer posterior. For an observation $\mathbf{y}^{(i)}$, the inferred vector with Langevin Dynamics is a sample from the posterior, $p_{\boldsymbol{\theta}}(\mathbf{z}|\mathbf{y}^{(i)})$, the Monte Carlo approximation of the gradient then becomes,

$$\begin{aligned}
L'(\boldsymbol{\theta}) &\approx \frac{\partial}{\partial \boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{z}^{(i)}, \mathbf{y}^{(i)}) \\
&= \frac{1}{\sigma^2}(\mathbf{y}^{(i)} - f(\mathbf{z}^{(i)}, \boldsymbol{\theta}) \frac{\partial}{\partial \boldsymbol{\theta}} f(\mathbf{z}^{(i)}, \boldsymbol{\theta}))
\end{aligned} \tag{5}$$

Algorithm 1 presents the alternating back-propagation algorithm with mini-batches. Analogous to the EM algorithm [3], it iterates two distinct steps: (1) *inferential back-propagation* and (2) *learning back-propagation*. During (1), the latent vectors $\{\mathbf{z}^{(i)}\}$ are inferred for samples $\{\mathbf{y}^{(i)}, i = 1, ..., b_s\}$. In step (2), $\{\mathbf{z}^{(i)}\}$ are used as input of the Generator model f and parameters $\boldsymbol{\theta}$ are updated with SGD.

One disadvantage of MCMC methods is the computational cost. Langevin Dynamics, however, relies on the gradients of the Generator function, which can be efficiently computed with modern

Algorithm 1: Mini-batch alternating back-propagation

---

input : training examples $\{\mathbf{y}^{(i)}, i = 1, ..., n\}$, Langevin steps l, learning iterations T
output: learned parameters $\boldsymbol{\theta}$, inferred latent vectors $\{\mathbf{z}^{(i)}, i = 1, ..., n\}$, learning rates γ_t
Let $t \leftarrow 0$, initialize $\boldsymbol{\theta}$
Initialize $\mathbf{z}^{(i)}$, for $i = 1, ..., n$
while $t < T$ **do**
    Take a random mini-batch $\{\mathbf{y}^{(j)}, j = 1, ...b\}$.
    Inferential back-propagation: For each j, run l steps of Langevin dynamics to sample
    $\mathbf{z}^{(j)} \sim p(\mathbf{z}|\mathbf{y}^{(j)}, \boldsymbol{\theta})$ following equation 4.
    Learning back-propagation: Update $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \gamma_t L'(\boldsymbol{\theta})$, following equation 5
    $t \leftarrow t + 1$
end

---

110 automatic differentiation packages such as Tensorflow and Pytorch. Moreover, back-propagation
111 on ConvNet is easily parallelizable in GPU. Several recent works [4], [18], [9] have shown models
112 trained with alternating-back-propagation achieved state-of-the-art performance on computer vision
113 and NLP tasks while remaining computationally efficient and comparable in training time to meth-
114 ods relying solely on SGD. We discuss training and inference times in section 4.

3 DGHL

3.1 Hierarchical Latent Factors

117 The model described in Equation 1 generates observations independently. We extend this model with
118 a novel hierarchical latent factor space. Let $\boldsymbol{Y} \in \mathbb{R}^{m \times s_w}$ be a window of size s_w of a multivariate
119 time-series with m features. The window $\boldsymbol{Y}$ is further divided in sub-windows of equal length
120 $\boldsymbol{Y_j} \in \mathbb{R}^{m \times \frac{s_w}{a_L}}, j = 0, ..., a_L$. The structure of the hierarchy is specified by $\boldsymbol{a} = [a_1, ..., a_l]$, where
121 L is the number of levels, and a_l determines the number of consecutive sub-windows with shared
122 latent vector on level l, with $a_{l-1} \mid a_l$. Our model for each sub-window $\boldsymbol{Y_j}$ of $\boldsymbol{Y}$ is given by,

$$
\begin{aligned}
\boldsymbol{s_j} &= F_\alpha(\boldsymbol{z}^1_{\lfloor \frac{j}{a_1} \rfloor}, ..., \boldsymbol{z}^L_{\lfloor \frac{j}{a_L} \rfloor}) \\
\boldsymbol{Y_j} &= G_\beta(\boldsymbol{s_j}) + \boldsymbol{e_j}
\end{aligned}
\tag{6}
$$

123 where F_α is the *Encoder model* parametrized by α, G_β is the *Generator model*, parametrized by β,
124 $\boldsymbol{s_j} \in \mathbb{R}^d$ is the state vector, and $\boldsymbol{e_j} \sim N(0, \boldsymbol{I}_d)$, and

$$
\boldsymbol{Z} = \{\boldsymbol{z}^l_{\lfloor \frac{j}{A_l} \rfloor} \in \mathbb{R}^{d_l}\}_{l,j}
\tag{7}
$$

125 is the hierarchical latent factor space for window $\boldsymbol{Y}$. For the *Encoder model* we used a concatenation
126 layer. For the *Generator model* we used a classic top-down Convolution Network (ConvNet), which
127 maps an input state vector to a multivariate time-series window. The *Encoder model* for each sub-
128 window has L latent vectors inputs. On each level l, the latent vectors of a_l consecutive sub-windows
129 are tied. For instance, the latent vector on the highest layer, L, is shared by all sub-windows of Y_i.
130 Figure 1 shows an example of a hierarchical latent space with $\boldsymbol{a} = [1, 3, 6]$.

131 The key idea of the hierarchical latent space is to leverage dynamics on the time-series, such as sea-
132 sonalities, to encode the information on the latent space more efficiently, i.e., with lower-dimensional
133 vectors. The hierarchical latent space allows generating realistic time-series of arbitrary length while
134 preserving long-term dynamics of the time-series. The hierarchical structure can be incorporated as
135 hyper-parameters to be tuned or pre-defined based on domain knowledge. For instance, hierarchies
136 can correspond to the multiple known seasonalities on the time-series.

137 The hierarchical latent space $\boldsymbol{Z}$ is jointly inferred using Langevin Dynamics. The relative size
138 of the lowest level state vector and the upper levels controls the flexibility of the model. Larger
139 lower hierarchy level vectors make the model more flexible, making it robust to normal changes or
140 randomness in long-term dependencies of the time-series and therefore reducing false positives by
141 reducing the reconstruction error. Larger tied vectors will make the model more strict, better for

Figure 1: Example of hierarchical latent factor space for $\boldsymbol{a} = [1, 3, 6]$. On each level l, the latent vectors of $\boldsymbol{a}_l$ consecutive sub-windows are tied. For instance, the latent vector on the highest layer, L, is shared by all sub-windows of $\boldsymbol{Y}$.

detecting contextual anomalies. The independent model described in the previous subsection can be seen as a single level hierarchical latent space model, with $\boldsymbol{a} = [1]$, in the current framework.

Previous work such as OmniAnomaly incorporates transition models to learn dynamics in the latent space. We believe our proposed hierarchical latent factors structure has several advantages over transition models. First, the computational cost and training time is lower for the proposed model since it does not rely on sequential computation and therefore on back-propagation through time for training parameters. Second, transition models implicitly assume the dynamics are constant over time, a non-realistic assumption in many settings. Our solution allows the model to share information across windows to model long-term dynamics without relying on a parametric model which assumes constant dynamics.

3.2 Training

The parameters α and β of DGHL are learned with the Alternating Back-Propagation algorithm described in the previous subsection. First, the training multivariate time-series $\boldsymbol{Y} \in \mathbb{R}^{m \times T}$ with m features and T timestamps, is divided in consecutive windows of size s_w and step size s in a rolling-window fashion.

In each iteration, the algorithm first randomly samples b windows. During the inference step, the hierarchical latent vectors are inferred simultaneously with Langevin Dynamics. The inferred vectors are the inputs to the *Encoder* and *Generator* models, and parameters are updated during the *learning step*.

As described in [17], Bayesian posterior sampling provides inbuilt protection against overfitting. The MCMC sampling allows DGHL to model complex multivariate time-series, while reducing the risk of overfitting. This is particularly helpful on problems with small training sets.

3.3 Online Anomaly Detection

By learning how to generate time-series windows based on the training data $\boldsymbol{Y}$, DGHL implicitly learns *normal* (non-anomalous) temporal dynamics and correlations between the multiple time-series. In this subsection, we explain the proposed approach to reconstruct windows on unseen test data $\boldsymbol{Y}^{test}$ to detect anomalies.

In Online Anomaly Detection we consider the test set $\boldsymbol{Y}^{test} \in \mathbb{R}^{m \times T_{test}}$ to be a stream of m time-series. The goal is to detect anomalies (the evaluation is equivalent to a supervised setting with two classes) as soon as possible. As with the training set, $\boldsymbol{Y}^{test}$ is first divided in consecutive windows with the same parameters s_w and s. We propose to reconstruct and compute anomalies scores one window at a time.

Let $\boldsymbol{Y}_{t^*}$ be the current window of interest. The latent space $\boldsymbol{Z}_{t^*}$ is jointly inferred to reconstruct the target window, namely $\hat{\boldsymbol{Y}}_{t^*}$. The anomaly score for a particular timestamp t in the window is computed as the Mean Square Error (MSE) considering all m time-series, given by [1]

$$s_t = \frac{1}{m} \sum_{i=1}^{m} (y_{i,t} - \hat{y}_{i,t})^2 \tag{8}$$

The size of the window s_w and step size s control how sooner anomalies can be detected. With a smaller s, anomaly scores for newer values in the stream are computed sooner. When $s < s_w$, consecutive windows have overlapping timestamps. In this case, scores are updated by considering the average reconstruction.

One main difference with the inference step during training is the removal of the Gaussian noise, ϵ_t, of the Langevin Dynamics update equation. The inferred factors then correspond to the maximum a posteriori mode, which in turn minimizes the reconstruction error conditional on the learned models F and G. This novel strategy makes DGHL unique among reconstruction-based models: it avoids overfitting during training by sampling from the posterior with Langevin Dynamics and minimizes the reconstruction error to reduce false positives by MAP estimation.

4 Experiments

4.1 Datasets

Server Machine Dataset (SMD) − Introduced in [16], SMD is a multivariate time-series dataset with 38 features for 28 server machines, monitored during 5 weeks. The time-series include common activity metrics in servers such as CPU load, network and memory usage, among others. Both training and testing sets contain around 50k timestamps each, with 5 % of anomalous cases. We trained separate models for each machine as suggested by the authors but with the same hyperparameters.

Soil Moisture Active Passive satellite (SMAP) and Mars Science Laboratory rover (MSL)− Published by NASA in [5], they contain real telemetric data of the SMAP satellite and MSL rover. SMAP includes 55 multivariate time-series datasets, each containing one anonymized channel and 24 variables encoding information sent to the satellite. MSL includes 27 datasets, each with one telemetry channel and 54 additional variables. Again, we train separate models for each telemetry channel, considering additional variables as exogenous, ie. only the anomaly score of the telemetry channel was used for detecting anomalies.

Secure Water Treatment (SWaT) − Is a public dataset with information of a water treatment testbed meant for cyber-security and anomaly detection research. It contains network traffic and data from 51 sensors for 11 days, 7 days of normal operation (train set) and 4 days with cyber attacks (test set).

4.2 Evaluation

We evaluate the performance of DGHL and benchmark models on the four datasets with the F_1-score, considering the anomaly detection problem as a binary classification task where the positive class corresponds to anomalies. Anomalies often occur continuously over a period of time, creating anomalous segments. [19] proposed an adjustment approach, where the predicted output is re-labeled as an anomaly for the whole continuous anomalous segment if the model correctly identifies

---

[1]The MSE corresponds to the likelihood, since we assume Y has a fixed variance of 1.

the anomaly in at least one timestamp. We use this adjustment technique for SMAP, MSL and SMD datasets to make results comparable with existing literature. Moreover, we followed the common practice of comparing the performance using the best F_1-score, by choosing the best threshold on the test set. For SMAP and MSL we use a single threshold through the entire dataset, and for SMD we use separate thresholds for each group of machines.

To make our results comparable with previous work, we follow the train, validation and test split described in [15] for SMAP, MSL and SWaT. For SMD we use the train and test splits described in [16]. All architecture hyper-parameters of the *Generator* model, training hyper-parameters such as batch size and learning rate, and all hyper-parameters of the Langevin Dynamics were kept constant across the four datasets.

4.3 Online Anomaly Detection

Table 1 shows the F_1 scores for DGHL, and the benchmark models for SMAP, MSL, SWaT and SMD datasets, following the experimental setup previously described. Our methods consistently achieves the Top-3 F_1 scores across datasets, with performance comparable to current state-of-the-art such as MTAD-GAT [20], THOC and NCAD, with improvements against all models in at least one dataset. Moreover, our approach achieved the highest performance between all reconstruction based models and generative models on all datasets. Both DGHL and the simpler version without hierarchical factors had similar performance on SMAP and SWaT, but the former improved considerably on MSL and SMD.

Table 1: F_1 scores on benchmark datasets (the larger the better). For SMAP, MSL and SWaT the benchmark models performance was taken from [15], [1] and [20]. First place is marked in bold and second place in bold and italic. DGHL corresponds to the full model described in previous section, DGHL - Hierarchical factors corresponds to the simpler model with fully independent latent vectors for each window.

Model	SMAP	MSL	SWaT	SMD
AnoGAN	74.59	86.39	86.64	-
DeepSVDD	71.71	88.12	82.82	-
DAGMM	82.04	86.08	85.37	70.93
LSTM-VAE	75.73	73.79	86.39	76.72
MAD-GAN	81.31	-	86.89	-
MSCRED	85.97	77.45	86.84	-
OmniAnomaly	85.35	90.14	86.67	*81.89*
MTAD-GAT	90.13	90.84	-	-
THOC	**95.18**	93.67	*88.09*	-
NCAD	94.45	**95.60**	-	80.16
DGHL	94.10	*95.26*	87.90	**83.27**
DGHL - Hierarchical factors	*94.88*	92.41	**88.81**	80.78

DGHL outperforms other pure reconstruction-based models because inferring latent vectors for computing anomaly scores provides several advantages. First, it provides additional flexibility and generalization capabilities to prevent false positives, which is instrumental on noisy or with non-constant temporal dynamics datasets such as the used datasets. Second, it helps to reduce the lasting impact of anomalies on the reconstruction error over time, reducing false positives once anomalies end.

DGHL took an average of 2 minutes to train for each entity (e.g. one machine of SMD or one channel of SMAP) consistently across datasets. For instance, the training time was around 60 minutes for SMD and MSL, and 100 minutes for SMAP. This is comparable to other state-of-the-art models self-reported training times such as NCAD and faster than RNN based models. For instance, Omni-Anomaly took an average of 20 minutes to train each model for each machine on the SMD dataset. The inference time varies depending on the length of the test set. The average time to infer 3000 timestamps (average downsampled SMD test set), with $s_w = 32$, was lower than 5 seconds.

4.4 Online Anomaly Detection with missing data

All current benchmark datasets in the time-series anomaly detection literature assume *perfect* data. However, this is not usually the case in real scenarios, with issues like missing values, corrupted data, and variable features. This section presents the first experiments to assess the robustness of current state-of-the-art models to common data issues such as missing values. In particular, we adapt the popular occlusion experiments from computer vision literature for training models with incomplete data.

As detailed in section 2, the first step of the ABP algorithm is to infer latent vectors with Langevin Dynamics. This is an explain-away process where latent factors are chosen such that the current residual on the reconstruction, $Y - f(Z_t, \theta)$, is minimized. The model can intrinsically deal with missing data by inferring Z computing the residuals only on the observed signal Y_o. The inferred vectors then correspond to samples from the posterior distribution conditional on the available signal, $p_\theta(Z|Y_o)$. Since no explicit learnable parameters map inputs to the latent space, the model is more robust to missing values and outliers (masked as missing data). Generative models trained with ABP algorithm outperformed VAEs and GANs on experiments with missing information on computer vision and NLP tasks [4].

We define the occlusion experiments with two parameters. First, the original time-series $Y \in \mathbb{R}^{m \times T}$, is divided in r segments of equal length, $Y_i \in \mathbb{R}^{m \times \frac{T}{r}}$. Second, each feature m in each segment is occluded for model training or inference with probability p. Figure 3 shows an example of occluded data, for a subset of features of one machine of the SMD dataset, with $r = 5$ and $p = 0.5$. Occluded segments are marked in gray. First, DGHL is able to precisely reconstruct the observed data (white region), even when most features are missing. This is most relevant for the anomaly detection task, since only the observed features are used to compute the anomaly score. Second, the model is able to recover missing data with great precision, which can be helpful in complete pipelines with downstream applications.

Figure 2: Occlusion experiment on machine-1-1 of the SMD with $r = 5$ and $p = 0.5$. Blue lines correspond to the actual values and orange lines present the reconstructed time-series with DGHL. Gray areas correspond to the occluded information during training.

We assess the robustness of models to incomplete training data with occluding experiments on the SMD dataset, for different levels of r and p, and using F_1 scores to evaluate performance. Figure 2 shows the F_1 score for DGHL , LSTM-VAE, and OmniAnomaly, for different occlusion probabilities. DGHL achieves the highest scores consistently, with an increasing relative performance on higher data occlusion probability. Moreover, DGHL maintained high F_1 scores even with up to 90% of missing information, without any changes to the hyper-parameters, architecture or training procedure.

Figure 3: F_1 scores for DGHL and LSTM-VAE benchmark for occlusion experiments on SMD for three levels of occlusion probability p, 0, 0.5, 0.9 and $r = 5$.

4.5 Time-series generation

DGHL is trained to generate time-series windows from a latent space representation. We examine how DGHL learns the representation by interpolating and extrapolating between two latent vectors, Z_l and Z_u, inferred from two consecutive windows of a real time-series from the SMD. The trained *Generator network* is then used to generate new windows across the interpolation subspace.

Figure 4 presents the generated windows for interpolated and extrapolated vectors for a subset of the original features. The generated time-series smoothly transition between clear patterns on both shape and scale. Moreover, DGHL is able to generate meaningful time-series on the extrapolation region. This experiment shows how our approach maps similar time-series windows into close points of the latent space, which is a desirable property of latent representations.

4.6 Time-series forecasting

This subsection shows how DGHL can be used as a forecasting model without any changes to the training procedure or architecture. We will perform quantitative analysis on forecasting datasets in future work. DGHL can forecast future values by masking them during the inference of latent vectors, analogous to how the model handles missing data as described in the previous subsection. The observed timestamps (left to the forecasting starting timestamp as represented with the vertical line of Figure 5) are used to infer the current latent vector, which then is used to generate the whole window, producing the forecasts.

Figure 5 shows an example of the forecasts produced by our model for a subset of machine-1-1 of the SMD dataset. In this example, the model is trained to reconstruct and generate windows of size 128. The first 64 timestamps are available during the inference of the latent vector, and the last 64 timestamps corresponds to the forecasted region.

Figure 4: Generated time-series windows from interpolation and extrapolation of latent vectors using DGHL trained on machine-1-1 of the SMD.

Figure 5: Example of forecasts produced by DGHL on a window of machine-1-1 test set of SMD dataset. The model is trained to generate windows of size 128, the first 64 timestamps are available during inference of latent vectors. The last 64 timestamps correspond to the forecasted region.

5 Conclusion

In this paper, we introduced DGHL, a state-of-the-art Deep Generative model for time-series anomaly detection. The proposed model maps time-series windows to a novel hierarchical latent space representation, which leverages time-series dynamics, to encode information more efficiently. A classic ConvNet is used as the *Generator*. DGHL does not rely on auxiliary networks, such as encoders or discriminators, but instead is trained by maximizing the likelihood directly with the Alternating Back-Propagation algorithm. Our model outperforms existing generative models on several benchmark datasets and on settings with missing values. We will explore how our model performs on the time-series forecasting task in future work.

References

[1] Chris U Carmona, François-Xavier Aubet, Valentin Flunkert, and Jan Gasthaus. Neural contextual anomaly detection for time series. *arXiv preprint arXiv:2107.07702*, 2021.

[2] Raghavendra Chalapathy and Sanjay Chawla. Deep learning for anomaly detection: A survey. *arXiv preprint arXiv:1901.03407*, 2019.

[3] Arthur P Dempster, Nan M Laird, and Donald B Rubin. Maximum likelihood from incomplete data via the em algorithm. *Journal of the Royal Statistical Society: Series B (Methodological)*, 39(1):1–22, 1977.

[4] Tian Han, Yang Lu, Song-Chun Zhu, and Ying Nian Wu. Alternating back-propagation for generator network. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

[5] Kyle Hundman, Valentino Constantinou, Christopher Laporte, Ian Colwell, and Tom Soderstrom. Detecting spacecraft anomalies using lstms and nonparametric dynamic thresholding. In *Proceedings of the 24th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 387–395, 2018.

[6] Dan Li, Dacheng Chen, Jonathan Goh, and See-kiong Ng. Anomaly detection with generative adversarial networks for multivariate time series. *arXiv preprint arXiv:1809.04758*, 2018.

[7] Dan Li, Dacheng Chen, Baihong Jin, Lei Shi, Jonathan Goh, and See-Kiong Ng. Mad-gan: Multivariate anomaly detection for time series data with generative adversarial networks. In *International Conference on Artificial Neural Networks*, pages 703–716. Springer, 2019.

[8] Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of markov chain monte carlo*, 2(11):2, 2011.

[9] E Nijkamp, B Pang, T Han, L Zhou, SC Zhu, and YN Wu. Learning multi-layer latent variable model with short run mcmc inference dynamics. In *European Conference on Computer Vision*, 2021.

[10] Bo Pang, Tian Han, Erik Nijkamp, Song-Chun Zhu, and Ying Nian Wu. Learning latent space energy-based prior model. *arXiv preprint arXiv:2006.08205*, 2020.

[11] Bo Pang, Erik Nijkamp, Tian Han, and Ying Nian Wu. Generative text modeling through short run inference. *arXiv preprint arXiv:2106.02513*, 2021.

[12] Daehyung Park, Yuuna Hoshi, and Charles C Kemp. A multimodal anomaly detector for robot-assisted feeding using an lstm-based variational autoencoder. *IEEE Robotics and Automation Letters*, 3(3):1544–1551, 2018.

[13] Lukas Ruff, Jacob R Kauffmann, Robert A Vandermeulen, Grégoire Montavon, Wojciech Samek, Marius Kloft, Thomas G Dietterich, and Klaus-Robert Müller. A unifying review of deep and shallow anomaly detection. *Proceedings of the IEEE*, 2021.

[14] Thomas Schlegl, Philipp Seeböck, Sebastian M Waldstein, Ursula Schmidt-Erfurth, and Georg Langs. Unsupervised anomaly detection with generative adversarial networks to guide marker discovery. In *International conference on information processing in medical imaging*, pages 146–157. Springer, 2017.

[15] Lifeng Shen, Zhuocong Li, and James Kwok. Timeseries anomaly detection using temporal hierarchical one-class network. *Advances in Neural Information Processing Systems*, 33:13016–13026, 2020.

[16] Ya Su, Youjian Zhao, Chenhao Niu, Rong Liu, Wei Sun, and Dan Pei. Robust anomaly detection for multivariate time series through stochastic recurrent neural network. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 2828–2837, 2019.

[17] Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 681–688. Citeseer, 2011.

[18] Jianwen Xie, Ruiqi Gao, Zilong Zheng, Song-Chun Zhu, and Ying Nian Wu. Learning dynamic generator model by alternating back-propagation through time. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 5498–5507, 2019.

[19] Haowen Xu, Wenxiao Chen, Nengwen Zhao, Zeyan Li, Jiahao Bu, Zhihan Li, Ying Liu, Youjian Zhao, Dan Pei, Yang Feng, et al. Unsupervised anomaly detection via variational autoencoder for seasonal kpis in web applications. In *Proceedings of the 2018 World Wide Web Conference*, pages 187–196, 2018.

[20] Hang Zhao, Yujing Wang, Juanyong Duan, Congrui Huang, Defu Cao, Yunhai Tong, Bixiong Xu, Jing Bai, Jie Tong, and Qi Zhang. Multivariate time-series anomaly detection via graph attention network. In *2020 IEEE International Conference on Data Mining (ICDM)*, pages 841–850. IEEE, 2020.