Mining Unseen Classes via Regional Objectness: A Simple Baseline for Incremental Segmentation

Abstract

Incremental or continual learning has been extensively studied for image classifica-
tion tasks to alleviate *catastrophic forgetting*, a phenomenon that earlier learned
knowledge is forgotten when learning new concepts. For class incremental se-
mantic segmentation, such a phenomenon often becomes much worse due to the
semantic shift of the background class, *i.e.*, some concepts learned at previous
stages are assigned to the background class at the current training stage, therefore,
significantly reducing the performance of these old concepts. To address this issue,
we propose a simple yet effective method in this paper, named **Mi**ning unseen
Classes via **R**egional **O**bjectness for **Seg**mentation (MicroSeg). Our MicroSeg is
based on the assumption that *background regions with strong objectness possibly
belong to those concepts in the historical or future stages*. Therefore, to avoid
forgetting old knowledge at the current training stage, our MicroSeg first splits
the given image into hundreds of segment proposals with a proposal generator.
Those segment proposals with strong objectness from the background are then
clustered and assigned newly-defined labels during the optimization. In this way,
the distribution characterizes of old concepts in the feature space could be better
perceived, relieving the *catastrophic forgetting* caused by the semantic shift of
the background class accordingly. Extensive experiments on Pascal VOC and
ADE20K datasets show competitive results with state-of-the-art, well validating
the effectiveness of the proposed MicroSeg. Code is made available.

1 Introduction

Deep learning based methods have made significant achievements on various recognition tasks, while
assuming the data distribution to be fixed or stable and the training samples are independently and
identically distributed [18]. However, in practical scenarios, the data always presents a continuous
stream without a stable distribution. Under these scenarios, the old knowledge will be easily interfered
with or even totally forgotten by continuously acquiring new knowledge, which is generally considered
to be *catastrophic forgetting* [3, 24, 28]. To tackle this problem, many approaches were proposed to
incrementally learn new concepts over time but without forgetting old knowledge, especially for the
classification task, *i.e.*, Class-Incremental Learning (CIL) [17, 19].

Meanwhile, Class-Incremental Semantic Segmentation (CISS), aiming to predict a pixel-wise mask
for an image in CIL scenarios, is crucial for applications like autonomous driving and robotics.
Nevertheless, besides *catastrophic forgetting of old concepts* in CIL, CISS involves an additional key
issue of *background shift* in the image [4], making CISS rather challenging. Specifically, *background
shift* means that the class of background (all other classes that are not learned at the moment) is shifting

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a)   (b)

Figure 1: (a) Comparison of our proposed MicroSeg and the state-of-the-art SSUL [5]. Saliency detection only points out the most important area of an image, leaving the rest unseen classes result in semantic shift and lead to incorrect predictions. The proposed proposal-based approach attends each pixels within the sample, including both things and stuff. (b) Performance comparison of prior works when the number of incremental step increases (mIoU < 45% has been dropped out).

over the learning steps. As a result, such background shift will confuse the model and make it more difficult to distinguish different unseen classes, which generally include the true background (dummy) class, the historical classes, and future classes.

The problems of catastrophic forgetting and background shift in CISS have been studied in recent works [4, 11, 5]. MiB [4] proposed a distillation-based framework to address the background shift issue. PLOP [11] re-models the background labels with pseudo-labeling w.r.t. predictions of the old model for historical classes. However, these prior works did not particularly address the future classes issue that leads to background shift, while instead treating those future classes as background These future classes will not only interfere with old knowledge due to catastrophic forgetting, but also be constantly introduced as current classes to be accurately identified. The state-of-the-art method SSUL [5] tried to address the future class issue by introducing an unknown class according to saliency detection. However, as shown in Fig. 1 (a), as saliency only highlights a few regions within an image, most unseen classes still remain in the background and result in *background shift*. As shown in Fig. 1 (b), with the number of incremental steps increasing, the performance of the aforementioned methods has a dramatic performance drop, suggesting that the *background shift* issue still apparently exists, especially for the challenging setting of more learning steps. Whereas for our approach (MicroSeg-M), it outperforms prior works at each step. Furthermore, if considering the incremental learner lies in a lifelong learning process, the number of unseen classes would be infinite and diverse with endless learning steps. Thus, the unseen classes in each learning step become even more non-negligible, which interfere not only with maintaining concepts of historical classes, but also with the learning of current classes.

To address the above-mentioned issues in CISS, especially the unseen classes, we propose a simple yet effective approach for **Mi**ning unseen **C**lasses via **R**egional **O**bjectness for the **Seg**mentation task (MicroSeg). MicroSeg first generates a set of proposals for input samples with a proposal generator. Each proposal is a binary mask pointing out a segment with strong objectness in an image. This mask is also class-agnostic and can generalize, even to unseen categories. With the assumption of *background regions with strong objectness belong to concepts either in the historical or future steps*, the proposals from the background can be confidently clustered and re-modeled as *unseen classes*. Following that, proposal-based mask classification [9, 8] is applied to label each proposal with current classes and unseen classes. Moreover, to better cache the feature diversity in loose future classes into particular unseen classes, multiple sub-classes are explicitly defined and clustered according to a contrastive loss As shown in Fig. 1 (a), the background shift issue gets alleviated with the discovery of unseen classes, showing the effectiveness of the proposed MicroSeg in reducing semantic ambiguity within categories.

Extensive experimental analysis on Pascal VOC2012 and ADE20K show the effectiveness and competitive performance of the proposed MicroSeg. MicroSeg consistently achieves higher performance across all benchmark datasets, on all incremental learning settings, *e.g.*, an average of 3% improvements over the state-of-the-art method on Pascal VOC2012 and 2% on ADE20K. Particularly,

73 MicroSeg outperforms prior works in the more challenging setting of long-term incremental scenarios,
74 *e.g.*, the performance gain of **6.2%** on Pascal VOC2012.

2 Related work

76 **Class incremental learning (CIL).** Class incremental learning (CIL) is incremental learning
77 bound to classification tasks. Due to the catastrophic forgetting, some approaches consider CIL as
78 a *trade-off* between defying forgetting and learning from new samples of a network. The earlier
79 work to deal with catastrophic forgetting is mainly about parameter isolation [2, 23, 33, 34, 35, 40],
80 which assigns isolated models parameters for each task, while the number of parameters will always
81 grow without an upper bound with task increases. Replay-based approaches [10, 22, 36, 30, 31]
82 were proposed by maintaining a sampler of data for future training. Later, regularization-based
83 methods [1, 17, 19, 41, 29], such as knowledge distillation [15] appears, which rely on a teacher
84 model for transferring knowledge of previous categories to current models.

85 **Semantic segmentation.** In semantic segmentation, deep models have achieved outstanding perfor-
86 mance. FCN [21] and U-Net [32] replace fully connected layers with convolution layers to preserve
87 the location information of pixels. The following methods [16, 25, 38, 39, 44] are mainly based on
88 FCN and enlarge the perceptual field, making it more suitable for semantic segmentation tasks that
89 require intensive annotation. DeepLab series methods [6, 7] contains an Atrous Spatial Pyramid Pool-
90 ing (ASPP) for semantic segmentation using dilated convolution to capture multi-scale information.
91 Meanwhile, MaskFormer [9, 8] regards the semantic segmentation as a mask classification task and
92 introduces the transformer [37] to obtain a better performance. Specifically, they first generate mask
93 proposals and then perform mask classification with the queries generated by the transformer.

94 **Class incremental semantic segmentation (CISS).** Previous work has made attempts at semantic
95 segmentation in incremental learning scenarios. Modeling-the-Background (MiB) [4] first clarifies
96 the background shift in CISS, and proposed a distillation-based framework as in CIL. The subsequent
97 work of Sparse and Disentangled Representations (SDR) [27] exploited a latent space to reduce
98 forgetting, especially stored prototypes (class centroids) to recall the previous categories. Meanwhile,
99 Douillard et al. [11] proposed the approach of PLOP to utilize the pseudo-label of the background
100 pixels in the current step with the previously learned model as supervision. Furthermore, the SSUL [5]
101 introduces an additional unknown class label to unseen objects in the background by an off-the-shelf
102 saliency-map detector, preventing the model from forgetting by freezing model parameters.

3 Method

3.1 Problem Definition

105 We follow the common definition of Class Incremental Semantic Segmentation (CISS) as in the
106 previous work [5, 11], but also give a more clear definition on the *background class* and *unseen*
107 *classes*. In CISS, there are a series of incremental *learning steps*, as $t = 1, \ldots, T$. Let $\mathcal{D}_t$ denotes
108 the dataset for the t_{th} learning step, and $\mathcal{C}_t$ the class set of samples in dataset $\mathcal{D}_t$. For any pair
109 $(\boldsymbol{x}_t, \boldsymbol{y}_t)$ within $\mathcal{D}_t$, $\boldsymbol{x}_t = \{\boldsymbol{x}_{t,i}\}_{i=1}^M$ and $\boldsymbol{y}_t = \{\boldsymbol{y}_{t,i}\}_{i=1}^N$ denote the input image with M pixels, and
110 its ground-truth mask with N pixels, respectively. Unlike previous approaches that specifically define
111 a background class, we argue that in a lifelong incremental learning process with annotations of both
112 stuff and thing, all pixels that not belong to current class will be learned in the future. Therefore, in
113 each learning step, we define the class set $\mathcal{C} = \mathcal{C}_t \cup \{c_u\}$, where $\mathcal{C}_t$ denotes the classes to be learned
114 currently, and c_u denotes a special class consisting of all the historical and future classes. c_u can also
115 be considered as the background class from the perspective of each current learning step, and varies
116 for each learning step, where the *background shift* lies.

117 The CISS model $f_{t,\theta}$ with parameters θ at the t_{th} learning step, aims at assigning each pixel of $\boldsymbol{x}_t$
118 with the probability for each class. The model $f_{t,\theta}$ includes a convolutional feature extractor and a
119 classifier (to classify each category within the union of $\mathcal{C}_{1:t} = \bigcup_{i=1}^t \mathcal{C}_i$ and the unseen class c_u). The
120 model after the learning step t gives a prediction for all historical classes within $\mathcal{C}_{1:t}$. Specifically,
121 the predicted result can be expressed as $\hat{\boldsymbol{y}}_t = \arg\max_{c \in \mathcal{C}_{1:t}} f_{t,\boldsymbol{\theta}}^c(\boldsymbol{x})$. Thus, catastrophic forgetting
122 happens due to the lack of historical and future classes supervision in $\mathcal{C}_t$.

Figure 2: Overall architecture of the proposed MicroSeg.

3.2 Overview of the MicroSeg

Fig. 2 illustrates the overall framework of our proposed method. We design a two-branch structure with the proposed Mining unseen Classes via Regional Objectness (Micro) mechanism. Given an input, the lower branch splits it into segment proposals by proposal generator and classifies them into corresponding categories, while the upper branch performs dense prediction over the whole image. In particular, we introduce the Micro mechanism in the optimization process of both branches, to address the background shift issue.

Proposal generator. The proposal generator aims to generate a group of binary masks $\boldsymbol{P} \in \{0,1\}^{N \times H \times W}$ where N is the number of proposals and H, W denote height and width. Unlike previous semantic segmentation methods, we split the task into segment proposal (class-agnostic) and classification by using [8]. In this study, all proposals are *disjoint*, and each pixel belongs to and only belongs to one proposal.

The dense prediction branch. Our model $f_{t,\boldsymbol{\theta}}$ is composed of a feature extractor $g_{t,\boldsymbol{\theta}_1}$ and a classifier $h_{t,\boldsymbol{\theta}_2}$. For convenience, we abbreviate $f_{t,\boldsymbol{\theta}}$ as $f = h \circ g(\cdot)$. Note that the proposal classification branch and dense prediction branch share the same structure and parameters of $g(\cdot)$, but with different designs of $h(\cdot)$, *i.e.*, $h_p(\cdot)$ and $h_d(\cdot)$. The dense prediction branch performs conventional semantic segmentation, *i.e.*, $\boldsymbol{p}_d = h_d(g(\boldsymbol{x}))$ where $\boldsymbol{p}_d$ indicates the prediction scores (logits).

The proposal classification branch. In this branch, masked average pooling (MAP) [42] is used to generate prototype (centroid) $\boldsymbol{pr} \in \mathbb{R}^{N \times C}$ of each proposal. The logits $\boldsymbol{p} \in \mathbb{R}^{N \times |\mathcal{C}_{1:t}|}$ of each proposal is generated by classifying $\boldsymbol{pr}$, where $|\mathcal{C}_{1:t}|$ is the number of all historical classes. Then $\boldsymbol{p}$ is *reorganized* to the original shape and the prediction scores are assigned accordingly. Formally, the proposal classification branch can be expressed as:

$$\boldsymbol{p}_p = Reg(h_p(MAP(g(\boldsymbol{x}), \boldsymbol{P}))), \tag{1}$$

where $Reg(\cdot)$ is the Proposal Reorganization shown in Fig. 2. The proposal classification branch focuses on objectness aggregation within a proposal, aiming at consistent representations in a particular proposal.

3.3 Mining Unseen Classes via Regional Objectness

Due to the background shift issue (*i.e.*, background class has unclear and unstable semantics during the training steps) mentioned above, the unseen class here refers to all the classes exclude the current foreground class. As mentioned in the observation in Sec. 1, this problem was not well explored in prior works, due to the ignorance of unseen classes. The proposed MicroSeg, on the other hand,

can discover the unseen area with the proposal classification branch. Based on the assumption that background regions with strong objectness possibly belong to those concepts in the historical or future steps, we further remodel the supervision label and **mi**ning unseen **c**lasses via **r**egional **o**bjectness, namely, Micro mechanism. Mirco mechanism clusters proposals with strong objectness in unseen classes, and assigns them with new defined labels during the optimization.

Label remodeling. To capture the knowledge learned in the past learning step $t-1$, we extract the sample on $f_{t-1,\theta}$ during inference to get the pseudo label of mask $\hat{\boldsymbol{y}}_{\boldsymbol{t-1}}$ and the corresponding prediction score map $\boldsymbol{s}_{\boldsymbol{t-1}}$. Formally:

$$
\begin{aligned}
\hat{\boldsymbol{y}}_{\boldsymbol{t-1}} &= \arg\max_{\mathcal{C}_{1:t-1}} f_{t-1,\boldsymbol{\theta}}(\boldsymbol{x}), \\
\boldsymbol{s}_{\boldsymbol{t-1}} &= \max_{\mathcal{C}_{1:t-1}} \sigma(f_{t-1,\boldsymbol{\theta}}(\boldsymbol{x})),
\end{aligned}
\tag{2}
$$

where $\sigma(\cdot)$ denotes Sigmoid function. With the ground truth mask $\boldsymbol{y_t}$ in current step, we augment the supervision label $\tilde{\boldsymbol{y}}_{t,i}$ of pixel i according to the following rules:

$$
\tilde{\boldsymbol{y}}_{t,i} = \begin{cases} \boldsymbol{y_{t,i}} & \text{where } \boldsymbol{y_{t,i}} \in \mathcal{C}_t \\ \hat{\boldsymbol{y}}_{\boldsymbol{t-1,i}} & \text{where } \boldsymbol{y_{t,i}} = c_u \wedge \boldsymbol{s_{t-1,i}} > \tau \\ c_{\hat{u}} & \text{others (or } \boldsymbol{y_{t,i}} = c_u \setminus \mathcal{C}_{1:t-1}) \end{cases}
\tag{3}
$$

where τ represents a threshold for $\hat{\boldsymbol{y}}_{\boldsymbol{t-1,i}}$ and $c_{\hat{u}}$ denotes *future classes* within the unseen class c_u.

Micro mechanism. The micro mechanism is introduced to characterize the various semantics in unseen classes during the optimization and to alleviate the background shift issue. Even the future classes $c_{\hat{u}}$ include several classes of stuff or things, so we represent it as a set of M classes to better cache the feature diversity in those loose future classes. Formally, we represent $c_{\hat{u}} = \{c_{\hat{u},k}\}_{k=1}^K$, and $|c_{\hat{u}}| = K$, where each $c_{\hat{u},k}$ can be viewed as a cluster center of all the future classes. We impose both supervised and unsupervised constraints (detailed in Sec. 3.4) on $c_{\hat{u}}$ during the optimization. For the supervised part, the prediction scores of class $c_{\hat{u}}$ are assembled with the summary of the logits of $c_{\hat{u},k}$:

$$
\boldsymbol{p}_{c_{\hat{u}}} = \sum_{k=1}^K \boldsymbol{p}_k(\boldsymbol{x}),
\tag{4}
$$

where $\boldsymbol{p}_k(\boldsymbol{x}) = f_{t,\boldsymbol{\theta}}^{c_{\hat{u},k}}(\boldsymbol{x}) \in \mathbb{R}^{H \times W}$ is the the prediction scores of class $c_{\hat{u},k}$. H and W denote the height and width of image samples respectively.

We argue that $c_{\hat{u}}$ captures more features with different spatial characteristics in unseen classes. This prevents potential classes from being incorrectly classified into historical classes $\mathcal{C}_{1:t-1}$, which reduces the impact on historical knowledge and the collapse of class predictions. Besides, we equipped our method with the memory sampling strategy [5], resulting in *MicroSeg-M*. With rehearsal of samples from historical learning steps, catastrophic forgetting is alleviated significantly.

3.4 Objective Function

MicroSeg constrains the two branches via Binary Cross-Entropy (BCE) loss, calculated with augmented supervision label $\tilde{\boldsymbol{y}}$ from Eq. 3. Specifically, $\mathcal{L}_{BCE}$ is defined as:

$$
\begin{aligned}
\mathcal{L}_{BCE} = &-\frac{1}{|\mathcal{C}_{1:t}|}\frac{1}{M}\sum_{l=1}^{|\mathcal{C}_{1:t}|}\sum_{i=1}^{M}(\mathbb{1}[\tilde{\boldsymbol{y}}_{t,i}=c^l]\log(\sigma(\boldsymbol{p}_i^l)) + (1-\mathbb{1}[\tilde{\boldsymbol{y}}_{t,i}=c^l])\log(1-\sigma(\boldsymbol{p}_i^l))) \\
&-\frac{1}{M}\sum_{i=1}^{M}(\mathbb{1}[\tilde{\boldsymbol{y}}_{t,i}=c_{\hat{u}}]\log(\sigma(\boldsymbol{p}_{c_{\hat{u}}})) + (1-\mathbb{1}[\tilde{\boldsymbol{y}}_{t,i}=c_{\hat{u}}])\log(1-\sigma(\boldsymbol{p}_{c_{\hat{u}}}))),
\end{aligned}
\tag{5}
$$

where $\boldsymbol{p}_i^l$ means the predicted logits of the i_{th} pixel to the l_{th} class in $\mathcal{C}_{1:t}$. and $\boldsymbol{p}_{c_u}$ corresponds to c_u in Eq. 3 when calculating $\mathcal{L}_{BCE}$. We note BCE loss of two branches as $\mathcal{L}_{BCE}^p$ and $\mathcal{L}_{BCE}^d$.

Benefiting from the class-agnostic proposals, the proposal classification is able to discover the unseen classes in CIL. Meanwhile, the dense prediction is still helpful when the supervised label is complete,

i.e., the first learning step. The reason is that there is no historical class at the very initial learning step, where catastrophic forgetting is not yet happened. The dense prediction branch is also beneficial to learn a robust and versatile feature extractor on base classes, which is vital for the incremental settings, where historical samples are not available in the latter learning steps. The output of the whole model is from the proposal classification branch. The loss for this part is then defined as:

$$\mathcal{L}_{BCE} = \begin{cases} \mathcal{L}_{BCE}^p + \mathcal{L}_{BCE}^d & \text{if } t = 1 \\ \mathcal{L}_{BCE}^p & \text{others} \end{cases}. \tag{6}$$

We also apply another constraint to enhance the unseen classes modeling, *i.e.*, the contrastive loss [13], to capture the diverse concepts in $c_{\hat{u}}$:

$$\mathcal{L}_c = -\frac{1}{K} \sum_{i=1}^{K} \log \frac{\exp(\boldsymbol{p_i} \cdot \boldsymbol{p_i})}{\sum_{j=1}^{K} \exp(\boldsymbol{p_i} \cdot \boldsymbol{p_j})}, \tag{7}$$

where $\cdot$ denotes the inner product. Finally, the overall loss function is defined as below with a hyper-parameter λ to balance the two terms:

$$\mathcal{L} = \mathcal{L}_{BCE} + \lambda \cdot \mathcal{L}_c. \tag{8}$$

4 Experiments

4.1 Experimental Setups

Dataset. We have evaluated our approach on datasets of Pascal VOC 2012 [12] and ADE20K [43]. Pascal VOC 2012 contains 10,582 training images and 1449 validation images, with total of 20 foreground classes and one background class. ADE20K contains 20,210 training images and 2,000 validation images with 100 thing classes and 50 stuff classes.

Protocols. Following the conventions of previous work [11, 5], we evaluate our approach with *overlapped* experimental setup, which is more realistic and challenging than the *disjoint* setting studied by [4, 27]. For the *incremental scenario*, we apply the same representation as in the previous works [4, 27]. For example, the 15-1 scenario of Pascal VOC 2012 (including 20 foreground classes) takes 6 steps to train the model, *i.e.*, 15 classes are used in step 1 and one class for each step in steps 2 to 6. More details of protocols are shown in the supplement materials.

Implementation details. We use DeepLabv3 [6] and ResNet-101 [14] pretrained on ImageNet as the segmentation network. MicroSeg freezes the parameters of the feature extractor in the learning steps $t \geq 1$, following [5]. Our experiments are implemented with PyTorch on two NVIDIA GeForce RTX 3090 GPUs. We choose Mask2Former [8] pre-trained on MS-COCO [20] to generate $N = 100$ class-agnostic proposals. Note that, for fair comparisons, the proposal generator is **not** fine-tuned on any benchmark dataset. The setting of Micro mechanism is $K = 5$ for Pascal VOC 2012 and $K = 1$ for ADE20K, considering dense labeled of both things and stuff on ADE20K dataset. Thus, all pixels of samples in ADE20K can be potential foreground. With the same setting of memory sampling strategy as [5], we set the $|\mathcal{M}| = 100$ for Pascal VOC 2012 and $|\mathcal{M}| = 300$ for ADE20K to evaluate MicroSeg-M. More details are shown in the supplementary materials.

Baselines. We evaluate our MicroSeg and MicroSeg-M, with the comparisons with some classical methods in CIL (*e.g.*, Lwf-MC [19] and ILT [26]), as well as the state-of-the-art methods in CISS, including MiB [4], SDR [27], PLOP [11], and SSUL [5]. For the methods of CIL, we applied them to each experimental setup of CISS. We use the commonly used mean Intersection-over-Union (mIoU) as the evaluation metric for all the experimental evaluation and comparisons. In our experiment, the result of each experiment setting shows in three columns, *i.e.*, mIoU of classes learned in learning step $t = 1$ (*base classes*), in $t \geq 2$ (*novel classes*), and in all historical classes to now, respectively.

4.2 Experimental Results

Experiments on Pascal VOC 2012. Besides the widely discussed scenarios of 19-1, 15-1, and 15-5 in previous works, we introduce several more challenging incremental scenarios, *e.g.*, scenarios

Table 1: Comparison with state-of-the-art methods on Pascal VOC 2012.

Method	VOC 10-1 (11 tasks)			VOC 2-2 (10 tasks)			VOC 15-1 (6 tasks)			VOC 5-3 (6 tasks)			VOC 19-1 (2 tasks)			VOC 15-5 (2 tasks)		
	0-10	11-20	all	0-2	2-18	all	0-15	16-20	all	0-5	6-20	all	0-19	20	all	0-15	16-20	all
LwF-MC [19]	4.7	5.9	4.9	3.5	4.7	4.5	6.4	8.4	6.9	20.9	36.7	24.7	64.4	13.3	61.9	58.1	35.0	52.3
ILT [26]	7.2	3.7	5.5	5.8	5.0	5.1	8.8	8.0	8.6	22.5	31.7	29.0	67.8	10.9	65.1	67.1	39.2	60.5
MiB [4]	12.3	13.1	12.7	41.1	23.4	25.9	34.2	13.5	29.3	57.1	42.6	46.7	71.4	23.6	69.2	76.4	50.0	70.1
SDR [27]	32.1	17.0	24.9	13.0	5.1	6.2	44.7	21.8	39.2	12.1	6.5	8.1	69.1	32.6	67.4	57.4	52.6	69.9
PLOP [11]	44.0	15.5	30.5	24.1	11.9	13.7	65.1	21.1	54.6	17.5	19.2	18.7	75.4	37.4	73.5	75.7	51.7	70.1
SSUL [5]	71.3	46.0	59.3	62.4	42.5	45.3	77.3	36.6	67.6	72.4	50.7	56.9	77.7	29.7	75.4	77.8	50.1	71.2
SSUL-M [5]	74.0	53.2	64.1	58.8	45.8	47.6	78.4	49.0	71.4	71.3	53.2	58.4	77.8	49.8	76.5	78.4	55.8	73.0
MicroSeg (Ours)	72.6	48.7	61.2	61.4	40.6	43.5	80.1	36.8	69.8	**77.6**	59.0	64.3	78.8	14.0	75.7	80.4	52.8	73.8
MicroSeg-M (Ours)	**77.2**	**57.2**	**67.7**	**60.0**	**50.9**	**52.2**	**81.3**	**52.5**	**74.4**	74.8	**60.5**	**64.6**	**79.3**	**62.9**	**78.5**	**82.0**	**59.2**	**76.6**
Joint	82.1	79.6	80.9	76.5	81.6	80.9	82.7	75.0	80.9	81.4	80.7	80.9	81.0	79.1	80.9	82.7	75.0	80.9

(a)   (b)   (c)

Figure 3: (a) mIoU visualization on Pascal VOC 2012 15-1, (b) mIoU visualization on Pascal VOC 2012 2-2 (c) mIoU on Pascal VOC 2012 in scenario 15-1, averaged over 20 different training orders.

of 5-3 (6 steps), 10-1 (11 steps), 2-2 (10 steps). These long-term incremental scenarios is more meaningful, and closer to situations in reality. Tab. 1 shows the final results after all learning steps in each incremental scenario. From the experiments, we can see that our approach has a very clear advantage over previous methods for all incremental scenarios. Even in the without-memory setting, MicroSeg shows performances over the state-of-the-art methods in almost all incremental scenarios. MicroSeg is obviously superior to SSUL with memory-free by the mIoU improvements of 2% to 3%, in the short-term incremental scenarios, *e.g.*, 19-1 and 15-5. While for the long-term scenarios, MicroSeg outperforms SSUL by a wider margin of up to over 7% improvement on mIoU. Not only that, MicroSeg-M (*i.e.*, MicroSeg with memory sampling of past samples) further strengthens the performances, and undoubtedly outperforms all prior methods in all scenarios.

Meanwhile, Fig. 3 (a) shows the change of average mIoU for all past classes under the scenarios of 15-1, with the training step progressing. In the first step, the performances of all methods are similar, but the mIoU starts to decrease as the learning steps increase because of the forgetting of the past classes. However, the mIoU of the previous work drops significantly, while MicroSeg effectively slows down the drop. By ensuring similar semantic segmentation capabilities to previous work, it demonstrates that MicroSeg exactly benefits incremental learning and outperforms prior works. Fig. 3 (b) shows the similar analysis on the long-term scenario of 2-2. The effect of MicroSeg has shown a more significant advantage in such more challenging settings. Fig. 3 (c) shows the performance of MicroSeg with 20 random learning orders of 15-1 incremental scenario. Compared with prior approaches, our approach performs a better result with lower variance. The result illustrates that the robustness of our approach with various task settings outperforms prior methods.

Experiments on ADE20K. On the ADE20K dataset, we have designed multiple incremental scenarios, which have various numbers of learning steps, and we extensively compared MicroSeg with prior methods in these setting. In Tab. 2, as in the case of Pascal VOC 2012, our MicroSeg has achieved a compelling enough performance without any samples sampling memory cost. Moreover, our MicroSeg-M extends this advantage and outperforms the previous state-of-the-art on all incremental scenarios. Further, the performance of our approach is very close to the offline training on base classes, and has a significant improvement to prior works on novel classes.

Qualitative analysis of MicroSeg. Fig. 4 shows qualitative analysis of our approach compared with SSUL-M, the current state-of-the-art method. Results are visualized of each learning step on

Table 2: Comparison with state-of-the-art methods on ADE20K.

Method	ADE 100-5 (11 tasks)			ADE 100-10 (6 tasks)			ADE 100-50 (2 tasks)			ADE 50-50 (3 tasks)		
	0-100	101-150	all	0-100	101-150	all	0-100	101-150	all	0-50	51-150	all
ILT [26]	0.1	1.3	0.5	0.1	3.1	1.1	18.3	14.4	17.0	3.5	12.9	9.7
MiB [4]	36.0	5.7	26.0	38.2	11.1	29.24	40.5	17.2	32.8	45.6	21.0	29.3
PLOP [11]	39.1	7.8	28.8	40.5	13.6	31.6	41.9	14.9	32.9	48.8	21.0	30.4
SSUL[5]	39.9	17.4	32.5	40.2	18.8	33.1	41.3	18.0	33.6	48.4	20.2	29.6
SSUL-M[5]	42.9	17.8	34.6	42.9	17.7	34.5	42.8	17.5	34.4	49.1	20.1	29.8
MicroSeg (Ours)	40.4	20.5	33.8	42.8	**23.1**	**36.3**	40.2	18.8	33.1	48.6	**24.8**	**32.9**
MicroSeg-M (Ours)	**43.6**	**22.4**	**36.6**	**43.7**	22.2	**36.6**	**43.4**	**20.9**	**35.9**	**49.8**	22.0	31.4
Joint	43.8	28.9	38.9	43.8	28.9	38.9	43.8	28.9	38.9	50.7	32.8	38.9

Figure 4: Qualitative analysis of MicroSeg on Pascal VOC 2012. Color-shaded boxes with semantic category and its index indicate the learned class during the corresponding step.

multiple incremental scenarios of Pascal VOC 2012. First, we evaluated the typical scenario of 15-1 with a large number of base classes, to assess the plasticity of the model, *i.e.*, the ability to learn new classes. Regarding the sample of {*dog*, *cat*, *sofa*}, {*dog*, *cat*} belongs to the base classes while {*sofa*} is learnt in step 4. In contrast to SSUL-M, MicroSeg-M extract the feature of {*sofa*} well, and performs a complete segmentation of the novel class *sofa*. The other sample is an image of *TV* (learned in the last learning step). The visualization indicated that, starting from step 4, SSUL-M tends to segment the images incorrectly into current foreground classes, *i.e.*, *sofa* and *train*, which are similar only in low-level semantic features (e.g., similar square shapes). Our approach, on the other hand, better learns the semantic features of the novel class by regional objectness, avoids the wrong segmentation, and segments it correctly and completely after learning the class *TV*.

We further evaluate the model stability (*i.e.*, ability to maintain old knowledge while learning new concepts) on the more challenging long-term scenario of 2-2. First SSUL-M incorrectly classifies *bird* in the image as bike at step 1 before learning *bird*. After learning class *bird*, SSUL-M products an acceptable result in step 3 . However, in the subsequent learning step, the prediction results

become more and more chaotic. However, our MicroSeg has stronger stability, even in a long-term incremental scenario. MicroSeg maintains consistent results in multiple steps, and mitigates the negative effect of noise on the prediction with Micro mechanism.

4.3 Ablation Study

Effect of components in MicroSeg. Tab. 3 shows the contributions of two components of our approach, including proposal classification branch and Micro mechanism. The first row refers to the baseline and the last row stands for MicroSeg. Our ablation study is done on VOC 15-1. We will analyze them separately. First is the proposal classification branch, which improves the mIoU in the base class and the novel class, thus leading to an overall performance improvement.

Table 3: Ablation study of components proposed methods on VOC 15-1, DP (dense prediction branch), Proposal (proposal classification branch), Micro (Micro mechanism),'✓' stands for applying the component. Results in brackets are the improvements over baseline (the first row).

DP	Proposal	Micro	15-1 (6 tasks)		
			0-15	16-20	all
✓	✗	✗	69.1	14.0	56.0
✓	✗	✓	76.8	31.2	65.9 (+9.9)
✓	✓	✗	77.8	32.2	66.9 (+10.9)
✓	✓	✓	**80.1**	**36.8**	**69.8 (+13.8)**

The usage of proposal classification branch increases both stability and plasticity, which are the most critical elements in incremental learning. As for Micro mechanism, observe the first and second rows of the table, the application of Micro mechanism decreases the influence of background shift, significantly improves the result. Due to the design of the Micro mechanism, the model generates more reasonable augmented labels and decreases the influence of background shift, strengthening the ability for acquiring novel classes and maintaining historical concepts. Finally, by combining the two components, MicroSeg can get better performance, 13.8% over the baseline.

Effect of dense prediction branch. Tab. 4 shows the effect of dense prediction branch. As we discussed in Sec. 3.4, this branch is only used when learning step $t = 1$. Hence, the constraint of dense prediction is only applied when the model is trained on the base classes. The result shows the comparison between the experiment of applying proposal classification branch only and using both branches. It can be observed that at the first learning step, dense prediction branch

Table 4: Ablation study of dense prediction branch on VOC 15-1, DP (dense prediction branch), Proposal (proposal classification branch).

setting	step=1	step=6		
	base	0-15	16-20	all
proposal	82.2	77.6	28.0	65.8
proposal+DP	**83.3**	**80.1**	**36.8**	**69.8**

benefits the training on base classes. When all training steps are done, mIoU of novel classes is significantly improved. Dense prediction branch enables the model to be trained better on the base classes. Since MicroSeg applies argument labels composed of pseudo label, the quality of predictions of past classes becomes vital to the results. Thus, it increases the performance of the novel classes by improving the reliability of the argument label.

5 Conclusions

In this study, we propose an effective method, MicroSeg, aiming at class incremental semantic segmentation problems by mining unseen classes via regional objectness. We first introduce proposals into class incremental semantic segmentation, and design a proposal-guided segmentation branch. To tackle background shift, we propose Micro mechanism, clustering and remodeling unseen classes, to capture diverse category features. Experiments demonstrate the effectiveness of our method. MicroSeg and MicroSeg-M achieve remarkable performance, especially on long-term incremental scenarios, outperforming prior state-of-the-art class incremental semantic segmentation methods.

Limitations and societal impact. Although our proposed Micro mechanism effectively mitigates background shift, catastrophic forgetting still exists as the learning step increases. As a simple baseline, we hope our work to inspire following-up research towards more challenging scenarios in incremental learning, *e.g.*, few base classes and long-term settings.

References

[1] Rahaf Aljundi, Francesca Babiloni, Mohamed Elhoseiny, Marcus Rohrbach, and Tinne Tuytelaars. Memory aware synapses: Learning what (not) to forget. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 139–154, 2018.

[2] Rahaf Aljundi, Punarjay Chakravarty, and Tinne Tuytelaars. Expert gate: Lifelong learning with a network of experts. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3366–3375, 2017.

[3] Gert Cauwenberghs and Tomaso Poggio. Incremental and decremental support vector machine learning. *Advances in neural information processing systems*, 13, 2000.

[4] Fabio Cermelli, Massimiliano Mancini, Samuel Rota Bulo, Elisa Ricci, and Barbara Caputo. Modeling the background for incremental learning in semantic segmentation. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 9233–9242, 2020.

[5] Sungmin Cha, YoungJoon Yoo, Taesup Moon, et al. Ssul: Semantic segmentation with unknown label for exemplar-based class-incremental learning. *Proc. Neural Information Processing Systems*, 34, 2021.

[6] Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE Transactions on Pattern Recognition and Machine Intelligence*, 40(4):834–848, 2017.

[7] Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint arXiv:1706.05587*, 2017.

[8] Bowen Cheng, Ishan Misra, Alexander G Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation. *arXiv preprint arXiv:2112.01527*, 2021.

[9] Bowen Cheng, Alexander G. Schwing, and Alexander Kirillov. Per-pixel classification is not all you need for semantic segmentation. *Proc. Neural Information Processing Systems*, 34, 2021.

[10] Matthias De Lange and Tinne Tuytelaars. Continual prototype evolution: Learning online from non-stationary data streams. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8250–8259, 2021.

[11] Arthur Douillard, Yifu Chen, Arnaud Dapogny, and Matthieu Cord. Plop: Learning without forgetting for continual semantic segmentation. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 4040–4050, 2021.

[12] Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88(2):303–338, 2010.

[13] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

[14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[15] Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

[16] Zilong Huang, Xinggang Wang, Lichao Huang, Chang Huang, Yunchao Wei, and Wenyu Liu. Ccnet: Criss-cross attention for semantic segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 603–612, 2019.

[17] Heechul Jung, Jeongwoo Ju, Minju Jung, and Junmo Kim. Less-forgetting learning in deep neural networks. *arXiv preprint arXiv:1607.00122*, 2016.

[18] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[19] Zhizhong Li and Derek Hoiem. Learning without forgetting. *IEEE Transactions on Pattern Recognition and Machine Intelligence*, 40(12):2935–2947, 2017.

[20] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *Proc. European Conference on Computer Vision*, pages 740–755, 2014.

[21] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 3431–3440, 2015.

[22] David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. *Advances in neural information processing systems*, 30, 2017.

[23] Arun Mallya and Svetlana Lazebnik. Packnet: Adding multiple tasks to a single network by iterative pruning. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 7765–7773, 2018.

[24] Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pages 109–165. Elsevier, 1989.

[25] Sachin Mehta, Mohammad Rastegari, Anat Caspi, Linda Shapiro, and Hannaneh Hajishirzi. Esp-net: Efficient spatial pyramid of dilated convolutions for semantic segmentation. In *Proceedings of the european conference on computer vision (ECCV)*, pages 552–568, 2018.

[26] Umberto Michieli and Pietro Zanuttigh. Incremental learning techniques for semantic segmen-tation. In *Proc. IEEE International Conference on Computer Vision Workshops*, pages 0–0, 2019.

[27] Umberto Michieli and Pietro Zanuttigh. Continual semantic segmentation via repulsion-attraction of sparse and disentangled latent representations. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 1114–1124, 2021.

[28] Robi Polikar, Lalita Upda, Satish S Upda, and Vasant Honavar. Learn++: An incremental learning algorithm for supervised neural networks. *IEEE transactions on systems, man, and cybernetics, part C (applications and reviews)*, 31(4):497–508, 2001.

[29] Amal Rannen, Rahaf Aljundi, Matthew B Blaschko, and Tinne Tuytelaars. Encoder based lifelong learning. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1320–1328, 2017.

[30] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. icarl: Incremental classifier and representation learning. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition*, pages 2001–2010, 2017.

[31] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. Ex-perience replay for continual learning. *Proc. Neural Information Processing Systems*, 32, 2019.

[32] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Proc. International Conference on Medical Image Comput-ing and Computer-Assisted Intervention*, pages 234–241, 2015.

[33] Amir Rosenfeld and John K Tsotsos. Incremental learning through deep adaptation. *IEEE Transactions on Pattern Recognition and Machine Intelligence*, 42(3):651–663, 2018.

[34] Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

[35] Joan Serra, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *Proc. International Conference on Machine Learning*, pages 4548–4557, 2018.

[36] Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. *Advances in neural information processing systems*, 30, 2017.

[37] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Proc. Neural Information Processing Systems*, 30, 2017.

[38] Panqu Wang, Pengfei Chen, Ye Yuan, Ding Liu, Zehua Huang, Xiaodi Hou, and Garrison Cottrell. Understanding convolution for semantic segmentation. In *2018 IEEE winter conference on applications of computer vision (WACV)*, pages 1451–1460. Ieee, 2018.

[39] Huikai Wu, Junge Zhang, Kaiqi Huang, Kongming Liang, and Yizhou Yu. Fastfcn: Rethinking dilated convolution in the backbone for semantic segmentation. *arXiv preprint arXiv:1903.11816*, 2019.

[40] Ju Xu and Zhanxing Zhu. Reinforced continual learning. *Advances in Neural Information Processing Systems*, 31, 2018.

[41] Junting Zhang, Jie Zhang, Shalini Ghosh, Dawei Li, Serafettin Tasci, Larry Heck, Heming Zhang, and C-C Jay Kuo. Class-incremental learning via deep model consolidation. In *Proc. IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1131–1140, 2020.

[42] Xiaolin Zhang, Yunchao Wei, Yi Yang, and Thomas S Huang. Sg-one: Similarity guidance network for one-shot semantic segmentation. *IEEE Transactions on Cybernetics*, 50(9):3855–3865, 2020.

[43] Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba. Scene parsing through ade20k dataset. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 633–641, 2017.

[44] Zhen Zhu, Mengde Xu, Song Bai, Tengteng Huang, and Xiang Bai. Asymmetric non-local neural networks for semantic segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 593–602, 2019.