You Only Evaluate Once:
a Simple Baseline Algorithm for Offline RL

Abstract: The goal of offline reinforcement learning (RL) is to find an optimal policy given prerecorded trajectories. Many current approaches customize existing off-policy RL algorithms, especially actor-critic algorithms in which policy evaluation and improvement are iterated. However, the convergence of such approaches is not guaranteed due to the use of complex non-linear function approximation and an intertwined optimization process. By contrast, we propose a simple baseline algorithm for offline RL that only performs the policy evaluation step once so that the algorithm does not require complex stabilization schemes. Since the proposed algorithm is not likely to converge to an optimal policy, it is an appropriate baseline for actor-critic algorithms that ought to be outperformed if there is indeed value in iterative optimization in the offline setting. Surprisingly, we empirically find that the proposed algorithm exhibits competitive and sometimes even state-of-the-art performance in a subset of the D4RL offline RL benchmark. This result suggests that future work is needed to fully exploit the potential advantages of iterative optimization in order to justify the reduced stability of such methods.

Keywords: offline reinforcement learning, conservative policy evaluation

1 Introduction

The standard reinforcement learning setting involves an active component during learning: an agent continuously gathers experience as it learns. This is a very general learning framework that resembles the way animals learn, but the interactive component often hurts the applicability of RL since the agent interaction can be expensive or unsafe. To address this challenge, the offline reinforcement learning paradigm has been proposed, which aims to learn a policy purely from pre-generated data [1]. Considering that many recent breakthroughs in machine learning can be attributed to large-scale data, this new paradigm is very promising. However, the offline setup causes significant theoretic and algorithmic difficulties that need to be resolved to fulfill this promise.

Specifically, actor-critic based off-policy RL algorithms, which iterate policy evaluation and improvement, suffer from the overestimation problem caused by function approximation error and bootstrapping [2, 3] in the offline RL setup, even though the algorithms are equipped with algorithmic techniques [4, 2, 5] that can stabilize learning and mitigate the so-called *Deadly Triad* [6]. This is because over-estimated values cannot be readjusted in offline RL, unlike the ordinary RL setup where incorrectly optimistic actions get executed and corrected.

The Deadly Triad cannot be avoided in these actor-critic algorithms since all of the three components – off-policy learning, function approximation, and bootstrapping – are in use. Many algorithms try to overcome the problem by ensuring the queries for bootstrapping to be within the data manifold of the given offline dataset [7, 8, 9, 10, 11, 12] since over-estimation is prominent when the value function is queried for out-of-distribution inputs. However, strictly speaking, the Deadly Triad occurs due to iteration of the actor-critic algorithm; the first critic update is simply policy evaluation of the action-value function of the behavior policy β using *on-policy* data. While the policy implied by the first value function Q^β is likely to be suboptimal that would be surpassed by iterative algorithms, it has not been fully examined that a greedy policy with regard to Q^β cannot work well in the offline RL setting.

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

To this end, we propose a baseline algorithm, named YOEO, that evaluates the value of a behavior policy once and extracts a greedy policy under the learned value approximation, and by doing so, we examine the hidden presumption of the actor-critic based offline RL algorithms that the iterative process is essential and beneficial. Our algorithm leverages pessimism under uncertainty [13, 14] within the distributional RL framework [15, 16, 17]. Surprisingly, we find that the greedy policy extracted from the value function of the behavior policy with our algorithm exhibits competitive and sometimes even state-of-the-art results in D4RL benchmarks [18]. Our results indicate not only the effectiveness of the proposed algorithm adopting pessimistic regularization, but also implies potential vulnerabilities of the iterative optimization process of actor-critic algorithms in the offline setting, especially when a complex function approximator like a deep neural network is used. We expect that the proposed strong baseline will foster future offline RL research by allowing researchers to measure the actual advantage coming from the iterative process, which is a main concern in offline RL.

2 Related Work

Evaluating and improving a policy with the data generated from a different policy (off-policy RL) has been widely investigated, and several papers have shown theoretical convergence properties of prediction and control algorithms in the off-policy setting [19, 20, 21]. However, theoretical frameworks are limited to linear function approximation, while non-linear function approximation is essential to handle large-scale MDPs. Yet, there have been efforts to build practical algorithms with non-linear function approximators, and they have shown considerable success in various domains [22, 23, 24, 25] tackling real-world RL problems.

In theory, off-policy algorithms can be used in the offline setup without any modifications, but the algorithms often catastrophically fail when applied in the batch setting [7]. This is due to the accumulation of extrapolation error from bootstrapping and the policy improvement step (i.e. $\max$ operation) [7, 8]. In the non-batch setting, new experiences gathered via interaction can prevent this degenerate case, but it is impossible in the batch setting where interaction is prohibited. Pertaining to this problem, much research has been proposed, especially in the context of actor-critic algorithms in which policy evaluation and improvement are iterated. One class of solutions constrains the policy improvement step so that the optimized policy matches the behavior policy, in distribution [9] or in support [8]. In more recent work, a behavior policy for distribution matching is replaced with a prior policy, which is trained along with policy evaluation via weighted behavior cloning [12]. In [11], the policy improvement step is omitted while using the prior policy as a target policy for the evaluation. While the prior works try to overcome the Deadly Triad, we sidestep the problem and examine the hidden assumption of the actor-critic algorithm that the iterative process is essential and beneficial.

The most closely related prior works are behavior cloning-based methods [26, 10] which mimic a subset of good state-action pairs from the pre-generated trajectories. Since these methods approximate a value function for a behavior policy without an iterative policy improvement step, the algorithm does not diverge. The main difference with our proposed approach is that we train an action-value function with regularization and directly use the function at policy execution time without learning a parameterized policy, while the prior works only evaluate a state-value function and filter state-action pairs based on advantage calculated with Monte-Carlo return [26] or TD(k) return [10] to train a parameterized policy.

For principled regularization of the action-value function, we adopt pessimism under uncertainty, which can address the overestimation problem when the given offline dataset is not informative enough to estimate the value of every policy [14]. This pessimism can be applied by directly penalizing Q values for a particular state-action distribution [13], or with model-approximation [27] that leverages uncertainty prediction techniques developed for supervised learning, such as [28] or [29]. While the previous approaches apply pessimism unconditionally for every state [13] or use transition-dynamics based proxies [27] for measuring uncertainty, we propose a regularization method that controls the pessimism strength intelligently by approximating value distributions instead of point estimates.

3 Preliminaries

The common mathematical framework for reinforcement learning is a Markov Decision Process (MDP), which is defined by a tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, T, d_0, r, \gamma)$ defined by a set of states $s \in \mathcal{S}$, a

set of actions $a \in \mathcal{A}$, conditional transition dynamics $T(s'|s, a)$, an initial state distribution d_0, a reward function $r : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, and a discount factor $\gamma \in (0, 1]$. In this framework, the goal of reinforcement learning is to find an optimal policy $\pi(a|s)$ that maximizes an expected sum of discounted reward (return). Formally, the objective is defined as:

$$J(\pi) = \mathbb{E}_{\tau \sim p^\pi} \left[\sum_{t=0}^{H} \gamma^t r(s_t, a_t) \right], \tag{1}$$

where τ is a sequence of states and actions $(s_0, a_0, \ldots, s_H, a_H)$ of length H, and p^π is a trajectory distribution of a policy, which can be represented as:

$$p^\pi(\tau) = d_0(s_0) \prod_{t=0}^{H} \pi(a_t|s_t) T(s_{t+1}|s_t, a_t). \tag{2}$$

One way to find an optimal policy is to estimate an action-value function Q^π, which represents the expected return over possible trajectories following a policy π starting from a given state and action: $Q^\pi(s_t, a_t) = \mathbb{E}_{\tau \sim p^\pi(s,a)} \left[\sum_{t'=t}^{H} \gamma^{t'-t} r(s_{t'}, a_{t'}) \right]$. Q^π function implies a greedy policy $\pi^+(a|s) = \delta(a = \arg\max_b Q^\pi(s, b))$, which is better than or equal to its original evaluation target policy π. Therefore, when we perform policy evaluation (Q estimation) and policy updates iteratively, we can move toward the optimal policy π^* and the optimal Q function Q^{π^*}. Policy evaluation can be done with a Monte-Carlo method, but bootstrapping is commonly used, which utilizes a recursive equation that must be satisfied at convergence:

$$Q^\pi(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim T(s'|s,a), a' \sim \pi(a'|s')} Q^\pi(s', a'). \tag{3}$$

When an MDP is discrete and Q can be represented by a tabular representation (i.e. when $|\mathcal{S}| \times |\mathcal{A}|$ is small), it is known that policy evaluation converges to a correct solution in the limit of the number of transition tuples [6]. However, when an MDP has a large state or action space, Q has to be represented with a function approximator, such as a deep neural network. In addition, when the action space is continuous, directly extracting a better policy from Q becomes infeasible due to the $\arg\max$ operator. These restrictions are addressed in actor-critic algorithms [4, 2, 5] which explicitly alternate policy evaluation and policy improvement with a batch of (online) transition samples D and a parameterized value function $\hat{Q}_\theta$ and a policy π_ϕ:

$$\theta^{k+1} \leftarrow \arg\min_\theta \mathbb{E}_{s,a,s' \sim D} \left[d\big(\hat{Q}_\theta(s, a), r(s, a) + \gamma \mathbb{E}_{a' \sim \pi_{\phi^k}(a'|s')} \hat{Q}_{\theta^k}(s', a') \big) \right] \text{ (policy evaluation)}, \tag{4}$$

$$\phi^{k+1} \leftarrow \arg\max_\phi \mathbb{E}_{s \sim D, a \sim \pi_\phi(a|s)} [\hat{Q}_{\theta^{k+1}}(s, a)] \text{ (policy improvement)}, \tag{5}$$

where k is an update step, and d is a distance measure such as squared l_2 or Huber loss.

4   You Only Evaluate Once

Behind actor-critic based offline RL algorithms, there is a common presumption that the iterative process is essential in achieving better performance than that of the behavior policy, even though it could sacrifice the reliability of the algorithm due to the over-estimation problem. This is because we want to find a policy that behaves differently from the data-generating policy by making counterfactual queries (policy improvement) and answering (policy evaluation) them iteratively [1]. However, it has not been established that a simpler and safer baseline cannot work well—a policy that selects the best action with regard to the action-value function of the *behavior policy*. Without rigorously examining this hypothesis, the true worth of iterative algorithms and counterfactual queries cannot be fully understood.

In this paper, we challenge the iterative offline algorithms by proposing a stable offline algorithm that recovers the best action of behavioral policy $\beta(s)$ that is used to generate an offline dataset D. Formally, our goal is to find the greedy *behavioral* policy $\beta^*(s)$ that selects the best action with respect to Q^β, only considering the action candidates of β:

$$\beta^*(s) := \arg\max_{a \in B(s)} Q^\beta(s, a) \quad \text{where} \quad B(s) = \text{supp}\,\beta(s). \tag{6}$$

When we have an oracle $B(s)$, $\beta^*(s)$ can be estimated by simply making on-policy queries to the approximated action-value function $\hat{Q}^\beta$. This can be reasonably correct as long as the given dataset is sufficient to perform an on-policy evaluation. However, since β can be a mixture of many stochastic policies, directly modeling the support of β is often infeasible, and therefore it is challenging to learn $\beta^*(s)$.

Instead, we propose to learn the greedy behavioral policy by estimating Q^β with pessimistic regularization, such that $\beta^*(s)$ is the greedy policy with respect to the approximated value function $\hat{Q}^\beta$. Pessimistic regularization is essential even for learning Q^β since there are always out-of-distribution actions $\tilde{a} \notin B(s)$ for every state in a dataset D, and the value for an unobserved state-action pair $(s, \tilde{a})$ solely depends on the generalization of the function approximator. Yet, in contrast to pessimistic regularization for Q^*, which requires a calibrated epistemic uncertainty measurement [14] or suffers from over-regularization due to excessive pessimism [13], $\hat{Q}^\beta$ can be properly regularized by enforcing $\hat{Q}^\beta(s, \tilde{a})$ to be smaller than the maximum value of $\hat{Q}^\beta(s, a)$ for $a \in B(s)$. This is valid since $\hat{Q}^\beta$ implies $\beta^*(s)$ if $\hat{Q}^\beta$ for known state-action pair (s, a) is accurate:

Theorem ($\hat{Q}^\beta$ implies β^*). *Let $\hat{Q}^\beta$ be a **valid pessimistic approximation** of Q^β: (1) $\hat{Q}^\beta(s, \tilde{a}) \leq \max_{a \in B(s)} Q^\beta(s, a) \ \forall\, s \in D, \ \tilde{a} \notin B(s)$ and (2) $\hat{Q}^\beta(s, a) = Q^\beta(s, a) \ \forall\, (s, a) \in D$. Then, a greedy policy over $\hat{Q}^\beta$ is β^*.*

Proof. $\arg\max_{a \in \mathcal{A}} \hat{Q}^\beta(s, a) = \arg\max_{a \in B(s)} \hat{Q}^\beta(s, a) = \arg\max_{a \in B(s)} Q^\beta(s, a) = \beta^*(s)$. $\square$

4.1 Practical Implementation

A valid pessimistic approximation of Q^β is based on two functions: (1) support of the behavioral policy $B(s)$ for $s \in D$ and (2) the action-value function of the behavioral policy for the pairs of state $s \in D$ and actions in $B(s)$: $\{Q^\beta(s, a)\}_{a \in B(s)}$. While the Q^β for on-policy input (s, a) can be trained with enough data, the function $B(s)$ is practically hard to train; when the behavioral policy β is a mixture of diverse policies, the output of B is a set containing the arbitrary number of elements. While Kumar et al. [8] try to estimate the support directly with Maximum Mean Discrepancy (MMD), the effect of the estimation error of $B(s)$ on β^* is unpredictable because the error of $\hat{Q}^\beta$ for out-of-distribution input $(s, \tilde{a})$ depends on the generalization ability of the trained $\hat{Q}^\beta$.

Instead of directly approximating $B(s)$ and Q^β, we train a state value distribution $\hat{Y}^\beta$ because the two constraints can be expressed with Y^β, and therefore, we can train the valid pessimistic approximation of Q^β with constrained supervised learning: $\hat{Q}^\beta(s, \cdot) \leq \max_{a \in B(s)} Q^\beta(s, a) = \max_w Y^\beta(s; w)$ and $\hat{Q}^\beta(s, a) = r + \gamma \mathbb{E}_{s' \sim T(s, a)}\big[\mathbb{E}_w[Y^\beta(s'; w)]\big]$. This algorithm can be stable since (1) the training of $\hat{Y}^\beta$ is policy evaluation with on-policy data, and (2) the constraint training of $\hat{Q}^\beta$ only makes in-distribution queries for $\hat{Y}^\beta$.

We propose a two-step approach: we first perform state value distribution learning without any regularization using (s, r, s') transition tuple in D (behavioral policy evaluation) and then train $\hat{Q}^\beta$ in a supervised manner that satisfies the given constraints. Specifically, we train a state-value distribution $\hat{Y}^\beta$ using implicit quantile network (IQN) [17], which is a recently proposed distributional RL algorithm that models a value distribution in the form of an inverse cumulative distribution function $\hat{Y}_\psi(s; \tau)$ where τ is queried probability. In IQN, the parameter ψ can be trained by a distributional TD learning; 1-Wasserstein metric between the bootstrapped target distribution $r + \gamma \hat{Y}_\psi(s')$ and the distribution $\hat{Y}_\psi(s)$ is minimized iteratively for all transition tuples:

$$\psi^{k+1} \leftarrow \arg\min_\psi \mathbb{E}_{(s, r, s') \sim D} \int_0^1 |r + \gamma \hat{Y}_{\psi^k}(s'; \tau) - \hat{Y}_\psi(s; \tau)| d\tau. \tag{7}$$

For details about how the given objective is optimized, please refer to Will et al. [17].

With the approximated state-value distribution $\hat{Y}_\psi$ of the behavior policy β, we train an action-value function $\hat{Q}_\theta$ with a supervised loss for on-policy state-action pair (s, a) and a pessimistic

regularization $\mathcal{R}$ for off-policy pair $(s, \tilde{a})$:

$$L = \mathbb{E}_{(s,a,r,s') \sim D} \frac{1}{2} \big| \hat{Q}_\theta(s, a) - \big(r + \gamma \mathbb{E}\big[\hat{Y}_\psi(s') \big] \big) \big|^2 + \lambda \mathcal{R}(s; \theta) \tag{8}$$

where λ is a hyperparameter that controls the level of pessimism. While we can approximate the expectation of $\hat{Y}_\psi$ with sampling, we use the median value of the distribution $\hat{Y}_\psi(s'; 0.5)$ for computational efficiency.

The main goal of $\mathcal{R}$ is to implement the pessimism on $\hat{Q}_\theta$ and guarantee $\hat{Q}_\theta$ to be a valid pessimistic approximation of Q^β that satisfies $\hat{Q}_\theta(s, \cdot) \leq \max Y^\beta(s)$. While every possible action $a \in \mathcal{A}$ needs to be checked, it is computationally infeasible when the action space is large or infinite. Hence, we sample actions from a static distribution μ (passive pessimistic regularization) and a distribution π_ϕ that is actively changing over training iterations (active pessimistic regularization). Then, we penalize $\hat{Q}_\theta$ if the estimations on the action samples violate the pessimistic constraint. We use a different hyperparameter τ for each of action samples. We sample n_b number of actions from each distribution and use the log-sum-exp trick to change the hard constraint into a soft constraint:

$$\mathcal{R}(s; \theta) = \log \Bigg[\exp(\hat{Y}_\psi(s; \tau_1)) + \sum_{\tilde{a} \sim \pi_\phi(s)} \exp \hat{Q}(s, \tilde{a}) \Bigg] + \log \Bigg[\exp(\hat{Y}_\psi(s; \tau_2)) + \sum_{b \sim \mu(s)} \exp \hat{Q}(s, b) \Bigg].$$
$$\tag{9}$$

We use a random uniform policy for μ while the π_ϕ is trained against trained Q (or a set of Qs when an ensemble technique is used) as same as an ordinary actor in the actor-critic algorithm. However, it is different from the actor in that π_ϕ works as an active regularizer that adversarially finds the wrong generalization part of $\hat{Q}_\beta$. For τ_1 and τ_2, we use 0.9 and 0.1 respectively. While the τ_1 is decided following the definition of valid pessimism with a safe margin of 0.1, we use a small τ_2 since we expect that a random policy will perform poorly. We train multiple $\hat{Q}_\theta$ models and aggregate them by taking a min over inferred $\hat{Q}_\theta$ values in training an π_ϕ to get a robust

---

Algorithm 1: You Only Evaluate Once

Input : Dataset $D = \{(s, a, r, s')\}$,
  Hyper-parameter λ, τ_1, τ_2
Initialize ψ, θ, and ϕ
Train $\hat{Y}_\psi$ with Eq. 7 until convergence
while *until convergence* **do**
  Update θ with a gradient $\nabla_\theta L$ (Eq. 8)
  Update ϕ with a gradient
  $\nabla_\phi \mathbb{E}_{s \sim D} \hat{Q}_\theta \big(s, \pi_\phi(s) \big)$
end

---

value estimate. We train multiple models with different initial parameters and the same data following Osband et al. [30].

The overall algorithm is shown in Algorithm 1. Since the training of $\hat{Q}_\theta$ largely depends on the trained state value distribution $\hat{Y}_\psi$, the correctness of $\hat{Y}_\psi$ is essential in learning greedy behavioral policy β^*. Fortunately, since we are performing policy evaluation with on-policy data, we avoid the Deadly Triad, and it is more likely to converge to a correct Y^β than other methods that perform off-policy learning. Furthermore, the correctness of $\hat{Y}_\psi$ and the regularized $\hat{Q}_\theta$ can be roughly tested by comparing the estimated value with the Monte-Carlo return. This is an extra debugging feature that is only available in YOEO, and we can leverage this to set the hyperparameters.

It is noteworthy that we are leveraging aleatoric uncertainty to implement pessimism. When epistemic uncertainty of action-value function $Q^*(s, a)$ can be estimated with a fixed dataset, using it to penalize the value function is a theoretically justifiable implementation of pessimism [14]. However, measuring epistemic uncertainty is still an open problem when a deep neural network is used even in the simpler supervised learning setting that does not include bootstrapping as RL. For that reason, pessimism is commonly implemented with a proximal objective, such as learning a lower bound of the true Q^* [13] or using an uncertainty proxy [27, 31], and therefore, these approaches often require sensitive hyperparameter tuning to find the right level of pessimism [1]. In contrast, the objective of YOEO allows us to use aleatoric uncertainty that can be directly estimated. Also, the two-step training prevents the error from propagating through bootstrapping, so our method is less susceptible to divergence at the cost of optimality. This makes our algorithm a suitable *baseline* for offline RL that achieves stability at the cost of optimality.

 4.2 Implementation Details

The state value distribution $\hat{Y}_\psi$ is parameterized following Will et al. [17]: $\hat{Y}_\psi(s;\tau) = F_\psi\big(E_\psi(s) \odot T_\psi(\tau)\big)$ where F_ψ and E_ψ is a multi-layer perceptron (MLP) that maps an input into 64 and 1-dimensional output, and T_ψ is a cosine-based embedding function that maps a 64-dimensional cosine basis vector $[\cos(\pi i \tau)]_{i=0}^{64}$ into the same length feature vector with a single fully-connected layer with ReLU activation. For $\hat{Q}_\theta$, we used an MLP that maps a concatenation of state and action input to a single scalar value. We used a deterministic policy π_ϕ that maps a state into an action-dimensional vector. For every MLP, we used 2 fully-connected layers, and we trained five $\hat{Y}_\psi$s and $\hat{Q}_\theta$s with a single π_θ. For the action samples used in Eq. 9, we added an action noise following Fujimoto et al. [2]. The actor π_ϕ at the last iteration is used for the evaluation. Both in training $\hat{Y}_\psi$ and $\hat{Q}_\theta$, we adapted an n-step TD trick instead of using TD(0); we sampled $(s_t, a_t, \sum_{t'=t}^{t+9} \gamma^{t-1} r_t, s_{t+10})$ from a dataset instead of sampling (s, a, r, s'). Also, we used a slowly moving target network in calculating the bootstrapped distribution by keeping an exponential moving average of ψ [4] and using the averaged weight for bootstrapping. All other hyperparameters used for the experiments are shown in Appendix, and code is also available [1].

5 Experiments

We aim to study the following question: how much performance gain do potentially risky policy iteration algorithms provide compared to more stable baseline algorithm YOEO? We compare the performance of YOEO against several baselines and prior works based on policy iteration: behavior cloning (BC), soft actor-critic (SAC) [5] without interaction, two policy constrained methods, namely bootstrapping error accumulation reduction (BEAR) [8] and behavior regularized actor-critic (BRAC) [9], and conservative Q-learning (CQL) [13].

The comparison is made on a subset of datasets in the D4RL offline RL benchmark [18]. We use MuJoCo [32] locomotion tasks [33] and Adroit hand-manipulation tasks [34]. For MuJoCo locomotion tasks, we use three environments (`hopper`, `walker2d`, and `halfcheetah`) in four different settings (`random`, `medium-replay`, `medium`, and `medium-expert`). For Adroit hand-manipulation tasks, we use four environments (`pen`, `door`, `relocate`, and `hammer`) in two settings (`human` and `cloned`). We train YOEO for 1 million stochastic gradient steps for both $\hat{Y}_\psi$ and $\hat{Q}_\theta$, then we report the average normalized performance score over 100 trajectories. The results are displayed in Table 1.

Despite the fact that YOEO aims to learn a greedy behavioral policy $\beta^*(s)$ with respect to Q^β rather than try to learn π^*, it shows highly competitive results: it achieves better performance than the current state-of-the-art model-free offline RL algorithms in four datasets (hopper-random, walker2d-medium-replay, hopper-medium, hopper-medium-expert, and hammer-cloned), and competitive performance across all other configurations surpassing most of the other offline RL algorithms. The results indicate that the previous offline RL algorithms fail to fully exploit the potential benefit of iterative evaluation and update.

5.1 Ablation Study: how much will each regularization term affect the performance?

We conduct an ablation study to show the effectiveness of the regularization and the contribution of each term in Eq. 9. Specifically, we consider two ablations: (1) $\hat{Q}^\beta$ trained only via TD loss based on (s, a, r, s', a') tuple without any regularization (denoted as $\hat{Q}^\beta \backslash \mathcal{R}$) and (2) $\hat{Q}^\beta$ trained without the second term in Eq. 9 (denoted as $\hat{Q}^\beta \backslash \mu$). Additionally, we test the effect of the ensemble by changing the number of trained models. The experiment settings and the results are summarized in Table 2.

We confirm the necessity of pessimistic regularization even when we do on-policy policy evaluation; the qualitative results shown in Figure A.1 reveal that $\hat{Q}_\theta \backslash \mathcal{R}$ can estimate the ground-truth value for on-policy input (s, a), but it fails to estimate the value for out-of-distribution input (s, b), especially when the given dataset is homogeneous such as the `-medium` dataset whose behavior policy β is not a mixture of different policies. This is because $\hat{Q}^\beta$ behaves more like a $\hat{V}^\beta$, ignoring the action, since

---

[1] https://github.com/anonymous/anonymous.git (included in supplementary material)

Table 1: Performance of YOEO and prior methods on a subset of D4RL benchmarks. Each number represents the performance relative to a random policy as 0 and an expert policy as 100. All the numbers except ours are borrowed from [18] and [13]. The numbers of our results are averaged over 3 different random seeds.

Type	Environemt	BC	SAC-offline	BEAR	BRAC	AWR	BCQ	CQL $(\mathcal{H})$	YOEO (π_ϕ)	YOEO $(\tilde{\pi})$
Random	HalfCheetah	2.1	30.5	25.1	31.2	2.5	2.2	35.4	4.5	5.7
	Hopper	9.8	11.3	11.4	**12.2**	10.2	10.6	10.8	**12.2**	12.3
	Walker2D	1.6	4.1	**7.3**	1.9	1.5	4.9	7	4.9	4.1
Medium-Replay	HalfCheetah	38.4	-2.4	38.6	47.7	40.3	38.2	**46.2**	36.2	30.9
	Hopper	11.8	3.5	33.7	0.6	28.4	33.1	**48.6**	42.5	37.2
	Walker2D	11.3	1.9	19.2	0.9	15.5	15	26.7	**41.9**	30.1
Medium	HalfCheetah	36.1	-4.3	41.7	**46.3**	37.4	40.7	44.4	45.1	43.6
	Hopper	29	0.8	52.1	31.1	35.9	54.5	58	**71.9**	62.5
	Walker2D	6.6	0.9	59.1	81.1	17.4	53.1	**79.2**	74.1	76.2
Medium-Expert	HalfCheetah	35.8	1.8	53.4	44.2	52.7	**64.7**	62.4	41.9	35.9
	Hopper	111.9	1.6	96.3	0.8	27.1	110.9	111	**112.1**	112
	Walker2D	6.4	-0.1	40.1	81.6	53.8	57.5	**98.7**	89.5	84.3
human	pen	34.4	6.3	-1	8.1	12.3	**68.9**	37.5	17.3	43.6
	door	0.5	3.9	-0.3	-0.3	0.4	0	**9.9**	-0.1	5.7
	relocate	0	0	-0.3	-0.3	0	-0.1	0.2	-0.1	0.2
	hammer	1.5	0.5	0.3	0.3	1.2	0.5	4.4	2.6	**5.4**
cloned	pen	**56.9**	23.5	26.5	1.6	28	44	39.2	32.6	30.5
	door	-0.1	0	-0.1	-0.1	0	0	0.4	0.1	**0.7**
	relocate	-0.1	-0.2	-0.3	-0.3	-0.2	-0.3	-0.1	-0.1	-0.2
	hammer	0.8	0.2	0.3	0.3	0.4	0.4	2.1	**2.7**	1.2

Table 2: Ablation experiment results. The normalized performance over 3 random seeds is displayed.

		$\hat{Q}_\theta \backslash \mathcal{R}$	$\hat{Q}_\theta \backslash \mu(s)$	$\hat{Q}_\theta$ (Ens. 1)	$\hat{Q}_\theta$ (Ens. 3)	YOEO
Supervised w/ $\hat{Y}_\psi$		✗	✓	✓	✓	✓
$\mathcal{R}$ w/ $\mu(s)$		✗	✓	✓	✓	✓
$\mathcal{R}$ w/ $\pi(s)$		✗	✗	✓	✓	✓
# Ensembles		5	5	1	3	5
Medium-Replay	Hopper	30.6	**49.1**	21.3	36.5	42.5
	Walker2D	3.7	21.2	18.9	28.2	**41.9**
Medium	Hopper	2.7	14.9	54.6	65.9	**71.9**
	Walker2D	-0.2	29	66.3	75.9	74.1
Medium-Expert	Hopper	10.4	58.2	89.6	112	112.1
	Walker2D	3	0.3	62.2	**94.9**	89.5

an effective action a is predictable based on s. The performance degradation of $\hat{Q}_\theta \backslash \mu$ indicates that a random policy μ is a good heuristic that can prevent the degeneration of the action-value function; the second regularization term using μ can foster the discrimination ability of the value function by enforcing $\hat{Q}_\theta$ to estimate a different value for (s, a) and (s, b), and this can increase the performance significantly especially when the given dataset is generated with a homogeneous policy.

We also observe the performance benefit of training more models and ensembling them, especially for `-medium-replay` type datasets. We hypothesize that YOEO's pessimistic regularization method has high variance due to the stochasticity of the loss function, and the ensembling technique can improve learning by enabling robust prediction for off-policy data from which the stochasticity is derived.

5.2 How does constrained $\tilde{\pi}$ perform?

While the greedy behavioral policy β^* can only execute an action that is in the support of the behavior policy β, the resulting π_ϕ is not guaranteed to satisfy that condition. Thus, we ask: how much will performance change if we use a policy $\tilde{\pi}$ that is explicitly constrained to emit an action that only exists in a dataset? Constraining the action space of the policy could provide a performance benefit

when the regularization $\mathcal{R}$ is less effective due to restriction of the data, such as the sample size, that allows a large room for the adversarial attack; when there is a large room for the adversarial attack, π_ϕ will continuously try to regularize $\hat{Q}_\theta$ by suggesting diverse actions $\tilde{a}$ while it does not converge to the desired policy β^*. Therefore, directly utilizing π_ϕ would result in a bad performance, but the action set restricted policy $\tilde{\pi}$ can perform well by querying $\hat{Q}_\theta$ with an action $a \in B(s)$. To examine this hypothesis, we define a greedy non-parametric policy $\tilde{\pi}$ that selects the best action among actions that exist in the dataset D: $\tilde{\pi}(s) = \arg\max_{a \sim D} \hat{Q}_\theta(s, a)$. For computational efficiency, we reduce the search space by first finding the 100 nearest states in raw-state space and querying the actions of those states. We use an approximated nearest neighbor algorithm called Annoy [35].

The results are shown in the last column of Table 1. $\tilde{\pi}$ shows a better result than π_ϕ in `-human` type dataset in Adroit tasks while it shows similar results in other datasets. This confirms our hypothesis since the size of the `-human` type dataset is relatively small compared to others, so there are diverse actions that π_ϕ need to regularize.

5.3 Why do CQL and other methods fail?

YOEO outperforms the current state-of-the-art methods, specifically CQL, in several datasets. Considering that the pessimistic regularization of YOEO is milder than CQL, we hypothesize that the failure of CQL to surpass β^* is derived from over-regularization; YOEO only penalizes $\hat{Q}_\theta(s, b)$ that are larger than the maximum value of the state value distribution $\max \hat{Y}_\psi$, while CQL performs unbounded minimization for $\hat{Q}^*(s, b)$ and maximization for $\hat{Q}^*(s, a)$. When b is sampled from a policy based on $\hat{Q}$, the regularization will practically penalize $\hat{Q}^*(s, b)$ until the value becomes smaller than $\hat{Q}^*(s, a)$. Even when $\hat{Q}^*(s, a)$ is smaller than $\max \hat{Y}_\psi$, CQL would still induce more pessimism than YOEO.

Table 3: Experimental results of CQ$^\beta$L and its variants. MR, M, and ME represent medium-replay, medium, and medium-expert dataset types, and H and W represent Hopper and Walker2D environments respectively. The averaged normalized performance over 3 random seed is displayed.

		YOEO	CQL(ρ)	CQ$^\beta$L(ρ)	MOReL
MR	H	42.5	26.9	29.7	**93.6**
	W	41.9	13.3	26.7	**49.8**
M	H	71.9	31.7	32	**95.4**
	W	74.1	**78.8**	65	77.8
ME	H	**112.1**	111.9	111.5	108.7
	W	89.5	63	83	**95.6**

Furthermore, when $\hat{Q}^*$ is over-regularized, we can expect that $\hat{Q}^*$ would behave more like $\hat{Q}^\beta$, losing the advantage of the iterative process.

To confirm this hypothesis, we modify CQL to estimate Q^β instead of Q^* by changing the TD loss to be computed with (s, a, r, s', a'), not (s, a, r, s'). The pessimistic regularization part remains intact. We denote this algorithm CQ$^\beta$L. We ran the CQL(ρ) algorithm, and the results are displayed in Table 3. CQ$^\beta$L(ρ) works similarly to CQL(ρ), and this supports our hypothesis that the CQL is over-regularizing. The success of the model-based offline algorithm (MOReL [31]), implies that the over-regularization of CQL can be avoided by utilizing the uncertainty that CQL lacks.

6 Discussion

We investigate a simple baseline algorithm for offline RL that only evaluates the value function of the behavior policy as opposed to approximate Q^* with unstable iterative process. Since the proposed algorithm does not involve a policy optimization step and value re-evaluation based on the updated policy, the algorithm can be stable, but the resulting policy is more likely to be suboptimal. This makes the algorithm an appropriate baseline for actor-critic algorithms that ought to outperform this baseline if there is indeed value in iterative optimization in the offline setting. In the experiments, the proposed baseline surprisingly shows competitive results on the several D4RL benchmarks, surpassing the state-of-the-art results in some tasks. This implies the usefulness of conservativeness under uncertainty, which can prevent incorrect generalization behavior of a complex function approximator occurring due to lack of data, as well as the potential flaws of iterative optimization in actor-critic algorithms in the offline setting. Therefore, it is essential for future work to build a theoretical framework that sheds light on iterative optimization and generalization of offline actor-critic methods that use deep neural networks, if iterative optimization is to be fully taken advantage of.

References

[1] S. Levine, A. Kumar, G. Tucker, and J. Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[2] S. Fujimoto, H. Hoof, and D. Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, pages 1582–1591, 2018.

[3] J. Fu, A. Kumar, M. Soh, and S. Levine. Diagnosing bottlenecks in deep q-learning algorithms. In *International Conference on Machine Learning*, 2019.

[4] T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016. URL http://arxiv.org/abs/1509.02971.

[5] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870, 2018. URL http://proceedings.mlr.press/v80/haarnoja18b.html.

[6] R. S. Sutton and A. G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, Cambridge, MA, USA, 2018. ISBN 978-0262039246. URL http://www.incompleteideas.net/book/the-book-2nd.html.

[7] S. Fujimoto, D. Meger, and D. Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pages 2052–2062, 2019.

[8] A. Kumar, J. Fu, M. Soh, G. Tucker, and S. Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems 32*, pages 11784–11794, 2019.

[9] Y. Wu, G. Tucker, and O. Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

[10] X. B. Peng, A. Kumar, G. Zhang, and S. Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

[11] Z. Wang, A. Novikov, K. Żołna, J. T. Springenberg, S. Reed, B. Shahriari, N. Siegel, J. Merel, C. Gulcehre, and N. Heess. Critic regularized regression. *arXiv preprint arXiv:2006.15134*, 2020.

[12] N. Siegel, J. T. Springenberg, F. Berkenkamp, A. Abdolmaleki, M. Neunert, T. Lampe, R. Hafner, N. Heess, and M. Riedmiller. Keep doing what worked: Behavior modelling priors for offline reinforcement learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rke7geHtwH.

[13] A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforcement learning. *arXiv preprint arXiv:2006.04779*, 2020.

[14] J. Buckman, C. Gelada, and M. G. Bellemare. The importance of pessimism in fixed-dataset policy optimization. *arXiv preprint arXiv:2009.06799*, 2020.

[15] M. G. Bellemare, W. Dabney, and R. Munos. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, page 449–458, 2017.

[16] W. Dabney, M. Rowland, M. G. Bellemare, and R. Munos. Distributional reinforcement learning with quantile regression. In *AAAI Conference on Artificial Intelligence*, pages 2892–2901, 2018. URL https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/17184.

[17] Will, G. Ostrovski, D. Silver, and R. Munos. Implicit quantile networks for distributional reinforcement learning. In *International Conference on Machine Learning*, pages 1104–1113, 2018. URL http://proceedings.mlr.press/v80/dabney18a.html.

[18] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[19] M. G. Lagoudakis and R. Parr. Least-squares policy iteration. *Journal of machine learning research*, 4(Dec):1107–1149, 2003.

[20] R. Munos. Error bounds for approximate value iteration. In *Proceedings of the National Conference on Artificial Intelligence*, volume 20, page 1006. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2005.

[21] A.-m. Farahmand, C. Szepesvári, and R. Munos. Error propagation for approximate policy and value iteration. In *Advances in Neural Information Processing Systems*, pages 568–576, 2010.

[22] G. Tesauro. Td-gammon, a self-teaching backgammon program, achieves master-level play. *Neural computation*, 6(2):215–219, 1994.

[23] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[24] D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

[25] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

[26] Q. Wang, J. Xiong, L. Han, H. Liu, T. Zhang, et al. Exponentially weighted imitation learning for batched historical data. In *Advances in Neural Information Processing Systems*, pages 6288–6297, 2018.

[27] T. Yu, G. Thomas, L. Yu, S. Ermon, J. Zou, S. Levine, C. Finn, and T. Ma. Mopo: Model-based offline policy optimization. *arXiv preprint arXiv:2005.13239*, 2020.

[28] B. Lakshminarayanan, A. Pritzel, and C. Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Neural Information Processing Systems*, page 6405–6416, 2017.

[29] J. van Amersfoort, L. Smith, Y. W. Teh, and Y. Gal. Uncertainty estimation using a single deep deterministic neural network. In *International Conference on Machine Learning*, 2020.

[30] I. Osband, C. Blundell, A. Pritzel, and B. Van Roy. Deep exploration via bootstrapped dqn. In *Advances in Neural Information Processing Systems*, volume 29, pages 4026–4034, 2016.

[31] R. Kidambi, A. Rajeswaran, P. Netrapalli, and T. Joachims. Morel: Model-based offline reinforcement learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 21810–21823. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/f7efa4f864ae9b88d43527f4b14f750f-Paper.pdf.

[32] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IROS*, pages 5026–5033. IEEE, 2012. URL http://dblp.uni-trier.de/db/conf/iros/iros2012.html#TodorovET12.

[33] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym. *CoRR*, abs/1606.01540, 2016.

[34] A. Rajeswaran, V. Kumar, A. Gupta, G. Vezzani, J. Schulman, E. Todorov, and S. Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[35] E. Bernhardsson. Approximate nearest neighbors oh yeah (annoy). https://github.com/spotify/annoy, 2020.