META LEARNING LOW RANK COVARIANCE FACTORS FOR ENERGY-BASED DETERMINISTIC UNCERTAINTY

ABSTRACT

Numerous recent works utilize bi-Lipschitz regularization of neural network layers to preserve relative distances between data instances in the feature spaces of each layer. This distance sensitivity with respect to the data aids in tasks such as uncertainty calibration and out-of-distribution (OOD) detection. In previous works, features extracted with a distance sensitive model are used to construct feature covariance matrices which are used in deterministic uncertainty estimation or OOD detection. However, in cases where there is a distribution over tasks, these methods result in covariances which are sub-optimal, as they may not leverage all of the meta information which can be shared among tasks. With the use of an attentive set encoder, we propose to meta learn either diagonal or diagonal plus low-rank factors to efficiently construct task specific covariance matrices. Additionally, we propose an inference procedure which utilizes scaled energy to achieve a final predictive distribution which can better separate OOD data, and is well calibrated under a distributional dataset shift.

1 INTRODUCTION

Accurate uncertainty in predictions (calibration) lies at the heart of being able to trust decisions made by deep neural networks (DNNs). However, DNNs can be mis-calibrated when given out-of-distribution (OOD) test examples (Ovadia et al., 2019; Guo et al., 2017). Hein et al. (2019) show that the problem can arise from ReLU non-linearities introducing linear polytopes into decision boundaries which lead to arbitrary high confidence regions outside of the domain of the training data. Another series of works (van Amersfoort et al., 2021; Liu et al., 2020a; Mukhoti et al., 2021; van Amersfoort et al., 2021) link the problem to feature collapse, whereby entire regions of feature space collapse into singularities which then inhibits the ability of a downstream function to differentiate between points after the collapse, which destroys any information which could be used to differentiate them. When these collapsed regions include areas of OOD data, the model loses any ability to differentiate between in-distribution (ID) and OOD data.

A solution to prevent feature collapse is to impose bi-Lipschitz regularization into the network which enforces both an upper and lower Lipschitz bound on the functions operating in feature space (van Amersfoort et al., 2021; Liu et al., 2020a), preventing feature collapse. Such features from bi-Lipschitz regualarized extractors are then used to improve downstream tasks such as OOD detection or uncertainty quantification. Broadly speaking, previous works have done this by constructing covariance matrices from the resulting features in order to aid in the uncertainty quantification (Liu et al., 2020a; Van Amersfoort et al., 2020) or OOD detection (Mukhoti et al., 2021). Intuitively, features from a Lipschitz regularized extractor make for more expressive covariances, due to the preservation of identifying information within different features.

However, empirical covariance estimation is limited when there are few datapoints on hand, such as in few-shot learning. A key aspect of few-shot learning is to learn from a task distribution, but empirical covariance estimation methods are not able to effectively encode shared knowledge over the task distribution, even when the features used to calculate the covariance come from a meta-learned feature extractor (see Figure 6). As a result, the empirical covariance matrices are not expressive given limited data and thus the model loses its ability to effectively adapt to a task and make calibrated predictions.

Figure 1: Examples of the learned entropy surface of protypical networks (top row) and our Proto Mahalanobis (bottom row). Each pixel in the the background color represents the entropy given to that coordinate in input space. Prototypical networks exhibit high confidence in areas where there has been no evidence, leading to high calibration error when presented with OOD data.

Another obstacle, highlighted by Mukhoti et al. (2021), is that plain softmax classifier cannot accurately model epistemic uncertainties. A contributing factor to this is the shift invariance property of the softmax function. Specifically, even if an evaluation point comes from an OOD area and is assigned low logits values (low energy), this alone is not sufficient for a well calibrated prediction. Small variations in logit values can lead to arbitrarily confident predictions due to the shift invariance. From the perspective of Prototypical Networks (Snell et al., 2017), we highlight this problem in Figure 3, although it applies to linear softmax classifiers as well.

In the following work, we first propose a method of meta-learning class-specific covariance matrices that is transferable across the task distribution. Specifically, we meta-learn a function that takes a set of class examples as an input and outputs a class-specific covariance matrix which is in the form of either a diagonal or diagonal plus low-rank factors. By doing so, the resulting covariance matrices remain expressive even with limited amounts of data. Further, in order to tackle the limitation caused by the shift invariance property of the softmax function, we propose to use scaled energy to parameterize a logit-normal softmax distribution which leads to better calibrated softmax scores. We enforce its variance to increase as the energy increases, and vice versa. In this way, the softmax prediction can become progressively more uniform between ID and OOD data, after marginalizing over logit-normal distribution (see example in Figure 1).

By combining those two components, we have the final inference procedure to effectively separate OOD data, and achieves a well calibrated probabilistic model using a deterministic DNN. Our contributions are as follows:

- We show that existing approaches fail to generalize to the meta-learning setting.
- We propose a meta learning framework which predicts diagonal or low-rank covariance factors as a function of a support set.
- We propose an energy-based inference procedure which leads to improved OOD detection, and better calibrated uncertainty.

2 RELATED WORK

Mahalanobis Distance. Mahalanobis distance has been used in previous works for OOD detection (Lee et al., 2018) which also showed that there is a connection between softmax classifiers and Gaussian discriminant analysis, and that the representation space in the latent features of DNN's provides for an effective multivariate Gaussian distribution which can be more useful in constructing

| (a) ProtoSNGP | (b) ProtoDDU | (c) Proto Mahalanobis |

Figure 2: Comparison between covariances learned in SNGP (Liu et al., 2020a), DDU (Mukhoti et al., 2021) and Proto Mahalanobis in the few shot setting. Covariance generated from Both SNGP and DDU are close to a multiple of the identity matrix, while that of ProtoMahalanobis contains significant off-diagonal elements.

class conditional Gaussian distributions than the output space of the softmax classifier. The method outlined in Lee et al. (2018) provides a solid groundwork for our method, which also utilizes Mahalanobis distance in the latent space, and adds a deeper capability to learn meta concepts which can be shared over a distribution of tasks.

Post Processing. We refer to post-processing as any method which applies some function after training and before inference in order to improve the test set performance. In the calibration literature, temperature scaling (Guo et al., 2017) is a common and effective post-processing method. As the name suggests, temperature scaling scales the logits by a constant before going through the softmax function. The temperature is tuned such that the negative log-likelihood (NLL) on a validation set is minimized. Previous works which utilize covariance (Lee et al., 2018; Mukhoti et al., 2021; Liu et al., 2020a) have also applied post-processing methods to construct latent feature covariance matrices after training. While effective for large data, these post-processing methods make less expressive covariances in the limited data regime of few-shot learning, as we demonstrate in Figure 2.

Bi-Lipschitz Regularization. Adding a regularizer to enforce functional smoothness of a DNN is a useful tactic in stabilizing the training of generative adversarial networks (GANs) (Miyato et al., 2018; Arjovsky et al., 2017), improving predictive uncertainty (Liu et al., 2020a; Van Amersfoort et al., 2020), and aiding in OOD detection (Mukhoti et al., 2021). By imposing a smoothness constraint on the network, distances which are semantically meaningful w.r.t. the feature manifold can be preserved in the latent representations, allowing for downstream tasks (such as uncertainty estimation) to make use of the preserved information. (Van Amersfoort et al., 2020) showed that without this regularization, a phenomena known as feature collapse can map regions of feature space onto singularities (Huang et al., 2020), where previously distinct features now become indistinguishable. For both uncertainty calibration and OOD detection, feature collapse can map OOD features onto the same feature spaces as ID samples, adversely affecting both calibration and OOD seperability.

Meta Learning. The goal of meta learning (Schmidhuber, 1987; Thrun & Pratt, 1998) is to leverage shared knowledge which may apply across a distribution of tasks. In the few shot learning scenario, models leverage general meta-knowledge gained through episodic training on a task distribution (Vinyals et al., 2016; Ravi & Larochelle, 2017), which allows for effective adaptation and inference on a task which may contain only limited amounts of data during inference. The current meta-learning approaches are roughly categorized into metric-based (Vinyals et al., 2016; Snell et al., 2017) or optimization-based approaches (Finn et al., 2017). In this work, we focus on metric-based approaches because they are closely related to generative classifiers, which have been shown to be important for epistemic uncertainty (Mukhoti et al., 2021).

3 APPROACH

We start by introducing a task distribution $p(\tau)$ which randomly generates tasks containing a support set $\mathcal{S} = \{(\tilde{\mathbf{x}}_i, \tilde{y}_i)\}_{i=1}^{N_s}$ and a query set $\mathcal{Q} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{N_q}$. Then, given randomly sampled task $\tau = (\mathcal{S}, \mathcal{Q})$, we meta-learn a generative classifier that can estimate the class-wise distribution of query examples, $p(\mathbf{x}|y = c, \mathcal{S})$ conditioned on the support set $\mathcal{S}$, for each class $c = 1, \ldots, C$. A generative classifier is a natural choice in our setting due to fact that it utilizes feature space densities which has been shown to be a requirement for accurate epistemic uncertainty prediction (Mukhoti et al., 2021). Under the class-balanced scenario $p(y = 1) = \cdots = p(y = C)$ we can easily predict

the class labels as follows.

$$p(y = c|\mathbf{x}, \mathcal{S}) = \frac{p(\mathbf{x}|y = c, \mathcal{S})}{\sum_{c'=1}^{C} p(\mathbf{x}|y = c', \mathcal{S})}. \tag{1}$$

3.1 Limitations of Existing Generative Classifiers

Possibly one of the simplest forms of deep generative classifier is ProtoNets (Snell et al., 2017). In ProtoNets we assume a deep feature extractor f_θ that embeds $\mathbf{x}$ to a common metric space such that $\mathbf{z} = f_\theta(\mathbf{x})$. We then explicitly model the class-wise distribution $p(\mathbf{z}|y = c, \mathcal{S})$ of the embedding $\mathbf{z}$ instead of the raw input $\mathbf{x}$. Under the assumption of a regular exponential family distribution for $p_\theta(\mathbf{z}|y = c, \mathcal{S})$ and a Bregman divergence d such as Euclidean or Mahalanobis distance, we have $p_\theta(\mathbf{z}|y = c, \mathcal{S}) \propto \exp(-d(\mathbf{z}, \boldsymbol{\mu}_c))$ (Snell et al., 2017), where $\boldsymbol{\mu}_c = \frac{1}{|\mathcal{S}_c|} \sum_{\tilde{\mathbf{x}} \in \mathcal{S}_c} f_\theta(\tilde{\mathbf{x}})$ is the class-wise embedding mean computed from $\mathcal{S}_c$, the set of examples from class c. In ProtoNets, d is squred Euclidean distance, resulting in the following likelihood of the query embedding $\mathbf{z} = f_\theta(\mathbf{x})$ in the form of softmax function.

$$p_\theta(y = c|\mathbf{z}, \mathcal{S}) = \frac{\exp(-\|\mathbf{z} - \boldsymbol{\mu}_c\|^2)}{\sum_{c'=1}^{C} \exp(-\|\mathbf{z} - \boldsymbol{\mu}_{c'}\|^2)}. \tag{2}$$

1. Limitations of fixed or empirical covariance. Unfortunately, Eq. (2) cannot capture a nontrivial class-conditional distribution structure, as Euclidean distance in Eq. (2) is equivalent to Mahalanobis distance with fixed covariance $\mathbf{I}$ for all classes, such that $p_\theta(\mathbf{z}|y = c, \mathcal{S}) = \mathcal{N}(\mathbf{z}; \boldsymbol{\mu}_c, \mathbf{I})$. For this reason, SNGP (Liu et al., 2020b) and DDU (Mukhoti et al., 2021) calculate empirical covariances from all available training data after training. However, such empirical covariance estimations are limited especially when the dataset size is small. If we consider the few-shot learning scenario where we have only a few training examples for each class, empirical covariances will provide unreliable estimates of the true class covariance. Unreliable covariance leads to poor estimation of Mahalanobis distances and therefore unreliable OOD detection and uncertainty estimation.

2. Shift invariant property of softmax and OOD calibration. Another critical limitation of Eq. (2) is that it produces overconfident predictions in areas distant from the class prototypes. The problem arises from the shift invariance property of the softmax function $\sigma(\omega) = e^\omega / \sum_{\omega'} e^{\omega'}$ with ω denoting the logits, such

Figure 3: $\|\boldsymbol{\mu}_2 - \boldsymbol{\mu}_1\|$ remains the same while $\mathbf{z}$ travels along the line, making a prediction with unnecessarily low entropy.

that $\sigma(\omega + s) = e^{\omega+s} / \sum_{\omega'} e^{\omega'+s} = e^\omega / \sum_{\omega'} e^{\omega'} = \sigma(\omega)$ for any shift s. More specifically, suppose we have two classes $c = 1, 2$, and $\mathbf{z}$ moves along the line extrapolating the prototypes $\boldsymbol{\mu}_1$ and $\boldsymbol{\mu}_2$ such that $\mathbf{z} = \boldsymbol{\mu}_1 + c(\boldsymbol{\mu}_2 - \boldsymbol{\mu}_1)$ for $c \leq 0$ or $c \geq 1$. Then, we can easily derive the following equality based on the shift invariant property of the softmax function:

$$p_\theta(y = 1|\mathbf{z}, \mathcal{S}) = \frac{1}{1 + \exp(\pm\|\boldsymbol{\mu}_2 - \boldsymbol{\mu}_1\|)} \tag{3}$$

where $\pm$ corresponds to the sign of c. Note that the expression is invariant to the value of c except for its sign. Therefore, even if $\mathbf{z}$ is OOD, residing somewhere distant from the prototypes $\boldsymbol{\mu}_1$ and $\boldsymbol{\mu}_2$ with extreme values of c, we still have equally confident predictions. See Figure 3 for illustration.

3.2 Meta-learning of the Class-wise Covariance

In order to remedy the limitations of empirical covariance, and capture a nontrivial structure of the class-conditional distribution even with a small support set, we propose to meta-learn the class-wise covariances over $p(\tau)$. Specifically, we meta-learn a set encoder g_ϕ that takes a class set $\mathcal{S}_c$ as input and outputs a covariance matrix corresponding to the density $p(\mathbf{z}|y = c, \mathcal{S})$, for each class $c = 1, \ldots, C$. We expect g_ϕ to encode shared meta-knowledge gained through episodic training over tasks from $p(\tau)$, which, as we will demonstrate in section 4, fills a key shortcoming of applying existing methods such as DDU (Mukhoti et al., 2021) and SNGP (Liu et al., 2020a). We denote the set-encoder g_ϕ for each class c as

$$\Lambda_c, \Phi_c = g_\phi(\mathcal{Z}_c), \qquad \mathcal{Z}_c = \{\tilde{\mathbf{z}} - \boldsymbol{\mu}_c | \tilde{\mathbf{z}} = f_\theta(\tilde{\mathbf{x}}) \text{ and } \tilde{\mathbf{x}} \in \mathcal{S}_c\}. \tag{4}$$

Algorithm 1 Proto Mahalanobis – Training

1: **Input:** Task distribution $p(\tau)$, initial θ and ϕ
2: **Output:** Meta-learned θ and ϕ
3: **while** not converged **do**
4:     Sample a task $\tau = (\mathcal{S}, \mathcal{Q})$
5:     **for** $c = 1$ **to** C **do**
6:         $\boldsymbol{\mu}_c \leftarrow \frac{1}{|\mathcal{S}_c|} \sum_{\tilde{\mathbf{x}} \in \mathcal{S}_c} f_\theta(\tilde{\mathbf{x}})$
7:         $\Lambda_c, \Phi_c \leftarrow g_\phi(\mathcal{Z}_c)$ ▷ Eq. 4
8:         $\boldsymbol{\Sigma}_c \leftarrow \Lambda_c + \Phi_c \Phi_c^\top$ ▷ Eq. 5
9:         Compute $\boldsymbol{\Sigma}_c^{-1}$ and $|\boldsymbol{\Sigma}_c|$ ▷ Eq. 8,9
10:    **end for**
11:    $\mathcal{L}_\tau \leftarrow \frac{1}{|\mathcal{Q}|} \sum_{(\mathbf{x},y) \in \mathcal{Q}} - \log p_{\theta,\phi}(y | \mathbb{E}[\boldsymbol{\omega}])$ ▷ Eq. 11
12:    $(\theta, \phi) \leftarrow (\theta, \phi) - \alpha \nabla_{\theta,\phi} \mathcal{L}_\tau$
13: **end while**

Algorithm 2 Proto Mahalanobis – Inference

1: **Input:** Task τ, meta-learned θ and ϕ
2: **for** $c = 1$ **to** C **do**
3:     $\boldsymbol{\mu}_c \leftarrow \frac{1}{|\mathcal{S}_c|} \sum_{\tilde{\mathbf{x}} \in \mathcal{S}_c} f_\theta(\tilde{\mathbf{x}})$
4:     $\Lambda_c, \Phi_c \leftarrow g_\phi(\mathcal{Z}_c)$ ▷ Eq. 4
5:     $\boldsymbol{\Sigma}_c \leftarrow \Lambda_c + \Phi_c \Phi_c^\top$ ▷ Eq. 5
6:     Compute $\boldsymbol{\Sigma}_c^{-1}$ and $|\boldsymbol{\Sigma}_c|$ ▷ Eq. 8,9
7: **end for**
8: Eval. $p_{\theta,\phi}(y | \mathbf{z}, \mathcal{S})$ for $(y, \mathbf{x}) \in \mathcal{Q}$ ▷ Eq. 11

---

where $\Lambda_c \in \mathbb{R}^{d \times d}$ is a diagonal matrix and $\Phi_c \in \mathbb{R}^{d \times r}$ is a rank-r matrix. Now, instead of the identity covariance matrix or empirical covariance estimation, we have the meta-learnable covariance matrix consisting of the strictly positive diagonal and low-rank component for each class $c = 1, \ldots, C$.

$$\boldsymbol{\Sigma}_c = \Lambda_c + \Phi_c \Phi_c^\top. \tag{5}$$

It is easy to see that $\boldsymbol{\Sigma}_c$ is a valid positive semi-definite covariance matrix for non-negative Λ_c. Note that the covariance becomes diagonal when $r = 0$. A natural choice for g_ϕ is the Set Transformer (Lee et al., 2019) which can model pairwise interactions between elements of the input set, an implicit requirement for covariance matrices.

Now, we let $p_{\theta,\phi}(\mathbf{z} | y = c, \mathcal{S}) = \mathcal{N}(\mathbf{z}; \boldsymbol{\mu}_c, \boldsymbol{\Sigma}_c)$. From Bayes' rule (see Appendix A.1), we compute the predictive distribution in the form of softmax function as follows,

$$p_{\theta,\phi}(y = c | \mathbf{z}, \mathcal{S}) = \frac{p_{\theta,\phi}(\mathbf{z} | y = c, \mathcal{S})}{\sum_{c'=1}^C p_{\theta,\phi}(\mathbf{z} | y = c', \mathcal{S})} \tag{6}$$

$$= \frac{\exp(-\frac{1}{2}(\mathbf{z} - \boldsymbol{\mu}_c)^\top \boldsymbol{\Sigma}_c^{-1} (\mathbf{z} - \boldsymbol{\mu}_c) - \frac{1}{2} \log |\boldsymbol{\Sigma}_c|)}{\sum_{c'=1}^C \exp(-\frac{1}{2}(\mathbf{z} - \boldsymbol{\mu}_{c'})^\top \boldsymbol{\Sigma}_{c'}^{-1} (\mathbf{z} - \boldsymbol{\mu}_{c'}) - \frac{1}{2} \log |\boldsymbol{\Sigma}_{c'}|)} \tag{7}$$

Covariance inversion and log-determinant. Note that the logit of the softmax function in Eq. (7) involves the inverse covariance $\boldsymbol{\Sigma}_c^{-1}$ and the log-determinant $\log |\boldsymbol{\Sigma}_c|$. In contrast to both DDU and SNGP which propose to calculate and invert an empircal feature covariance after training, the meta-learning setting requires that this inference procedure be performed on every iteration during meta-training, which may be cumbersome if a full $\mathcal{O}(d^3)$ inversion is to be performed. Therefore, we utilize the matrix determinant lemma (Ding & Zhou, 2007) and the Sherman-Morrison formula in the following recursive forms for both the inverse and the log determinant in Equation 7.

$$(\boldsymbol{\Sigma}_i + \Phi_{i+1} \Phi_{i+1}^\top)_{i+1}^{-1} = \boldsymbol{\Sigma}_i^{-1} - \frac{\boldsymbol{\Sigma}_i^{-1} \Phi_{i+1} \Phi_{i+1}^\top \boldsymbol{\Sigma}_i^{-1}}{1 + \Phi_{i+1}^\top \boldsymbol{\Sigma}_i^{-1} \Phi_{i+1}} \tag{8}$$

$$\det(\boldsymbol{\Sigma}_i + \Phi_{i+1} \Phi_{i+1}^\top)_{i+1} = (1 + \Phi_{i+1}^\top \boldsymbol{\Sigma}_i^{-1} \Phi_{i+1}) \det(\boldsymbol{\Sigma}_i) \tag{9}$$

3.3 OUT-OF-DISTRIBUTION CALIBRATION WITH SCALED ENERGY

Next, in order to tackle the overconfidence problem caused softmax shift invariance, we propose incorporating a positive constrained function of energy $h(E) = \max(0, -\frac{1}{T} \log \sum_c \exp(-E_c))$, with temperature T, into the predictive distribution. Energy has been used for OOD detection (Liu et al., 2020b) and density estimation (Grathwohl et al., 2019), and the success of energy in these tasks implies that it can be used to calibrate the predictive distribution (example in Figure 1h). Results in Grathwohl et al. (2019) show improvements in calibration, but their training procedure requires a full input space generative model during training, adding unwanted complexity if the end goal does not require input space generation. Our method makes use of our logit values $\boldsymbol{\omega} = (\omega_1, \ldots, \omega_C)$ to parameterize the mean of a logit-normal distribution with the variance given by $h(E)$. In this way,

Table 1: OOD ECE on models trained on variations of the Omniglot and MiniImageNet datasets. The OOD distribution for these models are random classes from the test set which are not present in the support set.

	Omniglot OOD Class ECE ↓				MiniImageNet OOD Class ECE ↓	
Model	5-way 5-shot	5-way 1-shot	20-way 5-shot	20-way 1-shot	5-way 5-shot	5-way 1-shot
MAML	64.93±0.58	62.09±0.57	58.99±5.94	56.82±1.22	30.91±1.07	41.46±0.51
Reptile	48.79±0.19	48.98±1.06	47.30±0.25	**38.67±0.52**	32.79±1.35	36.97±0.41
Protonet	68.50±0.69	67.64±0.63	77.58±0.37	72.07±0.63	33.23±1.20	47.06±1.30
Protonet-SN	69.43±0.57	67.67±0.70	77.84±0.44	72.36±0.58	33.24±2.14	46.76±1.40
ProtoDDU	69.16±0.63	66.61±1.15	78.14±0.19	71.39±0.74	35.31±2.09	46.82±1.28
ProtoSNGP	65.39±0.64	60.22±0.61	76.90±0.72	68.16±0.40	35.37±1.81	45.67±1.13
Ours (Diag)	33.95±0.98	40.52±0.68	**40.00±0.23**	50.39±1.84	**17.34±1.83**	**32.27±3.18**
Ours (Rank 1)	**33.19±0.94**	**39.62±2.02**	40.04±0.40	49.28±1.21	18.86±1.64	34.47±0.64

the logit-normal distribution variance rises in conjunction with the energy, making predictions more uniform over the simplex for higher energies.

$$p_{\theta,\phi}(\omega_c|\mathbf{z},\mathcal{S}) = \mathcal{N}(\omega_c; \tilde{\mu}_c, \tilde{\sigma}^2), \quad \text{where} \quad \tilde{\mu}_c = -\frac{1}{2}(\mathbf{z}-\boldsymbol{\mu}_c)^\top \boldsymbol{\Sigma}_c^{-1}(\mathbf{z}-\boldsymbol{\mu}_c) - \frac{1}{2}\log|\boldsymbol{\Sigma}_c|,$$

$$\tilde{\sigma}^2 = -\frac{1}{T}\log\sum_{c'}\exp\left(-\frac{1}{2}(\mathbf{z}-\boldsymbol{\mu}_{c'})^\top \boldsymbol{\Sigma}_{c'}^{-1}(\mathbf{z}-\boldsymbol{\mu}_{c'})\right)$$

(10)

Intuitively, $f(E)$ is dominated by $\min(E)$ thereby acting as a soft approximation to the minimum energy, which only becomes large when the energy is high for all classes represented in the logits. Then, the predictive distribution becomes

$$p_{\theta,\phi}(y=c|\mathbf{z},\mathcal{S}) = \int p(y=c|\boldsymbol{\omega})p_{\theta,\phi}(\boldsymbol{\omega}|\mathbf{z},\mathcal{S})d\boldsymbol{\omega} \tag{11}$$

$$\approx \frac{1}{M}\sum_{m=1}^{M}\frac{\exp(\omega_c^{(m)})}{\sum_{c'}\exp(\omega_{c'}^{(m)})}, \quad \omega_c^{(m)} \sim p(\omega_c|\mathbf{z},\mathcal{S}). \tag{12}$$

Meta-training   At training time, we do not sample $\boldsymbol{\omega}$ and use the simple deterministic approximation $p_{\theta,\phi}(y|\mathbf{z},\mathcal{S}) \approx p_{\theta,\phi}(y|\mathbb{E}[\boldsymbol{\omega}])$. Therefore, the loss for each task becomes $\mathcal{L}_\tau(\theta,\phi) = \frac{1}{|\mathcal{Q}|}\sum_{(\mathbf{x},y)\in\mathcal{Q}} -\log p_{\theta,\phi}(y|\mathbb{E}[\boldsymbol{\omega}])$. We then optimize θ and ϕ by minimizing the expected loss $\mathbb{E}_{p(\tau)}[\mathcal{L}_\tau(\theta,\phi)]$ over the task distribution $p(\tau)$ via episodic training.

Energy scaling.   Utilizing equation 11 directly for inference may lead to underconfidence when using unscaled $\tilde{\sigma}$ from 10. Therefore, in order properly scale the variance to maintain ID performance, we tune the temperature parameter T after training. Specifically, we start with $T = 1$ and iteratively increase T by 1 until $\mathbb{E}_{\mathcal{D}}[-\log p(y|\mathbf{z},\mathcal{S})] \leq \mathbb{E}_{\mathcal{D}}[-\log p(y|\mathbb{E}[\boldsymbol{\omega}])]$, where $-\log p(y|\mathbb{E}[\boldsymbol{\omega}])$ is the NLL evaluated by using only the deterministic logits $\mathbb{E}[\boldsymbol{\omega}]$.

3.4   SPECTRAL NORMALIZATION.

Lastly, we enforce a bi-Lipschitz regularization f_θ by employing both residual connections and spectral normalization on the weights Liu et al. (2020b), such that Equation 13 is satisfied. Using features $\mathbf{Z}$, the calculation of covariance $(\mathbf{Z}-\boldsymbol{\mu}_c)(\mathbf{Z}-\boldsymbol{\mu}_c)^\top$ and subsequently, the mean and variance of 10 both implicitly utilize distance, therefore we require bi-Lipschitz regularization of f_θ. We choose spectral normalization via the power iteration method (also known as the Von Mises Iteration (Mises & Pollaczek-Geiringer, 1929)) due to its low memory and computation overhead as compared to second order methods such as gradient penalties (Arjovsky et al., 2017). Specifically, for features at hidden layer $h(\cdot)$, at depth l, and for some constants α_1, α_2, for all $\mathbf{z}_i$ and $\mathbf{z}_j$, we enforce:

$$\alpha_1||\mathbf{z}_i^{(l)} - \mathbf{z}_j^{(l)}|| \leq ||h(\mathbf{z}_i^{(l-1)}) - h(\mathbf{z}_j^{(l-1)})|| \leq \alpha_2||\mathbf{z}_i^{(l)} - \mathbf{z}_j^{(l)}||. \tag{13}$$

4   EXPERIMENTS

The goal of our experimental evaluation is to answer the following questions. 1) What is the benefit of each component of our proposed model. 2) Does g_ϕ produce more expressive covariances than

Figure 4: ECE results for all models on different variants of the Omniglot dataset. ProtoMahalanobis models show comparable in distribution ECE while significantly improving ECE over the baselines on corrupted instances from the dataset.

empirical features? 3) How does the ID/OOD calibration and accuracy compare with other popular baseline models.

Datasets. For few shot learning, we evaluate our model on both the Omniglot (Lake et al., 2015) and MiniImageNet (Vinyals et al., 2017) datasets. We utilize corrupted versions (Omniglot-C and MiniImageNet-C) which consists of 17 corruptions at 5 different intensities (Hendrycks & Dietterich, 2019). We follow the precedent set by Snell et al. (2017) and test Omniglot for 1000 random episodes and MiniImageNet for 600 episodes. For corruption experiments, the support set is uncorrupted, and corruption levels 0-5 are used as the query set (0 being the uncorrupted query set). We also experiment with multiple toy datasets which include half-moons, and concentric circles for binary classification and random 2D multivariate Gaussian distributions for multiclass classification (Figure 1). On the toy datasets, we create task distributions by sampling random tasks with biased support sets, applying random class shuffling and varying levels of noise added to each task. Randomly biasing each task ensures that no single task contains information from the whole distribution and therefore, the true distribution must be meta-learned through the episodic training over many such tasks. For a detailed explanation of the exact toy dataset task creation procedure, see the appendix section A.2.

Baselines. We compare our model against Protonets (Snell et al., 2017), A spectral normalized version of Protonets (Protonet-SN), MAML (Finn et al., 2017), Reptile (Nichol et al., 2018), and

Figure 5: ECE for different variants of the MiniImageNet dataset. ProtoMahalanobis models show improved ECE on corrupted data instances while maintaining comparable performance on in-distribution data.

straightforward few-shot/protonet adaptations of Spectral Normalized Neural Gaussian Processes (ProtoSNGP) (Liu et al., 2020a) and Deep Deterministic Uncertainty (ProtoDDU) (Mukhoti et al., 2021). These models represent a range of both metric based, gradient based, and covariance based meta learning algorithms. All baseline models are temperature scaled after training, with the temperature parameter optimized via LBFGS for 50 iterations with a learning rate of 0.001. This follows the temperature scaling implementation from Guo et al. (2017).

Calibration Error. We provide results for ECE on various types of OOD data in Figures 4 and 5 as well as Table 1. We report extra results for Accuracy and NLL in Appendix A.7. In meta learning, there is generally a high level of relatedness between tasks, but random classes from different tasks which are not related to the current support set $\mathcal{S}$ should still be treated as OOD. In Table 1 we provide results where the query set $\mathcal{Q}$ consists of random classes which are not in $\mathcal{S}$. ProtoMahalanobis models perform the best in every case except for Omniglot 20-way/1-shot, where Reptile showed the lowest ECE. The reason for this can be seen in Figure 4, where Reptile shows poor ID performance relative to all other models. Under-confidence on ID data can lead to better confidence scores on OOD data, even though the model is poorly calibrated. Likewise we also evaluate our models on Omniglot-C and MiniImageNet-C in Figure 4 and 5. As the corruption intensity increases, ProtoMahalanobis models exhibit lower ECE in relation to baseline models while maintaining competitive ID performance. There are a few instances where Reptile appears to show strong OOD performance (Omniglot 20/5, 20/1 in Figure 4) but in each of these cases Reptile shows far worse performance on ID data, again indicating that Reptile is underconfident and miscalibrated for ID data.

A compelling hypothesis for this behavior from Reptile is that it is related to the transductive BatchNorm used by both MAML and Reptile baselines. The query sets used in each corruption are larger than seen during training which led to lower MAML and Reptile accuracies in Figure 19 and 21, may have conversely had an opposite effect on calibration error in Figure 4 and 5. We are not aware of any work which analyzes the effects of transductive BatchNorm on ECE, which may be an interesting line of future work.

Eigenvalue Distribution. In Figure 6, we evaluate the effectiveness of meta learning the low rank covariance factors with g_ϕ by analyzing the eigenvalue distribution of both empirical covariance (from DDU/SNGP baselines), and the covariance from g_ϕ (eq. (5)). The empirically calculated covariance exhibits low diversity in eigenvalues, which implies that the learned Gaussian distribution is near spherical for every class. ProtoMahalanobis models, on the other hand, exhibit a diverse range of eigenvalues, leading to non-trivial ellipsoid distributions. We also note that in addition to

(a) Ours $\mathbf{\Sigma}^{-1}$ Eigvals   (b) ProtoDDU $\mathbf{\Sigma}^{-1}$ Eigenvals   (c) ProtoSNGP $\mathbf{\Sigma}^{-1}$ Eigenvals

Figure 6: **Left:** precision matrix eigenvalue distribution for ProtoMahalanobis. **Right:** precision matrix eigenvalue distribution for DDU. The input data comes from the test set of Omniglot 20-way/5-shot experiments. ProtoMahalanobis models learn a precision matrix with a more diverse distribution of eigenvalues.

more diverse range of eigenvalues, the differences between the distributions of each class in $\mathcal{S}$ are also amplified in ProtoMahalanobis models, indicating a class specific variation between learned covariance factors. Extra figures are reported in the Appendix A.6, where it can be seen that the eigenvalue distribution becomes less diverse for ProtoMahalanobis models on the one-shot setting.

Architectures. For both Omniglot and MiniImageNet experiments, we utilize a 4 layer convolutional neural network with 64 filters, followed by BatchNorm and ReLU nonlinearities. Each of the four layers is followed by a max-pooling layer which results in a vector embedding of size 64 for Omniglot and 1600 for MiniImageNet. Exact architectures can be found in Appendix A.8. Protonet-like models use BatchNorm with statistics tracked over the training set, and MAML-like baselines use transductive BatchNorm as the original works do. As spectral normalized models require residual connections to maintain the lower Lipschitz bound in equation 13, we add residual connections to the CNN architecture in all Protonet based models.

4.1 IMPLEMENTATION DETAILS

ProtoSNGP & ProtoDDU Both ProtoSNGP and ProtoDDU baselines are adapted to meta learning by using the original implementation plus the addition of one meta parameter which represents the first diagonal term in Equation 8. This both acts as a meta parameter and a necessary first step in applying the recursive formula for inversion to make a prediction on each query set seen during during training.

Covariance Encoder g_ϕ. We utilize the Set Transformer (Lee et al., 2019), as the self-attention performed by the transformer is an expressive means to encode pairwise information between inputs. We initialize the seeds in the pooling layers (PMA), with samples from $\mathcal{N}(0, 1)$. We do not use any spectral normalization in g_ϕ, as it should be sufficient to only require that the input to the encoder is composed of geometry preserving features. Crucially, we remove the residual connection $Q + \sigma(QK^\top)V$ as we found that this led to the pooling layer ignoring the inputs and outputting an identical covariance for each class in each task. In the one-shot case, we skip the centering about the centroid in Equation 4 because it would send all class centroids to the origin.

5 CONCLUSION

It is widely known that DNNs are miscalibrated especially for OOD data. We have shown that existing covariance based methods fail to calibrate well when given a limited amounts of data for class-specific covariance construction. In this work, we have proposed a novel method which meta-learns a diagonal or diagonal plus low rank covariance matrix which can be used for downstream tasks such as uncertainty calibration. Additionally, we have proposed an inference procedure and energy tuning scheme which can overcome miscalibration due to the shift invariance property of softmax. We further enforce bi-Lipschitz regularization of neural network layers to preserve relative distances between data instances in the feature spaces. We validated our methods on a synthetic data and two benchmark few-shot learning datasets, and showed that the final predictive distribution of our method is well calibrated under a distributional dataset shift when compared with relevant baselines.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan, 2017.

Jiu Ding and Aihui Zhou. Eigenvalues of rank-one updated matrices with some applications. *Applied Mathematics Letters*, 20(12):1223–1226, 2007.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pp. 1126–1135. PMLR, 2017.

Will Grathwohl, Kuan-Chieh Wang, Jörn-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. *arXiv preprint arXiv:1912.03263*, 2019.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks, 2017.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem, 2019.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Haiwen Huang, Zhihan Li, Lulu Wang, Sishuo Chen, Bin Dong, and Xinyu Zhou. Feature space singularity for out-of-distribution detection. *arXiv preprint arXiv:2011.14654*, 2020.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International Conference on Machine Learning*, pp. 3744–3753. PMLR, 2019.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *arXiv preprint arXiv:1807.03888*, 2018.

Jeremiah Zhe Liu, Zi Lin, Shreyas Padhy, Dustin Tran, Tania Bedrax-Weiss, and Balaji Lakshminarayanan. Simple and principled uncertainty estimation with deterministic deep learning via distance awareness. *arXiv preprint arXiv:2006.10108*, 2020a.

Weitang Liu, Xiaoyun Wang, John D Owens, and Yixuan Li. Energy-based out-of-distribution detection. *arXiv preprint arXiv:2010.03759*, 2020b.

RV Mises and Hilda Pollaczek-Geiringer. Praktische verfahren der gleichungsauflösung. *ZAMM-Journal of Applied Mathematics and Mechanics/Zeitschrift für Angewandte Mathematik und Mechanik*, 9(1):58–77, 1929.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

Jishnu Mukhoti, Andreas Kirsch, Joost van Amersfoort, Philip H. S. Torr, and Yarin Gal. Deterministic neural networks with appropriate inductive biases capture epistemic and aleatoric uncertainty, 2021.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms, 2018.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua V Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *arXiv preprint arXiv:1906.02530*, 2019.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *ICLR*, 2017.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook*. PhD thesis, Technische Universität München, 1987.

Jake Snell, Kevin Swersky, and Richard S Zemel. Prototypical networks for few-shot learning. *arXiv preprint arXiv:1703.05175*, 2017.

Sebastian Thrun and Lorien Pratt (eds.). *Learning to Learn.* Kluwer Academic Publishers, Norwell, MA, USA, 1998. ISBN 0-7923-8047-9.

Joost Van Amersfoort, Lewis Smith, Yee Whye Teh, and Yarin Gal. Uncertainty estimation using a single deep deterministic neural network. In *International Conference on Machine Learning*, pp. 9690–9700. PMLR, 2020.

Joost van Amersfoort, Lewis Smith, Andrew Jesson, Oscar Key, and Yarin Gal. Improving deterministic uncertainty estimation in deep learning for classification and regression, 2021.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching Networks for One Shot Learning. In *NIPS*, 2016.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning, 2017.

A APPENDIX

A.1 LOSS DERIVATION (EQUATION 7)

The full derivation of Equation 7 can be achieved by first applying Bayes' Rule, assuming a simple uniform prior over the class labels, $p(y_i|x_i)$ can be proportionately expressed as,

$$p(y_i|\mathbf{x}_i) = \frac{p(\mathbf{x}_i|y_k)p(y_k)}{p(\mathbf{x}_i)} \propto p(\mathbf{x}_i|y_k)p(y_k) \tag{14}$$

In which case the objective of the model becomes raising the class conditional $p(\mathbf{x}_i|y_i)$, while simultaneously lowering $p(\mathbf{x}_i|y_j) \; \forall \; j \neq i$. This is in fact equivalent to a softmax + cross entropy loss over the class conditional densities which are output from our model. In the softmax case, maximizing $p(y_i|\mathbf{x}_i)$ for a given class can be done by,

$$p(y_i|\mathbf{x}_i) = \frac{e^{z_i}}{\sum_{z'} e^{z'}} \tag{15}$$

Which them implies that the loss to be minimized is the following, commonly known as the negative log likelihood of the data, or the empirical cross entropy between the true data distribution and the predictive distribution of the model.

$$
\begin{aligned}
\mathcal{L}_{NLL} &= \mathbb{E}_{\mathcal{D}}[-\log p(y|\mathbf{x})] \\
&= \frac{1}{N}\sum_{i=0}^{N} -\log p(y_i|\mathbf{x}_i) \\
&= \frac{1}{N}\sum_{i=0}^{N}\left(-z_j + \log\sum_{z'_j}\exp(z'_j)\right)_i \\
\mathcal{L}_{CE} &= -\int_{\mathbf{x}} p_{\mathbf{x}}(y|\mathbf{x})\log p_\theta(y|\mathbf{x})d\mathbf{x} \\
&\approx \frac{1}{N}\sum_{i=0}^{N} -\log p_\theta(y|\mathbf{x}) \\
&= \frac{1}{N}\sum_{i=0}^{N}\left(-z_j + \log\sum_{z'_j}\exp(z'_j)\right)_i
\end{aligned}
\tag{16}
$$

In our case, assuming a uniform prior over the classes, we can analogously formulate the loss as,

$$
\begin{aligned}
\mathcal{L} &= \mathbb{E}_{\mathcal{D}}[-\log p(\mathbf{x}|y)p(y)] \\
&= \frac{1}{N}\sum_{i=0}^{N}\left(-\log p(\mathbf{x}_i|y_k)p(y_k) + \log\sum_{\mathbf{x}'}p(\mathbf{x}'_i|y_k)p(y_k)\right) \\
&= \frac{1}{N}\sum_{i=0}^{N}\left(-\log p(\mathbf{x}_i|y_k) - \log p(y_k) + \log p(y_k) + \log\sum_{\mathbf{x}'}p(\mathbf{x}'_i|y_k)\right) \\
&= \frac{1}{N}\sum_{i=0}^{N}\left(-\log p(\mathbf{x}_i|y_k) + \log\sum_{\mathbf{x}'}p(\mathbf{x}'_i|y_k)\right)
\end{aligned}
\tag{17}
$$

A.2 TOY DATASETS

To add bias to each samples task from our 2D toy datasets, we first randomly choose an axis (X or Y) for each class and then slice the datapoints in half randomly. We then sample the support set from the

chosen biased subset and leave the rest of the remaining points for the query set. Each sampled task calculates the mean and variance from the support set, which are then used to normalize all instances in $\mathcal{S}$ and $\mathcal{Q}$.

Dataset	N-Way	K-Shot
Circles	2	5
Moons	2	5
Gaussians	10	10

A.2.1 META MOONS

For the Meta Moons dataset, we randomly invert the classes to make sure that the class indices appear in a random order for each task. We add a random amount of Gaussian noise to each moon with a uniform standard deviation in the range of $(0, 0.25]$.

Figure 7: Random task samples from the Meta Moons dataset.

A.2.2 META CIRCLES

For the Meta Circles dataset, we randomly invert the order of the classes so that the inner circle and the outer circle are not guaranteed to appear in the same order on every task. We inject a random amount of Gaussian noise into the data, with a uniformly random standard deviation in the range of $(0, 0.25]$. We also randomly choose the scale factor between the size of the inner circle and the outer circle, which is uniformly random in the range of $(0, 0.8]$

Figure 8: Random task samples from the Meta Circles dataset.

A.2.3 META GAUSSIANS

The task construction of the Meta Gaussians dataset requires that we construct random positive semidefinite covariance matrices for each class. We first uniformly sample N 2×2 matrices in the range $U(-1, 1)$ and perform a QR decomposition to extract orthonormal matrices Q. We then sample a random diagonal $D \sim U(0, 1)$, and construct the final matrix as $QDQ^\top$ which is positive

Table 2: Accuracy, ECE, NLL, and OOD AUPR for different n-way k-shot classification problems on the Omniglot-C dataset which contains 17 different corruptions at 5 different intensity levels.

	Accuracy ↑				NLL ↓			
Model	5-way 5-shot	5-way 1-shot	20-way 5-shot	20-way 1-shot	5-way 5-shot	5-way 1-shot	20-way 5-shot	20-way 1-shot
MAML	66.80±15.86	64.97±15.68	52.34±20.65	48.22±18.98	1.370±0.832	1.458±0.866	2.297±1.309	2.259±1.058
Reptile	70.09±16.45	70.67±15.27	51.52±21.18	46.00±18.72	2.555±1.934	1.691±1.167	2.881±1.836	2.754±1.385
Protonet	60.91±19.13	58.15±19.68	46.29±25.21	43.11±25.55	6.526±3.800	6.539±4.029	10.706±5.689	9.119±4.890
Protonet-SN	60.08±19.47	57.64±19.89	46.19±25.22	43.47±25.44	7.189±4.261	6.541±3.960	11.200±6.168	8.446±4.590
ProtoDDU	60.31±19.19	58.03±19.57	45.75±25.33	43.90±25.22	10.945±7.143	10.428±7.186	18.014±9.740	17.039±9.935
ProtoSNGP	59.18±19.66	57.03±19.91	46.49±25.12	44.37±24.85	2.534±1.302	2.015±0.967	6.409±3.196	4.151±1.982
Ours (Diag)	60.77±19.12	57.71±19.88	45.98±25.31	43.05±25.59	1.010±0.476	1.205±0.547	2.466±1.141	3.854±1.775
Ours (Rank 1)	59.88±19.55	58.15±19.59	45.47±25.57	43.12±25.57	1.020±0.481	1.312±0.595	2.541±1.212	3.564±1.624
Ours (Rank 2)	59.68±19.61	56.61±20.21	45.53±25.52	43.28±25.45	1.045±0.495	1.314±0.594	2.561±1.194	3.787±1.760
Ours (Rank 4)	60.28±19.51	59.14±19.32	45.87±25.44	42.38±25.90	1.068±0.510	1.263±0.580	2.528±1.168	4.019±1.877
Ours (Rank 8)	59.69±19.69	58.21±19.63	45.93±25.39	43.53±25.42	1.055±0.501	1.329±0.580	2.486±1.156	3.474±1.607
	ECE ↓				OOD AUPR			
MAML	14.77±11.03	16.14±11.29	13.83±10.00	11.37±6.99	0.727±0.109	0.741±0.117	0.757±0.136	0.775±0.140
Reptile	23.05±14.07	19.49±11.80	19.45±13.53	19.36±12.39	0.633±0.071	0.712±0.101	0.469±0.047	0.534±0.078
Protonet	34.08±17.02	35.69±17.62	43.57±20.89	43.47±20.69	0.867±0.169	0.853±0.163	0.876±0.172	0.863±0.166
Protonet-SN	35.12±17.46	36.27±17.85	43.75±20.89	42.06±20.10	0.869±0.169	0.857±0.164	0.875±0.171	0.862±0.166
ProtoDDU	27.84±14.19	33.79±16.61	37.62±18.16	40.83±19.55	0.675±0.083	0.552±0.044	0.647±0.074	0.579±0.062
ProtoSNGP	29.26±14.53	28.70±14.07	40.42±19.46	36.43±17.36	0.875±0.172	0.855±0.163	0.878±0.173	0.858±0.164
Ours (Diag)	5.87±2.58	11.15±4.93	9.81±4.36	21.99±9.65	0.869±0.169	0.855±0.164	0.876±0.172	0.863±0.166
Ours (Rank 1)	6.10±2.87	11.81±4.96	11.30±5.48	20.26±8.68	0.869±0.169	0.850±0.162	0.874±0.171	0.863±0.166
Ours (Rank 2)	6.62±3.09	12.38±5.11	11.49±5.12	21.42±9.45	0.867±0.169	0.853±0.163	0.874±0.171	0.862±0.166
Ours (Rank 4)	7.10±3.40	11.17±4.95	10.87±4.75	22.90±10.14	0.868±0.169	0.851±0.162	0.874±0.171	0.864±0.167
Ours (Rank 8)	7.05±3.42	12.89±5.60	10.61±4.84	20.56±9.22	0.868±0.169	0.851±0.162	0.876±0.172	0.863±0.166

semi-definite. This leads to the distribution of each class being an elliptical multivariate Gaussian distribution.

Figure 9: Random task samples from the Meta Gaussians dataset.

A.3 EXTRA RESULTS

We provide extra results on the MiniImageNet-C and Omniglot-C dataset here. Tables 2 and 3 contain results averaged over the whole corrupted dataset, including the natural test set and all 5 levels of corruption

A.4 EXTRA TOY RESULTS

In Figures 10, 11, 12, 13, 14, 15, and 16 we provide extra qualitative results on toy dataset covariances and entropy surfaces. In Tables 6, 7, and 8 we provide tabular results of all toy experiments, showcasing the differences between in-distribution data and random uniform OOD noise. While the best ID performanc is sometimes mixed between the

A.5 FURTHER IMPLEMENTATION DETAILS

SNGP In order to extend SNGP Liu et al. (2020a) to work in the few shot learning scenario under the prototypical network Snell et al. (2017) framework, we had to modify the original algorithm by replacing the last linear layer with the embedding layer and centroids used by prototypical networks.

Table 3: Accuracy, ECE, NLL, and AUPR for different n-way k-shot classification problems on the MiniImageNet-C dataset which contains 17 different corruptions at 5 different intensity levels.

	Accuracy ↑		NLL ↓	
Model	5-way 1-shot	5-way 5-shot	5-way 1-shot	5-way 5-shot
MAML	32.00±6.60	38.43±10.16	1.743±0.226	1.773±0.366
Reptile	31.52±6.20	37.26±9.69	1.709±0.115	1.640±0.229
Protonet	32.07±7.42	39.21±12.43	1.798±0.271	2.013±0.645
Protonet-SN	31.48±7.25	39.33±12.71	1.834±0.284	1.968±0.630
ProtoDDU	32.11±7.75	39.70±12.76	1.905±0.415	2.058±0.758
ProtoSNGP	31.58±7.41	39.17±12.47	1.733±0.227	1.876±0.537
Ours (Diag)	31.65±7.44	39.13±12.13	1.576±0.127	1.605±0.342
Ours (Rank 1)	31.42±7.32	39.42±12.51	1.594±0.142	1.651±0.390
Ours (Rank 2)	31.31±7.48	39.03±12.39	1.590±0.148	1.627±0.364
Ours (Rank 4)	30.93±7.15	39.72±12.26	1.610±0.159	1.657±0.395
Ours (Rank 8)	30.91±7.35	38.98±12.47	1.599±0.144	1.612±0.360
	ECE ↓		AUPR ↑	
MAML	20.16±7.23	24.49±8.20	0.558±0.088	0.620±0.098
Reptile	19.02±1.60	18.98±4.57	0.779±0.149	0.768±0.140
Protonet	20.09±8.35	26.12±12.75	0.642±0.095	0.586±0.071
Protonet-SN	20.96±8.39	25.66±12.81	0.634±0.086	0.579±0.068
ProtoDDU	22.02±9.55	25.39±12.85	0.504±0.039	0.597±0.053
ProtoSNGP	20.07±6.92	25.42±11.80	0.633±0.077	0.643±0.083
Ours (Diag)	7.52±3.56	14.09±6.24	0.639±0.091	0.582±0.065
Ours (Rank 1)	8.67±3.85	15.46±7.22	0.628±0.087	0.580±0.068
Ours (Rank 2)	9.06±4.09	14.82±6.24	0.635±0.087	0.586±0.065
Ours (Rank 4)	9.53±4.92	15.03±6.80	0.631±0.085	0.575±0.058
Ours (Rank 8)	8.75±4.19	14.42±6.56	0.640±0.091	0.581±0.070

Table 4: Accuracy, ECE, NLL, and AUPR for different n-way k-shot classification problems on the Omniglot dataset. All metrics are measured on the natural test set except AUPR/AUROC which is measured using random classes which are different from the classes in the support set.

	Accuracy ↑				NLL ↓			
Model	5-way 5-shot	5-way 1-shot	20-way 5-shot	20-way 1-shot	5-way 5-shot	5-way 1-shot	20-way 5-shot	20-way 1-shot
MAML	99.59±0.03	98.11±0.06	98.05±0.28	92.80±0.22	0.013±0.002	0.056±0.002	0.073±0.014	0.239±0.007
Reptile	98.82±0.08	98.00±0.11	96.69±0.02	92.14±0.39	0.042±0.002	0.064±0.003	0.130±0.001	0.302±0.013
Protonet	99.65±0.02	98.24±0.16	99.29±0.05	97.47±0.09	0.013±0.002	0.059±0.007	0.027±0.006	0.087±0.008
Protonet-SN	99.67±0.04	98.26±0.12	99.26±0.06	97.51±0.16	0.013±0.003	0.061±0.007	0.029±0.006	0.086±0.011
ProtoDDU	99.70±0.05	98.37±0.11	99.28±0.05	97.54±0.16	0.010±0.002	0.058±0.010	0.027±0.005	0.085±0.010
ProtoSNGP	99.65±0.07	98.23±0.08	99.23±0.06	97.41±0.13	0.012±0.001	0.054±0.004	0.029±0.006	0.085±0.006
Ours (Diag)	99.64±0.06	98.21±0.23	99.26±0.01	97.49±0.09	0.020±0.002	0.064±0.005	0.032±0.002	0.089±0.006
Ours (Rank 1)	99.63±0.06	98.21±0.12	99.29±0.03	97.61±0.14	0.020±0.002	0.067±0.005	0.031±0.002	0.086±0.007
Ours (Rank 2)	99.62±0.06	98.30±0.23	99.30±0.06	97.56±0.10	0.020±0.002	0.064±0.010	0.031±0.003	0.087±0.007
Ours (Rank 4)	99.66±0.04	98.42±0.17	99.28±0.07	97.56±0.16	0.019±0.002	0.060±0.005	0.032±0.003	0.088±0.007
Ours (Rank 8)	99.64±0.02	98.35±0.16	99.32±0.04	97.63±0.16	0.019±0.001	0.059±0.004	0.030±0.003	0.084±0.008
	ECE ↓				OOD AUPR ↑			
MAML	0.08±0.02	0.36±0.06	1.03±0.62	1.39±0.44	0.908±0.005	0.869±0.008	0.664±0.022	0.622±0.005
Reptile	1.09±0.06	1.37±0.19	2.76±0.07	6.60±0.21	0.887±0.012	0.870±0.015	0.622±0.005	0.604±0.006
Protonet	0.09±0.02	0.54±0.09	0.19±0.04	0.35±0.09	0.994±0.001	0.977±0.001	0.990±0.001	0.974±0.001
Protonet-SN	0.09±0.04	0.51±0.17	0.21±0.03	0.39±0.11	0.994±0.000	0.977±0.002	0.990±0.000	0.975±0.002
ProtoDDU	0.07±0.02	0.42±0.15	0.14±0.03	0.33±0.13	0.482±0.003	0.475±0.004	0.496±0.002	0.496±0.002
ProtoSNGP	0.09±0.04	0.15±0.04	0.14±0.05	0.20±0.04	0.994±0.001	0.977±0.003	0.989±0.001	0.972±0.002
Ours (Diag)	1.07±0.12	2.02±0.12	1.13±0.05	1.58±0.26	0.994±0.001	0.976±0.003	0.990±0.000	0.974±0.001
Ours (Rank 1)	1.06±0.09	2.14±0.30	1.14±0.05	1.71±0.27	0.994±0.001	0.976±0.002	0.990±0.001	0.974±0.001
Ours (Rank 2)	1.07±0.10	2.11±0.38	1.13±0.08	1.47±0.28	0.994±0.001	0.977±0.004	0.990±0.001	0.975±0.002
Ours (Rank 4)	1.00±0.11	2.00±0.45	1.16±0.06	1.52±0.12	0.994±0.000	0.977±0.002	0.990±0.001	0.975±0.001
Ours (Rank 8)	1.03±0.08	1.88±0.17	1.10±0.10	1.47±0.11	0.994±0.000	0.978±0.002	0.990±0.001	0.974±0.001

Table 5: Accuracy, NLL, ECE, and AUPR for different n-way k-shot classification problems on the MiniImageNet dataset. On uncorrupted in-distribution data, our method maintains performance relative to baseline methods.

	Accuracy ↑		NLL ↓	
Model	5-way 1-shot	5-way 5-shot	5-way 1-shot	5-way 5-shot
MAML	51.64±1.09	65.65±0.32	1.181±0.020	0.894±0.005
Reptile	49.26±0.97	61.33±0.56	1.263±0.015	1.003±0.009
Protonet	48.61±0.91	67.57±0.55	1.245±0.019	0.832±0.008
Protonet-SN	47.47±0.90	68.03±0.79	1.279±0.017	0.820±0.016
ProtoDDU	49.57±0.53	68.31±0.59	1.246±0.006	0.816±0.016
ProtoSNGP	49.55±0.90	66.89±0.88	1.232±0.012	0.841±0.020
Ours (Diag)	48.31±0.39	66.12±1.76	1.277±0.023	0.887±0.044
Ours (Rank 1)	48.57±0.96	66.54±0.66	1.267±0.013	0.859±0.016
Ours (Rank 2)	48.08±0.99	67.17±0.56	1.271±0.021	0.853±0.017
Ours (Rank 4)	47.76±0.62	66.73±0.37	1.274±0.020	0.868±0.010
Ours (Rank 8)	48.91±0.87	66.58±1.67	1.272±0.039	0.873±0.038
	ECE ↓		AUPR ↑	
MAML	1.71±0.35	2.54±0.40	0.529±0.009	0.566±0.008
Reptile	6.08±0.93	2.34±0.32	0.529±0.010	0.554±0.004
Protonet	5.62±1.08	4.09±0.86	0.609±0.010	0.596±0.006
Protonet-SN	6.77±1.81	3.22±0.96	0.608±0.011	0.602±0.002
ProtoDDU	7.33±1.44	3.46±0.55	0.473±0.006	0.479±0.003
ProtoSNGP	7.21±1.26	4.06±0.84	0.616±0.006	0.689±0.008
Ours (Diag)	9.40±1.82	8.32±2.46	0.607±0.011	0.602±0.013
Ours (Rank 1)	8.09±1.60	6.77±0.53	0.605±0.007	0.611±0.008
Ours (Rank 2)	7.50±2.30	7.92±1.34	0.610±0.008	0.611±0.003
Ours (Rank 4)	7.57±2.45	8.02±2.19	0.603±0.005	0.609±0.005
Ours (Rank 8)	10.03±3.64	8.80±1.53	0.609±0.010	0.606±0.005

(a) Meta Circles (ProtoMahalanobisFC)

(b) Meta Gaussians (ProtoMahalanobisFC)

Figure 10: ProtoMahalanobisFC model performance on the meta-moons and meta-circles toy datasets.

Figure 11: ProtoMahalanobisFC model performance on the meta Gaussians toy dataset.

Model	In Distribiution			Out of Distribiution		
	Accuracy ↑	NLL ↓	ECE ↓	ECE ↓	AUPR ↑	AUROC ↑
Protonet	97.02±1.60	0.171±0.110	**2.21±1.40**	48.16±0.91	0.999±0.000	0.931±0.012
ProtonetSN	**97.31±1.54**	0.140±0.088	2.38±1.38	48.40±0.64	0.999±0.000	0.932±0.006
Proto DDU	96.04±2.74	0.158±0.077	2.43±1.04	49.43±0.37	0.976±0.001	0.119±0.013
Proto SNGP	97.22±1.19	**0.138±0.046**	4.81±2.63	45.74±4.19	0.995±0.001	0.684±0.064
Ours (Diag)	96.82±1.09	0.167±0.056	5.09±1.18	**15.66±2.65**	0.999±0.000	0.937±0.006
Ours (Rank-1)	96.86±1.42	0.157±0.049	4.21±1.77	20.60±2.24	0.999±0.000	0.934±0.008
Ours (Rank-2)	96.90±1.55	0.162±0.042	5.13±1.39	17.74±2.76	0.999±0.000	0.939±0.006
Ours (Rank-4)	96.90±1.15	0.157±0.033	4.69±1.32	18.49±2.62	0.999±0.000	0.937±0.006
Ours (Rank-8)	96.69±1.36	0.171±0.047	4.74±1.48	19.75±3.53	0.999±0.000	0.935±0.007
Ours (Rank-16)	96.73±1.28	0.161±0.057	3.80±1.87	18.47±2.30	0.999±0.000	0.939±0.007
Ours (Rank-32)	96.73±1.28	0.170±0.042	4.49±1.01	18.22±3.26	0.999±0.000	**0.939±0.005**
Ours (Rank-64)	96.73±1.55	0.159±0.045	4.43±0.99	17.90±2.49	0.999±0.000	0.938±0.005

Table 6: Table of results from the meta-moons toy experiment

Model	In Distribiution			Out of Distribiution		
	Accuracy ↑	NLL ↓	ECE ↓	ECE ↓	AUPR ↑	AUROC ↑
Protonet	89.12±3.92	0.343±0.091	4.33±0.83	81.84±0.78	0.999±0.000	0.950±0.009
ProtonetSN	88.93±4.12	0.342±0.098	4.23±0.71	82.42±0.87	0.999±0.000	0.951±0.008
Proto DDU	90.45±2.67	0.267±0.061	**3.52±0.95**	84.48±0.41	0.969±0.001	0.175±0.003
Proto SNGP	89.63±3.30	0.323±0.063	7.39±2.71	62.60±6.57	0.999±0.000	0.916±0.014
Ours (Diag)	90.61±3.54	0.279±0.075	7.24±1.57	**42.55±0.98**	0.999±0.000	0.954±0.005
Ours (Rank-1)	91.01±2.65	0.271±0.062	7.12±1.00	42.77±1.62	0.999±0.000	0.954±0.005
Ours (Rank-2)	**91.31±2.87**	0.269±0.064	7.59±1.34	43.13±1.90	0.999±0.000	0.955±0.004
Ours (Rank-4)	90.96±2.76	0.272±0.068	6.68±0.56	43.33±1.80	0.999±0.000	0.955±0.004
Ours (Rank-8)	90.99±2.52	0.268±0.065	6.74±1.02	43.14±1.49	0.999±0.000	0.955±0.004
Ours (Rank-16)	91.01±2.88	0.264±0.065	6.96±1.23	42.93±1.94	0.999±0.000	0.955±0.005
Ours (Rank-32)	90.45±3.22	0.267±0.069	6.35±0.27	42.89±1.48	0.999±0.000	**0.956±0.004**
Ours (Rank-64)	90.83±2.99	**0.264±0.064**	6.79±0.83	42.67±1.67	0.999±0.000	**0.956±0.004**

Table 7: Table of results from the meta-Gaussians toy experiment

Model	In Distribiution			Out of Distribiution		
	Accuracy ↑	NLL ↓	ECE ↓	ECE ↓	AUPR ↑	AUROC ↑
Protonet	94.45±3.18	0.195±0.106	3.49±1.67	49.19±0.25	1.000±0.000	0.952±0.007
ProtonetSN	94.53±2.49	0.185±0.098	**3.03±1.58**	49.17±0.21	1.000±0.000	0.952±0.007
Proto DDU	95.02±1.79	**0.165±0.088**	3.62±2.27	48.87±0.18	0.972±0.001	0.072±0.008
Proto SNGP	94.49±2.09	0.192±0.071	6.05±3.56	45.14±3.08	0.992±0.001	0.683±0.055
Ours (Diag)	94.24±3.85	0.215±0.139	4.11±0.62	**14.64±4.32**	1.000±0.000	0.954±0.011
Ours (Rank-1)	94.08±4.62	0.214±0.158	4.34±1.46	19.04±8.21	1.000±0.000	0.953±0.013
Ours (Rank-2)	94.53±4.27	0.192±0.148	3.54±1.52	18.22±3.72	1.000±0.000	0.954±0.013
Ours (Rank-4)	94.12±4.68	0.209±0.158	4.27±1.83	19.61±4.52	1.000±0.000	0.954±0.013
Ours (Rank-8)	94.00±4.69	0.194±0.134	3.80±1.45	19.37±4.42	1.000±0.000	0.955±0.014
Ours (Rank-16)	94.12±4.40	0.205±0.148	4.12±1.93	20.59±5.47	1.000±0.000	0.955±0.013
Ours (Rank-32)	**93.84±4.66**	0.193±0.141	3.48±1.54	20.50±5.56	1.000±0.000	0.954±0.014
Ours (Rank-64)	94.16±4.61	0.196±0.146	3.46±1.31	19.53±6.30	1.000±0.000	0.955±0.014

Table 8: Table of results from the meta-circles toy experiment

This means that SNGP can use the pretrained ProtoNet-12-SN model as a backbone and we can apply the Random Features and construct the Gaussian process at meta test time for each sampled task.

OOD AUPR/AUROC In ordre to evaluate the OOD AUPR/AUROC metrics in the supplementary tables, we utilize the method proposed by Liu et al. (2020b). Specifically, we use the total energy in the logits $\log \sum_i \exp(z_i))$ as the score when evaluating AUPR/AUROC.

(a) Meta Circles (DDU)

(b) Meta Moons (DDU)

Figure 12: Proto DDU model performance on the two toy meta learning datasets.

A.6 ADDITIONAL EIGENVALUE DISTRIBUTIONS

The eigenvalue distributions highlighted in section 4 exhibit the most diverse case of eigenvalues. The eigenvalues of ProtoMahalanobis models become less diverse in the one-shot setting which is also where the calibration performance is more comptetitive with the baseline models in

A.7 ADDITIONAL BOXPLOT RESULTS

A.8 ARCHITECTURE DETAILS

Table 9: Convolutional architecture used for MAML/Reptile Omniglot

Layers
Conv2d(1, 64, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU
Conv2d(64, 64, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU
Conv2d(64, 64, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU
Conv2d(64, 64, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU
AveragePool(2)
FC(64, nway)

Table 10: Convolutional architecture used for MAML/Reptile MiniImageNet

Layers
Conv2d(1, 32, pad=1, stride=1) → BatchNorm(transductive=True) → ReLU → MaxPool2d(2)
Conv2d(32, 32, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU → MaxPool2d(2)
Conv2d(32, 32, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU → MaxPool2d(2)
Conv2d(32, 32, pad=1, stride=2) → BatchNorm(transductive=True) → ReLU → MaxPool2d(2)
Flatten
FC(1600, nway)

(a) Meta Gaussians (DDU)

Figure 13: Proto DDU model performance on the toy meta learning datasets.

(a) Meta Circles (Protonet) (b) Meta Gaussians (Protonet) (c) Meta Moons (Protonet)

Figure 14: Protonet model performance on the three meta-toy datasets.

(a) Meta Circles (SNGPProtoFC)

(b) Meta Moons (SNGPProtoFC)

Figure 15: SNGPProtoFC model performance on the meta-moons and meta-circles toy datasets.

Table 11: Convolutional architecture used for Protonet Models. Plain Protonets use no spectral normalization

Layers
SpectralNorm(Conv2d(1, 64, pad=1, stride=1), residual=True, c=3) → BatchNorm(transductive=False) → ReLU → Dropout() → AveragePool2d(2)
SpectralNorm(Conv2d(1, 64, pad=1, stride=1), residual=True, c=3) → BatchNorm(transductive=False) → ReLU → Dropout() → AveragePool2d(2)
SpectralNorm(Conv2d(1, 64, pad=1, stride=1), residual=True, c=3) → BatchNorm(transductive=False) → ReLU → Dropout() → AveragePool2d(2)
SpectralNorm(Conv2d(1, 64, pad=1, stride=1), residual=True, c=3) → BatchNorm(transductive=False) → ReLU → Dropout() → AveragePool2d(2)
Flatten()
FC(features, nway)

Figure 16: SNGPProtoFC model performance on the meta-Gaussians toy dataset.

Figure 17: From left to right: covariance, precision, and eigenvalue distribution for ProtoMahalanobis precision matrix on Omniglot 20-way/1-shot experiments.

Figure 18: From left to right: covariance, precision, and eigenvalue distribution for ProtoSNGP models on Omnniglot 20-way/5-shot. Even on 20-way/5-shot ProtoSNGP still exhibits a lack of diversity in the eigenvalues of the precision matrix.

Figure 19: Accuracy boxplots for different variations of the Omniglot dataset

Figure 20: NLL boxplots for different variations of the Omniglot dataset

Figure 21: Accuracy boxplots for different variations of the MiniImageNet dataset

Figure 22: NLL boxplots for different variations of the MiniIMageNet dataset