Generating Synthetic Datasets by Interpolating along Generalized Geodesics

Abstract

Data for pretraining machine learning models often consists of collections of heterogeneous datasets. Although training on their union is reasonable in agnostic settings, it might be suboptimal when the target domain —where the model will ultimately be used— is known in advance. In that case, one would ideally pretrain only on the dataset(s) most similar to the target one. Instead of limiting this choice to those datasets already present in the pretraining collection, here we explore extending this search to all datasets that can be synthesized as 'combinations' of them. We define such combinations as multi-dataset interpolations, formalized through the notion of generalized geodesics from optimal transport (OT) theory. We compute these geodesics using a recent notion of distance between labeled datasets, and derive alternative interpolation schemes based on it: using either barycentric projections or optimal transport maps, the latter computed using recent neural OT methods. These methods are scalable, efficient, and —notably— can be used to interpolate even between datasets with distinct and unrelated label sets. Through various experiments in transfer learning in computer vision, we demonstrate this is a promising new approach for targeted on-demand dataset synthesis.

1 INTRODUCTION

Recent progress in machine learning has been characterized by the rapid adoption of large pretrained models as a fundamental building block [Brown et al., 2020]. These models are typically pretrained on large amounts of general-purpose data and then adapted (e.g., *fine-tuned*) to a specific task of interest. Such pretraining datasets usually draw from multiple heterogeneous data sources, e.g., arising from different domains or sources. Traditionally, all available datasets are used in their entirety during pretraining, for example by pooling them together into a single dataset (when they all share the same label sets) or by training in all of them sequentially one by one. These strategies, however, come with important disadvantages. Training on the union of multiple datasets might be prohibitive or too time-consuming, and it might even be detrimental — indeed, there is a growing line of research showing that removing pretraining data sometimes improves transfer performance [Jain et al., 2022]. On the other hand, sequential learning (i.e., consuming datasets one by one) is infamously prone to *catastrophic forgetting* [McCloskey and Cohen, 1989, Kirkpatrick et al., 2017]: the information from earlier datasets gradually vanishing as the model is trained on new datasets. The pitfalls of both of these approaches suggest training instead on a *subset* of the available pretraining datasets, but how to choose that subset is unclear. However, when the target dataset on which the model is to be used is known in advance, the answer is much easier: intuitively, one would train only of those relevant to the target one: e.g., those most similar to it. Indeed, recent work has shown that selecting pretraining datasets based on the distance to the target is a successful strategy [Alvarez-Melis and Fusi, 2020, Gao and Chaudhari, 2021]. However, such methods are limited to selecting (only) among individual datasets already present in the collection.

In this work, we propose a novel approach to *generate* synthetic pretraining datasets as combinations of existing ones. In particular, this method searches among all possible continuous combinations of the available datasets, and thus is not limited to selecting specifically one of them. When given access to the target dataset of interest, we seek among all such combinations the one closest (in terms of a metric between datasets) to the target. By characterizing datasets as sampled from an underlying probability distribution, this problem can be understood as a generalization (from Euclidean to probability space) of the problem of finding among the convex hull of a set of reference points, that which is closest to a query point. While this problem has a simple closed-form

Submitted to the 39th Conference on Uncertainty in Artificial Intelligence (UAI 2023). **To be used for reviewing only**.

solution in Euclidean space (via an orthogonal projection), solving it in probability space is —as we shall see here— significantly more challenging.

We tackle this problem from the perspective of interpolation. Formally, we model the combination of datasets as an interpolation between their distributions, formalized through the notion of geodesics in probability space endowed with the Wasserstein metric [Ambrosio et al., 2008, Villani, 2008]. In particular, we rely on *generalized geodesics* [Craig, 2016, Ambrosio et al., 2008]: constant-speed curves connecting a pair (or more) distributions parametrized with respect to a 'base' distribution, whose role is played by the target dataset in our setting. Computing such geodesics requires access to either an optimal transport coupling or map between the base distribution and every other reference distribution. The former can be computed very efficiently with off-the-shelf OT solvers, but are limited to generating only as many samples as the problem is originally solved on. In contrast, OT maps allow for on-demand out-of-sample mapping and can be estimated using recent advances in neural OT methods [Fan et al., 2020, Korotin et al., 2022b, Makkuva et al., 2020]. However, most existing OT methods assume unlabeled (feature-only) distributions, but our goal here is to interpolate between classification (i.e., labeled) datasets. Therefore, we leverage a recent generalization of OT for labeled datasets to compute couplings [Alvarez-Melis and Fusi, 2020] and adapt and generalize neural OT methods to the labeled setting to estimate OT maps.

In summary, the contributions of this paper are: (i) a novel approach to generate new synthetic classification datasets from existing ones by using geodesic interpolations, applicable even if they have disjoint label sets, (ii) two efficient methods to solve OT between labeled datasets, which might be of independent interest, (iii) empirical validation of the method in various transfer learning settings.

2 RELATED WORK

Mixup and related In-Domain Interpolation Generating training data through convex combinations was popularized by *mixup* [Zhang et al., 2018]: a simple data augmentation technique that interpolates features and labels between pairs of points. This and other works based on it [Zhang et al., 2021, Chuang and Mroueh, 2021] use mixup to improve in-domain model robustness [Zhu et al., 2023] and generalization by increasing the in-distribution diversity of the training data. Although sharing some intuitive principles with mixup, our method interpolates entire datasets —rather than individual datapoints— with the goal of improving across-distribution diversity and therefore out-of-domain generalization.

Dataset synthesis in machine learning Generating data beyond what is provided as a training dataset is a crucial component of machine learning in practice. Basic transformations such as rotations, cropping, and pixel transformations can be found in most state-of-the-art computer vision models. More recently, Generative Adversarial Nets (GAN) have been used to generate synthetic data in various contexts [Bowles et al., 2018, Yoon et al., 2019], a technique that has proven particularly successful in the medical imaging domain [Sandfort et al., 2019]. Since GANs are trained to replicate the dataset on which they are trained, these approaches are typically confined to generating in-distribution diversity, and typically operate on features only.

Discrete OT, Neural OT, Gradient Flows Barycentric projection [Ambrosio et al., 2008, Perrot et al., 2016] is a simple and effective method to approximate an optimal transport map with discrete regularized OT. On the other hand, there has been remarkable recent progress in methods to estimate OT maps in Euclidean space using neural networks [Makkuva et al., 2020, Fan et al., 2021, Rout et al., 2022], which have been successfully used for image generation [Rout et al., 2022], style transfer [Korotin et al., 2022b], among other applications. However, the estimation of an optimal map between (labeled) datasets has so far received much less attention. Some conditional Monge map solvers [Asadulaev et al., 2022, Bunne et al., 2022a] utilize the label information in a semi-supervised manner, where they assume the label-to-label correspondence between two distributions is known. Our method differs from their in that we do not require a pre-specified label-to-label mapping, but instead estimate it from data. Geodesics and interpolation in general metric spaces based on have been studied extensively in the optimal transport and metric geometry literatures [McCann, 1997, Agueh and Carlier, 2011, Ambrosio et al., 2008, Santambrogio, 2015, Villani, 2008, Craig, 2016], albeit mostly in a theoretical setting. Gradient flows [Santambrogio, 2015], increasingly popular in machine learning to model existing processes [Bunne et al., 2022b, Mokrov et al., 2021, Fan et al., 2022] or solving optimization problems over datasets [Alvarez-Melis and Fusi, 2021], provide an alternative approach for interpolation between distributions but are computationally expensive.

3 BACKGROUND

3.1 DISTRIBUTION INTERPOLATION WITH OT

Consider $\mathcal{P}(\mathcal{X})$ the space of probability distribution finite second moments over some Euclidean space $\mathcal{X}$. Given $\mu, \nu \in \mathcal{P}(\mathcal{X})$, the Monge formulation optimal transport problem seeks a map $T : \mathcal{X} \to \mathcal{X}$ that transforms μ into ν at a minimal cost. Formally, the objective of this problem is $\min_{T:T\sharp\mu=\nu} \int_{\mathbb{R}^d} \|x - T(x)\|_2^2 \mathrm{d}\mu(x)$, where the minimization is over all the maps that pushforward distribution μ into distribution ν. While a solution to this problem might not exist, a relaxation due to Kantorovich is guaranteed to have

one. This modified version yields the 2-Wasserstein distance: $W_2^2(\mu, \nu) = \min_{\pi \in \Pi(\mu,\nu)} \int_{\mathbb{R}^d} \|x - x'\|_2^2 \mathrm{d}\pi(x, x')$, where now the constraint set $\Pi(\mu, \nu) = \{\pi \in \mathcal{P}(\mathcal{X}^2) \mid P_{0\sharp}\pi = \mu, P_{1\sharp}\pi = \nu\}$ contains all couplings with marginals μ and ν. The optimal such coupling is known as the OT plan. A celebrated result by Brenier [1991] states that whenever P has density with respect to the Lebesgue measure, the optimal T^* exists and is unique. In that case, the Kantorovich and Monge formulations coincide and their solutions are linked by $\pi^* = (\mathrm{Id}, T^*)_{\sharp}\mu$ where Id is the identity map. The Wasserstein-2 distance enjoys many desirable geometrical properties compared to other distances for distributions [Ambrosio et al., 2008]. One such property is the characterization of geodesics in probability space [Agueh and Carlier, 2011, Santambrogio, 2015]. When $\mathcal{P}(\mathcal{X})$ is equipped with metric W_2, the unique minimal geodesic between any two distributions μ_0 and μ_1 is fully determined by π, the optimal transport plan between them, through the relation:

$$\rho_t^D := ((1 - t)x + ty)\sharp\pi(x, y), \quad t \in [0, 1],$$

known as *displacement interpolation*. If the Monge map from μ_0 to μ_1 exists, the geodesic can also be written as

$$\rho_t^M := ((1 - t)\mathrm{Id} + tT^*)\sharp\mu_0, \quad t \in [0, 1], \qquad (1)$$

and is known as *McCann's interpolation* [McCann, 1997]. It is easy to see that $\rho_0^M = \mu_0$ and $\rho_1^M = \mu_1$.

Such interpolations are only defined between two distributions. When there are $m \geq 2$ marginal distributions $\{\mu_1, \ldots, \mu_m\}$, the *Wasserstein barycenter*

$$\rho_a^B := \arg\min_\rho \sum_{i=1}^m a_i W_2^2(\rho, \mu_i), \quad a \in \Delta_m \subset \mathbb{R}^m$$

generalizes McCann's interpolation [Agueh and Carlier, 2011]. Intuitively, the interpolation parameters $a = [a_1, \ldots, a_m]$ determine the 'mixture proportions' of each dataset in the combination, akin to the weights in a convex combination of points in Euclidean space. In particular, when a is a one-hot vector with $a_i = 1$, then $\rho_a^B = \mu_i$, i.e., the barycenter is simply the i-th distribution. Barycenters have attracted significant attention in machine learning recently [Srivastava et al., 2018, Korotin et al., 2021], but they remain challenging to compute in high dimension [Fan et al., 2020, Korotin et al., 2022a].

Another limitation of these interpolation notions is the non-convexity of W_2^2 along them. In Euclidean space, given three points $x_1, x_2, y \in \mathbb{R}^d$, the function $t \mapsto \|x_t - y\|_2^2$, where x_t is the interpolation $x_t = (1 - t)x_1 + tx_2$, is convex. In contrast, in Wasserstein space, neither the function $t \mapsto W_2^2(\rho_t^M, \nu)$ or $\mapsto W_2^2(\rho_a^B, \nu)$ are guaranteed to be convex [Santambrogio, 2017, Sec. 4.4]. This complicates their theoretical analysis, such as in gradient flows. To circumvent this issue, Ambrosio et al. [2008] introduced the *generalized*

geodesic of $\{\mu_1, \ldots, \mu_m\}$ with base $\nu \in \mathcal{P}(\mathcal{X})$:

$$\rho_a^G := \left(\sum_{i=1}^m a_i T_i^*\right)\sharp\nu, \quad a \in \Delta_m,$$

where T_i^* is the optimal map from ν to μ_i.

Lemma 1. *The functional $\mu \mapsto W_2^2(\mu, \nu)$ is convex along the generalized geodesics, and $W_2^2(\rho_a^G, \nu) \leq \sum_{i=1}^m a_i W_2^2(\mu_i, \nu)$.*

Thus, unlike the barycenter, the generalized geodesic does yield a notion of convexity satisfied by the Wasserstein distance, and is easier to compute. For these reasons, we adopt this notion of interpolation for our approach. It remains to discuss how to use it on (labeled) datasets.

3.2 DATASET DISTANCE

Consider a dataset $\mathcal{D}_P = \{z^{(i)}\}_{i=1}^N = \{x^{(i)}, y^{(i)}\}_{i=1}^N \overset{i.i.d.}{\sim} P(x, y)$. The Optimal Transport Dataset Distance (OTDD) [Alvarez-Melis and Fusi, 2020] measures its distance to another dataset $\mathcal{D}_Q$ as:

$$d_{\mathrm{OT}}^2(\mathcal{D}_P, \mathcal{D}_Q) =$$
$$\min_{\pi \in \Pi(P,Q)} \int \left(\|x - x'\|_2^2 + W_2^2(\alpha_y, \alpha_{y'})\right) \mathrm{d}\pi(z, z'), (2)$$

which defines a proper metric between datasets. Here, $\alpha_y, \alpha_{y'}$ are class-conditional measures corresponding to $P(x|y)$ and $Q(x|y')$. This distance is strongly correlated with transfer learning performance, i.e., the accuracy achieved when training a model on $\mathcal{D}_P$ and then fine-tuning and evaluating on $\mathcal{D}_P$. Therefore, it can be used to select pretraining datasets for a given target domain. Henceforth we abuse the notation P to represent both a dataset and its underlying distribution for simplicity. To avoid confusion, we use ν and μ to represent distributions in the feature space (typically $\mathbb{R}^d$) and use P, Q to represent distributions in the product space of features and labels.

4 METHOD AND ALGORITHM

Our method consists of two steps: estimating optimal transport maps between the target dataset and all training datasets (Sec. 4.1), and using them to generate a convex combinations of these datasets by interpolating along generalized geodesics (Sec. 4.2). For some downstream applications we will additionally project the target dataset into the 'convex hull' of the training datasets (Sec. 4.3).

4.1 ESTIMATING OPTIMAL MAPS BETWEEN LABELED DATASETS

The OTDD is a special case of Wasserstein distance, so it is natural to consider the alternative Monge (map-based)

Figure 1: Visualization of barycentric projection on binary PCAM dataset. Each mapped data contains a weighted image and a weighted soft label.

Figure 2: Visualization of loss for OTDD neural map

formulation to (2). We propose two methods to approximate the OTDD map, one using the entropy-regularized OT and another one based on neural OT.

OTDD barycentric projection. Barycentric projections [Ambrosio et al., 2008, Pooladian and Niles-Weed, 2021] can be efficiently computed for entropic regularized OT using the Sinkhorn algorithm [Sinkhorn, 1967]. Assume that we have empirical distributions $\nu = \sum_{i=1}^{N_\nu} \frac{1}{N_\nu} \delta_{x_\nu^{(i)}}$ and $\mu = \sum_{i=1}^{N_\mu} \frac{1}{N_\mu} \delta_{x_\mu^{(i)}}$, where δ_x is the Dirac function at x. Denote all the samples compactly as matrices: $X_\nu = \left(x_\nu^{(1)}, \ldots, x_\nu^{(N_\nu)} \right) \in \mathbb{R}^{N_\nu \times d}, X_\mu = \left(x_\mu^{(1)}, \ldots, x_\mu^{(N_\mu)} \right) \in \mathbb{R}^{N_\mu \times d}$. After solving the optimal coupling $\pi^* := \min_{\pi \in \Pi(\nu,\mu)} \sum_{i,j} \|x_\nu^{(i)} - x_\mu^{(j)}\|^2 \pi(i,j)$, the barycentric projection can be expressed as $T_B(X_\nu) = N_\nu \pi^* X_\mu$. We extend this method to two datasets $Z_Q = \{X_Q, Y_Q\}, Z_P = \{X_P, Y_P\}$, where we have additional one-hot label data $Y_Q = (y_Q^{(1)}, \ldots, y_Q^{(N_Q)}) \in \mathbb{R}^{N_Q \times C_Q}, Y_P = (y_P^{(1)}, \ldots, y_P^{(N_P)}) \in \mathbb{R}^{N_P \times C_P}$. C_Q and C_P are the number of classes in dataset Q and P. We solve the optimal coupling $\pi^* \in \mathbb{R}^{N_P \times N_Q}$ for OTDD (2) following the regularized scheme in Alvarez-Melis and Fusi [2020]. The barycentric projection can then be written as:

$$\mathcal{T}_B(Z_Q) = [N_Q \pi^* X_P, N_Q \pi^* Y_P]. \tag{3}$$

However, this approach has two important limitations: it can not naturally map out-of-sample data and it does not scale well to large datasets (due to the quadratic dependency on sample size).

OTDD neural map. Inspired by recent approaches to estimate Monge maps using neural networks [Rout et al., 2022, Fan et al., 2021], we design a similar framework for the OTDD setting. Fan et al. [2021] approach the Monge OT problem with general cost functions by solving its max-min dual problem

$$\sup_f \inf_T \int [c(x, T(x)) - f(T(x))] \, \mathrm{d}\nu(x) + \int f(x') \mathrm{d}\mu(x').$$

We extend this method to the distributions involving labels by introducing an additional classifier in the map. Given two datasets P, Q, we parameterize the map $\mathcal{T}_N : \mathbb{R}^d \times \mathbb{R}^{C_Q} \to \mathbb{R}^d \times \mathbb{R}^{C_P}$ as

$$\mathcal{T}_N(z) = \mathcal{T}_N(x, y) = [\bar{x}; \bar{y}] = [G(z); \ell(G(z))],$$

where $G(\cdot) : \mathbb{R}^d \to \mathbb{R}^d$ is the pushforward feature map, and the $\ell(\cdot) : \mathbb{R}^d \to \mathbb{R}^{C_P}$ is a frozen classifier that is pre-trained on the dataset P. Notice that, with the cost $c(z, \mathcal{T}(z)) = \|x - G(z)\|_2^2 + W_2^2(\alpha_y, \alpha_{\bar{y}})$, the Monge formulation of OTDD (2) reads $\inf_{T \sharp Q = P} \int \|x - G(z)\|_2^2 + W_2^2(\alpha_y, \alpha_{\bar{y}}) \mathrm{d}Q(z)$. We therefore propose to solve the max-min dual problem

$$\sup_f \inf_G \int \left[\|x - G(z)\|_2^2 + W_2^2(\alpha_y, \alpha_{\bar{y}}) \right] \mathrm{d}Q(z)$$
$$- \int f(\bar{x}, \bar{y}) \mathrm{d}Q(z) + \int f(x', y') \mathrm{d}P(z'). \tag{4}$$

Implementation details are provided in Appendix B. Compared to previous conditional Monge map solvers [Bunne et al., 2022a, Asadulaev et al., 2022], the two methods proposed here: (i) do not assume class overlap across datasets, allowing for maps between datasets with different label sets; (ii) are invariant to class permutation and re-labeling; (iii) do not force one-to-one class alignments, e.g., samples can be mapped across similar classes.

4.2 CONVEX COMBINATION IN DATASET SPACE

Computing generalized geodesics requires constructing convex combinations of datapoints from different datasets. Given a weight vector $a \in \mathbb{R}^m$, features can be naturally combined as $x_a = \sum_{i=1}^m a_i x_i$. But combining labels is not as simple because: (i) we allow for datasets with different number of labels, so adding them directly is not possible; (ii) we do not assume different datasets have the same label sets, e.g. MNIST (digits) vs CIFAR10 (objects). Our solution is to represent all labels in the same dimensional space by padding them with zeros in all entries corresponding to other datasets. As an example, consider three datasets with 2, 3, and 4 classes respectively. Given a label vector $y_1 \in \mathbb{R}^3$ for the first one, we embed it into $\mathbb{R}^9$ as $\tilde{y}_1 = [y_1; \mathbf{0}_3; \mathbf{0}_4]^\top$.

Figure 3: In few-shot experiments, the test dataset labels are pseudo labels, e.g. KNN classified labels. If there exists training data from the test dataset, we will replace the pseudo labels in the above diagram by them.

Defining $\tilde{y}_2, \tilde{y}_3$ analogously, we compute their combination as $y_a = a_1\tilde{y}_1 + a_2\tilde{y}_2 + a_3\tilde{y}_3$. This representation is loss-less and preserves the distinction of labels across datasets.

4.3 PROJECTION ONTO GENERALIZED GEODESIC OF DATASETS

We finally put together the components in Sec 4.1 and 4.2 to construct generalized geodesics between datasets in two steps. First, we compute OTDD maps $\mathcal{T}_i^*$ between Q and all other datasets $P_i, i = 1, \ldots, m$ using the discrete or neural OT approaches. Then, for any interpolation vector $a \in \Delta_m$ we identify a dataset along the generalized geodesic via

$$P_a := \left(\sum_{i=1}^m a_i \mathcal{T}_i^* \right) \sharp Q.$$

By using the convex combination method in Sec. 4.2 for labeled data, we can efficiently sample from P_a.

Next, we find the dataset P_a^* that minimizes the distance between P_a and Q, i.e. the projection of Q onto the generalized geodesic. We first approach this problem from a Euclidean viewpoint. Suppose there are several distributions $\{\mu_i\}_{i=1}^m$ and an additional distribution ν on Euclidean space $\mathbb{R}^d$. Lemma 1 guarantees there exists a unique parameter a^* that minimizes $W_2^2(\rho_a^G, \nu)$. However, finding a^* is far from trivial because there is no closed-form formula of the map $a \mapsto W_2^2(\rho_a^G, \nu)$ and it can be expensive to calculate $W_2^2(\rho_a^G, \nu)$ for all possible a. To solve this problem, we resort to another transport distance: the $(2,\nu)$-transport metric.

Definition 1 (Craig [2016]). *Given distributions μ_i, μ_j, the $(2,\nu)$-transport metric between them is given by*

$$W_{2,\nu}(\mu_i, \mu_j) := \left(\int \|T_i^*(x) - T_j^*(x)\|_2^2 d\nu(x) \right)^{1/2},$$

where T_i^* is the optimal map from ν to μ_i.

When ν has a density with respect to Lebesgue measure $W_{2,\nu}$ is a valid metric [Craig, 2016, Prop. 1.15]. Moreover, we can derive a closed-form formula for the map $a \mapsto W_{2,\nu}^2(\rho_a^G, \nu)$.

Proposition 1. $W_{2,\nu}^2(\rho_a^G, \nu) = \sum_{i=1}^m a_i W_{2,\nu}^2(\mu_i, \nu) - \frac{1}{2} \sum_{i \neq j} a_i a_j W_{2,\nu}^2(\mu_i, \mu_j)$.

This equation implies that given distributions $\{\mu_i\}, \nu$ in Euclidean space, we can trivially solve the optimal a^* that minimizes $W_{2,\nu}^2(\rho_a^G, \nu)$ by a quadratic programming solver[1]. The proof (Appendix A) relies on Brenier's theorem. Inspired by this, we also define a transport metric for datasets:

Definition 2. *The squared (2,Q)-dataset distance is*

$$\mathcal{W}_{2,Q}^2(P_i, P_j) := \int \left(\|x_i - x_j\|_2^2 + W_2^2(\alpha_{y_i}, \alpha_{y_j}) \right) dQ(z),$$

where $[x_i; y_i] = \mathcal{T}_i^*(z)$ and $\mathcal{T}_i^*$ is the OTDD map from Q to P_i.

Denote $\mathcal{P}_{2,Q}(\mathcal{X} \times \mathcal{P}(\mathcal{X}))$ as the set of all probability measures P that satisfy $d_{\text{OT}}(P, Q) < \infty$ and the OTDD map from Q to P exists. The following result shows that $(2,Q)$-dataset distance is a proper distance. The proof is again deferred to Appendix A.

Proposition 2. $\mathcal{W}_{2,Q}$ *is a valid metric on* $\mathcal{P}_{2,Q}(\mathcal{X} \times \mathcal{P}(\mathcal{X}))$.

Unfortunately, in this case $\mathcal{W}_{2,Q}^2(P_i, P_j)$ does not have an analytic form like before because Brenier's theorem may not hold for a general transport cost problem. However, we still borrow this idea and define an approximated projection $\hat{P}_a$ as the minimizer of function

$$\mathcal{W}^2(P_a, Q) :=$$
$$\sum_{i=1}^m a_i \mathcal{W}_{2,Q}^2(P_i, Q) - \frac{1}{2} \sum_{i \neq j} a_i a_j \mathcal{W}_{2,Q}^2(P_i, P_j), \quad (5)$$

which is an analog of Proposition 1. Unlike the Wasserstein distance, $\mathcal{W}_{2,Q}^2(\cdot, \cdot)$ is easier to compute because it does not involve optimization, so it is relatively cheap to find the minimizer of $\mathcal{W}^2(P_a, Q)$. Experimentally, we observe that $W_{2,Q}^2(P_a, Q)$ is predictive of model transferability across tasks. Figure 4(a) illustrates this projection on toy 3D datasets, color-coded by class.

5 EXPERIMENTS

5.1 LEARNING OTDD MAPS

In this section, we visualize the quality of the learnt OTDD maps on both synthetic and realistic datasets.

---

[1]We use the implementation https://github.com/stephane-caron/qpsolvers

(a)

(b)

Figure 4: **Comparison to mixup interpolation,** (a) Approximated projection $\widehat{P}_a$ of 3D dataset Q onto the generalized geodesic of datasets $\{P_i\}$. (b) Left to right: the 2D projection of the datasets Q, the dataset $\left(\sum_{i=1}^m a_i^* \mathcal{T}_i^*\right) \sharp Q$, and the dataset $\left(\sum_{i=1}^m a_i^* \mathcal{T}_i\right) \sharp Q$, where $\mathcal{T}_i^*$ is the (optimal) OTDD map and $\mathcal{T}_i$ is a randomly generated map.

Synthetic datasets Figure 4 (b) illustrates the role of the optimal map in estimating the projection of a dataset into the generalized geodesic hull of three others. Using maps $\mathcal{T}_i^*$ estimated via barycentric projection (3) results in a better preservation of class structure, whereas using non-optimal maps $\mathcal{T}_i$ based on random couplings (as the usual *mixup* does) destroys class structure.

*NIST datasets In Figure 5, we provide qualitative results of OTDD map from EMNIST (letter) [Cohen et al., 2017] dataset to all other *NIST dataset and USPS dataset. At this point, we can confirm three traits of OTDD map, which are mentioned at the end of Sec. 4.1. 1) We don't assume a known source label to target label correspondence. So we can map between two irrelevant datasets such as EM-NIST and FashionMNIST. 2) The map is invariant to the permutation of label assignment. For example, we show two different labelling in Figure 7, and the final OTDD map will be the same. 3) It doesn't enforce the label-to-label mapping but would follow the feature similarity. From Figure 5, we notice many cross-class mapping behaviors. For example, when the target domain is USPS [Hull, 1994] dataset, the lower-case letter "l" is always mapped to digit 1, and the capital letter "L" is mapped to other digits such as 6 or 0 because the map follows the feature similarity.

5.2 TRANSFER LEARNING ON *NIST DATASETS

Next, we use our framework to generate new pretraining datasets for transfer learning. Preceding works illustrate that the transfer learning performance can be quite sensitive to the type of test datasets if there is abundant training data from the test task [Zhai et al., 2019, Table 1]. Thus, we will focus on the few-shot setting, where we only have few labeled data from the test task. We first show that the generalization ability of training models has a strong correlation with the distance $\mathcal{W}_{2,Q}^2(P_a, Q)$. Then we compare our framework with several baseline methods.

Figure 5: The dataset Q is EMNIST (letters). We show all the datasets pushforwarded towards Fashion-MNIST, MNIST, USPS, KMNIST by OTDD map. The OTDD map is solved by neural OT method.

Setup Given m labeled pretraining datasets $\{P_i\}$, we consider a few-shot task in which only a limited amount of data from the target domain is labeled, e.g. 5 samples per class. The goal is to find a single dataset of size comparable to any individual P_i that yields the best generalization to the target domain when pre-training a model on it and fine-tuning on the target few-shot data. Here, we seek this training dataset within those generated by generalized geodesics $\{P_a\}$, which can be understood as weighted interpolations of the training datasets $\{P_i\}$. Note this includes individual datasets as particular cases when a is a one-hot vector.

Connection to generalization The closed-form expression of $W_{2,\nu}^2(\rho_a^G, \nu)$ (Prop. 1) provides a distance between

Figure 6: Relationship between the function $\mathcal{W}^2(P_a, Q)$ and the accuracy of the fine-tuned model. The model trained on the projection dataset $\hat{P}_a$, i.e. the minimizer of $\mathcal{W}^2(P_a, Q)$, tends to have a better generalization accuracy. The training datasets are marked on the vertexes of each ternary plot. Each ternary plot is an average of 5 runs with distinct random seeds.

Table 1: **Pretraining on synthetic data**. For each of the *NIST datasets, we treat it as the target domain and pretrain a neural net on a synthetic dataset generated as a combination of the remaining dataset with three interpolation methods. Here we show 5-shot transfer accuracy (mean $\pm$ s.d. over 5 runs).

Methods	MNIST-M	EMNIST	MNIST	FMNIST	USPS	KMNIST
OTDD barycentric projection	**42.10±4.37**	**67.06±2.55**	**93.74±1.46**	**70.12±3.02**	86.01±1.50	**52.55±2.73**
OTDD neural map	40.06±4.75	65.32±1.80	88.78±3.85	70.02±2.59	83.80±1.60	50.32±3.10
Mixup	33.85±2.22	60.95±1.38	88.68±1.57	66.74±3.79	**88.61±2.00**	48.16±3.38
Train on few-shot dataset	19.10±3.57	53.60±1.18	72.80±3.10	60.50±3.07	80.73±2.07	41.67±2.11
1-NN on few-shot dataset	20.95±1.39	39.70±0.57	64.50±3.32	60.92±2.42	73.64±2.35	40.18±3.09

a base distribution ν and the distribution along generalized geodesic ρ_a^G in Euclidean space. We study its analog (5) for labeled datasets Q and $\{P_i\}$ and visualize it in Figure 6 (first row). To investigate the generalization abilities of models trained on different datasets, we discretize the simplex Δ_2 to obtain 36 interpolation parameters a, and train a 5-layer LeNet classifier on each P_a. Then we fine-tune all of these classifiers on the few-shot test dataset Q with only 20 samples per each class. We control the same number of training iterations and fine-tuning iterations across all experiments. The second row of Figure 6 shows fine-tuning accuracy. Comparing the first row and the second, we find the accuracy and $\mathcal{W}^2(P_a, Q)$ are highly correlated. This implies that the model trained on the minimizer dataset of $\mathcal{W}^2(P_a, Q)$ tends to have a better generalization ability. We fix the same colorbar range for all heatmaps across datasets to highlight the impact of training dataset choice. A more concrete visualization of the correlation between $\mathcal{W}^2(P_a, Q)$ and accuracy is shown in Figure 11.

For some test datasets, the choice of training dataset strongly affects the fine-tuning accuracy. For example, when Q is EMNIST and the training dataset is FMNIST, the fine-tuning accuracy is only $\sim 60\%$, but this can be improved to $> 70\%$ by choosing an interpolated dataset closer to MNIST. This is reasonable because MNIST is more similar to EMNSIT than FMNIST or USPS. To some test datasets like FMNIST and KMNIST, this difference is not so obvious because all training datasets are all far away from the test dataset.

Comparison with baselines. Next, we compare our method with several baseline methods on NIST datasets. In each set of experiments, we select one *NIST dataset as the target domain, and use the rest for pre-training. We consider a 5-shot task, so we randomly choose 5 samples per class to be the labeled data, and treat the remaining samples as unlabeled. Our method first trains a model on $\hat{P}_a$, and fine-tunes the model on the 5-shot target data. To obtain $\hat{P}_a$, we use barycentric projection or neural map to approximate the OTDD maps from the test to training datasets. Our results are shown in the first two rows in Table 1.

The first baseline method is to create a synthetic dataset as training dataset by Mixup among datasets. We randomly sample data from each training datasets, and do the convex combination of them with weight $\hat{a}$. We use the same convex combination method in Sec. 4.2, thus this baseline is equivalent to our framework with suboptimal OTDD maps.

The other two baselines (the bottom block in Table 1) skip the transfer learning part, and directly train the model or solve 1-NN on the few-shot test dataset. Overall, transfer learning can bring additional knowledge from other domains and improve the test accuracy by at most 21%. Among the methods in the first block, training on datasets generated by OTDD barycentric projection outperforms others except USPS dataset, where the difference is only about 2.6%.

5.3   TRANSFER LEARNING ON VTAB DATASETS

Finally, we use our method for transfer learning with large-scale VTAB datasets [Zhai et al., 2019]. In particular, we take Oxford-IIIT Pet dataset as the target domain, and use Caltech101, DTD, and Flowers102 for pre-training. To encode a richer geometry in our interpolation, we embed the datasets using a masked auto encoder (MAE) [He et al., 2022] and learn the OTDD map in this ($\sim$200K dimensional) latent space. Since OTDD barycentric projection consistently works better than OTDD neural map (see Table 1), we only use barycentric projection in this section. We use ResNet-18 as the model architecture and pre-train the model on decoded MAE images (interpolated dataset) or original images (single dataset).

Table 2: **Transfer Learning on VTAB datasets**. The table shows relative improvement (w.r.t. a no-transfer baseline) of test accuracy on OXFORD-IIIT PET (mean $\pm$ std over 5 runs) given only 1000 samples of this dataset to fine-tune. The first three rows show single-pretraining-dataset baselines, and the remaining rows show methods that pretrain on a synthetic interpolation of these three, generated using Mixup or our proposed OTDD Map, using uniform or optimal (see Eq. (5)) dataset interpolation weights.

Pre-Training	Map	Weights	Rel. Improv. (%)
CALTECH101	–	–	59.68 ± 41.44
DTD	–	–	-1.17 ± 9.52
FLOWERS102	–	–	-2.45 ± 26.25
Interpolation	Mixup	uniform	33.26 ± 21.30
Interpolation	Mixup	optimal	51.99 ± 34.10
Interpolation	OTDD	uniform	82.61 ± 25.93
Interpolation	OTDD	optimal	$\mathbf{95.17 \pm 20.57}$

The pre-training interpolation dataset generated by our method has 'optimal' mixture weights $a = (0.43, 0.24, 0.33)$ for (CALTECH101, DTD, FLOWERS102), suggesting a stronger similarity between the first of these and the target domain (PETS). This is consistent with the single-dataset transfer accuracies shown in Table 2. However, their interpolation yields better transfer than any single dataset, particularly when using our full method (interpolating using OTDD map with optimal mixture weights).

6   CONCLUSION AND DISCUSSION

The method we introduce in this work provides, as shown by our experimental results, a promising new approach to generate synthetic datasets as combinations of existing ones. Crucially, our method allows one to combine datasets even if their label sets are different, and is grounded on principled and well-understood concepts from optimal transport theory. Two key applications of this approach that we envision are:

- **Pretraining data enrichment**. Given a collection of classification datasets, generate additional interpolated datasets to increase diversity, with the aim of achieving better out-of-distribution generalization. This could be done even without knowledge of the specific target domain (as we do here) by selecting various datasets to play the role of the 'reference' distribution.
- **On-demand optimized synthetic data generation**. Generate a synthetic dataset, by combining existing ones, that is 'optimized' for transferring a model to a new (data-limited) target domain.

Complexity   The complexity of solving OTDD barycentric projection by Sinkhorn algorithm is $\mathcal{O}(N^2)$ [Dvurechensky et al., 2018], where N is the number of data in both datasets. This can be expensive for large-scale dataset. In practice, we solve the batched barycentric projection, i.e. take a batch from both datasets and solve the projection from source to target batch, and we normally fix batch size B as 10^4. This reduces the complexity from $\mathcal{O}(N^2)$ to $\mathcal{O}(BN)$. The complexity of solving OTDD neural map is $\mathcal{O}(BKH)$, where K is number of iterations, and H is the size of the network. We always choose $K = \mathcal{O}(N)$ in the experiments. The complexity of solving all the $(2, Q)$-dataset distances in (5) is $\mathcal{O}(m^2 N)$ since we need to solve the dataset distance between each pair of training datasets. Putting these pieces together, the complexity of approximating the interpolation parameter $\hat{a}$ for the minimizer of (5) is $\mathcal{O}(N(B + m^2))$.

Barycentric projection vs Neural map   These two versions of our method offer complementary advantages. While estimating the OT map allows for easy out-of-sample mapping and continuous generation, the barycentric projection approach often yields better downstream performance (Table 1). We hypothesize this is due to the barycentric projection relying on (re-weighted) *real* data, while the neural map *generates* data which might be noisy or imperfect.

Limitations   Our method for generating a synthetic dataset relies on solving OTDD maps from the test dataset to each training dataset. These OTDD maps are tailored to the considered test dataset and can not be reused for a new test dataset. Another limitation is our framework is based on model training and fine-tuning pipeline. This can be resource-demanding for large-scale models, like GPT [Brown et al., 2020] or other similar models.

References

M. Agueh and G. Carlier. Barycenters in the wasserstein space. *SIAM Journal on Mathematical Analysis*, 43(2):904–924, 2011.

D. Alvarez-Melis and N. Fusi. Geometric dataset distances via optimal transport. *Advances in Neural Information Processing Systems*, 33:21428–21439, 2020.

D. Alvarez-Melis and N. Fusi. Dataset dynamics via gradient flows in probability space. In *International Conference on Machine Learning*, pages 219–230. PMLR, 2021.

L. Ambrosio, N. Gigli, and G. Savaré. *Gradient flows: in metric spaces and in the space of probability measures*. Springer Science & Business Media, 2008.

A. Asadulaev, A. Korotin, V. Egiazarian, and E. Burnaev. Neural optimal transport with general cost functionals. *arXiv preprint arXiv:2205.15403*, 2022.

C. Bowles, L. Chen, R. Guerrero, P. Bentley, R. Gunn, A. Hammers, D. A. Dickie, M. V. Hernández, J. Wardlaw, and D. Rueckert. GAN augmentation: Augmenting training data using generative adversarial networks, Oct. 2018.

Y. Brenier. Polar factorization and monotone rearrangement of vector-valued functions. *Communications on pure and applied mathematics*, 44(4):375–417, 1991.

T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. Henighan, R. Child, A. Ramesh, D. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei. Language models are Few-Shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc., 2020.

C. Bunne, A. Krause, and M. Cuturi. Supervised training of conditional monge maps. *arXiv preprint arXiv:2206.14262*, 2022a.

C. Bunne, L. Papaxanthos, A. Krause, and M. Cuturi. Proximal optimal transport modeling of population dynamics. In G. Camps-Valls, F. J. R. Ruiz, and I. Valera, editors, *Proceedings of The 25th International Conference on Artificial Intelligence and Statistics*, volume 151 of *Proceedings of Machine Learning Research*, pages 6511–6528. PMLR, 2022b.

C.-Y. Chuang and Y. Mroueh. Fair mixup: Fairness via interpolation. In *International Conference on Learning Representations*, 2021.

G. Cohen, S. Afshar, J. Tapson, and A. Van Schaik. Emnist: Extending mnist to handwritten letters. In *2017 international joint conference on neural networks (IJCNN)*, pages 2921–2926. IEEE, 2017.

K. Craig. The exponential formula for the wasserstein metric. *ESAIM: Control, Optimisation and Calculus of Variations*, 22(1):169–187, 2016.

P. Dvurechensky, A. Gasnikov, and A. Kroshnin. Computational optimal transport: Complexity by accelerated gradient descent is better than by sinkhorn's algorithm. In *International conference on machine learning*, pages 1367–1376. PMLR, 2018.

J. Fan, A. Taghvaei, and Y. Chen. Scalable computations of wasserstein barycenter via input convex neural networks. *arXiv preprint arXiv:2007.04462*, 2020.

J. Fan, S. Liu, S. Ma, H. Zhou, and Y. Chen. Neural monge map estimation and its applications. *arXiv preprint arXiv:2106.03812*, 2021.

J. Fan, Q. Zhang, A. Taghvaei, and Y. Chen. Variational Wasserstein gradient flow. In K. Chaudhuri, S. Jegelka, L. Song, C. Szepesvari, G. Niu, and S. Sabato, editors, *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 6185–6215. PMLR, 2022.

Y. Gao and P. Chaudhari. An Information-Geometric distance on the space of tasks. In *Proceedings of the 38th International Conference on Machine Learning*. PMLR, 2021.

K. He, X. Chen, S. Xie, Y. Li, P. Dollár, and R. Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16000–16009, 2022.

J. J. Hull. A database for handwritten text recognition research. *IEEE Transactions on pattern analysis and machine intelligence*, 16(5):550–554, 1994.

S. Jain, H. Salman, A. Khaddaj, E. Wong, S. M. Park, and A. Madry. A data-based perspective on transfer learning. *arXiv preprint arXiv:2207.05739*, 2022.

H. D. Kabir, M. Abdar, A. Khosravi, S. M. J. Jalali, A. F. Atiya, S. Nahavandi, and D. Srinivasan. Spinalnet: Deep neural network with gradual input. *IEEE Transactions on Artificial Intelligence*, 2022.

J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell. Overcoming catastrophic forgetting in neural networks. *PNAS*, 114(13):3521–3526, mar 2017.

A. Korotin, L. Li, J. Solomon, and E. Burnaev. Continuous wasserstein-2 barycenter estimation without minimax optimization. *arXiv preprint arXiv:2102.01752*, 2021.

A. Korotin, V. Egiazarian, L. Li, and E. Burnaev. Wasserstein iterative networks for barycenter estimation. *arXiv preprint arXiv:2201.12245*, 2022a.

A. Korotin, D. Selikhanovych, and E. Burnaev. Neural optimal transport. *arXiv preprint arXiv:2201.12220*, 2022b.

H. Liu, X. Gu, and D. Samaras. Wasserstein gan with quadratic transport cost. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 4832–4841, 2019.

A. Makkuva, A. Taghvaei, S. Oh, and J. Lee. Optimal transport mapping via input convex neural networks. In *International Conference on Machine Learning*, volume 37, 2020.

R. J. McCann. Existence and uniqueness of monotone measure-preserving maps. *Duke Mathematical Journal*, 80(2):309–323, 1995.

R. J. McCann. A convexity principle for interacting gases. *Advances in mathematics*, 128(1):153–179, 1997.

M. McCloskey and N. J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In G. H. Bower, editor, *Psychology of Learning and Motivation*, volume 24, pages 109–165. Academic Press, Jan. 1989. doi: 10.1016/S0079-7421(08)60536-8.

P. Mokrov, A. Korotin, L. Li, A. Genevay, J. M. Solomon, and E. Burnaev. Large-Scale wasserstein gradient flows. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. S. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 15243–15256. Curran Associates, Inc., 2021.

M. Perrot, N. Courty, R. Flamary, and A. Habrard. Mapping estimation for discrete optimal transport. *Advances in Neural Information Processing Systems*, 29, 2016.

A.-A. Pooladian and J. Niles-Weed. Entropic estimation of optimal transport maps. *arXiv preprint arXiv:2109.12004*, 2021.

O. Ronneberger, P. Fischer, and T. Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

L. Rout, A. Korotin, and E. Burnaev. Generative modeling with optimal transport maps. In *International Conference on Learning Representations*, 2022.

V. Sandfort, K. Yan, P. J. Pickhardt, and R. M. Summers. Data augmentation using generative adversarial networks (CycleGAN) to improve generalizability in CT segmentation tasks. *Sci. Rep.*, 9(1):16884, Nov. 2019. ISSN 2045-2322. doi: 10.1038/s41598-019-52737-x.

F. Santambrogio. Optimal transport for applied mathematicians. *Birkäuser, NY*, 55(58-63):94, 2015.

F. Santambrogio. {Euclidean, metric, and Wasserstein} gradient flows: an overview. *Bulletin of Mathematical Sciences*, 7(1):87–154, 2017.

R. Sinkhorn. Diagonal equivalence to matrices with prescribed row and column sums. *The American Mathematical Monthly*, 74(4):402–405, 1967.

S. Srivastava, C. Li, and D. B. Dunson. Scalable bayes via barycenter in wasserstein space. *The Journal of Machine Learning Research*, 19(1):312–346, 2018.

C. Villani. *Optimal transport, Old and New*, volume 338. Springer Science & Business Media, 2008. ISBN 9783540710493.

A. Yeaton, R. G. Krishnan, R. Mieloszyk, D. Alvarez-Melis, and G. Huynh. Hierarchical optimal transport for comparing histopathology datasets. *arXiv preprint arXiv:2204.08324*, 2022.

J. Yoon, J. Jordon, and M. van der Schaar. PATE-GAN: Generating synthetic data with differential privacy guarantees. In *International Conference on Learning Representations*, 2019.

X. Zhai, J. Puigcerver, A. Kolesnikov, P. Ruyssen, C. Riquelme, M. Lucic, J. Djolonga, A. S. Pinto, M. Neumann, A. Dosovitskiy, et al. A large-scale study of representation learning with the visual task adaptation benchmark. *arXiv preprint arXiv:1910.04867*, 2019.

H. Zhang, M. Cisse, Y. N. Dauphin, and D. Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

L. Zhang, Z. Deng, K. Kawaguchi, A. Ghorbani, and J. Zou. How does mixup help with robustness and generalization? In *International Conference on Learning Representations*, 2021.

J. Zhu, J. Qiu, A. Guha, Z. Yang, X. Nguyen, B. Li, and D. Zhao. Interpolation for robust learning: Data augmentation on geodesics. *arXiv preprint arXiv:2302.02092*, 2023.