ADAPTIVE HIERARCHICAL HYPER-GRADIENT DESCENT

ABSTRACT

In this study, we investigate learning rate adaption at different levels based on the framework of hyper-gradient descent, and further propose a method that adaptively learns the optimizer parameters by combining different levels of adaptations. Meanwhile, we show the relationship between regularizing over-parameterized learning rates and building combination of adaptive learning rates at different levels. The experiments on several network architectures, including feed-forward networks, LeNet-5 and ResNet-18/34 show that the proposed multi-level adaptive approach significantly outperforms baseline adaptive methods in a variety of circumstances.

1 INTRODUCTION

The basic optimization algorithm for training deep neural networks is gradient descent method (GD), including stochastic gradient descent (SGD), mini-batch gradient descent and batch gradient descent. Model parameters are updated according to the first-order gradients of the empirical risks with respect to the parameters being optimized, while back-propagation is implemented for calculating the gradients of parameters (Ruder, 2016). Naïve gradient descent methods apply fixed learning rates without any adaptation mechanisms. However, considering the change of available information during the learning process, SGD with fixed learning rates can result in inefficiency and requires a large amount of computing resources in hyper-parameter searching. One solution is to introduce learning rate adaptation. This idea can be traced back to the work of gain adaptation for connectionist learning methods (Sutton, 1992), and related extensions for non-linear cases (Schraudolph, 1999; Yu et al., 2006). In recent years, optimizers with adaptive updating rules were developed in the context of deep learning, while the learning rates are still fixed in training. The proposed methods include AdaGrad (Duchi et al., 2011), RMSProp (Tieleman and Hinton, 2012), and Adam (Kingma and Ba, 2015). Also, there are optimizers aiming at addressing the convergence issue in Adam (Reddi et al., 2018; Luo et al., 2018), or rectifying the variance of the adaptive learning rate (Liu et al., 2019). Other techniques such as *Lookahead* could also achieve variance reduction and stability improvement with negligible extra computational cost (Zhang et al., 2019).

Even though the adaptive optimizers with fixed learning rates can converge faster than SGD in a wide range of tasks, the updating rules are designed manually, while more hyper-parameters are introduced. Another idea is to use the information of objective function and to update the learning rates as trainable parameters. This set of methods was introduced as automatic differentiation, where the hyper-parameters can be optimized with backpropagation (Maclaurin et al., 2015; Baydin et al., 2018). As gradient-based hyper-parameter optimization methods, they can be implemented as an online approach (Franceschi et al., 2017). With the idea of auto-differentiation, learning rates can be updated in real time with the corresponding derivatives of the empirical risk (Almeida et al., 1998), which can be generated to all types of optimizers for deep neural networks (Baydin et al., 2017). Another step size adaptation approach, called "L4", is based on the linearized expansion of the loss function, which rescales the gradient in order to make fixed predicted progress on the loss (Rolinek and Martius, 2018). Further more, by addressing the issue of poor generalization performance of adaptive methods, dynamic bound for gradient methods was introduced to build a gradual transition between adaptive method and SGD (Luo et al., 2018).

Another set of approaches train an RNN (recurrent neural network) agent to generate the optimal learning rates in the next step given the historical training information, known as "learning to learn"

(Andrychowicz et al., 2016). It empirically outperforms hand-designed optimizers in a variety of learning tasks, but another study shows that it may not be effective for long horizon (Lv et al., 2017). The generalization ability can be improved by using meta training samples and hierarchical LSTMs (Long Short-Term Memory) (Wichrowska et al., 2017).

We notice that the existing gradient or model based learning rate adaptation methods including hyper-gradient descent, L4 and learning to learn only focus on global adaptation, which could be further extended to multi-level cases. The main contribution of our study can be summarized as follows:

- We introduce hierarchical learning rate structures for neural networks, and apply hyper-gradient descent to obtain adaptive learning rates at different levels.

- We introduce a set of regularization techniques for learning rates to address the balance of global and local adaptations, and show the relationship with weighted combinations.

- We propose an algorithm implementing the combination of adaptive learning rates at multiple levels for model parameter updating.

2 MULTI-LEVEL ADAPTATION METHODS

2.1 LAYER-WISE, UNIT-WISE AND PARAMETER-WISE ADAPTATION

In the paper of hyper-descent (Baydin et al., 2017), the learning rate is set to be a scalar. However, to make the most of learning rate adaptation, in this study we introduce layer-wise or even parameter-wise updating rules, where the learning rate $\boldsymbol{\alpha}_t$ in each iteration time step is considered to be a vector (layer-wise) or even a list of matrices (parameter-wise). For the sake of simplicity, we collect all the learning rates in a vector: $\boldsymbol{\alpha}_t = (\alpha_{1,t}, ..., \alpha_{N,t})^T$. Correspondingly, the objective $f(\boldsymbol{\theta})$ is a function of $\boldsymbol{\theta} = (\theta_1, \theta_2, ..., \theta_N)^T$, collecting all the model parameters. In this case, the derivative of the objective function f with respect to each learning rate can be written as:

$$\frac{\partial f(\boldsymbol{\theta}_{t-1})}{\partial \alpha_{i,t-1}} = \frac{\partial f(\theta_{1,t-1}, ..., \theta_{N,t-1})}{\partial \alpha_{i,t-1}} = \sum_{j=1}^{N} \frac{\partial f(\theta_{1,t-1}, ..., \theta_{N,t-1})}{\partial \theta_{j,t-1}} \frac{\partial \theta_{j,t-1}}{\partial \alpha_{i,t-1}}, \quad (1)$$

where N is the total number of all the model parameters. Eq. (1) can be generalized to group-wise updating, where we associate a learning rate with a special group of parameters, and each parameter group is updated according to its only learning rate. Notice that although there is a dependency between α_{t-1} and θ_{t-2} with: $\alpha_{t-1} = \alpha_{t-2} - \beta \nabla f(\theta_{t-2})$, where β is the updating rate of hyper-gradient descent, we consider that α_{t-1} is calculated after θ_{t-2} and thus a change of α_{t-1} will not result in a change of θ_{t-2}. Assume $\boldsymbol{\theta}_t = u(\boldsymbol{\Theta}_{t-1}, \alpha)$ is the updating rule, where $\boldsymbol{\Theta}_t = \{\boldsymbol{\theta}_s\}_{s=0}^{t}$ and α is the learning rate, then the basic gradient descent method for each group i gives $\boldsymbol{\theta}_{i,t} = u(\boldsymbol{\Theta}_{t-1}, \alpha_{i,t-1}) = \boldsymbol{\theta}_{i,t-1} - \alpha_{i,t-1} \nabla_{\boldsymbol{\theta}_i} f(\boldsymbol{\theta}_{t-1})$. Hence for gradient descent,

$$\frac{\partial f(\boldsymbol{\theta}_{t-1})}{\partial \alpha_{i,t-1}} = \nabla_{\boldsymbol{\theta}_i} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\alpha_{i,t-1}} u(\boldsymbol{\Theta}_{t-1}, \alpha_{i,t-1}) = -\nabla_{\boldsymbol{\theta}_i} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\boldsymbol{\theta}_i} f(\boldsymbol{\theta}_{t-2}). \quad (2)$$

Here $\alpha_{i,t-1}$ is a scalar with index i at time step $t-1$, corresponding to the learning rate of the ith group, while the shape of $\nabla_{\boldsymbol{\theta}_i} f(\boldsymbol{\theta})$ is the same as the shape of $\boldsymbol{\theta}_i$. We particularly consider two special cases: (1) In **layer-wise adaptation**, $\boldsymbol{\theta}_i$ is the weight matrix of ith layer, and α_i is the particular learning rate for this layer. (2) In **parameter-wise adaptation**, $\boldsymbol{\theta}_i$ corresponds to a certain parameter involved in the model, which can be an element of the weight matrix in a certain layer.

2.2 REGULARIZATION ON ADAPTIVE LEARNING RATES

The selection of adaptation level should depend on a case-by-case basis. Global or parameter-wise adaptation is usually not the optimal choice across all circumstances. Recall that for deep neural networks, we usually use a relatively large architecture with regularization. This idea can also be applied for learning rate space with parameter structure. To address the issue of over-parameterization in implementing lower-level learning rate adaptation, we introduce regularization on learning rates to

control the flexibility. First, for layer-wise adaptation, we can add the following regularization term to the loss function:

$$L_{\text{lr\_reg\_layer}} = \lambda_{\text{layer}} \sum_l (\alpha_l - \alpha_g)^2, \tag{3}$$

where l is the indices for each layer, λ_{layer} is the layer-wise regularization coefficient, α_l and α_g are the layer-wise and global-wise adaptive learning rates. A larger λ_{layer} can push the learning rate of each layer towards the global learning rate across all the layers. Given a particular $\alpha_{g,t}$, the gradient of the loss function with respect to the learning rate α_l in layer l can be written as:

$$\begin{aligned}
\frac{\partial L_{\text{full}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{l,t}} &= \frac{\partial L_{\text{model}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{l,t}} + \frac{\partial L_{\text{lr\_reg}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{l,t}} \\
&= \nabla_{\boldsymbol{\theta}_l} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\alpha_{l,t-1}} u(\boldsymbol{\Theta}_{t-2}, \alpha_{t-1}) + 2\lambda_{\text{layer}}(\alpha_{l,t} - \alpha_{g,t}).
\end{aligned} \tag{4}$$

Notice that the time step index of layer-wise regularization term is t rather than $t-1$, which ensures that we push the layer-wise learning rates towards the corresponding global learning rates of the current step t. Denoting by $h_{l,t-1} = -\nabla_{\boldsymbol{\theta}_l} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\theta_l} u(\boldsymbol{\Theta}_{t-2}, \alpha_{l,t-1})$, then the updating rule for learning rates can be written as:

$$\alpha_{l,t} = \alpha_{l,t-1} - \beta \frac{\partial L_{\text{full}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{l,t}} = \alpha_{l,t-1} - \beta(-h_{l,t-1} + 2\lambda_{\text{layer}}(\alpha_{l,t} - \alpha_{g,t})). \tag{5}$$

Eq. (5) has a close form solution but only applicable in two-level's case. However, there is an extra hyper-parameter λ_{layer} to be tuned. In addition, when there are more levels, components of learning rates in different levels can be interdependent on each other. To construct a workable updating scheme for Eq. (5), we replace $\alpha_{l,t}$ and $\alpha_{g,t}$ with their relevant approximations. We take the strategy of using their updated version without considering regularization, i.e., $\hat{\alpha}_{l,t} = \alpha_{l,t-1} + \beta h_{l,t-1}$ and $\hat{\alpha}_{g,t} = \alpha_{g,t-1} + \beta h_{g,t-1}$, where $h_{g,t-1} = -\nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\alpha_{g,t-1}} u(\boldsymbol{\Theta}_{t-2}, \alpha_{g,t-1})$ is the global h for all parameters. Here we regard $\hat{\alpha}_{l,t}$ and $\hat{\alpha}_{g,t}$ as the "virtual" layer-wise and global-wise learning rates for time step t and taking them into the right hand side of Eq. (5) gives the new updating rule as follows,

$$\alpha_{l,t}^* = \alpha_{l,t-1} + \beta h_{l,t-1} - 2\beta\lambda_{\text{layer}}(\hat{\alpha}_{l,t} - \hat{\alpha}_{g,t}) = (1 - 2\beta\lambda_{\text{layer}})\hat{\alpha}_{l,t} + 2\beta\lambda_{\text{layer}}\hat{\alpha}_{g,t}. \tag{6}$$

Notice that in Eq. (6), the two terms is actually a weighted average of the layer-wise learning rate $\hat{\alpha}_{l,t}$ and global learning rate $\hat{\alpha}_{g,t}$ at the current time step. Since we hope to push the layer-wise learning rates towards the global one, the parameters should meet the constraint: $0 < 2\beta\lambda_{\text{layer}} < 1$, and thus they can be optimized using hyper-parameter searching within a bounded interval as well as gradient-based hyper-parameter optimizations. We can also consider the case where three levels of learning rate adaptations are involved, including global-wise, layer-wise and parameter-wise adaptation. If we introduce two more regularization terms to control the variation of parameter-wise learning rate with respect to layer-wise learning rate and global learning rates, the regularization loss can be written as:

$$L_{\text{lr\_reg\_para}} = \lambda_{\text{layer}} \sum_l (\alpha_l - \alpha_g)^2 + \lambda_{\text{para\_layer}} \sum_l \sum_p (\alpha_{pl} - \alpha_l)^2 + \lambda_{\text{para}} \sum_l \sum_p (\alpha_{pl} - \alpha_g)^2,$$

where α_{pl} is the learning rate for the p-th parameter inside layer l. The second and third terms push each parameter-wise learning rate towards the layer-wise learning rate and the global learning rates, respectively. Similar to the two-level case, the updating rule with this three-level regularization can be approximated by the weighted combination of three components under "virtual approximation". The detail of updating rule for three-level's case is given by Algorithm 1 in Section 2.3. We also provided a discussion on the bias of implementing "virtual approximation" in Appendix A.1.

In general, we can organize all the learning rates in a tree structure. For example, in three level case above, α_g will be the root node, while $\{\alpha_l\}$ are the children node at level 1 of the tree and $\{\alpha_{lp}\}$ are the children node of α_l as leave nodes at level three of the tree. In a general case, we assume there are L levels in the tree. Denote the set of all the paths from the root node to each of leave nodes as $\mathcal{P}$ and a path is denoted by $p = \{\alpha_1, \alpha_2, ..., \alpha_L\}$ where α_1 is the root node and α_L is the leave node on the path. On this path, denote ancestors(i) all the ancestor nodes of α_i along the path, i.e.,

$\text{ancestors}(i) = \{\alpha_1, ..., \alpha_{i-1}\}$. We will construct a regularizer to push α_i towards each of its parents. Then the regularization can be written as

$$L_{\text{lr\_reg}} = \sum_{p \in \mathcal{P}} \sum_{\alpha_i \in p} \sum_{\alpha_j \in \text{ancestor}(i)} \lambda_{ij} (\alpha_i - \alpha_j)^2. \tag{7}$$

Under this pair-wise L_2 regularization, the updating rule for any leave node learning rate α_L can be given by the following theorem whose proof is given in Appendix A.2.

Theorem 1. *Under virtual approximation, the effect of applying pair-wise L_2 regularization Eq. (7) results in performing a weighted linear combination of virtual learning rates at different levels $\alpha_L^* = \sum_{j=1}^{L} \gamma_j \hat{\alpha}_j$ with $\sum_{j=1}^{L} \gamma_j = 1$, where each component $\hat{\alpha}_j$ is calculated by assuming no regularization.*

Remarks: Theorem 1 actually suggests that the similar updating rule can be obtained for the learning rate at any level on the path. All these have been demonstrated in Algorithm 1 for the three level case.

2.3 PROSPECTIVE OF ADAPTIVE LEARNING RATE COMBINATION

Motivated by the analytical derivation in Section 2.2, we can consider the combination of adaptive learning rates at different levels as a substitute and approximation of regularization on the differences of learning rates. This makes the effect of learning rate regularization trainable with gradient based methods. In a general form, assume that we have L levels, which could include global-level, layer-level, unit-level and parameter-level, etc, Theorem 1 suggests the following updating rule: $\alpha_t = \sum_{j=1}^{L} \gamma_j \hat{\alpha}_{j,t}$. In a more general form, we can implement non-linear models such as neural networks to model the final adaptive learning rates with respect to the learning rates at different levels: $\alpha_t = g(\hat{\alpha}_{1,t}, \hat{\alpha}_{2,t}...\hat{\alpha}_{L,t}; \theta)$, where θ is the vector of parameters of the non-linear model. We can treat the combination weights $\{\gamma_1, ..., \gamma_L\}$ as trainable parameters, which can also be globally shared or parameter/layer-specific. In this study, we consider the globally shared combination weights. To apply this method, we only need these different levels of learning rate have a hierarchical relationship. For example, for convolutional neural network, we can further introduce "filter level" to replace layer-level if their is no clear layer structure, where the parameters in each filter will share a same learning rate.

As the real learning rates implemented in model parameter updating is a weighted combination, the corresponding gradient matrices cannot be directly used for learning rate updating. In this case, we first break down the gradient by the combined learning rate to three levels, use each of them to updated the learning rate at each level, and then calculate the combination by the updated learning rates. Especially, $h_{p,t}$, $h_{l,t}$ and $h_{g,t}$ are calculated by the gradients of model losses without regularization, as is shown in Eq. (8)[1].

$$h_{p,t} = \frac{\partial f(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{p,t}} = -\nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}_{t-1}, \alpha)|_p \cdot \nabla_\alpha u(\boldsymbol{\Theta}_{t-2}, \alpha)|_p$$

$$h_{l,t} = \frac{\partial f(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{l,t}} = -\text{tr}(\nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}_{t-1}, \alpha)|_l^T \nabla_\alpha u(\boldsymbol{\Theta}_{t-2}, \alpha)|_l) \tag{8}$$

$$h_{g,t} = \frac{\partial f(\boldsymbol{\theta}, \alpha)}{\partial \alpha_t} = -\sum_{l=1}^{n} \text{tr}(\nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}_{t-1}, \alpha)|_l^T \nabla_\alpha u(\boldsymbol{\Theta}_{t-2}, \alpha)_l)$$

where $h_t = \sum_l h_{l,t} = \sum_p h_{p,t}$ and $h_{l,t} = \sum_{p \in l\text{th layer}} h_p$ and $f(\theta, \alpha)$ corresponds to the model loss $L_{model}(\theta, \alpha)$ in Section 2.2. Algorithm 1 is the full updating rules for the newly proposed optimizer with three levels, which can be denoted as combined adaptive multi-level hyper-gradient descent (CAM-HD). In Algorithm 1, we introduce the general form of gradient descent based optimizers (Reddi et al., 2018; Luo et al., 2018): for SGD, $\phi_t(g_1, ...g_t) = g_t$ and $\psi_t(g_1, ...g_t) = 1$, while for Adam, $\phi_t(g_1, ...g_t) = (1 - \beta_1)\Sigma_{i=1}^{t} \beta_1^{t-1} g_i$ and $\psi_t(g_1, ...g_t) = (1 - \beta_2)\text{diag}(\Sigma_{i=1}^{t} \beta_2^{t-1} g_i^2)$. Meanwhile, the corresponding $u(\boldsymbol{\Theta}_{t-2}, \alpha)$ should be changed accordingly. Notice that in each updating time step of Algorithm 1, we re-normalize the combination weights γ_1, γ_2 and γ_3 to make

---

[1]Here we use trace form to represent the sum of element-wise product but compute in the simplest way.

Algorithm 1: Updating rule of three-level CAM-HD

---

input: $\alpha_0, \beta, \delta, T$
initialization: $\theta_0, \gamma_{1,0}, \gamma_{2,0}, \gamma_{3,0}, \alpha_{p,0}, \alpha_{l,0}, \alpha_0, \alpha_{l,0}^* = \gamma_{1,0}\alpha_{p,0} + \gamma_{2,0}\alpha_{l,0} + \gamma_{3,0}\alpha_0$
for $t \in 1, 2, ..., T$ **do**

$\quad g_t = \nabla_\theta f(\theta, \alpha)$
$\quad$ **Update** $h_{p,t}, h_{l,t}$ **and** $h_{g,t}$ **by Eq. (8).**
$\quad \alpha_{p,t} = \alpha_{p,t-1} - \beta_p \frac{\partial f(\theta_{t-1})}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \alpha_{p,t-1}} = \alpha_{p,t-1} - \beta_p \gamma_{1,t-1}h_{p,t}$
$\quad \alpha_{l,t} = \alpha_{l,t-1} - \beta_l \sum_p \frac{\partial f(\theta_{t-1})}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \alpha_{l,t-1}} = \alpha_{l,t-1} - \beta_l \gamma_{2,t-1}\sum_p h_{p,t} = \alpha_{l,t-1} - \beta_l \gamma_{2,t-1}h_{l,t}$
$\quad \alpha_t = \alpha_{t-1} - \beta_g \sum_l \sum_p \frac{\partial f(\theta)}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \alpha_{t-1}} = \alpha_{t-1} - \beta_g \gamma_{3,t-1}h_{g,t}$
$\quad \alpha_{p,t}^* = \gamma_{1,t-1}\alpha_{p,t} + \gamma_{2,t-1}\alpha_{l,t} + \gamma_{3,t-1}\alpha_t$
$\quad \gamma_{1,t} = \gamma_{1,t-1} - \delta\frac{\partial L}{\partial \gamma_{1,t-1}} = \gamma_{1,t-1} - \delta\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \gamma_{1,t-1}} = \gamma_{1,t-1} - \delta\alpha_{p,t-1}\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}$
$\quad \gamma_{2,t} = \gamma_{2,t-1} - \delta\frac{\partial L}{\partial \gamma_{2,t-1}} = \gamma_{2,t-1} - \delta\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \gamma_{2,t-1}} = \gamma_{1,t-1} - \delta\alpha_{l,t-1}\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}$
$\quad \gamma_{3,t} = \gamma_{3,t-1} - \delta\frac{\partial L}{\partial \gamma_{3,t-1}} = \gamma_{3,t-1} - \delta\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}\frac{\partial \alpha_{p,t-1}^*}{\partial \gamma_{3,t-1}} = \gamma_{3,t-1} - \delta\alpha_{t-1}\sum_p \frac{\partial L}{\partial \alpha_{p,t-1}^*}$
$\quad \gamma_1 = \gamma_1/(\gamma_1 + \gamma_2 + \gamma_3), \gamma_2 = \gamma_1/(\gamma_1 + \gamma_2 + \gamma_3), \gamma_3 = \gamma_1/(\gamma_1 + \gamma_2 + \gamma_3)$
$\quad m_t = \phi_t(g_1, ...g_t)$
$\quad V_t = \psi_t(g_1, ...g_t)$
$\quad \theta_t = \theta_{t-1} - \alpha_{p,t}^* m_t/\sqrt{V_t}$

end
return $\theta_T, \gamma_{1,T}, \gamma_{2,T}, \gamma_{3,T}, \alpha_{p,T}, \alpha_{l,T}, \alpha_T$

---

sure that their summation is always 1 even after updating with stochastic gradient-based methods. An alternative way of doing this is to implement Softmax function. In addition, the training of γs can also be extended to multi-level cases, which means we can have different combination weights in different layers. For the updating rates β_p, β_l and β_g of the learning rates at different levels, we set: $\beta_p = n_p\beta = \beta$, $\beta_l = n_l\beta$, $\beta_g = n\beta$, where β is a shared parameter. This setting will make the updating steps of learning rates at different levels be in the same scale considering their difference in the number of parameters. An alternative way is to take average based on the number of parameters in Eq. (8) at first.

2.4 CONVERGENCE ANALYSIS

The proposed CMA-HD is not an independent optimization method, which can be applied in any kinds of gradient-based updating rules. Its convergence properties highly depend on the base optimizer that is applied. By referring the discussion on convergence in (Baydin et al., 2017), we introduce $\kappa_{p,t} = \tau(t)\alpha_{p,t}^* + (1 - \tau(t))\alpha_\infty$, where the function $\tau(t)$ is selected to satisfy $t\tau(t) \to 0$ as $t \to \infty$, and α_∞ is a selected constant value. Then we can demonstrate the convergence analysis for the three level case in the following theorem.

Theorem 2 (Convergence under mild assumptions about f). *Suppose that f is convex and L-Lipschitz smooth with $\|\nabla_p f(\theta)\| < M_p$, $\|\nabla_l f(\theta)\| < M_l$, $\|\nabla_g f(\theta)\| < M_g$ for some fixed M_p, M_l, M_g and all θ. Then $\theta_t \to \theta^*$ if $\alpha_\infty < 1/L$ where L is the Lipschitz constant for all the gradients and $t \cdot \tau(t) \to 0$ as $t \to \infty$, where the θ_t are generated according to (non-stochastic) gradient descent.*

In the above theorem, ∇_p is the the gradient of target function w.r.t. a model parameter with index p, ∇_l is the average gradient of target function w.r.t. a parameters in a layer with index l, and ∇_g is the global average gradient of target function w.r.t. all model parameters. The proof of this theorem is given in Appendix A.3. Notice that when we introduce $\kappa_{p,t}$ instead of $\alpha_{p,t}^*$ in Algorithm 1, the corresponding gradients $\frac{\partial L(\theta)}{\partial \alpha_{p,t-1}^*}$ will also be replaced by $\frac{\partial L(\theta)}{\partial \kappa_{p,t-1}^*}\frac{\partial \kappa_{p,t-1}^*}{\partial \alpha_{p,t-1}^*} = \frac{\partial L(\theta)}{\partial \kappa_{p,t-1}^*}\tau(t)$.

3 EXPERIMENTS

To compare with existing baseline optimizers, we use the models of feed-forward neural network, and different types of convolutions neural network on multiple benchmark datasets. The comparison will be based on the convergence speed and the validation performance. For each learning tasks, following optimizers will be applied: (a) Standard baseline optimizers such as Adam and SGD; (b) Hyper-gradient descent in (Baydin et al., 2017); (c) L4 stepsize adaptation for standard optimizers (Rolinek and Martius, 2018); (d) The Proposed adaptive combination of different levels of hyper-descent. The implementation of (b) is based on code provided with the original paper. For each experiment, we provide the average curve and standard error bar in each time step with 10 runs.

3.1 HYPER-PARAMETER TUNING

To compare the effect of CAM-HD with baseline optimizers, we first do hyper-parameter tunning for the model training process with baseline optimizers by referring related papers (Kingma and Ba, 2015; Baydin et al., 2017; Rolinek and Martius, 2018; Luo et al., 2018) as well as implementing independent grid search. We mainly consider the hyper-parameters of batch size, learning rate and momentum for models with different architecture. The search space for batch size is the set of $\{2^n\}_{n=3,...,9}$, while the search space for learning rate, hyper-gradient updating rate and combination weight updating rate (CAM-HD-lr) are $\{10^{-1}, ..., 10^{-4}\}$, $\{10^{-1}, ..., 10^{-10}\}$ and $\{10^{-1}, ..., 10^{-4}\}$ respectively. The selection criterion is the 5-fold cross-validation loss by early-stopping at patience of 3. The optimized hyper-parameters for the tasks in this paper is give by Table 1. For the learning tasks with recommended learning rate schedules, we will apply these schedules as well.

Table 1: Hyper-parameter Settings for Experiments

Architecture	Dataset	Batch size	lr (SGD/SGDN)	lr (Adam)	Hyper-grad lr (SGD/SGDN)	Hyper-grad lr (Adam)	CAM-HD-lr
MLP 1		32	-	0.0003	-	1.00E-09	0.01
MLP 2	MNIST	64	-	0.001	-	1.00E-09	0.01
MLP 3		128	-	0.001	-	1.00E-09	0.01
	MNIST	256	-	0.001	1.00E-03	1.00E-08	0.03
LeNet-5	CIFAR10	256	-	0.001	1.00E-03	1.00E-08	0.03
	SVHN	128	-	0.001	1.00E-03	1.00E-08	0.03
ResNet-18		256	0.1	0.001	1.00E-06	1.00E-08	0.001
ResNet-34	CIFAR10	256	0.1	0.001	1.00E-06	1.00E-08	0.001

3.2 COMBINATION RATIO AND MODEL PERFORMANCES

First we perform a study on the combination of different level learning rates. The simulations are based on image classification tasks on MNIST and CIFAR10 (LeCun et al., 1998; Krizhevsky and Hinton, 2012). One feed-forward neural network with three hidden layers of size [100, 100, 100] and two convolutional network models including LeNet-5 (LeCun et al., 2015) and ResNet-18 (He et al., 2016), are implemented. We use full training sets of MNIST and CIFAR10 for training and full test sets for validation. Two levels of learning rates are considered in each case, which are global and layer-wise adaptation for FFNN, global and filter-wise adaptation for CNNs. Adam optimizer is implemented in all the three simulations. We change the combination weights of two levels in each case to see the change of model performance in terms of classification accuracy at epoch 10, with the corresponding updating rate $\delta = 0$. Other hyper-parameter setting follows Table 1. For all the three simulations, we conduct 10 runs at each combination weights with different parameter initializations, and draw the error bars for standard errors. The result is given in Figure 1. We can see that in all of three cases, the optimal performance is neither at full global level nor full layer/filter level, but a combination of two levels of adaptive learning rates. Still, the differences between the end points and the optimal combination in terms of model performance are with some level of statistical significance. This supports our analysis in Section 2.2. Also, in real training processes, it is possible that the learning in favor of different combination weights in different stages, and this requires the online updating of the combination weights.

Figure 1: The diagram of a model performance under different combination ratios in the case of two-level learning rates adaptation.

Figure 2: The comparison of learning curves of FFNN on MNIST with different adaptive optimizers.

3.3 FFNN FOR IMAGE CLASSIFICATION

This experiment is done with feed-forward neural networks for image classification on MNIST, which includes 60,000 training examples and 10,000 test examples. We use the full training set for training and the full test set for validation. Three FFNN with three different hidden layer configurations are implemented, including [100, 100], [1000, 100], and [1000, 1000]. Adaptive optimizers including Adam, Adam-HD with two hyper-gradient updating rate, as well as proposed Adam-CAM-HD are applied. For Adam-CAM-HD, we apply three-level parameter-layer-global adaptation with initialization of $\gamma_1 = \gamma_2 = 0.3$ and $\gamma_3 = 0.4$, and two-level layer-global adaptation with $\gamma_1 = \gamma_2 = 0.5$. Figure 2 shows the validation accuracy for different optimizers during the training process of 30 epochs. We can learn that both the two-level and three-level Adam-CAM-HD outperform baseline Adam optimizer with optimized hyper-parameters significantly. For Adam-HD, we find that the default hyper-gradient updating rate (10^{-7}) for Adam applied in (Baydin et al., 2017) does not work well in our experiments, while an optimized one of 10^{-9} can outperform Adam but still worse than Adam-CAM-HD with default hyper-gradient updating rate (10^{-7}).

3.4 LENET-5 FOR IMAGE CLASSIFICATION

The second experiment is done with LeNet-5, which is an early-year convolutional neural network without involving many tricks in building and training. We compare a set of adaptive Adam optimizers including Adam, Adam-HD, Adam-CAM-HD and L4 for the image classification learning task of MNIST, CIFAR10 and SVHN (Netzer et al., 2011). For Adam-CAM-HD, we apply two-level setting with filter-wise and global learning rates adaptation, and initialize $\gamma_1 = 0.2$, $\gamma_2 = 0.8$. We also implement an exponential decay function $\tau(t) = \exp(-rt)$ as was discussed in Section 2.4 with rate $r = 0.002$, while t is the number of iterations. For L4, we implement the recommended L4 learning rate of 0.15. The other hyper-parameter settings are optimized in Table 1. As we can see in Figure 3, Adam-CAM-HD again shows the advantage over other methods in all the three sub-experiments, except that on MNIST L4 could perform better in later stage. Also, the experiment on SVHN indicates that the recommended learning rate for L4 could fail in some cases with unstable accuracy curves. On the other hand, Adam-HD can not significantly outperform Adam with recommended and optimized hyper-gradient updating rate that is shared with Adam-CAM-HD.

Figure 3: The comparison of learning curves of training LeNet-5 with different adaptive optimizers.

3.5 RESNET FOR IMAGE CLASSIFICATION

In the third experiment, we apply ResNet-18 and ResNet-34 for image classification task on CIFAR10. We compare Adam and its adaptive optimizers for training ResNet-18, and compare SGD with Nestorov momentum (SGDN) and corresponding adaptive optimizers for training ResNet-34. For SGDN methods, we apply a learning rate schedule, in which the learning rate is initialized to default value of 0.1, and reduced to 0.01 or 10% (for SGDN-CAM-HD) after epoch 150. The momentum is set to be 0.9 for all SGDN methods. For Adam-CAM-HD SGDN-CAM-HD, we apply two-level adaptation with the same setting as the second experiment. In addition, we apply an exponential decay function with a decay rate $r = 0.001$. The results of validation accuracy, training loss and validation loss are shown in Figure 4. We can see that the validation accuracy of Adam-CAM-HD reaches about

Figure 4: The learning curves of training ResNet on CIFAR10 with adaptive optimizers.

90% in 40 epochs and consistently outperforms other Adam-based adaptive optimizers in later stage. The recommended hyper-parameter for L4 in ResNet-34 seems not work well in ResNet-18 due to over-fitting and requires extra tuning, although its training loss outperforms other methods. Adam-HD achieves better training loss than Adam after epoch 100, but the validation performance is not as well with default hyper-gradient coefficient of 10^{-8} (shared with Adam-CAM-HD). In addition, we find that in training ResNet-34, the validation accuracy and validation loss of SGDN-CAM-HD outperform that of SGDN in most of epochs even after the resetting of learning rate at epoch 150.

4 CONCLUSION

In this study, we propose a gradient-based learning rate adaptation strategy by introducing hierarchical multiple-level learning rates in deep neural networks. By considering the relationship between regularization and the combination of adaptive learning rate at different levels, we further propose a joint algorithm for adaptively learning the combination weight of each level. Experiments on FFNN, LeNet-5 and ResNet-18/34 indicate that the proposed methods can outperform the standard ADAM/SGDN and other baseline methods. Although the advantage is not fully guaranteed, our methods achieves a higher level of adaptation and can be continuously reduced to baseline methods under specific setting of hyper-parameters. This could bring more thoughts and further study on implementing hierarchical learning rate system for deep neural networks.

REFERENCES

L. B. Almeida, T. Langlois, J. D. Amaral, and A. Plakhov. Parameter adaptation in stochastic optimization. *On-Line Learning in Neural Networks, Publications of the Newton Institute*, pages 111–134, 1998.

M. Andrychowicz, M. Denil, S. Gomez, M. W. Hoffman, D. Pfau, T. Schaul, B. Shillingford, and N. De Freitas. Learning to learn by gradient descent by gradient descent. In *NeurIPS*, pages 3981–3989, 2016.

A. G. Baydin, R. Cornish, D. M. Rubio, M. Schmidt, and F. Wood. Online learning rate adaptation with hypergradient descent. *ICLR*, 2017.

A. G. Baydin, B. A. Pearlmutter, A. A. Radul, and J. M. Siskind. Automatic differentiation in machine learning: a survey. *JMLR*, 18(153), 2018.

J. Duchi, E. Hazan, and Y. Singer. Adaptive subgradient methods for online learning and stochastic optimization. *JMLR*, 12:2121–2159, 2011.

L. Franceschi, M. Donini, P. Frasconi, and M. Pontil. Forward and reverse gradient-based hyperparameter optimization. In *ICML*, pages 1165–1173. JMLR. org, 2017.

K. He and J. Sun. Convolutional neural networks at constrained time cost. In *CVPR*, pages 5353–5360, 2015.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *CVPR*, pages 770–778, 2016.

H. Karimi, J. Nutini, and M. Schmidt. Linear convergence of gradient and proximal-gradient methods under the polyak-łojasiewicz condition. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 795–811. Springer, 2016.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *ICLR*, 2015.

A. Krizhevsky and G. Hinton. Learning multiple layers of features from tiny images. *University of Toronto*, 2012.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Y. LeCun et al. Lenet-5, convolutional neural networks. *URL: http://yann. lecun. com/exdb/lenet*, 20: 5, 2015.

L. Liu, H. Jiang, P. He, W. Chen, X. Liu, J. Gao, and J. Han. On the variance of the adaptive learning rate and beyond. In *ICLR*, 2019.

L. Luo, Y. Xiong, Y. Liu, and X. Sun. Adaptive gradient methods with dynamic bound of learning rate. In *ICLR*, 2018.

K. Lv, S. Jiang, and J. Li. Learning gradient descent: Better generalization and longer horizons. In *ICML*, pages 2247–2255. JMLR. org, 2017.

D. Maclaurin, D. Duvenaud, and R. Adams. Gradient-based hyperparameter optimization through reversible learning. In *ICML*, pages 2113–2122, 2015.

Y. Netzer, T. Wang, A. Coates, A. Bissacco, B. Wu, and A. Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL `http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf`.

S. J. Reddi, S. Kale, and S. Kumar. On the convergence of adam and beyond. In *ICLR*, 2018.

M. Rolinek and G. Martius. L4: Practical loss-based stepsize adaptation for deep learning. In *NeurIPS*, pages 6433–6443, 2018.

S. Ruder. An overview of gradient descent optimization algorithms. *arXiv:1609.04747*, 2016.

N. N. Schraudolph. Local gain adaptation in stochastic gradient descent. In *1999 Ninth International Conference on Artificial Neural Networks ICANN 99. (Conf. Publ. No. 470)*, volume 2, pages 569–574 vol.2, 1999.

R. Sun. Optimization for deep learning: theory and algorithms. *arXiv:1912.08957*, 2019.

R. S. Sutton. Gain adaptation beats least squares. In *Proceedings of the 7th Yale workshop on adaptive and learning systems*, volume 161168, 1992.

T. Tieleman and G. Hinton. Rmsprop: Divide the gradient by a running average of its recent magnitude. coursera: Neural networks for machine learning. *Tech. Rep., Technical report*, page 31, 2012.

O. Wichrowska, N. Maheswaranathan, M. W. Hoffman, S. G. Colmenarejo, M. Denil, N. de Freitas, and J. Sohl-Dickstein. Learned optimizers that scale and generalize. In *ICML*, pages 3751–3760. JMLR. org, 2017.

J. Yu, D. Aberdeen, and N. N. Schraudolph. Fast online policy gradient learning with smd gain vector adaptation. In *NeurIPS*, pages 1185–1192, 2006.

M. Zhang, J. Lucas, J. Ba, and G. E. Hinton. Lookahead optimizer: k steps forward, 1 step back. In *NeurIPS*, pages 9593–9604, 2019.

A Appendix for Paper: Adaptive Multi-level Hyper-gradient Descent

A.1 Analysis about Virtual Approximation

Consider the difference between Eq. (5) and Eq. (6) in the paper:

$$\alpha_{l,t}^* - \alpha_{l,t} = -2\beta\lambda_{\text{layer}}((\hat{\alpha}_{l,t} - \hat{\alpha}_{g,t}) - (\alpha_{l,t} - \alpha_{g,t})). \tag{9}$$

Based on the setting of multi-level adaptation, on the right-hand side of Eq. (9), global learning rate is updated without regularization $\hat{\alpha}_{g,t} = \alpha_{g,t}$. For the layer-wise learning rates, the difference is given by $\hat{\alpha}_{l,t} - \alpha_{l,t} = 2\beta\lambda_{\text{layer}}(\alpha_{l,t} - \alpha_{g,t})$, which corresponds to the gradient with respect to the regularization term. Thus, Eq. (9) can be rewritten as:

$$\alpha_{l,t}^* - \alpha_{l,t} = -2\beta\lambda_{\text{layer}}(2\beta\lambda_{\text{layer}}(\alpha_{l,t} - \alpha_{g,t})) = -4\beta^2\lambda_l^2(1 - \frac{\alpha_{g,t}}{\alpha_{l,t}})\alpha_{l,t} \tag{10}$$

which is the error of the virtual approximation introduced in Eq. (6) in the paper. If $4\beta^2\lambda_l^2 << 1$ or $\frac{\alpha_{g,t}}{\alpha_{l,t}} \to 1$, this approximation becomes accurate. Another way for handling Eq. (4) in the paper is to implement the previous-step learning rates in the regularization term.

$$\alpha_{l,t} \approx \alpha_{l,t-1} - \beta(-h_{l,t-1} + 2\lambda_{\text{layer}}(\alpha_{l,t-1} - \alpha_{g,t-1})). \tag{11}$$

Since we have $\alpha_{l,t} = \hat{\alpha}_{l,t} - 2\beta\lambda_{\text{layer}}(\alpha_{l,t} - \alpha_{g,t})$ and $\hat{\alpha}_{l,t} = \alpha_{l,t-1} + \beta h_{l,t-1}$, using the learning rates in the last step for regularization will introduce a higher variation from term $\beta h_{l,t-1}$, with respect to the true learning rates in the current step. Thus, we consider the proposed virtual approximation works better than last-step approximation.

A.2 Proof of Theorem 1:

Proof. Consider the learning regularizer

$$L_{\text{lr\_reg}}(\alpha) = \sum_{p\in\mathcal{P}} \sum_{\alpha_i\in p} \sum_{\alpha_j\in\text{parents}(i)} \lambda_{ij}(\alpha_i - \alpha_j)^2. \tag{12}$$

To apply hyper-gradient descent method to update the learning rate α_L at level L, we need to work out the derivative of $L_{\text{lr\_reg}}$ with respect to α_L. The terms in Eq. (12) involving α_L are only $(\alpha_i - \alpha_j)^2$ where α_j is an ancestor on the path from the root to the leave node α_L. Hence

$$\frac{\partial L_{\text{full}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{L,t}} = \frac{\partial L_{\text{model}}(\boldsymbol{\theta}, \alpha)}{\partial \alpha_{L,t}} + \frac{\partial L_{\text{lr\_reg}}(\alpha)}{\partial \alpha_{L,t}}$$

$$= -\nabla_{\boldsymbol{\theta}_L} f(\boldsymbol{\theta}_{t-1})^T \nabla_{\boldsymbol{\theta}_L} u(\Theta_{t-2}, \alpha_{t-1}) + \sum_{\alpha_j\in\text{acenstors}(L)} 2\lambda_{Lj}(\alpha_{L,t} - \alpha_{j,t}). \tag{13}$$

As there are exactly $L - 1$ ancestors on the path, we can simply use the index $j = 1, 2, ..., L - 1$. The corresponding updating function for $\alpha_{n,t}$ is:

$$\alpha_{L,t} = \alpha_{n,t-1} - \beta(h_L + \sum_{j=1}^{L-1} 2\lambda_{Lj}(\alpha_{L,t} - \alpha_{j,t}))$$

$$\approx \hat{\alpha}_{L,t}(1 - 2\beta\sum_{j=1}^{L-1}\lambda_{Lj}\alpha_{n,t}) + \sum_{j=1}^{L-1}(2\beta\lambda_{Lj}\hat{\alpha}_{j,t})) \tag{14}$$

$$= \sum_{j=1}^{L} \gamma_j\hat{\alpha}_{j,t}.$$

where

$$\gamma_L = 1 - 2\beta\sum_{j=1}^{L-1}\lambda_{Lj}, \tag{15}$$

$$\gamma_j = 2\beta\lambda_{Lj}, \quad \text{for } j = 1, 2, ..., L - 1.$$

This form satisfies $\alpha_L^* = \sum_{j=1}^{L} \gamma_j\hat{\alpha}_j$ with $\sum_{j=1}^{L} \gamma_j = 1$. This completes the proof. $\square$

A.3 PROOF OF THEOREM 2:

Proof. We take three-level's case discussed in Section 2 for example, which includes global level, layer-level and parameter-level. Suppose that the target function f is convex, L-Lipschitz smooth at all levels, which means for all θ_1 and θ_2:

$$
\begin{aligned}
||\nabla_p f(\theta_1) - \nabla_p f(\theta_2)|| &\leq L_p ||\theta_1 - \theta_2|| \\
||\nabla_l f(\theta_1) - \nabla_l f(\theta_2)|| &\leq L_l ||\theta_1 - \theta_2|| \\
||\nabla_g f(\theta_1) - \nabla_g f(\theta_2)|| &\leq L_g ||\theta_1 - \theta_2|| \\
L &= \max\{L_p, L_l, L_g\}
\end{aligned}
\tag{16}
$$

and its gradient with respect to parameter-wise, layer-wise, global-wise parameter groups satisfy $||\nabla_p f(\theta)|| < M_p$, $||\nabla_l f(\theta)|| < M_l$, $||\nabla_g f(\theta)|| < M_g$ for some fixed M_p, M_l, M_g and all θ. Then the effective combined learning rate for each parameter satisfies:

$$
\begin{aligned}
|\alpha_{p,t}^*| = |\gamma_{p,t-1}\alpha_{p,t} &+ \gamma_{l,t-1}\alpha_{l,t} + \gamma_{g,t-1}\alpha_t| \\
&\leq (\gamma_{p,t-1} + \gamma_{l,t-1} + \gamma_{g,t-1})\alpha_0 + \beta \sum_{i=0}^{t-1} \left(\gamma_{p,t-1}n_p \max_p\{|\nabla f(\theta_{p,i+1})^T \nabla f(\theta_{p,i})|\} \right. \\
&\left. + \gamma_{l,t-1}n_l \max_l\{|\nabla f(\theta_{l,i+1})^T \nabla f(\theta_{l,i})|\} + \gamma_{g,t-1}|\nabla f(\theta_{g,i+1})^T \nabla f(\theta_{g,i})| \right) \\
&\leq \alpha_0 + \beta \sum_{i=0}^{t-1} \left(\gamma_{p,t-1}n_p \max_p\{||\nabla f(\theta_{p,i+1})||||\nabla f(\theta_{p,i})||\} \right. \\
&\left. + \gamma_{l,t-1}n_l \max_l\{||\nabla f(\theta_{l,i+1})||||\nabla f(\theta_{l,i})||\} + \gamma_{g,t-1}||\nabla f(\theta_{g,i+1})||||\nabla f(\theta_{g,i})|| \right) \\
&\leq \alpha_0 + t\beta(n_p M_p^2 + n_l M_l^2 + M_g^2)
\end{aligned}
\tag{17}
$$

where $\theta_{p,i}$ refers to the value of parameter indexed by p at time step i, $\theta_{l,i}$ refers to the set/vector of parameters in layer with index l at time step i, and $\theta_{g,i}$ refers to the whole set of model parameters at time step i. In addition, n_p and n_l are the total number of parameters and number of the layers, and we have applied $0 < \gamma_p, \gamma_l, \gamma_g < 1$. This gives an upper bound for the learning rate in each particular time step, which is $O(t)$ as $t \to \infty$. By introducing $\kappa_{p,t} = \tau(t)\alpha_{p,t}^* + (1 - \tau(t))\alpha_\infty$, where the function $\tau(t)$ is selected to satisfy $t\tau(t) \to 0$ as $t \to \infty$, so we have $\kappa_{p,t} \to \alpha_\infty$ as $t \to \infty$. If $\alpha_\infty < \frac{1}{L}$, for larger enough t, we have $1/(L+1) < \kappa_{p,t} < 1/L$, and the algorithm converges when the corresponding gradient-based optimizer converges for such a learning rate under our assumptions about f. This follows the discussion in (Karimi et al., 2016; Sun, 2019). □

A.4 ALGORITHM COMPLEXITY

A.4.1 NUMBER OF PARAMETERS AND SPACE COMPLEXITY

The proposed adaptive optimizer is for efficiently updating the model parameters, while the final model parameters will not be increase by introducing CMA-HD optimizer. However, during the training process, several extra intermediate variables are introduced. For example, in the discussed three-level's case for feed-forward neural network with n_{layer} layers, we need to restore $h_{p,t}$, $h_{l,t}$ and $h_{g,t}$, which have the sizes of $S(h_{p,t}) = \sum_{l=1}^{n_{\text{layer}}-1}(n_l + 1)n_{l+1}$, $S(h_{l,t}) = n_{\text{layer}}$ and $S(h_{g,t}) = 1$, respectively, where n_i is the number of units in ith layer. Also, learning rates $\alpha_{p,t}$, $\alpha_{l,t}$, $\alpha_{g,t}$ and take the sizes of $S(a_{p,t}) = \sum_{l=1}^{n_{\text{layer}}-1}(n_l + 1)n_{l+1}$, $S(a_{l,t}) = n_{\text{layer}}$, $S(a_{g,t}) = 1$, $S(a_{g,t}) = 1$, and $S(a_{p,t}^*) = \sum_{l=1}^{n_{\text{layer}}-1}(n_l + 1)n_{l+1}$, respectively. Also we need a small set of scalar parameters to restore γ_1, γ_2 and γ_3 and other coefficients.

Consider the fact that in training the baseline models, we need to restore model parameters, corresponding gradients, as well as the intermediate gradients during the implementation of chain rule, CAM-HD will take twice of the space for storing intermediate variables in the worst case. For two-level learning rate adaptation considering global and layer-wise learning rates, the extra space complexity by CAM-HD will be one to two orders' smaller than that of baseline model during training.

A.4.2   TIME COMPLEXITY

In CMA-HD, we need to calculate gradient of loss with respect to the learning rates at each level, which are $h_{p,t}$, $h_{l,t}$ and $h_{g,t}$ in three-level's case. However, the gradient of each parameter is already known during normal model training, the extra computational cost comes from taking summations and updating the lowest-level learning rates. In general, this cost is in linear relation with the number of differentiable parameters in the original models. Here we discuss the case of feed-forward networks and convolutional networks.

Recall that for feed-forward neural network the whole computational complexity is:

$$T(n) = O(m \cdot n_{\text{iter}} \cdot \sum_{l=2}^{n_{\text{layer}}} n_l \cdot n_{l-1} \cdot n_{l-2}) \tag{18}$$

where m is the number of training examples, n_{iter} is the iterations of training, and n_l is the number of units in the l-th layer. On the other hand, when using three-level CAM-HD with, where the lowest level is parameter-wise, we need n_{layer} element products to calculate $h_{p,t}$ for all layers, one n_{layer} matrix element summations to calculate $h_{l,t}$ for all layers, as well as a list summation to calculate $h_{g,t}$. In addition, two element-wise summations will also be implemented for calculating $\alpha_{p,t}$ and α_p^*. Therefore, the extra computational cost of using CAM-HD is $\Delta T(n) = O(m_b \cdot n_{\text{iter}} \sum_{l=2}^{n_{\text{layer}}} (n_l \cdot n_{l-1} + n_l))$, where m_b is the number of mini-batches for training. Notice that m/m_b is the batch size, which is usually larger than 100. This extra cost is more than one-order smaller than the computational complexity of training a model without learning rate adaptation. For the cases when the lowest level is layer-wise, only one element-wise matrix product is needed in each layer to calculate $h_{l,t}$. For convolutional neural networks, we have learned that the total time complexity of all convolutional layers is (He and Sun, 2015):

$$O(m \cdot n_{\text{iter}} \cdot \sum_{l=1}^{n_{conv\_layer}} (n_{l-1} \cdot s_l^2 \cdot n_l \cdot m_l^2)) \tag{19}$$

where l is the index of a convolutional layer, and n_{conv_layer} is the depth (number of convolutional layers). n_l is the number of filters in the l-th layer, while n_{l-1} is known as the number of input channels of the l-th layer. s_l is the spatial size of the filter. m_l is the spatial size of the output feature map. If we consider convolutional filters as layers, the extra computational cost for CAM-HD in this case is $\Delta T(n) = O(m_b \cdot n_{\text{iter}} \sum_{l=1}^{n_{conv\_layer}} ((n_{l-1} \cdot s_l^2 + 1) \cdot n_l))$, which is still more than one order smaller than the cost of model without learning rate adaptation.

Therefore, for large networks, applying CMA-HD will not significantly increase the computational cost from the theoretical prospective.

A.5 SUPPLEMENTARY EXPERIMENTAL RESULTS

A.5.1 LEARNING OF COMBINATION WEIGHTS

The following figures give the learning curves of combination weights with respect to the number of training iterations in each experiments. Each curve is averaged by 5 trials with error bars. Figure 5

Figure 5: Learning curves of γs for FFNN on MNIST with Adam.

Figure 6: Learning curves of γs for LeNet-5 on MNIST with SGD, SGDN and Adam.

Figure 7: Learning curves of γs for LeNet-5 on CIFAR10 and SVHN.

corresponds to the experiment of FFNN on MNIST in Section 3.3, which is a three-level case. We can see that for different FFNN architecture, the learning behaviors of γs are also different. On the other hand, Figure 6 and Figure 7 correspond to the learning curves of γs in the experiments of LeNet-5 for MNIST image classification with SGD, SGDN and Adam, which are trained on 10% of original training dataset. As is shown in these two figures, for SGD-CAM-HD and SGDN-CAM-HD, the equilibrium value of combination weights are different from that of Adam-CAM-HD. For LeNet-5 image classification tasks, although the initialization $\gamma_1 = 0.2$, $\gamma_2 = 0.8$, and the updating rate $\delta = 0.03$ are the same, the values of γ_1 and γ_2 only change in a small proportion when training with Adam-CAM-HD, but the change is much more significant towards larger filter/layer wise adaptation when SGD-CAM-HD or SGDN-CAM-HD are implemented. The similar effect can also be observed from the learning curves of γs for ResNet-18, which is given in Figure 9 and we only take the first 8,000 iterations. This indicates that Adam may require high proportion of global-level adaptation, or

Figure 8: Learning curves of γs for ResNet-18.

require smaller level of combination ratio adaptation, for the same network architecture compared with SGD/SGDN. Notice that although we run each setting for 5 trials, the learning curves of γs do not have a large standard error, which suggests they are not quite sensitive to the initialization of model parameters.

A.5.2 OTHER EXPERIMENTAL RESULTS

In Figure 2, Figure 3 and Figure 4 of the paper, we have shown the curves of validation accuracies to compare different adaptive optimizers in a variety of learning tasks. Here we further provide the training and validation cross-entropy loss curves for corresponding methods in these tasks. Figure 9 is the full results of FFNNs, and Figure 10 is the results of LeNet-5.

Figure 9: The comparison of learning curves of FFNN on MNIST with different adaptive optimizers.

Figure 10: The comparison of learning curves of training LeNet-5 on MNIST, CIFAR10 and SVHN with different adaptive optimizers.