Exploiting Local Dynamics Regularity for Reusable Skills in Offline Hierarchical RL

Sarthak Dayal, Abhinav Peri, Carl Qi, Claas Voelcker, Alexander Levine, Caleb Chuck, Amy Zhang

Keywords: Reinforcement Learning, Representation Learning, Temporal Abstraction

Summary

Hierarchical Reinforcement Learning (HRL) promises to solve long-horizon Reinforcement Learning (RL) tasks more efficiently than non-hierarchical counterparts by discovering and reusing temporally-extended skills. However, obtaining skills that are actually reusable remains an open challenge. Towards this end, we focus on abstractions that exploit the intuition of local dynamics: local transitions in different global contexts require similar kinds of action sequences. By aligning these contexts with the action sequences they require, we are able to learn which skills to reuse and where to reuse them. In principle, this information should benefit many HRL algorithms, where high-level policies have to reason about the low-level skills they use. The resulting algorithm CARL (**C**ontrastive **A**ction-based **R**epresentations for Reusable **L**ocal Control) shows both qualitative clustering of meaningful skills in complex humanoid environments and improved downstream performance on the OGBench benchmark when integrated with HIQL. We visualize additional results and video rollouts on our accompanying website.[a]

---

[a] https://sites.google.com/view/behavior-rep/home

Contribution(s)

1. We propose CARL, a contrastive representation learning method that aligns state–goal pairs with the action sequences that achieve them in order to learn abstractions for reusable local control in hierarchical reinforcement learning.
   Context: CARL is motivated by local dynamics and skill reuse, and we study this approach empirically in the offline RL setting.

2. We integrate CARL with HIQL and show improved downstream performance on long-horizon OGBench tasks relative to the corresponding HIQL baseline.
   Context: Our evaluation focuses on OGBench tasks and the HIQL integration, providing evidence for the benefits of CARL in this setting.

3. We provide qualitative evidence that CARL's learned representation clusters meaningful short-horizon behaviors, including skills in complex humanoid environments.
   Context: These visualizations complement the quantitative results by illustrating the structure of the learned representation and the behaviors it captures.

Exploiting Local Dynamics Regularity for Reusable Skills in Offline Hierarchical RL

Sarthak Dayal[1][†]**, Abhinav Peri**[1][†]**, Carl Qi**[1]**, Claas Voelcker**[1]**, Alexander Levine**[1]**, Caleb Chuck**[1]**, Amy Zhang**[1]
sarthak@utexas.edu, app2452@utexas.edu

[1]**Department of Computing Science, University of Texas at Austin, United States**

[†] Equal contribution.

Abstract

Hierarchical Reinforcement Learning (HRL) promises to solve long-horizon Reinforcement Learning (RL) tasks more efficiently than non-hierarchical counterparts by discovering and reusing temporally-extended skills. However, obtaining skills that are actually reusable remains an open challenge. Towards this end, we focus on abstractions that exploit the intuition of local dynamics: local transitions in different global contexts require similar kinds of action sequences. By aligning these contexts with the action sequences they require, we are able to learn which skills to reuse and where to reuse them. In principle, this information should benefit many HRL algorithms, where high-level policies have to reason about the low-level skills they use. The resulting algorithm CARL (**C**ontrastive **A**ction-based **R**epresentations for Reusable **L**ocal Control) shows both qualitative clustering of meaningful skills in complex humanoid environments and improved downstream performance on the OGBench benchmark when integrated with HIQL. We visualize additional results and video rollouts on our accompanying website.[1]

1 Introduction

Hierarchical Reinforcement Learning (HRL) methods offer a framework (Sutton et al., 1999) for abstracting low-level policies or action sequences—commonly referred to as *skills*—so that they can be reused to accomplish complex tasks. However, this promise of reusable skills has often been outweighed by the limitations of existing approaches (Zhang et al., 2020), which include training instability when co-learning skills with the policies that use those skills (Levy et al., 2019; Wang et al., 2025), and failure to leverage reusability. One promising direction involves representing low-level skills as goal-conditioned policies (Park et al., 2023; Hafner et al., 2022; Eysenbach et al., 2019), which decouples low- and high-level policy training. However, representing skills via a goal-conditioned low-level policy loses many of the desirable properties of skills, such as temporal abstraction and consistent reusability. In this work, we formalize the idea of local dynamics—the idea that many local regions of the state space share similar dynamics—to enable reuse of low-level goal-conditioned skills across the state space.

To formalize the idea of local dynamics we define local, finite-horizon MDPs for each state to capture its surrounding states and their dynamics. We then draw on bisimulation as a principled way to define state equivalences based on these MDPs. To derive a practical algorithm from this principle, we leverage the idea of *behavioral similarity*: two state-goal pairs (s_1, g_1) and (s_2, g_2) are considered similar when a policy can use the same skill $(a_1, a_2, a_3, \ldots, a_k)$ to achieve the transition from s_1 to

---

[1]https://sites.google.com/view/behavior-rep/home

Figure 1: Learning state–goal representations for skill reuse. Humanoid poses left-to-right in each pane reflect progress in time. CARL learns a representation $\phi(s, g)$ that clusters state–goal pairs if they admit the same kinds of k-step action sequences. CARL clusters "walking backward" and "standing up" behaviors for humanoids situated in globally different parts of the maze.

g_1 and from s_2 to g_2. Our hypothesis is that behavioral similarity will naturally emerge when many states share local dynamics structure, making it a useful heuristic for understanding when skills can be reused. Our method is built upon these insights and leverages a contrastive learning objective to align state-goal pairs with the action sequences that achieve them.

We introduce CARL (**C**ontrastive **A**ction-based **R**epresentations for Reusable **L**ocal Control) to learn representations of local dynamics from offline datasets at a fixed skill horizon. By recognizing the underlying local dynamics structure, CARL identifies where skills can be reused instead of forcing HRL methods to relearn low-level policies from scratch. We demonstrate this by integrating these abstractions into existing HRL algorithms, HIQL and HGCBC (Park et al., 2023) which yields clear performance benefits on the OGBench benchmark. Furthermore, our objective shapes the latent geometry so that state–goal pairs requiring similar local skills are embedded nearby, even when they occur in different regions of the environment. Figure 1 illustrates this in a humanoid maze environment, where CARL groups skills together regardless of where they occur in the maze.

As noted, CARL relies on an offline dataset and fixed horizon to capture local dynamics, which may constrain expressible skills when data coverage is poor or the horizon fails to capture useful structure. We include ablations analyzing the effects of coverage, imbalance, and horizon length. Overall, our work shows that local dynamics structure provides a principled basis for skill extraction and reuse, helping HRL reconnect with the temporal abstractions central to long-horizon decision-making.

2 Related Work

2.1 Hierarchical Reinforcement Learning

Hierarchical Reinforcement Learning studies how to solve long-horizon Reinforcement Learning (RL) tasks by introducing *temporal abstraction*, which refers to high-level decisions that invoke temporally extended behaviors. One of the first formulations of this idea is the options framework, which models a skill as a policy with an initiation set and termination condition, enabling re-use of temporally extended actions within an SMDP view of control (Sutton et al., 1999). Early HRL work explored a variety of hierarchical decompositions and skill abstractions, including feudal-style manager–worker architectures (Dayan & Hinton, 1992), value-function decomposition methods such as MAXQ (Dietterich, 2000), and policy-constraining formalisms such as hierarchies of abstract machines (HAMs) (Parr & Russell, 1997).

A core challenge in learning hierarchies *end-to-end* is non-stationarity. As the low-level policy changes, the effective dynamics faced by the high-level policy shift, often destabilizing joint optimization. Many modern approaches therefore decouple the training of the hierarchy, by using subgoals (goals in state space) to train a local goal-conditioned policy while learning a high-level policy that proposes useful targets (Nachum et al., 2018; Levy et al., 2019). Recent offline and

model-based hierarchical methods further improve this paradigm by extracting effective policies from offline data or learned dynamics models (Hafner et al., 2022; Park et al., 2023). Although this paradigm substantially improves the training stability of HRL methods, reasoning directly in the global state–goal space makes it difficult for the low-level policy to recognize when the same behavior can be reused. To overcome this limitation, we focus on learning representations of state–goal pairs that highlight the short-horizon action structure and thus enable appropriate reuse of behaviors.

2.2 Abstractions via Behavioral Equivalences and Invariances

In this section, we discuss methods that seek to generalize by learning behavior-preserving abstractions, where distinct states (or state-goal contexts) are mapped to similar representations when they are interchangeable (Agarwal et al., 2021; Hansen-Estruch et al., 2022; Islam et al., 2023; Ajay et al., 2021; Park et al., 2025b). A common theme is to define an equivalence relation that preserves global decision-relevant structure: for example via value-, policy-, or model-based notions of similarity—and then learn representations that collapse equivalent situations while discarding irrelevant variation. This perspective is closely related to bisimulation-based ideas, which characterize when two states can be treated as equivalent without materially changing long-horizon outcomes (Zhang et al., 2021; Rudolph et al., 2024; Hansen-Estruch et al., 2022; Castro, 2020).

Our work fits into this line of research, but fundamentally targets a complementary notion of equivalence grounded in *local reuse*. Rather than requiring states to match in long-horizon value or reward structure, we ask when different state-goal pairs admit similar local goal-reaching behaviors, which allows us to cluster exactly the state-goal pairs which are the same from the perspective of short-horizon control, regardless of the long-horizon effects.

2.3 Contrastive Representations for Control

Contrastive Representation Learning provides a general mechanism for extracting structure in embeddings that score positive pairs higher than selected negative pairs, typically trained via objectives such as InfoNCE or NCE (van den Oord et al., 2018; Radford et al., 2021). In RL, contrastive methods have been applied to learn task relevant structure and enable downstream generalization (Eysenbach et al., 2022; Agarwal et al., 2021; Laskin et al., 2020). Particularly, Contrastive RL (Eysenbach et al., 2022) connects contrastive objectives to goal-conditioned RL by learning representations in which reaching a goal corresponds to matching future states under a learned similarity metric. Our method is inspired by this viewpoint, but captures a different structure: instead of learning representations that reflect goal reachability, we capture when similar action sequences are admitted by the state-goal transitions that the low-level policy aims to achieve. This greatly changes the contrastive structure compared to previous approaches that instead reason about the long-horizon effects of actions.

3 Problem Setup and Local Dynamics

3.1 Offline Goal-Conditioned RL

In this work, we investigate behavioral equivalences in the context of offline goal-conditioned RL (OGCRL), which is defined by the Markov decision process $\mathcal{M} := (\mathcal{S}, \mathcal{A}, p, r, \gamma)$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $p : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ is the transition function, and $\Delta(\mathcal{S})$ is a distribution over states, $r : \mathcal{S} \times \mathcal{G} \to \mathbb{R}$ is a reward function, and $\gamma \in (0,1)$ is a discount factor. We consider the case where $\mathcal{G} \subseteq \mathcal{S}$. The objective is to learn a goal conditioned policy $\pi : \mathcal{S} \times \mathcal{G} \to \Delta(A)$ such that for time horizon H, the expected reward is maximized: $\max_\pi J(\pi) = \max_\pi \mathbb{E}_{g \sim \rho(g), \tau \sim \rho^\pi(\tau)}[\sum_{t=0}^{H} \gamma^t r(s_t, g)]$, where $\rho(g)$ is the goal distribution. We define trajectory $\tau = (s_0, a_0, s_1, a_1, \dots, s_H)$ to be a sequence of states and actions with a fixed horizon H. Trajectories are sampled according to $\rho^\pi(\tau) = \mu(s_0)\Pi_{t=0}^{H-1}\pi(a_t \mid s_t, g)p(s_{t+1}|s_t, a_t)$, where μ is the initial distribution over states. We write $p(s_{t+k} \mid s_t, \mathbf{a_k}) = \sum_{s_1, \dots, s_{k-1} \in \mathcal{S}} \prod_{i=0}^{k-1} p(s_{i+1} \mid s_i, a_i)$,

to mean the k-step transition function, where $\mathbf{a_k}$ denotes a k-step action sequence starting at state s, and a_i denote individual actions in that sequence.

3.2 Local Dynamics

Here we formalize our intuition of local dynamics as a state equivalence relation. Specifically, we use the transition dynamics within a fixed horizon k in order to characterize a state's local dynamics.

Definition 3.1 (k-ball)**.** For any $k \in \mathbb{N}$ and $s \in \mathcal{S}$, the k-ball of s, denoted $\mathcal{B}_k(s)$, is the set of states reachable from s within k steps. Formally, $s' \in \mathcal{B}_k(s)$ if there exist $t \in \{0, 1, \ldots, k\}$ and an action sequence $\mathbf{a_t}$ such that $p(s' \mid s, \mathbf{a_t}) > 0$.

Definition 3.2 (k-ball MDP)**.** The k-ball MDP rooted at s is the finite-horizon MDP

$$\mathcal{M}_s^{(k)} = \big(\mathcal{B}_k(s), \ \mathcal{A}, \ p, \ r, \ k\big),$$

whose transition dynamics p, action space $\mathcal{A}$, and reward r are inherited from $\mathcal{M}$.

We now use the k-ball MDP to formalize a notion of state similarity grounded in local dynamics. Prior works adapting bisimulation to RL (Ferns et al., 2004; Zhang et al., 2021; Rudolph et al., 2024) measure similarity between MDPs through the sequences of rewards or single-step controllability metrics under identical action sequences. Our formalism instead considers dynamics directly, capturing whether two MDPs are interchangeable for goal reaching behavior.

Definition 3.3 (Dynamics Bisimilarity)**.** Let $\mathcal{M}_1 = (\mathcal{S}_1, \mathcal{A}, p_1, r_1)$ and $\mathcal{M}_2 = (\mathcal{S}_2, \mathcal{A}, p_2, r_2)$ be two MDPs sharing an action space $\mathcal{A}$. We say that $\mathcal{M}_1$ and $\mathcal{M}_2$ are *dynamics-bisimilar* if there exists a total relation $B \subseteq \mathcal{S}_1 \times \mathcal{S}_2$ such that every $(x, x') \in B$ for all $a \in \mathcal{A}$ satisfies

$$\forall\, y \in \mathcal{S}_1, \ \exists\, y' \in \mathcal{S}_2 \text{ (and vice versa)}: \quad p_1(y \mid x, a) = p_2(y' \mid x', a),$$
$$\forall\, C \in \mathcal{S}_1/B: \quad \bar{p_1}(C \mid x, a) = \bar{p_2}(B^{-1}(C) \mid x', a).$$

where $\mathcal{S}_1/B$ is the partition of $\mathcal{S}_1$ induced by B (the set of equivalence classes C of B-related states in $\mathcal{S}_1$), $B^{-1}(C) = \{y' \in \mathcal{S}_2 : \exists\, y \in C, \ (y, y') \in B\}$ is the corresponding subset of $\mathcal{S}_2$, and $\bar{p}(C \mid s, a) = \sum_{s' \in C} p(s' \mid s, a)$ extends p to subsets.

We say that two states s and s' share local dynamics if their corresponding k-ball MDPs, $\mathcal{M}_s^{(k)}$ and $\mathcal{M}_{s'}^{(k)}$, are *dynamics-bisimilar*. This definition gives us a formal way to reason about local dynamics. If two local MDPs are dynamics-bisimilar, then the same actions lead to corresponding next-state distributions and therefore similar local behavior. In practice, we use the reverse direction as a heuristic: when two state-goal pairs are achieved by similar action sequences, local dynamics are likely similar. This gives us a practical way to find where skills can be reused across the state space.

4 Method

4.1 Learning Representation for Skill Reuse

Although our state equivalence relates local dynamics, directly estimating this quantity in a practical algorithm for skill-reuse is challenging because it would require constructing the k-ball MDP around each state and comparing their transition structure under all relevant actions. In continuous, high-dimensional domains, the k-ball MDP is especially hard to obtain and enumerate for comparison. In the offline setting, this problem is compounded by the fact that we only observe a finite set of trajectories, which may sparsely cover the relevant local transitions. As a result, we seek an approximation that preserves the key ideas from our formalism while remaining simple to implement.

Our core insight is that offline datasets with near-expert behavior can reveal local dynamics structure without requiring us to directly model dynamics-bisimulation relations as described in Definition 3.3. Intuitively, when two states have dynamics-bisimilar k-ball MDPs, the same k-step action sequence

Algorithm 1: CARL

1. **Input:** Offline dataset $\mathcal{D}$, horizon k, temperature τ;
2. **Initialize:** Encoders $\phi(s, g)$ and $\psi(\mathbf{a_k})$;
3. **Initialize:** Goal-conditioned learner $\pi(\cdot \mid \phi(s, g))$;
4. **while** *not converged* **do**
5.   Sample batch $b \sim \mathcal{D}$ of k-step segments $(s_t, \mathbf{a_k}, s_{t+k})$;
6.   Train encoders: $\mathcal{L}_{\text{InfoNCE}}(b; \phi, \psi)$;   // Eq. (1)
7.   Train policy: $\mathbb{E}_b[J(\pi \mid \phi)]$;

Algorithm 2: HIQL + CARL (changes in blue)

1. **Input:** dataset $\mathcal{D}$, horizon k, temperature τ;
2. **Initialize:** value $V_{\theta_V}(s, \phi(s, g))$, policies $\pi^h_{\theta_h}(\cdot \mid s, g)$, $\pi^\ell_{\theta_\ell}(\cdot \mid s, \phi(s, s'))$;
3. **Initialize:** encoders $\phi_{\theta_\phi}(s, s')$, $\psi_{\theta_\psi}(a_\tau)$;
4. **while** *not converged* **do**
5.   Sample minibatch $(s_t, a_{t:t+k-1}, s_{t+k}, g) \sim \mathcal{D}$, indices $j \sim \text{Unif}[k]$;
6.   Train encoders:
7. $\mathcal{L}_{\text{InfoNCE}}(\{s^i_t, s^i_{t+j}, a^i_{t:t+k-1}\}_i; \phi_{\theta_\phi}, \psi_{\theta_\psi})$;
8.   Update value: $V_{\theta_V}(s_t, \phi_{\theta_\phi}(s_t, g))$;
9. $z^\star_t \leftarrow \phi_{\theta_\phi}(s_t, s_{t+k})$;   // embed subgoal
10.   Train high-level: fit $\pi^h_{\theta_h}(z^\star_t \mid s_t, g)$ (AWR);
11.   Train low-level: fit $\pi^\ell_{\theta_\ell}(a_t \mid s_t, z^\star_t)$ (AWR);

accomplishes equivalent transitions from both. A near-expert data-collecting policy will exploit this, leaving repeated action-sequence structure as a footprint in the dataset. We call this footprint *behavioral similarity*: two state-goal pairs (s_1, g_1) and (s_2, g_2) are behaviorally similar if they are solved by similar k-step action sequences in the dataset. This yields a much simpler heuristic that lets us identify skill-reuse opportunities directly from the dataset.

This motivates our method CARL (**C**ontrastive **A**ction-based **R**epresentations for Reusable **L**ocal Control) which learns to relate skills with the global contexts in which they are used. To do this, we sample batches of size B from a diverse offline dataset to learn representations $\phi(s, g_k)$ and $\psi(\mathbf{a_k})$ contrastively such that the loss below is minimized.

$$\mathcal{L}_{\text{InfoNCE}}\big(\{(s^i, g^i_k, \mathbf{a_k}^i)\}_{i=1}^B; \phi, \psi\big) = -\frac{1}{B}\sum_{i=1}^B \log \frac{\exp\big(\langle\phi(s^i, g^i_k), \psi(\mathbf{a_k}^i)\rangle/\tau\big)}{\sum_{j=1}^B \exp\big(\langle\phi(s^i, g^i_k), \psi(\mathbf{a_k}^j)\rangle/\tau\big)}. \tag{1}$$

Algorithm 1 summarizes the training procedure, which alternates between training the encoders via contrastive loss and training a goal-conditioned policy in the learned representation space.

4.2 Integration with Hierarchical Offline RL

Aligning state-goal pairs with action sequences that achieve the transition between them induces a behaviorally structured representation: state–goal pairs that can be solved by similar k-step action sequences are embedded nearby, regardless of where they occur in the state space. This representation structure is well suited as an input to the low-level policy in subgoal-based HRL algorithms, where a policy can reuse the same skill in different contexts rather than relearning it separately in each region.

Following this intuition, we integrate CARL into HIQL (Park et al., 2023), a recent and competitive hierarchical offline RL algorithm, by co-training its subgoal representation with CARL's objective. This introduces CARL's skill reuse benefits into the input space of the low-level policy and value function, and the output space of the high-level policy. These changes are highlighted in blue in Algorithm 2. We provide further details on the specific sampling and training procedures that we used in Appendix A, specific hyperparameter changes we made in Appendix B, and present experiments analyzing these design choices in Appendix C.

We also modify the HGCBC (**H**ierarchical **G**oal-**C**onditioned **B**ehavior **C**loning) algorithm that is used as a baseline in Park et al. (2023) to assess the generality of CARL's benefits to HRL algorithms in an identical manner to our modification of HIQL by using CARL as a low-level policy input.

5 Experiments

Our experiments analyze both the embedding structure produced by CARL and its effect on downstream performance when integrated into an existing HRL method. The following sections seek to address the questions below.

Q1. Does CARL's representation structure enable skills to be reused?

Q2. How does CARL benefit HRL methods in downstream tasks?

Q3. What are the important components for capturing behavioral similarity?

Q4. How does CARL organize different skills in its representation structure?

5.1 Skill Reuse in Toy Environments

(Q1) Skill Reuse. To test how CARL enables skill reuse, we design a toy environment consisting of five identical grid-world rooms (Figure 2). These rooms differ only in their global (x, y) coordinates, which form the proprioceptive state for the agent.

We test zero-shot generalization in two settings. First, a goal-conditioned policy trained in a single room must solve the same task in held-out rooms. We compare HIQL to HIQL augmented with a CARL encoder trained on all rooms. Since CARL aliases state-goal pairs reachable by the same action sequences, the policy should transfer through the shared representation. Our experiments confirm this: HIQL+CARL solves all held-out rooms, while HIQL fails to generalize. Second, we scale to 20 identical grid-world rooms, training on 4 and testing on the remaining 16. Both the CARL encoder and the hierarchical policy are trained using data from only four rooms. Performance in the remaining rooms therefore requires extrapolation to unseen absolute state coordinates, rather than reuse of representations previously trained in those rooms.

HIQL+CARL generalizes to 12 unseen rooms versus 8 for HIQL alone, further demonstrating that explicitly modeling skill reusability improves transfer. We note that while CARL does not achieve perfect extrapolation, failing on four held-out rooms, it provides a substantial improvement in extrapolation over the HIQL baseline, likely because the data allows CARL to find consistent patterns that are useful for policy transfer across rooms. We hypothesize that residual estimation error in the learned representation prevents perfect generalization.

5.2 Evaluating Performance Benefits for HRL

(Q2) HRL Integration. Here, we examine how CARL benefits HRL by benchmarking on OGBench tasks. We analyze results for HIQL+CARL and HGCBC+CARL, as described in Section 4.2.

5 Rooms Diagnostic Gridworld

OGBench Environments

Figure 2: Examples of environments used to benchmark CARL, including a diagnostic grid world as well as environments from the OGBench suite.

5.2.1 Experimental setup

We evaluate on two task categories from OGBench. The first is the locomotion suite, where various embodiments (point-mass, ant, humanoid) have to navigate throughout a maze. These tasks test learning high-level planning and low-level locomotion skills from offline data. We use the navigate datasets for these tasks, collected with a noisy expert policy that wanders the maze by achieving randomly sampled goals. This strategy yields broad coverage with repeating low-level structure, providing opportunities for skill reuse and leveraging CARL's core capability.

The second category is the manipulation suite, where a 6-DoF UR5e arm performs tasks like stacking cubes, arranging tabletop scenes, or solving puzzles, testing object manipulation and combinatorial generalization. We test on the play datasets, collected by open loop planners with temporally correlated noise. These planners rely on repeated behavior primitives, which we expect CARL to take advantage of.

These environments feature continuous control and span a range of complexity, from the low-dimensional point maze to the high-dimensional humanoid, allowing us to assess how CARL scales with state and action space complexity. The robotics domains introduce additional challenges through multi-entity interactions. Together, these environments test CARL across a diverse range of control difficulties. We defer to the OGBench paper for additional environment and dataset specifications (Park et al., 2025a).

5.2.2 OGBench State-Based Performance

We examine the effect of CARL on HRL algorithms in Table 2a by comparing HIQL and HGCBC with their augmented variants in downstream OGBench performance. Notably, HIQL+CARL improves HIQL by at least 10% on giant maze variants, 17% on smaller cube environments, 28% on smaller puzzle environments, and an impressive 30% on the scene task. HGCBC+CARL tends to outperform HGCBC around 10% for most navigation environments. This provides strong evidence that CARL's representation benefits HRL in downstream tasks.

Task	HIQL+CARL	HIQL
visual-antmaze-medium	**97.3 ± 2.7**	93 ± 6.4
visual-antmaze-large	**85.5 ± 5.6**	53 ± 14.3
visual-antmaze-giant	**43.0 ± 6.2**	6 ± 6.4
visual-antmaze-teleport	**45.3 ± 2.7**	37 ± 3.2
visual-humanoidmaze-medium	**2.3 ± 2.4**	0 ± 0.0
visual-humanoidmaze-large	**0.0 ± 0.0**	0 ± 0.0
visual-humanoidmaze-giant	**0.0 ± 0.0**	**0 ± 0.0**
visual-cube-single	87.8 ± 8.1	**89 ± 0.0**
visual-cube-double	**41.8 ± 9.4**	39 ± 3.2
visual-cube-triple	**24.8 ± 2.7**	21 ± 0.0
visual-cube-quadruple	**14.8 ± 4.5**	14 ± 1.6
visual-puzzle-3x3	**75.5 ± 4.6**	73 ± 12.7
visual-puzzle-4x4	**83.5 ± 7.0**	60 ± 65.2
visual-puzzle-4x5	**18.0 ± 3.7**	13 ± 14.3
visual-puzzle-4x6	**15.8 ± 8.0**	9 ± 9.5
visual-scene	**54.3 ± 2.1**	49 ± 6.4
win-rate	**13/14**	1/14

Table 1: HIQL+CARL vs HIQL on visual environments. Mean success rates (%) ± 95% CI over 4 seeds. Values within 95% of the best per row are **bolded**; for win-rates, ties are excluded and the highest is **bolded**.

CARL's gains are more limited on antmaze-teleport, antsoccer-medium, and the harder cube and puzzle tasks. The underlying causes remain unclear, but we hypothesize that these environments pose distinct challenges: stochastic dynamics (portals in antmaze-teleport), long horizons with entity-centric generalization (antsoccer-medium, cube), and combinatorial generalization over large configuration spaces (puzzle). Addressing these will likely require advances in the representation structure, such as representations that are invariant to entity permutations or that explicitly support compositional reasoning at the level of the high-level policy.

In robotics domains, CARL improves HIQL substantially more than it improves HGCBC. We attribute this to the difference in how each algorithm extracts its low-level policy: HIQL uses AWR, which selectively reweights toward high-advantage actions while HGCBC relies on unweighted behavioral cloning. Combining our method (to discover where a skill can be reused) with AWR (to discover which skills are optimal) allows us to reuse skills that are more likely to achieve the global task, and thus results in better task performance. While it remains unclear why robotics tasks in particular benefit disproportionately, the pattern suggests a complementary relationship between extracting high-quality skills and knowing where to use them.

Task	(a) HRL Comparisons				(b) CARL Ablations			
	HIQL+CARL	HIQL	HGCBC+CARL	HGCBC	CARL	Single-Action CARL	Multi-Action IDM	Single-Action IDM
pointmaze-medium	**84.4 ± 3.1**	79 ± 4.3	**13.6 ± 1.8**	0.0 ± 0.0	**84.4 ± 3.1**	**86.6 ± 3.8**	67.6 ± 4.0	74.1 ± 5.4
pointmaze-large	**75.4 ± 3.1**	58 ± 4.3	**19.5 ± 3.8**	0.4 ± 0.3	**75.4 ± 3.1**	**74.7 ± 8.0**	58.1 ± 9.5	62.6 ± 7.1
pointmaze-giant	**64.5 ± 15.8**	46 ± 7.6	**0.0 ± 0.0**	**0.0 ± 0.0**	**64.5 ± 15.8**	53.6 ± 13.2	22.7 ± 7.3	18.2 ± 9.2
pointmaze-teleport	**31.4 ± 14.0**	18 ± 3.3	**29.7 ± 1.8**	16.7 ± 1.2	**31.4 ± 14.0**	25.0 ± 8.0	18.0 ± 4.7	19.4 ± 6.4
antmaze-medium	**97.9 ± 0.9**	96 ± 0.9	**73.1 ± 1.5**	59.8 ± 1.6	**97.9 ± 0.9**	95.5 ± 2.4	**96.9 ± 1.7**	**96.1 ± 1.2**
antmaze-large	**91.9 ± 2.4**	91 ± 1.7	**64.9 ± 0.9**	59.3 ± 1.9	**91.9 ± 2.4**	86.4 ± 6.1	**91.5 ± 3.5**	**91.5 ± 1.2**
antmaze-giant	**75.2 ± 3.8**	65 ± 4.3	**18.4 ± 1.3**	8.5 ± 0.8	**75.2 ± 3.8**	47.1 ± 7.3	70.0 ± 4.3	**72.3 ± 3.5**
antmaze-teleport	41.4 ± 2.1	**42 ± 2.6**	**38.5 ± 1.3**	36.9 ± 1.9	41.4 ± 2.1	42.5 ± 4.5	46.6 ± 2.4	**47.0 ± 4.5**
humanoidmaze-medium	**90.5 ± 2.4**	89 ± 1.7	**44.4 ± 1.3**	32.4 ± 0.9	**90.5 ± 2.4**	88.9 ± 4.5	86.5 ± 3.1	**87.1 ± 2.8**
humanoidmaze-large	**58.3 ± 3.8**	49 ± 3.3	**31.0 ± 0.8**	22.6 ± 0.8	**58.3 ± 3.8**	51.1 ± 3.3	45.9 ± 3.3	50.0 ± 4.0
humanoidmaze-giant	**27.2 ± 3.1**	12 ± 3.3	**20.0 ± 1.1**	9.5 ± 1.3	**27.2 ± 3.1**	18.1 ± 3.8	17.0 ± 5.2	16.3 ± 3.1
antsoccer-medium	12.8 ± 2.4	**13 ± 1.7**	**7.0 ± 0.4**	5.9 ± 0.7	**12.8 ± 2.4**	5.6 ± 1.7	10.9 ± 2.8	12.1 ± 2.6
antsoccer-arena	**63.7 ± 3.1**	58 ± 1.7	**24.9 ± 1.6**	12.5 ± 0.8	**63.7 ± 3.1**	56.0 ± 7.3	56.9 ± 4.0	**63.0 ± 5.2**
cube-single	**32.8 ± 3.1**	15 ± 2.6	**6.9 ± 0.7**	4.4 ± 0.8	**32.8 ± 3.1**	30.5 ± 6.9	25.9 ± 4.3	22.4 ± 3.5
cube-double	**23.4 ± 4.5**	6 ± 1.7	**1.3 ± 0.3**	1.1 ± 0.3	**23.4 ± 4.5**	18.9 ± 4.0	5.4 ± 2.6	5.4 ± 1.2
cube-triple	**15.2 ± 3.5**	3 ± 0.9	**2.1 ± 0.6**	0.4 ± 0.3	**15.2 ± 3.5**	**24.4 ± 4.0**	6.4 ± 2.1	9.0 ± 4.0
cube-quadruple	**0.1 ± 0.2**	0 ± 0.0	**0.1 ± 0.1**	0.0 ± 0.0	0.1 ± 0.2	**1.8 ± 1.7**	0.4 ± 0.7	0.3 ± 0.5
puzzle-3x3	**45.5 ± 7.3**	12 ± 1.7	**6.0 ± 0.9**	4.1 ± 0.3	**45.5 ± 7.3**	15.0 ± 4.3	27.1 ± 5.2	28.1 ± 3.8
puzzle-4x4	**35.2 ± 7.1**	7 ± 1.7	**5.9 ± 0.9**	0.3 ± 0.2	**35.2 ± 7.1**	22.5 ± 4.0	14.2 ± 3.1	13.7 ± 2.4
puzzle-4x5	**4.2 ± 2.4**	4 ± 0.9	**1.6 ± 0.6**	0.4 ± 0.2	4.2 ± 2.4	**5.0 ± 1.4**	3.0 ± 1.9	3.1 ± 0.9
puzzle-4x6	**3.6 ± 2.1**	3 ± 0.9	**0.6 ± 0.3**	0.3 ± 0.2	3.6 ± 2.1	**3.9 ± 1.7**	2.4 ± 1.4	2.3 ± 1.7
scene	**70.5 ± 5.2**	38 ± 2.6	**15.8 ± 1.0**	8.5 ± 1.1	**70.5 ± 5.2**	69.8 ± 6.4	55.7 ± 5.7	64.3 ± 3.1
win-rate	**20/22**	2/22	**21/21**	0/21	**16/22**	5/22	0/22	1/22

Table 2: Success rates (%) on state-based OGBench tasks, reported as mean ± 95% CI over 8 seeds. **(a) HRL Comparison** contrasts HIQL and HGCBC with their CARL-augmented variants, where we **bold** values within 95% of the better method in each pair. **(b) CARL Ablations** compares variants of CARL combined with HIQL, where we **bold** values within 95% of the best ablation. The final row reports per-algorithm win-rates excluding ties, with the highest **bolded**.

5.2.3 OGBench Pixel-Based Performance

Visual observations represent a higher-dimensional and more relevant setting for real-world control, making them an important test for CARL's applicability beyond compact state representations. Thus, we benchmark our HIQL+CARL variant on OGBench's visual suite without further hyperparameter tuning, and present results in Table 1. We find significant gains on longer horizon antmaze tasks (over 30% in large and giant). Robotics domains also see at least a 5% improvement in scene and larger puzzle tasks, with gains of over 20% on puzzle-4x4. However, CARL does not always improve performance. Visual humanoid control is still too difficult even with CARL's representation, and cube tasks also benefit less than other robotics domains.

5.3 Ablating CARL's Design for Capturing Behavioral Similarity

(Q3) Component Ablation. In this section, we analyze how different parts of our representation learning approach affect its ability to capture behavioral similarity. Our full method optimizes $\mathcal{L}_{\text{InfoNCE}}$ (Eq. 1) with the action sequence $\mathbf{a_k}$ as the contrastive target. The three ablations modify this along one of two axes. *Single-Action CARL* replaces $\mathbf{a_k}$ with the first action $a_{k,1}$, keeping the contrastive objective. *Multi-Action Prediction* keeps $\mathbf{a_k}$ but replaces the contrastive loss with direct regression, $\|\xi\big(\phi(s, g_k)\big) - \mathbf{a_k}\|_2^2$, where ξ is a network head which takes in representations of state-goal pairs produced by ϕ. *Single-Action Prediction* applies both changes.

To compare these ablations, we use UMAP (McInnes et al., 2018) to visualize how well each method organizes their latent structure by behavioral similarity. More concretely, we construct state-goal pairs corresponding to motion in cardinal directions for the pointmaze environment from OGBench. We use pointmaze, because the simple dynamics make it easy to reason about the ideal clustering structure: pairs should cluster by the direction of motion they induce.

Figure 3 provides qualitative evidence that only CARL's combination of action-sequence modeling and a contrastive objective produces tight, disjoint clusters suitable for downstream skill reuse. The ablations yield scattered, overlapping clusters, with the exception of Multi-Action Prediction, whose

Figure 3: UMAP visualization of learned embeddings colored by behavioral mode. When embeddings are trained using CARL, state-goal pairs that require similar action sequences cluster tightly, even when the raw states differ substantially. Other ablations show more overlap and looser clusters.

clusters are looser but still disjoint enough to capture skill reuse meaningfully. This suggests that modeling action sequences is important for capturing behavioral similarity and supporting skill reuse.

We also evaluate downstream performance on state-based OGBench environments in Table 2b to contextualize these differences in representation geometry. CARL generally outperforms the other variants, emphasizing the importance of both action-sequence modeling and a contrastive objective. Single-Action CARL comes closest in performance, while the prediction methods perform comparably to each other. This suggests that the contrastive objective is an effective way to translate behavioral similarity into useful downstream representations.

5.4   Visualizing CARL's Representation Structure

(Q4) Skill Structure. We've already observed how CARL's geometry tightly clusters state-goal pairs by behavioral similarity. In this section, we examine whether this result extends to higher-dimensional and less structured settings by studying our representations in the humanoid maze environment.

To probe CARL's clustering structure, we select nearest neighbors of two reference state-goal pairs, one corresponding to walking backwards and one to standing up, and visualize their rollouts. As shown in Figure 4, the nearest-neighbor trajectories (blue, yellow, and red) are behaviorally coherent with the gray reference trajectory, whereas the random encoder's neighbors are not. Together with Figure 3, this provides qualitative evidence that CARL's representation organizes less structured, complex skills by their behavioral similarity, even in scaled-up environments.

6   Limitations and Opportunities for Future Work

6.1   Limitations

Skill extraction horizon.   In this work, the notion of a skill depends on the choice of extraction horizon k. We analyze CARL's sensitivity to k in Appendix C.4 and find that the optimal value is environment-dependent. A more principled approach would remove this dependence, discovering relevant local dynamics structure at various horizons to solve a given task.

Dataset coverage.   Our representation depends on the diversity, coverage, and quality of the offline dataset. Data from a random policy lacks the behaviors needed to learn useful representations, and sparse coverage can cause the collapse of distinct state-goal pairs. Appendix C.5 characterizes this sensitivity and shows CARL does not amplify it relative to HIQL. Addressing these limitations in an online setting will require intelligent data collection or a more robust objective.

Figure 4: Visualizations of nearest-neighbor trajectories under CARL and a random encoder for two reference skills (walking backwards and standing up); although these neighbors originate from across the maze, we shift them to share the reference's starting position to highlight their behavioral similarity. The grey trajectory is the reference; blue, yellow, and red are its nearest neighbors.

6.2 Future Work

Skill discovery. The behavior-centric view suggests a connection between representation learning and skill discovery. Future work could explicitly extract, label, or compose the clusters in CARL's representation structure, extending prior work (Lin et al., 2022) to yield a unified framework for offline skill discovery and hierarchical control.

Action abstraction. Our InfoNCE objective aligns state-goal pairs with their short-horizon action sequences, suggesting a duality in how skills can be defined: by the contexts where they are used or by the behaviors that achieve them. Future work could explore this duality by treating action-sequence abstractions, defined by the state-goal pairs they achieve, as skills in their own right.

High-level policy representations. CARL improves the low-level policy, but the high-level policy may be an equally important bottleneck. A natural next step is to develop representations for high-level decision-making: ones that support better planning, guide exploration, or operate over more abstract action primitives.

Online skill discovery. CARL currently operates offline, but the behavioral similarity objective could be extended to the online setting. More broadly, addressing the dataset coverage limitations discussed earlier could yield sample-efficiency gains and widen the applicability of hierarchical RL.

7 Closing Remarks

We introduced CARL, a representation learning approach for goal-conditioned offline RL that explicitly captures reusable short-horizon behaviors. Our central claim is that many RL problems contain *local dynamical structure*, lending themselves to a separation between local and global information. We demonstrated that building a notion of local re-usability into the low-level policy of a hierarchy unlocks performance benefits through skill reuse. By learning embeddings that cluster state–goal pairs according to the short-horizon behaviors they admit, our method provides a concrete mechanism for skill reuse that improves existing hierarchical RL frameworks.

A   Training Details

InfoNCE Loss.   In practice, we calculate our InfoNCE loss using the normalized dot product

$$f(\phi(s,g),\ \psi(\mathbf{a}_k)) = \left\langle \frac{\phi(s,g)}{\|\phi(s,g)\|_2},\ \frac{\psi(\mathbf{a}_k)}{\|\psi(\mathbf{a}_k)\|_2} \right\rangle,$$

where the loss function is

$$\mathcal{L}_{\text{InfoNCE}} = -\frac{1}{B} \sum_{i=1}^{B} \log \frac{\exp\big(f\big(\phi(s^i,g_k^i),\ \psi(\mathbf{a}_k^i)\big)/\tau\big)}{\sum_{j=1}^{B} \exp\Big(f\Big(\phi(s^i,g_k^i),\ \psi(\mathbf{a}_k^j)\Big)/\tau\Big)}.$$

Normalizing the InfoNCE score function prevents trivial solutions such as scaling the norms of embeddings, and bounds the scale of logits which makes the temperature parameter meaningful.

Goal Sampling.   Given a k-step triplet $(s_t, \mathbf{a_k}, s_{t+k})$ sampled from our dataset, we construct positive pairs by uniformly sampling goals from the range $s_{t+1} \ldots s_{t+k}$. In other words, we obtain positive pairs that consist of (s_t, s_{t+i}) and $\mathbf{a_k}$, where $1 \leq i \leq k$. This allows us to capture state-goal equivalences for all goals reachable within k steps from a state, aligning closer to our theoretical formulation. In addition, this allows us to capture richer temporal structure in the environment since skills at different horizons may become useful for the high-level policy. The benefits from this strategy are further explored in Appendix C.2.

Action Sequence Striding.   For humanoid maze, we found that long action sequences and large action spaces presented computational challenges due to the memory required to store large sequences of large actions. As a result, we introduced an action stride hyperparameter which avoids encoding the entire action sequence. We empirically selected an action stride of 4 for humanoid tasks because we found that this satisfied our computational budget constraints and minimally changed the action sequence. We additionally note that this minimally affects downstream performance, likely because the action sequence with striding captures most of the structure in the action sequence with no striding.

Action Sequence Truncation.   An edge case arises when constructing state–goal pairs near the end of a trajectory, where the full k-step action sequence and goal are unavailable. In this case, we pair the state with the last available goal in the trajectory and pad the action sequence to length k by repeating the final action.

Auxiliary Loss Weighting.   When combining our method with HIQL and HGCBC, we introduce a hyperparameter λ_{aux}, which weights the policy and value losses against our added objectives, $\mathcal{L}_{aux}$. Specifically, the final loss is calculated as

$$\mathcal{L}_{total} = (1 - \lambda_{aux})(\mathcal{L}_{value} + \mathcal{L}_{high} + \mathcal{L}_{low}) + \lambda_{aux}\mathcal{L}_{aux}.$$

Here, $\mathcal{L}_{low}$ refers to the low-level policy loss, $\mathcal{L}_{high}$ refers to the high-level policy loss, and $\mathcal{L}_{value}$ refers to the value function loss. $\mathcal{L}_{aux}$ refers to the auxiliary loss applied (which is $\mathcal{L}_{\text{InfoNCE}}$ for CARL). We report the λ_{aux} we select empirically in Table 3.

B   Implementation Details

We base our implementation of CARL on OGBench (Park et al., 2025a). We run our experiments on an internal GPU Cluster composed of Quadro RTX 5000 GPUs with around 16GB of memory. Similar to times reported in Park et al. (2025a), each run typically takes around 4 hours (state-based tasks) or around 10 hours (pixel-based tasks) when running HIQL+CARL and HGCBC+CARL. We estimate a total of around 10k GPU-hours were required for all experiments, with some additional hours for preliminary experiments.

Hyperparameter	Value
Learning rate	0.0003
Optimizer	Adam (Kingma & Ba, 2015)
# gradient steps	1000000 (states), 500000 (pixels)
Minibatch size	1024 (states), 256 (pixels)
MLP dimensions	(512, 512, 512)
Representation architecture (pixel-based)	IMPALA CNN (Espeholt et al., 2018)
Image augmentation probability	0.5 (pixel-based manipulation), 0 (others)
AWR Temperature	3.0
State-Goal MLP dimensions $\phi(s, g)$	(512, 512, 512)
Action sequence MLP dimensions $\psi(\mathbf{a_k})$	(256, 256)
Nonlinearity	GELU (Hendrycks & Gimpel, 2016)
Target smoothing coefficient	0.005
Discount factor γ	0.995 ({antmaze, pointmaze}-giant, humanoidmaze), 0.99 (others)
Expectile κ	0.7
Subgoal step	100 (humanoidmaze), 25 (other locomotion), 10 (others)
Representation horizon k	100 (humanoidmaze), 25 (other locomotion), 10 (others)
Action stride	4 (humanoidmaze), 1 (other)
Representation dimension	100
Single-Action CARL auxiliary loss weight λ_{aux}	0.1 (humanoidmaze), 0.5 (other locomotion), 0.1 (others)
CARL auxiliary loss weight λ_{aux}	0.1 (humanoidmaze), 0.3 (other locomotion), 0.7 (others)
Prediction auxiliary loss weight λ_{aux}	0.1 (humanoidmaze), 0.7 (other locomotion), 0.9 (others)
Single-Action CARL temperature τ	0.1 (locomotion), 0.05 (other)
CARL temperature τ	0.1 (locomotion), 0.05 (other)
Evaluation Episodes	20

Table 3: Hyperparameters used for comparisons across CARL, and other algorithms used in this paper. "Prediction" refers to parameters used for both Single-Action and Multi-Action Prediction.

B.1   Hyperparameters

We base our implementation of HIQL+CARL on the implementation of HIQL in the OGBench codebase (Park et al., 2025a). To ensure fair comparisons, we keep most hyperparameters the same when integrating CARL with HIQL and HGCBC. One notable exception was the size of the representation dimension. HIQL and HGCBC originally use representation dimensions of 10, but we change this to 100 in their CARL variants. For fair comparison, we compare HIQL+CARL to HIQL with a bigger representation dimension in Table 6. We find that HIQL's performance does not change significantly overall, with effects varying by environment: increasing the dimension causes regressions on pointmaze tasks while substantially improving performance on puzzle-3x3. Therefore, we use the original hyperparameters from Park et al. (2023) in our main benchmark.

Our selections of auxiliary loss weights λ_{aux} and temperatures τ were tuned for all algorithms through hyperparameter sweeps of equal effort.

For a full description of the hyperparameters used in our training, refer to Table 3.

B.2   Humanoid Visualization Details

For qualitative humanoid evaluations, we use a custom tool to visualize rollouts of trajectories associated with state-goal pairs in our dataset. We used Muwanx Tsujimoto [2], a project combining Mujoco, Web Assembly, ThreeJS, and Onnx to bring live Mujoco simulation to web browsers. Building off of this tool, we added various UI features and visualizations suited for our experiments.

To perform the evaluation, we first find all of the nearest neighbors for a reference state-goal pair. We embed every k step segment in our dataset and bin them into sequential groups of 500. From these bins, we select the best matches to the reference state-goal pair, and then select the top 30. Because the state-goal pairs in the humanoidmaze dataset span a variety of global (x, y) locations, we center them to visualize relative differences in joint behavior.

In Figure 4, we inspect nearest neighbors for different encoders by comparing k-step trajectories to a reference behavior. Although it is clear in videos of these 30 matches that representation learning methods cluster better than random encoders, snapshots of trajectories show only part of the picture. Therefore, we choose trajectories representative of the behavior seen in the videos we release on our website: https://sites.google.com/view/behavior-rep/home.

---

[2]Muwanx Github: https://github.com/ttktjmt/muwanx

C   Additional Experiments

C.1   Pre-training vs Co-training in HIQL

Task	Co-train	Pre-train
pointmaze-medium	**84.4 ± 3.1**	75.0 ± 6.7
pointmaze-large	**75.4 ± 3.1**	67.0 ± 6.6
pointmaze-giant	**64.5 ± 15.8**	48.5 ± 7.6
pointmaze-teleport	**31.4 ± 14.0**	18.0 ± 5.2
antmaze-medium	**97.9 ± 0.9**	**97.2 ± 2.3**
antmaze-large	**91.9 ± 2.4**	**92.8 ± 2.4**
antmaze-giant	**75.2 ± 3.8**	68.2 ± 5.0
antmaze-teleport	41.4 ± 2.1	**50.5 ± 2.0**
humanoidmaze-medium	**90.5 ± 2.4**	66.8 ± 4.0
humanoidmaze-large	**58.3 ± 3.8**	17.2 ± 1.4
humanoidmaze-giant	**27.2 ± 3.1**	4.0 ± 2.0
antsoccer-medium	**12.8 ± 2.4**	10.8 ± 4.2
antsoccer-arena	**63.7 ± 3.1**	58.5 ± 4.7
cube-single	**32.8 ± 3.1**	20.5 ± 6.0
cube-double	**23.4 ± 4.5**	8.2 ± 3.1
scene	**70.5 ± 5.2**	49.5 ± 7.2

Table 4: Success rates (%) comparing Co-train (jointly trained representations) against Pre-train (frozen representations). Results reported as mean $\pm$ 95% confidence interval; values within 95% of the best per row are **bolded**.

We explored two ways of integrating CARL into HIQL: pretraining, where the subgoal representation is learned with CARL and then finetuned with low-level policy gradients from HIQL, and co-training, where CARL's objective is optimized jointly with HIQL's value and policy losses. Pretraining keeps CARL isolated from HIQL's value learning — the encoder shapes the low-level policy's input but does not interact with the value function. Co-training instead shares the subgoal representation across the low-level policy and value function, fully integrating skill reuse into the algorithm. Pretraining alone improved performance on most state-based tasks but regressed on humanoid maze tasks. Co-training, by contrast, improved results across all tasks (Table 4), with the largest gains on longer-horizon tasks. We attribute this to the shared subgoal representation benefiting both the policy and value function, and view it as further evidence for the importance of integrated skill-reuse abstractions in HRL.

C.2 Surface Sampling vs Interior Sampling

Task	Interior	Surface
pointmaze-medium	**84.4 ± 3.1**	71.4 ± 5.9
pointmaze-large	**75.4 ± 3.1**	9.9 ± 9.7
pointmaze-giant	**64.5 ± 15.8**	7.2 ± 5.9
pointmaze-teleport	**31.4 ± 14.0**	26.7 ± 6.1
antmaze-medium	**97.9 ± 0.9**	95.0 ± 4.7
antmaze-large	91.9 ± 2.4	**92.4 ± 3.1**
antmaze-giant	**75.2 ± 3.8**	71.8 ± 6.4
antmaze-teleport	**41.4 ± 2.1**	39.7 ± 5.7
humanoidmaze-medium	**90.5 ± 2.4**	89.3 ± 3.1
humanoidmaze-large	**58.3 ± 3.8**	52.6 ± 5.7
humanoidmaze-giant	**27.2 ± 3.1**	21.5 ± 3.3
antsoccer-medium	**12.8 ± 2.4**	11.4 ± 2.4
antsoccer-arena	**63.7 ± 3.1**	56.9 ± 4.0
cube-single	**32.8 ± 3.1**	28.5 ± 3.8
cube-double	**23.4 ± 4.5**	15.7 ± 4.3
cube-triple	**15.2 ± 3.5**	9.9 ± 4.0
cube-quadruple	0.1 ± 0.2	**0.3 ± 0.5**
puzzle-3x3	45.5 ± 7.3	**47.9 ± 8.0**
puzzle-4x4	35.2 ± 7.1	**38.2 ± 5.0**
puzzle-4x5	4.2 ± 2.4	**6.5 ± 2.1**
puzzle-4x6	3.6 ± 2.1	**4.0 ± 1.4**
scene	70.5 ± 5.2	**71.6 ± 3.5**
win-rate	**15/22**	7/22

Table 5: Success rates (%) comparing CARL representations trained with Interior and Surface sampling techniques. Results report mean ± 95% confidence interval over 8 seeds. Win-rates for each sampling technique are reported, with the best win-rate bolded.

Given a tuple $s_t, \mathbf{a_k}, s_{t+k}$, one simple sampling technique would be to select positive examples as (s_t, s_{t+k}) and $\mathbf{a_k}$. We call this surface sampling, because this technique samples state-goal pairs that are on the surface of a k-step walk from s_t. However, we could also form positive pairs for (s_t, s_{t+i}), where $i \leq k$, because these shorter state pairs are still achieved with a portion of these longer action sequences. This also benefits the low-level policy, which may have to reason about state-goal pairs that are fewer than k-steps away. We call this interior sampling, because it samples state-goal pairs that are on the interior of the k–step walk from s_t. Empirically, we find that interior sampling performs better on average, obtaining a win-rate of 15/22 as shown in Table 5.

C.3 Training HIQL with larger representation dimensions

Task	HIQL Variants			HGCBC Variants		
	HIQL+CARL	HIQL (rep_dim=100)	HIQL	HGCBC+CARL	HGCBC (rep_dim=100)	HGCBC
pointmaze-medium	**84.4 ± 3.1**	65.5 ± 7.3	79 ± 4.3	**13.6 ± 1.8**	0.0 ± 0.0	0.0 ± 0.0
pointmaze-large	**75.4 ± 3.1**	60.1 ± 10.2	58 ± 4.3	**19.5 ± 3.8**	0.3 ± 0.2	0.4 ± 0.3
pointmaze-giant	**64.5 ± 15.8**	21.7 ± 6.9	46 ± 7.6	**0.0 ± 0.0**	**0.0 ± 0.0**	**0.0 ± 0.0**
pointmaze-teleport	**31.4 ± 14.0**	16.0 ± 4.5	18 ± 3.3	**29.7 ± 1.8**	12.6 ± 1.1	16.7 ± 1.2
antmaze-medium	**97.9 ± 0.9**	**96.5 ± 1.7**	**96 ± 0.9**	**73.1 ± 1.5**	60.7 ± 2.2	59.8 ± 1.6
antmaze-large	**91.9 ± 2.4**	**89.9 ± 3.3**	**91 ± 1.7**	**64.9 ± 0.9**	48.0 ± 0.9	59.3 ± 1.9
antmaze-giant	**75.2 ± 3.8**	68.8 ± 5.4	65 ± 4.3	**18.4 ± 1.3**	4.4 ± 1.1	8.5 ± 0.8
antmaze-teleport	41.4 ± 2.1	**45.6 ± 6.6**	42 ± 2.6	**38.5 ± 1.3**	34.6 ± 2.1	**36.9 ± 1.9**
humanoidmaze-medium	**90.5 ± 2.4**	87.6 ± 4.5	89 ± 1.7	**44.4 ± 1.3**	40.8 ± 1.8	32.4 ± 0.9
humanoidmaze-large	**58.3 ± 3.8**	52.9 ± 5.2	49 ± 3.3	**31.0 ± 0.8**	19.8 ± 1.7	22.6 ± 0.8
humanoidmaze-giant	**27.2 ± 3.1**	22.8 ± 4.5	12 ± 3.3	**20.0 ± 1.1**	12.0 ± 1.3	9.5 ± 1.3
antsoccer-medium	**12.8 ± 2.4**	11.7 ± 2.8	**13 ± 1.7**	**7.0 ± 0.4**	4.9 ± 1.0	5.9 ± 0.7
antsoccer-arena	**63.7 ± 3.1**	57.9 ± 3.1	58 ± 1.7	**24.9 ± 1.6**	15.2 ± 1.2	12.5 ± 0.8
cube-single	**32.8 ± 3.1**	19.9 ± 4.0	15 ± 2.6	**6.9 ± 0.7**	5.6 ± 1.1	4.4 ± 0.8
cube-double	**23.4 ± 4.5**	4.5 ± 2.4	6 ± 1.7	**1.3 ± 0.3**	**1.3 ± 0.5**	1.1 ± 0.3
cube-triple	**15.2 ± 3.5**	3.3 ± 1.2	3 ± 0.9	**2.1 ± 0.6**	0.0 ± 0.0	0.4 ± 0.3
cube-quadruple	0.1 ± 0.2	**0.3 ± 0.5**	0 ± 0.0	**0.1 ± 0.1**	0.0 ± 0.0	0.0 ± 0.0
puzzle-3x3	45.5 ± 7.3	**63.4 ± 8.3**	12 ± 1.7	**6.0 ± 0.9**	4.0 ± 0.8	4.1 ± 0.3
puzzle-4x4	**35.2 ± 7.1**	4.3 ± 2.6	7 ± 1.7	**5.9 ± 0.9**	0.3 ± 0.2	0.3 ± 0.2
puzzle-4x5	4.2 ± 2.4	**5.2 ± 1.9**	4 ± 0.9	**1.6 ± 0.6**	1.1 ± 0.5	0.4 ± 0.2
puzzle-4x6	**3.6 ± 2.1**	2.5 ± 1.7	3 ± 0.9	**0.6 ± 0.3**	**0.6 ± 0.2**	0.3 ± 0.2
scene	**70.5 ± 5.2**	41.0 ± 2.6	38 ± 2.6	**15.8 ± 1.0**	7.7 ± 1.3	8.5 ± 1.1
win-rate	**17/22**	4/22	1/22	**19/19**	0/19	0/19

Table 6: Success rates (%) comparing CARL-augmented HRL algorithms against their 100 dimensional representation variants and normal variants. Results report mean ± 95% confidence interval over 8 seeds, with the performance within 95% of best **bolded**. For win-rate calculations, we ignore ties and **bold** the highest win-rate.

We use a different representation dimension than Park et al. (2023), who do not ablate this choice. To verify that our gains do not come from the change in representation dimension alone, Table 6 compares our CARL-augmented HRL algorithms against both their default versions and variants with a 100-dimensional representation. Increasing the representation dimension alone yields mixed results: HIQL (rep_dim=100) shows degraded performance on most pointmaze environments and improves only on `puzzle-3x3` and `cube-single`. This confirms that the increased capacity alone cannot explain our performance gains — CARL's representation structure is essential for the consistent improvements we see across nearly every task.

C.4 K-step Sensitivity Analysis

Environment	k=5	k=10	k=25	k=50	k=75
pointmaze-medium	76.50 ± 10.8	$\mathbf{80.75 \pm 3.2}$	$\mathbf{84.00 \pm 0.7}$	81.00 ± 3.4	72.75 ± 4.9
pointmaze-large	45.75 ± 17.7	61.00 ± 13.2	70.00 ± 6.8	$\mathbf{88.25 \pm 5.5}$	$\mathbf{88.75 \pm 4.8}$
pointmaze-giant	22.50 ± 15.4	47.50 ± 14.1	62.50 ± 13.3	67.75 ± 12.4	$\mathbf{72.25 \pm 9.5}$
pointmaze-teleport	24.00 ± 8.5	26.50 ± 4.0	28.50 ± 7.8	27.75 ± 6.8	$\mathbf{36.25 \pm 6.4}$
antmaze-medium	89.75 ± 0.8	$\mathbf{95.75 \pm 1.4}$	$\mathbf{96.50 \pm 1.1}$	90.75 ± 2.5	90.75 ± 3.4
antmaze-large	51.75 ± 3.2	74.75 ± 1.4	$\mathbf{86.50 \pm 6.5}$	$\mathbf{86.00 \pm 3.5}$	68.25 ± 1.7
antmaze-giant	3.75 ± 2.1	38.75 ± 6.6	$\mathbf{73.00 \pm 2.5}$	57.75 ± 4.7	26.25 ± 6.4
antmaze-teleport	36.25 ± 4.5	41.50 ± 6.1	40.75 ± 2.7	$\mathbf{48.00 \pm 3.1}$	43.25 ± 5.8
antsoccer-medium	6.25 ± 2.8	4.75 ± 2.5	$\mathbf{12.25 \pm 1.7}$	$\mathbf{12.25 \pm 1.1}$	6.50 ± 0.5
antsoccer-arena	$\mathbf{58.75 \pm 6.2}$	53.25 ± 3.6	58.75 ± 5.6	60.00 ± 6.3	59.00 ± 4.0

Table 7: Sensitivity to horizon length k on locomotion environments. Success rates (%) averaged over 8 seeds with 95% confidence intervals reported. Results within 95% of the best are **bolded**.

Environment	k=25	k=75	k=100	k=125	k=150
humanoidmaze-medium	$\mathbf{88.00 \pm 4.4}$	85.00 ± 1.7	$\mathbf{87.00 \pm 3.0}$	86.67 ± 5.4	$\mathbf{87.33 \pm 4.6}$
humanoidmaze-large	44.67 ± 5.6	$\mathbf{48.67 \pm 2.7}$	48.50 ± 4.8	49.33 ± 6.2	$\mathbf{50.00 \pm 5.2}$
humanoidmaze-giant	18.00 ± 4.7	$\mathbf{26.67 \pm 2.4}$	22.75 ± 3.9	$\mathbf{28.00 \pm 5.9}$	21.67 ± 0.5

Table 8: Sensitivity to horizon length k on humanoidmaze environments. Success rates (%) averaged over 8 seeds with 95% confidence intervals reported. Results within 95% of the best are **bolded**.

Environment	k=3	k=5	k=10	k=15	k=30
cube-single	27.50 ± 7.8	29.25 ± 3.8	$\mathbf{36.00 \pm 3.1}$	31.00 ± 1.0	30.75 ± 5.2
cube-double	11.50 ± 7.0	15.75 ± 3.0	$\mathbf{21.00 \pm 5.2}$	$\mathbf{21.00 \pm 5.1}$	9.75 ± 0.4
cube-triple	1.25 ± 0.8	3.25 ± 2.2	5.75 ± 2.4	8.75 ± 1.4	$\mathbf{10.50 \pm 4.0}$
cube-quadruple	0.00 ± 0.0	0.00 ± 0.0	$\mathbf{0.25 \pm 0.4}$	0.00 ± 0.0	$\mathbf{0.25 \pm 0.4}$
scene	$\mathbf{74.75 \pm 6.5}$	66.75 ± 1.3	70.75 ± 1.7	71.00 ± 7.5	50.25 ± 3.6
puzzle-3x3	8.50 ± 2.2	11.75 ± 3.0	31.75 ± 5.5	$\mathbf{50.50 \pm 10.7}$	40.00 ± 12.0
puzzle-4x4	31.00 ± 1.2	32.00 ± 3.6	34.00 ± 1.2	$\mathbf{38.00 \pm 2.6}$	29.25 ± 2.8
puzzle-4x5	6.00 ± 1.7	$\mathbf{6.75 \pm 1.6}$	3.75 ± 0.4	4.00 ± 2.0	2.75 ± 0.8
puzzle-4x6	$\mathbf{4.75 \pm 2.5}$	4.25 ± 1.3	3.25 ± 1.3	3.25 ± 1.6	1.75 ± 1.3

Table 9: Sensitivity to horizon length k on manipulation environments. Success rates (%) averaged over 8 seeds with 95% confidence intervals reported. Results within 95% of the best are **bolded**.

We provide sensitivity analysis for our k-step hyperparameter in Table 7 for locomotion environments (except humanoidmaze), Table 8 for humanoidmaze, and Table 9 for manipulation environments. For some environments, we observe better performance with larger k (pointmaze-large, pointmaze-giant, and humanoidmaze-large). We also observe the opposite trend where performance drops off after increasing k too much (puzzle-3x3, cube-double, and scene). Other environments are largely robust to the chosen value of the horizon k.

C.5 Data Sensitivity Analysis

Method	Environment	0% Coverage	25% Coverage	50% Coverage	75% Coverage
CARL + HIQL	pointmaze-medium	10.7 ± 30.5	76.3 ± 12.9	80.7 ± 3.0	$\mathbf{85.3 \pm 14.6}$
	antmaze-medium	11.0 ± 24.1	$\mathbf{95.7 \pm 1.3}$	$\mathbf{99.7 \pm 1.3}$	$\mathbf{98.0 \pm 5.2}$
	humanoidmaze-medium	40.0 ± 9.0	$\mathbf{92.7 \pm 11.2}$	88.3 ± 5.2	89.3 ± 1.3
HIQL	pointmaze-medium	12.7 ± 26.7	62.7 ± 28.4	$\mathbf{72.0 \pm 25.0}$	69.7 ± 12.0
	antmaze-medium	0.0 ± 0.0	$\mathbf{93.0 \pm 6.5}$	$\mathbf{96.7 \pm 3.9}$	$\mathbf{95.0 \pm 4.3}$
	humanoidmaze-medium	33.0 ± 19.8	$\mathbf{89.0 \pm 13.3}$	85.0 ± 9.9	89.3 ± 1.3

Table 10: Robustness to reduced dataset coverage. Success rates (%) are reported as mean $\pm$ 95% confidence interval over 3 seeds. Results within 95% of the best in each row are **bolded**.

Method	Environment	25% Removed	50% Removed	75% Removed	100% Removed
CARL + HIQL	pointmaze-medium	$\mathbf{81.0 \pm 1.7}$	$\mathbf{81.0 \pm 2.6}$	59.7 ± 18.1	19.7 ± 1.3
	antmaze-medium	$\mathbf{99.3 \pm 1.3}$	$\mathbf{96.3 \pm 7.3}$	$\mathbf{96.7 \pm 3.0}$	18.0 ± 0.0
	humanoidmaze-medium	$\mathbf{90.3 \pm 7.3}$	$\mathbf{89.0 \pm 4.3}$	$\mathbf{86.7 \pm 1.3}$	16.0 ± 5.2
HIQL	pointmaze-medium	$\mathbf{66.0 \pm 5.2}$	$\mathbf{63.7 \pm 16.8}$	36.3 ± 11.6	19.0 ± 4.3
	antmaze-medium	$\mathbf{96.0 \pm 2.6}$	$\mathbf{95.3 \pm 8.6}$	$\mathbf{95.3 \pm 1.3}$	15.0 ± 4.3
	humanoidmaze-medium	$\mathbf{88.3 \pm 5.2}$	$\mathbf{87.0 \pm 9.9}$	$\mathbf{84.0 \pm 6.5}$	21.0 ± 4.3

Table 11: Robustness to dataset imbalance induced by removing action sequences in the left half of the maze that move downwards. Success rates (%) are reported as mean $\pm$ 95% confidence interval over 3 seeds. Results within 95% of the best in each row are **bolded**.

In this section, we analyze the sensitivity of CARL to two types of data imbalance. First, to test performance under low coverage, we remove portions of data from the left half of the maze. Specifically, we retain 0, 25, 50, and 75% of the data present in the left of the maze and test the accuracy of a policy learned with CARL +HIQL in these conditions and compare it to the performance of HIQL. We report results in Table 10 and find that CARL +HIQL shows a similar drop in performance over time as HIQL. This suggests that CARL improves the performance of HIQL while making data sensitivity no worse than the baseline.

Second, we test performance under dataset imbalance. We remove a percentage of action sequences in the left half of the maze that move downwards, biasing the action sequence distribution. We report results for this experiment in Table 11. Similar to the result in the first case, we find that CARL +HIQL's drop in performance as we increase dataset imbalance is very similar to the performance drop of HIQL. The similar robustness trends between CARL + HIQL and HIQL suggest that dataset quality impacts performance primarily through the core HRL components rather than the representation. While data diversity and coverage should in principle affect CARL's performance, these results indicate that CARL does not further exacerbate existing data sensitivity.

References

Rishabh Agarwal, Marlos C. Machado, Pablo Samuel Castro, and Marc G. Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=qda7-sVg84.

Anurag Ajay, Aviral Kumar, Pulkit Agrawal, Sergey Levine, and Ofir Nachum. OPAL: Offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=V69LGwJ0lIN.

Pablo Samuel Castro. Scalable methods for computing state similarity in deterministic Markov decision processes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 10069–10076, 2020.

Peter Dayan and Geoffrey E. Hinton. Feudal reinforcement learning. In Stephen J. Hanson, Jack D. Cowan, and C. Lee Giles (eds.), *Advances in Neural Information Processing Systems*, volume 5. Morgan Kaufmann, 1992. URL https://proceedings.neurips.cc/paper_files/paper/1992/file/d14220ee66aeec73c49038385428ec4c-Paper.pdf.

Thomas G. Dietterich. Hierarchical reinforcement learning with the MAXQ value function decomposition. *Journal of Artificial Intelligence Research*, 13:227–303, 2000.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, Shane Legg, and Koray Kavukcuoglu. IMPALA: Scalable distributed deep-RL with importance weighted actor-learner architectures. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1407–1416. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/espeholt18a.html.

Ben Eysenbach, Russ R. Salakhutdinov, and Sergey Levine. Search on the replay buffer: Bridging planning and reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Benjamin Eysenbach, Tianjun Zhang, Sergey Levine, and Russ R. Salakhutdinov. Contrastive learning as goal-conditioned reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 35, pp. 35603–35620, 2022.

Norm Ferns, Prakash Panangaden, and Doina Precup. Metrics for finite Markov decision processes. In *Proceedings of the 20th Conference on Uncertainty in Artificial Intelligence*, UAI '04, pp. 162–169. AUAI Press, 2004.

Danijar Hafner, Kuang-Huei Lee, Ian Fischer, and Pieter Abbeel. Deep hierarchical planning from pixels. *Advances in Neural Information Processing Systems*, 35:26091–26104, 2022.

Philippe Hansen-Estruch, Amy Zhang, Ashvin Nair, Patrick Yin, and Sergey Levine. Bisimulation makes analogies in goal-conditioned reinforcement learning. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 8407–8426. PMLR, 2022. URL https://proceedings.mlr.press/v162/hansen-estruch22a.html.

Dan Hendrycks and Kevin Gimpel. Gaussian error linear units (GELUs), 2016. URL https://arxiv.org/abs/1606.08415.

Riashat Islam, Manan Tomar, Alex Lamb, Yonathan Efroni, Hongyu Zang, Aniket Rajiv Didolkar, Dipendra Misra, Xin Li, Harm Van Seijen, Remi Tachet Des Combes, and John Langford. Principled offline RL in the presence of rich exogenous information. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning*

Research, pp. 14390–14421. PMLR, 2023. URL https://proceedings.mlr.press/v2 02/islam23a.html.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015. URL https://arxiv.org/abs/1412.6 980.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 5639–5650. PMLR, 2020. URL https://proceedings.mlr.press/v119/laskin20a.html.

Andrew Levy, Robert Platt, and Kate Saenko. Hierarchical reinforcement learning with hindsight. In *International Conference on Learning Representations*, 2019. URL https://openreview.n et/forum?id=ryzECoAcY7.

Xingyu Lin, Carl Qi, Yunchu Zhang, Zhiao Huang, Katerina Fragkiadaki, Yunzhu Li, Chuang Gan, and David Held. Planning with spatial-temporal abstraction from point clouds for deformable object manipulation. In *6th Annual Conference on Robot Learning*, 2022. URL https://open review.net/forum?id=tyxyBj2w4vw.

Leland McInnes, John Healy, and James Melville. UMAP: Uniform manifold approximation and projection for dimension reduction, 2018. URL https://arxiv.org/abs/1802.03426.

Ofir Nachum, Shixiang Shane Gu, Honglak Lee, and Sergey Levine. Data-efficient hierarchical reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

Seohong Park, Dibya Ghosh, Benjamin Eysenbach, and Sergey Levine. HIQL: Offline goal-conditioned RL with latent states as actions. In *Advances in Neural Information Processing Systems*, volume 36, pp. 34866–34891, 2023.

Seohong Park, Kevin Frans, Benjamin Eysenbach, and Sergey Levine. OGBench: Benchmarking offline goal-conditioned RL. In *International Conference on Learning Representations*, 2025a. URL https://proceedings.iclr.cc/paper_files/paper/2025/file/ecd9 2623ac899357312aaa8915853699-Paper-Conference.pdf.

Seohong Park, Deepinder Mann, and Sergey Levine. Dual goal representations, 2025b. URL https://arxiv.org/abs/2510.06714.

Ronald Parr and Stuart J. Russell. Reinforcement learning with hierarchies of machines. In *Advances in Neural Information Processing Systems*, volume 10, 1997.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8748–8763. PMLR, 2021. URL https://proceedings.mlr.press/v139 /radford21a.html.

Max Rudolph, Caleb Chuck, Kevin Black, Misha Lvovsky, Scott Niekum, and Amy Zhang. Learning action-based representations using invariance. *Reinforcement Learning Journal*, 1:342–365, 2024.

Richard S. Sutton, Doina Precup, and Satinder Singh. Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1–2):181–211, 1999. DOI: 10.1016/S0004-3702(99)00052-1.

Tatsuki Tsujimoto. mjswan: MuJoCo simulation on web assembly with neural networks. URL https://github.com/ttktjmt/mjswan.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding, 2018. URL https://arxiv.org/abs/1807.03748.

Vivienne Huiling Wang, Tinghuai Wang, and Joni Pajarinen. Hierarchical reinforcement learning with uncertainty-guided diffusional subgoals. In *Forty-Second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=1YOYA2zN1j.

Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=-2FCwDKRREu.

Tianren Zhang, Shangqi Guo, Tian Tan, Xiaolin Hu, and Feng Chen. Generating adjacency-constrained subgoals in hierarchical reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 21579–21590, 2020.