Wasserstein Iterative Networks
for Barycenter Estimation

Abstract

Wasserstein barycenters have become popular due to their ability to represent the average of probability measures in a geometrically meaningful way. In this paper, we present an algorithm to approximate the Wasserstein-2 barycenters of continuous measures via a generative model. Previous approaches rely on regularization (entropic/quadratic) which introduces bias or on input convex neural networks which are not expressive enough for large-scale tasks. In contrast, our algorithm does not introduce bias and allows using arbitrary neural networks. In addition, based on the celebrity faces dataset, we construct Ave, celeba! *dataset* which can be used for quantitative evaluation of barycenter algorithms by using standard metrics of generative models such as FID.

1   Introduction

Wasserstein barycenters [1] provide a geometrically meaningful notion of the average of probability measures based on optimal transport (OT, see [59]). Methods for computing barycenters have been successfully applied to various practical problems. In geometry processing, shape interpolation can be performed by barycenters [53]. In image processing, barycenters are used for color and style translation [44, 39], texture mixing [45] and image interpolation [27, 51]. In language processing, barycenters can be applied to text evaluation [12]. In online learning, barycenters are used for aggregating probabilistic forecasts of experts [26, 42]. In Bayesian inference, the barycenter of subset posteriors converges to the full data posterior [54, 55] allowing efficient computation of full posterior based on barycenters. In reinforcement learning, barycenters are used for uncertainty propagation [36]. Other applications are data augmentation [6], multivariate density registration [7], distributions alignment [20], domain generalization [34] and adaptation [38], model ensembling [13].

$$\overline{\mathbb{P}} = \underset{\mathbb{P}}{\operatorname{argmin}} \sum_{n=1}^{N} \alpha_n \mathbb{W}_2^2(\mathbb{P}, \mathbb{P}_n)$$

Figure 1: The barycenter w.r.t. weights $(\alpha_1, \alpha_2, \alpha_3) = (\frac{1}{4}, \frac{1}{2}, \frac{1}{4})$ of Ave, Celeba! subsets computed by our Algorithm 1. The figure shows random samples from the input subsets and generated images from the barycenter.

The bottleneck of obtaining barycenters is the computational complexity. For *discrete* measures, fast and accurate barycenter algorithms exist for low-dimensional problems; see [43] for a survey. How-

ever, discrete methods scale poorly with the number of support points of the barycenter. Consequently, they cannot approximate continuous barycenters well, especially in high dimensions.

Existing continuous barycenter approaches [29, 15, 25] are based on entropic/quadratic regularization or parametrization of Brenier potentials with input-convex neural networks (ICNNs, see [4]). The regularization-based [CR$\mathbb{W}$B] algorithm by [29] recovers a barycenter *biased* from the true one. Algorithms [C$\mathbb{W}_2$B] by [25] and [SC$\mathbb{W}_2$B] by [15] based on ICNNs resolve this issue, see [25, Tables 1-3]. However, despite the growing popularity of ICNNs in OT applications [35, 23, 37], they could be suboptimal architectures according to a recent study [24]. According to the authors, more expressive networks without the convexity constraint outperform ICNNs in practical OT problems.

Furthermore, *evaluation* of barycenter algorithms is challenging due to the limited number of continuous measures with explicitly known barycenters. It can be computed when the input measures are location-scatter (e.g. Gaussians) [3, §4] or 1-dimensional [8, §2.3]. Recent works [29, 25, 15] consider the Gaussian case in dimensions ≤ 256 for quantitative evaluation. In higher dimensions, the computation of the ground truth barycenter is hard even for the Gaussian case: it involves matrix inversion and square root extraction [2, Algorithm 1] with the cubic complexity in the dimension.

Contributions.

- We develop a novel *iterative algorithm* (§4) for estimating Wasserstein-2 barycenters based on the fixed point approach by [3] combined with a neural solver for optimal transport [24]. Unlike predecessors, our algorithm does not introduce bias and allows arbitrary network architectures.
- We construct the *Ave, celeba!* (*av*eraging *celeb*rity faces, §5) dataset consisting of 64×64 RGB images for large-scale quantitative evaluation of continuous Wasserstein-2 barycenter algorithms. The dataset includes 3 subsets of degraded images of faces (Figure 1). The barycenter of these subsets corresponds to the original clean faces.

Our algorithm is suitable for large-scale Wasserstein-2 barycenters applications. The developed dataset will allow quantitative evaluation of barycenter algorithms at a large scale improving transparency and allowing healthy competition in the optimal transport research.

Notation. We work in a Euclidean space $\mathbb{R}^D$ for some D. All the integrals are computed over $\mathbb{R}^D$ unless stated otherwise. We denote the set of all Borel probability measures on $\mathbb{R}^D$ with finite second moment by $\mathcal{P}_2(\mathbb{R}^D)$. We use $\mathcal{P}_{2,\mathrm{ac}}(\mathbb{R}^D) \subset \mathcal{P}_2(\mathbb{R}^D)$ to denote the subset of absolutely continuous measures. We denote its subset of measures with positive density by $\mathcal{P}_{2,\mathrm{ac}}^+(\mathbb{R}^D) \subset \mathcal{P}_{2,\mathrm{ac}}(\mathbb{R}^D)$. We denote the set of probability measures on $\mathbb{R}^D \times \mathbb{R}^D$ with marginals $\mathbb{P}$ and $\mathbb{Q}$ by $\Pi(\mathbb{P}, \mathbb{Q})$. For a measurable map $T : \mathbb{R}^D \to \mathbb{R}^D$, we denote the associated push-forward operator by $T\sharp$. For $\phi : \mathbb{R}^D \to \mathbb{R}$, we denote by $\overline{\phi}$ its Legendre-Fenchel transform [16] defined by $\overline{\phi}(y) = \max_{x \in \mathbb{R}^D}[\langle x, y \rangle - \phi(x)]$. Recall that $\overline{\phi}$ is a convex function, even when ϕ is not.

2 Preliminaries

Wasserstein-2 distance. For $\mathbb{P}, \mathbb{Q} \in \mathcal{P}_2(\mathbb{R}^D)$, Monge's *primal* formulation of the squared Wasserstein-2 distance, i.e., OT with *quadratic cost*, is

$$\mathbb{W}_2^2(\mathbb{P}, \mathbb{Q}) \stackrel{\mathrm{def}}{=} \min_{T\sharp\mathbb{P}=\mathbb{Q}} \int \frac{1}{2}\|x - T(x)\|^2 d\mathbb{P}(x), \tag{1}$$

where the minimum is taken over measurable functions (transport maps) $T : \mathbb{R}^D \to \mathbb{R}^D$ mapping $\mathbb{P}$ to $\mathbb{Q}$. The optimal T^* is called the *optimal transport map*. Note that (1) is not symmetric, and this formulation does not allow mass splitting. That is, for some $\mathbb{P}, \mathbb{Q} \in \mathcal{P}_2(\mathbb{R}^D)$, there might be no map T that satisfies $T\sharp\mathbb{P} = \mathbb{Q}$. Thus, [21] proposed the following relaxation:

$$\mathbb{W}_2^2(\mathbb{P}, \mathbb{Q}) \stackrel{\mathrm{def}}{=} \min_{\pi \in \Pi(\mathbb{P}, \mathbb{Q})} \int_{\mathbb{R}^D \times \mathbb{R}^D} \frac{1}{2}\|x - y\|^2 d\pi(x, y), \tag{2}$$

where the minimum is taken over all transport plans π, i.e., measures on $\mathbb{R}^D \times \mathbb{R}^D$ whose marginals are $\mathbb{P}$ and $\mathbb{Q}$. The optimal $\pi^* \in \Pi(\mathbb{P}, \mathbb{Q})$ is called the *optimal transport plan*. If π^* is of the form $[\mathrm{id}, T^*]\sharp\mathbb{P} \in \Pi(\mathbb{P}, \mathbb{Q})$ for some T^*, then T^* minimizes (1). The *dual form* [58] of $\mathbb{W}_2^2$ is:

$$\mathbb{W}_2^2(\mathbb{P}, \mathbb{Q}) = \max_{u \oplus v \leq \frac{\|\cdot\|^2}{2}} \left[\int u(x) d\mathbb{P}(x) + \int v(y) d\mathbb{Q}(y) \right], \tag{3}$$

where the maximum is taken over $u \in \mathcal{L}^1(\mathbb{P})$, $v \in \mathcal{L}^1(\mathbb{Q})$ satisfying $u(x) + v(y) \leq \frac{1}{2} \|x - y\|^2$ for all $x, y \in \mathbb{R}^D$. The functions u and v are called *potentials*. There exist optimal u^*, v^* satisfying $u^* = (v^*)^c$, where $f^c(y) \overset{def}{=} \min_{x \in \mathbb{R}^D} \left[\frac{1}{2} \|x - y\|^2 - f(x) \right]$ is the c-transform of f. We rewrite (3) as

$$\mathbb{W}_2^2(\mathbb{P}, \mathbb{Q}) = \max_v \left[\int v^c(x) d\mathbb{P}(x) + \int v(y) d\mathbb{Q}(y) \right], \tag{4}$$

where the maximum is taken over all $v \in \mathcal{L}^1(\mathbb{Q})$. It is customary [59, Cases 5.3 & 5.17] to define $u(x) = \frac{1}{2} \|x\|^2 - \psi(x)$ and $v(y) = \frac{1}{2} \|y\|^2 - \phi(x)$. There exist convex optimal ψ^* and ϕ^* satisfying $\overline{\psi^*} = \phi^*$ and $\overline{\phi^*} = \psi^*$. If $\mathbb{P} \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$, then the optimal T^* of (1) always exists and can be recovered from the dual solution u^* (or ψ^*) of (3): $T^*(x) = x - \nabla u^*(x) = \nabla \psi^*(x)$ [49, Theorem 1.17]. The map T^* is a gradient of a convex function, see the Brenier Theorem [9].

Wasserstein-2 barycenter. Let $\mathbb{P}_1, \ldots, \mathbb{P}_N \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$ such that at least one of them has bounded density. Their barycenter w.r.t. weights $\alpha_1, \ldots, \alpha_N$ ($\alpha_n > 0$; $\sum_{n=1}^N \alpha_n = 1$) is given by [1]:

$$\overline{\mathbb{P}} \overset{\text{def}}{=} \operatorname*{arg\,min}_{\mathbb{P} \in \mathcal{P}_2(\mathbb{R}^D)} \sum_{n=1}^N \alpha_n \mathbb{W}_2^2(\mathbb{P}_n, \mathbb{P}). \tag{5}$$

The barycenter $\overline{\mathbb{P}}$ exists uniquely and $\overline{\mathbb{P}} \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$. Moreover, its density is bounded [1, Definition 3.6 & Theorem 5.1]. For $n \in \{1, 2, \ldots, N\}$, let $T_{\overline{\mathbb{P}} \to \mathbb{P}_n} = \nabla \psi_n^*$ be the OT maps from $\overline{\mathbb{P}}$ to $\mathbb{P}_n$. The following holds $\overline{\mathbb{P}}$-almost everywhere:

$$\sum_{n=1}^N \alpha_n T_{\overline{\mathbb{P}} \to \mathbb{P}_n}(x) = \sum_{n=1}^N \alpha_n \nabla \psi_n^*(x) = x, \tag{6}$$

see [3, §3]. If $\overline{\mathbb{P}} \in \mathcal{P}_{2,ac}^+(\mathbb{R}^D)$, then (6) holds for every $x \in \mathbb{R}^D$, i.e., $\sum_{n=1}^N \alpha_n \psi_n^*(x) = \frac{\|x\|^2}{2} + c$. We call such convex potentials ψ_n^* *congruent*.

3   Related Work

Below we review existing continuous methods for OT. In §3.1, we discuss methods for OT problems (1), (2), (3). In §3.2, we review algorithms that compute barycenters (5).

3.1   Continuous OT Solvers for $\mathbb{W}_2$

We use the phrase *OT solver* to denote any method capable of recovering T^* or u^* (or ψ^*).

Primal-form solvers based on (1) or (2), e.g., [61, 32], parameterize T^* using complicated generative modeling techniques with adversarial losses to handle the pushforward constraint $T \sharp \mathbb{P} = \mathbb{Q}$ in the primal form (1). They depend on careful hyperparameter search and complex optimization [33].

Dual-form continuous solvers [17, 50, 41, 57, 23] based on (3) or (4) have straightforward optimization procedures and can be adapted to various tasks without extensive hyperparameter search.

A comprehensive overview and a benchmark of dual-form solvers are given in [24]. According to the evaluation, the best performing OT solver is *reversed maximin solver* $\lceil$MM:R$\rceil$, a modification of the idea proposed by [41] in the context of Wasserstein-1 GANs [5]. In this paper, we employ this solver as a part of our algorithm. We review it below.

Reversed Maximin Solver. In (4), $v^c(x)$ can be expanded through v via the definition of c-transform:

$$\max_v \int \min_{y \in \mathbb{R}^D} \left[\frac{\|x - y\|_2^2}{2} - v(y) \right] d\mathbb{P}(x) + \int v(y) d\mathbb{Q}(y) =$$
$$\max_v \min_T \int \left[\frac{\|x - T(x)\|_2^2}{2} - v(T(x)) \right] d\mathbb{P}(x) + \int v(y) d\mathbb{Q}(y). \tag{7}$$

In (7), the optimization over $y \in \mathbb{R}^D$ is replaced by the equivalent optimization over functions $T : \mathbb{R}^D \to \mathbb{R}^D$. This is done by the interchanging of integral and minimum, see [46, Theorem 3A].

The key point of this reformulation is that the optimal solution of this maximin problem is given by (v^*, T^*), where T^* is the OT map from $\mathbb{P}$ to $\mathbb{Q}$, see discussion in [24, §2] or [48, §4.1]. In practice, the potential $v : \mathbb{R}^D \to \mathbb{R}$ and the map $T : \mathbb{R}^D \to \mathbb{R}^D$ are parametrized by neural networks v_ω, T_θ. To train θ and ω, stochastic gradient ascent/descent (SGAD) over mini-batches from $\mathbb{P}, \mathbb{Q}$ is used.

3.2 Algorithms for Continuous $\mathbb{W}_2$ Barycenters

Variational optimization. Problem (5) is optimization over probability measures. To estimate $\overline{\mathbb{P}}$, one may employ a generator $G_\xi : \mathbb{R}^H \to \mathbb{R}^D$ with a latent measure $\mathbb{S}$ on $\mathbb{R}^H$ and train ξ by minimizing

$$\sum_{n=1}^N \alpha_n \mathbb{W}_2^2(\underbrace{G_\xi \sharp \mathbb{S}}_{\mathbb{P}_\xi}, \mathbb{P}_n) \to \min_\xi. \tag{8}$$

Optimization (8) can be performed by using SGD on random mini-batches from measures $\mathbb{P}_n$ and $\mathbb{S}$.

The difference between possible variational algorithms lies in the particular estimation method for $\mathbb{W}_2^2$ terms. To our knowledge, only ICNN-based minimax solver [35] has been used to compute $\mathbb{W}_2^2$ in (8) yielding [S$\mathbb{CW}_2$B] algorithm [15].

Potential-based optimization. [29, 25] recover the optimal potentials $\{\psi_n^*, \phi_n^*\}$ for each pair $(\overline{\mathbb{P}}, \mathbb{P}_n)$ via a non-minimax regularized dual formulation. No generative model is needed: the barycenter is recovered by pushing forward measures using gradients of potentials or by barycentric projection. However, the non-trivial choice of the *prior* barycenter distribution is required. Algorithm [CR$\mathbb{W}$B] by [29] uses entropic or quadratic regularization and [$\mathbb{CW}_2$B] algorithm by [25] uses ICNNs, congruence and cycle-consistency [23] regularization.

4 Iterative $\mathbb{W}_2$-Barycenter Algorithm

Our proposed algorithm is based on the *fixed point approach* by [3] which we recall in §4.1. In §4.2, we formulate our algorithm for computing Wasserstein-2 barycenters. In §4.3, we show that our algorithm generalizes the variational barycenter approach.

4.1 Theoretical Fixed Point Approach

Following [3], we define an operator $\mathcal{H} : \mathcal{P}_{2,ac}(\mathbb{R}^D) \to \mathcal{P}_{2,ac}(\mathbb{R}^D)$ by $\mathcal{H}(\mathbb{P}) = [\sum_{n=1}^N \alpha_n T_{\mathbb{P} \to \mathbb{P}_n}] \sharp \mathbb{P}$, where $T_{\mathbb{P} \to \mathbb{P}_n}$ denotes the OT map from $\mathbb{P}$ to $\mathbb{P}_n$. The measure $\mathcal{H}(\mathbb{P})$ obtained by the operator is indeed absolutely continuous, see [3, Theorem 3.1]. According to (6), the barycenter $\overline{\mathbb{P}}$ defined by (5) is a *fixed point* of $\mathcal{H}$, i.e., $\mathcal{H}(\overline{\mathbb{P}}) = \overline{\mathbb{P}}$. This suggests a way to compute $\overline{\mathbb{P}}$ by picking some $\mathbb{P} \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$ and recursively applying $\mathcal{H}$ until convergence. However, there are several **challenges**:

(a) A fixed point $\mathbb{P} \in \mathcal{P}_{2,\text{ac}}(\mathbb{R}^D)$ satisfying $\mathcal{H}(\mathbb{P}) = \mathbb{P}$ may be not the barycenter [3, Example 3.1]. The situation is analogous to that of the iterative k-means algorithm for a different problem – clustering. There may be fixed points which are not globally optimal.

(b) The sequence $\{\mathcal{H}^k(\mathbb{P})\}_k$ is tight [3, Theorem 3.6] so it has a subsequence converging in $\mathcal{P}_{2,ac}(\mathbb{R}^D)$, but the entire sequence may not converge. Nevertheless, the value of the objective (5) decreases for $\mathcal{H}^k(\mathbb{P})$ as $k \to \infty$ [3, Prop. 3.3].

(c) Efficient parametrization of the evolving measure $\mathcal{H}^k(\mathbb{P})$ is required. Moreover, to get $\mathcal{H}^{k+1}(\mathbb{P})$ from $\mathcal{H}^k(\mathbb{P})$, one needs to compute N optimal transport maps $T_{\mathcal{H}^k(\mathbb{P}) \to \mathbb{P}_n}$ which can be costly.

In [11] and [2], the fixed point approach is considered in the Gaussian case where the sequence $\mathcal{H}^k(\mathbb{P})$ is guaranteed to converge to the unique fixed point – the barycenter. The Gaussian case also makes parameterization **(c)** simple since both measures $\mathbb{P}_n$ and $\mathcal{H}^k(\mathbb{P})$ can be parametrized by means and covariance matrices, and the maps $T_{\mathcal{H}^k(\mathbb{P}) \to \mathbb{P}_n}$ are linear with closed form.

For general continuous measures $\mathbb{P}_n$, it remains an open problem to find sharp conditions on inputs $\mathbb{P}_n$ and the initial measure $\mathbb{P}$ of the fixed-point iteration for the sequence $\{\mathcal{H}^k(\mathbb{P})\}_k$ to converge to the barycenter. In this work, we empirically verify that the fixed point approach works well for the input measures that we consider and for a randomly initialized generative model representing the evolving barycenter (§4.2). We tackle challenge **(c)** and develop a scalable optimization procedure that requires only sample access to $\mathbb{P}_n \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$.

(a) **Step 1.** We compute N approximate OT maps T_{θ_n} from generated measure $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S}$ to input measures $\mathbb{P}_n$.

(b) **Step 2.** We regress $G_\xi(\cdot)$ onto $\sum_{n=1}^N \alpha_n T_{\theta_n}\big(G_{\xi_0}(\cdot)\big)$, where G_{ξ_0} is a fixed copy of G_ξ before the update.

Figure 2: Our proposed two-step implementation of the fixed-point operator $\mathcal{H}(\cdot)$..

4.2 Practical Iterative Optimization Procedure

We employ a generative model to parametrize the evolving measure, i.e., put $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S}$, where $\mathbb{S}$ is a latent measure, e.g., $\mathbb{S} = \mathcal{N}(0, I_H)$, and G_ξ is a neural network $\mathbb{R}^H \to \mathbb{R}^D$ with parameters ξ. Our approach to compute the operator $\mathcal{H}(\mathbb{P}_\xi)$ and update G_ξ consists of two steps.

First, we approximately recover N maps $T_{\mathbb{P}_\xi \to \mathbb{P}_n}$ via $\lceil$MM:R$\rceil$ solver, i.e., we use N pairs or networks $\{T_{\theta_n}, v_{\omega_n}\}$ and train them by optimizing (7) with $\mathbb{P} \leftarrow \mathbb{P}_\xi$ and $\mathbb{Q} \leftarrow \mathbb{P}_n$. For each $n = 1, 2, \ldots, N$, we perform SGAD by using batches from $G_\xi \sharp \mathbb{S}$ and $\mathbb{P}_n$ and get $T_{\theta_n} \approx T_{\mathbb{P}_\xi \to \mathbb{P}^n}$.

Second, we update G_ξ to represent $\mathcal{H}(\mathbb{P}_\xi)$ instead of $\mathbb{P}_\xi$. Inspired by [10], we do this via regression. We introduce G_{ξ_0}, a fixed copy of G_ξ. Next, we regress $G_\xi(\cdot)$ onto $\sum_{n=1}^N \alpha_n T_{\theta_n}\big(G_{\xi_0}(\cdot)\big)$

$$\int_z \ell\bigg(G_\xi(z), \sum_{n=1}^N \alpha_n T_{\theta_n}\big(G_{\xi_0}(z)\big)\bigg) d\mathbb{S}(z) \to \min_\xi$$

by performing SGD on random batches from $\mathbb{S}$, e.g., by using *squared error* $\ell(x, x') \stackrel{\text{def}}{=} \frac{1}{2}\|x - x'\|^2$. Thus, generator $G_\xi(\cdot)$ becomes close to $\sum_{n=1}^N \alpha_n T_{\theta_n}\big(G_{\xi_0}(\cdot)\big)$ as a function $\mathbb{R}^H \to \mathbb{R}^D$. We get

$$\mathbb{P}_\xi = G_\xi \sharp \mathbb{S} \approx \Big[\sum_{n=1}^N \alpha_n T_{\theta_n}\Big] \sharp \big[G_{\xi_0} \sharp \mathbb{S}\big] = \Big[\sum_{n=1}^N \alpha_n T_{\theta_n}\Big] \sharp \mathbb{P}_{\xi_0} \approx \Big[\sum_{n=1}^N \alpha_n T_{\mathbb{P}_{\xi_0} \to \mathbb{P}_n}\Big] \sharp \mathbb{P}_{\xi_0} = \mathcal{H}(\mathbb{P}_{\xi_0}),$$

i.e., the new generated $G_\xi \sharp \mathbb{S}$ measure approximates $\mathcal{H}(\mathbb{P}_{\xi_0})$.

Summary. Our two-step approach iteratively recomputes OT maps $T_{\mathbb{P}_\xi \to \mathbb{P}_n}$ (Figure 2a) and then uses regression to update the generator (Figure 2b). The *optimization procedure* is detailed in Algorithm 1 (Appendix B.2). Note that when fitting OT maps $T_{\mathbb{P}_\xi \to \mathbb{P}^n}$, we start from previously used $\{T_{\theta_n}, v_{\omega_n}\}$ rather than re-initialize them. Empirically, this works better.

4.3 Relation to Variational Barycenter Algorithms

We show that our Algorithm 1 reduces to variational approach (§3.2) when the number of generator updates, K_G, is equal to 1. More specifically, we show the equivalence of the gradient update w.r.t. parameters ξ of the *generator* in our iterative Algorithm 1 and that of (8). We assume that $\mathbb{W}_2^2$ terms are computed exactly in (8) regardless of the particular OT solver. Similarly, in Algorithm 1, we assume that maps $G_{\xi_0} \sharp \mathbb{S} \to \mathbb{P}_n$ before the generator update are always exact, i.e., $T_{\theta_n} = T_{\mathbb{P}_{\xi_0} \to \mathbb{P}_n}$.

Lemma 1. *Assume that $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S} \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$. Consider $K_G = 1$ for the iterative Algorithm 1, i.e., we do a single gradient step regression update per OT solvers' update. Assume that $\ell(x, x') = \frac{1}{2}\|x - x'\|^2$, i.e., the squared loss is used for regression. Then the generator's gradient update in*

Algorithm 1 is the same as in the variational algorithm:

$$\frac{\partial}{\partial \xi} \int_z \frac{1}{2} \big\| G_\xi(z) - \sum_{n=1}^N \alpha_n T_{\mathbb{P}_{\xi_0} \to \mathbb{P}_n} \big(G_{\xi_0}(z) \big) \big\|^2 d\mathbb{S}(z) = \frac{\partial}{\partial \xi} \sum_{n=1}^N \alpha_n \mathbb{W}_2^2 (G_\xi \sharp \mathbb{S}, \mathbb{P}_n), \qquad (9)$$

where the derivatives are evaluated at $\xi = \xi_0$.

We prove the lemma in Appendix A. In practice, we choose $K_G = 50$ as it empirically works better.

5   Ave, celeba! Images Dataset

In this section, we develop a generic methodology for building measures with known $\mathbb{W}_2$ barycenter. We then use it to construct Ave, celeba! dataset for quantitative evaluation of barycenter algorithms.

Key idea. Consider $\alpha_1, \ldots, \alpha_N > 0$ with $\sum_{n=1}^N \alpha_n = 1$, congruent convex functions $\psi_1, \ldots \psi_N :$ $\mathbb{R}^D \to \mathbb{R}$, and a measure $\mathbb{P} \in \mathcal{P}_{2,\mathrm{ac}}^+(\mathbb{R}^D)$ with positive density. Define $\mathbb{P}_n = \nabla \psi_n \sharp \mathbb{P}$. Thanks to Brenier's theorem [9], $\nabla \psi_n$ is the unique OT map from $\mathbb{P}$ to $\mathbb{P}_n$. Since the support of $\mathbb{P}$ is $\mathbb{R}^D$, ψ_n is the unique (up to a constant) dual potential for $(\mathbb{P}, \mathbb{P}_n)$[56]. Since potentials ψ_n's are congruent, the barycenter $\overline{\mathbb{P}}$ of $\mathbb{P}_n$ w.r.t. weights $\alpha_1, \ldots, \alpha_N$ is $\mathbb{P}$ itself [11, C.2]. If ψ_n's are such that all $\mathbb{P}_n$ are absolutely continuous, then $\mathbb{P} = \overline{\mathbb{P}}$ is the unique barycenter (§2).

If one obtains N congruent ψ_n, then for any $\mathbb{P} \in \mathcal{P}_{2,ac}(\mathbb{R}^D)$, pushforward measures $\mathbb{P}_n = \nabla \psi_n \sharp \mathbb{P}$ can be used as the input measures for the barycenter task. For $\mathbb{P}$ accessible by samples, measures $\mathbb{P}_n$ are also accessible by samples: one may sample $x \sim \mathbb{P}$ and push samples forward by $\nabla \psi_n$.

The challenging part is to construct non-trivial congruent convex functions ψ_n. First, we provide a novel method to transform a single convex function ψ into a *pair* (ψ^l, ψ^r) of convex functions satisfying $\alpha \nabla \psi^l(x) + (1-\alpha)\nabla \psi^r(x) = x$ for all $x \in \mathbb{R}^D$ (Lemma 2). Next, we extend the method to generate congruent N-*tuples* (Lemma 3).

Lemma 2 (Constructing congruent pairs)**.** *Let* ψ *be a strongly convex and L-smooth (for some $L > 0$) function. Let $\beta \in (0, 1)$. Define β-left and β-right functions of ψ by*

$$\psi^l \overset{def}{=} \overline{\beta \frac{\|\cdot\|^2}{2} + (1-\beta)\psi} \qquad and \qquad \psi^r \overset{def}{=} \overline{(1-\beta)\frac{\|\cdot\|^2}{2} + \beta\overline{\psi}}. \qquad (10)$$

Then $\beta\psi^l(x) + (1-\beta)\psi^r(x) = \frac{\|x\|^2}{2}$ for $x \in \mathbb{R}^D$, i.e., convex functions ψ^l, ψ^r are congruent w.r.t. weights $(\beta, 1-\beta)$. Besides, for all $x \in \mathbb{R}^D$ the gradient $y^l \overset{def}{=} \nabla \psi^l(x)$ can be computed via solving β-strongly concave optimization:

$$y^l = \underset{y \in \mathbb{R}}{\arg\max} \left(\langle x, y \rangle - \beta \frac{\|y\|^2}{2} - (1-\beta)\psi(y) \right). \qquad (11)$$

In turn, the value $y^r \overset{def}{=} \nabla \psi^r(x)$ is given by $y^r = \nabla \psi(y^l)$.

The proof is given in Appendix A. We visualize the idea of our Lemma 2 in Figure 7a. Thanks to Lemma 2, any analytically known convex ψ, e.g., an ICNN, can be used to produce a congruent pair ψ^l, ψ^r. To compute the gradient maps, optimization (11) can be solved by convex optimization tools with $\nabla \psi$ computed by automatic differentiation.

Lemma 3 (Constructing N congruent functions.)**.** *Let* $\psi_1^0, \ldots, \psi_M^0$ *be convex functions, $\beta_1, \ldots, \beta_M \in (0,1)$ and ψ_m^l, ψ_m^r be β_m-left, β_m-right functions for ψ_m^0 respectively. Let $\gamma^l, \gamma^r \in \mathbb{R}^{N \times M}$ be two rectangular matrices with non-negative elements and the sum of elements in each column equals to 1. Let $w_1, \ldots, w_M > 0$ satisfy $\sum_{m=1}^M w_m = 1$. For $n = 1, \ldots, N$ define*

$$\psi_n(x) \overset{def}{=} \frac{\sum_{m=1}^M w_m \big[\beta_m \gamma_{nm}^l \psi_m^l(x) + (1-\beta_m)\gamma_{nm}^r \psi_m^r(x) \big]}{\sum_{m=1}^M w_m \big[\beta_m \gamma_{nm}^l + (1-\beta_m)\gamma_{nm}^r \big]}. \qquad (12)$$

Then $\psi_1, \ldots, \psi_N$ are congruent w.r.t. weights $\alpha_n \overset{def}{=} \sum_{m=1}^M w_m \big[\beta_m \gamma_{nm}^l + (1-\beta_m)\gamma_{nm}^r \big]$.

We prove Lemma 3 in Appendix A. We visualize the idea of our Lemma 3 in Figure 7b. The lemma provides an elegant way to create $N \geq 2$ congruent functions from convex linear combinations of

Figure 3: The production of **Ave, celeba! dataset**. The 1st line shows images $x \sim \mathbb{P}_{\text{Celeba}}$. Each of 3 next lines shows OT maps $\nabla \psi_n(x) \sim \nabla \psi_n \sharp \mathbb{P}_{\text{Celeba}} = \mathbb{P}_n$ to constructed measures $\mathbb{P}_n$. Their barycenter w.r.t. $(\alpha_1, \alpha_2, \alpha_3) = (\frac{1}{4}, \frac{1}{2}, \frac{1}{4})$ is $\mathbb{P}_{\text{Celeba}}$. The last line shows congruence of ψ_n, i.e., $\sum_{n=1}^{N} \alpha_n \nabla \psi_n(x) \equiv x$. Samples **in green boxes** are included to dataset.

functions in given congruent pairs (ψ_m^l, ψ_m^r). Gradients $\nabla \psi_n$ of these functions are respective linear combinations of gradients $\nabla \psi_m^l$ and $\nabla \psi_m^r$.

Dataset creation. We use CelebA 64×64 faces dataset [31] as the basis for our Ave, celeba! dataset. We assume that CelebA dataset is an empirical sample from the continuous measure $\mathbb{P}_{\text{Celeba}} \in \mathcal{P}_{2,\text{ac}}^+(\mathbb{R}^{3 \times 64 \times 64})$ which we put to be the barycenter in our design, i.e., $\overline{\mathbb{P}} = \mathbb{P}_{\text{Celeba}}$. We construct diffirentiable congruent ψ_n with bijective gradients that produce $\mathbb{P}_n = \nabla \psi_n \sharp \overline{\mathbb{P}} \in \mathcal{P}_{2,\text{ac}}^+(\mathbb{R}^{3 \times 64 \times 64})$ whose unique barycenter is $\mathbb{P}_{\text{Celeba}}$. In Lemma 3, we set $N = 3$, $M = 2$, $\beta_1 = \beta_2 = \frac{1}{2}$, $w_1 = w_2 = \frac{1}{2}$ and

$$(\gamma^l)^\top = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}, \qquad (\gamma^r)^\top = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

which yields weights $(\alpha_1, \alpha_2, \alpha_3) = (\frac{1}{4}, \frac{1}{2}, \frac{1}{4})$ We choose the constants above manually to make sure the final produced measures $\mathbb{P}_n$ are visually distinguishable. We use $\psi_m^0(x) = \text{ICNN}_m\big(s_m(\sigma_m(d_m(x)))\big) + \lambda \frac{\|x\|^2}{2}$ as convex functions, where ICNNs have ConvICNN64 architecture [24, Appendix B.1], σ_1, σ_2 are random permutations of pixels and channels, s_1, s_2 are axis-wise random reflections, $\lambda = \frac{1}{100}$. In both functions, d_m is a de-colorization transform which sets R, G, B channels of each pixel to $(\frac{7}{10}R + \frac{1}{25}G + \frac{13}{50}B)$ for ψ_1^0 and $\frac{1}{3}(R+G+B)$ for ψ_2^0. The weights of ICNNs are initialized by the pre-trained potentials of $\mathbb{W}_2^2$ "Early" transport benchmark which map blurry faces to the clean ones [24, §4.1]. All the implementation details are given in Appendix B.1.

Finally, to create *Ave, celeba!* dataset, we randomly split the images dataset into 3 equal parts containing $\approx 67K$ samples, and map each part to respective measure $\mathbb{P}_n = \nabla \psi_n \sharp \mathbb{P}_{\text{Celeba}}$ by $\nabla \psi_n$. Resulting $3 \times 67K$ samples form the dataset consisting of 3 parts. We show the samples in Figure 3. The samples from the respective parts are in green boxes.

6 Evaluation

The code is written on the PyTorch and includes the script for producing Ave, celeba! dataset. The experiments are conducted on $4 \times$GPU GTX 1080ti. The details are given in Appendix B.

6.1 Evaluation on Ave, celeba! Dataset

We evaluate our *iterative* algorithm 1 and a recent state-of-the-art *variational* [SC$\mathbb{W}_2$B] by [15] on Ave, celeba! dataset. Both algorithms use a generative model $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S}$ for the barycenter and yield approximate maps $\widehat{T}_{\mathbb{P}_\xi \to \mathbb{P}_n}$ to input measures. In our case, the maps are neural networks T_{θ_n}, while in [SC$\mathbb{W}_2$B] they are gradients of ICNNs. The barycenters of Ave, celeba! fitted by our algorithm and [SC$\mathbb{W}_2$B] are shown in Figures 4a and 4b respectively. Recall the ground truth barycenter is $\mathbb{P}_{\text{Celeba}}$. Thus, for quantitative evaluation we use FID score [19] computed on 200K generated samples w.r.t.

(a) **Our** Algorithm 1. (b) **Competitive** [SCW₂B] algorithm.

Figure 4: The barycenter and maps to input measures estimated by barycenter algorithms. The 1st line shows generated samples $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S} \approx \mathbb{P}_{\text{Celeba}}$. Lines 2-4 show maps $\widehat{T}_{\mathbb{P}_\xi \to \mathbb{P}_n}$. The last line shows the average map $\sum_{n=1}^{N} \alpha_n \widehat{T}_{\mathbb{P}_\xi \to \mathbb{P}_n}$.

(a) Maps from $\mathbb{P}_1$ to the barycenter. (b) Maps from $\mathbb{P}_2$ to the barycenter. (c) Maps from $\mathbb{P}_3$ to the barycenter.

Figure 5: Maps from inputs $\mathbb{P}_n$ to the barycenter $\overline{\mathbb{P}}$ estimated by the barycenter algorithms in view. For comparison with the original barycenter images, the faces are the same as in Figure 3.

Method		FID↓
[SCW₂B]	$G_\xi(z)$	156.3
	$\sum_{n=1}^{N} \alpha_n \widehat{T}_{\mathbb{P}_\xi \to \mathbb{P}_n}(G_\xi(z))$	152.1
Ours	$G_\xi(z)$	75.8
	$\sum_{n=1}^{N} \alpha_n \widehat{T}_{\mathbb{P}_\xi \to \mathbb{P}_n}(G_\xi(z))$	52.85

Table 1: FID scores of images from the learned barycenter.

Method		FID↓		
		$n=1$	$n=2$	$n=3$
[CS]	$y + (\overline{\mu} - \mu_n)$	90.5	75.5	88.8
[SCW₂B]	$\widehat{T}_{\mathbb{P}_n \to \mathbb{P}_\xi}(y)$	67.4	62.4	319.62
Ours	$\widehat{T}_{\mathbb{P}_n \to \mathbb{P}_\xi}(y)$	49.3	46.9	61.5

Table 2: FID scores of images mapped from inputs $\mathbb{P}_n$.

the original CelebA dataset, see Table 1. Our method *drastically* outperforms [SCW₂B]. Presumably, this is due to the latter using ICNNs which do not provide sufficient performance.

Additionally, we evaluate to which extent the algorithms allow to recover the inverse OT maps $T_{\mathbb{P}_n \to \mathbb{P}_\xi}$ from inputs $\mathbb{P}_n$ to the barycenter $\mathbb{P}_\xi \approx \overline{\mathbb{P}}$. In [SCW₂B], these maps are computed during training. Our algorithm does not compute them. Thus, we separately fit the inverse maps after main training by using [MM:R] solver between each input $\mathbb{P}_n$ and learned $\mathbb{P}_\xi$ (Algorithm 2 of Appendix 2). The inverse maps are given in Figure 5; their FID scores – in Table 2. Here we add an additional *constant shift* [CS] baseline which simply shifts the mean of input $\mathbb{P}_n$ to the mean $\overline{\mu}$ of $\overline{\mathbb{P}}$. The vector $\overline{\mu}$ is given by $\sum_{n=1}^{N} \alpha_n \mu_n$, where μ_n is the mean of $\mathbb{P}_n$ [3]. We estimate $\overline{\mu}$ from samples $y \sim \mathbb{P}_n$.

6.2 Additional Experimental Results

Different domains. To stress-test our algorithm 1, we compute the barycenters w.r.t. $(\alpha_1, \alpha_2, \alpha_3) = (\frac{1}{3}, \frac{1}{3}, \frac{1}{3})$ of notably different datasets: 50K Shoes [62], 138K Amazon Handbags and 90K Fruits [40]. All the images are rescaled to 64×64. The *ground gruth barycenter is unknown*, but one may imagine what it looks like. Due to (6), each barycenter image is a *pixel-wise average* of a shoe, a

(a) Generated samples $\mathbb{P}_\xi \approx \overline{\mathbb{P}}$, fitted maps to each $\mathbb{P}_n$ and their average.

(b) Samples $y \sim \mathbb{P}_1$ mapped through $\mathbb{P}_\xi$ to each $\mathbb{P}_n$.

(c) Samples $y \sim \mathbb{P}_2$ mapped through $\mathbb{P}_\xi$ to each $\mathbb{P}_n$.

(d) Samples $y \sim \mathbb{P}_3$ mapped through $\mathbb{P}_\xi$ to each $\mathbb{P}_n$.

Figure 6: The barycenter of Handbags, Shoes, Fruit (64×64) datasets fitted by **our** Algorithm 1. We give the results of **competitive** [SC$\mathbb{W}_2$B] in Appendix B.4.

handbag and a fruit, which is supported by our result shown in Figure 6. In the same figure, we also show the maps between datasets *through* the barycenter (Figures 6b, 6c, 6d): this allows generation of images in other categories with styles similar to a given image. For instance, in Figure 6d, we generate an orange bag and an orange shoe by pushing the image of an orange through the barycenter. We provide more examples in Figure 13 of Appendix C.4.

Extra results. In Appendix D, we compute the barycenters of toy 2D dsitributions. In Appendix C.1, we provide *quantitative* results for computing barycenters in the Gaussian case. In Appendix C.2, we test how our algorithm works as a *generative model* on the original CelebA dataset, i.e., when $N = 1$ and $\mathbb{P}_1 = \mathbb{P}_{\text{Celeba}}$. We show that in this case it achieves FID scores comparable to recent WGAN models. In Appendix C.3, similar to [15], we compute barycenters of digit classes 0/1 of 32×32 grayscale MNIST [28]. We also test our algorithm on FashionMNIST [60] **10 classes** dataset.

7   Discussion

Potential impact (algorithm). We present a scalable barycenter algorithm based on fixed-point iterations with many application prospects. For instance, in medical imaging, MRI is often acquired at multiple sites where the overlap of information (imaging, genetic, diagnosis) between any two sites is limited. Consequently, the data on each site may be biased and can cause generalizability and robustness issues when training models. The developed algorithm could help aggregate data from multiple sites and overcome the distributional shift issue across sites.

Potential impact (dataset). There is no high-dimensional dataset for the barycenter problem except for location-scattered cases (e.g. Gaussians), where the transport maps are always linear. Hence our proposed dataset fills an important gap, thereby allowing quantitative evaluation of future related methods. We expect our Ave, celeba! to become a standard dataset for evaluating continuous barycenter algorithms. In addition, we describe a generic recipe (§5) to produce new datasets.

Limitations (algorithm). In our algorithm, the evolving measure $\mathbb{P}_\xi$ is not guaranteed to be continuous, while it is continuous in the underlying fixed point approach. To enforce the absolute continuity of $\mathbb{P}_\xi = G_\xi \sharp \mathbb{S}$, one may use an invertible network [14] for G_ξ and an absolutely continuous latent measure $\mathbb{S}$ in a latent space of dimension $H = D$. However, our results suggest this is unnecessary in practice — common GANs approaches also assume $H \ll D$. During the fixed-point iterations, the barycenter objective (5) decreases. However, there is no guarantee that the sequence of measures converges to a fixed point which is the barycenter. Identifying the precise conditions on the input measures and the initial point is an important future direction. Besides, our algorithm does not recover inverse OT maps $T_{\mathbb{P}_n \to \overline{\mathbb{P}}}$; we compute them with an OT solver as a follow-up. To avoid this second step, one may consider using invertible neural nets [14] to parametrize maps T_{θ_n} in our Algorithm 1.

Limitations (dataset). To create Ave, celeba! dataset (§5), we compose ICNNs with decolorization, random reflections and permutations to simulate degraded images. It is unclear how to produce other practically interesting effects via ICNNs. It also remains an open question on how to better hide the information of the barycenter image in the constructed marginal measures. Studying these questions is an interesting future direction that can inspire benchmarking other OT problems.

References

[1] Martial Agueh and Guillaume Carlier. Barycenters in the Wasserstein space. *SIAM Journal on Mathematical Analysis*, 43(2):904–924, 2011.

[2] Jason M Altschuler, Sinho Chewi, Patrik Gerber, and Austin J Stromme. Averaging on the bures-wasserstein manifold: dimension-free convergence of gradient descent. *arXiv preprint arXiv:2106.08502*, 2021.

[3] Pedro C Álvarez-Esteban, E Del Barrio, JA Cuesta-Albertos, and C Matrán. A fixed-point approach to barycenters in Wasserstein space. *Journal of Mathematical Analysis and Applications*, 441(2):744–762, 2016.

[4] Brandon Amos, Lei Xu, and J Zico Kolter. Input convex neural networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 146–155. JMLR. org, 2017.

[5] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein GAN. *arXiv preprint arXiv:1701.07875*, 2017.

[6] Iaroslav Bespalov, Nazar Buzun, Oleg Kachan, and Dmitry V Dylov. Data augmentation with manifold barycenters. *arXiv preprint arXiv:2104.00925*, 2021.

[7] Jérémie Bigot, Elsa Cazelles, and Nicolas Papadakis. Data-driven regularization of wasserstein barycenters with an application to multivariate density registration. *Information and Inference: A Journal of the IMA*, 8(4):719–755, 2019.

[8] Nicolas Bonneel, Julien Rabin, Gabriel Peyré, and Hanspeter Pfister. Sliced and radon wasserstein barycenters of measures. *Journal of Mathematical Imaging and Vision*, 51(1):22–45, 2015.

[9] Yann Brenier. Polar factorization and monotone rearrangement of vector-valued functions. *Communications on pure and applied mathematics*, 44(4):375–417, 1991.

[10] Yucheng Chen, Matus Telgarsky, Chao Zhang, Bolton Bailey, Daniel Hsu, and Jian Peng. A gradual, semi-discrete approach to generative network training via explicit Wasserstein minimization. In *International Conference on Machine Learning*, pages 1071–1080. PMLR, 2019.

[11] Sinho Chewi, Tyler Maunu, Philippe Rigollet, and Austin J Stromme. Gradient descent algorithms for bures-wasserstein barycenters. In *Conference on Learning Theory*, pages 1276–1304. PMLR, 2020.

[12] Pierre Colombo, Guillaume Staerman, Chloe Clavel, and Pablo Piantanida. Automatic text evaluation through the lens of wasserstein barycenters, 2021.

[13] Pierre Dognin, Igor Melnyk, Youssef Mroueh, Jerret Ross, Cicero Dos Santos, and Tom Sercu. Wasserstein barycenter model ensembling. *arXiv preprint arXiv:1902.04999*, 2019.

[14] Christian Etmann, Rihuan Ke, and Carola-Bibiane Schönlieb. iunets: learnable invertible up-and downsampling for large-scale inverse problems. In *2020 IEEE 30th International Workshop on Machine Learning for Signal Processing (MLSP)*, pages 1–6. IEEE, 2020.

[15] Jiaojiao Fan, Amirhossein Taghvaei, and Yongxin Chen. Scalable computations of Wasserstein barycenter via input convex neural networks. *arXiv preprint arXiv:2007.04462*, 2020.

[16] Werner Fenchel. On conjugate convex functions. *Canadian Journal of Mathematics*, 1(1):73–77, 1949.

[17] Aude Genevay, Marco Cuturi, Gabriel Peyré, and Francis Bach. Stochastic optimization for large-scale optimal transport. In *Advances in neural information processing systems*, pages 3440–3448, 2016.

[18] Aude Genevay, Gabriel Peyré, and Marco Cuturi. Gan and vae from an optimal transport point of view. *arXiv preprint arXiv:1706.01807*, 2017.

[19] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pages 6626–6637, 2017.

[20] David I Inouye, Zeyu Zhou, Ziyu Gong, and Pradeep Ravikumar. Iterative barycenter flows. *arXiv preprint arXiv:2104.07232*, 2021.

[21] Leonid Kantorovitch. On the translocation of masses. *Management Science*, 5(1):1–4, 1958.

[22] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[23] Alexander Korotin, Vage Egiazarian, Arip Asadulaev, Alexander Safin, and Evgeny Burnaev. Wasserstein-2 generative networks. In *International Conference on Learning Representations*, 2021.

[24] Alexander Korotin, Lingxiao Li, Aude Genevay, Justin Solomon, Alexander Filippov, and Evgeny Burnaev. Do neural optimal transport solvers work? a continuous wasserstein-2 benchmark. *arXiv preprint arXiv:2106.01954*, 2021.

[25] Alexander Korotin, Lingxiao Li, Justin Solomon, and Evgeny Burnaev. Continuous wasserstein-2 barycenter estimation without minimax optimization. In *International Conference on Learning Representations*, 2021.

[26] Alexander Korotin, Vladimir V'yugin, and Evgeny Burnaev. Mixability of integral losses: A key to efficient online aggregation of functional and probabilistic forecasts. *Pattern Recognition*, 120:108175, 2021.

[27] Julien Lacombe, Julie Digne, Nicolas Courty, and Nicolas Bonneel. Learning to generate wasserstein barycenters. *arXiv preprint arXiv:2102.12178*, 2021.

[28] Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010.

[29] Lingxiao Li, Aude Genevay, Mikhail Yurochkin, and Justin Solomon. Continuous regularized Wasserstein barycenters. *arXiv preprint arXiv:2008.12534*, 2020.

[30] Huidong Liu, Xianfeng Gu, and Dimitris Samaras. Wasserstein GAN with quadratic transport cost. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 4832–4841, 2019.

[31] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

[32] Guansong Lu, Zhiming Zhou, Jian Shen, Cheng Chen, Weinan Zhang, and Yong Yu. Large-scale optimal transport via adversarial training with cycle-consistency. *arXiv preprint arXiv:2003.06635*, 2020.

[33] Mario Lucic, Karol Kurach, Marcin Michalski, Sylvain Gelly, and Olivier Bousquet. Are GANs created equal? a large-scale study. In *Advances in neural information processing systems*, pages 700–709, 2018.

[34] Boyang Lyu, Thuan Nguyen, Prakash Ishwar, Matthias Scheutz, and Shuchin Aeron. Barycentric distribution alignment and manifold-restricted invertibility for domain generalization, 2021.

[35] Ashok Vardhan Makkuva, Amirhossein Taghvaei, Sewoong Oh, and Jason D Lee. Optimal transport mapping via input convex neural networks. *arXiv preprint arXiv:1908.10962*, 2019.

[36] Alberto Maria Metelli, Amarildo Likmeta, and Marcello Restelli. Propagating uncertainty in reinforcement learning via wasserstein barycenters. In *33rd Conference on Neural Information Processing Systems, NeurIPS 2019*, pages 4335–4347. Curran Associates, Inc., 2019.

[37] Petr Mokrov, Alexander Korotin, Lingxiao Li, Aude Genevay, Justin Solomon, and Evgeny Burnaev. Large-scale wasserstein gradient flows. *arXiv preprint arXiv:2106.00736*, 2021.

[38] Eduardo Fernandes Montesuma and Fred Maurice Ngole Mboula. Wasserstein barycenter for multi-source domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16785–16793, 2021.

[39] Youssef Mroueh. Wasserstein style transfer. *arXiv preprint arXiv:1905.12828*, 2019.

[40] Horea Mureşan and Mihai Oltean. Fruit recognition from images using deep learning. *arXiv preprint arXiv:1712.00580*, 2017.

[41] Quan Hoang Nhan Dam, Trung Le, Tu Dinh Nguyen, Hung Bui, and Dinh Phung. Threeplayer Wasserstein GAN via amortised duality. In *Proc. of the 28th Int. Joint Conf. on Artificial Intelligence (IJCAI)*, 2019.

[42] Quentin Paris. Online learning with exponential weights in metric spaces. *arXiv preprint arXiv:2103.14389*, 2021.

[43] Gabriel Peyré, Marco Cuturi, et al. Computational optimal transport. *Foundations and Trends® in Machine Learning*, 11(5-6):355–607, 2019.

[44] Julien Rabin, Sira Ferradans, and Nicolas Papadakis. Adaptive color transfer with relaxed optimal transport. In *2014 IEEE International Conference on Image Processing (ICIP)*, pages 4852–4856. IEEE, 2014.

[45] Julien Rabin, Gabriel Peyré, Julie Delon, and Marc Bernot. Wasserstein barycenter and its application to texture mixing. In *International Conference on Scale Space and Variational Methods in Computer Vision*, pages 435–446. Springer, 2011.

[46] R Tyrrell Rockafellar. Integral functionals, normal integrands and measurable selections. In *Nonlinear operators and the calculus of variations*, pages 157–207. Springer, 1976.

[47] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[48] Litu Rout, Alexander Korotin, and Evgeny Burnaev. Generative modeling with optimal transport maps. *arXiv preprint arXiv:2110.02999*, 2021.

[49] Filippo Santambrogio. Optimal transport for applied mathematicians. *Birkäuser, NY*, 55(58-63):94, 2015.

[50] Vivien Seguy, Bharath Bhushan Damodaran, Rémi Flamary, Nicolas Courty, Antoine Rolet, and Mathieu Blondel. Large-scale optimal transport and mapping estimation. *arXiv preprint arXiv:1711.02283*, 2017.

[51] Dror Simon and Aviad Aberdam. Barycenters of natural images constrained wasserstein barycenters for image morphing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7910–7919, 2020.

[52] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[53] Justin Solomon, Fernando De Goes, Gabriel Peyré, Marco Cuturi, Adrian Butscher, Andy Nguyen, Tao Du, and Leonidas Guibas. Convolutional Wasserstein distances: Efficient optimal transportation on geometric domains. *ACM Transactions on Graphics (TOG)*, 34(4):1–11, 2015.

[54] Sanvesh Srivastava, Volkan Cevher, Quoc Dinh, and David Dunson. Wasp: Scalable bayes via barycenters of subset posteriors. In *Artificial Intelligence and Statistics*, pages 912–920, 2015.

[55] Sanvesh Srivastava, Cheng Li, and David B Dunson. Scalable bayes via barycenter in Wasserstein space. *The Journal of Machine Learning Research*, 19(1):312–346, 2018.

[56] Thomas Staudt, Shayan Hundrieser, and Axel Munk. On the uniqueness of kantorovich potentials. *arXiv preprint arXiv:2201.08316*, 2022.

[57] Amirhossein Taghvaei and Amin Jalali. 2-Wasserstein approximation via restricted convex potentials with application to improved training for GANs. *arXiv preprint arXiv:1902.07197*, 2019.

[58] Cédric Villani. *Topics in optimal transportation*. Number 58. American Mathematical Soc., 2003.

[59] Cédric Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

[60] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

[61] Yujia Xie, Minshuo Chen, Haoming Jiang, Tuo Zhao, and Hongyuan Zha. On scalable and efficient computation of large scale optimal transport. volume 97 of *Proceedings of Machine Learning Research*, pages 6882–6892, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

[62] Aron Yu and Kristen Grauman. Fine-grained visual comparisons with local learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 192–199, 2014.