LIFELONG LEARNING WITH OUTPUT KERNELS

ABSTRACT

Lifelong learning poses considerable challenges in terms of effectiveness (minimizing prediction errors for all tasks) and overall computational tractability for real-time performance. This paper addresses continuous lifelong multitask learning by jointly re-estimating the inter-task relations and the per-task model parameters at each streaming cycle, assuming data arrives in an online fashion. A novel Online Output Kernel Learning Algorithm (OOKLA) for lifelong learning setting is proposed, as are robust budget-limited versions thereof. In addition, we propose a two-stage budgeted scheme for efficiently tackling the task-specific budget constraints in lifelong learning. Our empirical results over three datasets indicate superior AUC performance for OOKLA and its budget-limited cousins over strong baselines.

1 INTRODUCTION

The power of joint learning in multiple tasks arises from the transfer of relevant knowledge across said tasks, especially from information-rich tasks to information-poor ones. Instead of learning individual models, multi-task methods leverage the relationships between tasks to jointly build a better model for each task. Most existing work in multi-task learning focuses on how to take advantage of these task relationships, either to share data directly Crammer & Mansour (2012) or to learn model parameters via cross-task regularization techniques Argyriou et al. (2008); Xue et al. (2007); Zhang & Yeung (2014); Kshirsagar et al. (2015), or to embed tasks into a common space Moon & Carbonell (2017). In a broad sense, there are two settings to learn these task relationships 1) batch learning, in which an entire training set is available to the learner 2) online learning, in which the learner sees the data in a sequential fashion. In recent years, online multi-task learning has attracted extensive research attention Abernethy et al. (2007); Dekel et al. (2007); Lugosi et al. (2009); Cavallanti et al. (2010); Saha et al. (2011).

Following the online setting, particularly from Dekel et al. (2007); Lugosi et al. (2009), at each round t, the learner *receives* a set of n observations from K tasks and *predicts* the output label for each of these observations. Subsequently, the learner receives the true labels and *updates* the model(s) as necessary. This process is repeated as additional data streams in, or simulating streaming data from a given dataset. Our approach follows an error-driven update rule in which the model for a given task is updated only when the prediction for that task is in error. The goal of an online learner is to minimize errors compared to the full hindsight learner. The key challenge in online learning with a large number of tasks is to adaptively learn the model parameters and the task relationships, which potentially change over time. Without manageability-efficient updates at each round, learning the task relationship matrix automatically may impose a severe computational burden. In other words, we need to make predictions and update the models in an efficient real time manner.

We propose an online learning framework that *efficiently* learns multiple related tasks by estimating the task relationship matrix from the data, along with the model parameters for each task. We learn the model for each task by sharing data from related tasks directly. Our model provides a natural way to specify the trade-off between learning the hypothesis from each task's own (possibly quite limited) data and shared data from multiple related tasks. We propose an iterative algorithm to learn the task parameters and the task-relationship matrix alternatively. We first describe our proposed approach under a batch setting and then extend it to the online learning paradigm. In addition, we provide a theoretical analysis for our online algorithm and show that it can achieve a sub-linear regret compared to the best linear predictor in hindsight. We evaluate our model with several state-of-the-art online learning algorithms for multiple tasks.

There are many useful application areas for online multi-task learning, including optimizing financial trading, email prioritization, personalized news, and spam filtering. Consider the latter, where some spam is universal to all users (e.g. financial scams), some messages might be useful to certain affinity groups, but spam to most others (e.g. announcements of meditation classes or other special interest activities), and some may depend on evolving user interests. In spam filtering each user is a "task," and shared interests and dis-interests formulate the inter-task relationship matrix. If we can learn the matrix as well as improving models from specific spam/not-spam decisions, we can perform mass

customization of spam filtering, borrowing from spam/not-spam feedback from users with similar preferences. The primary contribution of this paper is precisely the joint learning of inter-task relationships and its use in estimating per-task model parameters in an online setting.

1.1 RELATED WORK

Most existing work in online learning of multiple task focuses on how to take advantage of task relationships. To achieve this, Lugosi et. al Lugosi et al. (2009) imposed a hard constraint on the K simultaneous actions taken by the learner in the expert setting, Agarwal et. al Agarwal et al. (2008) used matrix regularization, and Dekel et. al Dekel et al. (2007) proposed a global loss function, as an absolute norm, to tie together the loss values of the individual tasks. Different from existing online multi-task learning models, our paper proposes an intuitive and efficient way to learn the task relationship matrix automatically from the data, and to explicitly take into account the learned relationships during model updates.

Cavallanti et. al Cavallanti et al. (2010) assumes that task relationships are available *a priori*. However such task-relation prior knowledge is either unavailable or infeasible to obtain for many applications especially when the number of tasks K is large Weinberger et al. (2009) and/or when the manual annotation of task relationships is expensive Kshirsagar et al. (2013). Saha et. al Saha et al. (2011) formulated the learning of task relationship matrix as a Bregman-divergence minimization problem w.r.t. positive definite matrices. The model suffers from high computational complexity as semi-definite programming is required when updating the task relationship matrix at each online round. We show that with a different formulation, we can obtain a similar but much cheaper updating rule for learning the inter-task weights.

Recent works in output kernel learning learn task covariance matrix in RKHS space, inferred directly from the data Dinuzzo et al. (2011); Sindhwani et al. (2013); Jawanpuria et al. (2015). The task covariance matrix is called the output kernel defined on the tasks, similar to the scalar kernel on the inputs. Most recently, Jawanpuria et al. (2015) showed that for a class of regularization functions, we can efficiently learn this output kernel. But most of the proposed methods for learning output kernels are for the batch setting, which requires access to the entire data for the learning algorithm, a luxury unavailable for the lifelong learning setting.

Unlike in online multitask learning, most lifelong learning approaches use a single model for all the tasks or reuse the models from the previous tasks to build a model for the new task Alquier et al. (2016); Pentina & Urner (2016); Pentina & Ben-David (2015); Balcan et al. (2015); Rusu et al. (2016); Hinton et al. (2015); Rebuffi et al. (2016). These approaches increases the computation time on iterations where we encounter a novel task. To the best of our knowledge, relationship between the tasks has not been explicitly learned in the lifelong learning setting due to the difficulty in learning a positive semi-definite task relationship matrix in large-scale applications. This paper provides an efficient way to learn the task relationship matrix in the lifelong learning setting.

2 LIFELONG LEARNING OF MULTIPLE TASKS

Let $((x_t, i_t), y_t)$ be the example received by the learner from the task i_t (at the time step t) where we assume that the $x_t \in \mathcal{X}$ and y_t is its corresponding true label. The task i_t can be a new task or seen by the learner in the previous iterations. We denote by $[N]$ the consecutive integers ranging from 1 to N. In this paper, we do not assume that the number of tasks is known to the learner ahead of time, an important constraint in lifelong learning problems. Let K be the number of tasks seen so far until the current iteration t.

For brevity, we consider a binary classification problem for each task $y_t \in \{-1, +1\}$, but the methods generalize to multi-class and are also applicable to regression tasks. We assume that the learner made a mistake if $y_t \neq \hat{y}_t$ where $\hat{y}_t$ is the predicted label. Our approach follows a mistake-driven update rule in which the model for a given task is updated only on rounds where the learner made a mistake.

Let $\mathcal{K} : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ (kernel on *input* space) and $\Omega : \mathbb{N} \times \mathbb{N} \to \mathbb{R}$ (*output* kernel) be symmetric, positive semi-definite (p.s.d) multitask kernel functions and denote $\mathcal{H}$ as their corresponding RKHS of functions with the norm $\| \cdot \|_{\mathcal{H}}$ on multitask examples (Smola & Schölkopf (1998); Dinuzzo et al. (2011); Jawanpuria et al. (2015)). Using the above notation, we can define a kernel representation of an example based on a set of representative examples collected on the previous iterations (*prototypes*). Formally, given an example $x \in \mathcal{X}$, its kernel representation can be written using this set:

$$x \longmapsto \{\mathcal{K}(x, x_s) : s \in \mathcal{S}\}$$

$\mathcal{S}$ is the set of stored examples for which the learner made a mistake in the past. The set $\mathcal{S}$ is called the *support set*. The online classification function is then defined as the weighted sum of the kernel combination of the examples in the support set. To account for the examples from the different tasks, we consider both the kernel on the input spaces $\mathcal{K}$ and

---

Algorithm 1: Online Output Kernel Learning Algorithm

Initialize: $\mathcal{S} = \emptyset$, $\mathbf{\Omega}$
For $t = 1, 2, \cdots$
    Receive new example (x_t, i_t)
    Let $f_{i_t} = \sum_{(x_s, i_s) \in \mathcal{S}} y_s \Omega_{i_s i_t} \phi(x_s)$
    Predict $\hat{y}_t = sign(f_{i_t}(x_t))$
    Receive label y_t
    If $y_t \neq \hat{y}_t$
        $\mathcal{S} \leftarrow \mathcal{S} \cup (x_t, i_t)$
        Update $\Omega_{i_t k} \forall k \in [K]$

$$\Omega_{i_t k} \leftarrow \Omega_{i_t k} + \frac{1}{\lambda} \sum_{\substack{(x_s, i_s) \in \mathcal{S} \\ i_s = k}} y_t \mathcal{K}(x_t, x_s) y_s \qquad (2)$$

$$(or)$$

$$\Omega_{i_t k} \leftarrow \Omega_{i_t k} \exp \left\{ \frac{1}{\lambda} \sum_{\substack{(x_s, i_s) \in \mathcal{S} \\ i_s = k}} y_t \mathcal{K}(x_t, x_s) y_s \right\} \qquad (3)$$

    end
end

---

the output kernel Ω in our classification function.

$$f(\cdot) = \sum_{(x_s, i_s) \in \mathcal{S}} \alpha_s \Omega_{i_s \cdot} \phi(x_s) \qquad (1)$$

We set $\alpha_s = y_s$. The predicted label for a new example is computed from the linear combination of the labels of the examples from the support set $\mathcal{S}$ weighted by their input similarity $\mathcal{K}$ and the task similarity Ω to the new example. Using the *kernel trick*, one can write:

$$f((x_t, i_t)) = \langle \phi(x_t) \sum_{(x_s, i_s) \in \mathcal{S}} \alpha_s \Omega_{i_s i_t} \phi(x_s) \rangle = \sum_{(x_s, i_s) \in \mathcal{S}} \alpha_s \Omega_{i_s i_t} \mathcal{K}(x_s, x_t)$$

Note that, in the above representation, we need learn both the support set $\mathcal{S}$ and the output kernel Ω from the data. As explained in the previous section, for a successful lifelong learning with kernels, we need to address two key challenges: (1) learn the relationships between the tasks (output kernel) efficiently from the data arriving in an online fashion and (2) bound the size of the *support* set $\mathcal{S}$ to avoid memory explosion. We address these two challenges in the following sections.

2.1 ONLINE OUTPUT KERNEL LEARNING

Our objective function for the lifelong learning problem is given as follows:

$$\min_{\Omega \in S_+, f \in \mathcal{H}} \sum_t \ell(y_t, f((x_t, i_t))) + \frac{1}{2} \|f\|_{\mathcal{H}}^2 + \lambda \mathcal{R}(\Omega) \qquad (4)$$

where $\ell(\cdot)$ is some loss function such as hinge loss or logistic loss, $\mathcal{R}(\cdot)$ is the regularization on the task relationship matrix Ω and λ is the regularization parameter. Note that f in the above equation depends on Ω. In order to reduce the time taken for each time-step, we require an efficient update to the task relationship matrix Ω. Following the work of Jawanpuria et al. (2015) in the batch setting, we consider a subset of regularization functions $\mathcal{R}$ for which we can efficiently learn the task covariance matrix. Consider the dual function of the above equation, at time-step t (see Barzilai & Crammer (2015); Jawanpuria et al. (2015)):

$$\max_{\Omega \in S_+} \frac{1}{2} \sum_k \sum_{\substack{(x_s, i_s) \in \mathcal{S} \\ i_s = k}} \alpha_t \mathcal{K}(x_t, x_s) \alpha_s \Omega_{i_t k} - \lambda \mathcal{R}(\Omega, \Omega_{(t-1)}) \qquad (5)$$

When we consider entry-wise l_p norm between Ω and $\Omega_{(t-1)}$ from the previous iteration as our regularization i.e., $\mathcal{R}(\Omega, \Omega_{(t-1)}) = \sum_k |\Omega_{i_t k} - (\Omega_{(t-1)})_{i_t k}|^p$ for $p \geq 1$ [1], we get the update function in Equation 2. Similarly, if we consider generalized KL-divergence between Ω and $\Omega_{(t-1)}$ i.e., $\mathcal{R}(\Omega, \Omega_{(t-1)}) = \sum_k \Omega_{i_t k} \log \frac{\Omega_{i_t k}}{(\Omega_{(t-1)})_{i_t k}} - \Omega_{i_t k} + (\Omega_{(t-1)})_{i_t k}$, we get the update function in Equation 3. Unlike in the previous works, we update only the row (and the corresponding column) of the task relationship matrix Ω specific to the task i_t, which significantly reduces the time taken per example.

We can see that the update equations are simple and quite intuitive. For a given new example (x_t, i_t) at round t, the algorithm updates $\Omega_{i_t k}$ (for some $k \in [K]$) by computing the similarity between the new example and the examples in the support set $\mathcal{S}$ that belongs to the task k. If the two examples have similar (different) labels and high similarity $\mathcal{K}(x_t, x_s)$, then the $\Omega_{i_t k}$ is increased to reflect the positive (negative) correlation and vice versa. The value closer to 0 implies no significant relationship between the tasks. The update to the $\Omega_{i_t k}$ is normalized by the regularization parameter λ for scaling.

It is worth noting that our update equations does not violate the *p.s.d* constraints on Ω in Equation 5. If Ω from the previous iteration is a *p.s.d* matrix and the update is a *p.s.d* matrix (as it is computed using the Gram matrix of the example from the previous iteration), the sum and Hadamard product of two *p.s.d* matrices satisfy the *p.s.d* constraint (using Schur Product Theorem).

Algorithm 1 outlines the key steps in our proposed method. We write $f((x_t, i_t))$ as $f_{i_t}(x_t)$ for notational convenience. At each time-step t, the learner *receives* an example $x_t \in \mathcal{X}$ and *predicts* the output label y_t using $\hat{y}_t = sign(f_{i_t}(x_t))$. We update both the support set $\mathcal{S}$ and the output kernel Ω_{i_t} when the learner makes a mistake.

Algorithm 2: Budgeted OOKLA

Initialize: $\mathcal{S} = \emptyset$, $\mathbf{\Omega}$
For $t = 1, 2, \cdots$
    Receive new example (x_t, i_t)
    Let $f_{i_t} = \sum_{(x_s, i_s) \in \mathcal{S}} y_s \Omega_{i_s i_t} \phi(x_s)$
    Predict $\hat{y}_t = sign(f_{i_t}(x_t))$
    Receive label y_t
    If $y_t \neq \hat{y}_t$
        If $|\mathcal{S}| < B$
            $\mathcal{S} \leftarrow \mathcal{S} \cup (x_t, i_t)$
        Else
            Find an example to remove

$$\arg\max_{(x_r, i_r) \in \mathcal{S}} \sum_{k \in [K]} \Omega_{i_r k}[y_r(f_k - y_r \Omega_{i_r k}\phi(x_r))\phi(x_r)]$$
(6)

            $\mathcal{S} \leftarrow \mathcal{S} \cup (x_t, i_t) \setminus (x_r, i_r)$
        end
        Update $\Omega_{i_t k} \forall k \in [K]$ as in Algorithm 1.
    end
end

Algorithm 3: Two-Stage Budgeted Learning

Initialize: $\mathcal{S} = \emptyset$, $\mathcal{T}_k = \emptyset$, $k \in [K]$, $\mathbf{\Omega}$
For $t = 1, 2, \cdots$
    Receive new example (x_t, i_t)
    Let $f_{i_t} = \sum_{(x_s, i_s) \in \mathcal{T}_{i_t}} y_s \Omega_{i_s i_t} \phi(x_s)$
    Predict $\hat{y}_t = sign(f_{i_t}(x_t))$
    Receive label y_t
    If $y_t \neq \hat{y}_t$
        $\mathcal{S} \leftarrow \mathcal{S} \cup \{t\} \setminus \{r\}$
        `/* r=∅ if |S| < B, else choose r`
        `    using Equation 6  */`
        For $k \in [K]$
            $\mathcal{T}_k \leftarrow \mathcal{T}_k \cup \{l\} \setminus \{r\}$
            `/* remove r from T_k; choose l`
            `    from S − T_k  */`
        end
        Update $\Omega_{i_t k} \forall k \in [K]$ as in Algorithm 1.
    end
end

2.2 Budgeted Learning

In Algorithm 1, we can see that both the classification function *f* and the update equations for Ω uses the support set $\mathcal{S}$. When the target function changes over time, the support set $\mathcal{S}$ grows unboundedly. This leads to serious computational and runtime issues especially in the lifelong learning setting. The most common solution to this problem is to impose a bound on the number of examples in the support set $\mathcal{S}$. There are several budget maintenance strategies proposed recently (Cavallanti et al. (2007); Dekel et al. (2008); Orabona et al. (2008)). Unfortunately these schemes cannot be directly used in our setting due to the output kernels in our learning formulation. Cavallanti & Cesa-Bianchi (2012) proposed the multitask variant of these schemes but they are impractical for the lifelong learning setting. We follow a simple support set removal schemes based on Crammer et al. (2004). In single-task setting, when the number of examples in the support set $\mathcal{S}$ exceeds the limit (say B), a simple removal scheme chooses an example x_r with the

---

[1] We set $p = 2$ in this paper.

highest confidence from $\mathcal{S}$. The confidence of an example x_r is measured using $y_r f(x_r)$ after removing x_r from the support set $\mathcal{S}$.

$$\arg \max_{x_r \in \mathcal{S}} \left[y_r \left(f - y_r \phi(x_r) \right) \phi(x_r) \right] \tag{7}$$

We can extend the above approach to the multitask and lifelong learning settings. Since the support set $\mathcal{S}$ is shared by all the tasks, we choose an example x_r with high confidence to remove from each task function f_k, weighted by the relationship between the tasks. The objective function to choose the example is shown in Equation 6. We show in the experiment section, this simple approach is efficient and performs significantly better than the state-of-the-art budget maintenance strategies. Algorithm 2 shows pseudocode of the proposed budgeted learning algorithm.

2.2.1 Two-Stage Budgeted Learning

In lifelong learning setting, the number of tasks is typically large. The support set $\mathcal{S}$ has hundreds of examples from all the tasks. Each task does not use all the examples from the support set $\mathcal{S}$. For example, in movie recommendations task, recommendation for each user (task) can be characterized by just a few movies (subset of examples) in the support set $\mathcal{S}$. Motivated by this observation, we propose a two-stage budgeted learning algorithm for the lifelong learning setting.

Algorithm 3 shows pseudocode of the proposed two-stage budgeted learning algorithm. In addition to the support set $\mathcal{S}$, we maintain task-specific support set $\mathcal{T}_k$. We choose the budget for each task (say L) where $L <<< B$. Similar to the removal strategies for $\mathcal{S}$, we remove an example from $\mathcal{T}_k$ when $|\mathcal{T}_k| > L$ and replace with an example from the set $\mathcal{S} - \mathcal{T}_k$. One may consider a different budget size for each task L_k based on the complexity of the task. In addition, the proposed two-stage budgeted learning algorithm provides an alternative approach to using state-of-the-art budget maintenance strategies. For example, it is easier to use the Projectron algorithm (Orabona et al. (2008)) on $\mathcal{T}_k$, rather than on $\mathcal{S}$. We will explore this line of research in our future work.

3 Experiments

We evaluate the performance of our algorithm under batch and online settings. All reported results in this section are averaged over 10 random runs or permutations of the training data. Unless otherwise specified, all model parameters are chosen via 5-fold cross validation.

3.1 Benchmark Datasets

We use three datasets for our experiments. Details are given below:

Newsgroups Dataset[2] consists of 20 tasks generated from two subject groups: *comp* and *talk.politics*. We paired two newsgroups, one from each subject (e.g.,comp.graphics vs talk.politics.guns), for each task. In order to account for positive/negative correlation between the tasks, we randomly choose one of the newsgroups as positive $(+)$ or negative $(-)$ class. Each post in a newsgroup is represented by a vocabulary of approximately $60K$ unique features.

Spam Dataset[3] We use the dataset obtained from ECML PAKDD 2006 Discovery challenge for the spam detection task. We used the task B challenge dataset which consists of labeled training data from the inboxes of 15 users. We consider each user as a single task and the goal is to build a personalized spam filter for each user. Each task is a binary classification problem: spam $(+)$ or non-spam $(-)$ and each example consists of approximately $150K$ features representing term frequency of the word occurrences. Since some spam is universal to all users (e.g. financial scams), some messages might be useful to certain affinity groups, but spam to most others. Such adaptive behavior of user's interests and dis-interests can be modeled efficiently by utilizing the data from other users to learn per-user model parameters.

Sentiment Dataset[4]We evaluated our algorithm on product reviews from amazon. The dataset contains product reviews from 25 domains. We consider each domain as a binary classification task. Reviews with rating > 3 were labeled positive $(+)$, those with rating < 3 were labeled negative $(-)$, reviews with rating = 3 are discarded as the sentiments were ambiguous and hard to predict. Similar to the previous datasets, each example consists of approximately $350K$ features representing term frequency of the word occurrences.

We choose 2000 examples (100 posts per task) for *20 Newsgroups*, 1500 emails for *spam* (100 emails per user inbox) and 2500 reviews for *sentiment* (100 reviews per domain) for our experiments. Note that we intentionally kept the size

---

[2]http://qwone.com/~jason/20Newsgroups/
[3]http://ecmlpkdd2006.org/challenge.html
[4]http://www.cs.jhu.edu/~mdredze/datasets/sentiment

Table 1: Average performance on three datasets: means and standard (test set) scores over 10 random shuffles.

Models	Newsgroups			Spam			Sentiment		
	AUC	*nSV*	*Time (s)*	*AUC*	*nSV*	*Time (s)*	*AUC*	*nSV*	*Time (s)*
Perceptron	0.7974 (0.01)	1421.6	8.36	0.8621 (0.01)	1110.0	9.23	0.6363 (0.01)	1018.8	255.3
PA	0.7633 (0.02)	1926.6	9.89	0.8394 (0.01)	1482.1	11.5	0.5321 (0.01)	2500.0	357.7
FOML	0.7830 (0.01)	1592.0	18.46	**0.8803** (0.01)	1228.2	16.0	0.6484 (0.01)	1030.0	266.0
OMTRL	0.7694 (0.01)	1560.4	72.36	0.8583 (0.01)	1266.3	45.4	0.5651 (0.01)	1057.6	328.2
OSMTL	0.7969 (0.02)	1426.2	18.18	0.8611 (0.01)	1115.1	17.3	0.6425 (0.01)	1021.8	264.3
OOKLA-*sum*	**0.8512** (0.02)	884.9	15.58	**0.8825** (0.01)	833.4	17.3	0.6261 (0.01)	925.0	306.6
OOKLA-*exp*	0.8382 (0.02)	886.9	15.50	**0.8819** (0.01)	1062.5	19.2	**0.6731** (0.01)	882.2	302.8

of the training data small to drive the need for learning from other tasks, which diminishes as the training sets per task become large. Since these datasets have a class-imbalance issue (with few $(+)$ examples as compared to $(-)$ examples), we use average Area Under the ROC Curve (AUC) as the performance measure.

3.2 RESULTS

To evaluate the performance of our proposed algorithm (*OOKLA*), we use the three datasets (*Newsgroups*, *Spam* and *Sentiment*) for evaluation and compare our proposed methods to 5 baselines. We implemented Perceptron and Passive-Aggressive algorithm (*PA*) Crammer et al. (2006) for online multitask learning. Both Perceptron and *PA* learns independent model for each task. These two baselines do not exploit the task-relationship or the data from other tasks during model update. Next, we implemented two online multitask learning related to our approach: *FOML* – initializes Ω with fixed weights Cavallanti et al. (2010), Online Multitask Relationship Learning (*OMTRL*) Saha et al. (2011) – learns a task covariance matrix along with task parameters. Since *OMTRL* requires expensive call to SVD routines, we update the task-relationship matrix every 50 iterations. In addition, we compare our proposed methods against the performance of Online Smooth Multitask Learning (*OSMTL*) which learn a probabilistic distribution over all tasks, and adaptively refining such distribution over time Murugesan et al. (2016). We implement two versions of our proposed algorithm with different updates for the task-relationship matrix: *OOKLA-sum* (OOKLA with sum update) *OOKLA-exp* (OOKLA with exponential update) as shown in Algorithm 1.

Table 1 summarizes the performance of all the above algorithms on the three datasets. In addition to the AUC scores, we report the average total number of support vectors (*nSV*) and the CPU time taken for learning from one instance (*Time*).

From the table, it is evident that both OOKLA-*sum* and OOKLA-*exp* outperform all the baselines in terms of both AUC and *nSV*. This is expected for the two default baselines (*Perceptron* and *PA*). The update rule for *FOML* is similar to ours but using fixed weights. The results justify our claim that learning the task-relationship matrix adaptively leads to improved performance. As expected, both *OOKLA* and *OSMTL* consume less or comparable CPU time than the baselines which take into account for learning inter-task relationships. Unlike in the *OMTRL* algorithm that recomputes the task covariance matrix every (50) iteration using expensive SVD routines, the task-relationship matrix in our proposed methods (and *OSMTL*) are updated independently for each task. We implement the *OSMTL* with exponential update for our experiments as it have shown to perform better than the other baselines. One of the major drawbacks of *OSMTL* is that it learn only the positive correlations between the tasks. The performance of *OSMTL* worsens when the tasks are negatively correlated. As we can see from the table, our proposed methods outperform *OSMTL* significantly in the 20Newsgroup dataset.

Table 2 compares the proposed methods with different budget schemes and budget sizes in terms of test set AUC scores and the runtime. We use *OOKLA-sum* for this experiment. We set the value of B to $\{50, 100, 150\}$ for all the datasets. We compare our proposed budgeted learning algorithm (Algorithm 2) with the following state-of-the-art algorithm for online budget learning: (1) Random Budgeted Perceptron (RBP) Cavallanti et al. (2007)- randomly chooses an

Table 2: Evaluation of proposed methods with different budgets: means and standard AUC (test set) scores over 10 random shuffles.

Models	Newsgroups			Spam			Sentiment		
Budget *(B)*	*50*	*100*	*150*	*50*	*100*	*150*	*50*	*100*	*150*
RBP	0.6272 (0.07) 6.5s	0.6954 (0.03) 6.4s	0.7373 (0.01) 7.4s	0.6426 (0.06) 14.5s	0.7197 (0.03) 18.5s	0.7536 (0.04) 16.3s	0.5679 (0.02) 1772.4s	0.5790 (0.02) 1666.9s	0.5889 (0.02) 1860.2s
Forgetron	0.6353 (0.07) 9.1s	0.6860 (0.05) 8.6s	0.7240 (0.01) 9.9s	0.6546 (0.06) 20.5s	0.7403 (0.04) 21.4s	0.7339 (0.04) 21.9s	0.5579 (0.02) 2219.1s	0.5847 (0.02) 2097.0s	0.6195 (0.02) 2272.6s
Projectron	0.6399 (0.03) 16.7s	0.6984 (0.02) 16.6s	0.6986 (0.02) 17.6s	0.6352 (0.03) 24.7s	0.6041 (0.05) 26.1s	0.6402 (0.05) 27.9s	0.5215 (0.01) 2712.0s	0.5187 (0.01) 2622.5s	0.5221 (0.02) 2804.5s
Budget -OKL	0.6810 (0.02) 6.3s	0.7106 (0.03) 10.2s	0.7499 (0.03) 13.4s	0.6472 (0.03) 18.8s	0.6471 (0.03) 22.6s	0.6552 (0.04) 24.7s	0.5683 (0.02) 1708.8s	0.5732 (0.01) 1674.4s	0.6153 (0.01) 1935.2s
Budget -OOKLA	**0.7576** (0.04) 9.9s	**0.7562** (0.04) 11.7s	**0.7749** (0.03) 14.1s	**0.7485** (0.08) 20.1s	**0.7969** (0.04) 24.3s	**0.8472** (0.02) 26.9s	**0.6117** (0.06) 2250.5s	**0.6901** (0.01) 2073.0s	**0.7000** (0.04) 2334.3.3s

example to remove (2) (Self-tuned) Forgetron Dekel et al. (2008)- forgets the oldest example (3) Projectron++ Orabona et al. (2008)- projects the new example on the others (4) Budgeted Online Kernel learning (Budget-OKL)- removes an example using equation 7 (5) Budgeted Online Output Kernel Learning (Budget-OOKLA)- removes an example using equation 6. Following Cavallanti & Cesa-Bianchi (2012), we implement the multitask version of RBP, Forgetron and Projectron for our experiments.

Table 2 shows both the test set AUC scores (first line) and time taken for learning from one instance (including the removal step). It is evident from the table, our proposed budgeted learning algorithm for online multitask learning outperforms the other state-of-the-art budget schemes on most settings. Our proposed algorithm uses the relationship between the tasks efficiently to choose the next example for removal.

Figure 1: Average rate of mistakes calculated for different values of L.

Figure 1 shows the average rate of mistakes on *newsgroup* dataset for different values of L. We fix the value of $B = 50$. As we can see from the figure, even for the small values of L (say 15), the mistake rate is close to the model which uses all the examples from the support set $\mathcal{S}$. On average, we achieved 36% improvement in running time compared to the budget maintenance scheme in Algorithm 2.

4 CONCLUSIONS

We proposed a novel lifelong learning algorithm using output kernels. The proposed method efficiently learns both the model and the inter-task relationships at each iteration. Our update rules for learning the task relationship matrix, at each iteration, were motivated by the recent work in output kernel learning. In order to handle the memory explosion from the unbounded support set in lifelong learning setting, we proposed a novel budget maintenance scheme that utilize the task relationship matrix to remove the least-useful (high confidence) example from the support set. In addition, we proposed two-stage budget learning scheme based on the intuition that each task only requires a subset of the representative examples in the support set for efficient learning. It provides a competitive and efficient approach to handle large number of tasks in many real-life applications. Effectiveness of our algorithm is empirically verified over several benchmark datasets, outperforming several competitive baselines both in the unconstrained case and the budget-limited case, where selective forgetting was required. Future research includes other forms of budget limits (e.g. time or reprocessing capacity), more complex inter-task relationships (e.g. hierarchical), and additional factors such as task reliability (e.g. prefer transferring from a well-trained related task, vs from a relatively data-sparse one, whose model is less reliable).

REFERENCES

Jacob Abernethy, Peter Bartlett, and Alexander Rakhlin. Multitask learning with expert advice. In *Learning Theory*, pp. 484–498. Springer, 2007.

Alekh Agarwal, Alexander Rakhlin, and Peter Bartlett. Matrix regularization techniques for online multitask learning. *EECS Department, University of California, Berkeley, Tech. Rep. UCB/EECS-2008-138*, 2008.

Pierre Alquier, The Tien Mai, and Massimiliano Pontil. Regret bounds for lifelong learning. *arXiv preprint arXiv:1610.08628*, 2016.

Andreas Argyriou, Theodoros Evgeniou, and Massimiliano Pontil. Convex multi-task feature learning. *Machine Learning*, 73(3):243–272, 2008.

Maria-Florina Balcan, Avrim Blum, and Santosh Vempala. Efficient representations for lifelong learning and autoencoding. In *Conference on Learning Theory*, pp. 191–210, 2015.

Aviad Barzilai and Koby Crammer. Convex multi-task learning by clustering. In *Proceedings of the 18th International Conference on Artificial Intelligence and Statistics (AISTATS-15)*, 2015.

Giovanni Cavallanti and Nicolo Cesa-Bianchi. Memory constraint online multitask classification. *arXiv preprint arXiv:1210.0473*, 2012.

Giovanni Cavallanti, Nicolo Cesa-Bianchi, and Claudio Gentile. Tracking the best hyperplane with a simple budget perceptron. *Machine Learning*, 69(2-3):143–167, 2007.

Giovanni Cavallanti, Nicolo Cesa-Bianchi, and Claudio Gentile. Linear algorithms for online multitask classification. *The Journal of Machine Learning Research*, 11:2901–2934, 2010.

Koby Crammer and Yishay Mansour. Learning multiple tasks using shared hypotheses. In *Advances in Neural Information Processing Systems*, pp. 1475–1483, 2012.

Koby Crammer, Jaz Kandola, and Yoram Singer. Online classification on a budget. In *Advances in neural information processing systems*, pp. 225–232, 2004.

Koby Crammer, Ofer Dekel, Joseph Keshet, Shai Shalev-Shwartz, and Yoram Singer. Online passive-aggressive algorithms. *The Journal of Machine Learning Research*, 7:551–585, 2006.

Ofer Dekel, Philip M Long, and Yoram Singer. Online learning of multiple tasks with a shared loss. *Journal of Machine Learning Research*, 8(10):2233–2264, 2007.

Ofer Dekel, Shai Shalev-Shwartz, and Yoram Singer. The forgetron: A kernel-based perceptron on a budget. *SIAM Journal on Computing*, 37(5):1342–1372, 2008.

Francesco Dinuzzo, Cheng S Ong, Gianluigi Pillonetto, and Peter V Gehler. Learning output kernels with block coordinate descent. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pp. 49–56, 2011.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Pratik Jawanpuria, Maksim Lapin, Matthias Hein, and Bernt Schiele. Efficient output kernel learning for multiple tasks. In *Advances in Neural Information Processing Systems*, pp. 1189–1197, 2015.

Meghana Kshirsagar, Jaime Carbonell, and Judith Klein-Seetharaman. Multitask learning for host–pathogen protein interactions. *Bioinformatics*, 29(13):i217–i226, 2013.

Meghana Kshirsagar, Sylvia Schleker, Jaime Carbonell, and Judith Klein-Seetharaman. Techniques for transferring host-pathogen protein interactions knowledge to new tasks. *Frontiers in microbiology*, 6, 2015.

Gábor Lugosi, Omiros Papaspiliopoulos, and Gilles Stoltz. Online multi-task learning with hard constraints. *arXiv preprint arXiv:0902.3526*, 2009.

Seungwhan Moon and Jaime Carbonell. Completely heterogeneous transfer learning with attention-what and what not to transfer. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, 2017.

Keerthiram Murugesan, Hanxiao Liu, Jaime Carbonell, and Yiming Yang. Adaptive smoothed online multi-task learning. In *Advances in Neural Information Processing Systems*, pp. 4296–4304, 2016.

Francesco Orabona, Joseph Keshet, and Barbara Caputo. The projectron: a bounded kernel-based perceptron. In *Proceedings of the 25th international conference on Machine learning*, pp. 720–727. ACM, 2008.

Anastasia Pentina and Shai Ben-David. Multi-task and lifelong learning of kernels. In *International Conference on Algorithmic Learning Theory*, pp. 194–208. Springer, 2015.

Anastasia Pentina and Ruth Urner. Lifelong learning with weighted majority votes. In *Advances in Neural Information Processing Systems*, pp. 3612–3620, 2016.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, and Christoph H Lampert. icarl: Incremental classifier and representation learning. *arXiv preprint arXiv:1611.07725*, 2016.

Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

Avishek Saha, Piyush Rai, Suresh Venkatasubramanian, and Hal Daume. Online learning of multiple tasks and their relationships. In *International Conference on Artificial Intelligence and Statistics*, pp. 643–651, 2011.

Vikas Sindhwani, Ha Quang Minh, and Aurélie C Lozano. Scalable matrix-valued kernel learning for high-dimensional nonlinear multivariate regression and granger causality. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pp. 586–595. AUAI Press, 2013.

Alex J Smola and Bernhard Schölkopf. *Learning with kernels*. GMD-Forschungszentrum Informationstechnik, 1998.

Kilian Weinberger, Anirban Dasgupta, John Langford, Alex Smola, and Josh Attenberg. Feature hashing for large scale multitask learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, pp. 1113–1120. ACM, 2009.

Ya Xue, Xuejun Liao, Lawrence Carin, and Balaji Krishnapuram. Multi-task learning for classification with dirichlet process priors. *The Journal of Machine Learning Research*, 8:35–63, 2007.

Yu Zhang and Dit-Yan Yeung. A regularization approach to learning task relationships in multitask learning. *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 8(3):12, 2014.