Stochastic activation pruning for robust adversarial defense

Guneet S. Dhillon[1,2]**, Kamyar Azizzadenesheli**[3]**, Zachary C. Lipton**[1,4]**,**
Jeremy Bernstein[1,5]**, Jean Kossaifi**[1,6]**, Aran Khanna**[1]**, Anima Anandkumar**[1,5]
[1]Amazon AI, [2]UT Austin, [3]UC Irvine, [4]CMU, [5]Caltech, [6]Imperial College London
`guneetdhillon@utexas.edu, kazizzad@uci.edu, zlipton@cmu.edu,`
`bernstein@caltech.edu, jean.kossaifi@imperial.ac.uk,`
`aran@arankhanna.com, anima@amazon.com`

Abstract

Neural networks have been found vulnerable to adversarial examples. Carefully chosen perturbations to real images, while imperceptible to humans, induce misclassification and threaten the reliability of deep learning systems in the wild. To guard against adversarial examples, we take inspiration from game theory. We cast the problem as a minimax zero-sum game between the adversary and the model. For such games, it is in general optimal for players to use a stochastic policy, also known as a *mixed strategy*. In light of this, we propose a mixed strategy for the model: *stochastic activation pruning*. SAP prunes a random subset of activations (preferentially pruning activations with smaller magnitude) and scales up the survivors to compensate. SAP can be applied to pre-trained neural networks—even adversarially trained models—without fine-tuning, providing robustness against adversarial examples. Experiments demonstrate that SAP confers robustness in the adversarial setting, increasing accuracy whilst preserving calibration.

1 Introduction

While deep neural networks have emerged as dominant tools for supervised learning problems, they remain vulnerable to adversarial examples (Szegedy et al., 2013). Small, carefully chosen perturbations to input data can induce misclassification with high probability. In the image domain, even perturbations so small as to be imperceptible to humans can fool powerful convolutional neural networks (Szegedy et al., 2013; Goodfellow et al., 2014). This fragility presents an obstacle to using machine learning in the wild. For example, a vision system vulnerable to adversarial examples might be fundamentally unsuitable for a computer security application. Even if a vision system is not explicitly used for security, these weaknesses might be critical. Moreover these problems seem unnecessary. If these perturbations are not perceptible to people, why should they fool a machine?

Since this problem was first identified, a rapid succession of papers have proposed various techniques both for *generating* and for *guarding against* adversarial attacks. Goodfellow et al. (2014) argues the deep networks, have a linear nature and introduces a simple method for quickly producing adversarial examples called *the fast gradient sign method* (FGSM). Moreover, the significance of the sign-gradient methods in the parameter spaces is also studied in the context of deep networks (Bernstein et al., 2018). To produce an adversarial example using FGSM, we update the inputs by taking one step in the direction of the *sign* of the gradient of the loss with respect to the input.

To defend against adversarial examples some papers propose training the neural network on adversarial examples themselves, either using the same model (Goodfellow et al., 2014; Madry et al., 2017), or using an ensemble of models (Tramèr et al., 2017a). Taking a different approach, Nayebi & Ganguli (2017) draws inspiration from biological systems. They propose that to harden neural networks against adversarial examples, one should learn flat, compressed representations that are sensitive to a minimal number of input dimensions.

In this paper, we introduce a method for guarding pre-trained networks, even adversarially trained models, against adversarial examples. During the forward pass, we stochastically prune a subset of

the activations in each layer, preferentially retaining activations with larger magnitudes. Following the pruning, we scale up the surviving activations to normalize the dynamic range of the inputs to the subsequent layer. Unlike other adversarial defense methods, our method can be applied post-hoc to already-trained networks and requires no additional fine-tuning. The method can be applied to any existing neural network where a greater robustness to adversarial examples, generated by either FGSM or by an iterative attack, is desired.

2 PRELIMINARIES

We denote an n-layered deep neural network $h : \mathcal{X} \to Y$ as a chain of functions $h = h^n \circ h^{n-1} \circ \ldots \circ h^1$, where each h^i consists of a linear transformation W^i followed by a non-linearity ϕ^i. Given a set of nonlinearities and weight matrices, a deep neural network provides a nonlinear mapping from inputs $x \in \mathcal{X}$ to outputs $\hat{y} \in \mathcal{Y}$, i.e.

$$\hat{y} := h(x) = \phi^n(W^n \phi^{n-1}(W^{n-1} \phi^{n-2}(\ldots \phi^1(W^1 x)))).$$

In supervised classification and regression problems, we are given a data set $\mathcal{D}$ of pairs (x, y), where each pair is drawn from an unknown joint distribution. For the classification problems, y is a categorical random variable, and for regression, y is a real-valued vector. Conditioned on a given dataset, network architecture, and a loss function (e.g. cross entropy, $L2$-loss), a learning algorithm, e.g. stochastic gradient descent, learns a set of parameters $\theta := \{W^i\}_{i=1}^n$ in order to map the input x to output $\hat{y}$. We denote $J(\theta, x, y)$ as the loss of a learned network, parameterized by θ, on a pair of (x, y). In order to ease the notation, we focus on the classification problems for the rest of the paper while the methods are broadly applicable to more general settings.

Consider an input x, which is correctly classified by the model h. An adversary seeks to apply a small perturbation to x, $x^{adv} = x + \Delta x$, such that $h(x) \neq h(x^{adv})$ while the perturbation remains minimally perceptible to a human. For the perturbations applied to the images, the l_∞-norm is considered a better measure of human perceptibility than more common norms like l_2, and has been studied as a natural notion of such perturbations, as put forward in Goodfellow et al. (2014). Throughout this paper, we assume that the manipulative power of the adversary, the perturbation Δx, is of bounded norm $\|\Delta x\|_\infty \leq \lambda$.

Given a classifier, one common way to generate an adversarial example is to perturb the input in the direction that increases the cross-entropy loss. This is equivalent to minimizing the probability assigned to the true label. Given the neural network h, network parameters θ, input data x, and corresponding true output y, an adversary could create a perturbation Δx as follows

$$\Delta x = \arg \max_{r \sim \rho} J(\theta, x + r, y), \tag{1}$$

where ρ is the adversary's policy, a deterministic mapping from input x to the space of bounded (allowed) perturbations (for any r in range of ρ, $\|r\|_\infty \leq \lambda$). Due to nonlinearities in the underlying neural network, and therefore of the objective function J, solving the optimization Eq. 1 is difficult.

Following Madry et al. (2017); Goodfellow et al. (2014), we use the Taylor expansion of the loss function up to the first order term and we get

$$\Delta x = \arg \max_{r \sim \rho} [J(\theta, x, y) + r^\top \mathcal{J}(\theta, x, y)], \qquad \text{where } \mathcal{J} = \frac{\partial J}{\partial x}.$$

The first term in the optimization does not depend on the adversary's policy, therefore

$$\Delta x = \arg \max_{r \sim \rho} r^\top \mathcal{J}(\theta, x, y).$$

Given that input, label and a fixed model, an adversary can choose r to be in the direction of $\mathcal{J}(\theta, x, y)$, i.e. $\Delta x = \lambda \cdot \text{sign}(\mathcal{J}(\theta, x, y))$. This is the FGSM technique due to Goodfellow et al. (2014). Note that FGSM requires an adversary to access the model in order to compute the gradient.

3 STOCHASTIC ACTIVATION PRUNING

Consider the defense problem from a game-theoretic perspective (Osborne & Rubinstein, 1994). The adversary designs a policy in order to maximize the defender's loss while knowing the defenders policy. At the same time defender needs to come up with a strategy to minimize this maximized loss.

Therefore, we can rewrite Eq. 1 as follows

$$\pi^*, \ \rho^* := \arg\min_{p \sim \pi} \max_{r \sim \rho} \mathbb{E}_{\pi,\rho}\left[J(M_p(\theta), x + r, y)\right], \tag{2}$$

where the adversary tries to maximize the loss of the defender by perturbing the input under a strategy ρ and the defender tries to minimize the loss by changing model parameters θ to $M_p(\theta)$ under strategy π. The optimization problem in Eq. 2 is a *minimax* zero-sum game between the adversary and defender where the optimal strategies (π^*, ρ^*), in general, are mixed Nash equilibrium, i.e. stochastic policies. Recall that the set of policies for the adversary is limited to perturbations with constrained l_∞ norm. For the defender, the policy set is constraint to those policies which preserve the overall accuracy of the model.

In this paper, we propose Stochastic Activation Pruning (SAP). Intuitively, the idea is to stochastically drop out nodes in each layer during forward propagation. We retain nodes with probabilities proportional to the magnitude of their activation and scale up the surviving nodes to preserve the dynamic range of the activations in each layer. Empirically, the approach preserves the accuracy of the original model. Notably, the method can be applied post-hoc to already-trained models.

Formally, assume a given pre-trained model, with activation layers (*ReLU, Sigmoid, etc.*) and input pair of (x, y). For each of those layers, SAP converts the activation map to a multinomial distribution, choosing each activation with a probability proportional to its absolute value. In other words, we obtain the multinomial distribution of each activation layer with L_1 normalization of their absolute values onto a L_1-ball simplex. Given the i'th layer activation map, $h^i \in \mathbb{R}^{a^i}$, the probability of sampling the j'th activation with value $(h^i)_j$ is given by

$$p_j^i = \frac{|(h^i)_j|}{\sum_{k=1}^{a^i} |(h^i)_k|}.$$

Random samples are drawn from the activation map given the probability distribution described above. Samples are drawn with replacement. This makes it convenient to determine whether an activation would be sampled at all. If an activation is sampled, we scale it up by the inverse of the probability of sampling it over all the draws. If not, we set the activation to 0. In this way, SAP preserves inverse propensity scoring of each activation.

Under an instance p of policy π, we draw r_p^i samples with replacement from this multinomial distribution. The new activation map, $M_p(h^i)$ is given by

$$M_p(h^i) = h^i \odot m_p^i, \qquad\qquad (m_p^i)_j = \frac{\mathbb{I}((h^i)_j)}{1 - (1 - p_j^i)^{r_p^i}},$$

where $\mathbb{I}((h^i)_j)$ is the indicator function that returns 1 if $(h^i)_j$ was sampled at least once, and 0 otherwise. The algorithm is described in Algorithm 1. In this way, the model parameters are changed from θ to $M_p(\theta)$, for instance p under policy π, while the reweighing $1 - (1 - p_j^i)^{r_p^i}$ preserves $\mathbb{E}_{p \sim \pi}[M_p(h^i)_j] = (h^i)_j$. If the model was linear, the proposed pruning method would behave the same way as the original model in expectation. In practice, we find that even with the non-linearities in deep neural networks, for sufficiently many examples, SAP performs similarly to the un-pruned model. This guides our decision to apply SAP to pre-trained models without performing any fine-tuning.

3.1 ADVANTAGE AGAINST ADVERSARIAL ATTACK

We attempt to explain the advantages of SAP under the assumption that we are applying it to a pre-trained model that achieves high generalization accuracy. For instance p under policy π, if the number of samples drawn for each layer i, r_p^i, is large, then fewer parameters of the neural network are pruned, and the scaling factor gets closer to 1. Under this scenario, the stochastically pruned model performs almost identically to the original model. The stochasticity is not advantageous in this case, but there is no loss in accuracy in the pruned model as compared to the original model.

On the other hand, with fewer samples in each layer, r_p^i, a large number of parameters of the neural network are pruned. Under this scenario, the SAP model's accuracy will drop compared to the original model's accuracy. But this model is stochastic and has more freedom to deceive the adversary. So the

---

Algorithm 1 Stochastic Activation Pruning (SAP)

1: **Input:** input datum x, neural network with n layers, with i^{th} layer having weight matrix W^i, non-linearity ϕ^i and number of samples to be drawn r^i.
2: $h^0 \leftarrow x$
3: **for each** layer i **do**
4:     $h^i \leftarrow \phi^i(W^i h^{i-1})$ ▷ activation vector for layer i with dimensions a^i
5:     $p_j^i = \frac{|(h^i)_j|}{\sum_{k=1}^{a^i} |(h^i)_k|}, \ \forall j \in \{1, \ldots, a^i\}$ ▷ normalized onto a simplex
6:     $S \leftarrow \{\}$ ▷ repository for indices not to be pruned
7:     **repeat** r^i **times**   ▷ each activation has at most r^i chances of being kept
8:         Draw $s \sim \text{categorical}(p^i)$ ▷ s is the set of successful indices
9:         $S = S \cup s$ ▷ add indices in s to keep set
10:    **for each** $j \notin S$ **do**
11:        $(h^i)_j \leftarrow 0$ ▷ prune the activations not in S
12:    **for each** $j \in S$ **do**
13:        $(h^i)_j \leftarrow \frac{(h^i)_j}{1-(1-p_j^i)^{r^i}}$ ▷ scale up the activations in S
14: **return** h^n

---

advantage of SAP comes if we can balance the number of samples drawn in a way that negligibly affects the original model's accuracy while conferring robustness against adversarial examples.

SAP is similar to the *dropout* technique due to Srivastava et al. (2014). However, there is a crucial difference. SAP is more likely to sample activations that are high in absolute value, whereas dropout samples each activation with the same probability. Because of this difference, SAP, unlike dropout, can be applied post-hoc *to pre-trained models* without significantly decreasing the accuracy of the model. Experiments comparing SAP and dropout are included in section 5. Interestingly, dropout confers little advantage over the baseline. We suspect that the reason for this is that the dropout training procedure encourages all possible dropout masks to result in similar mappings.

4 ADVERSARIAL ATTACK ON SAP MODEL

If the adversary knows that our defense policy is to apply SAP, it might try to calculate the best strategy against the SAP model. Given the neural network h, input data x, corresponding true output y, a policy ρ over the allowed perturbations, and a policy π over the model parameters that come from SAP (this result holds true for any stochastic policy chosen over the model parameters), the adversary determines the perturbation Δx as follows

$$\Delta x = \arg\max_{r \sim \rho} \mathbb{E}_{p \sim \pi}[J(M_p(\theta), x+r, y)].$$

Using the result from section 2

$$\Delta x = \arg\max_{r \sim \rho} r^\top \mathbb{E}_{p \sim \pi}[\mathcal{J}(M_p(\theta), x, y)].$$

To maximize the term, the adversary will set r to be in the direction of $\mathbb{E}_{p \sim \pi}[\mathcal{J}(M_p(\theta), x, y)]$.

Analytically computing $\mathbb{E}_{p \sim \pi}[\mathcal{J}(M_p(\theta), x, y)]$ is not feasible. However, the adversary can use Monte Carlo sampling to estimate the expectation as $\widetilde{\mathcal{J}}(M_p(\theta), x, y)$. Then, using the FGSM method, $\Delta x = \lambda \cdot \text{sign}(\widetilde{\mathcal{J}}(M_p(\theta), x, y))$.

5 EXPERIMENTS

Our experiments to evaluate SAP address two tasks: image classification and reinforcement learning. We apply the method to the *ReLU* activation maps at each layer of the pre-trained neural networks. To create adversarial examples in our evaluation, we use FGSM, $\Delta x = \lambda \cdot \text{sign}(\mathcal{J}(M_p(\theta), x, y))$. For stochastic models, the adversary estimates $\mathcal{J}(M_p(\theta), x, y)$ using Monte Carlo sampling unless otherwise mentioned. All perturbations are applied to the pixel values of images, which normally take

| (a) | (b) | (c) |

Figure 1: Accuracy plots of a variety of attacks against dense model and SAP models with different perturbation strengths, λ. For the SAP $\tau\%$ models, τ denotes the percentages of samples drawn from the multinomial distribution, at each layer. (a) SAP models tested against random perturbation. (b) SAP models tested against the FGSM attack, using Monte Carlo sampling. (c) SAP-100 tested against an iterative adversarial attack, using Monte Carlo sampling (legend shows defender vs. adversary). It is worth restating that obtaining the iterative attack of SAP models is much more expensive and noisier than the iterative attack of dense models.

values in the range 0-255. So the fraction of perturbation with respect to the data's dynamic range would be $\frac{\lambda}{256}$. To ensure that all images are valid, even following perturbation, we clip the resulting pixel values so that they remain within the range $[0, 255]$. In all plots, we consider perturbations of the following magnitudes $\lambda = \{0, 1, 2, 4, 8, 16, 32, 64\}$.[1]

To evaluate models in the image classification domain, we look at two aspects: the model accuracy for varying values of λ, and the calibration of the models (Guo et al., 2017). Calibration of a model is the relation between the confidence level of the model's output and its accuracy. A linear calibration is ideal, as it suggests that the accuracy of the model increases with the confidence level of its output. For stochastic models, we compute the output as an average over multiple forward passes.

To evaluate models in the reinforcement learning domain, we look at the average score that the model achieves on the games played, for varying values of λ. The higher the score, the better is the model's performance. Because the units of reward are arbitrary, we report results in terms of the the relative percent change in rewards.

5.1 ADVERSARIAL ATTACKS IN IMAGE CLASSIFICATION

The Cifar-10 dataset (Krizhevsky & Hinton, 2009) was used for the image classification domain. We trained a ResNet-20 model (He et al., 2016) using SGD, with minibatches of size 512, momentum of 0.9, weight decay of 0.0001, and a learning rate of 0.5 for the first 100 epochs, then 0.05 for the next 30 epochs, and then 0.005 for the next 20 epochs. This achieved an accuracy of 89.8% with cross-entropy loss and *ReLU* non-linearity. For all the figures in this section, this model is referenced to as the *dense* model.

The accuracy of the dense model degrades quickly with λ. For $\lambda = 1$, the accuracy drops down to 66.3%, and for $\lambda = 2$ it is 56.4%. These are small (hardly perceptible) perturbations in the input images, but the dense model's accuracy decreases significantly.

5.1.1 STOCHASTIC ACTIVATION PRUNING (SAP)

We apply SAP to the dense model. For each activation map $h^i \in \mathbb{R}^{a^i}$, we pick $k\%$ of a^i activations to keep. Since activations are sampled with replacement, k can be more than 100. We will refer to k as the percentage of samples drawn.

Fig. 1a plots performance of SAP models against examples perturbed with random noise. Perturbations of size $\lambda = 64$ are readily perceptible and push all models under consideration to near-random outputs, so we focus our attention on smaller values of λ. Fig. 1b plots performance of these models

---

[1]All the implementations were coded in MXNet framework (Chen et al., 2015) and sample code is available at https://github.com/Guneet-Dhillon/Stochastic-Activation-Pruning

(a) (b) (c)

Figure 2: Robustness of dropout models, with different rates of dropout (denoted in the legends), against adversarial attacks, using Monte Carlo sampling, with a variety of perturbation strengths, λ: (a) dropout is applied on the pre-trained models during the validations; (b) the models are trained using dropout, and dropout is applied during the validations; (c) the models are trained using dropout, but dropout is not applied during the validations.

against adversarial examples. With many samples drawn, SAP converges to the dense model. With few samples drawn, accuracy diminishes, even without perturbation. The plot explains this balance well. We achieve the best performance with $\sim 100\%$ samples picked.

We will now only look at SAP 100% (SAP-100). Against adversarial examples, with $\lambda = 1, 2$ and 4, we observe a 12.2%, 16.3% and 12.8% absolute increase in accuracy respectively. However, for $\lambda = 0$, we observe a 6.5% absolute decrease in accuracy. For $\lambda = 16$ again, there is a 5.2% absolute decrease in accuracy.

5.1.2 DROPOUT (DRO)

Dropout, a technique due to Srivastava et al. (2014), was also tested to compare with SAP. Similar to the SAP setting, this method was added to the *ReLU* activation maps of the dense model. We see that low dropout rate perform similar to the dense model for small λ values, but its accuracy starts decreasing very quickly for higher λ values (Fig. 2a).

We also trained ResNet-20 models, similar to the dense model, but with different dropout rates. This time, the models were trained for 250 epochs, with an initial learning rate of 0.5, reduced by a factor of 0.1 after 100, 150, 190 and 220 epochs. These models were tested against adversarial examples with and without dropout during validation (Figs. 2b and 2c respectively). The models do similar to the dense model, but do not provide additional robustness.

5.1.3 ADVERSARIAL TRAINING (ADV)

Adversarial training (Goodfellow et al., 2014) has emerged a standard method for defending against adversarial examples. It has been adopted by Madry et al. (2017); Tramèr et al. (2017a) to maintain high accuracy levels even for large λ values.

We trained a ResNet-20 model, similar to the dense model, with an initial learning rate of 0.5, which was halved every 10 epochs, for a total of 100 epochs. It was trained on a dataset consisting of 80% un-perturbed data and 20% adversarially perturbed data, generated on the model from the previous epoch, with $\lambda = 2$. This was done on the Cifar-10 dataset. This achieved an accuracy of 75.0% on the un-perturbed validation set, with cross-entropy loss and *ReLU* non-linearity. Note that the model capacity was not changed.

When tested against adversarial examples, the accuracy dropped to $72.9\%, 70.9\%$ and 67.5% for $\lambda = 1, 2$ and 4 respectively. We ran SAP-100 on the ADV model (referred to as ADV+SAP-100). The accuracy in the no perturbation case was 74.1%. For adversarial examples, both models act similar to each other for small values of λ. But for $\lambda = 16$ and 32, ADV+SAP-100 gets a higher accuracy than ADV by an absolute increase of 7.8% and 7.9% respectively.

We compare the accuracy-λ plot for dense, SAP-100, ADV and ADV+SAP-100 models. This is illustrated in Fig. 3 For smaller values of λ, SAP-100 achieves high accuracy. As λ gets larger, ADV+SAP-100 performs better than all the other models. We also compare the calibration plots for

Figure 3: Accuracy plots of the dense, SAP-100, ADV and ADV+SAP-100 models, against adversarial attacks, using Monte Carlo sampling, with a variety of perturbation strengths, λ.

Figure 4: Calibration plots of the dense, SAP-100, ADV and ADV+SAP-100 models, against adversarial attacks, using Monte Carlo sampling, with a variety of different perturbation strengths, λ. These plots show the relation between the confidence level of the model's output and its accuracy.

these models, in Fig. 4. The dense model is not linear for any $\lambda \neq 0$. The other models are well calibrated (close to linear), and behave similar to each other for $\lambda \leq 4$. For higher values of λ, we see that ADV+SAP-100 is the closest to a linearly calibrated model.

5.2 ADVERSARIAL ATTACKS IN DEEP REINFORCEMENT LEARNING (RL)

Previously, (Behzadan & Munir, 2017; Huang et al., 2017; Kos & Song, 2017) have shown that the Reinforcement learning agents can also be easily manipulated by adversarial examples. The RL agent learns the long term value $Q(a, s)$ of each state-action pair (s, a) through interaction with

Table 1: Relative percentage increase in rewards gained for SAP-100 compared to original model while playing different Atari games.

λ	Assault	Asterix	BankHeist	BattleZone	BeamRider	Bowling
0	-12.2%	-33.4%	-59.2%	-65.8%	-15.8%	-4.5%
1	10.4%	13.3%	131.7%	-22.0%	164.5%	3425.9%
2	9.8%	20.8%	204.8%	110.1%	92.3%	
4	12.4%	14.0%	1760.0%	202.6%		
8	16.6%	7.4%	60.9%	134.8%		

(a) Random noisy weights. (b) Randomly scaled weights. (c) Deterministic weight pruning.

(d) Stochastic weight pruning. (e) Random noisy activations. (f) Randomly scaled activations.

Figure 5: Robustness of different pruning and noisifying strategies against their adversarial attacks (Monte Carlo sampling is used for estimating the gradients of stochastic models) under a variety of different perturbation strengths, λ.

an environment where given a state s, the optimal action is $\arg\max_a Q(a, s)$. A regression based algorithm, Deep Q-Network (DQN)(Mnih et al., 2015) and its improved version, Double DQN (DDQN) have been proposed for the popular Atari games (Bellemare et al., 2013) as benchmarks. We deploy DDQN algorithm and train an RL agent in variety of different Atari game settings.

Similar to the image classification experiments, we tested SAP on a pre-trained model (the model is described in the Appendix section A), by applying the method on the *ReLU* activation maps. SAP-100 was used for these experiments. Table 1 specifies the percentage relative increase in rewards of SAP-100 as compared to the original model. For all the games, we observe a drop in performance for the no perturbation case. But for $\lambda \neq 0$, the relative increase in rewards is positive (except for $\lambda = 1$ in the BattleZone game), and is very high in some cases (3425.9% for $\lambda = 1$ for the Bowling game).

5.3 ADDITIONAL BASELINES

In addition to experimenting with SAP, dropout, and adversarial training, we conducted extensive experiments with other methods for introducing stochasticity into a neural network. These techniques included 0-mean Gaussian noise added to weights (RNW), 1-mean multiplicative Gaussian noise for the weights (RSW), and corresponding additive (RNA) and multiplicative (RSA) noise added to the activations. We describe each method in detail in Appendix B. Each of these models performs worse than the dense baseline at most levels of perturbation and none matches the performance of SAP. Precisely why SAP works while other methods for introducing stochasticity do not remains an open question that we continue to explore in future work.

Figure 6: Accuracy plots of adversarial attacks, with different perturbation strengths, λ. The legend shows defender vs. adversary models (used for gradient computation), and the number of MC samples used to estimate the gradient.

5.4   MONTE CARLO SAMPLES FOR GRADIENT ESTIMATION AND DENSE MODEL ATTACK

Previously, the adversary used a 100 Mote Carlo samples to estimate the gradient with respect to the SAP models to create adversarial examples. In Fig. 6 we compare the performance of SAP-100 against different kinds of adversarial examples - generated on the dense model and generated on SAP-100 with different number of Monte Carlo samples taken. We see that if the adversary uses the dense model to generate adversarial examples, SAP-100 model's accuracy decreases. Additionally, if the adversary uses the SAP-100 model to generate adversarial examples, as the number Monte Carlo samples it uses to estimate the gradient is increased, the lower the accuracy gets. But for low amounts of perturbation ($\lambda = 1$ and 2), SAP-100 does better than the dense model.

Computing a single backward pass of the SAP-100 model for 512 examples takes ~ 20 seconds on 8 GPUs. If the adversary uses 100 and 1000 Monte Carlo samples to estimate the gradient, for the same number of examples under the same setting, it would take ~ 0.6 and ~ 6 hours respectively. Considering that there are 10000 images just in the validation set for Cifar-10, that is a lot of computational power for the adversary.

5.5   ITERATIVE ADVERSARIAL ATTACK

One way that the adversary creates perturbations is to take one step in the direction of the gradient (FGSM). However, a more sophisticated perturbation could be computed if the adversary repeatedly updates the adversarial input in the direction of the local sign-gradients. This can be done by taking a small step of size $k \leq \lambda$ in the direction of the sign-gradient at the updated point and repeating the procedure $\lceil \frac{\lambda}{k} \rceil$ times (Kurakin et al., 2016) as follows

$$x^0 = x,$$
$$x^t = Clip_{x,\lambda}\left(x^{t-1} + k \, \text{sign}(\mathcal{J}(\theta, x^{t-1}, y)))\right),$$

where function $Clip_{x,\lambda}$ is a projection into a L_∞-ball of radius λ centered at x, and also into the hyper-cube of image space (each pixel is clipped to the range of $[0, 255]$). The dense and SAP-100 models are tested against this adversarial attack, with $k = 1.0$ (Fig. 1c). The accuracies of the dense model at $\lambda = 0, 1, 2$ and 4 are $89.8\%, 66.3\%, 50.1\%$ and 31.0% respectively. The accuracies of the SAP-100 model against attacks computed on its own (with 10 Monte Carlo samples taken at each step to estimate the gradient) are $83.3\%, 82.0\%, 80.2\%$ and 76.7% respectively for $\lambda = 0, 1, 2, 4$. The SAP-100 model provides accuracies of $83.3\%, 75.2\%, 67.0\%$ and 50.8%, respectively, against attacks computed on the dense model, also, with the perturbation rage of $\lambda = 0, 1, 2, 4$. Obtaining the iterative attack of SAP models is much more expensive and noisier than iterative attack of dense models. This is why the adversarial attack computed on the dense model results in lower accuracies on the SAP-100 model than the adversarial attack computed on the SAP-100 model itself.

6 RELATED WORK

Recently, the paradigm of adversarial attacks and defenses to machine learning models have been addressed as a serious problem in the field of machine learning where creating such attacks and finding ways to defend against them are the essential core this paradigm (Goodfellow et al., 2014; Kurakin et al., 2016; Papernot & McDaniel, 2016; Tramèr et al., 2017b; Fawzi et al., 2018). Goodfellow et al. (2014) introduced the FGSM method, which involves taking a step in the direction of the gradient of the loss function with respect to the input data. Kurakin et al. (2016) proposed an iterative method where FGSM is used for smaller step sizes, which leads to a better approximation of the gradient. Papernot et al. (2017) observed that adversarial examples could be transferred to other models as well. Madry et al. (2017) introduce adding random noise to the image and then using the FGSM method to come up with adversarial examples.

Being robust against adversarial examples has primarily focused on training on the adversarial examples. Goodfellow et al. (2014) use the FGSM and inject data perturbed in that way into their training dataset. Madry et al. (2017) use an iterative FGSM approach of creating adversarial examples to train on. Madry et al. (2017) introduced an ensemble adversarial training method of training on the adversarial examples created on the model itself and an ensemble of other pre-trained models. These works have been successful, achieving only a small drop in accuracy form the clean and adversarially generated data.

Other papers on adversarial defense propose training a new model with a new objective function. One such example is the technique introduced due to Nayebi & Ganguli (2017), where the activations are encouraged to be saturated. In doing so, small perturbations in the input data does not effect the output much.

7 CONCLUSION

We introduced SAP, demonstrating that it confers significant improvements in the robustness of pre-trained models against adversarial examples. The approach guards networks without requiring any additional training. In the image classification domain, we showed that in the adversarial setting, applying SAP improves both the accuracy of the model and its calibration, achieving close to linear calibration for small perturbations and outperforming other models. Applying SAP is enough to be robust against small perturbation values. For larger perturbations, even SAP models suffer, but they compare favorably to their dense counterparts. Notably, SAP can be combined with adversarial training, compounding the respective benefits of each approach. Even in the domain of reinforcement learning, SAP is able to defend against adversarial examples better than the original model.

REFERENCES

Vahid Behzadan and Arslan Munir. Vulnerability of deep reinforcement learning to policy induction attacks. *arXiv preprint arXiv:1701.04143*, 2017.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *J. Artif. Intell. Res.(JAIR)*, 47:253–279, 2013.

Jeremy Bernstein, Yu-Xiang Wang, Kamyar Azizzadenesheli, and Anima Anandkumar. signsgd: compressed optimisation for non-convex problems. *arXiv preprint arXiv:1802.04434*, 2018.

Tianqi Chen, Mu Li, Yutian Li, Min Lin, Naiyan Wang, Minjie Wang, Tianjun Xiao, Bing Xu, Chiyuan Zhang, and Zheng Zhang. Mxnet: A flexible and efficient machine learning library for heterogeneous distributed systems. *arXiv preprint arXiv:1512.01274*, 2015.

Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Analysis of classifiers' robustness to adversarial perturbations. *Machine Learning*, 107(3):481–508, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. *arXiv preprint arXiv:1706.04599*, 2017.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Sandy Huang, Nicolas Papernot, Ian Goodfellow, Yan Duan, and Pieter Abbeel. Adversarial attacks on neural network policies. *arXiv preprint arXiv:1702.02284*, 2017.

Jernej Kos and Dawn Song. Delving into adversarial attacks on deep policies. *arXiv preprint arXiv:1705.06452*, 2017.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *arXiv preprint arXiv:1607.02533*, 2016.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Aran Nayebi and Surya Ganguli. Biologically inspired protection of deep networks from adversarial attacks. *arXiv preprint arXiv:1703.09202*, 2017.

Martin J Osborne and Ariel Rubinstein. *A course in game theory*. MIT press, 1994.

Nicolas Papernot and Patrick McDaniel. On the effectiveness of defensive distillation. *arXiv preprint arXiv:1607.05113*, 2016.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pp. 506–519. ACM, 2017.

Nitish Srivastava, Geoffrey E Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *Journal of machine learning research*, 15(1):1929–1958, 2014.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. *arXiv preprint arXiv:1705.07204*, 2017a.

Florian Tramèr, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. The space of transferable adversarial examples. *arXiv preprint arXiv:1704.03453*, 2017b.

A   REINFORCEMENT LEARNING MODEL ARCHITECTURE

For the experiments in section 5.2, we trained the network with RMSProp, minibatches of size 32, a learning rate of 0.00025, and a momentum of 0.95 and as in (Mnih et al., 2015) where the discount factor is $\gamma = 0.99$, the number of steps between target updates to 10000 steps. We updated the network every 4 steps by randomly sampling a minibatch of size 32 samples from the replay buffer and trained the agents for a total of $100M$ steps per game. The experience replay contains the $1M$ most recent transitions. For training we used an ε-greedy policy with ε annealed linearly from 1 to 0.1 over the first $1M$ time steps and fixed at 0.1 thereafter.

The input to the network is $4 \times 84 \times 84$ tensor with a rescaled, gray-scale version of the last four observations. The first convolution layer has 32 filters of size 8 with a stride of 4. The second convolution layer has 64 filters of size 4 with stride 2. The last convolution layer has 64 filters of size 3 followed by two fully connected layers with size 512 and the final fully connected layer Q-value of each action where *ReLU* rectifier is deployed for the nonlinearity at each layer.

B   OTHER METHODS ON CIFAR-10

We tried a variety of different methods that could be added to pretrained models and tested their performance against adversarial examples. The following is a continuation of section 5.1, where we use the dense model again on the CIFAR-10 dataset.

B.1   RANDOM NOISY WEIGHTS (RNW)

One simple way of introducing stochasticity to the activations is by adding random Gaussian noise to each weight, with mean 0 and constant standard deviation, s. So each weight tensor W^i now changes to $M(W^i)$, where the j'th entry is given by

$$M(W^i)_j = (W^i)_j + \eta, \qquad\qquad \eta \sim \mathcal{N}(0, s^2).$$

These models behave very similar to the dense model (Fig. 5a, the legend indicates the value of s). While we test several different values of s, we do not observe any significant improvements regarding robustness against adversarial examples. As s increased, the accuracy for non-zero λ decreased.

B.2   RANDOMLY SCALED WEIGHTS (RSW)

Instead of using additive noise, we also try multiplicative noise. The scale factor can be picked from a Gaussian distribution, with mean 1 and constant standard deviation s. So each weight tensor W^i now changes to $M(W^i)$, where the j'th entry is given by

$$M(W^i)_j = \eta \cdot (W^i)_j, \qquad\qquad \eta \sim \mathcal{N}(1, s^2).$$

These models perform similar to the dense model, but again, no robustness is offered against adversarial examples. They follow a similar trend as the RNW models (Figure 5b, the legend indicates the value of s).

B.3   DETERMINISTIC WEIGHT PRUNING (DWP)

Following from the motivation of preventing perturbations to propagate forward in the network, we tested deterministic weight pruning, where the top $k\%$ entries of a weight matrix were kept, while the rest were pruned to 0, according to their absolute values. This method was prompted by the success achieved by this pruning method, introduced by Han et al. (2015), where they also fine-tuned the model.

For low levels of pruning, these models do very similar to the dense model, even against adversarial examples (Fig. 5c, the legend indicates the value of k). The adversary can compute the gradient of the sparse model, and the perturbations propagate forward through the surviving weights. For higher levels of sparsity, the accuracy in the no-perturbation case drops down quickly.

B.4 STOCHASTIC WEIGHT PRUNING (SWP)

Observing the failure of deterministic weight pruning, we tested a mix of stochasticity and pruning, the stochastic weight pruning method. Very similar to the idea of SAP, we consider all the entries of a weight tensor to be a multinomial distribution, and we sample from it with replacement. For a weight tensor $W^i \in \mathbb{R}^{a^i}$, we sample from it r^i times with replacement. The probability of sampling $(W^i)_j$ is given by

$$p_j^i = \frac{|(W^i)_j|}{\sum_{k=1}^{a^i} |(W^i))_k|}.$$

The new weight entry, $M(W^i)_j$, is given by

$$M(W^i)_j = W_j^i \cdot \frac{\mathbb{I}(W_j^i)}{1 - (1 - p_i)^{r^i}},$$

where $\mathbb{I}(W_j^i)$ is the indicator function that returns 1 if W_j^i was sampled at least once, and 0 otherwise.

For these experiments, for each weight matrix $W^i \in \mathbb{R}^{m^i}$, the number of samples picked were $k\%$ of m^i. Since samples were picked with replacement, k could be more than 100. We will refer to k as the percentage of samples drawn.

These models behave very similar to the dense model. We tried drawing range of percentages of samples, but no evident robustness could be seen against adversarial examples (Figure 5d, the legend indicates the value of k). For a small s, it is very similar to the dense model. As s increases, the these models do marginally better for low non-zero λ values, and then drops again (similar to the SAP case).

B.5 RANDOM NOISY ACTIVATIONS (RNA)

Next we change our attention to the activation maps in the dense model. One simple way of introducing stochasticity to the activations is by adding random Gaussian noise to each activation entry, with mean 0 and constant standard deviation, s. So each activation map h^i now changes to $M(h^i)$, where the j'th entry is given by

$$M(h^i)_j = (h^i)_j + \eta, \qquad\qquad \eta \sim \mathcal{N}(0, s^2).$$

These models too do not offer any robustness against adversarial examples. Their accuracy drops quickly with λ and s (Fig. 5e, the legend indicates the value of s).

B.6 RANDOMLY SCALED ACTIVATIONS (RSA)

Instead of having additive noise, we can also make the model stochastic by scaling the activations. The scale factor can be picked from a Gaussian distribution, with mean 1 and constant standard deviation s. So each activation map h^i now changes to $M(h^i)$, where the j'th entry is given by

$$M(h^i)_j = \eta(h^i)_j, \qquad\qquad \eta \sim \mathcal{N}(1, s^2).$$

These models perform similar to the dense model, exhibiting no additional robustness against adversarial examples (Figure 5f, the legend indicates the value of s).