Self-Supervised Visual Representation Learning with Semantic Grouping

Abstract

In this paper, we tackle the problem of learning visual representations from un-labeled scene-centric data. Existing works have demonstrated the potential of utilizing the underlying complex structure within scene-centric data; still, they commonly rely on hand-crafted objectness priors or specialized pretext tasks to build a learning framework, which may harm generalizability. Instead, we pro-pose contrastive learning from data-driven semantic slots, namely SlotCon, for joint semantic grouping and representation learning. The semantic grouping is performed by assigning pixels to a set of learnable prototypes, which can adapt to each sample by attentive pooling over the feature and form new slots. Based on the learned data-dependent slots, a contrastive objective is employed for representation learning, which enhances the discriminability of features, and conversely facilitates grouping semantically coherent pixels together. Compared with previous efforts, by simultaneously optimizing the two coupled objectives of semantic grouping and contrastive learning, our approach bypasses the disadvantages of hand-crafted priors and is able to learn object/group-level representations from scene-centric im-ages. Experiments show our approach effectively decomposes complex scenes into semantic groups for feature learning and significantly benefits downstream tasks, including object detection, instance segmentation, and semantic segmentation.

1 Introduction

Existing self-supervised approaches have demonstrated that visual representations can be learned from unlabeled data by constructing pretexts such as transformation prediction [22], instance dis-crimination [64, 27], and masked image modeling [2, 26, 77, 61], *etc*. Among them, approaches based on instance discrimination [25, 6, 7, 11], which treat each image as a single class and employ a contrastive learning objective for training, have attained remarkable success and is beneficial to boost performance on many downstream tasks.

However, this success is largely built upon the well-curated object-centric dataset ImageNet [15], which has a large gap with the real-world data for downstream applications, such as city scenes [13] or crowd scenes [41]. Directly applying the instance discrimination pretext to these real-world data by simply treating the scene as a whole overlooks its intrinsic structures (*e.g.*, multiple objects and complex layouts) and thus will limit the potential of pre-training with scene-centric data [56]. This leads to our focus: learning visual representations from unlabeled scene-centric data.

Recent efforts to address this problem can be coarsely categorized into two types of research. One stream extends the instance discrimination task to pixel level for dense representation learning [49, 60, 67], which show strong performance in downstream dense prediction tasks. Yet, these methods still lack the ability to model object-level relationships presented in scene-centric data, which is

crucial for learning representations. Although another stream of works attempts to perform object-level representation learning, most of them still heavily rely on domain-specific priors to discover objects, which include saliency estimators [57, 51], unsupervised object proposal algorithms [62, 66], hand-crafted segmentation algorithms [75, 30] or unsupervised clustering [31]. However, if the representation is supervised by hand-crafted objectness priors, it will be discouraged from learning objectness from data itself and prone to mistakes from priors. Therefore, the capability and generalizability of the representation will be limited. In this work, we aim at a fully learnable and data-driven approach to enable learning representations from scene-centric data for enhanced effectiveness, transferability and generalizability.

We propose contrastive learning from data-driven semantic slots, namely SlotCon, for joint semantic grouping and representation learning. Semantic grouping is formulated as a feature-space pixel-level deep clustering problem where the cluster centers are initialized as a set of learnable semantic prototypes shared by the dataset, and grouping is achieved by assigning pixels to clusters. The cluster centers can then be updated for each sample by softly assigning pixels into cluster centers and aggregating their features in a weighted manner to form new ones, also called *slots*. Further, upon the learned data-dependent slots from two random views of one image, a contrastive objective, which attempts to pull positive slots (*i.e.*, slots from the same prototype and sample) together and push away negative ones, is employed for representation learning. The optimized representations will enhance the discriminability of features, prototypes, and slots, which conversely facilitates grouping semantically coherent pixels together. Compared with previous efforts, by simultaneously optimizing the two coupled objectives of semantic grouping and contrastive representation learning, our approach bypasses the disadvantages of hand-crafted priors and is able to learn object/group-level representations from scene-centric images.

We extensively assess the representation learning ability of our model by conducting transfer learning evaluation on COCO object detection [41], instance segmentation, and semantic segmentation on Cityscapes [13], PASCAL VOC [20], and ADE20K [76]. Our method shows strong results with COCO pre-training and ImageNet-1K pre-training, bridging the gap between scene-centric and object-centric pre-training. As a byproduct, our method also achieves state-of-the-art performance in unsupervised segmentation, showing strong ability in semantic concept discovery.

In summary, our main contributions in this paper are: 1) We show that the decomposition of natural scenes (semantic grouping) can be done in a learnable fashion and jointly optimized with the representations from scratch. 2) We demonstrate that semantic grouping is crucial for learning good representations from scene-centric data. 3) Combining semantic grouping and representation learning, we unleash the potential of scene-centric pre-training, largely close its gap with object-centric pre-training and achieve state-of-the-art results in various downstream tasks.

2   Related work

Our work is in the domain of self-supervised visual representation learning where the goal is to learn visual representations without human annotations. We briefly review relevant works below.

Image-level self-supervised learning   aims at learning visual representations by treating each images as one data sample. To this end, a series of pretext tasks are designed in which the labels are readily available without human annotations. Early explorations range from low-level pixel-wise reconstruction tasks that include denoising [59], inpainting [50], and cross-channel prediction [74] to higher-level instance discrimination [17], rotation prediction [22], context prediction [16], jigsaw puzzle [47], counting [48], and colorization [73]. Modern variants of instance discrimination [17] equipped with contrastive learning [55, 32] have shown great potential in learning transferable visual representations [64, 8, 27, 53, 18, 78]. Other works differ in their learning objectives, but still treat an image as a whole [25, 10, 72]. To further utilize the complex structure in natural images, some works exploit local crops [6, 65, 68, 56] while others either step to pixel- or object-level, detailed as follows.

Pixel-level contrastive learning   extends the instance discrimination task from image-level feature vectors to feature maps [49, 42, 60, 67]. Their main differences lie in the way positive pixel-pairs

Figure 1: Overview of our proposed framework. Based on a shared pixel embedding function, the model learns to classify pixels into groups according to their feature similarity in a pixel-level deep clustering fashion (Sec. 3.1); the model produces group-level feature vectors (slots) through attentive pooling over the feature maps, and further performs group-level contrastive learning (Sec. 3.2). We omit the symmetrized loss computed by swapping the two views for simplicity. (*best viewed in color*)

are matched (spatial adjacency [49, 67], feature-space-NN [60], sink-horn matching [42]), and the image-level baseline they build upon (MoCo v2 [49, 60], BYOL [42, 67]). Their pixel-level objective naturally helps learn dense representations that are favorable for dense prediction downstream tasks but lacks the grasp of holistic semantics and commonly require an auxiliary image-level loss to attain stronger performance [60, 67].

Object-level contrastive learning first discovers the objects in images and applies the contrastive objective over them, achieving a good balance in fine-grained structure and holistic semantics, yielding strong empirical gains with both object-centric [30, 31] and scene-centric data [66]. The key issue lies in how to find the objects in an image without supervision. Current works, however, still heavily rely on heuristic strategies that include saliency estimators [57, 51], selective-search [62, 66], hand-crafted segmentation algorithms [75, 30] or k-means clustering [31]. In contrast, our semantic grouping method is fully learnable and end-to-end, ensuring data-driven transferability and simplicity.

Unsupervised semantic segmentation is a emerging task that targets at addressing semantic segmentation with only unlabeled images. The first attempt of IIC [35] maximizes the mutual information of augmented image patches, and a later work MaskContrast [57] relies on saliency estimator as a prior to bootstrap semantic pixel representations. Recently, PiCIE [34] adopted pixel-level deep clustering [5] to cluster the pixels into semantic groups, which SegDiscover [33] further improves by adopting super-pixels. On the other hand, Leopart [79] exploits pre-trained vision transformer's attention maps [7]. Still, they commonly rely on a (self-supervised) pre-trained network for initialization, while our method is trained fully from scratch.

Object-centric representation learning is viewed as an essential component of data-efficient, robust and interpretable machine learning algorithms [24]. Towards unsupervised object-centric representation learning, a series of work have been proposed based on image reconstruction [23, 3, 19, 43]. While there are recent advances based on contrastive learning, they are either limited to synthetic data [37, 46, 1] or require the motion prior from flow [69, 36]. Instead, our method is capable of learning *category slots* [24] from natural scene-centric images in the wild.

3 Method

3.1 Semantic grouping with pixel-level deep clustering

Given a dataset $\mathcal{D}$ of unlabeled images, we aim at learning a set of prototypes $\mathcal{S}$ that classifies each pixel into a meaningful group, such that pixels within the same group are semantic-consistent (have similar feature representations), and pixels between different groups are semantic-incoherent. We find that this problem can be viewed as unsupervised semantic segmentation [22, 34], and solved with pixel-level deep clustering [5, 70, 6, 7].

Intuitively, a semantic meaningful grouping should be invariant to data augmentations. Thus, for different augmentations of the same image, we enforce the pixels that lie in the same location to

have similar assignment scores w.r.t. the same set of cluster centers (prototypes). Besides consistent grouping, the groups should be different from each other to ensure that the learned representations are discriminative and avoid trivial solutions, *e.g.* identical features. Together with common techniques used in self-supervised learning (*e.g.*, non-linear projector and momentum teacher [25, 7], *etc.*), this leads to the following framework.

Specifically, as illustrated in Fig. 1, our method contains two neural networks: the student network is parameterized by θ and include an encoder f_θ, a projector g_θ and a set of K learnable prototypes $\mathcal{S}_\theta = \left[s_\theta^1, s_\theta^2, \ldots, s_\theta^K \right] \in \mathbb{R}^{K \times D}$; the teacher network holds the same architecture with the student, but uses a different set of weights ξ that updates as an exponential moving average of θ. Given an input image x, two random augmentations are applied to produce two augmented views v^1 and v^2. Each augmented view $v^l \in \{v^1, v^2\}$ is then encoded with an encoder f into a hidden feature map $h^l \in \mathbb{R}^{H \times W \times D}$, and then transformed with a two-layer multilayer perceptron (MLP) g to get $z^l = g\left(h^l \right) \in \mathbb{R}^{H \times W \times D}$. We then compute the assignment $\mathcal{P}_\theta^l$ of the projections z_θ^l with the corresponding prototypes $\mathcal{S}_\theta$, and enforce it to match the assignment $\mathcal{Q}_\xi^{l'}$ produced with another view $v^{l'}$ by the teacher network. More precisely, with ℓ_2-normalized projections $\overline{z} = z/\|z\|$ and prototypes $\overline{s} = s/\|s\|$,

$$\mathcal{Q}_\xi^{l'} = \underset{K}{\mathrm{softmax}} \left(\left(\overline{z}_\xi^{l'} \cdot \overline{\mathcal{S}}_\xi^\top - c \right) / \tau_t \right), \quad \mathcal{P}_\theta^l = \underset{K}{\mathrm{softmax}} \left(\overline{z}_\theta^l \cdot \overline{\mathcal{S}}_\theta^\top / \tau_s \right) \in \mathbb{R}^{H \times W \times K} . \quad (1)$$

with $\tau_s, \tau_t > 0$ temperature parameters that control the sharpness of the output distribution of the two networks. The c can be omitted and will be explained later. Note that the scale or layout of the two feature maps z_θ^l and $z_\xi^{l'}$ can be inconsistent due to geometric image augmentations, *e.g.*, random crop, scale or flip. So we perform the inverse augmentation process (including RoIAlign [28] and an optional flipping, details provided in the supplementary file) on the predicted assignments to align their spatial locations: $\widetilde{\mathcal{Q}}_\xi^{l'} = \mathrm{invaug}\left(\mathcal{Q}_\xi^{l'} \right), \widetilde{\mathcal{P}}_\theta^l = \mathrm{invaug}\left(\mathcal{P}_\theta^l \right)$. The inverse augmentation is performed on the assignments $\mathcal{Q}$ rather than the projections z to keep the context information out of the overlapping area for slot generation, which will be detailed in Section 3.2.

Based on the aligned assignments, we apply the cross-entropy loss $\mathcal{L}_{\theta,\xi}^{\mathrm{CE}} \left(q_\xi, p_\theta \right) = -\sum_k q_\xi^k \log p_\theta^k$ to enforce the consistency in assignment score between spatial-aligned pixels from different views. The cross-entropy loss is averaged over all spatial locations to produce the grouping loss:

$$\mathcal{L}_{\theta,\xi}^{\mathrm{Group}} = \frac{1}{H \times W} \sum_{i,j} \left[\mathcal{L}_{\theta,\xi}^{\mathrm{CE}} \left(\widetilde{\mathcal{Q}}_\xi^2[i,j], \widetilde{\mathcal{P}}_\theta^1[i,j] \right) + \mathcal{L}_{\theta,\xi}^{\mathrm{CE}} \left(\widetilde{\mathcal{Q}}_\xi^1[i,j], \widetilde{\mathcal{P}}_\theta^2[i,j] \right) \right] . \quad (2)$$

Directly optimizing the above objective resembles an unsupervised variant of Mean Teacher [52], which collapses as shown in [25]. In order to avoid collapsing, we follow [7] to maintain a *mean logit* $c \in \mathbb{R}^K$ and reduce it when producing the teacher assignments $\mathcal{Q}_\xi$, as indicated in Eq. 1. The mean logit stores an exponential moving average of all the logits produced by the teacher network:

$$c \leftarrow \lambda_c c + (1 - \lambda_c) \frac{1}{B \times H \times W} \sum_{i,j,k} \overline{z}_\xi^{(i)}[j,k] \cdot \overline{\mathcal{S}}_\xi^\top , \quad (3)$$

where B stands for the batch size. Intuitively, reducing the mean logit amplifies the difference in assignment between different pixels, hence avoiding all pixels to be assigned to the same prototype. Besides that, the teacher temperature τ_t is set to be smaller than the student temperature τ_s to produce a sharper target and avoid uniform assignments. Both operations help avoiding collapse, and enforces the network to learn a meaningful semantic grouping.

Discussions. The resulting solution for semantic grouping may seem like a naive extension of DINO [7]. However, this is far from the whole picture. DINO is an image-level representation learning approach that adopts a very large amount of prototypes (*e.g.*, 65536) that are *shared over the whole dataset*, the only objective is representation learning and the prototypes are just adopted as proxies for feature matching. In contrary, our objective builds on pixel-level and is specialized to learn a meaningful semantic grouping (see Table 5 and Figure 2), and require much less prototypes (*e.g.*, 256 for COCO, see ablations in Table 7a). The representation learning is instead performed through

contrastive learning over the learned groups that are *adaptive to each image* (detailed in Section 3.2), which significantly contribute to the performance (see ablations in Table 7b). Our method overall presents a novel view for the decoupling of online clustering and representation learning, and the motivation from DINO mainly lies in the techniques for avoiding collapse during online clustering.

3.2 Group-level representation learning by contrasting slots

Inspired by Slot Attention [43], we then reuse the assignments computed by the semantic grouping module in Eq. 1 to perform attentive pooling over the dense projections z to produce group-level feature vectors (rephrased as *slots*), as shown in Fig. 1. Intuitively, as the $\mathrm{softmax}$ normalization applies to the slot dimension, the attention coefficients sum to one for each individual input feature vector. As a result, the soft assignments $\mathcal{A}$ of the dense projections z w.r.t. the corresponding prototypes $\mathcal{S}$ can also be viewed as the attention coefficients that describe how the prototypes decompose the dense projections into non-overlapping groups. This inspires us to decompose the dense projections with attentive pooling following [43]. Specifically, for a dense projection z_θ^l produced from view v^l, we extract K slots:

$$\mathcal{S}_\theta^l = \frac{1}{\sum_{i,j} \mathcal{A}_\theta^l[i,j]} \sum_{i,j} \mathcal{A}_\theta^l[i,j] \odot z_\theta^l[i,j] \in \mathbb{R}^{K \times D}, \mathcal{A}_\theta^l = \underset{K}{\mathrm{softmax}} \left(\overline{z}_\theta^l \cdot \overline{\mathcal{S}}_\theta^\top / \tau_t \right) \in \mathbb{R}^{H \times W \times K}, \tag{4}$$

where $\odot$ denotes the Hadamard product, and similar operation applies for the teacher network to produce $\mathcal{S}_\xi^{l'}$. Note that since the initial slots are shared by the whole dataset, the corresponding semantic may be missing in a specific view v^l, thus producing redundant slots. Therefore, we compute the following binary indicator $\mathbb{1}^l$ to mask out the slots that fail to occupy a dominating pixel:

$$\mathbb{1}_\theta^{k,l} = \exists_{i,j} \quad \text{such that} \quad \underset{K}{\arg\max} \left(\mathcal{A}_\theta^l \right) [i,j] = k, \tag{5}$$

and $\mathbb{1}_\xi^{l'}$ is computed similarly. Following the literature in object-level SSL [57, 30, 66, 31], we then apply a contrastive learning objective to discriminate the slot that hold the same semantic across views from distracting slots with the InfoNCE [55] loss:

$$\mathcal{L}_{\theta,\xi}^{\mathrm{InfoNCE}} \left(\mathcal{S}_\theta^l, \mathcal{S}_\xi^{l'} \right) = \frac{1}{K} \sum_{k=1}^K -\log \frac{\mathbb{1}_\theta^{k,l} \mathbb{1}_\xi^{k,l'} \exp \left(\overline{q_\theta} \left(s_\theta^{k,l} \right) \cdot \overline{s}_\xi^{k,l'} / \tau_c \right)}{\sum_{k'} \mathbb{1}_\theta^{k,l} \mathbb{1}_\xi^{k',l'} \exp \left(\overline{q_\theta} \left(s_\theta^{k,l} \right) \cdot \overline{s}_\xi^{k',l'} / \tau_c \right)}. \tag{6}$$

This objective helps maximize the similarity between different views of the same slot, while minimizing the similarity between slots from another view with different semantics and all slots from other images. Note that here an additional predictor q_θ with the same architecture as the projector g_θ is applied to the slots $\mathcal{S}_\theta$ as empirically it yields stronger performance [11, 62, 31]. And the resulting slot-level contrastive loss also follow a symmetric design like Eq. 2:

$$\mathcal{L}_{\theta,\xi}^{\mathrm{Slot}} = \mathcal{L}_{\theta,\xi}^{\mathrm{InfoNCE}} \left(\mathcal{S}_\theta^1, \mathcal{S}_\xi^2 \right) + \mathcal{L}_{\theta,\xi}^{\mathrm{InfoNCE}} \left(\mathcal{S}_\theta^2, \mathcal{S}_\xi^1 \right). \tag{7}$$

3.3 The overall optimization objective

We jointly optimize the semantic grouping objective (Eq. 2) and the group-level contrastive learning objective (Eq. 7), controlled with a balancing factor λ_g:

$$\mathcal{L}_{\theta,\xi}^{\mathrm{Overall}} = \lambda_g \mathcal{L}_{\theta,\xi}^{\mathrm{Group}} + (1 - \lambda_g) \mathcal{L}_{\theta,\xi}^{\mathrm{Slot}}. \tag{8}$$

At each training step, the student network is optimized with gradients from the overall loss function: $\theta \leftarrow \mathrm{optimizer} \left(\theta, \nabla_\theta \mathcal{L}_{\theta,\xi}^{\mathrm{Overall}}, \eta \right)$, where η denotes the learning rate; and the teacher network updates as an exponential moving average of the student network: $\xi \leftarrow \lambda_t \xi + (1 - \lambda_t)\theta$, with λ_t denoting the momentum value. After training, only the teacher encoder f_ξ is kept for downstream tasks.

4 Experiments

4.1 Implementation details

Pre-training datasets. We pre-train our models on COCO `train2017` [41] and ImageNet-1K [15], respectively. COCO `train2017` [41] contains ~118K images of diverse scenes with objects of

multiple scales, which is closer to real-world scenarios. In contrast, ImageNet-1K is a curated object-centric dataset containing more than $\sim$1.28M images, which is better for evaluating a model's potential with large-scale data. Besides, we also explore the limit of scene-centric pre-training on COCO+, *i.e.* COCO `train2017` set plus the `unlabeled2017` set. See details in Table 1.

Data augmentation. The image augmentation setting is the same as BYOL [25]: a 224×224-pixel random resized crop with a random horizontal flip, followed by a random color distortion, random grayscale conversion, random Gaussian blur, and so-larization. The crop pairs without overlap are discarded during training.

Table 1: Details of the datasets used for pre-training.

Dateset	#Img.	#Obj./Img.	#Class
ImageNet-1K [15]	1.28M	1.7	1000
COCO [41]	118K	7.3	80
COCO+ [41]	241K	N/A	N/A

Network architecture. We adopt ResNet-50 [29] as the default encoder for f_θ and g_ξ. The projector g_θ and predictor q_θ are two-layer MLPs whose architecture are identical to that in [7] with a hidden dimension of 4096 and the output dimension is 256.

Optimization. We adopt the LARS optimizer [71] to pre-train the model, with a batch size of 512 across 8 NVIDIA 2080 Ti GPUs. Following [67], we utilize the cosine learning rate decay schedule [45] with a base learning rate of 1.0, linearly scaled with the batch size (LearningRate $= 1.0 \times$ BatchSize$/256$), a weight decay of 10^{-5}, and a warm-up period of 5 epochs. Following [66, 60, 67], the model is pre-trained for 800 epochs on COCO(+) and 100/200 epochs on ImageNet, respectively. Following the common practice of [25], the momentum value λ_t starts from 0.99 and is increased to 1 in the teacher model. Synchronized batch normalization and automatic mixed precision are also enabled during training.

Hyper-parameters. The temperature values τ_s and τ_t in the student and teacher model are set to 0.1 and 0.07, respectively. Besides, the center momentum λ_c is set to 0.9. While the default number of prototypes K is set to 256 for COCO(+), and 2048 for ImageNet, respectively. Additionally, the default balancing ratio λ_g is set to 0.5.

4.2 Evaluation protocols

Following the common practice of previous self-supervised works[60, 67, 66], we evaluate the representation ability of the pre-trained models by taking it as the backbone of downstream tasks. Specifically, we add a newly initialized task-specific head to the pre-trained model for different downstream tasks. *i.e.* object detection and instance segmentation on COCO [41], and semantic segmentation on PASCAL VOC [20], Cityscapes [13], and ADE20K [76].

Object detection and instance segmentation. We train a Mask R-CNN [28] model with R50-FPN [40] backbone implemented in `Detectron2` [63]. We fine-tune all layers end-to-end on COCO `train2017` split with the standard $1\times$ schedule and report AP, AP_{50}, AP_{75} on the `val2017` split. Following [27] we train with the standard $1\times$ schedule with batch normalization layers synchronized.

Semantic segmentation. The evaluations details of PASCAL VOC and Cityscapes strictly follow [27]. We take our network to initialize the backbone of a fully-convolutional network [44] and fine-tune all the layers end-to-end. For PASCAL VOC, we fine-tune the model on `train_aug2012` set for 30k iterations and report the mean intersection over union (mIoU) on the `val2012` set. For Cityscapes, we fine-tune on the `train_fine` set for 90k iterations and evaluate it on the `val_fine` set. For ADE20K, we follow the standard 80k iterations schedule of `MMSegmentation` [12].

Unsupervised semantic segmentation. We also evaluate the model's ability of discovering semantic groups in complex scenes, which is accomplished by performing unsupervised semantic segmentation on COCO-Stuff [4]. We follow the common practice in this field [35, 34, 33] to merge the labels into 27 categories (15 "stuff" categories and 12 "thing" categories), and evaluate with a subset created by [35]. We inference with resolution 320 and number of prototypes 27 following the common practice. The predicted labels are matched with the ground truth through Hungarian matching [38], and evaluate on mIoU and pixel accuracy (pAcc).

Table 2: **Main transfer results with COCO pre-training.** We report the results in COCO [41] object detection, COCO instance segmentation, and semantic segmentation in Cityscapes [13], PASCAL VOC [20] and ADE20K [76]. Compared with other image-, pixel-, and object-level self-supervised learning methods, our method shows consistent improvements over different tasks without leveraging multi-crop [6] and objectness priors. (†: re-impl. w/ official weights; ‡: full re-impl.)

Method	Epochs	Multi crop	Obj. Prior	COCO detection			COCO segmentation			Semantic seg. (mIoU)		
				AP^b	AP^b_{50}	AP^b_{75}	AP^m	AP^m_{50}	AP^m_{75}	City.	VOC	ADE
random init.	-	✗	✗	32.8	50.9	35.3	29.9	47.9	32.0	65.3	39.5	29.4
Image-level approaches												
MoCo v2‡ [9]	800	✗	✗	38.5	58.1	42.1	34.8	55.3	37.3	73.8	69.2	36.2
Revisit.† [56]	800	✓	✗	40.1	60.2	43.6	36.3	57.3	38.9	75.3	70.6	37.0
Pixel-level approaches												
Self-EMD [42]	800	✗	✗	39.3	60.1	42.8	-	-	-	-	-	-
DenseCL† [60]	800	✗	✗	39.6	59.3	43.3	35.7	56.5	38.4	75.8	71.6	37.1
PixPro‡ [67]	800	✗	✗	40.5	60.5	44.0	36.6	57.8	39.0	75.2	**72.0**	38.3
Object / Group-level approaches												
DetCon† [30]	1000	✗	✓	39.8	59.5	43.5	35.9	56.4	38.7	76.1	70.2	38.1
ORL† [66]	800	✓	✓	40.3	60.2	44.4	36.3	57.3	38.9	75.6	70.9	36.7
Ours (SlotCon)	800	✗	✗	**41.0**	**61.1**	**45.0**	**37.0**	**58.3**	**39.8**	**76.2**	71.6	**39.0**

4.3 Transfer learning results

COCO pretraining. In Table 2 we show the main results with COCO pre-training. There have been steady improvements in object-level pre-training with COCO, in which the top performance methods are DetCon [39] and ORL [66], which still rely on objectness priors like selective-search [54] or hand-crafted segmentation algorithm [21], yet fail to beat the pixel-level state-of-the-art PixPro [67].[1] Our method alleviates such limitations and significantly improves over current object-level methods in all tasks, achieving consistent improvement over the previous approaches, and even several methods that were pre-trained on the large dataset ImageNet-1K (Table 3). It is also notable that our method can achieve a better performance on the largest and most challenging dataset for segmentation, ADE20K, adding to the significance of this work.

Table 3: **Main transfer results with ImageNet-1K pre-training.** Our method is also compatible with object-centric data, and shows consistent improvements over different tasks under *fair* comparisons without using FPN [40] and objectness priors. (†: re-impl. w/ official weights; ‡: full re-impl.)

Method	Epochs	w/ FPN	Obj. Prior	COCO detection			COCO segmentation			Semantic seg. (mIoU)		
				AP^b	AP^b_{50}	AP^b_{75}	AP^m	AP^m_{50}	AP^m_{75}	City.	VOC	ADE
random init.	-	✗	✗	32.8	50.9	35.3	29.9	47.9	32.0	65.3	39.5	29.4
supervised	100	✗	✗	39.7	59.5	43.3	35.9	56.6	38.6	74.6	74.4	37.9
Image-level approaches												
MoCo v2† [9]	800	✗	✗	40.4	60.1	44.2	36.5	57.2	39.2	76.2	73.7	36.9
DetCo† [65]	200	✗	✗	40.1	61.0	43.9	36.4	58.0	38.9	76.0	72.6	37.8
InsLoc† [68]	200	✓	✗	40.9	60.9	44.7	36.8	57.8	39.4	75.4	72.9	37.3
Pixel-level approaches												
DenseCL† [60]	200	✗	✗	40.3	59.9	44.3	36.4	57.0	39.2	76.2	72.8	38.1
PixPro† [67]	100	✗	✗	40.7	60.5	44.8	36.8	57.4	39.7	**76.8**	73.9	38.2
Object / Group-level approaches												
DetCon [30]	200	✗	✓	40.5	-	-	36.4	-	-	76.5	72.6	-
SoCo‡ [62]	100	✓	✓	41.6	61.9	45.6	37.4	58.8	40.2	76.5	71.9	37.8
Ours (SlotCon)	100	✗	✗	41.4	61.6	45.6	37.2	58.5	39.9	75.4	73.1	38.6
Ours (SlotCon)	200	✗	✗	**41.8**	**62.2**	**45.7**	**37.8**	**59.1**	**40.7**	76.3	**75.0**	**38.8**

---

[1] PixPro aggregates the global context with self-attention [58], so each pixel can also be viewed as an object-level embedding.

ImageNet-1K pre-training. In Table 3, we also benchmark our method with ImageNet-1k pre-training to compare it with most of the current works and show its compatibility with object-centric data. Without selective-search for object proposals and without pre-training and transferring the FPN head, our method still beats most of the current works and largely closes the gap with SoCo.

Table 4: **Pushing the limit of scene-centric pre-training.** Our method further sees a notable gain in all tasks with extended COCO+ data, showing the great potential of scene-centric pre-training.

Method	Dataset	Epochs	COCO detection			COCO segmentation			Semantic seg. (mIoU)		
			AP^b	AP^b_{50}	AP^b_{75}	AP^m	AP^m_{50}	AP^m_{75}	City.	VOC	ADE
SlotCon	COCO	800	41.0	61.1	45.0	37.0	58.3	39.8	76.2	71.6	39.0
SlotCon	ImageNet	100	41.4	61.6	45.6	37.2	58.5	39.9	75.4	73.1	38.6
SlotCon	ImageNet	200	**41.8**	**62.2**	45.7	**37.8**	59.1	**40.7**	76.3	**75.0**	38.8
ORL [66]	COCO+	800	40.6	60.8	44.5	36.7	57.9	39.3	-	-	-
SlotCon	COCO+	800	**41.8**	**62.2**	**45.8**	**37.8**	**59.4**	40.6	**76.5**	73.9	**39.2**

COCO+ pre-training. In Table 4, we report the results with COCO+ pre-training. The COCO+ is COCO `train2017` plus `unlabeled2017` set, which roughly doubles the number of training images and greatly adds to the data diversity. Our method further sees a notable gain in all tasks with extended COCO+ data, and even show comparable results with our best-performing model pre-trained on ImageNet-1K ($5\times$ large of COCO+), showing the great potential of scene-centric pre-training.

4.4 Unsupervised semantic segmentation results

Table 5: Main results in COCO-Stuff unsupervised semantic segmentation.

Method	mIoU	pAcc
MaskContrast [57]	8.86	23.03
PiCIE + H. [34]	14.36	49.99
SegDiscover [33]	14.34	**56.53**
Ours (SlotCon)	**18.26**	42.36

Given the consistent improvement our approach achieved in representation learning, we need further analysis of how well our semantic grouping component can parse scenes quantitatively and qualitatively. Unlike current SSL approaches that exhaustively enumerate the massive object proposals and report the best score [7, 31], we follow the common practice of unsupervised semantic segmentation [34, 33] to match the predicted results with the ground-truth using the Hungarian algorithm [38], where each ground-truth label is assigned to a prototype mutual-exclusively. For fair comparisons, the model used for evaluation is trained with $K = 27$ to match the number of categories of COCO-Stuff. As shown in Table 5, our method can surpass the previous works PiCIE [34] and SegDiscover [33] with 4 points higher mIoU. Besides, the pAcc is lower since we pre-train the model with a lower resolution (7×7 v.s. 80×80 feature map). Table 5 also depicts the visualization result, our method distinguishes confusing objects apart (4th column) and successfully localizes small objects (5th column). Since we only need to separate pixels with different semantics within the same image, the errors in category prediction can be ignored.

4.5 Ablation study

Number of prototypes K. Table 7a ablates the number of prototypes, we observe that the most suitable K for COCO detection is 256, which is around its real semantic class number 187 (thing + stuff) [4]. Besides, the performance on Cityscapes and PASCAL VOC have a consistent tendency of dropping, while the performance on ADE20K is consistently good if K is big enough. We hypothesis that a suitable K can encourage learning data-specific semantic features, which are only helpful when the pre-training and downstream data are alike (from COCO to COCO); increasing K produces fine-grained features that may lack discriminability in semantics but hold better transferability to ADE20K that require fine-grained segmentation [14].

Table 6: **Ablation studies with COCO 800 epochs pre-training.** We show the AP^b on COCO objection detection and mIoU on Cityscapes, PASCAL VOC, and ADE20K semantic segmentation. The default options are marked with gray background.

(a) **Number of prototypes**					(b) **Loss balancing**					(c) **Teacher temperature**				
K	COCO	City	VOC	ADE	λ_g	COCO	City	VOC	ADE	τ_t	COCO	City	VOC	ADE
128	40.7	**76.4**	**71.9**	38.5	0.3	**41.0**	76.1	**72.1**	37.9	0.04	40.4	75.5	70.2	37.9
256	**41.0**	76.2	71.6	39.0	0.5	**41.0**	**76.2**	71.6	**39.0**	0.07	**41.0**	**76.2**	**71.6**	**39.0**
512	40.9	75.6	71.6	38.9	0.7	40.5	75.2	71.5	38.4					
1024	40.7	75.8	70.9	**39.1**	1.0	40.4	74.2	70.1	38.6					

Loss balancing weight λ_g. Table 7b ablates the balancing between the semantic grouping loss and the group-level contrastive loss, where the best balance is achieved with both losses treated equally. It is notable that when $\lambda_g = 1.0$, only the semantic grouping loss is applied, and the performance drops considerably, indicating the importance of our group-level contrastive loss.

Teacher temperature τ_t. Table 7c ablates the temperature parameter for the teacher model, and it indicates that a softer teacher distribution with $\tau_t = 0.07$ helps achieve good performance.

4.6 Probing the prototypes

Figure 2: Example of visual concepts discovered by our method from the COCO `val2017` split. Each column shows the top-5 segments retrieved with the same prototype, marked with reddish masks or arrows. Our method can discover visual concepts across a wide range of scenarios and semantic granularities regardless of small object size and occlusion. (*best viewed in color*)

Finally, we analyze whether the prototypes learn semantic meanings by visualizing their nearest-neighbors in COCO `val2017` split. We first perform semantic grouping on each image to split them into non-overlapping groups (segments), then pool each group to a feature vector, and retrieve the top-5 nearest-neighbor segments for each prototypes according to cosine similarity. As shown in Fig. 2, the prototypes well bind to semantic meanings that cover a wide range of scenarios and semantic granularities from animals, foods, and sports, to furniture, buildings, etc., localizing them well regardless of small object size and occlusion; and notably, *without any human annotation*.

5 Conclusion

This work presents a unified framework for joint semantic grouping and representation learning from unlabeled scene-centric images. The semantic grouping is performed by assigning pixels to a set of learnable prototypes, which can adapt to each sample by attentive pooling over the feature and form new slots. Based on the learned data-dependent slots, a contrastive objective is employed for representation learning, enhancing features' discriminability and facilitating the grouping of semantically coherent pixels together. By simultaneously optimizing the two coupled objectives of semantic grouping and contrastive learning, the proposed approach bypasses the disadvantages of handcrafted priors and can learn object/group-level representations from scene-centric images. Experiments show the proposed approach effectively decomposes complex scenes into semantic groups for feature learning and significantly facilitates downstream tasks, including object detection, instance segmentation, and semantic segmentation.

References

[1] Federico Baldassarre and Hossein Azizpour. Towards Self-Supervised Learning of Global and Object-Centric Representations. *arXiv:2203.05997 [cs]*, March 2022.

[2] Hangbo Bao, Li Dong, and Furu Wei. BEiT: BERT Pre-Training of Image Transformers. *arXiv:2106.08254 [cs]*, June 2021.

[3] Christopher P. Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. MONet: Unsupervised Scene Decomposition and Representation. *arXiv:1901.11390 [cs, stat]*, January 2019.

[4] Holger Caesar, Jasper Uijlings, and Vittorio Ferrari. COCO-Stuff: Thing and Stuff Classes in Context. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1209–1218, June 2018.

[5] Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep Clustering for Unsupervised Learning of Visual Features. In Vittorio Ferrari, Martial Hebert, Cristian Sminchisescu, and Yair Weiss, editors, *Computer Vision – ECCV 2018*, pages 139–156, Cham, 2018. Springer International Publishing.

[6] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 9912–9924. Curran Associates, Inc., 2020.

[7] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging Properties in Self-Supervised Vision Transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9650–9660, 2021.

[8] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A Simple Framework for Contrastive Learning of Visual Representations. In *Proceedings of the 37th International Conference on Machine Learning*, pages 1597–1607. PMLR, November 2020.

[9] Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved Baselines with Momentum Contrastive Learning. *arXiv:2003.04297 [cs]*, March 2020.

[10] Xinlei Chen and Kaiming He. Exploring Simple Siamese Representation Learning. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15745–15753, Nashville, TN, USA, June 2021. IEEE.

[11] Xinlei Chen, Saining Xie, and Kaiming He. An Empirical Study of Training Self-Supervised Vision Transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9640–9649, 2021.

[12] MMSegmentation Contributors. MMSegmentation: Openmmlab semantic segmentation toolbox and benchmark. https://github.com/open-mmlab/mmsegmentation, 2020.

[13] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The Cityscapes Dataset for Semantic Urban Scene Understanding. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3213–3223. IEEE Computer Society, June 2016.

[14] Quan Cui, Bingchen Zhao, Zhao-Min Chen, Borui Zhao, Renjie Song, Jiajun Liang, Boyan Zhou, and Osamu Yoshie. Discriminability-Transferability Trade-Off: An Information-Theoretic Perspective. *arXiv:2203.03871 [cs]*, March 2022.

[15] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, June 2009.

[16] Carl Doersch, Abhinav Gupta, and Alexei A. Efros. Unsupervised Visual Representation Learning by Context Prediction. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pages 1422–1430, December 2015.

[17] Alexey Dosovitskiy, Philipp Fischer, Jost Tobias Springenberg, Martin Riedmiller, and Thomas Brox. Discriminative unsupervised feature learning with exemplar convolutional neural networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 38(9):1734–1747, 2015.

[18] Debidatta Dwibedi, Yusuf Aytar, Jonathan Tompson, Pierre Sermanet, and Andrew Zisserman. With a Little Help From My Friends: Nearest-Neighbor Contrastive Learning of Visual Representations. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9588–9597, 2021.

[19] Martin Engelcke, Adam R. Kosiorek, Oiwi Parker Jones, and Ingmar Posner. GENESIS: Generative Scene Inference and Sampling with Object-Centric Latent Representations. In *International Conference on Learning Representations*, September 2019.

[20] Mark Everingham, S. M. Ali Eslami, Luc Van Gool, Christopher K. I. Williams, John Winn, and Andrew Zisserman. The Pascal Visual Object Classes Challenge: A Retrospective. *International Journal of Computer Vision*, 111(1):98–136, January 2015.

[21] Pedro F. Felzenszwalb and Daniel P. Huttenlocher. Efficient Graph-Based Image Segmentation. *International Journal of Computer Vision*, 59(2):167–181, September 2004.

[22] Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised Representation Learning by Predicting Image Rotations. In *International Conference on Learning Representations*, February 2018.

[23] Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-Object Representation Learning with Iterative Variational Inference. In *Proceedings of the 36th International Conference on Machine Learning*, pages 2424–2433. PMLR, May 2019.

[24] Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the Binding Problem in Artificial Neural Networks. *arXiv:2012.05208 [cs]*, December 2020.

[25] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, koray kavukcuoglu, Remi Munos, and Michal Valko. Bootstrap your own latent - a new approach to self-supervised learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 21271–21284. Curran Associates, Inc., 2020.

[26] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked Autoencoders Are Scalable Vision Learners. *arXiv:2111.06377 [cs]*, December 2021.

[27] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum Contrast for Unsupervised Visual Representation Learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, June 2020.

[28] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 2980–2988, October 2017.

[29] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, June 2016.

[30] Olivier J. Hénaff, Skanda Koppula, Jean-Baptiste Alayrac, Aaron van den Oord, Oriol Vinyals, and João Carreira. Efficient Visual Pretraining With Contrastive Detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10086–10096, 2021.

[31] Olivier J. Hénaff, Skanda Koppula, Evan Shelhamer, Daniel Zoran, Andrew Jaegle, Andrew Zisserman, João Carreira, and Relja Arandjelović. Object discovery and representation networks. *arXiv:2203.08777 [cs]*, March 2022.

[32] R. Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *International Conference on Learning Representations*, September 2018.

[33] Haiyang Huang, Zhi Chen, and Cynthia Rudin. SegDiscover: Visual Concept Discovery via Unsupervised Semantic Segmentation. *arXiv:2204.10926 [cs]*, April 2022.

[34] Jang Hyun Cho, Utkarsh Mall, Kavita Bala, and Bharath Hariharan. PiCIE: Unsupervised Semantic Segmentation using Invariance and Equivariance in Clustering. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 16789–16799, Nashville, TN, USA, June 2021. IEEE.

[35] Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 9865–9874, 2019.

[36] Thomas Kipf, Gamaleldin F. Elsayed, Aravindh Mahendran, Austin Stone, Sara Sabour, Georg Heigold, Rico Jonschkowski, Alexey Dosovitskiy, and Klaus Greff. Conditional Object-Centric Learning from Video. *arXiv:2111.12594 [cs, stat]*, March 2022.

[37] Thomas Kipf, Elise van der Pol, and Max Welling. Contrastive Learning of Structured World Models. In *International Conference on Learning Representations*, September 2019.

[38] H. W. Kuhn. The Hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, 2(1-2):83–97, 1955.

[39] Chunyuan Li, Jianwei Yang, Pengchuan Zhang, Mei Gao, Bin Xiao, Xiyang Dai, Lu Yuan, and Jianfeng Gao. Efficient Self-supervised Vision Transformers for Representation Learning. *arXiv:2106.09785 [cs]*, June 2021.

[40] Tsung-Yi Lin, Piotr Dollár, Ross Girshick, Kaiming He, Bharath Hariharan, and Serge Belongie. Feature Pyramid Networks for Object Detection. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 936–944, July 2017.

[41] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft COCO: Common Objects in Context. In David Fleet, Tomas Pajdla, Bernt Schiele, and Tinne Tuytelaars, editors, *Computer Vision – ECCV 2014*, pages 740–755, Cham, 2014. Springer International Publishing.

[42] Songtao Liu, Zeming Li, and Jian Sun. Self-EMD: Self-Supervised Object Detection without ImageNet. *arXiv:2011.13677 [cs]*, March 2021.

[43] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 11525–11538. Curran Associates, Inc., 2020.

[44] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3431–3440, June 2015.

[45] Ilya Loshchilov and Frank Hutter. SGDR: Stochastic Gradient Descent with Warm Restarts. *arXiv:1608.03983 [cs, math]*, May 2017.

[46] Sindy Löwe, Klaus Greff, Rico Jonschkowski, Alexey Dosovitskiy, and Thomas Kipf. Learning Object-Centric Video Models by Contrasting Sets. *arXiv:2011.10287 [cs]*, November 2020.

[47] Mehdi Noroozi and Paolo Favaro. Unsupervised Learning of Visual Representations by Solving Jigsaw Puzzles. In Bastian Leibe, Jiri Matas, Nicu Sebe, and Max Welling, editors, *Computer Vision – ECCV 2016*, pages 69–84, Cham, 2016. Springer International Publishing.

[48] Mehdi Noroozi, Hamed Pirsiavash, and Paolo Favaro. Representation Learning by Learning to Count. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 5899–5907, October 2017.

[49] Pedro O O. Pinheiro, Amjad Almahairi, Ryan Benmalek, Florian Golemo, and Aaron C Courville. Unsupervised learning of dense visual representations. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 4489–4500. Curran Associates, Inc., 2020.

[50] Deepak Pathak, Philipp Krähenbühl, Jeff Donahue, Trevor Darrell, and Alexei A. Efros. Context Encoders: Feature Learning by Inpainting. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2536–2544, June 2016.

[51] Ramprasaath R. Selvaraju, Karan Desai, Justin Johnson, and Nikhil Naik. CASTing Your Model: Learning to Localize Improves Self-Supervised Representations. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11053–11062, June 2021.

[52] Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[53] Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 6827–6839. Curran Associates, Inc., 2020.

[54] J. R. R. Uijlings, K. E. A. van de Sande, T. Gevers, and A. W. M. Smeulders. Selective Search for Object Recognition. *International Journal of Computer Vision*, 104(2):154–171, September 2013.

[55] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation Learning with Contrastive Predictive Coding. *arXiv:1807.03748 [cs, stat]*, January 2019.

[56] Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, and Luc V Gool. Revisiting contrastive methods for unsupervised learning of visual representations. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 16238–16250. Curran Associates, Inc., 2021.

[57] Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, and Luc Van Gool. Unsupervised Semantic Segmentation by Contrasting Object Mask Proposals. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10052–10062, 2021.

[58] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, pages 6000–6010, Red Hook, NY, USA, December 2017. Curran Associates Inc.

[59] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th International Conference on Machine Learning - ICML '08*, pages 1096–1103, Helsinki, Finland, 2008. ACM Press.

[60] Xinlong Wang, Rufeng Zhang, Chunhua Shen, Tao Kong, and Lei Li. Dense Contrastive Learning for Self-Supervised Visual Pre-Training. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3023–3032, Nashville, TN, USA, June 2021. IEEE.

[61] Chen Wei, Haoqi Fan, Saining Xie, Chao-Yuan Wu, Alan Yuille, and Christoph Feichtenhofer. Masked Feature Prediction for Self-Supervised Visual Pre-Training. *arXiv:2112.09133 [cs]*, December 2021.

[62] Fangyun Wei, Yue Gao, Zhirong Wu, Han Hu, and Stephen Lin. Aligning Pretraining for Detection via Object-Level Contrastive Learning. In *Advances in Neural Information Processing Systems*, volume 34, pages 22682–22694. Curran Associates, Inc., 2021.

[63] Yuxin Wu, Alexander Kirillov, Francisco Massa, Wan-Yen Lo, and Ross Girshick. Detectron2. `https://github.com/facebookresearch/detectron2`, 2019.

[64] Zhirong Wu, Yuanjun Xiong, Stella X. Yu, and Dahua Lin. Unsupervised Feature Learning via Non-parametric Instance Discrimination. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3733–3742, June 2018.

[65] Enze Xie, Jian Ding, Wenhai Wang, Xiaohang Zhan, Hang Xu, Peize Sun, Zhenguo Li, and Ping Luo. DetCo: Unsupervised Contrastive Learning for Object Detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8392–8401, 2021.

[66] Jiahao Xie, Xiaohang Zhan, Ziwei Liu, Yew Soon Ong, and Chen Change Loy. Unsupervised object-level representation learning from scene images. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 28864–28876. Curran Associates, Inc., 2021.

[67] Zhenda Xie, Yutong Lin, Zheng Zhang, Yue Cao, Stephen Lin, and Han Hu. Propagate Yourself: Exploring Pixel-Level Consistency for Unsupervised Visual Representation Learning. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 16679–16688, Nashville, TN, USA, June 2021. IEEE.

[68] Ceyuan Yang, Zhirong Wu, Bolei Zhou, and Stephen Lin. Instance Localization for Self-supervised Detection Pretraining. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3986–3995, June 2021.

[69] Charig Yang, Hala Lamdouar, Erika Lu, Andrew Zisserman, and Weidi Xie. Self-Supervised Video Object Segmentation by Motion Grouping. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 7177–7188, 2021.

[70] Asano Ym, Rupprecht C, and Vedaldi A. Self-labelling via simultaneous clustering and representation learning. In *International Conference on Learning Representations*, September 2019.

[71] Yang You, Igor Gitman, and Boris Ginsburg. Large Batch Training of Convolutional Networks. *arXiv:1708.03888 [cs]*, September 2017.

[72] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stephane Deny. Barlow Twins: Self-Supervised Learning via Redundancy Reduction. In *Proceedings of the 38th International Conference on Machine Learning*, pages 12310–12320. PMLR, July 2021.

[73] Richard Zhang, Phillip Isola, and Alexei A. Efros. Colorful Image Colorization. In Bastian Leibe, Jiri Matas, Nicu Sebe, and Max Welling, editors, *Computer Vision – ECCV 2016*, pages 649–666, Cham, 2016. Springer International Publishing.

[74] Richard Zhang, Phillip Isola, and Alexei A. Efros. Split-Brain Autoencoders: Unsupervised Learning by Cross-Channel Prediction. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 645–654, July 2017.

[75] Xiao Zhang and Michael Maire. Self-supervised visual representation learning from hierarchical grouping. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 16579–16590. Curran Associates, Inc., 2020.

[76] Bolei Zhou, Hang Zhao, Xavier Puig, Tete Xiao, Sanja Fidler, Adela Barriuso, and Antonio Torralba. Semantic Understanding of Scenes Through the ADE20K Dataset. *International Journal of Computer Vision*, 127(3):302–321, March 2019.

[77] Jinghao Zhou, Chen Wei, Huiyu Wang, Wei Shen, Cihang Xie, Alan Yuille, and Tao Kong. iBOT: Image BERT Pre-Training with Online Tokenizer. *arXiv:2111.07832 [cs]*, January 2022.

[78] Rui Zhu, Bingchen Zhao, Jingen Liu, Zhenglong Sun, and Chang Wen Chen. Improving Contrastive Learning by Visualizing Feature Transformation. *arXiv:2108.02982 [cs]*, August 2021.

[79] Adrian Ziegler and Yuki M. Asano. Self-Supervised Learning of Object Parts for Semantic Segmentation. *arXiv:2204.13101 [cs]*, April 2022.