DIMINISHING RETURN OF VALUE EXPANSION METHODS IN MODEL-BASED REINFORCEMENT LEARNING

ABSTRACT

Model-based reinforcement learning is an approach to increase sample efficiency. However, the accuracy of the dynamics models and the resulting compounding error over trajectories are commonly regarded as a limitation of model-based approaches. A natural question to ask is: How much more sample efficiency can be gained by improving the learned dynamics models? Specifically, this paper addresses the value expansion class of model-based approaches. Our empirical study shows that expanding the value function for the critic or actor update increases sample efficiency, but the gain in improvement decreases with each added expansion step. Therefore, longer horizons yield diminishing returns in terms of sample efficiency. In an extensive experimental comparison that uses the oracle dynamics model to avoid compounding model error, we show that short horizons are sufficient to obtain the lowest sample complexity for the given tasks. For long horizons, the improvements are marginal or can even decrease learning performance despite using the oracle dynamics model. Model-free counterparts, which use off-policy trajectories from a replay buffer and introduce no computational overhead, often show on-par performance and pose as a strong baseline. Finally, as we observe the same issues with both oracle and learned models, we conclude that the limitation of model-based value expansion methods is not so much the model accuracy of the learned models. While higher model accuracy is beneficial, our experiments show that even a perfect model is not going to provide an un-rivalled sample efficiency, but that the bottleneck lies elsewhere.

1 INTRODUCTION

Sample efficiency is a central issue that prevents reinforcement learning (RL) agents from learning in physical environments. Especially in applications like robotics, samples from the real systems are particularly scarce and expensive to acquire due to the high cost of operating robots. A technique that has proven to substantially enhance sample efficiency is model-based reinforcement learning (Deisenroth et al., 2013). In model-based RL, a model of the system dynamics is usually learned from data, which is subsequently used for planning (Chua et al., 2018; Hafner et al., 2019) or for policy learning (Sutton, 1990; Janner et al., 2019).

Over the years, the model-based RL community has identified several ways of applying (learned) dynamics models in the RL framework. Sutton's (1990) DynaQ framework uses the model for data augmentation, where model rollouts are started from real environment states coming from a replay buffer. The collected data is afterwards given to a model-free RL agent. Recently, various improvements have been proposed to the original DynaQ algorithm, such as using ensemble neural network models and short rollout horizons (Janner et al., 2019; Lai et al., 2020), and improving the synthetic data generation with model predictive control (Morgan et al., 2021). Feinberg et al. (2018) proposed an alternative way of incorporating a dynamics model into the RL framework. Their model-based value expansion (MVE) algorithm unrolls the dynamics model and discounts along the modelled trajectory to approximate better targets for value function learning. Subsequent works were primarily concerned with adaptively setting the rollout horizon based on some (indirect) measure of the modelling error, e.g., model uncertainty (Buckman et al., 2018; Abbas et al., 2020), a reconstruction loss (Wang et al., 2020) or approximating the local model error through temporal difference learning (Xiao et al., 2019). Lastly, using backpropagation through time (BPTT) (Werbos, 1990), dynamics models have been applied to the policy improvement step to assist in computing better

policy gradients. Deisenroth & Rasmussen (2011) use Gaussian process regression (Rasmussen & Williams, 2006) and moment matching to find a closed-form solution for the gradient of the trajectory loss function. Others leverage the model's differentiability to algorithmically compute policy gradients. Stochastic value gradients (SVG) (Heess et al., 2015), uses a model in combination with the reparametrization trick (Kingma & Welling, 2014) to propagate gradients along real environment trajectories. Others differentiate through model trajectories (Byravan et al., 2020; Amos et al., 2021). On a more abstract level, MVE-type and SVG-type algorithms are very similar. They both learn a dynamics model and use it for H-step trajectories (where H is the number of modelled time steps) to better approximate the quantity of interest – the next state Q-function in the case of SVG and the Q-function for MVE. These value expansion methods all assume that longer rollout horizons will improve learning if the model is sufficiently accurate. The common opinion is that learning models with less prediction error may further improve the sample efficiency of RL. This argument is based on the fact that the single-step approximation error can become a substantial problem when using learned dynamics models. Minor modelling errors can accumulate quickly along the trajectory when multi-step trajectories are built by bootstrapping successive model predictions. This problem is known as the *compounding model error*. Furthermore, most bounds in model-based RL are usually dependent on the model error (Feinberg et al., 2018), and improvement guarantees assume model errors converging to zero. In practice, rollout horizons are often kept short to avoid significant compounding model error build-up (Janner et al., 2019). Intuitively, using longer model horizons has the potential of exploiting the benefits of the model even more. For this reason, immense research efforts have been put into building and learning better dynamics models. We can differentiate between purely engineered (white-box) models and learned (black-box) models (Nguyen-Tuong & Peters, 2011). White-box models offer many advantages over black-box models, as they are more interpretable and, thus, more predictable. However, most real-world robotics problems are too complex to model analytically, and one has to retreat to learning a (black-box) dynamics model (Chua et al., 2018; Janner et al., 2020). Recently, authors have proposed neural network models that use physics-based inductive biases, also known as grey-box models (Lutter et al., 2019a;b; Greydanus et al., 2019).

While research has focused on improving model quality, a question that has received little attention yet is: ***Is model-based reinforcement learning even limited by the model quality?*** For data augmentation algorithms, e.g. DynaQ and model-based policy optimization (MBPO) (Janner et al., 2019), the answer is yes, as these methods treat model- and real-environment samples the same. In this paper, we empirically address this question for a specific class of model-based reinforcement learning — *value expansion methods*. Using the true dynamics model, we empirically show that the sample efficiency does not increase significantly when a perfect model is used. Furthermore, we find that increasing the rollout horizon, even with oracle dynamics, yields *diminishing returns* in improving sample efficiency. With the phrase *diminishing returns*, we refer to its definition in economics (Case & Fair, 1999). In the context of rollout horizons in model-based RL, we mean that *increase in performance gain decreases with each additional model step* along a modelled trajectory.

Running our analysis would be highly inefficient with traditional CPU-based physics simulators (Todorov et al., 2012; Coumans & Bai, 2016–2021). For this reason, we use Brax (Freeman et al., 2021), a new JAX-based (Bradbury et al., 2018) simulator that runs on GPU-only. It allows us to seamlessly integrate oracle dynamics rollouts into the training procedure. Furthermore, Brax's differentiability is necessary for implementing value gradient methods with oracle dynamics.[1]

Contributions. In this paper, we empirically address the question of whether the sample efficiency of value expansion methods is limited by the dynamics model quality. We summarize our contributions as follows. (1) Using the oracle dynamics model, we empirically show that the sample efficiency of value expansion methods does not increase significantly over a learned model. (2) We find that increasing the rollout horizon yields diminishing returns in improving sample efficiency, even with oracle dynamics. (3) We show that off-policy RETRACE (Munos et al., 2016) is a very strong baseline, which adds virtually no computational overhead. (4) Our experiments show that for the critic expansion, the benefits of using a learned model does not appear to justify the added computational complexity.

---

[1]We will open-source our code upon publication.

2 H-STEP POLICY EVALUATION AND IMPROVEMENT

In this section, we introduce the necessary background and components of value expansion.

Reinforcement Learning.   Consider a discrete-time Markov Decision Process (MDP) (Puterman, 2014), defined by the tuple $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \rho, \gamma \rangle$ with state space $\mathcal{S}$ and action space $\mathcal{A}$. At each time step t, the agent observes a state $s_t \in \mathcal{S}$ and samples an action $a_t \in \mathcal{A}$ according to a (stochastic) policy $a_t \sim \pi(\cdot|s_t)$. The environment returns a next state $s_{t+1} \in \mathcal{S}$ according to the transition probability $s_{t+1} \sim \mathcal{P}(\cdot|s_t, a_t)$ and a scalar reward $r_t = \mathcal{R}(s_t, a_t)$. The initial state of a trajectory is sampled from the initial state distribution $s_0 \sim \rho$. $\gamma \in [0, 1)$ is a discount factor. Wherever it is clear, we will make use of the tick notation s' and a' to refer to the next state and action at time $t + 1$. A trajectory $\tau = (s_0, a_0, s_1, a_1, \ldots, s_T)$ is a sequence of states and actions. The objective of an RL agent is to find an optimal policy that maximizes the expected sum of discounted rewards $\pi^* = \arg\max_\pi \mathbb{E}_{\tau \sim \rho, \pi, \mathcal{P}} \left[\sum_{t=0}^{\infty} \gamma^t r_t \right]$. Often π is parametrized and, in the model-free case, it is common to optimize its parameters with on-policy (Sutton et al., 1999; Peters & Schaal, 2008; Schulman et al., 2015; 2017) or off-policy gradient methods (Degris et al., 2012; Silver et al., 2014; Lillicrap et al., 2016; Fujimoto et al., 2018; Haarnoja et al., 2018).

Model-Based Reinforcement Learning.   In model-based RL an approximate model $\hat{\mathcal{P}}$ of the true dynamics is learned, and optionally also an approximate reward function $\hat{\mathcal{R}}$. There are several ways to use these models for policy optimization: generate simulated data to populate a replay buffer, e.g. DynaQ (Sutton, 1990) and MBPO (Janner et al., 2019); planning with model predictive control (MPC) and stochastic optimization, e.g. PETS (Chua et al., 2018) and PlaNet (Hafner et al., 2019); and gradient-based optimization with BPTT , e.g. PILCO (Deisenroth & Rasmussen, 2011), SVG (Heess et al., 2015), MAAC (Clavera et al., 2020) and SAC-SVG(H) (Amos et al., 2021).

Maximum-Entropy Reinforcement Learning   (MaxEnt RL) augments the MDP's reward r_t with a policy entropy term, which avoids collapsing to a deterministic policy, thus implicitly enforcing continuing exploration (Ziebart et al., 2008; Fox et al., 2016; Haarnoja et al., 2017). The (soft) action-value function $Q^\pi(s, a) = \mathbb{E}_{\pi, \mathcal{P}} \left[\sum_{t=0}^{\infty} \gamma^t (r_t - \alpha \log \pi(a_t|s_t)) \mid s_0 = s, a_0 = a \right]$ computes the expected sum of discounted soft-rewards following a policy π. The goal is to maximize $\mathcal{J}_\pi = \mathbb{E}_{s_0 \sim \rho} \left[\sum_{t=0}^{\infty} \gamma^t (r_t - \alpha \log \pi(a_t|s_t)) \right]$ w.r.t. π. Haarnoja et al. (2018) have proposed the Soft Actor-Critic (SAC) algorithm to solve this objective. The SAC actor and critic losses are defined as

$$\mathcal{J}_\pi(\mathcal{D}) = \mathbb{E}_{s \sim \mathcal{D}} \left[-V^\pi(s) \right] = \mathbb{E}_{s \sim \mathcal{D}, \, a \sim \pi(\cdot|s)} \left[\alpha \log \pi(a|s) - Q^\pi(s, a) \right], \tag{1}$$

$$\mathcal{J}_Q(\mathcal{D}) = \mathbb{E}_{(s,a,r,s') \sim \mathcal{D}} \left[\left(r + \gamma V^\pi(s') - Q^\pi(s, a) \right)^2 \right], \tag{2}$$

where $\mathcal{D}$ is a dataset of previously collected transitions (replay buffer), and the next state value target is $V^\pi(s') = \mathbb{E}_{a' \sim \pi(\cdot|s')} \left[Q^\pi(s', a') - \alpha \log \pi(a'|s') \right]$. Note, that $r_t + \gamma V^\pi(s')$ is a target value, and, therefore, we do not differentiate through it, as is common practice in value functions approximated with (deep) neural networks (Riedmiller, 2005; Mnih et al., 2013).

Value Expansion.   Through the recursive definition of the value- and action-value functions (Bellman, 1957), they can be approximated by rolling out the model for H time steps. We refer to this (single sample) estimator as the H-step value expansion, defined as

$$Q^H(s, a) = \mathcal{R}(s, a) + \sum_{t=1}^{H-1} \gamma^t (r_t - \alpha \log \pi(a_t|s_t)) + \gamma^H V^\pi(s_H) \tag{3}$$

with $Q^0(s, a) := Q^\pi(s, a)$ and $V^\pi(s) = \mathbb{E}_{a \sim \pi(\cdot|s)} \left[Q^\pi(s, a) - \alpha \log \pi(a|s) \right]$. For $H = 0$ this estimator reduces to the function approximator used in SAC. It is important to note that these trajectories are on-policy. In practice, the SAC implementation uses a double Q-function (Fujimoto et al., 2018; Haarnoja et al., 2018), but to keep the notation simple we do not include it here. We further evaluate the expectation for the next state value function with a single sample, i.e. $V^\pi(s') = Q^\pi(s', a') - \log \pi(a'|s')$ with $a' \sim \pi(\cdot \mid s')$, as done in Haarnoja et al. (2018).

Actor Expansion.   The H-step value expansion can now be used in the actor update, by incorporating Equation 3 in the actor loss (Equation 1)

$$\mathcal{J}_\pi^H(\mathcal{D}) = \mathbb{E}_{s \sim \mathcal{D}, \, a \sim \pi(\cdot|s)} \left[\alpha \log \pi(a|s) - Q^H(s, a) \right], \tag{4}$$

which resembles the class of SVG algorithms (Heess et al., 2015; Byravan et al., 2020; Amos et al., 2021; Clavera et al., 2020). The difference from the original SVG is the addition of the entropy term. Note that, for $H = 0$ this definition reduces to the regular SAC actor loss (Equation 1). We will refer to the H-step value expansion for the actor update as *actor expansion* (AE).

Critic Expansion. Incorporating value expansion in the policy evaluation step results in TD-λ style (Sutton & Barto, 2018; Schulman et al., 2016) or Model-Based Value Expansion (MVE) methods (Wang et al., 2020; Buckman et al., 2018). The corresponding critic loss is defined as

$$\mathcal{J}_Q^H(\mathcal{D}) = \mathbb{E}_{(s,a,r,s')\sim\mathcal{D},\, a'\sim\pi(\cdot|s')} \left[\left(r + \gamma(Q^H(s', a') - \alpha \log \pi(a'|s')) - Q^\pi(s, a) \right)^2 \right]. \quad (5)$$

Similar to actor expansion, for $H = 0$ the critic update reduces to the SAC critic update (Equation 2). We will refer to the H-step value expansion for the critic update as *critic expansion* (CE).

Extension to Off-Policy Trajectories. We can naturally extend the action-value expansion in Equation 3 with the RETRACE formulation (Munos et al., 2016), which allows to use off-policy trajectories collected with a policy $\mu \neq \pi$ (e.g. stored in a replay buffer). The H-step RETRACE state-action value expansion (single sample) estimator is defined as

$$Q_{\text{retrace}}^H(s,a) = \mathcal{R}(s,a) + \left[\sum_{t=1}^{H-1} \gamma^t \left(c_t r_t + c_{t-1} V(s_t) - c_t Q(s_t, a_t) \right) \right] + \gamma^H c_{H-1} V(s_H), \quad (6)$$

with the importance sampling weight $c_t = \prod_{j=1}^t \lambda \min\left(1, \pi(a_j|s_j)/\mu(a_j|s_j)\right)$ and $c_0 := 1$. We set $\lambda = 1$ for the remainder of this paper. And by definition $Q_{\text{retrace}}^0(s,a) := Q^\pi(s,a)$. The RETRACE extension has the desirable property that $c_t = 1$ for on-policy trajectories (i.e. $\mu = \pi$), and in that case Q_{retrace}^H reduces to the H-step action-value target Q^H (Equation 3, see Appendix A.2 for a detailed derivation). Furthermore, for $H = 0$, it reduces to the SAC target. The second desirable property is that trajectories from the real environment or a dynamics model can be used. Hence, we use the RETRACE formulation to evaluate all combinations of CE and AE with on- and off-policy data and real and model-generated data. Since RETRACE encompasses all the variants we introduced, for readability, we will from now on overload notation and define $Q^H(s,a) := Q_{\text{retrace}}^H(s,a)$.

A natural combination is to merge actor and critic expansion into one algorithm. However, we decided to do our analysis on each method separately, to better understand their issues. Table A.1 provides an overview of related value expansion literature and displays further information about their usage of actor and critic expansion and on- and off-policy data.

3 EMPIRICAL STUDY

In this experimental section, we investigate the initial research question, **how much will more accurate dynamics models increase sample efficiency?** To answer it, we construct an experimental setup that replaces the learned dynamics model with an oracle model – the environment's simulator – which is the most accurate model that could be learned. In this scenario, no model error exists, which lets us examine the impact of the compounding model error — or rather the lack of it. In these experiments, we specifically exclude data augmentation methods; as for these methods, it is trivial to realize that they can arbitrarily benefit from the oracle dynamics, i.e. more accurate dynamics models. In the following, we conduct a series of empirical studies across the introduced value expansion algorithms on five standard continuous control benchmark tasks: InvertedPendulum, Cartpole SwingUp, Hopper, Walker2d, and HalfCheetah. These tasks range from simple to complex, with the latter three including contact forces, often resulting in discontinuous dynamics.

In the following subsections, we first present the premise of this paper — the diminishing returns of value expansion methods even with a perfect dynamics model (Section 3.1). Given the oracle model, we *rule out the existence of a compounding model error* and, therefore, possible impacts on the learning performance. Next, we turn to the generated H-step target values and analyse the impact of increasing horizons (Section 3.2). Then, we investigate the additional variance, introduced by the H-step rollouts (Section 3.3), and finally, in Section 3.4 we look into the critic and actor gradients. Throughout this section, we also use a learned dynamics model, implemented as a stochastic neural network ensemble, similar to PETS and MBPO. Implementation details are listed in Appendix A.3.

3.1 DIMINISHING RETURNS ON CONTINUOUS CONTROL TASKS

Figure 1a presents an extensive evaluation of the training performance for the referred value expansion methods based on SAC. Figure 1b shows results for DDPG, which serves as a baseline to ensure that the diminishing returns do not simply stem from training a stochastic policy in SAC. Adding

Figure 1: This plot shows the diminishing return of critic and actor expansion methods. For each, we present learning curves for multiple rollout horizons H based on SAC and DDPG. Critic expansion does not benefit noticeably from using horizons greater than five in most cases. There is also no clear trend that critic expansion methods would benefit from better models since the neural network model (row 2) performs mostly on par with the oracle model (row 1). Model-free RETRACE often is a strong contender, showing comparable performance. For actor expansion (rows 4 and 5), larger horizons can be detrimental, even with an oracle model. We plot the mean (solid line) and standard deviation (shaded area) of 9 random seeds of the average episode undiscounted return on the y-axis. The x-axis displays the number of interaction steps with the real environment. Note: some actor expansion runs for longer horizons terminate early due to exploding gradients (See section 3.4).

the DDPG experiments gives a more nuanced answer to the research question since in combination with the deterministic dynamics, there is no stochasticity in the target rollouts. All experiments are performed with the oracle dynamics model and a learned model for reference. We further provide results for RETRACE as a model-free H-step baseline that uses off-policy trajectories from a re-

Figure 2: Analysis of H-step targets for multiple checkpoints along the training process. The first row shows the undiscounted episodic return of SAC along training for one seed. The checkpoints along this single training run are used for the analyses in the following rows. The second row shows the Wasserstein distance between the sample-based target distribution predicted by the H-step estimator and the true target distribution represented by Monte Carlo samples. The third row displays the mean over particles of the sample-based target distributions, and the bottom row displays the variance. The expected value of targets computed with different horizons is roughly equal, while the variance increases with longer horizons.

play buffer. We used rollout horizons ranging from very short to long $H \in [0, 1, 3, 5, 10, 20, 30]$. $H = 0$ reduces to vanilla SAC. It would be interesting to investigate much larger horizons $H \gg 30$, closer to the true Monte Carlo targets. But, even with current GPU-based physics simulators, the computational time complexity is intractable (see Table A.3).

Within short horizons, less than 5 steps, we consistently observed that in most cases a single increase in the rollout horizon leads to increased performance. However, the rate of improvement decreases quickly with each additional expansion step (see Figure 1a), and close to all variants of SAC reach the peak performance for $H = 5$. We refer to this phenomenon as the *diminishing return* of value expansion methods. SAC with Actor Expansion (SAC-AE), either with an oracle (4th row) or a learned dynamics model (5th row), typically shows comparable or lower returns than SAC with Critic Expansion (SAC-CE) (1st and 2nd rows), higher variance and learning instability, especially with longer horizons. Agents with a neural network dynamics model show the same pattern but generally slightly reduced overall learning performance compared to the oracle model, which is expected. Nevertheless, with the oracle model experiments, we can say that the diminishing returns are not primarily caused by the compounding model errors, which might have been hypothesised by only observing the experiments with the learned neural network model. Moreover, since both SAC and DDPG show the same qualitative results, we conclude that the diminishing returns do not originate from the H-step rollouts' variance, as DDPG does not have any variance in those targets. We will, however, provide further evidence in Section 3.3.

3.2 EMPIRICAL ANALYSIS OF $Q^H(s, a)$ TARGET DISTRIBUTIONS

SAC estimates $Q^H(s, a)$ by rolling out a model with a stochastic policy. This can be seen as traversing a Markov reward process for H steps, for which it is well known that the target estimator's variance increases linearly with H, similar to the REINFORCE policy gradient (Williams, 1992), as pointed out in (Pflug, 1996; Carvalho et al., 2021). On the other hand, the targets will be more accurate (less bias), due to discounting the learned Q-function (Feinberg et al., 2018).

In our experiments, the oracle dynamics guarantee that there is no bias coming from a learned model. In this section, we analyse the state-action value function's expected value and variance for the different rollouts. We compare the true return distribution, approximated by particles of infinite horizon Monte Carlo returns, to the targets produced by different rollout horizons, using $D_{\mathrm{W}}^H = \mathbb{E}_{s,a\sim\mathcal{D}}\left[D_{\mathrm{W}}\left(\left\{Q_p^\infty(s,a)\right\}_{p=1\dots P}\middle|\left\{Q_p^H(s,a)\right\}_{p=1\dots P}\right)\right]$, where D_W is the Wasserstein dis-

Figure 3: Variance reduction through particles for SAC-CE and SAC-AE experiments. Each Q-function target is averaged over multiple particles to reduce the variance (30 particles for SAC-CE and 10 for SAC-AE). Compared to experiments from Figure 1a, we see that variance reduction gives the same qualitative training performance. Therefore, we conclude that increased variance in the targets is not the root cause of diminishing returns in value expansion.

tance (Villani, 2009), $P = 100$ particles per target (to model the distribution over targets) and $Q^\infty(s, a)$ is the true Monte Carlo return to compare against (in practice, we use a rollout horizon of 300 steps for computational reasons). Finally, we evaluate the expectation of this estimator over 10^4 samples $(s, a) \sim \mathcal{D}$ drawn from the replay buffer. We repeat this analysis for all horizons and 25 checkpoints along the vanilla SAC training. The 2nd row of Figure 2 shows how the Wasserstein distance decreases with increasing horizons, from which we conclude that, as expected, longer rollouts do indeed capture the true return distribution better. Notice how the curves from larger horizons (darker) are below the ones with shorter horizons (brighter), indicating a smaller distance. The 3rd and 4th row of Figure 2 depict the expectation of the target values particles over a replay buffer batch $\mathbb{E}_{s,a\sim\mathcal{D}}[\mathbb{E}[\{Q_p^H(s, a)\}_{p=1..P}]]$, and the corresponding variance $\mathbb{E}_{s,a\sim\mathcal{D}}[\mathrm{Var}[\{Q_p^H(s, a)\}_{p=1..P}]]$. The expected values of the target distribution Q^H are very similar for different horizons. This observation means that the approximated Q^0-function already captures the true return very well and, therefore, a model-based expansion only marginally improves the targets in expectation. The 4th row shows, however, that the variance over targets increases by orders of magnitude with the increasing horizon (darker lines have larger variance). This poses the question if the variance is the reason for the diminishing returns, which we will analyse in Section 3.3.

3.3 INCREASING VARIANCE AS THE ROOT CAUSE?

We discuss whether the increased variance in the Q-function targets over the course of longer rollouts is linked to the diminishing returns. For the DDPG experiments, which use a deterministic policy, the answer is straightforward. In combination with the deterministic dynamics of the oracle model, there exists no variance in the targets, i.e. longer horizons do not increase the variance. Combined with the fact that DDPG shows the same effect of diminishing returns, it tells us that the target variance introduced by a stochastic SAC policy is not the cause for the diminishing returns. A different way of confirming this is through active variance reduction of the SAC targets. To test this, we conduct an additional set of experiments. To compute the target $Q^H(s, a)$ during training, we averaged over multiple particles per target estimation (see Figure 3). For SAC-CE we used 30 particles and for SAC-AE 10 particles respectively. Comparing these experiments with variance reduction through particle with the prior results from Figure 1a, there is no qualitative difference in training performance. Based on these two investigations, we draw the conclusion, that the diminishing returns do not stem from the increasing target variance.

3.4 IMPACT ON THE GRADIENTS

We now analyse the impact of the different rollout horizons on the critic and actor gradients, for critic and actor expansion methods, respectively. It is important to note that the critic gradient $\nabla_Q \mathcal{J}_Q^H$ of the loss in Equation 5 is just simply differentiating through Q^π in the squared loss, since we assume $Q^H(s', a')$ is a fixed target as is common in RL algorithms (Ernst et al., 2005; Riedmiller, 2005;

(a) Critic parameter gradients' mean and standard deviation for H-step critic expansion SAC-CE.

(b) Actor parameter gradients' mean and standard deviation for H-step actor expansion SAC-AE.

Figure 4: These plots show the critic and actor gradients for the Cartpole and Halfcheetah environments and different rollout horizons. In Figure 4a we observe that the critic gradients show reasonable magnitudes and low variance. On the contrary, in Figure 4b, we see that for some environments the actor gradient explodes, which hinders learning.

Mnih et al., 2013). To calculate the actor gradient $\nabla_\pi \mathcal{J}_\pi^H$ we perform backpropagation through time through the whole trajectory resulting from expanding $Q^H(s, a)$ in Equation 4. We use the reparametrization trick (Kingma & Welling, 2014) to backpropagate through the stochastic nodes of the computational graph, as done in SAC-SVG, MAAC or SHAC (Xu et al., 2022).

Critic Expansion Gradients. Figure 4a shows the critic's gradient mean and standard deviation (averaged over a replay buffer batch), over all dimensions of the Q-function parameter space, along the training procedure for the critic expansion algorithm SAC-CE. Due to space constraints, we present only a subset of the environments and horizons in the main paper (see Figure A.2 for all experiments, as well as Figure A.4 for DDPG-CE gradients). For all environments and horizons, the gradient mean and standard deviation appear within resonable orders of magnitude. Although, as

expected, we observe a slight increase in the standard deviation with an increasing horizon for both the oracle and the learned neural network model. The mean is around zero (10^{-5}) and the standard deviation between 10^{-3} and 10^{-1}. Therefore, for both SAC-CE and DDPG-CE there is no clear signal in the gradient's mean or standard deviation that links to the diminishing returns in critic expansion methods. Looking at the first and second rows of Figures 1a (SAC-CE) and 1b (DDPG-CE), the returns of the oracle dynamics and the learned neural network model are comparable between different horizons. Also, increasing the horizon for target estimation in critic expansion does not seem to translate into much better returns, i.e. diminishing returns. For critic expansion, our experiments show that using off-policy data with RETRACE might be an option to consider without losing performance if the computational overhead of learning and rolling out a model does not justify it.

Actor Expansion Gradients. Figure 4b shows the actor's gradient mean and standard deviation (averaged over a replay buffer batch), over all dimensions of the policy parameter space, along the training process for the actor expansion algorithm SAC-AE (see Figure A.3 for all experiments, as well as Figure A.5 for DDPG-AE gradients). Contrary to critic expansion, in actor expansion, we backpropagate through the whole rollout trajectory to compute the gradient w.r.t. the policy parameters. Comparing the results from the fourth and fifth rows of Figure 1a, we observe that having a better dynamics model does not directly translate into faster learning or higher rewards since both the oracle and neural network model show the same effect - lower returns for larger horizons. We partially correlate these results with the actor gradients in Figure 4b for SAC-AE. Note, e.g., how in the Halfcheetah environment (last two rows of Figure 4b), the gradients' mean and standard deviation explodes for horizons larger or equal to 5 for the oracle and 20 for the learned models. This problem can also be seen in the Hopper environment using learned dynamics. In Figure 1a (row 5, col 3), the horizons 20 and 30 fail to solve the task. By inspecting the gradients standard deviation in Figure A.3 (row 6, last two columns), note the spikes in the standard deviation that are clipped at 10^2. This increase in variance can be correlated with the lower returns. A similar phenomenon can be seen in the DDPG-AE experiments as well, where the policy and oracle dynamics are deterministic. Therefore, increasing the horizon must be done with care even if a better model does not suffer from compounding model errors. Our observation is that when doing actor expansion, developing a very accurate differentiable model that predicts into the future might not be worth it since, due to gradient instability, it might only be possible to expand for a few steps; otherwise we might need methods to handle gradient variance (Parmas et al., 2018).

4 CONCLUSION & FUTURE WORK

In this paper, we answer the question of whether dynamics model errors are the main limitation for improving the sample efficiency of model-based RL. More specifically, we focus on value expansion methods, which unroll a model in the actor- or critic-update step. For these methods, we observe that in most cases, oracle dynamics are barely better than current learned dynamics models. Furthermore, we show that model-free value expansion through RETRACE, which simply uses off-policy rollouts from a replay buffer, is often only negligibly worse. With our findings in mind, we argue that the computational overhead of model learning for value expansion methods outweighs the benefits in the case of a limited computation budget. On the other hand, one central benefit of model-based RL methods over model-free is, that they allow for the generation of arbitrary amounts of additional data. And therefore, one could increase the number of gradient steps per real environment sample (often referred to as update-to-data ratio) at the expense of even further increasing the computational complexity. We leave studying the effectiveness of additional gradient steps for value expansion methods to future work. Most importantly, in this paper we present the diminishing returns of value expansion methods. Our experiments with the oracle dynamics model show that model errors are not the root cause of this phenomenon, contrary to common belief. We cannot pinpoint the root causes – neither the produced targets nor the produced gradients reveal clear signals. Our experiments show that for model-based RL we may rethink if we should put the effort into learning better models, since computing critic expansion targets with RETRACE matched the oracle dynamics, and updating policies with actor expansion methods can lead to gradient problems. Therefore, the search for the root cause remains an open research problem. From this observation, we conclude that the gains in sample efficiency with this class of algorithms, which can be gained by learning more accurate models, are limited. Our findings are strictly limited to infinite horizon, continuous state- and action space problems with deterministic dynamics. The possible extension to other problem settings is left to future work.

REFERENCES

Zaheer Abbas, Samuel Sokota, Erin Talvitie, and Martha White. Selective dyna-style planning under limited model capacity. In *International Conference on Machine Learning*, 2020.

Brandon Amos, Samuel Stanton, Denis Yarats, and Andrew Gordon Wilson. On the model-based stochastic value gradient for continuous reinforcement learning. In *Learning for Dynamics and Control*, 2021.

Richard Bellman. *Dynamic Programming*. Princeton University Press, 1 edition, 1957.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL `http://github.com/google/jax`.

Jacob Buckman, Danijar Hafner, George Tucker, Eugene Brevdo, and Honglak Lee. Sample-efficient reinforcement learning with stochastic ensemble value expansion. In *Advances in Neural Information Processing Systems*, 2018.

Arunkumar Byravan, Jost Tobias Springenberg, Abbas Abdolmaleki, Roland Hafner, Michael Neunert, Thomas Lampe, Noah Siegel, Nicolas Heess, and Martin Riedmiller. Imagined value gradients: Model-based policy optimization with tranferable latent dynamics models. In *Conference on Robot Learning*, 2020.

João Carvalho, Davide Tateo, Fabio Muratore, and Jan Peters. An empirical analysis of measure-valued derivatives for policy gradients. In *International Joint Conference on Neural Networks*, 2021.

K.E. Case and R.C. Fair. *Principles of Economics*. Prentice Hall, 1999.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems*, 2018.

Ignasi Clavera, Violet Fu, and Pieter Abbeel. Model-augmented actor-critic: Backpropagating through paths. In *International Conference on Learning Representations*, 2020.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. `http://pybullet.org`, 2016–2021.

Thomas Degris, Martha White, and Richard S. Sutton. Off-policy actor-critic. In *International Conference on Machine Learning*, 2012.

Marc Deisenroth and Carl E Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *International Conference on Machine Learning*, 2011.

Marc Peter Deisenroth, Gerhard Neumann, Jan Peters, et al. A survey on policy search for robotics. *Foundations and Trends in Robotics*, 2(1–2):1–141, 2013.

Damien Ernst, Pierre Geurts, and Louis Wehenkel. Tree-based batch mode reinforcement learning. *Journal of Machine Learning Research*, 6:503–556, 2005.

Vladimir Feinberg, Alvin Wan, Ion Stoica, Michael I. Jordan, Joseph E. Gonzalez, and Sergey Levine. Model-based value estimation for efficient model-free reinforcement learning. In *International Conference on Machine Learning*, 2018.

Roy Fox, Ari Pakman, and Naftali Tishby. Taming the Noise in Reinforcement Learning via Soft Updates. In *Conference on Uncertainty in Artificial Intelligence*, 2016.

C. Daniel Freeman, Erik Frey, Anton Raichuk, Sertan Girgin, Igor Mordatch, and Olivier Bachem. Brax - a differentiable physics engine for large scale rigid body simulation, 2021. URL `http://github.com/google/brax`.

Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, 2018.

Sam Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In *Advances in Neural Information Processing Systems*, 2019.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. In *International Conference on Machine Learning*, 2017.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, 2019.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

Nicolas Heess, Gregory Wayne, David Silver, Timothy Lillicrap, Tom Erez, and Yuval Tassa. Learning continuous control policies by stochastic value gradients. In *Advances in Neural Information Processing Systems*, 2015.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, 2019.

Michael Janner, Igor Mordatch, and Sergey Levine. Gamma-models: Generative temporal difference learning for infinite-horizon prediction. In *Advances in Neural Information Processing Systems*, 2020.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. In *International Conference on Learning Representations*, 2014.

Hang Lai, Jian Shen, Weinan Zhang, and Yong Yu. Bidirectional model-based policy optimization. In *International Conference on Machine Learning*, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

Michael Lutter, Kim Listmann, and Jan Peters. Deep lagrangian networks for end-to-end learning of energy-based control for under-actuated systems. In *International Conference on Intelligent Robots and Systems*, 2019a.

Michael Lutter, Christian Ritter, and Jan Peters. Deep lagrangian networks: Using physics as model prior for deep learning. In *International Conference on Learning Representations*, 2019b.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Andrew S Morgan, Daljeet Nandha, Georgia Chalvatzaki, Carlo D'Eramo, Aaron M Dollar, and Jan Peters. Model predictive actor-critic: Accelerating robot skill acquisition with deep reinforcement learning. In *International Conference on Robotics and Automation*, 2021.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc Bellemare. Safe and efficient off-policy reinforcement learning. In *Advances in Neural Information Processing Systems*, 2016.

Duy Nguyen-Tuong and Jan Peters. Model learning for robot control: a survey. *Cognitive Processing*, 12(4):319–340, 2011.

Paavo Parmas, Carl E Rasmussen, Jan Peters, and Kenji Doya. Pipps: Flexible model-based policy search robust to the curse of chaos. In *International Conference on Machine Learning*, 2018.

Jan Peters and Stefan Schaal. Natural actor-critic. *Neurocomputing*, 2008.

Georg Ch. Pflug. *Optimization of Stochastic Models*. Springer, 1996.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Carl E Rasmussen and Christopher Williams. *Gaussian processes for machine learning*. The MIT Press, 2006.

Martin A. Riedmiller. Neural fitted Q iteration - first experiences with a data efficient neural reinforcement learning method. In *European Conference on Machine Learning*, 2005.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International Conference on Machine Learning*, 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International Conference on Machine Learning*, 2014.

Richard S Sutton. Integrated architectures for learning, planning, and reacting based on approximating dynamic programming. *Machine Learning*, 1990.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, 2018.

Richard S. Sutton, David A. McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in Neural Information Processing Systems*, 1999.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *International Conference on Intelligent Robots and Systems*, 2012.

Cédric Villani. *Optimal transport: old and new*, volume 338. Springer, 2009.

Junjie Wang, Qichao Zhang, Dongbin Zhao, Mengchen Zhao, and Jianye Hao. Dynamic horizon value estimation for model-based reinforcement learning. *arXiv preprint arXiv:2009.09593*, 2020.

P.J. Werbos. Backpropagation through time: what it does and how to do it. *Proceedings of the IEEE*, 78(10):1550–1560, 1990. doi: 10.1109/5.58337.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 1992.

Chenjun Xiao, Yifan Wu, Chen Ma, Dale Schuurmans, and Martin Müller. Learning to combat compounding-error in model-based reinforcement learning. *arXiv preprint arXiv:1912.11206*, 2019.

Jie Xu, Viktor Makoviychuk, Yashraj Narang, Fabio Ramos, Wojciech Matusik, Animesh Garg, and Miles Macklin. Accelerated policy learning with parallel differentiable simulation. 2022.

Brian D. Ziebart, Andrew L. Maas, J. Andrew Bagnell, and Anind K. Dey. Maximum entropy inverse reinforcement learning. In *Conference on Artificial Intelligence*, 2008.

A APPENDIX

A.1 RELATED WORK

Table A.1: Overview of key related literature. We categorize model-based RL algorithms using value expansion in the actor and/or critic update, and further note which ones use on-policy trajectories resulting from a dynamics model and which use off-policy trajectories from a replay buffer.

Algorithm	Expansion		Policy	
	Actor	Critic	On	Off
SVG (Heess et al., 2015)	×			×
IVG (Byravan et al., 2020)	×		×	
SAC-SVG (Amos et al., 2021)	×		×	
MAAC (Clavera et al., 2020)	×		×	
MVE (Feinberg et al., 2018)		×	×	
STEVE (Buckman et al., 2018)		×	×	
RETRACE (Munos et al., 2016)		×		×
Dreamer (Hafner et al., 2020)	×	×	×	

A.2 FROM RETRACE TO ON-POLICY H-STEP VALUE EXPANSION

In this section, we show how RETRACE reduces to the H-step value expansion target (Equation 3) in the on-policy case, with $\lambda = 1$. First, we perform a simple rewrite from the original RETRACE formulation in Munos et al. (2016) such that it is more in line with the notation in this paper. Note, that in RETRACE the rollouts are generated with a policy μ. While the value function V^π corresponds to the current policy π.

$$Q_{\text{retrace}}^H(s_0, a_0) = Q(s_0, a_0) + \mathbb{E}_{a_t \sim \mu}\left[\sum_{t=0}^{H}\gamma^t c_t(\mathcal{R}(s_t, a_t) + \gamma V^\pi(s_{t+1}) - Q(s_t, a_t))\,\middle|\, s_0,\, a_0\right]$$

$$= Q(s_0, a_0) + \mathbb{E}_{a_t \sim \mu}\left[\left[\sum_{t=0}^{H}\gamma^t c_t(\mathcal{R}(s_t, a_t) - Q(s_t, a_t))\right] + \left[\sum_{t=0}^{H}\gamma^{t+1}c_t V^\pi(s_{t+1})\right]\,\middle|\, s_0,\, a_0\right]$$

$$= Q(s_0, a_0) + \mathbb{E}_{a_t \sim \mu}\left[\left[\sum_{t=0}^{H}\gamma^t c_t(\mathcal{R}(s_t, a_t) - Q(s_t, a_t))\right] + \left[\sum_{t=1}^{H+1}\gamma^t c_{t-1} V^\pi(s_t)\right]\,\middle|\, s_0,\, a_0\right]$$

$$= Q(s_0, a_0) + \mathbb{E}_{a_t \sim \mu}\left[\gamma^0 c_0(\mathcal{R}(s_0, a_0) - Q(s_0, a_0))\right]$$

$$+ \mathbb{E}_{a_t \sim \mu}\left[\left[\sum_{t=1}^{H}\gamma^t c_t(\mathcal{R}(s_t, a_t) - Q(s_t, a_t))\right] + \left[\sum_{t=1}^{H}\gamma^t c_{t-1} V^\pi(s_t)\right]\right]$$

$$+ \mathbb{E}_{a_t \sim \mu}\left[\gamma^{H+1}c_H V^\pi(s_{H+1})\right]$$

$$= Q(s_0, a_0) + \mathcal{R}(s_0, a_0) - Q(s_0, a_0)$$

$$+ \mathbb{E}_{a_t \sim \mu}\left[\sum_{t=1}^{H}\gamma^t c_t(\mathcal{R}(s_t, a_t) - Q(s_t, a_t)) + \gamma^t c_{t-1} V^\pi(s_t) + \gamma^{H+1}c_H V^\pi(s_{H+1})\right]$$

$$= \mathcal{R}(s_0, a_0) + \mathbb{E}_{a_t \sim \mu}\left[\sum_{t=1}^{H}\gamma^t(c_t \mathcal{R}(s_t, a_t) + c_{t-1} V^\pi(s_t) - c_t Q(s_t, a_t)) + \gamma^{H+1}c_H V^\pi(s_{H+1})\right]$$

Now, when $\lambda = 1$ the importance sampling weights all become $c_t = 1$ and we get

$$
= \mathcal{R}(s_0, a_0) + \mathbb{E}_{a_t \sim \mu} \left[\sum_{t=1}^{H} \gamma^t (\mathcal{R}(s_t, a_t) + V^\pi(s_t) - Q(s_t, a_t)) + \gamma^{H+1} V^\pi(s_{H+1}) \right]
$$

$$
= \mathcal{R}(s_0, a_0) + \mathbb{E}_{a_t \sim \mu} \left[\sum_{t=1}^{H} \gamma^t (\mathcal{R}(s_t, a_t) + \mathbb{E}_{\hat{a}_t \sim \pi} [Q(s_t, \hat{a}_t) - \alpha \log \pi(\hat{a}_t | s_t)] - Q(s_t, a_t)) \right]
$$
$$
+ \gamma^{H+1} V^\pi(s_{H+1})
$$

$$
= \mathcal{R}(s_0, a_0) + \sum_{t=1}^{H} \gamma^t (\mathbb{E}_{a_t \sim \mu} [\mathcal{R}(s_t, a_t)] + \mathbb{E}_{\hat{a}_t \sim \pi} [Q(s_t, \hat{a}_t)]
$$
$$
- \mathbb{E}_{\hat{a}_t \sim \pi} [\alpha \log \pi(\hat{a}_t | s_t)] - \mathbb{E}_{a_t \sim \mu} [Q(s_t, a_t)]) + \gamma^{H+1} V^\pi(s_{H+1})
$$

Since $\mu = \pi$, the expectations over Q are identical and it further reduces to

$$
= \mathcal{R}(s_0, a_0) + \sum_{t=1}^{H} \gamma^t (\mathbb{E}_{a_t \sim \pi} [\mathcal{R}(s_t, a_t)] - \mathbb{E}_{a_t \sim \pi} [\alpha \log \pi(a_t | s_t)]) + \gamma^{H+1} V^\pi(s_{H+1})
$$

$$
= \mathcal{R}(s_0, a_0) + \mathbb{E}_{a_t \sim \pi} \left[\sum_{t=1}^{H} \gamma^t (\mathcal{R}(s_t, a_t) - \alpha \log \pi(a_t | s_t)) + \gamma^{H+1} V(s_{H+1}) \right].
$$

Finally, we see, that in the on-policy case with $\lambda = 1$, the RETRACE target reduces to the regular SAC H-step value expansion target from Equation 3.

A.3 EXPERIMENT DETAILS

This section provides detailed information regarding policy and Q-function networks, as well as the learned dynamics model. Further, we include hyperparameters of the training procedure.

Policy Representation. The policy is represented by a neural network. It consists of two hidden layers with 256 neurons each and ReLU activations. The network outputs a mean vector and a per-dimension standard deviation vector which are then used to parameterize a diagonal multivariate Gaussian.

Q-function Representation. To represent the Q-function we use a double Q network. Each network has two hidden layers with 256 neurons each and ReLU activations and outputs a single scalar Q value. The minimum of the two Q networks is taken in critic and actor targets.

Learned Dynamics Model. The learned dynamics model is a reimplementation of the one introduced in Janner et al. (2019). It is an ensemble of 5 neural networks with 4 hidden layers with 256 neurons each and ReLU activations. To generate a prediction, one of the networks from the ensemble is sampled uniformly at random. The selected network then predicts mean and log variance over the change in state. This change is added to the current state to get the prediction for the next state.

Hyperparameters for Training. For a fair comparison, hyperparameters are shared across SAC and DDPG for the different expansion methods. In Table A.2 we report the hyperparameters across all experiments.

Computation Times. We report some of the computation times for the reader to get a better grasp of the computational complexity. Even though our GPU-only implementation using Brax (Freeman et al., 2021) is much more efficient than having a CPU-based simulator and transferring data back and forth to the GPU, the computational complexity of rolling out the physics simulator in the inner training loop, is still significant. This relates to complexity in computation time as well as VRAM requirements. Table A.3 shows the computation times on an NVIDIA A100 GPU.

Table A.2: Hyperparameters used for SAC and DDPG training. Note, that DDPG does not use the α learning rate due to its deterministic policy.

Parameter	Inverted Pendulum	Cartpole	Hopper	Walker2d	HalfCheetah
policy learning rate			$3e^{-4}$		
critic learning rate			$3e^{-4}$		
α learning rate			$5e^{-5}$		
target network τ			0.005		
RETRACE λ			1		
number parallel envs		1		128	
min replay size		512		2^{16}	
minibatch size			256		512
discount γ	0.95		0.99		0.95
action repeat	4		2		1

Table A.3: Computation times of the training with oracle dynamics. The computational overhead dominates for short horizons already.

H	0	1	3	5	10	20	30
InvertedPendulum							
SAC-CE	6m	8m	10m	12m	18m	28m	42m
SAC-AE	6m	14m	30m	42m	1h	2h	3h
RETRACE	6m	6m	7m	8m	10m	14m	18m
Hopper & Walker2d							
SAC-CE	20m	1h20m	2h30m	5h30m	10h30m	20h20m	30h20m
SAC-AE	20m	9h 40m	35h	55h	114h	167h	278h
RETRACE	20m	20m	22m	23m	27m	30m	40m
HalfCheetah							
SAC-CE	40m	3h15m	5h 40m	13h	25h	49h	77h
SAC-AE	40m	30h	62h	100h	168h	-	-
RETRACE	40m	41m	45m	50m	52m	1h	1h30m

A.4 ANALYSIS OF DISCOUNT FACTOR

Another hypothesis for the source of the diminishing return could be the discount factor γ. Figure A.1 shows a line of initial experiments with an ablation over different discount factors on the InvertedPendulum environment. The phenomenon of diminishing returns is obvious in all experiments no matter the discount factor. We also do not see a correlation between the diminishing return and the discount factor γ in these experiments. This leads us to believe that the discount factor is not the source of diminishing returns. Further experiments and a formal investigation are left to future work.

Figure A.1: Ablation of different discount factors γ on the InvertedPendulum. The discount factor does not appear to influence the diminishing returns and, therefore, the discount factor does not seem to be the source of diminishing returns.

A.5 GRADIENT EXPERIMENTS

Figures A.2, A.3, A.4 and A.5 show critic and actor gradients' mean and standard deviation for the different expansion methods of SAC and DDPG, respectively.

A.5.1 SAC CRITIC EXPANSION GRADIENTS

Figure A.2: These plots show the critic's gradients mean and standard deviation of SAC-CE for all environments and all rollout horizons. The values are in reasonable orders of magnitude and, therefore, the diminishing returns in SAC-CE cannot be explained via the critic gradients.

A.5.2   SAC ACTOR EXPANSION GRADIENTS

Figure A.3: These plots show the actor's gradients mean and standard deviation of SAC-AE for all environments and all rollout horizons. For readability, we clip large gradients to 10^2 (Halfcheetah environment). Even though the gradients' mean have reasonable values (close to zero), except for the Halfcheetah environment, the standard deviation shows spikes and abnormal values for increasing rollout horizons, e.g., note the spikes in the standard deviation in the Hopper (NN model) experiments for horizons 20 and 30 (row 6, last two columns), which go up to the clipped value of 10^2. These increase in variance can be correlated with the lower return in Figure 1a (row 5, col 3).

A.5.3 DDPG Critic Expansion Gradients

Figure A.4: These plots show the critic's gradients mean and standard deviation of DDPG-CE for all environments and all rollout horizons. The values are in reasonable orders of magnitude and, therefore, the diminishing returns in DDPG-CE cannot be explained via the critic gradients.

A.5.4 DDPG Actor Expansion Gradients

Figure A.5: These plots show the actor's gradients mean and standard deviation of DDPG-AE for all environments and all rollout horizons. For readability, we clip large gradients to 10^2 (Halfcheetah environment).