Decision-Theoretic Planning with Communication in Open Multiagent Systems

Abstract

In open multiagent systems, the set of agents operating in the environment changes over time and in ways that are nontrivial to predict. For example, if collaborative robots were tasked with fighting wildfires, they may run out of suppressants and be temporarily unavailable to assist their peers. Because an agent's optimal action depends on the actions of others, each agent must not only predict the actions of its peers, but, before that, reason whether they are even present to perform an action. Addressing openness thus requires agents to model each other's presence, which can be enhanced through agents communicating about their presence in the environment. At the same time, communicative acts can also incur costs (e.g., consuming limited bandwidth), and thus an agent must tradeoff the benefits of enhanced coordination with the costs of communication. We present a new principled, decision-theoretic method in the context provided by the recent communicative interactive POMDP framework for planning in open agent settings that balances this tradeoff. Simulations of multiagent wildfire suppression problems demonstrate how communication can improve planning in open agent environments, as well as how agents tradeoff the benefits and costs of communication under different scenarios.

1 INTRODUCTION

When operating in a multiagent system, an optimizing agent benefits from reasoning about how other agents will behave–i.e., peer modeling–while choosing actions that maximize its chances of accomplishing shared or self-interested goals. However, nuances in real-world environments often introduce numerous sources of uncertainty that make such peer modeling challenging. One of these is **agent openness** that occurs whenever individual agents join or leave the system (temporarily or permanently) over time. For example, cooperative robots tasked with suppressing wildfires alongside or in place of human firefighters would need to periodically leave the environment to recharge their limited suppressants that were spent during firefighting. Likewise, competitive autonomous ride-sharing cars can no longer compete for new passengers while transporting a full ride. Consequently, openness requires that an agent not only predict *what* actions their neighbors will take, but also *whether* they are even present to take actions.

However, the presence or absence of neighbors is commonly unobservable to the optimizing agent. Instead, the agent is required to *infer* the dynamics of the agent population by the changes in the environment state. For instance, in the wildfire example, if a fire's intensity rises when the agent predicted it would decrease, then it likely that neighbors were not present to help fight this fire. Chandrasekaran et al. [2016] introduced a decision-theoretic solution to this problem based on modeling the optimizing agent's decision problem as an IPOMDP-Lite [Hoang and Low, 2013]. Notably, in this solution, agents are not assumed to coordinate their behaviors or communicate information, making it applicable in a wide range of cooperative (e.g., wildfire suppression), competitive (e.g., autonomous ride-sharing), and self-interested scenarios, as well as ad hoc environments [Stone et al., 2010, Rahman et al., 2021, Mirsky et al., 2022].

On the other hand, if agents were instead capable of communicating with one another, then they could share information about their presence. That is, communicative acts, unlike regular actions that directly impact the physical state, can influence facets of the interacting agent's mental state such as its belief. Consequently, deciding to *purposefully* communicate requires modeling others' mental states and how communicative acts could change the receiving agent's belief, and subsequently its action. In this context, a recent framework called the communicative interactive POMDP (CI-POMDP) [Gmytrasiewicz and Adhikari,

2019, Gmytrasiewicz, 2020], building on the well-known I-POMDP [Gmytrasiewicz and Doshi, 2005], includes communicative acts, which leverages the framework's unique capability of modeling other agents' mental states, how they may change with time, and their modeling of others as a part of sequential decision making. To date, research studying the CI-POMDP model [Gmytrasiewicz, 2020] has focused on the underlying mathematical model and exploring how agents would decide to communicate on benchmark domains (e.g., the multiagent Tiger problem), but it has not been applied to solve real-world challenges such as communicating in open agent environments.

In this paper, we present a new method for decision-theoretic planning that extends Gmytrasiewicz [2020] by leveraging the CI-POMDP as a point of departure to enable agents to plan with *both physical and communicative actions in open multiagent systems*. In particular, we make the following key contributions:

1. We extend the CI-POMDP to include *modeling the presence of other agents*, suitable for open agent systems, building on prior work on decision-theoretic planning in open environments [Chandrasekaran et al., 2016, Eck et al., 2020]. Notably, in such environments, agents benefit from a different vocabulary of communicative messages than in the original CI-POMDP, which also changes how messages are incorporated into the receiving agents' belief update.

2. We produce the CI-POMCP-PF$_O$ algorithm for online planning with the CI-POMDP in open agent systems. We also extend ideas in Monte Carlo Tree Search (MCTS) from single agent planning in problems with large observation spaces [Sunberg and Kochenderfer, 2018, Garg et al., 2019, Thomas et al., 2020] to multiagent planning.

3. We conduct experiments using the benchmark wildfire suppression problem domain [Chandrasekaran et al., 2016] to investigate the impact on agent behaviors and task accomplishment from introducing communication, as well as how our extended CI-POMDP model balances the benefits and costs of planning communication. Our CI-POMCP-PF$_O$ algorithm led to statistically significantly higher rewards from increased task accomplishment through increased coordination of agent behaviors in several situations, and agents were able to reduce communication as costs increased without reducing the *benefits* of communicating.

2 BACKGROUND

The communicative interactive POMDP (CI-POMDP) builds on the well-known finitely-nested I-POMDP framework to include an additional action of sending a message, an additional observation of receiving messages, and a set of messages that are sent or received. Formally,

$$\mathsf{CI\text{-}POMDP}_{i,l} \triangleq \langle Ag, IS_{i,l}, A, \Omega_i, M, T_i, O_i, R_i, \gamma, b_{i,l}^0 \rangle$$

- Ag is a finite set of agents, consisting of a *subject agent i* using the CI-POMDP to decide how to act and communicate with other agents $j \in N(i)$ in its neighborhood $N(i) = Ag \setminus \{i\}$.

- $IS_{i,l}$ is the set of level l interactive states, $IS_{i,l} = S \times \times \bigtimes_{j \in N(i)} IS_{j,l-1}$ for $l > 0$. Here, S is the set of states of the decision-making problem, possibly factored into variables $\dot{S}_1 \times \dot{S}_2 \times \ldots \times \dot{S}_k$, such as the intensities of the k wildfires the agents need to suppress. Each agent $j \in N(i)$ is ascribed a model $\mathcal{M}_{j,l-1} = \langle b_{j,l-1}, \hat{\theta}_j \rangle$ where $b_{j,l-1}$ is the agent's belief over its level $l-1$ interactive state and $\hat{\theta}_j$ denotes the agent's frame. A frame represents the agent's capabilities and preferences. The level-0 interactive states $IS_{i,0} = S$.

- $A = A_i \times \bigtimes_{j \in N(i)} A_j$ is the set of possible joint actions of the agents; e.g., the individual fires that each agent chooses to fight. For notational convenience, $\mathbf{a_{-i}} \in \bigtimes_{j \in N(i)} A_j$ denotes the joint action by agents in $N(i)$.

- Ω_i is the set of observations of agent i.

- M is the set of messages sent and received by any agent. Let $m_{i \rightarrow j} \in M$ denote a message that is sent to an agent j and $m_{i \leftarrow j} \in M$ denote a message that is received from j. Let $\mathbf{m}_{i \leftarrow -i}$ denote the vector of messages received by i from to all other agents.

- $T_i(s, a_i, \mathbf{a_{-i}}, s') = P(s'|s, a_i, \mathbf{a_{-i}})$ gives probabilities of stochastic state transitions caused by actions of Ag.

- $O_i(s', a_i, \mathbf{a_{-i}}, o_i) = P(o_i|a_i, \mathbf{a_{-i}}, s')$ models the probabilities of stochastic observations revealed to subject agent i after joint action $(a_i, \mathbf{a_{-i}})$.

- $R_i(s, a_i, \mathbf{a}_{-i}, m_{i \rightarrow -i}) \in \mathbb{R}$ is the reward function of agent i dependent on the state, joint actions, and messages sent to the other agents. While there is cost of sending messages, there is no cost to receiving (and processing) messages.

- $\gamma \in (0, 1]$ and $b_{i,l}^0$ are the discount factor and initial belief state of subject agent i over its level-l interactive state space, respectively.

An agent with $l > 0$ in the CI-POMDP framework updates its belief on performing an action and/or sending a message at the previous time step followed by receiving an observation and/or vector of messages at the current time step. The belief update shown below yields the new belief $b_{i,l}^t = Pr(IS_{i,l}^t | b_{i,l}^{t-1}, a_i^{t-1}, \mathbf{m}_{i \rightarrow -i}^{t-1}, o_i^t, \mathbf{m}_{i \leftarrow -i}^t)$.

$$b_{i,l}^t(is^t) = \alpha \sum_{is^{t-1}} b_{i,l}(is^{t-1}) \prod_{j \in Ag/\{i\}} \left(\sum_{a_j^{t-1}} Pr(a_j^{t-1}, m_{j \rightarrow i}^{t-1} | \theta_{j,l-1}^{t-1}) \right)$$
$$\times T_i(s^{t-1}, a_i^{t-1}, \mathbf{a}_{-i}^{t-1}, s^t) \, O_i(s^t, a_i^{t-1}, \mathbf{a}_{-i}^{t-1}, o_i^t)$$

$$\times \prod_{j \in Ag/\{i\}} \left(\sum_{o_j^t} \tau_{\hat{\theta}_j}(b_{j,l-1}^{t-1}, a_j^{t-1}, m_{j \to i}^{t-1}, o_j^t, m_{j \leftarrow i}^t, b_{j,l-1}^t) \right.$$

$$\left. \times O_j(s^t, a_j^{t-1}, \mathbf{a}_{-j}^{t-1}, o_j^t) \right). \tag{1}$$

Here, $m_{j \to i}^{t-1}$ is the message sent by agent j to i at timestep $t-1$, which is same as the message received by agent i from j at timestep t, $m_{i \leftarrow j}^t$, since the framework assumes a perfect communication channel. Therefore, the term $Pr(a_j^{t-1}, m_{j \to i}^{t-1} | \theta_{j,l-1}^{t-1})$ makes those models of j that support sending this message more probable. $\tau_{\hat{\theta}_j}(b_{j,l-1}^{t-1}, a_j^{t-1}, m_{j \to i}^{t-1}, o_j^t, m_{j \leftarrow i}^t, b_{j,l-1}^t)$ is 1 if agent j's belief in is^{t-1} on performing its predicted action a_j^{t-1} and sending message $m_{j \to i}^{t-1}$ to i (which is same as the message received by agent i from j) followed by receiving possible observation o_j^{t-1} and i's sent message $m_{j \leftarrow i}^t$ to j updates to $b_{j,l-1}^t$ in is^t. A level-0 agent updates its belief using the POMDP belief update by first marginalizing the other agent from the transition and observation functions using a fixed probability distribution.

Analogously to I-POMDPs, subject agent i assigns a value to each level l belief, which is the expected cumulative, discounted rewards over a finite or infinite horizon H, $r_0 + \gamma r_1 + \gamma^2 r_2 + \ldots + \gamma^{H-1} r_{H-1}$, by maximizing over the Bellman equation for each belief and action-message pair:

$$Q_{i,l}(b_{i,l}^t, a_i^t, m_{i \to -i}^t) = \rho_i(b_{i,l}^t, a_i^t, m_{i \to -i}^t)$$

$$+ \gamma \sum_{o_i^{t+1}, \mathbf{m}_{i \leftarrow -i}^{t+1}} Pr(o_i^{t+1}, \mathbf{m}_{i \leftarrow -i}^{t+1} | b_{i,l}^t, a_i^t, m_{i \to -i}^t) V_{i,l}^{t+1}(b_{i,l}^{t+1})$$

$$\tag{2}$$

$$V_{i,l}^t(b_{i,l}^t) = \max_{a_i \in A_i, m_{i \to -i}^t} Q_i^t(b_{i,l}^t, a_i^t, m_{i \to -i}^t) \tag{3}$$

where

$$\rho_i(b_{i,l}^t, a_i^t, m_{i \to -i}^t) = \sum_{is^t \in IS_{i,l}^t} b_{i,l-1}^t(is^t) \sum_{\mathbf{a}_{-i} \in A_{-i}}$$

$$\times \prod_{j \in Ag} \sum_{m_{j \to -j}^t} Pr(a_j^t, m_{j \to -j}^t | \theta_{j,l-1}^t) R_i(s, a_i, \mathbf{a}_{-i}, m_{i \to -i}^t)$$

and $b_{i,l}^{t+1}$ is the updated belief on performing action a_i^t and sending message $m_{i \to -i}^t$ followed by receiving observation o_i^{t+1} and messages $\mathbf{m}_{i \leftarrow -i}^{t+1}$.

Policy $\pi_{i,l}$ is then the distribution of those action and message pairs that maximize the Q-value:

$$OPT(b_{i,l}^t) = \operatorname*{argmax}_{a_i \in A, m \in M} Q_{i,l}(b_{i,l}^t, a_i, m_{i \to -i}) \tag{4}$$

$$\pi_{i,l}(a_i, m_{i \to -i} | b_{i,l}^t) = \frac{1}{|OPT|} \quad \forall (a_i, m_{i \to -i}) \in OPT \tag{5}$$

Prior research [Gmytrasiewicz and Adhikari, 2019, Gmytrasiewicz, 2020] have proposed the CI-POMDP model and analyzed the expected agent behaviors in the two-agent instance of the multiagent Tiger problem [Gmytrasiewicz and Doshi, 2005]. To the best of our knowledge, no algorithm has yet been published that solves the CI-POMDP to acquire OPT and π.

3 PLANNING WITH COMMUNICATION IN OPEN AGENT SYSTEMS

In this paper, we limit our attention to systems where agents may leave the environment at any time and possibly reenter, but new agents do not enter the system (a common assumption in open agent systems research). Still, this brings unique conceptual and computational challenges.

In open systems, individual planning is complicated by the need of each agent to track which other agents are currently present in the system and to reason about the actions of present agents only. In wildfire suppression, each firefighter must know how many others are currently unavailable due to recharging their suppressant, so as to focus on the behaviors of those currently fighting the fires. Note that a firefighter j's absence is not the same as j choosing to do nothing, and thus would lead to a firefighter i updating its beliefs differently when modeling j.

Prior research studying decision-theoretic reasoning in open environments has kept track of this information in two ways. Either by maintaining coalitions of operating agents in the Open Dec-POMDP [Cohen et al., 2017], or by adding a presence state variable $present_j$ for each agent $j \in N(i)$ that records the neighbor's current presence in the system [Chandrasekaran et al., 2016]. Eck et al. [2020] proposed moving the $present_j$ state variables from the environment state s into the mental models $\mathcal{M}_{j,l-1}$ maintained by the subject agent in an IPOMDP-Lite model [1] [Hoang and Low, 2013] of the environment in order to gain efficiencies in the problem state space. We adopt this latter approach.

Unfortunately, these $present_j$ state variables are commonly unobservable to the subject agent. On the other hand, it may infer the neighboring agents' absences from the interaction through sensing a lack of expected change in the state variables. For example, if firefighting agent i senses that the intensity of a shared fire is not reducing despite fighting the fire, it likely infers that its neighbors are not assisting. If agent i believes that their suppressant levels were previously low, it may further infer that those agents are currently not participating in the interaction. However, this indirect inference is slow, unreliable, and often post hoc.

---

[1] The IPOMDP-Lite approximates an I-POMDP but models each neighbor as having full observability using a Nested-MDP model to gain computational efficiency, instead of modeling other agents as also solving a I-POMDP

3.1 COMMUNICATION

Use of a direct communication modality between agents may yield faster inference. To illustrate, a neighboring agent that sends the message that its suppressant level is very low is likely to be predicted to be absent from the interaction in the next time step. The planning agent will update its belief to give a higher probability mass to those models of the other agent that have the $present_j$ variable as false. These $present_j$ variables represent the significant information required to address the challenges of reasoning about neighbor behavior in open agent systems, and yet are unobservable directly by the subject agent. Therefore, allowing agents to directly communicate about their presence should improve the modeling performed by neighbors and offer a mechanism for coordinating behaviors in cooperative or self-interested environments. For instance, if all agents now ascribe the similar high probabilities about the presence or absence of the same agents, they are likely to choose actions that optimize that maximize rewards after reducing uncertainty in the critically important presence states.

Traditionally, agents in a CI-POMDP communicate messages that represent marginals over their beliefs about the environment state as a way of affecting the beliefs of their neighbors. For suitability in open agent systems, we propose instead that the set of messages M that are sent and received by agents relate to the agent exiting the interaction or reentering it. In our firefighting example, we may let M = {'*Have suppressant*', '*Nearly out of suppressant*', '*Out of suppressant*', '*No message*'}. All of these messages pertain to the suppressant level of the communicating agent, which determines whether the agent is able to currently participate in the interaction or not. Messages in the CI-POMDP framework reveal information on the sender's mental models as shown in the belief update (Eq. 1). Therefore, the example messages in M allow the receiver to update its belief about the sender being present or absent from the firefighting.

Henceforth, we denote a CI-POMDP that models the presence of agents and communicates about presence states as the *open agent CI-POMDP*, enabling decision-theoretic reasoning about not only how agents should act, but *when and how they should communicate*, in open agent systems.

3.2 NESTED MODELING COMPLICATES COMMUNICATION

Although CI-POMDPs offer a way to integrate communicative acts into decision making, the nested modeling of others as practiced in the framework inhibits communication. To understand this, recall that $IS_{i,0} = S$. In other words, level-0 agents in I-POMDPs do not ascribe intentional models to others in their environment. Instead, they may ascribe a flat probability distribution to the predicted actions of others which facilitates marginalizing others' actions, or

ignoring others' presence. Subsequently, messages received from others may not influence a level-0 agent's beliefs. An unintended consequence of this is that the level-1 agent may decide to not communicate with its neighbor because it reasons that any message it sends may not influence the neighbors's level-0 belief. Furthermore, the level-1 agent does not expect to receive any messages either because it thinks that others are not modeling others intentionally, so level-0 agents would determine there is no benefit to sending messages (especially in costly communication channels).

Gmytrasiewicz [2020] also notes this challenge; to address it, they propose treating level-0 agents as both "literal listeners" and "literal speakers", respectively. Level-0 agents act as literal listeners by incorporating any received information, even though they do not attribute the sender as having been intentional (and thus honest or dishonest) in their communication. For this process, Gmytrasiewicz proposes a separate update process than the Bayesian update defined previously in Eq. 1 that mixes the existing belief with new information. Likewise, level-0 agents act as literal speakers by sending messages to "no one in particular", optimistically assuming that if another agent were instead intentional, they could take advantage of the communicated message. For this process, Gmytrasiewicz proposes a message generation function: with a probability α, the agent communicates the honest marginal over its belief, and it does not communicate with probability $1 - \alpha$.

In our open agent CI-POMDP, where agents communicate information about their presence states that are not modeled by the level-0 agent's belief, we instead propose *indirectly* incorporating received messages about the sender's presence in the level-0 belief update in order to incentivize the level-1 agent to communicate. Since level-0 agents do not ascribe intentionality to their neighbors (e.g., treating neighbors as behaving randomly), the transition and observation functions of level-0 agents treat all other actors as behaving randomly, which is likely to cause a mismatch from the true transitions and observations that will occur. If a level-1 agent were to assume that it can influence the transition and observation functions considered by a level-0 literal listener through the messages it sends, then the level-1 agent might determine a measurable benefit in terms of future cooperation when sending messages while planning.

In particular, we propose that a level-1 agent consider the following while modeling the decision-making process of its level-0 neighbors. Let $f_j : m_{i \leftarrow j} \rightarrow a_j$, which maps a message received from agent j to its action $a_j \in A_j$, replace the fixed distribution ascribed by the level-0 agent i to sender j's actions. For more than one other agent, denote the vector of maps, one for each other agent, as $\mathbf{f_{-i}}$. Then, level-0 i's updated belief about the environment state is:

$$b_{i,0}^t(s^t) = \alpha \, O_i(s^t, a_i^{t-1}, \mathbf{f_{-i}}(\mathbf{m_{i\leftarrow -i}^t}), o_i^t)$$
$$\times \sum_{s^{t-1}} b_{i,0}^{t-1}(s^{t-1}) \, T_i(s^{t-1}, a_i^{t-1}, \mathbf{f_{-i}}(\mathbf{m_{i\leftarrow -i}^t}), s^t) \quad (6)$$

This update is analogous to a POMDP belief update with the modification that it allows messages received from others in the neighborhood to impact the updated belief. Consequently, given that the level-1 agent is aware that an agent modeled at level-0 updates its belief using Eq. 6, the level-1 agent may conclude that there is value in communicating with others because messages sent by it and received by others may indeed impact their beliefs over the state, which in turn may potentially affect their action choice.

Further, we propose that a level-1 agent consider an adapted version of the literal sender of Gmytrasiewicz [2020]. They stochastically generate a message that is honest about their actual presence with a probability $1-\alpha$, while the remainder of the probability mass is uniformly spread across sending an incorrect presence state or no message. We denote this generator with the function $g_i^\alpha : presence_i \to m_{i\to -i}$.

With both of these changes, level-1 agents are now incentivized to both send and receive messages since they believe messages will be received and sent by lower level level-0 agents. By induction, all higher levels of agents will also be incentivized to communicate, enabling decision making about communication in open agent systems.

4 MCTS FOR CI-POMDPS

We present an online planning algorithm for our open agent CI-POMDP model called CI-POMCP-PF$_O$ that uses Monte Carlo Tree Search (MCTS) to calculate the subject agent's set of optimal actions $OPT(b_{i,l}^t)$ (Eq. 4) for its current belief $b_{i,l}^t$ and the resulting policy $\pi(b_{i,l}^t)$. This algorithm is the first planning algorithm for the CI-POMDP, and it offers several important and non-trivial improvements over the state-of-the-art I-POMCP$_O$ algorithm [Eck et al., 2020] for decision-theoretic planning in open environments:

1. CI-POMCP-PF$_O$ reasons about benefits and costs of communication to determine when and how the subject agent should communicate with its neighbors, as well as incorporates information from received messages into its beliefs about other agent's mental models.
2. CI-POMCP-PF$_O$ produces solutions to a full CI-POMDP model where other agents are modeled as also solving a CI-POMDP of the world, rather than producing solutions to a IPOMDP-Lite model where neighbors are modeled as solving the simpler Nested-MDP representation of the environment.
3. CI-POMCP-PF$_O$ addresses the large branching factor due to reasoning about receiving messages from all neigh-

bors by projecting weighted PFs during each trajectory MCTS, rather than a single particle at a time. This adapts recent advancements in single agent planning [Garg et al., 2019, Thomas et al., 2020, Sunberg and Kochenderfer, 2018] for the first time in multiagent contexts.
4. CI-POMCP-PF$_O$ can run fully online, requiring no offline pre-calculations of neighbor policies, although it can also exploit offline neighbor policies if available before the agent operates in the environment.

4.1 MONTE CARLO TREE SEARCH

The POMCP algorithm [Silver and Veness, 2010] is a canonical approach for MCTS in partially observable environments. It operates by constructing an AND-OR tree of alternating belief (OR) and action (AND) nodes (e.g., Fig. 4) by following the general process in Alg. 2 in the supplementary material. The root node signified by ε represents the agent's current belief about the environment, stored as an unweighted particle filter. Operating for a number of trajectories, the algorithm iteratively samples a particle (i.e., state) from the root belief, then projects the particle down the tree. During each trajectory, an action is chosen to balance the exploration-exploitation tradeoff using the UCB-1 heuristic $\underset{a\in A}{\arg\max}\, Q(h,a) + \sqrt{\frac{\log n(h)}{n(ha)}}$, where h represents a history of actions and observations since the root node (alternatively a path from the root of the tree to a unique belief node), $Q(h,a)$ is the Q-value of action a for the belief reached by history h, $n(h)$ and $n(ha)$ are the number of trajectories that have reached the belief node at history h and simulated action a, respectively. Next, the algorithm simulates taking the chosen action in the particle's current to produce a next state, reward, and observation. The algorithm then appends the action and observation to the history h and recurses on the next belief at the new history hao with the next state s' as the trajectory's particle. If a leaf of the tree is reached, then the algorithm instead performs a rollout by randomly choosing and performing actions for the remaining horizon, and the leaf is expanded by adding its children action nodes and their children belief nodes (one for each observation). Finally, the algorithm unrolls the recursion by returning the sum of rewards earned from the current belief node to the leaf reached, and $Q(h,a)$ is updated using a rolling average formula and $n(h)$ and $n(ha)$ are incremented.

Once all trajectories have been exhausted, $OPT(b_{i,l}^t)$ is the child actions of the root node with maximal Q value. The agent physically acts by choosing an action from OPT (e.g., uniformly at random), then follows the branch in the tree for the received observation to identify its next belief.

Finally, the I-POMCP$_O$ algorithm [Eck et al., 2020] extends POMCP to multiagent settings, where the subject agent solves an IPOMDP-Lite model, and addresses agent openness by maintaining beliefs about the presence of other

agents within their mental models (Sec. 3.1). I-POMCP$_O$ is the first online planning algorithm for the I-POMDP family of models and demonstrated great scalability to many-agent systems. The primary differences between the I-POMCP$_O$ and single agent POMCP are that (1) particles contain not only an environment state, but also the subject agent's own presence state $present_i$ and a mental model for each neighbor[2] (that include a $present_j$ state to model openness), and (2) each time the algorithm simulates the agents' action to produce a next state, reward, and observation, it predicts (using pre-computed level $l-1$ offline policies) and simulates the actions of the neighbors based on its mental models.

4.2 CI-POMCP-PF

Our novel algorithm CI-POMCP-PF$_O$ (Alg. 1) extends I-POMCP$_O$ to reason about not only physical actions, but also communicative actions that can enhance the agents' modeling of each other's presence in the open agent system. However, planning for the open agent CI-POMDP, rather than an IPOMDP-Lite that cannot reason about communication, requires overcoming several critical challenges.

First, the structure of the tree must be adapted to decide how to communicate, as well as incorporating received messages into next beliefs, illustrated in Fig. 1. The fanout of action nodes under each belief node increases linearly with the number of messages $|M|$ since now the agent must decide not only what action to perform in each situation, but also which message it will send (or not send a message at all). Moreover, the fanout of belief nodes under each action node increases *exponentially* in the number of neighbors $|N(i)|$ since now the subject agent i must consider not only what observation it receives from the environment, but also what *combination* of messages it receives from all neighbors.

This high fanout is challenging not only due to its impact on the size of the tree, but it has severe implications from only projecting a single particle per trajectory [Sunberg and Kochenderfer, 2018]: almost all belief nodes near the bottom of the tree would suffer from particle deprivation because they would be reached only once with a single particle, hence their Q estimates would be poor approximations close to those estimated by loose bound QMDP [Littman et al., 1995]. Furthermore, high fanout implies the leaves are shallower for a fixed number of trajectories than planning without communication, so the poorly approximated leaves will be near the root, and consequently Q estimates will be poor not only at the leaves of the tree, but all throughout.

Algorithm 1 CI-POMCP-PF

1: **procedure** CREATECOMMPLAN($b_{i,l}, \mathbf{m_{i\leftarrow-i}}$)
2:    **for** $traj \in 1, 2, \dots, \tau$ **do**
3:      UpdateTree($b_{i,l}, \mathbf{m_{i\leftarrow-i}}, 0, \varepsilon$)
4:    **return** $\underset{a\in A_i, m\in M}{\mathrm{argmax}}\ Q(\varepsilon, a, m)$

5: **procedure** UPDATETREE($b_{i,l}, \mathbf{m_{i\leftarrow-i}}, t, h$)
6:    **if** $t \geq H$ **then**
7:      return 0
8:    **if** h is a leaf **then**
9:      Expand(h, i, l)
10:      return Rollout($b_{i,l}, t$)
11:    $a, m_{i\rightarrow-i} \leftarrow$ ChooseActionComm(h)
12:    $b'_{i,l}, \mathbf{m'_{i\leftarrow-i}}, r, o \leftarrow$ SimulateComm($b_{i,l}, \mathbf{m_{i\leftarrow-i}}, a, m_{i\rightarrow-i}$)
13:    $R \leftarrow r + \gamma * $ UpdateTree($b'_{i,l}, \mathbf{m'_{i\leftarrow-i}}, t+1, hao m'_{\mathbf{i\leftarrow-i}}$)
14:    StoreResults($h, b_{i,l}, a, R$)
15:    return R

16: **procedure** SIMULATECOMM($b_{i,l}, \mathbf{m_{i\leftarrow-i}}, a, m_{i\rightarrow-i}$)
17:    $R \leftarrow 0$
18:    $w(o_i) \leftarrow 0, \quad \mu(o_i) \leftarrow \emptyset, \quad b^{o_i}_{i,l} \leftarrow \emptyset \ \forall o_i \in \Omega_i$
19:    **for** $(w, s, present_i, \bigtimes_{j\in N(i)} \langle b_{j,l-1}, present_j, \theta_j \rangle) \in b_{i,l}$ **do**
20:      **if** $l > 0$ **then**
21:        $a_j, m_{j\rightarrow-j} \leftarrow$ CreateCommPlan($b_{j,l-1}, \mathbf{m_{j\leftarrow-j}}$) $\forall j$
22:      **else**
23:        $a_j \leftarrow f_i(m_{i\leftarrow j}), \quad m_{j\rightarrow-j} \leftarrow g^\alpha_j(present_j) \ \forall j \in N(i)$
24:      $s', r, o_i, \mathbf{present'} \leftarrow$ Simulate($s, \mathbf{present}, a, \mathbf{a_{-i}}$)
25:      $w' \leftarrow w \cdot T_i(s, a, \mathbf{a_{-i}}, s') \cdot O(s', a, \mathbf{a_{-i}}, o_i)$
26:      $w(o_i) \overset{+}{\leftarrow} w', \quad \mu(o_i) \overset{\cup}{\leftarrow} (w', \mathbf{m'_{i\leftarrow-i}}), \quad R \overset{+}{\leftarrow} w \cdot r$
27:      $b^{o_i}_{i,l} \overset{\cup}{\leftarrow} (w', s', present'_i, \bigtimes_{j\in N(i)} \langle b'_{j,l-1}, present'_j, \theta_j \rangle)$
28:    $o_i \sim w(o_i), \quad \mathbf{m'_{i\leftarrow i}} \sim \mu(o_i)$
29:    return $b^{o_i}_{i,l}, \mathbf{m'_{i\leftarrow i}}, R, o_i$

30: **procedure** EXPAND(h, i, l)
31:    $B_{i,l}(h) \leftarrow \emptyset, \quad n_{i,l}(h) \leftarrow 0$
32:    $n_{i,l}(ha) \leftarrow 0, \quad Q_{i,l}(h, a, m) \ \forall a \in A_i, m \in M$

33: **procedure** CHOOSEACTIONCOMM(h)
34:    return $\underset{a\in A, m\in M}{\mathrm{argmax}}\ Q_{i,l}(h, a, m) + \sqrt{\frac{\log n_{i,l}(h)}{n_{i,l}(ham)}}$

35: **procedure** STORERESULTS($h, b_{i,l}, a, m, R$)
36:    $B_{i,l}(h) \leftarrow \mathrm{norm}(B_{i,l}(h) \cup b_{i,l})$
37:    $n_{i,l}(h) \overset{+}{\leftarrow} 1, \quad n_{i,l}(ham) \overset{+}{\leftarrow} 1$
38:    $Q_{i,l}(h, a, m) \overset{+}{\leftarrow} \frac{R - Q_{i,l}(h,a)}{n_{i,l}(ham)}$

To address this first challenge, we adopt a recently popular technique from single agent MCTS algorithms PFT-DPW [Sunberg and Kochenderfer, 2018], DESPOT-α [Garg et al., 2019], and ρ-POMCP [Thomas et al., 2020] that address improvements to MCTS in environments with large observation spaces (analogous to our challenge since received messages are fundamentally observations about unobservable $present_j$ states contained in mental models). To avoid poor Q estimates due to particle deprivation, these algorithms instead employ a *weighted* particle filter and project the entire filter down the tree during each trajectory so that Q estimates for each action node are calculated with more

Figure 1: Example AND-OR tree created by CI-POMCP-PF with 3 neighbors, 2 actions, 4 messages, and 2 observations. The fanout is 8 action + message nodes and 128 belief nodes.

than single particle and better approximate result. A second benefit to this approach is that the agent's belief update after taking a physical action is more informed since the corresponding weighted particle filter in the second level of the tree will not suffer from particle deprivation, either.

The second challenge is that pre-computing offline policies for neighbors might be impossible when (1) the mental models of neighbors are unknown until the agent operates in the environment (e.g., when different organizations contribute robots in response to a rapidly emerging wildfire), or (2) when the problem size is too large to afford planning for all possible scenarios (including the resulting beliefs from all possible combinations of received messages from all neighbors, which potentially exponentially expands the number of reachable beliefs from the initial belief). To address this challenge, our CI-POMCP-PF$_O$ algorithm can operate fully online, predicting the behaviors of neighbors by *embedding* MCTS at one lower level each time a predicted action is needed for each neighbor; line 21 can also be replaced by a lookup from pre-computed policies if available.

5 EXPERIMENTS

We evaluate Alg. 1 on the wildfire suppression problem, a complex benchmark for planning in open agent systems [Chandrasekaran et al., 2016, Eck et al., 2020].

Setups Agents are tasked with putting out fires of different sizes in the absence of prior coordination. Putting out small, medium, large, and huge fires provide agents shared rewards of 20, 50, 125, and 300, respectively, whereas a fire burning out earns a shared penalty. The spread of fires is modeled on the dynamics of real wildfires Boychuk et al. [2009], Ure et al. [2015]; fires can take on five levels between non-existant to burned out. Agents have limited amounts of suppressant with *present* levels starting at full, followed by half full, then empty that transition stochastically when the agents take actions to fight adjacent fires or recharge while taking a NOOP action when empty (suppressant level

reduces 25% and recharges to full with 50% probability). Details about agent and fire types are presented in Fig. 2.

We consider three different setups varying in the need for co-ordinated behavior, illustrated in Fig. 2. Setup 1 represents a situation where two agents each have unique small fires they can put out individually, as well as a shared fire that requires both agents to act simultaneously to reduce. Thus, agents can act independently, but they earn more rewards by acting together, where communication might help them coordinate. Setup 2 represents a more complicated scenario necessitating more coordination where no fires can be reduced independently; instead, two fires require two agents to work together and a third fire requires all three agents to act simultaneously. Finally, Setup 3 further increases the size of fires and adds mixed types to determine how agents communicate within and across frames.

Figure 2: Our setups involve a varying number, sizes, and positions of fires, as well as a varying number of agents and their types. Fires require different units of suppressant to reduce. Ground firefighters apply 1 unit, helicopters 2 units.

Evaluations Within each setup, we evaluate the benefits of reasoning about communication by comparing our CI-POMCP-PF$_O$ algorithm with an ablated I-POMCP-PF$_O$ that keeps all extensions from state-of-the-art I-POMCP$_O$ [Eck et al., 2020], except that agents do not send or receive messages. We do not compare against other communicating algorithms as no prior solutions exist to the CI-POMDP. To further evaluate how well our model and algorithm reason about balancing the trade offs between the benefits and costs of communication, we vary communication costs for each sent message in $\{0, -0.05, -0.1, -0.2, -0.5, -1\}$. Agent performance is measured by the average rewards, and we also evaluate how many messages were sent, also when and how messages were sent, as communication costs vary. All results are averaged over 50 runs, each 15 time steps.

Hyperparameters The f function assumes that agents with full suppressant will be around long enough to fight the largest fire in the environment, whereas agents with half suppressant will need to leave soon and favor smaller fires; empty suppressant maps to NOOP and no message maps uniformly to all actions. The g function assumes level-0 agents are honest with $\alpha = 0.95$ probability. Agents plan with $\tau = 1000$ trajectories at level $l = 1$, horizon $H = 10$, 50 particles in the particle filter, and $c = 50, 75, 100$ for

Setups 1, 2, 3. Neighbor level-0 policies were pre-computed.

Results   From Fig. 3, we first observe that in both Setups 1 and 3, agents planning with CI-POMCP-PF$_O$ created policies that earned *statistically significantly* greater rewards than I-POMCP-PF$_O$. In Setup 1, I-POMCP-PF$_O$ agents focused first on the small fires they could handle individually, then only worked on the shared fire when the small fires were put out, whereas communicating CI-POMCP-PF$_O$ agents focused first on the shared fire that required coordination, which was enabled through information shared in messages, to earn higher rewards and better task accomplishment. We observed similar behavior in Setup 3, where non-communicating agents focused on the smaller fires first, while CI-POMCP-PF$_O$-enabled coordination to put out the huge fire worth the most rewards. Overall, our model and algorithm reasoned successfully about *when* to communicate.

Figure 3: Average rewards and messages sent per agent.

On the other hand, we observe for Setup 2 that I-POMCP-PF$_O$ statistically significantly outperformed our CI-POMCP-PF$_O$ agents. Once again, I-POMCP-PF$_O$ agents without communication focused their initial attention on the smaller fires; the fire reduced depended on the initial choice of the middle agent (who equally decided between both small fires). With communication, the CI-POMCP-PF$_O$ encouraged more agents to attempt to put out the large fire more frequently initially. However, since the large fire requires all three agents to be present and work together, they failed whenever one of them ran out of suppressant before the fire was put out, or someone chose to switch actions (possibly due to randomness during MCTS planning). As a result, they were delayed in shifting to the smaller fires like the I-POMCP-PF$_O$ agents, which burned out first and thus led to a penalty rather than a reward. Overall, communication led to more coordinated behavior, but

the challenge of needing all agents to put out the shared fire in this particular setup was too difficult to frequently overcome in the open environment.

Across all setups, we also observe that as communication costs increased, CI-POMCP-PF$_O$ agents communicated less frequently, yet their rewards earned did not significantly decrease. This implies that in response to communication costs of varying levels, CI-POMCP-PF$_O$ enables agents to choose *when* it is best to communicate (especially in Setups 1 and 3) to balance the benefits of communicating when it is most effective vs. the costs of communication. In other words, the agents were able to become more efficient with how they utilize communication to improve coordination and rewards received when communication cost was greater.

Finally, we investigate the messages sent by agents (c.f., Appendix C in the supplementary material for figures). In Setups 1 and 3, all agents frequently communicated a *full suppressant* message as they began fighting fires (approximately 45%-80% of messages; higher costs increased *no message* frequency), which corresponds both to the starting suppressant levels of agents (honest messages) and the message that maps to fighting the shared fire (the agent's true action) in the f function. As the agents continued operating in the environment, their messages correspond more closely to the actions chosen (c.f., Appendix B in the supplementary material) than their true suppressant level. This implies that level-1 agents determined that they could indeed influence the behaviors of level-0 literal listening neighbors and sent messages they believed would be interpreted in such a way that would lead to coordinated behaviors. In Setup 2, agents also sent messages frequently corresponding to their actions, but the challenge of at least one agent running out of suppressant before putting out the shared fire still limited their task success.

6   CONCLUDING REMARKS

Real-world domains often exhibit agent openness, where agents may leave and then return. We proposed an extension to the CI-POMDP where agents decide when and how to communicate about their presence to provide information about their availability, effectively adding observations of the commonly unobservable presence of neighbors. We developed the CI-POMCP-PF$_O$ algorithm, a MCTS-based online planning algorithm that extends the state-of-the-art I-POMCP$_O$ to enable reasoning about communication in open and typed multiagent systems. Simulations in three challenging benchmark wildfire suppression problems demonstrated that our algorithm not only enables agents to reason about *how* to communicate in order to produce more coordination and task accomplishment, but also *when* to communicate to balance the benefits and costs of communicating. We plan to further explore how our model and algorithm can be adapted to many-agent environments.

References

D. Boychuk, W.J. Braun, R.J. Kulperger, Z.L. Krougly, and D.A. Stanford. A stochastic forest fire growth model. *Environmental and Ecological Statistics*, 16(2):133–151, 2009.

Muthukumaran Chandrasekaran, Adam Eck, Prashant Doshi, and Leenkiat Soh. Individual planning in open and typed agent systems. In *Proceedings of the Thirty-Second Conference on Uncertainty in Artificial Intelligence*, UAI'16, pages 82–91, Arlington, Virginia, United States, 2016. AUAI Press. ISBN 978-0-9966431-1-5. URL http://dl.acm.org/citation.cfm?id=3020948.3020958.

Jonathan Cohen, Jilles-Steeve Dibangoye, and Abdel-Illah Mouaddib. Open decentralized pomdps. In *2017 IEEE 29th International Conference on Tools with Artificial Intelligence (ICTAI)*, pages 977–984, 2017.

Adam Eck, Maulik Shah, Prashant Doshi, and Leenkiat Soh. Scalable decision-theoretic planning in open and typed multiagent systems. In *Proceedings of the Thirty-Fourth AAAI Conference on Artificial Intelligence*, AAAI'20, 2020.

Neha Priyadarshini Garg, David Hsu, and Wee Sun Lee. Despot-alpha: Online pomdp planning with large state and observation spaces. In *Proceedings of Robotics: Science and Systems*, FreiburgimBreisgau, Germany, June 2019. doi: 10.15607/RSS.2019.XV.006.

Piotr Gmytrasiewicz. How to do things with words: A bayesian approach. *Journal of Artificial Intelligence Research*, 68:753–776, 2020.

Piotr Gmytrasiewicz and Sarit Adhikari. Optimal sequential planning for communicative actions: A bayesian approach. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, AAMAS '19, page 1985–1987, Richland, SC, 2019. International Foundation for Autonomous Agents and Multiagent Systems. ISBN 9781450363099.

Piotr J. Gmytrasiewicz and Prashant Doshi. A framework for sequential planning in multiagent settings. *Journal of Artificial Intelligence Research*, 24:49–79, 2005.

Trong Nghia Hoang and Kian Hsiang Low. Interactive POMDP lite: Towards practical planning to predict and exploit intentions for interacting with self-interested agents. In *23rd International Joint Conference on AI (IJCAI)*, 2013.

Michael L Littman, Anthony R Cassandra, and Leslie Pack Kaelbling. Learning policies for partially observable environments: Scaling up. In *Proceedings of the Twelfth International Conference on Machine Learning*, ICML'95, pages 362–370, 1995.

Reuth Mirsky, Ignacio Carlucho, Arrasy Rahman, Elliot Fosong, William Macke, Mohan Sridharan, Peter Stone, and Stefano V. Albrecht. A survey of ad hoc teamwork: Definitions, methods, and open problems, 2022.

Muhammad A Rahman, Niklas Hopner, Filippos Christianos, and Stefano V Albrecht. Towards open ad hoc teamwork using graph-based policy learning. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 8776–8786. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/rahman21a.html.

David Silver and Joel Veness. Monte-carlo planning in large pomdps. In *23rd International Conference on Neural Information Processing Systems (NIPS)*, NIPS'10, pages 2164–2172, 2010.

E. Sonu, Y. Chen, and P. Doshi. Individual planning in agent populations: Exploiting anonymity and frame-action hypergraphs. In *International Conference on Automated Planning and Scheduling (ICAPS)*, pages 202–210, 2015.

Ekhlas Sonu, Yingke Chen, and Prashant Doshi. Decision-theoretic planning under anonymity in agent populations. *J. Artif. Int. Res.*, 59(1):725–770, May 2017. ISSN 1076-9757. URL http://dl.acm.org/citation.cfm?id=3176788.3176805.

Peter Stone, Gal A. Kaminka, Sarit Kraus, and Jeffrey S. Rosenschein. Ad hoc autonomous agent teams: Collaboration without pre-coordination. In *Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence*, AAAI'10, pages 1504–1509, 2010.

Zachary Sunberg and Mykel Kochenderfer. Online algorithms for pomdps with continuous state, action, and observation spaces, 2018.

Vincent Thomas, Geremy Hutin, and Olivier Buffet. Monte information-oriented planning. In *Proceedings of the Twenty-fourth European Conference on Artificial Intelligence*, ECAI'20, 2020.

N.K. Ure, S. Omidshafiei, B.T. Lopez, A.-A. Agha-Mohammadi, J.P. How, and J. Vian. Online heterogeneous multiagent learning under limited communication with applications to forest fire management. In *Intelligent Robotics and Systems (IROS)*, pages 5181–5188, 2015.

Supplementary Material

A MONTE CARLO TREE SEARCH

Here, we provide the pseudocode for single agent POMCP Silver and Veness [2010] in Alg 2, as well as an example AND-OR tree in Fig. 4 for reference in Section 4.1.

Algorithm 2 POMCP [Silver and Veness, 2010]

1: **procedure** CREATEPLAN(b)
2:   **for** $traj \in 1, 2, \ldots, \tau$ **do**
3:     $s \leftarrow$ SampleParticle (b)
4:     UpdateTree$(s, 0, \varepsilon)$
5:   return $\underset{a \in A}{\mathrm{argmax}}\ Q(\varepsilon, a)$
6: **procedure** UPDATETREE(s, t, h)
7:   **if** $t \geq H$ **then**
8:     return 0
9:   **if** h is a leaf **then**
10:     Expand(h)
11:     return Rollout(s, t)
12:   $a^* \leftarrow$ ChooseAction(h)
13:   $s', r, o \leftarrow$ SimulateComm(s, a)
14:   $R \leftarrow r + \gamma *$ UpdateTree$(s', t + 1, hao)$
15:   StoreResults(h, s, a, R)
16:   return R
17: **procedure** EXPAND(h)
18:   $B(h) \leftarrow \emptyset, \quad n(h) \leftarrow 0$
19:   $n(ha) \leftarrow 0, \ Q(h, a) \leftarrow 0 \ \forall a \in A$
20: **procedure** CHOOSEACTION(h)
21:   return $\underset{a \in A}{\mathrm{argmax}}\ Q(h, a) + \sqrt{\frac{\log n(h)}{n(ha)}}$
22: **procedure** STORERESULTS(h, s, a, R)
23:   $B(h) \leftarrow B(h) \cup \{s\}$
24:   $n(h) \leftarrow n(h) + 1, , \quad n(ha) \leftarrow n(ha) + 1$
25:   $Q(h, a) \leftarrow Q(h, a) + \frac{R - Q(h,a)}{n(ha)}$

B AGENT ACTIONS PERFORMED IN EXPERIMENTS

In Figs. 5-13, we document the actions chosen by each agent in all three setups for both the I-POMCP-PF$_O$ and

Figure 4: The first two levels of an example AND-OR tree created by MCTS for a POMDP with 2 actions, 2 observations, and 4 states

CI-POMCP-PF$_O$ algorithms (using communication costs of 0 and -1 to show both ends of the spectrum). Note: for all setups, action 0 = the left most fire, action 1 = the middle fire, action 2 = the right fire, and action 3 = NOOP.

C MESSAGES SENT IN EXPERIMENTS

In Figs. 14-19, we document the messages sent by each agent in all three setups for CI-POMCP-PF$_O$ algorithms (using communication costs of 0 and -1 to show both ends of the spectrum).

Figure 5: Agent actions using I-POMCP-PF in Setup 1

Figure 6: Agent actions using CI-POMCP-PF (cost = 0) in Setup 1

Figure 7: Agent actions using CI-POMCP-PF (cost = -1) in Setup 1

Figure 8: Agent actions using I-POMCP-PF in Setup 2

Figure 9: Agent actions using CI-POMCP-PF (cost = 0) in Setup 2

Figure 10: Agent actions using CI-POMCP-PF (cost = -1) in Setup 2

Figure 11: Agent actions using I-POMCP-PF in Setup 3

Figure 12: Agent actions using CI-POMCP-PF (cost = 0) in Setup 3

Figure 13: Agent actions using CI-POMCP-PF (cost = -1) in Setup 3

Figure 14: Messages sent using CI-POMCP-PF (cost = 0) in Setup 1

Figure 15: Messages sent using CI-POMCP-PF (cost = -1) in Setup 1

Figure 16: Messages sent using CI-POMCP-PF (cost = 0) in Setup 2

Figure 17: Messages sent using CI-POMCP-PF (cost = -1) in Setup 2

Figure 18: Messages sent using CI-POMCP-PF (cost = 0) in Setup 3

Figure 19: Messages sent using CI-POMCP-PF (cost = -1) in Setup 3