A Deeper look at the Layerwise Sparsity of Magnitude-based Pruning

Abstract

Recent discoveries on neural network pruning reveal that, with a carefully chosen *layerwise sparsity*, a simple magnitude-based pruning achieves state-of-the-art tradeoff between sparsity and performance. However, without a clear consensus on "how to choose," the layerwise sparsities are mostly selected algorithm-by-algorithm, often resorting to handcrafted heuristics or an extensive hyperparameter search. To fill this gap, we propose a novel importance score for global pruning, coined layer-adaptive magnitude-based pruning (LAMP) score; the score is a rescaled version of weight magnitude that incorporates the model-level ℓ_2 distortion incurred by pruning, and does not require any hyperparameter tuning or heavy computation. Under diverse datasets and models, LAMP consistently outperforms popular existing schemes for layerwise sparsity selection. Furthermore, we observe that LAMP continues to outperform baselines even in weight-rewinding setups, while the connectivity-oriented layerwise sparsity (the strongest baseline overall) performs worse than a simple global magnitude-based pruning in this case.

1 Introduction

Neural network pruning is an art of removing "unimportant weights" from a model, with an intention to meet practical constraints (Han et al., 2015), mitigate overfitting (Hanson & Pratt, 1988), enhance interpretability (Mozer & Smolensky, 1988), or deepen our understanding on neural network training (Frankle & Carbin, 2019). Yet, the *importance of weight* is still a vaguely defined notion, and thus a wide range of pruning algorithms based on various importance scores has been proposed. One popular approach is to estimate the loss increment from removing the target weight to use as an importance score, e.g., Hessian-based approximations (LeCun et al., 1989; Hassibi & Stork, 1993; Dong et al., 2017), coreset-based estimates (Baykal et al., 2019; Mussay et al., 2020), convex optimization (Aghasi et al., 2017), and operator distortion (Park et al., 2020). Other approaches include on-the-fly[1] regularization (Louizos et al., 2018; Xiao et al., 2019), Bayesian methods (Molchanov et al., 2017; Louizos et al., 2017; Dai et al., 2018), and reinforcement learning (Lin et al., 2017).

Recent discoveries (Gale et al., 2019; Evci et al., 2020) demonstrate that, given an appropriate choice of *layerwise sparsity*, simply pruning on the basis of weight magnitude yields a surprisingly powerful unstructured pruning scheme. For instance, Gale et al. (2019) evaluates the performance of magnitude-based pruning (MP; Han et al. (2015); Zhu & Gupta (2018)) with an extensive hyperparameter tuning, and shows that MP achieves comparable or better performance than state-of-the-art pruning algorithms that use more complicated importance scores. To arrive at such a performance level, the authors introduce the following handcrafted heuristic: Leave the first convolutional layer fully dense, and prune up to only 80% of weights from the last fully-connected layer; the heuristic is motivated by the sparsity pattern from other state-of-the-art algorithms (Molchanov et al., 2017) and additional experimental/architectural observations.

Unfortunately, there is an apparent lack of consensus on "how to choose the layerwise sparsity" for the magnitude-based pruning. Instead, the layerwise sparsity is selected mostly on an algorithm-by-algorithm basis. The iterative pruning scheme of Han et al. (2015) uses *global MP* criteria, where the layerwise sparsity is automatically determined by using a single global threshold on weight magnitude. Lin et al. (2020) propose a magnitude-based pruning algorithm using a feedback signal,

---

[1] i.e., simultaneously training and pruning

$$
\begin{bmatrix} u_1 \\ u_2 \\ u_3 \\ \cdots \end{bmatrix}
\begin{bmatrix} v_1 \\ v_2 \\ v_3 \\ \cdots \end{bmatrix}
\longrightarrow
\begin{bmatrix} \frac{u_1^2}{u_1^2} \\ \frac{u_2^2}{u_1^2 + u_2^2} \\ \frac{u_3^2}{u_1^2 + u_2^2 + u_3^2} \\ \cdots \end{bmatrix}
\begin{bmatrix} \frac{v_1^2}{v_1^2} \\ \frac{v_2^2}{v_1^2 + v_2^2} \\ \frac{v_3^2}{v_1^2 + v_2^2 + v_3^2} \\ \cdots \end{bmatrix}
\longrightarrow
\begin{bmatrix} \frac{u_1^2}{u_1^2} & \frac{v_1^2}{v_1^2} \\ \frac{u_2^2}{u_1^2 + u_2^2} & \varnothing \\ \varnothing & \varnothing \\ \cdots & \cdots \end{bmatrix}
$$

(sorted) Weight Magnitudes   LAMP score   Global Pooling and Pruning

Figure 1: The LAMP score is a squared weight magnitude, normalized by the sum of all "surviving weights" in the layer. Global pruning by LAMP is equivalent to the layerwise magnitude-based pruning with an automatically chosen layerwise sparsity.

using a heuristic rule of keeping the last fully connected layer dense. A recent work by Evci et al. (2020) proposes a magnitude-based dynamic sparse training method, adopting layerwise sparsity inspired from the network science approach toward neural network pruning (Mocanu et al., 2018).

Contributions. In search of a "go-to" layerwise sparsity for MP, we take a *model-level distortion minimization* perspective towards MP. We build on the observation of Dong et al. (2017); Park et al. (2020) that each neural network layer can be viewed as an operator, and MP is a choice that incurs minimum ℓ_2 distortion to the operator output (given a worst-case input signal). We bring the perspective further to examine the "model-level" distortion incurred by pruning a layer; preceding layers scale the input signal to the target layer, and succeeding layers scale the output distortion.

Based on the distortion minimization framework, we propose a novel importance score for global pruning, coined LAMP (Layer-Adaptive Magnitude-based Pruning). The LAMP score is a rescaled weight magnitude, approximating the model-level distortion from pruning. Importantly, the LAMP score is designed to approximate the distortion on the *model being pruned*, i.e., all connections with a smaller LAMP score than the target weight is already pruned. Global pruning[2] with the LAMP score is equivalent to the MP with an automatically determined layerwise sparsity. At the same time, pruning with LAMP keeps the benefits of MP intact; the LAMP score is efficiently computable, hyperparameter-free, and does not rely on any model-specific knowledge.

We validate the effectiveness of LAMP under a diverse experimental setup, encompassing various convolutional neural network architectures (VGG-16, ResNet-18/34, DenseNet-121, EfficientNet-B0) and various image datasets (CIFAR-10/100, SVHN, Restricted ImageNet). In all considered setups, LAMP consistently outperforms the baseline layerwise sparsity selection schemes. We also perform additional ablation studies with one-shot pruning and weight-rewinding setup to confirm that LAMP performs reliably well under a wider range of scenarios.

We believe that our paper can be a strong guideline when other researchers pursue the related tasks in the future.

Organization. In Section 2, we briefly describe existing methods to choose the layerwise sparsity for magnitude-based pruning. In Section 3, we formally introduce LAMP and describe how the ℓ_2 distortion minimization perspective motivates the LAMP score. In Section 4, we empirically validate the effectiveness and versatility of LAMP. In Section 5, we take a closer look at the layerwise sparsity discovered by LAMP and compare with baseline methods and previously proposed handcrafted heuristics. In Section 6, we summarize our findings and discuss future directions. Appendices include the experimental details (Appendix A), complexity analysis (Appendix B), derivation of the LAMP score (Appendix C), additional experiments on Transformer (Appendix D), and detailed experimental results with standard deviations (Appendix E).

2 RELATED WORK

This section gives a (necessarily non-exhaustive) survey of various layerwise sparsity selection schemes used for magnitude-based pruning algorithms. Magnitude-based pruning of neural networks

---

[2]i.e., using a global threshold for LAMP score

dates back to the early works of Janowsky (1989); LeCun et al. (1989), and has been actively studied again under the context of model compression since the work of Han et al. (2015). In Han et al. (2015), the authors propose an iterative pruning scheme based on *global MP*, where each layer is pruned non-uniformly with a shared global threshold on weight magnitude. Zhu & Gupta (2018) propose a uniform pruning algorithm with a carefully tuned gradual pruning schedule combined with weight re-growths. Gale et al. (2019) refine the algorithm by adding a heuristic constraint of keeping the first convolutional layer fully dense and keeping at least 20% of the weights surviving in the last fully-connected layer.

MP has also been studied in the context of "pruning at initialization." Frankle & Carbin (2019) combine MP with weight rewinding to discover efficiently trainable subnetworks; the authors employ uniform layerwise sparsity, but use different rates for convolutional layers and fully-connected layers (with an added heuristic on the last fully-connected layer). Morcos et al. (2019) consider transferring the "winning ticket" initializations, and observe that global MP tend to work better with weight rewinding. Evci et al. (2020) proposes a training scheme for sparsely initialized neural networks, where the layerwise sparsity is given by the Erdős-Rényi kernel method; the method generalizes the scheme initially proposed by Mocanu et al. (2018) to convolutional neural networks.

We note that there is a line of results on the *trainable layerwise sparsity*; we refer the interested readers to the recent work of Kusupati et al. (2020) for a concise survey. However, we do not make direct comparisons to these methods, as our primary purpose is to deliver an easy-to-use layerwise sparsity selection scheme without requiring the modification of training objective, or an extensive hyperparameter tuning.

We also note that we focus on the *unstructured sparsity*. While such unstrutured pruning techniques have been considered less practical (compared to structured pruning), several recent breakthroughs provide promising methods to bridge this gap; see Gale et al. (2020); Elsen et al. (2020).

3 LAYER-ADAPTIVE MAGNITUDE-BASED PRUNING (LAMP)

We now formally introduce the Layer-Adaptive Magnitude-Based Pruning (LAMP) score. Consider a depth-d feedforward neural network with weight tensors $W_1, \ldots, W_d$ associated to each fully-connected/convolutional layer. For each layer, we assume (without loss of generality) that the weights are sorted in an ascending order according to the given index map, i.e., $|W_i[u]| \leq |W_i[v]|$ holds whenever $u < v$. The LAMP score is then defined as

$$\mathsf{score}_i(u) := \frac{W_i^2[u]}{\sum_{v \geq u} W_i^2[v]}. \tag{1}$$

Informally, the LAMP score (Eq. 1) measures the relative importance of a connection among all *surviving connections* belonging to the same layer. We note that, as a consequence, two connections with identical weight magnitudes have different LAMP scores, depending on the index map.

Once the LAMP score is computed, we globally prune the connections with smallest LAMP scores until the desired global sparsity constraint is met; the procedure is equivalent to performing MP with an automatically selected layerwise sparsity. To see this, it suffices to check that

$$W_i^2[u] > W_i^2[v] \Rightarrow \mathsf{score}_i(u) > \mathsf{score}_i(v) \tag{2}$$

holds for any layer $i \in \{1, \ldots, d\}$. From the definition of the LAMP score (Eq. 1), it is easy to see that the logical relation (2) holds. Indeed, for the weight with larger magnitude, the denominator of Eq. 1 is smaller, while the numerator is larger.

We also note that the LAMP score is easy-to-use. Similar to the vanilla MP, the LAMP score does not have any hyperparameter to be tuned, and is easily implementable via elementary tensor operations. Furthermore, computing the LAMP score imposes only a minimal computational overhead; the sorting of squared weight magnitudes required to compute the denominator in Eq. 1 is already a part of typical vanilla MP algorithms. For more discussions, see Appendix B.

3.1 DESIGN PRINCIPLE: MINIMIZING OUTPUT ℓ_2 DISTORTION

To motivate LAMP, we begin by viewing the layerwise MP as a minimization of pruning-incurred ℓ_2 distortion in layer output, given the worst-case (unit) input signal. Then, we proceed to consider

the model-level distortion, motivating the LAMP score (Eq. 1). For a formal discussion, consider a depth-d feedforward neural network, whose output given an input x is

$$f(x; W_{1:d}) = W_d \sigma \big(W_{d-1} \sigma \big(\cdots W_2 \sigma \big(W_1 x \big) \cdots \big) \big), \tag{3}$$

where σ denotes the ReLU activation and W_i denotes the linear transformation corresponding to i-th layer. For a fully-connected layer, W_i is its weight matrix. For a two-dimensional convolutional layer, W_i is a doubly block circulant matrix built with the kernel tensor (Sedghi et al., 2019). We focus on fully-connected layers for a simple presentation, but the extension to convolutional layers is straightforward, as the magnitude ranking for a doubly block circulant matrix is identical to the magnitude ranking of the convolutional kernel.

MP: layerwise distortion minimization. We first focus on a single fully-connected layer. Let ξ_i be the input to the i-th layer and $\widetilde{W}_i$ be a pruned version of W_i. We aim to minimize the output distortion from pruning, as measured by the ℓ_2 distance $\|W_i \xi_i - \widetilde{W}_i \xi_i\|_2$. Minimizing ℓ_2 distortion for the worst-case input signal is equivalent to minimizing the spectral norm distortion

$$\min_{\widetilde{W}_i} \sup_{\|\xi_i\|_2 \leq 1} \|W_i \xi_i - \widetilde{W}_i \xi_i\|_2 = \min_{\widetilde{W}_i} \|W_i - \widetilde{W}_i\|, \tag{4}$$

where the search space for $\widetilde{W}_i$ is determined by some given sparsity constraint. The optimization (4) can be relaxed (via Cauchy-Schwarz inequality) to a Frobenius distortion minimization

$$\min_{M_i : \|M_i\|_0 \leq \kappa_i} \|W_i - M_i \odot W_i\| \leq \min_{M_i : \|M_i\|_0 \leq \kappa} \|W_i - M_i \odot W_i\|_F, \tag{5}$$

where M_i is a binary matrix, i.e. having only 0s and 1s as its entries, $\|\cdot\|_0$ denotes the entrywise ℓ_0 norm, and κ denotes the given sparsity constraint. We now observe that the (layerwise) MP gives an optimal solution for the optimization (5). Indeed, the squared Frobenius distortion is simply a sum of pruned squared weight magnitudes, and the optimal decision is to keep κ_i weights with the largest weight magnitudes.

LAMP: greedy minimization of model distortion. Now we step further to consider the ℓ_2 distortion from pruning depth-d neural network. Namely, we want to minimize

$$\min_{\widetilde{W}_{1:d}} \sup_{\|x\|_2 \leq 1} \|f(x; W_{1:d}) - f(x; \widetilde{W}_{1:d}), \|_2, \tag{6}$$

where the search space of $\widetilde{W}_{1:d}$ is characterized by the given global sparsity constraint. Due to the non-linearities introduced by activation functions, unfortunately, it is difficult to solve Eq. 6 exactly. Instead, we consider the following greedy procedure: At each step, (1) we compute a *damage score* (not identical to the LAMP score, will be explained shortly) that approximates the distortion incurred by pruning the target weight. (2) Then, we remove a *single connection* with the smallest score. (3) Finally, we go back to step (1) and re-compute the scores based on the *pruned model*.

To approximate the distortion incurred by pruning a weight in i-th layer, we use a popular relaxation from the generalization theory literature (see, e.g., Neyshabur et al. (2015)). Namely, we use the fact that the ReLU activation is 1-Lipschitz and has zero-in-zero-out property[3] to arrive at

$$\sup_{\|x\|_2 \leq 1} \|f(x; W_{1:d}) - f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d})\|_2 \leq \frac{\|W_i - \widetilde{W}_i\|_F}{\|W_i\|_F} \cdot \left(\prod_{j=1}^{d} \|W_j\|_F \right). \tag{7}$$

A (straightforward) proof of Ineq. 7 is given in Appendix C. Inspired by this relaxation, we use the right-hand side as the *damage score*, which should be re-computed every time after pruning each connection. Luckily, the product term $\prod_{j=1}^{d} \|W_j\|_F$ does not affect the pruning decision at each pruning step, and what we need to re-compute at each time step is the denominator $\|W_i\|_F$. Even more luckily, this quantity can be pre-computed at a single step by replacing $\|W_i\|_F$ with a cumulative sum $\sum_{v \geq u} W_i^2[v]$ for each element u in W_i. By the replacement, we arrive at the LAMP score (Eq. 1), which does not require a re-computation after pruning every single connection.

4   EXPERIMENTS & ANALYSES

To empirically validate the effectiveness of the proposed method, we compare LAMP with following layerwise sparsity selection schemes for magnitude-based pruning:

---

[3]i.e. $\sigma(0) = 0$.

Figure 2: Sparsity-accuracy tradeoff curves of VGG-16, ResNet-18, DenseNet-121, and EfficientNet-B0. All models are iteratively pruned and retrained with CIFAR-10 dataset.

- **Global.** A global threshold on the weight magnitudes is imposed on every layers to meet the global sparsity constraint, and the layerwise sparsity is automatically determined according to this threshold; see, e.g., Han et al. (2015); Morcos et al. (2019).

- **Uniform.** Every layer is pruned to have identical layerwise sparsity levels, which is in turn equal to the global sparsity constraint; see, e.g., Zhu & Gupta (2018).

- **Uniform+.** Same as Uniform, but we impose two additional constraints: (1) we keep the first convolutional layer unpruned, and (2) retain at least 20% of connections alive in the last fully-connected layer; this heuristic rule is proposed by Gale et al. (2019).

- **Erdős-Rényi kernel.** An extension of Erdős-Rényi method (originally given by Mocanu et al. (2018)) accounting for convolutional layers, as proposed by Evci et al. (2020). The numbers of nonzero parameters of sparse convolutional layers are scaled proportional to $1 - \frac{n^{l-1}+n^l+w^l+h^l}{n^{l-1}\cdot n^l \cdot w^l \cdot h^l}$, where n^l denotes the number of neurons at layer l, and w^l, h^l denotes the width and height of the lth layer convolutional kernel.

As a default setup, we perform *five independent trials* for each baseline method, where in each trial we use iterative pruning-and-retraining (Han et al., 2015): we prune 20% of the surviving weights at each iteration. For the Restricted-ImageNet experiment, we provide the result from a single trial. For a clear presentation, we only report the average on the figures appearing in the main text. Standard deviations for five-seed results in Section 4.1 will be given in Appendix E. In Appendix D, we also present experimental results for language modeling tasks on Transformers (Vaswani et al., 2017).

Summary of observations. From the experimental results (Figs. 2 to 4), we observe that LAMP consistently outperforms all other baselines, in terms of the sparsity-accuracy tradeoff. The performance gap between LAMP and baseline methods seems be more pronounced with modern network architectures, e.g., EfficientNet-B0. We also observe that LAMP performs well under weight rewinding setup, while the strongest baseline (Erdős-Rényi kernel) seems to be sensitive to such rewinding.

(a) SVHN (b) CIFAR-100 (c) Restricted ImageNet (1 seed)

Figure 3: Sparsity-accuracy tradeoff curves of pruned models trained for SVHN and CIFAR-100 (on VGG-16) and Restricted ImageNet (on ResNet-34).

4.1 MAIN RESULTS

Our main experimental results are on image classification models. We explore a diverse set of model architectures and datasets, with a base setup of VGG-16 (Simonyan & Zisserman, 2015) trained on CIFAR-10 (Krizhevsky & Hinton, 2009) dataset. In particular, our experiments cover the following models and datasets.

Models. We consider four network architectures for image classification experiments: (1) VGG-16 (Simonyan & Zisserman, 2015) adapted for CIFAR-10 to have batch normalization layers and one fully-connected layer (as used in Liu et al. (2019); Frankle & Carbin (2019); (2) ResNet-18/34 (He et al., 2016); (3) DenseNet-121 (Huang et al., 2017); (4) EfficientNet-B0 (Tan & Le, 2019). For all four models, we prune the weight tensors for fully-connected and convolutional units. Biases and batch normalization layers are kept unpruned.

Datasets. We consider the following datasets; CIFAR-10/100 (Krizhevsky & Hinton, 2009), SVHN (Netzer et al., 2011), and Restricted ImageNet (Tsipras et al., 2019). All datasets except for Restricted ImageNet are used for training VGG-16; Restricted ImageNet is used for training ResNet-34.

Other details. Detailed experimental setup is given in Appendix A.

In Fig. 2, we provide sparsity-accuracy tradeoff curves for four different model architectures trained on CIFAR-10 dataset. The first observation is that LAMP achieves the best tradeoff; in all four models, LAMP consistently outperforms baseline methods. We also observe that Erdős-Rényi kernel method also outperforms other baselines in VGG-16, ResNet-18, and EfficientNet-B0, but fails to do so on DenseNet-121. Furthermore, the gap between LAMP and the Erdős-Rényi kernel method seems to widen as the model architecture gets more complicated; the gap between two methods is notable especially in EfficientNet-B0, where mobile inverted bottleneck convolutional layers replace traditional convolutional modules. In particular, LAMP achieves 88.1% test accuracy when only 1.44% of all weights survive, while Erdős-Rényi kernel achieves 77.8%. Lastly, we observe that the heuristic of Gale et al. (2019) seems to provide an improvement over the Uniform MP.

In Fig. 3, we present the tradeoff curves for three additional datasets: SVHN, CIFAR-100, and Restricted ImageNet. Similar to Fig. 2, we observe that LAMP outperforms all other baselines and Erdős-Rényi kernel remains to be the most competitive baseline.

4.2 ABLATIONS: ONE-SHOT PRUNING, WEIGHT REWINDING, AND SNIP

Modern magnitude-based pruning algorithms are often used in combination with customized pruning schedules (e.g., Zhu & Gupta (2018)) or weight rewinding (e.g., Frankle & Carbin (2019); Renda et al. (2020)). As a sanity check that LAMP perform reliably well along with such techniques, we conduct following additional experiments.

- **One-shot pruning.** As an extreme case of pruning schedule, we test the scheme where we only run a single training-pruning-retraining cycle, instead of iterating multiple cycles. We test the one-shot pruning on VGG-16 trained with CIFAR-10 dataset.

- **Weight rewinding.** After pruning, we rewind the remaining weights to their initial value, as in the "lottery ticket" experiments by Frankle & Carbin (2019). We perform iterative magnitude-based

| (a) One-shot pruning | (b) Weight rewinding | (c) SNIP score |

Figure 4: Sparsity-accuracy tradeoff curves under one-shot pruning, weight rewinding, and the SNIP setup. One-shot pruning experiment is done on VGG-16 trained on CIFAR-10 dataset. Weight-rewinding and SNIP experiments are performed on Conv-6 trained on CIFAR-10.

pruning (IMP) on Conv-6, consisting of six convolutional layers followed by three fully-connected layers; we use this model because it is the largest model from Frankle & Carbin (2019) which does not require any additional trick, such as warm-ups.

- **SNIP.** As an additional experiment, we test whether LAMP can provide a general-purpose layerwise sparsity for pruning schemes other than MP. We test under the "pruning at initialization" setup with SNIP scores (Lee et al., 2019). As in the weight-rewinding experiment, we use Conv-6 model on CIFAR-10 dataset, with a batch size of 128.

Again, other experimental details are given at the Appendix A.

Results for all three experiments are given in Fig. 4. On one-shot pruning, we confirm that LAMP comfortably leads other baselines, as in the iterative pruning case. We note that the gap between one-shot pruning and iterative pruning is quite small for LAMP; when 1.15% of all prunable weights survive, iterative LAMP brings only 1.09% accuracy gain over one-shot LAMP. By contrast, the gain from iteration for Uniform MP is 41.62% at the same sparsity level.

On the weight-rewinding experiment, we observe that LAMP remains beneficial over the baseline methods. An unexpected observation is the under-performance of Erdős-Rényi kernel method; the method performs worse than both Global and Uniform+ baselines. This phenomenon seems to be connected to the observation of Zhou et al. (2019) that the initial weights and final weights of a model are highly correlated; global MP may help preserving connections with larger initial magnitudes, which play important roles in terms of signal propagation at initialization (Lee et al., 2020).

On the SNIP experiment, we observe that LAMP achieves a similar performance to the Global SNIP. Recalling that the SNIP score is designed for global pruning (Lee et al., 2019), such high performance of LAMP is unexpected. We suspect that this is because LAMP is also designed for "output distortion minimization," which shares a similar spirit with the "gradient distortion minimization."

5 LAYERWISE SPARSITY: GLOBAL MP, ERDŐS-RÉNYI KERNEL, AND LAMP

With the effectiveness of LAMP confirmed, we take a closer look at the layerwise sparsity discovered by LAMP. We focus on answering two questions: **Q1.** Does layerwise sparsity *distilled* from LAMP behave similarly to the heuristics constructed from experiences, e.g. the one given by Gale et al. (2019)? **Q2.** Is there any other defining characteristic of LAMP sparsity patterns, which may help us guide the design of (sparse) network architectures?

In Fig. 5, we plot the layerwise survival rates and the number of nonzero weights discovered by iteratively pruning VGG-16 (trained on CIFAR-10), by Global MP, Erdős-Rényi kernel, and LAMP. Layerwise survival rates are given for the global survival rates of $\{51.2\%, 26.2\%, 13.4\%, 6.87\%, 3.52\%\}$ (from lighter to darker). Number of nonzero weights are plotted for the pruned models with total $\{3.52\%, 1.80\%, 0.92\%, 0.47\%, 0.24\%\}$ fraction of all weights surviving.

We observe that LAMP sparsities share a similar tendency to sparsity levels given by the Erdős-Rényi kernel method. In particular, both methods tend to keep the first and layer layers of the neural network relatively dense; this property is reminiscent of the handcrafted heuristic given in Gale et al. (2019):

| (a) Global | (b) Erdős-Rényi kernel | (c) LAMP (Ours) |

Figure 5: Layerwise statistics of VGG-16 iteratively pruned on CIFAR-10. **Top:** Layerwise survival rate for models with $\{51.2\%, 26.2\%, 13.4\%, 6.87\%, 3.52\%\}$ weights surviving. **Bottom:** Number of nonzero weights for models with $\{3.52\%, 1.80\%, 0.92\%, 0.47\%, 0.24\%\}$ weights surviving.

keep the first convolutional layer unpruned, and prune at most 80% from the last fully-connected layer. While Global MP also keeps a large fraction of the last fully-connected layer unpruned, the first convolutional layer gets pruned quickly.

LAMP sparsities differ from Erdős-Rényi kernel sparsities in two senses.

- Although LAMP demonstrates its tendency to keep the first and the last layers relatively unpruned, this tendency is softer. When 3.52% of weights survive, LAMP keeps $\sim 79\%$ and $\sim 62\%$ of weights unpruned from the first and last layers (respectively), while Erdős-Rényi kernel does not prune any weight from those two layers.

- LAMP tends to keep the number of nonzero weights relatively uniform throughout the layers at extreme sparsity levels (indeed, the first observation can be understood as a consequence of the second observation). In contrast, Erdős-Rényi kernel method keeps the relative ratio constant, regardless of the global sparsity level.

Following the second observation, we conjecture that having a similar number of nonzero connections in each layer may be an essential condition to guarantee maximal memory capacity (see, e.g., Yun et al. (2019)), given a global sparsity constraint on the neural network. Theoretical investigations of the approximability by such sparse neural networks may be an interesting future research direction, potentially leading to a more principled and robust pruning algorithms.

6 CONCLUSION

In this paper, we investigate an under-explored problem on the layerwise sparsity for magnitude-based pruning scheme. The proposed method, coined LAMP (Layer-Adaptive Magnitude-based Pruning), is motivated from the ℓ_2 distortion minimization perspective on magnitude-based pruning, and provides a consistent performance gain on a wide range of models and datasets. Furthermore, LAMP performs reliably well when combined with one-shot pruning schedule or weight rewinding, which makes it an attractive candidate as a "go-to" layerwise sparsity for the magnitude-based pruning. Taking a deeper look at LAMP-discovered layerwise sparsities, we observe that LAMP automatically recovers the handcrafted rules for the layerwise sparsity. Furthermore, we observe that LAMP tend to keep the number of nonzero weights relatively uniform throughout the layers, as we consider more extreme sparsity levels. We conjecture that such uniformity in the number of unpruned weights may be an essential condition for a maximal expressive power of sparsified neural networks.

REFERENCES

A. Aghasi, A. Abdi, N. Nguyen, and J. Romberg. Net-trim: Convex pruning of deep neural networks with performance guarantee. In *Advances in Neural Information Processing Systems*, 2017.

C. Baykal, L. Liebenwein, I. Gilitschenski, D. Feldman, and D. Rus. Data-dependent coresets for compressing neural networks with applications to generalization bounds. In *International Conference on Learning Representations*, 2019.

B. Dai, C. Zhu, B. Guo, and D. Wipf. Compressing neural networks using the variational information bottleneck. In *Proceedings of International Conference on Machine Learning*, 2018.

X. Dong, S. Chen, and S. J. Pan. Learning to prune deep neural networks via layer-wise optimal brain surgeon. In *Advances in Neural Information Processing Systems*, 2017.

E. Elsen, M. Dukhan, T. Gale, and K. Simonyan. Fast sparse ConvNets. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

U. Evci, T. Gale, J. Menick, P. S. Castro, and E. Elsen. Rigging the lottery: Making all tickets winners. In *Proceedings of International Conference on Machine Learning*, 2020.

J. Frankle and M. Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

T. Gale, E. Elsen, and S. Hooker. The state of sparsity in deep neural networks. In *ICML ODML-CDNNR Workshop*, 2019.

T. Gale, M. Zaharia, C. Young, and E. Elsen. Sparse GPU kernels for deep learning. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage, and Analysis*, 2020.

S. Han, J. Pool, J. Tran, and W. Dally. Learning both weights and connections for efficient neural network. In *Advances in Neural Information Processing Systems*, 2015.

S. J. Hanson and L. Y. Pratt. Comparing biases for minimal network construction with back-propagation. In *Advances in Neural Information Processing Systems*, 1988.

B. Hassibi and D. G. Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *Advances in Neural Information Processing Systems*, 1993.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

S. A. Janowsky. Pruning versus clipping in neural networks. *Physical Review A*, 1989.

A. Krizhevsky and G. Hinton. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

A. Kusupati, V. Ramanujan, R. Somani, M. Wortsman, P. Jain, S. Kakade, and A. Farhadi. Soft threshold weight reparametrization for learnable sparsity. In *Proceedings of International Conference on Machine Learning*, 2020.

Y. LeCun, J. S. Denker, and S. A. Solla. Optimal brain damage. In *Advances in Neural Information Processing Systems*, 1989.

N. Lee, T. Ajanthan, and P. H. S. Torr. Snip: Single-shot network pruning based on connection sensitivity. In *International Conference on Learning Representations*, 2019.

N. Lee, T. Ajanthan, S. Gould, and P. H. S. Torr. A signal propagation perspective for pruning neural networks at initialization. In *International Conference on Learning Representations*, 2020.

J. Lin, Y. Rao, J. Lu, and J. Zhou. Runtime neural pruning. In *Advances in Neural Information Processing Systems*, 2017.

T. Lin, S. U. Stich, L. Barba, D. Dmitriev, and M. Jaggi. Dynamic model pruning with feedback. In *International Conference on Learning Representations*, 2020.

Z. Liu, M. Sun, T. Zhou, G. Huang, and T. Darrell. Rethinking the value of network pruning. In *International Conference on Learning Representations*, 2019.

I. Loshchilov and F. Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

C. Louizos, K. Ullrich, and M. Welling. Bayesian compression for deep learning. In *Advances in Neural Information Processing Systems*, 2017.

C. Louizos, M. Welling, and D. P. Kingma. Learning sparse neural networks through l_0 regularization. In *International Conference on Learning Representations*, 2018.

M. Marcus, B. Santorini, and M. Marcinkiewicz. Building a larger annotated corpus of English: The Penn treebank. *Computational Linguistics*, 1993.

S. Merity, C. Xiong, J. Bradbury, and R. Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations*, 2016.

D. C. Mocanu, E. Mocanu, P. Stone, P. H. Nguyen, M. Gibescu, and A. Liotta. Scalable training of artificial neural networks with adaptive sparse connec- tivity inspired by network science. *Nature Communications*, 2018.

D. Molchanov, A. Ashukha, and D. Vetrov. Variational dropout sparsifies deep neural networks. In *Proceedings of International Conference on Machine Learning*, 2017.

A. S. Morcos, H. Yi, M. Paganini, and Y. Tian. One ticket to win them all: Generalizing lottery ticket initializations across datasets and optimizers. In *Advances in Neural Information Processing Systems*, 2019.

M. C. Mozer and P. Smolensky. Skeletonization: A technique for trimming the fat from a network via relevance assessment. In *Advances in Neural Information Processing Systems*, 1988.

B. Mussay, M. Osadchy, V. Braverman, S. Zhou, and D. Feldman. Data-indenpendent neural pruning via coresets. In *International Conference on Learning Representations*, 2020.

Y. Netzer, T. Wang, A. Coates, A. Bissacco, B. Wu, and A. Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NeurIPS Deep Learning and Unsupervised Feature Learning Workshop*, 2011.

B. Neyshabur, R. Tomioka, and N. Srebro. Norm-based capacity control in neural networks. In *Conference on Learning Theory*, 2015.

S. Park, J. Lee, S. Mo, and J. Shin. Lookahead: A far-sighted alternative of magnitude-based pruning. In *International Conference on Learning Representations*, 2020.

A. Renda, J. Frankle, and M. Carbin. Comparing fine-tuning and rewinding in neural network pruning. In *International Conference on Learning Representations*, 2020.

V. Sanh, T. Wolf, and A. M. Rush. Movement pruning: Adaptive sparsity by fine-tuning. arXiv preprint 2005.07683, 2020.

H. Sedghi, V. Gupta, and P. M. Long. The singular values of convolutional layers. In *International Conference on Learning Representations*, 2019.

K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015.

M. Tan and Q. V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *Proceedings of International Conference on Machine Learning*, 2019.

D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Madry. Robustness may be at odds with accuracy. In *International Conference on Learning Representations*, 2019.

A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

X. Xiao, Z. Wang, and S. Rajasekaran. AutoPrune: Automatic network pruning by regularizing auxiliary parameters. In *Advances in Neural Information Processing Systems*, 2019.

C. Yun, S. Sra, and A. Jadbabaie. Small ReLU networks are powerful memorizers: a tight analysis of memorization capacity. In *Advances in Neural Information Processing Systems*, 2019.

H. Zhou, J. Lan, R. Liu, and J. Yosinki. Deconstructing lottery tickets: Zeros, signs, and supermasks. In *Advances in Neural Information Processing Systems*, 2019.

M. Zhu and S. Gupta. To prune, or not to prune: exploring the efficacy of pruning for model compression. In *ICLR Workshop track*, 2018.

A   EXPERIMENTAL SETUPS

For any implementational details not given in this section, we refer to our code which will be uploaded to the URL `https://anonymous.code.base` (to be publicly released after reviews).

Optimizer. With an exception of the weight rewinding experiment, we use AdamW (Loshchilov & Hutter, 2019) with learning rate 0.0003; we use vanilla Adam with learning rate 0.0003 for the weight rewinding experiment, following the setup of Frankle & Carbin (2019). For other hyperparameters, we follow the PyTorch default setup: $\vec{\beta} = (0.9, 0.999)$, wd $= 0.01$, $\varepsilon = 10^{-8}$.

Pre-processing. CIFAR-10/100 dataset is augmented with random crops with a padding of 4 and random horizontal flips. We normalize both training and test datasets with constants

$$(0.4914, 0.4822, 0.4465), (0.237, 0.243, 0.261).$$

SVHN training dataset is augmented with random crops with a padding of 2. We normalize both training and test datasets with constants

$$(0.4377, 0.4438, 0.4728), (0.198, 0.201, 0.197).$$

Restricted ImageNet training dataset is augmented with Random resized crop to size 224 and random horizontal flips. Restricted ImageNet test dataset is resized to 256 and then center-cropped to size 224. We normalize both training and test datasets with constants

$$(0.485, 0.456, 0.406), (0.229, 0.224, 0.225).$$

Table 1: Optimization details.

Dataset	Model	Initial training iter.	Re-training iter.	Batch size
SVHN	VGG-16	40000	30000	100
CIFAR-10	{VGG-16, ResNet-18, EfficientNet-B0}	50000	40000	100
CIFAR-10	DenseNet-121	80000	60000	100
CIFAR-100	VGG-16	60000	50000	100
Restricted ImageNet	ResNet-34	80000	80000	128
CIFAR-10	Conv-6 (Weight rewinding)	30000	30000	60
CIFAR-10	Conv-6 (SNIP)	50000	40000	128

B COMPUTATIONAL AND IMPLEMENTATIONAL ASPECTS OF LAMP

In this section, we discuss the computational complexity of LAMP and describe how LAMP can be implemented. We consider a depth-d neural network, with n_i number of connections in i-th layer. We also let $n = \sum_{i=1}^{d} n_i$.

The global MP is comprised of two steps:

- **Step 1.** Pool and sort the weight magnitudes of all connections, taking $\mathcal{O}(n \log n)$ operations.
- **Step 2.** Assign 0s to connections with smallest weights until the desired sparsity level is achieved, taking $\mathcal{O}(n)$ computations.

The total computational cost is of order $\mathcal{O}(n \log n)$. Similarly, we see that performing MP with any pre-determined sparsity levels incurs $\mathcal{O}(\sum_{i=1}^{d} n_i \log n_i)$ computations.

LAMP, on the other hand, can be done in four steps.

- **Step 1.** Weight magnitudes are squared and sorted for each layer, which can be done with a computation cost of $\mathcal{O}(\sum_{i=1}^{d} n_i \log n_i)$.
- **Step 2.** LAMP score denominators $\sum_{v \geq u} W_i^2[v]$ for each layer is computed by summing-and-storing the squared weight magnitudes according to a descending order; takes $\mathcal{O}(n)$ computations.
- **Step 3.** The LAMP score is computed by dividing squared weight magnitudes by the denominators, using $\mathcal{O}(n)$ steps.
- **Step 4.** We sort and prune as in global MP, taking $\mathcal{O}(n \log n)$ steps.[4]

We observe that step 4 is the dominant term, which is shared by the global MP. The first three steps can be easily implemented in PyTorch as follows.

```
def lamp_score(weight):
    normalizer = weight.norm() ** 2

    sorted_weight, sorted_idx = weight.abs().view(-1).sort(descending=False)

    weight_cumsum_temp = (sorted_weight ** 2).cumsum(dim=0)
    weight_cumsum = torch.zeros(weight_cumsum_temp.shape)
    weight_cumsum[1:] = weight_cumsum_temp[:len(weight_cumsum_temp) - 1]

    sorted_weight /= (normalizer - weight_square_cumsum).sqrt()

    score = torch.zeros(weight_cumsum.shape)
    score[sorted_idx] = sorted_weight

    score = score.view(weight.shape)

    return score
```

---

[4]This cost can be further reduced, recalling that the LAMP scores in each layer are already sorted. All that remains is a merging step.

C   PROOF OF INEQUALITY (7)

In this section, we prove the following inequality.

$$\sup_{\|x\|_2 \leq 1} \|f(x; W_{1:d}) - f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d})\|_2 \leq \|W_i - \widetilde{W}_i\|_F \cdot \prod_{j \neq i} \|W_j\|_F. \tag{8}$$

This inequality is a simplified and modified version of what is popularly known as "peeling" procedure in the generalization literature (e.g., (Neyshabur et al., 2015)), and we present the proof only for the sake of completeness. We begin by peeling the outermost layer as

$$\|f(x; W_{1:d}) - f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d})\|_2 \tag{9}$$

$$= \left\| W_d \left(\sigma(f(x; W_{1:d-1}) - \sigma(f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d-1})) \right) \right\|_2 \tag{10}$$

$$\leq \|W_d\|_F \cdot \left\| \sigma(f(x; W_{1:d-1}) - \sigma(f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d-1})) \right\|_2 \tag{11}$$

$$\leq \|W_d\|_F \cdot \left\| f(x; W_{1:d-1}) - f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d-1}) \right\|_2, \tag{12}$$

where we have used Cauchy-Schwarz inequality for the first inequality, and the 1-Lipschitzness of ReLU activation with respect to ℓ_2 norm. We keep on peeling until we get

$$\|f(x; W_{1:d}) - f(x; W_{1:i-1}, \widetilde{W}_i, W_{i+1:d})\|_2 \tag{13}$$

$$\leq \left(\prod_{j > i} \|W_j\|_F \right) \cdot \|f(x; W_{1:i}) - f(x; W_{1:i-1}, \widetilde{W}_i)\|_2. \tag{14}$$

The second multiplicative term on the right-hand side requires a slightly different treatment. Via Cauchy-Schwarz, we get

$$\|f(x; W_{1:i}) - f(x; W_{1:i-1}, \widetilde{W}_i)\|_2 = \left\| \left(W_i - \widetilde{W}_i \right) \sigma(f(x; W_{1:i-1})) \right\|_2 \tag{15}$$

$$\leq \|W_i - \tilde{W}_i\|_F \cdot \|\sigma(f(x; W_{1:i-1}))\|_2. \tag{16}$$

The activation functions from this point require zero-in-zero-out (ZIZO; $\sigma(\mathbf{0}) = \mathbf{0}$) property to be peeled, in addition to the Lipschitzness. Indeed, we can proceed as

$$\|\sigma(f(x; W_{1:i-1}))\|_2 = \|\sigma(f(x; W_{1:i-1})) - \sigma(\mathbf{0})\|_2 \leq \|f(x; W_{1:i-1}) - \mathbf{0}\|_2 \tag{17}$$

$$= \|f(x; W_{1:i-1})\|_2. \tag{18}$$

Iteratively applying the Cauchy-Schwarz inequality and the step Eq. (18), we arrive at Eq. (8).

Table 2: Test perplexities of Transformer-XL iteratively pruned and trained on Penn Treebank. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	26.2%	21.0%	16,8%	13.4%	10.8%	8.59%	6.87%	5.50%	4.40%	3.52%
Global	$71.38_{\pm 0.39}$	$71.78_{\pm 0.34}$	$73.23_{\pm 0.38}$	$73.67_{\pm 0.10}$	$76.23_{\pm 0.43}$	$78.21_{\pm 0.31}$	$80.92_{\pm 0.10}$	$83.98_{\pm 0.36}$	$88.62_{\pm 0.25}$	$92.30_{\pm 0.54}$
Uniform	$71.57_{\pm 0.46}$	$71.74_{\pm 0.39}$	$73.27_{\pm 0.36}$	$74.18_{\pm 0.34}$	$76.98_{\pm 0.41}$	$79.25_{\pm 0.29}$	$81.79_{\pm 0.13}$	$84.95_{\pm 0.35}$	$89.41_{\pm 0.39}$	$92.44_{\pm 0.69}$
Erdős-Rényi ker.	$71.53_{\pm 0.33}$	$71.94_{\pm 0.20}$	$73.56_{\pm 0.31}$	$74.43_{\pm 0.20}$	$77.15_{\pm 0.33}$	$79.38_{\pm 0.26}$	$82.03_{\pm 0.13}$	$85.01_{\pm 0.38}$	$89.34_{\pm 0.31}$	$92.75_{\pm 0.55}$
LAMP (Ours)	$71.51_{\pm 0.38}$	$71.79_{\pm 0.24}$	$73.11_{\pm 0.37}$	$73.74_{\pm 0.21}$	$76.23_{\pm 0.27}$	$78.27_{\pm 0.18}$	$80.73_{\pm 0.09}$	$83.60_{\pm 0.35}$	$88.06_{\pm 0.24}$	$91.24_{\pm 0.38}$

Table 3: Test perplexities of Transformer-XL iteratively pruned and trained on WT-2. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	26.2%	21.0%	16,8%	13.4%	10.8%	8.59%	6.87%	5.50%	4.40%	3.52%
Global	$87.62_{\pm 0.28}$	$90.43_{\pm 0.58}$	$91.35_{\pm 0.21}$	$94.65_{\pm 0.30}$	$96.34_{\pm 0.35}$	$100.07_{\pm 0.48}$	$103.56_{\pm 0.48}$	$107.95_{\pm 0.74}$	$112.20_{\pm 0.34}$	$117.03_{\pm 0.63}$
Uniform	$87.88_{\pm 0.26}$	$90.46_{\pm 0.69}$	$91.58_{\pm 0.29}$	$95.01_{\pm 0.21}$	$96.72_{\pm 0.79}$	$100.83_{\pm 0.32}$	$104.25_{\pm 0.28}$	$108.31_{\pm 0.53}$	$112.71_{\pm 0.25}$	$117.01_{\pm 0.50}$
Erdős-Rényi ker.	$88.01_{\pm 0.23}$	$90.62_{\pm 0.64}$	$91.99_{\pm 0.28}$	$95.40_{\pm 0.36}$	$97.13_{\pm 0.72}$	$100.83_{\pm 0.38}$	$104.49_{\pm 0.51}$	$108.51_{\pm 0.90}$	$112.56_{\pm 0.47}$	$116.69_{\pm 0.34}$
LAMP (Ours)	$87.73_{\pm 0.26}$	$90.76_{\pm 0.54}$	$91.47_{\pm 0.33}$	$94.58_{\pm 0.30}$	$96.10_{\pm 0.53}$	$99.62_{\pm 0.19}$	$103.01_{\pm 0.22}$	$106.60_{\pm 0.46}$	$110.87_{\pm 0.63}$	$115.31_{\pm 0.64}$

D EXPERIMENTAL RESULTS ON LANGUAGE MODELING

In this section, we apply LAMP and baseline schemes on the language modeling task. We note, however, that it is still unclear whether magnitude-based pruning approaches achieve state-of-the-art results for pruning natural language processing tasks (see, e.g., Sanh et al. (2020), for more discussions). We also note that we do not test Uniform+ baseline for this task, as the heuristic is proposed explicitly for image classification models, not language models (Gale et al., 2019).

Model. We consider the simplified version of Transformer-XL (Dai et al., 2018) architecture, which has six self-attention layers (original has 16) and removed some regularizing heuristics, such as exponential moving average and cosine annealing. Similar to the setting of Sanh et al. (2020), we focus on pruning self-attention layers of the model (approximately 7.57M parameters).

Optimizer. We use AdamW (Loshchilov & Hutter, 2019) with learning rate 0.0003, following the PyTorch default setup for other hyperparameters: $\vec{\beta} = (0.9, 0.999)$, wd $= 0.01$, $\varepsilon = 10^{-8}$. We use batch size 20 and maximum sequence length 70. We train the initial unpruned model for 200,000 iterations and re-train the model after pruning for 50,000 iterations.

Datasets. We use Penn Treebank (Marcus et al., 1993) and WikiText-2 (Merity et al., 2016) datasets.

We provide the experimental results in Tables 2 and 3. We observe that LAMP consistently achieves the near-best performance among all considered methods. We note, however, that the gain is marginal. We suspect that this marginal-ity is due to the fact that *widths* of the Transformer layers are relatively uniform compared to image classification models. We do not observe any notable pattern among the baseline methods.

E DETAILED EXPERIMENTAL RESULTS (WITH STANDARD DEVIATIONS)

Table 4: Test accuracies of VGG-16 iteratively pruned and trained on CIFAR-10. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	6.87%	4.40%	2.81%	1.80%	1.15%	0.74%	0.47%	0.30%	0.19%	0.12%
Global	$91.30_{\pm0.23}$	$90.80_{\pm0.23}$	$89.28_{\pm0.30}$	$85.55_{\pm2.38}$	$81.56_{\pm3.73}$	$54.58_{\pm22.07}$	$41.91_{\pm18.63}$	$31.93_{\pm21.24}$	$21.87_{\pm21.21}$	$11.72_{\pm2.29}$
Uniform	$91.47_{\pm0.19}$	$90.78_{\pm0.12}$	$88.61_{\pm1.09}$	$84.17_{\pm4.46}$	$55.68_{\pm12.20}$	$38.51_{\pm24.83}$	$26.41_{\pm8.83}$	$16.75_{\pm6.62}$	$11.58_{\pm2.79}$	$9.95_{\pm0.28}$
Uniform+	$91.54_{\pm0.19}$	$91.20_{\pm0.28}$	$90.16_{\pm0.12}$	$89.44_{\pm0.15}$	$87.85_{\pm0.26}$	$86.53_{\pm0.05}$	$84.84_{\pm0.41}$	$82.41_{\pm0.44}$	$74.54_{\pm5.41}$	$24.46_{\pm14.98}$
Erdős-Rényi ker.	$\mathbf{92.34}_{\pm0.25}$	$\mathbf{91.99}_{\pm0.14}$	$\mathbf{91.66}_{\pm0.29}$	$91.15_{\pm0.24}$	$90.55_{\pm0.19}$	$89.51_{\pm0.50}$	$88.21_{\pm0.38}$	$86.73_{\pm0.25}$	$84.85_{\pm0.28}$	$81.50_{\pm0.42}$
LAMP (Ours)	$\mathbf{92.24}_{\pm0.24}$	$\mathbf{92.06}_{\pm0.21}$	$\mathbf{91.71}_{\pm0.30}$	$\mathbf{91.66}_{\pm0.21}$	$\mathbf{91.07}_{\pm0.40}$	$\mathbf{90.49}_{\pm0.21}$	$\mathbf{89.64}_{\pm0.32}$	$\mathbf{88.75}_{\pm0.29}$	$\mathbf{87.07}_{\pm0.37}$	$\mathbf{84.90}_{\pm0.59}$

Table 5: Test accuracies of ResNet-18 iteratively pruned and trained on CIFAR-10. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	6.87%	4.40%	2.81%	1.80%	1.15%	0.74%	0.47%	0.30%	0.19%	0.12%
Global	$92.74_{\pm0.22}$	$92.49_{\pm0.18}$	$92.18_{\pm0.11}$	$91.27_{\pm0.10}$	$89.78_{\pm0.36}$	$86.80_{\pm1.55}$	$83.57_{\pm2.44}$	$61.25_{\pm28.40}$	$60.72_{\pm23.04}$	$29.84_{\pm26.45}$
Uniform	$92.94_{\pm0.21}$	$92.59_{\pm0.21}$	$91.99_{\pm0.23}$	$90.89_{\pm0.27}$	$89.67_{\pm0.11}$	$87.71_{\pm0.27}$	$84.90_{\pm0.73}$	$61.85_{\pm29.20}$	$20.53_{\pm11.13}$	$11.42_{\pm2.21}$
Uniform+	$92.88_{\pm0.18}$	$92.53_{\pm0.17}$	$92.07_{\pm0.18}$	$91.29_{\pm0.20}$	$90.08_{\pm0.18}$	$88.67_{\pm0.40}$	$86.67_{\pm0.16}$	$83.98_{\pm0.37}$	$77.13_{\pm3.32}$	$44.69_{\pm30.24}$
Erdős-Rényi ker.	$\mathbf{93.29}_{\pm0.27}$	$\mathbf{93.05}_{\pm0.11}$	$\mathbf{92.90}_{\pm0.18}$	$\mathbf{92.45}_{\pm0.14}$	$91.86_{\pm0.25}$	$90.69_{\pm0.22}$	$89.52_{\pm0.22}$	$88.16_{\pm0.28}$	$85.71_{\pm0.38}$	$81.87_{\pm0.35}$
LAMP (Ours)	$\mathbf{93.24}_{\pm0.25}$	$\mathbf{93.18}_{\pm0.15}$	$\mathbf{92.96}_{\pm0.22}$	$\mathbf{92.68}_{\pm0.31}$	$\mathbf{92.12}_{\pm0.19}$	$\mathbf{91.40}_{\pm0.35}$	$\mathbf{90.54}_{\pm0.14}$	$\mathbf{88.99}_{\pm0.22}$	$\mathbf{87.24}_{\pm0.23}$	$\mathbf{84.61}_{\pm0.48}$

Table 6: Test accuracies of DenseNet-121 iteratively pruned and trained on CIFAR-10. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	5.50%	4.40%	3.52%	2.82%	2.25%	1.80%	1.44%	1.15%	0.92%	0.74%
Global	$90.16_{\pm0.36}$	$89.52_{\pm0.36}$	$88.83_{\pm0.44}$	$88.00_{\pm0.43}$	$86.85_{\pm0.47}$	$85.32_{\pm0.58}$	$77.68_{\pm8.01}$	$45.30_{\pm27.75}$	$49.65_{\pm21.88}$	$20.96_{\pm19.49}$
Uniform	$90.24_{\pm0.11}$	$89.50_{\pm0.13}$	$88.44_{\pm0.19}$	$87.94_{\pm0.45}$	$86.83_{\pm0.41}$	$85.00_{\pm1.54}$	$82.16_{\pm3.37}$	$70.13_{\pm13.69}$	$66.46_{\pm18.72}$	$48.71_{\pm21.42}$
Uniform+	$90.25_{\pm0.18}$	$89.70_{\pm0.20}$	$89.03_{\pm0.17}$	$88.22_{\pm0.27}$	$87.40_{\pm0.41}$	$86.26_{\pm0.44}$	$84.55_{\pm0.45}$	$81.87_{\pm0.77}$	$69.25_{\pm19.28}$	$58.91_{\pm8.26}$
Erdős-Rényi ker.	$90.21_{\pm0.29}$	$89.79_{\pm0.29}$	$88.92_{\pm0.07}$	$88.20_{\pm0.23}$	$87.25_{\pm0.36}$	$86.22_{\pm0.30}$	$84.11_{\pm0.50}$	$81.82_{\pm0.90}$	$59.06_{\pm25.61}$	$59.07_{\pm25.70}$
LAMP (Ours)	$\mathbf{90.89}_{\pm0.17}$	$\mathbf{90.11}_{\pm0.13}$	$\mathbf{89.72}_{\pm0.26}$	$\mathbf{89.12}_{\pm0.35}$	$\mathbf{88.39}_{\pm0.26}$	$\mathbf{87.75}_{\pm0.18}$	$\mathbf{86.53}_{\pm0.33}$	$\mathbf{85.13}_{\pm0.31}$	$\mathbf{82.92}_{\pm0.66}$	$\mathbf{79.23}_{\pm1.29}$

Table 7: Test accuracies of EfficientNet-B0 iteratively pruned and trained on CIFAR-10. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	41.0%	26.2%	16.8%	10.7%	6.87%	4.40%	2.82%	1.80%	1.15%	0.74%
Global	$\mathbf{89.66}_{\pm0.21}$	$89.55_{\pm0.30}$	$88.80_{\pm0.32}$	$87.64_{\pm0.35}$	$84.36_{\pm0.59}$	$79.25_{\pm0.67}$	$11.09_{\pm2.14}$	$10.62_{\pm1.38}$	$10.00_{\pm0.00}$	$10.00_{\pm0.00}$
Uniform	$88.99_{\pm0.31}$	$88.26_{\pm0.32}$	$86.48_{\pm0.38}$	$83.40_{\pm0.38}$	$23.65_{\pm28.16}$	$10.83_{\pm0.83}$	$10.00_{\pm0.00}$	$10.00_{\pm0.00}$	$10.00_{\pm0.00}$	$10.00_{\pm0.00}$
Uniform+	$89.18_{\pm0.35}$	$88.03_{\pm0.19}$	$86.71_{\pm0.40}$	$84.16_{\pm0.65}$	$36.64_{\pm35.77}$	$10.45_{\pm0.67}$	$10.00_{\pm0.00}$	$10.19_{\pm1.62}$	$10.00_{\pm0.00}$	$10.00_{\pm0.00}$
Erdős-Rényi ker.	$\mathbf{89.54}_{\pm0.17}$	$\mathbf{90.09}_{\pm0.09}$	$\mathbf{90.01}_{\pm0.31}$	$89.62_{\pm0.26}$	$88.82_{\pm0.39}$	$87.08_{\pm0.32}$	$84.72_{\pm0.24}$	$81.53_{\pm0.44}$	$51.31_{\pm25.77}$	$13.40_{\pm3.04}$
LAMP (Ours)	$\mathbf{89.52}_{\pm0.51}$	$89.95_{\pm0.20}$	$\mathbf{89.97}_{\pm0.23}$	$\mathbf{90.21}_{\pm0.28}$	$\mathbf{89.91}_{\pm0.14}$	$\mathbf{89.79}_{\pm0.33}$	$\mathbf{89.30}_{\pm0.08}$	$\mathbf{88.51}_{\pm0.37}$	$\mathbf{86.79}_{\pm0.73}$	$\mathbf{65.76}_{\pm20.07}$

Table 8: Test accuracies of VGG-16 iteratively pruned and trained on SVHN. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	6.87%	4.40%	2.82%	1.80%	1.15%	0.74%	0.47%	0.30%	0.19%	0.12%
Global	$95.75_{\pm0.17}$	$95.46_{\pm0.10}$	$94.91_{\pm0.48}$	$61.06_{\pm30.93}$	$65.06_{\pm11.01}$	$49.51_{\pm24.23}$	$26.83_{\pm19.39}$	$15.37_{\pm5.95}$	$7.79_{\pm1.60}$	$14.72_{\pm3.65}$
Uniform	$95.78_{\pm0.16}$	$95.52_{\pm0.10}$	$95.35_{\pm0.14}$	$94.98_{\pm0.19}$	$93.26_{\pm1.42}$	$64.32_{\pm15.03}$	$29.54_{\pm10.21}$	$19.63_{\pm7.54}$	$13.73_{\pm6.97}$	$17.94_{\pm4.85}$
Uniform+	$95.70_{\pm0.13}$	$95.68_{\pm0.17}$	$95.42_{\pm0.11}$	$95.05_{\pm0.15}$	$94.57_{\pm0.16}$	$93.87_{\pm0.10}$	$93.07_{\pm0.16}$	$92.25_{\pm0.25}$	$74.88_{\pm25.75}$	$17.67_{\pm14.33}$
Erdős-Rényi ker.	$\mathbf{96.00}_{\pm0.09}$	$\mathbf{95.89}_{\pm0.11}$	$95.59_{\pm0.15}$	$95.47_{\pm0.10}$	$95.16_{\pm0.08}$	$94.81_{\pm0.16}$	$94.30_{\pm0.18}$	$93.74_{\pm0.27}$	$93.48_{\pm0.27}$	$93.06_{\pm0.25}$
LAMP (Ours)	$\mathbf{95.98}_{\pm0.15}$	$\mathbf{95.87}_{\pm0.13}$	$\mathbf{95.74}_{\pm0.10}$	$\mathbf{95.58}_{\pm0.07}$	$\mathbf{95.35}_{\pm0.18}$	$\mathbf{95.16}_{\pm0.08}$	$\mathbf{94.71}_{\pm0.18}$	$\mathbf{94.24}_{\pm0.17}$	$\mathbf{94.05}_{\pm0.15}$	$\mathbf{93.97}_{\pm0.19}$

Table 9: Test accuracies of VGG-16 iteratively pruned and trained on CIFAR-100. Bold denotes the pruning scheme with accuracy within one standard deviation from the highest.

Surv. weights	13.42%	8.59%	5.50%	3.52%	2.25%	1.44%	0.92%	0.59%	0.38%	0.24%
Global	$\mathbf{68.02}_{\pm0.22}$	$67.20_{\pm0.13}$	$66.82_{\pm0.25}$	$65.68_{\pm0.28}$	$63.25_{\pm0.37}$	$60.18_{\pm0.33}$	$53.52_{\pm1.97}$	$33.66_{\pm18.02}$	$7.80_{\pm2.97}$	$4.29_{\pm6.04}$
Uniform	$\mathbf{67.92}_{\pm0.23}$	$67.43_{\pm0.37}$	$66.41_{\pm0.54}$	$63.94_{\pm0.71}$	$57.62_{\pm2.01}$	$48.88_{\pm4.56}$	$32.60_{\pm14.16}$	$14.99_{\pm8.65}$	$3.94_{\pm3.67}$	$3.35_{\pm2.80}$
Uniform+	$\mathbf{67.94}_{\pm0.32}$	$67.41_{\pm0.16}$	$66.37_{\pm0.09}$	$65.51_{\pm0.33}$	$63.43_{\pm0.35}$	$60.76_{\pm0.29}$	$57.93_{\pm0.39}$	$55.40_{\pm0.22}$	$51.90_{\pm1.30}$	$33.35_{\pm13.08}$
Erdős-Rényi ker.	$\mathbf{68.07}_{\pm0.42}$	$67.92_{\pm0.36}$	$67.45_{\pm0.22}$	$\mathbf{67.09}_{\pm0.31}$	$\mathbf{65.86}_{\pm0.18}$	$64.15_{\pm0.31}$	$62.04_{\pm0.37}$	$60.07_{\pm0.35}$	$58.58_{\pm0.58}$	$55.88_{\pm0.51}$
LAMP (Ours)	$\mathbf{68.07}_{\pm0.58}$	$\mathbf{68.22}_{\pm0.27}$	$\mathbf{67.84}_{\pm0.31}$	$\mathbf{67.37}_{\pm0.28}$	$\mathbf{66.35}_{\pm0.53}$	$\mathbf{65.25}_{\pm0.23}$	$\mathbf{63.46}_{\pm0.28}$	$\mathbf{62.37}_{\pm0.28}$	$\mathbf{60.77}_{\pm0.42}$	$\mathbf{58.05}_{\pm0.42}$