Auto-scaling Vision Transformers without Training

Abstract

This work targets automated designing and scaling of Vision Transformers (ViTs). The motivation comes from two pain spots: 1) the lack of efficient and principled methods for designing and scaling ViTs; 2) the tremendous computational cost of training ViT that is much heavier than its convolution counterpart. To tackles these issues, we propose **As-ViT**, an auto-scaling framework for ViTs without training, which automatically discovers and scales up ViTs in an efficient and principled manner. Specifically, we first design a "seed" ViT topology by leveraging a training-free search process. This extremely fast search is fulfilled by a comprehensive study of ViT's network complexity, yielding a strong Kendall-tau correlation with ground-truth accuracies. Second, starting from the "seed" topology, we automate the scaling rule for ViTs by growing widths/depths to different ViT layers. This results in a series of architectures with different numbers of parameters in a single run. Finally, based on the observation that ViTs can tolerate coarse tokenization in early training stages, we propose a progressive tokenization strategy to train ViTs faster and cheaper. As a unified framework, **As-ViT** achieves strong performance on classification (83.5% top1 on ImageNet-1k) and detection (52.7% mAP on COCO) without any tedious hand-crafting and scaling of ViT architectures, at significantly low cost for model designing (only 12 GPU-hours, one V100). We will release our codes and pre-trained models upon acceptance.

1 Introduction

Transformer (Vaswani et al., 2017), a family of architectures based on the self-attention mechanism, is notable for modeling long-range dependencies in the data. The success of transformers has evolved from natural language processing to computer vision. Recently, Vision Transformer (ViT) (Dosovitskiy et al., 2020), a transformer architecture consisting of self-attention encoder blocks, has been proposed to achieve competitive performance to convolution neural networks (CNNs) (Simonyan & Zisserman, 2014; He et al., 2016) on ImageNet (Deng et al., 2009).

However, it remains elusive in ViTs on how to effectively design, scale up, and train them, with three important gaps awaiting. First, Dosovitskiy et al. (2020) directly hard-split the 2D image into a series of local patches, and learn the representation with a pre-defined number of attention heads and channel expansion ratios. These ad-hoc "tokenization" and embedding mainly inherit from language tasks (Vaswani et al., 2017) but not customized for vision, which calls for more flexible and principled **designs**. Second, the learning behaviors of ViT, including feature diversity (Zhou et al., 2021), receptive fields (Raghu et al., 2021) and augmentations (Touvron et al., 2020), are very different from CNNs. Benefiting from self-attention, ViT can capture global information even with shallow layers, whereas its performance is more quickly plateaued as going deeper. Besides, strong augmentations are vital to avoid ViTs from overfitting. These observations indicate that ViT architectures may require uniquely customized **scaling-up** to learn meaningful visual representations. Third, as mentioned by Dosovitskiy et al. (2020) and many successors, training ViTs is both data and computation-consuming. To achieve state-of-the-art performance, ViT requires up to 300 million images and thousands of TPU-days. Although recent works attempt to train ViTs on ImageNet-1k from scratch (Touvron et al., 2020), the heavy computation cost to the token number (usually quadratic due to self-attention) is still overwhelming, compared with training CNNs.

We point out that the above gaps are inherently connected by the core architecture problem: how to design and scale up ViTs? Different from the convolutional layer that directly digests raw pixels,

ViT has to embed coarse-level local patches as input tokens. Shall we divide an image into tokens of smaller size, or larger but overlapped tokens? The former could embed more visual details in each token, while the latter sacrifices the local details but may benefit more spatial correlations among tokens. A further question is about ViT's depth/width trade-off: shall we prefer a wider and shallower ViT, or a narrower and deeper one? Moreover, a similar dilemma persists for ViT training: reducing the number of tokens would effectively speed up the ViT training, but meanwhile might sacrifice the training performance if sticking to coarse token sizes from end to end.

In this work, we aim to reform the discovery of novel ViT architectures. Our framework, called **As-ViT** (Auto-scaling ViT), allows for extremely fast, efficient, and principled ViT design and scaling. In short, As-ViT first finds a promising "seed" topology for ViT of small depths and widths, then progressively "grow" it into different sizes (number of parameters) to meet different needs. Specifically, our "seed" ViT topology is discovered from a search space relaxed from recent manual ViT designs. To compare different topologies, we automate this process by a training-free architecture search approach via measuring the network complexity, which is extremely fast and efficient. This training-free search is supported by our comprehensive study of various network complexity metrics, where we find the expected length distortion has the best trade-off between time costs and Kendall-tau correlations. Our "seed" ViT topology is then progressively scaled up from a small to a large network, generating a series of ViT variants in a single run. Each step, how to increase the depth and width is automatically determined by comparing network complexities of different scaling choices, being both principled and efficient. Furthermore, to address the data-hungry and heavy computation costs of ViTs, we make our ViT tokens elastic, and propose a progressive re-tokenization method for efficient ViT training. We summarize our contributions as below:

1. We for the first time automate both the design and scaling of ViTs. A "seed" ViT topology is first discovered (in only seven V100 GPU-hours), and then its depths and widths are grown into different sizes with a principled scaling rule in a single run (only five V100 GPU-hours).

2. To estimate ViT's performance at initialization without any training, we conduct the first comprehensive study of ViT's network complexity measurements. We find the expected length distortion has the best trade-off between costs of computation time and Kendall-tau correlations with ViT's ground-truth accuracy.

3. During training, we propose a progressive re-tokenization scheme via the change of dilation and stride, which demonstrates to be a highly efficient ViT training strategy that saves up to 56.2% training FLOPs and 41.1% training time, while preserving a competitive accuracy.

4. Our **As-ViT** achieves strong performance on classification (83.5% top1 on ImageNet-1k) and detection (52.7% mAP on COCO).

2 WHY WE NEED AUTOMATED DESIGN AND SCALING PRINCIPLE FOR VIT?

Background and recent development of ViT[1]   To transform a 2D image into a sequence, ViT (Dosovitskiy et al., 2020) splits each image into 14×14 or 16×16 patches and embeds them into a fixed number of tokens; then following practice of the transformer for language modeling, ViT applies self-attention to learn reweighting masks as relationship modeling for tokens, and leverages FFN (Feed-Forward Network) layers to learn feature embeddings. To better facilitate the visual representation learning, recently works try to train deeper ViTs (Touvron et al., 2021; Zhou et al., 2021), incorporate convolutions (Wu et al., 2021; d'Ascoli et al., 2021; Yuan et al., 2021a), and design multi-scale feature extractions (Chen et al., 2021b; Zhang et al., 2021; Wang et al., 2021).

Why manual design and scaling may be suboptimal?   As the ViT architecture is still in its infant stage, there is no principle in its design and scaling. Early designs incorporate large token sizes, constant sequence length, and hidden size (Dosovitskiy et al., 2020; Touvron et al., 2020), and recent trends include small patches, spatial reduction, and channel doubling (Zhou et al., 2021; Liu et al., 2021). They all achieve comparably good performance, leaving the optimal choices unclear. Moreover, different learning behaviors of transformers from CNNs make the scaling law of ViTs highly unclear. Recent works (Zhou et al., 2021) demonstrated that attention maps of ViTs gradually become similar in deeper layers, leading to identical feature maps and saturated performance. ViT

---

[1]We generally use the term "ViT" to indicate deep networks of self-attention blocks for vision problems. We always include a clear citation when we specifically discuss the ViTs proposed by Dosovitskiy et al. (2020).

also generates more uniform representations across layers, enabling early aggregation of global context (Raghu et al., 2021). This is contradictory to CNNs as deeper layers help the learning of visual global information (Chen et al., 2018). These observations all indicate that previously studied scaling laws (depth/width allocations) for CNNs (Tan & Le, 2019) may not be appropriate to ViTs.

What principle do we want? We aim to automatically design and scale up ViTs, being principled and avoiding manual efforts and potential biases. We also want to answer two questions: 1) Does ViT have any preference in its topology (patch sizes, expansion ratios, number of attention heads, etc.)? 2) Does ViT necessarily follow the same scaling rule of CNNs?

3 AUTO-DESIGN & SCALING OF VITS WITH NETWORK COMPLEXITY

To accelerate in ViT designing and avoid tedious manual efforts, we target efficient, automated, and principled search and scaling of ViTs. Specifically, we have two problems to solve: 1) with minimal or even zero training cost (Section 3.2), how to efficiently find the optimal ViT architecture topology (Section 3.3)? 2) how to scale up depths and widths of the ViT topology to meet different needs of model sizes (Section 3.4)?

3.1 EXPANDED TOPOLOGY SPACE FOR VITS

Before designing and scaling, we first briefly introduce our expanded topology search space for our As-ViT (*blue italics* in Figure 1). We first downsample the input image to $\frac{1}{4}$-scale resolution, and adopt a stage-wise spatial reduction and channel doubling strategy. This is for the convenience of dense prediction tasks like detection that require multi-scale features. Table 1 summarizes details of our topology space, and will be explained below.

Figure 1: Overall architecture of our As-ViT. *Blue italics* indicates topology configurations to be searched (Table 1). Red indicates depth/width to be scaled-up.

Elastic kernels. Instead of generating non-overlapped image patches, we propose to search for the kernel size. This will enable patches to be overlapped with their neighbors, introducing more spatial correlations among tokens. Moreover, each time we downsample the spatial resolution, we also introduce overlaps when re-embedding local tokens (implemented by either a linear or a convolutional layer).

Elastic attention splits. Splitting the attention into local windows is an important design to reduce the computation cost of self-attention without sacrificing much performance (Zaheer et al., 2020; Liu et al., 2021). Instead of using a fixed number of splits, we propose to search for elastic attention splits for each stage[2]. Note that we try to make our design general and do not use shifted windows (Liu et al., 2021).

More search dimensions. ViT (Dosovitskiy et al., 2020) by default leveraged an FFN layer with $4\times$ expanded hidden dimension for each attention block. To enable a more flexible design of ViT architectures, for each stage we further search over the FFN expansion ratio. We also search for the final number of heads for the self-attention module.

Table 1: Topology Search Space for our As-ViT.

Stage	Sub-space	Choices
#1	Kernel K_1	4, 5, 6, 7, 8
	Attention Splits S_1	2, 4, 8
	FFN Expansion E_1	2, 3, 4, 5, 6
#2	Kernel K_2	2, 3, 4
	Attention Splits S_2	1, 2, 4
	FFN Expansion E_2	2, 3, 4, 5, 6
#3	Kernel K_3	2, 3, 4
	Attention Splits S_3	1, 2
	FFN Expansion E_3	2, 3, 4, 5, 6
#4	Kernel K_4	2, 3, 4
	FFN Expansion E_4	2, 3, 4, 5, 6
-	Num. Heads	16, 32, 64

____
[2]Due to spacial reduction, the 4^{th} stage may already reach a resolution at 7×7 on ImageNet, and we set its splitting as 1.

3.2 ASSESSING THE COMPLEXITY OF VITS AT INITIALIZATION: A MANIFOLD PROPAGATION PERSPECTIVE

Training ViT is slow: hence an architecture search guided by evaluating trained models' accuracies will be dauntingly expensive, if at all feasible. There is a recent surge of training-free neural architecture search methods for ReLU-based CNNs, leveraging local linear maps (Mellor et al., 2020), gradient sensitivity (Abdelfattah et al., 2021), number of linear regions (Chen et al., 2021d), etc. However, ViTs are equipped with more complex non-linear functions: self-attention, softmax, and GeLU. Therefore, we need to measure the learning capacity of ViTs in a more general way.

To estimate how complex functions can be approximated by ViTs, we consider measuring the complexity of manifold propagation through ViT. Intuitively, a complex network can propagate a simple input into a complex manifold at its output layer, thus being more likely in approximating complex functions (i.e. strong learning capacity). In our work, we study the manifold complexity of mapping a simple circle input through the ViT: $\mathbf{h}(\theta) = \sqrt{N}\left[\mathbf{u}^0 \cos(\theta) + \mathbf{u}^1 \sin(\theta)\right]$. Here, N is the dimension of ViT's input (e.g. $N = 3 \times 224 \times 224$ for ImageNet images), $\mathbf{u}^0$ and $\mathbf{u}^1$ form an orthonormal basis for a 2-dimensional subspace of $\mathbb{R}^N$ in which the circle lives. We further define ViT network as $\mathcal{N}$, its input-output Jacobian $\boldsymbol{v}(\theta) = \partial_\theta \mathcal{N}(\mathbf{h}(\theta))$ at the input θ, and $\boldsymbol{a}(\theta) = \partial_\theta \boldsymbol{v}(\theta)$. We will calculate expected complexities over a certain number of θs uniformly sampled from $[0, 2\pi)$. In our work, we study three different types of manifold complexities:

1. Curvature is defined as the reciprocal of the radius of the osculating circle on the ViT's output manifold. Intuitively, a larger curvature indicates that $\mathcal{N}(\theta)$ changes fast at a certain θ. According to Riemannian geometry (Lee, 2006), the curvature can be explicitly calculated as $\kappa = \int (\boldsymbol{v}(\theta) \cdot \boldsymbol{v}(\theta))^{-3/2} \sqrt{(\boldsymbol{v}(\theta) \cdot \boldsymbol{v}(\theta))(\boldsymbol{a}(\theta) \cdot \boldsymbol{a}(\theta)) - (\boldsymbol{v}(\theta) \cdot \boldsymbol{a}(\theta))^2} d\theta$.

2. Length Distortion in Euclidean space is defined as $\mathcal{L}^E = \frac{\text{length}(\mathcal{N}(\theta))}{\text{length}(\theta)} = \int \sqrt{\|\boldsymbol{v}(\theta)\|_2} d\theta$. It measures when the network takes a unit-length curve as input, what is the length of the output curve. Since the ground-truth function we want to estimate (using $\mathcal{N}$) is usually very complex, one may also expect that networks with better performance should also generate longer outputs.

3. The problem of $\mathcal{L}^E$ is that, longer outputs not necessarily translate to complex outputs. A simple example: even an appropriately initialized linear network could grow a straight line into a long output (i.e. a large norm of input-output Jacobian). Therefore, one could instead use **Length Distortion taking curvature into consideration** to measure how quickly the normalized Jacobian $\hat{\mathbf{v}}(\theta) = \mathbf{v}(\theta)/\sqrt{\mathbf{v}(\theta) \cdot \mathbf{v}(\theta)}$ changes with respect to θ, defined as $\mathcal{L}^E_\kappa = \int \sqrt{\|\partial_\theta \hat{\mathbf{v}}(\theta)\|_2} d\theta$.

Figure 2: Correlations between $\kappa, \mathcal{L}^E, \mathcal{L}^E_\kappa$ and trained accuracies of ViT topologies from our search space.

In our study, we aim to compare the potential of using these three complexity metrics to guide the ViT architecture selection. As the core of neural architecture search is to rank the performance of different architectures, we measure the Kendall-tau correlations (τ) between these metrics and models' ground-truth accuracies. We randomly sampled 87 ViT topologies from Table 1 (with $L_1 = L_2 = L_3 = L_4 = 1, C = 32$), fully train them on ImageNet-1k for 300 epochs (following the same training recipe of DeiT (Touvron et al., 2020)), and also measure their

Table 2: Complexity Study. τ: Kendall-tau correlation. Time: per ViT topology on average on 1 V100 GPU.

Complexity	τ	Time
κ	-0.49	38.3s
$\mathcal{L}^E$	0.49	12.8s
$\mathcal{L}^E_\kappa$	-0.01	48.2s

$\kappa, \mathcal{L}^E, \mathcal{L}^E_\kappa$ at initialization. As shown in Figure 2, we can clearly see that both κ and $\mathcal{L}^E$ exhibit high Kendall-tau correlations. κ has a negative correlation, which may indicate that changes of output manifold on the tangent direction are more important to ViT training, instead of on the perpendicular direction. Meanwhile, κ costs too much computation time due to second derivatives. We decide to choose $\mathcal{L}^E$ as our complexity measure for highly fast ViT topology search and scaling.

3.3 $\mathcal{L}^E$ AS REWARD FOR SEARCHING VIT TOPOLOGIES

We now propose our training-free search based on $\mathcal{L}^E$ (Algorithm 1). Most NAS (neural architecture search) methods evaluate the accuracies or loss values of single-path or super networks as proxy inference. This training-based search will suffer from more computation costs when applied to ViTs. Instead of training ViTs, for each architecture we sample, we calculate $\mathcal{L}^E$ and treat it as the reward to guide the search process. In addition to $\mathcal{L}^E$, we also include the NTK condition number $\kappa_\Theta = \frac{\lambda_{\max}}{\lambda_{\min}}$ to indicate the trainability of ViTs (Chen et al., 2021d; Xiao et al., 2019; Yang, 2020; Hron et al., 2020). $\lambda_{\max}$ and $\lambda_{\min}$ are the largest and smallest eigenvalue of NTK matrix Θ.

Algorithm 1: Training-free ViT Topology Search.

---

1 **Input:** RL policy π, step $t = 0$, total steps T.
2 **while** $t < T$ **do**
3   Sample topology $\boldsymbol{a}_t$ from π.
4   Calculate $\mathcal{L}_t^E$ and $\kappa_{\Theta,t}$ for $\boldsymbol{a}_t$.
5   Normalization: $\widehat{\mathcal{L}}_t^E = \frac{\mathcal{L}_t^E - \mathcal{L}_{t-1}^E}{\max_{t'} \mathcal{L}_{t'}^E - \min_{t'} \mathcal{L}_{t'}^E}, \widehat{\kappa}_{\Theta,t} = \frac{\kappa_{\Theta,t} - \kappa_{\Theta,t-1}}{\max_{t'} \kappa_{\Theta,t'} - \min_{t'} \kappa_{\Theta,t'}}, t' = 1, \cdots, t$.
6   Update policy π using reward $r_t = \widehat{\mathcal{L}}_t^E - \widehat{\kappa}_{\Theta,t}$ by policy gradient (Williams, 1992).
7      $t = t + 1$.
8 **return** *Topology $\boldsymbol{a}^*$ of highest probability from π.*

We use reinforcement learning (RL) for search. The RL policy is formulated as a joint categorical distribution, and is updated by policy gradient (Williams, 1992). We update our policy for 500 steps, which is observed enough for the policy to converge (entropy drops from 15.3 to 5.7). The search process is extremely fast: only seven GPU-hours (V100) on ImageNet-1k, thanks to the simple calculation of $\mathcal{L}^E$ that bypasses the ViT training. To address the different magnitude of $\mathcal{L}^E$ and κ_Θ, we normalize them by their relative value ranges (line 5 in Algorithm 1). We summarize the ViT topology statistics from our search in Table 3. We can see that $\mathcal{L}^E$ and κ_Θ highly prefer: (1) tokens with overlaps ($K_1 \sim K_4$ are all larger than strides), and (2) larger FFN expansion ratios in deeper layers ($E_1 < E_2 < E_3 < E_4$). No clear preference of $\mathcal{L}^E$ and κ_Θ are found on attention splits and number of heads.

Table 3: Statistics of topology search. *Standard deviation is normalized by mean due to different value ranges.

Search Space	Mean	Std*
K_1	7.3	0.1
K_2	4	0
K_3	4	0
K_4	4	0
E_1	3.3	0.4
E_2	3.9	0.4
E_3	4.2	0.3
E_4	5.2	0.2
S_1	4	0.6
S_2	2.7	0.5
S_3	1.5	0.3
Head	42.7	0.5

3.4 AUTOMATIC AND PRINCIPLED SCALING OF VITS

After obtaining an optimal topology, another question is: how to balance the network depth and width? Currently, there is no such rule of thumb for ViT scaling. Recent works try to scale up or grow convolutional networks of different sizes to meet various resource constraints (Liu et al., 2019a; Tan & Le, 2019). However, to automatically find a principled scaling rule, training ViTs will cost enormous computation costs. It is also possible to search different ViT variants (as in Section 3.3), but that requires multiple runs. Instead, "scaling-up" is a more natural way to generate multiple model variants in one experiment. We are therefore motivated to scale up our searched basic "seed" ViT to a larger model in an efficient training-free and principled manner.

We depict our auto-scaling method in Algorithm 2. The starting-point architecture has one attention block for each stage, and an initial hidden dimension $C = 32$. In each iteration, we greedily find the optimal depth and width to scale up next. For depth, we try to find out which stage to deepen (i.e., add one attention block to which stage); for width, we try to discover the best expansion ratio (i.e., widen the channel number to what extent). The rule to choose how to scale up is by comparing the propagation complexity among a set of scaling choices. For example, in the case of four backbone stages (Table 1) and four expansion ratio choices ($[0.05\times, 0.1\times, 0.15\times, 0.2\times]$), we have $4 \times 4 = 16$ scaling choices in total for each step. We calculate $\mathcal{L}^E$ and κ_Θ after applying each choice, and the one with the best $\mathcal{L}^E$ / κ_Θ trade-off (minimal sum of rankings by $\mathcal{L}^E$ and κ_Θ) will be selected to scale-up with. The scaling stops when a certain limit of parameter number is reached. In our work, we stop the scaling process once the number of parameters reaches 100 million, and the scaling only takes five GPU hours (V100) on ImageNet-1k.

The scaling trajectory is visualized in Figure 3. By comparing our automated scaling against random scaling, we find our scaling principle prefers to sacrificing the depths to win more widths, keeping a

Figure 3: Scaling-up ViTs. Left: Scaling rules from our As-ViT, random scaling, Swin (Liu et al., 2021), ViT (Zhai et al., 2021), and ResNet (He et al., 2016). "Total Depths": number of blocks ("bottleneck" of ResNet, "attention-block" of ViTs). "Total Widths": sum of output channel numbers from all blocks. Grey areas indicate standard deviations measured with 10 repeated runs with different random seeds. Right: During the auto-scaling, both the network's complexity and trainability are improved (numbers indicate scaling-up steps, $\mathcal{L}^E$ higher the better, κ_Θ lower the better).

shallower but wider network. Our scaling is more similar to the rule developed by Zhai et al. (2021). In contrast, ResNet and Swin Transformer (Liu et al., 2021) choose to be more narrower and deeper.

Algorithm 2: Training-free Auto-scaling ViTs.

1 **Input:** seed As-ViT topology $\boldsymbol{a}_0$, stop criterion (#parameters) P, $t = 0$,
    channel expansion ratio choices $\mathcal{C} = \{1.05\times, 1.1\times, 1.15\times, 1.2\times\}$,
    depth choices $\mathcal{D} = \{(+1, 0, 0, 0), (0, +1, 0, 0), (0, 0, +1, 0), (0, 0, 0, +1)\}$.
2 **while** $|\boldsymbol{a}_t| \leq P$ **do**
3   **for** *each scaling choice* $g_i \in \mathcal{C} \times \mathcal{D}$ **do**
4   Scale-up: $\boldsymbol{a}_{t,i} = \boldsymbol{a}_t \leftarrow g_i$.   ▷ which stage to deepen, to what extent to widen.
5   Calculate $\mathcal{L}_i^E$ and $\kappa_{\Theta,i}$ for $\boldsymbol{a}_{t,i}$.
6   Get ranking of each scaling choice $r_{\mathcal{L},i}$ by descendingly sort $\mathcal{L}_i^E$, $i = 1, \cdots, |\mathcal{C} \times \mathcal{D}|$.
7   Get ranking of each scaling choice $r_{\kappa_\Theta,i}$ by ascendingly sort $\kappa_{\Theta,i}$, $i = 1, \cdots, |\mathcal{C} \times \mathcal{D}|$.
8   Ascendingly sort each scaling choice g_i by $r_{\mathcal{L}^E,i} + r_{\kappa_\Theta,i}$.
9   Select the scaling choice g_i^* with the top (smallest) ranking.
10     $\boldsymbol{a}_{t+1} = \boldsymbol{a}_t \leftarrow g_i^*$.
11     $t = t + 1$.
12 **return** *Growed ViT architectures* $\boldsymbol{a}_1, \boldsymbol{a}_2, \cdots, \boldsymbol{a}_t$.

---

4 EFFICIENT VIT TRAINING VIA PROGRESSIVE ELASTIC RE-TOKENIZATION

Recent works (Fu et al., 2021; Jia et al., 2018; Zhou et al., 2019) show that one can use mixed or progressive precision to achieve an efficient training purpose. The rationale behind this strategy is that, there exist some "short-cuts" on the network's loss landscape that can be manually created to bypass perhaps less important gradient descent steps, especially during early training phases. As in ViT, both self-attention and FFN have quadratic computation costs to the number of tokens. It is therefore natural to ask: do we need full-resolution tokens during the whole training process?

Figure 4: By progressively changing the sampling granularity (stride and dilation) of the first linear project layer, we can reduce the spatial resolutions of tokens and save training FLOPs (37.4% here), while still maintain a competitive final performance (ImageNet-1k 224×224). See Table 6 for more studies.

We provide an affirming answer by proposing a progressive elastic re-tokenization training strategy. To update the number of tokens during training without affecting the shape of weights in linear projections, we adopt different sampling granularities in the first linear projection layer. Taking the first projection kernel $K_1 = 4$ with $\mathrm{stride} = 4$ as an example: during training we gradually change

the $(\mathrm{stride}, \mathrm{dilation})$ pair [3] of the first projection kernel to $(16, 5)$, $(8, 2)$, and $(4, 1)$, keeping the shape of weights and the architecture unchanged.

This re-tokenization strategy stimulates curriculum learning for ViTs: when the training begins, we introduce coarse sampling to significantly reduce the number of tokens. In other words, our As-ViT quickly learns coarse information from images in early training stages at extremely low computation cost (only 13.2% FLOPs of full-resolution training). Towards the late phase of training, we progressively switch to fine-grained sampling, and restore the full token resolution and maintain the competitive accuracy. As shown in Figure 4, when the ViT is trained with coarse sampling in early training phases, it can still obtain high accuracy while requiring extremely low computation cost. The transition between different sampling granularity introduces a jump in performance, and eventually the network restores its competitive final performance.

Table 4: As-ViT topology and scaling rule.

Design	Stage	K	S	E	Head
Seed Topology (*Blue italics* in Fig. 1)	#1	8	2	3	4
	#2	4	1	2	8
	#3	4	1	4	16
	#4	4	1	6	32
Scaling (Red in Fig. 1)	Stage-wise Depth				Width (C)
	L_1	L_2	L_3	L_4	
As-ViT-Small	3	1	4	2	88
As-ViT-Base	3	1	5	2	116
As-ViT-Large	5	2	5	2	180

5 EXPERIMENTS

5.1 AS-VIT: AUTO-SCALING VIT

We show our searched As-ViT topology in Table 4. This architecture facilitates strong overlaps among tokens during both the first projection ("tokenization") step and three re-embedding steps. FFN expansion ratios are first narrow then become wider in deeper layers. A small number of attention splits are leveraged for better aggregation of global information.

The seed topology is automatically scaled-up, and three As-ViT variants of comparable sizes with previous works will be benchmarked. Our scaling rule prefers shallower and wider networks, and layers are more balanced among different resolution stages.

5.2 IMAGE CLASSIFICATION

Settings. We benchmark our As-ViT on ImageNet-1k (Deng et al., 2009). We use Tensorflow and Keras for training implementations and conduct all training on TPUs. We set the default image size as 224×224, and use AdamW (Loshchilov & Hutter, 2017) as the optimizer with cosine learning rate decay (Loshchilov & Hutter, 2016). A batch size of 1024, an initial learning rate of 0.001, and a weight decay of 0.05 are adopted.

Table 5 demonstrates comparisons of our As-ViT to other models. Compared to the previous both Transformer-based and CNN-based architectures, As-ViT achieves state-of-the-art performance with a comparable number of parameters and FLOPs.

Table 5: Image Classification on ImageNet-1k (224×224).

Method	Params.	FLOPs	Top-1
RegNetY-4GF (Radosavovic et al., 2020)	21.0 M	4.0 B	80.0%
ViT-S (Dosovitskiy et al., 2020)	22.1 M	9.2 B	81.2%
DeiT-S (Touvron et al., 2020)	22.0 M	4.6 B	79.8%
T2T-ViT-14 (Yuan et al., 2021b)	21.5 M	6.1 B	81.7%
TNT-S (Han et al., 2021)	23.8 M	5.2 B	81.5%
PVT-Small (Wang et al., 2021)	24.5 M	3.8 B	79.8%
CaiT XS-24 (Touvron et al., 2021)	26.6 M	5.4 B	81.8%
DeepVit-S (Zhou et al., 2021)	27 M	6.2 B	82.3%
ConViT-S (d'Ascoli et al., 2021)	27 M	5.4 B	81.3%
CvT-13 (Wu et al., 2021)	20 M	4.5 B	81.6%
CvT-21 (Wu et al., 2021)	32 M	7.1 B	82.5%
Swin-T (Liu et al., 2021)	29.0 M	4.5 B	81.3%
BossNet-T0 (Li et al., 2021)	-	3.4 B	80.8%
AutoFormer-s (Chen et al., 2021c)	22.9 M	5.1 B	81.7%
GLiT-Small (Chen et al., 2021a)	24.6 M	4.4 B	80.5%
As-ViT Small (ours)	29.0 M	5.3 B	81.2%
RegNetY-8GF (Radosavovic et al., 2020)	39.0 M	8.0 B	81.7%
T2T-ViT-19 (Yuan et al., 2021b)	39.2 M	9.8 B	82.2%
CaiT S-24 (Touvron et al., 2021)	46.9 M	9.4 B	82.7%
ConViT-S+ (d'Ascoli et al., 2021)	48 M	10 B	82.2%
ViT-S/16 (Dosovitskiy et al., 2020)	48.6 M	20.2 B	78.1%
Swin-S (Liu et al., 2021)	50.0 M	8.7 B	83.0%
DeepViT-L (Zhou et al., 2021)	55 M	12.5 B	82.2%
PVT-Medium (Wang et al., 2021)	44.2 M	6.7 B	81.2%
PVT-Large (Wang et al., 2021)	61.4 M	9.8 B	81.7%
T2T-ViT-24 (Yuan et al., 2021b)	64.1 M	15.0 B	82.6%
TNT-B (Han et al., 2021)	65.6 M	14.1 B	82.8%
BossNet-T1 (Li et al., 2021)	-	7.9 B	82.2%
AutoFormer-b (Chen et al., 2021c)	54 M	11 B	82.4%
ViT-ResNAS-t (Liao et al., 2021)	41 M	1.8 B	80.8%
ViT-ResNAS-s (Liao et al., 2021)	65 M	2.8 B	81.4%
As-ViT Base (ours)	52.6 M	8.9 B	82.5%
RegNetY-16GF (Radosavovic et al., 2020)	84.0 M	16.0 B	82.9%
ViT-B/16 (Dosovitskiy et al., 2020) [†]	86.0 M	55.4 B	77.9%
DeiT-B (Touvron et al., 2020)	86.0 M	17.5 B	81.8%
ConViT-B (d'Ascoli et al., 2021)	86 M	17 B	82.4%
Swin-B (Liu et al., 2021)	88.0 M	15.4 B	83.3%
GLiT-Base (Chen et al., 2021a)	96.1 M	17.0 B	82.3%
ViT-ResNAS-m (Liao et al., 2021)	97 M	4.5 B	82.4%
CaiT S-48 (Touvron et al., 2021)	89.5 M	18.6 B	83.5%
As-ViT Large (ours)	88.1 M	22.6 B	83.5%

[†] Under 384×384 resolution.

---

[3] $\mathrm{dilation} = round((\mathrm{stride}/S_1 - 1) * K_1/(K_1 - 1)) + 1$, $S_1 = 4$ is the stride at the full token resolution.

More importantly, our As-ViT framework achieve competitive or strong performance than concurrent NAS works for ViTs with much more search efficiency. As-ViTs are designed with highly reduced human or NAS efforts. All our three As-ViT variants are generated in only 12 GPU hours (on a single V100 GPU). In contrast, BoneNAS (Li et al., 2021) requires 10 GPU days to search a single architecture. For each variant of ViT-ResNAS (Liao et al., 2021), the super-network training takes 16.7∼21 hours, followed by another 5.5∼6 hours of evolutionary search.

Efficient Training. We leverage the progressive elastic re-tokenization strategy proposed in Section 4 to reduce both FLOPs and training time for large ViT models. As illustrated in Figure 4, we progressively apply $4\times$ and $2\times$ reductions on the number of tokens during training by changing both the dilation and the stride of the first linear projection layer. We tune the epochs allocated to each token reduction stage and show the results in Table 6. Standard training takes 42.8 TPU days, whereas our efficient training could save up to 56.2% training FLOPs and 41.1% training TPU days, still achieving a strong accuracy.

Table 6: Efficient training on ImageNet-1k (224×224) via progressive elastic re-tokenization strategy (Section 4).

Token Reduction (Epochs)			FLOPs Saving	Training Time (TPU days)	Top1 Acc.
$4\times$	$2\times$	N/A			
1∼40	41∼70	71∼300	18.7%	36.9	83.1%
1∼80	81∼140	141∼300	37.4%	31.0	82.9%
1∼120	121∼210	211∼300	56.2%	25.2	82.5%
Baseline			100%	42.8	83.5

Decoupled Contributions from Designed Topology and Scaling. To better verify the contribution from our searched topology and scaling rule, we conduct more ablation studies (Table 7). First, we directly train the searched topology before scaling. Our searched seed topology is better than the best from 87 random topologies in Figure 2. Second, we compare our complexity-based scaling rule with "random scaling + As-ViT topology". At different scales, our automated scaling is also better than random scaling.

Table 7: Decoupled Contributions from Designed Topology and Scaling, on ImageNet-1K.

Model	Params.	FLOPs	Top-1
As-ViT Topology	2.4 M	0.5 B	61.7%
Random Topologies	2.2 M	0.4 B	61.4%
As-ViT Small	29.0 M	5.3 B	81.2%
Random (Small)	24.2 M	8.7 B	80.5%
As-ViT Base	52.6 M	8.9 B	82.5%
Random (Base)	42.4 M	15.5 B	82.2%
As-ViT Large	88.1 M	22.6 B	83.5%
Random (Large)	81.1 M	28.7 B	83.2%

5.3 Object Detection on COCO

Settings Beyond image classification, we further evaluate our designed As-ViT on the detection task. Object detection is conducted on COCO 2017 that contains 118,000 training and 5000 validation images. We adopt the popular Cascade Mask R-CNN as the object detection framework for our As-ViT. We use an input size of 1024×1024, AdamW optimizer (initial learning rate of 0.001), weight decay of 0.0001, and a batch size of 256. Efficiently pretrained ImageNet-1K checkpoint (82.9% in Table 6) is leveraged as the initialization.

We compare our As-ViT to standard CNNs (ResNext, SpineNet (Du et al., 2020)) and previous Transformer networks (Swin (Liu et al., 2021)). The comparisons are conducted by changing only the backbones with other settings unchanged. In Table 8 we can see that our As-ViT can also capture multi-scale features and achieve state-of-the-art detection performance, although being designed on ImageNet and its complexity is measured for classification.

Table 8: Two-stage object detection and instance segmentation results. We compare employing different backbones with Cascade Mask R-CNN on single model without test-time augmentation.

Backbone	Resolution	FLOPs	Params.	AP_{val}	AP_{val}^{mask}
ResNeXt-101	480∼800×1333	972 B	140 M	48.3	41.6
Swin-B (Liu et al., 2021)	480∼800×1333	982 B	145 M	51.9	45
SpineNet-190 (Du et al., 2020)	1536×1536	2076.8 B	176.2 M	52.2	46.1
As-ViT Large (ours)	1024×1024	1094.2 B	138.8 M	52.7	45.2

6 RELATED WORKS

6.1 VISION TRANSFORMER

Transformers (Vaswani et al., 2017) leverage the self-attention to extract global correlation, and become the dominant models for natural language processing (NLP) (Devlin et al., 2018; Radford et al., 2018; Brown et al., 2020; Liu et al., 2019b). Recent works explored transformers to vision problems: image classification (Dosovitskiy et al., 2020), object detection (Carion et al., 2020; Zhu et al., 2020; Zheng et al., 2020; Dai et al., 2020; Sun et al., 2020), segmentation (Chen et al., 2020; Wang et al., 2020), etc. The Vision Transformer (ViT) (Dosovitskiy et al., 2020) designed a pure transformer architecture and achieved SOTA performance on image classification. However, ViT heavily relies on large-scale datasets (ImageNet-21k (Deng et al., 2009), JFT-300M (Sun et al., 2017)) for pretraining, requiring huge computation resources. DeiT (Touvron et al., 2020) proposed Knowledge Distillation (KD) (Hinton et al., 2015; Yuan et al., 2020) via a special KD token to improve both performance and training efficiency. In contrast, our proposed As-ViT introduces more flexible tokenization, attention splitting, and FFN expansion strategies, with automated discovery.

6.2 NEURAL ARCHITECTURE DESIGN AND SCALE

Manual design of network architectures heavily relies on human prior, which is difficult to scale up. Recent works leverage AutoML to find optimal combinations of operators/topology in a given search space (Zoph & Le, 2016; Real et al., 2019; Liu et al., 2018; Dong & Yang, 2019). However, the searched model are small due to the fixed and hand-crafted search space, far from being scaled-up to modern networks. For example, models from NASNet space (Zoph et al., 2018) only have ∼5M parameters, much smaller than real-world ones (20 to over 100M). One main reason for not being scalable is because NAS is a computation-consuming task, typically costing 1∼2 GPU days to search even small architectures. Meanwhile, many works try to grow a "seed" architecture to different variants. EfficientNet (Tan & Le, 2019) manually designed a scaling rule for width and depth. Give a template backbone with fixed depth, Liu et al. (2019a) grow the width by gradient descent. For ViT, we for the first time bring both architecture design and scaling together in one framework. To overcome the computation-consuming problem in the training of transformers, we directly use the complexity of manifold propagation as a surrogate measure towards a training-free search and scale.

6.3 EFFICIENT TRAINING

A number of methods have been developed to accelerate the training of deep neural networks, including mixed precision (Jia et al., 2018), distributed optimization (Cho et al., 2017), large-batch training (Goyal et al., 2017; Akiba et al., 2017; You et al., 2018), etc. Jia et al. (2018) combined distributed training with a mixed-precision framework. Wang et al. (2019) proposed to save deep CNN training energy cost via stochastic mini-batch dropping and selective layer update. In our work, a customized progressive tokenization via the changing of stride/dilation can effectively reduce the number of tokens during ViT training, thus largely saves the training cost.

7 CONCLUSIONS

To automate the principled design of vision transformers without tedious human efforts, we propose As-ViT, a unified framework that searches and scale-up ViTs without any training. Compared with hand-crafted ViT architecture, our As-ViT leverages more token overlaps, increased FFN expansion ratios, and is wider and shallower. Ablation studies demonstrate the difference between our scaling rule and manual ones from previous CNN and ViT works, both our searched topology and automated scaling rule outperform random ones. Our As-ViT achieves state-of-the-art accuracies on both ImageNet-1K classification and COCO detection, which verifies the strong performance of our framework. Moreover, with progressive tokenization, we can train heavy ViT models with largely reduced training FLOPs and time. We hope our methodology could encourage the efficient design and training of ViTs for both the transformer and NAS community.

8 ETHICS STATEMENT

The authors are already fully cognizant of the importance of the ethic codes and practices. Our work is conducted with full compliance with research ethics norms, more specifically, the codes and practices established by the ICLR conference.

In this work, we did not and will not engage with any issue of harm, privacy, and data reuse and repurposing. Our work did not and will not involve any human participants.

All data collection leveraged in our work does not involve any personal identifiers. The raw data of each experiment are collated in password-protected computers and can only be accessed by the authors of this work. The data are systematized and stored in password-protected storage drives.

In sum, all stages of our research work strictly follow the ICLR ethics norms.

9 REPRODUCIBILITY STATEMENT

Implementation details can be found in Appendix A. All code for computing $\kappa, \mathcal{L}^E, \mathcal{L}_\kappa^E$, reinforcement learning, automated scaling, ImageNet training/inference, COCO training/inference, will be released upon acceptance, with detailed annotations and guidance of usage. Logs of experiments, including topology design, scaling, training, and complexity measurements, will also be available.

REFERENCES

Mohamed S Abdelfattah, Abhinav Mehrotra, Łukasz Dudziak, and Nicholas D Lane. Zero-cost proxies for lightweight nas. *arXiv preprint arXiv:2101.08134*, 2021.

Takuya Akiba, Shuji Suzuki, and Keisuke Fukuda. Extremely large minibatch sgd: Training resnet-50 on imagenet in 15 minutes. *CoRR*, abs/1711.04325, 2017.

Navaneeth Bodla, Bharat Singh, Rama Chellappa, and Larry S Davis. Soft-nms–improving object detection with one line of code. In *Proceedings of the IEEE international conference on computer vision*, pp. 5561–5569, 2017.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. *arXiv preprint arXiv:2005.12872*, 2020.

Boyu Chen, Peixia Li, Chuming Li, Baopu Li, Lei Bai, Chen Lin, Ming Sun, Wanli Ouyang, et al. Glit: Neural architecture search for global and local image transformer. *arXiv preprint arXiv:2107.02960*, 2021a.

Chun-Fu Chen, Quanfu Fan, and Rameswar Panda. Crossvit: Cross-attention multi-scale vision transformer for image classification. *arXiv preprint arXiv:2103.14899*, 2021b.

Hanting Chen, Yunhe Wang, Tianyu Guo, Chang Xu, Yiping Deng, Zhenhua Liu, Siwei Ma, Chunjing Xu, Chao Xu, and Wen Gao. Pre-trained image processing transformer. *arXiv preprint arXiv:2012.00364*, 2020.

Kai Chen, Jiangmiao Pang, Jiaqi Wang, Yu Xiong, Xiaoxiao Li, Shuyang Sun, Wansen Feng, Ziwei Liu, Jianping Shi, Wanli Ouyang, et al. Hybrid task cascade for instance segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4974–4983, 2019.

Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 801–818, 2018.

Minghao Chen, Houwen Peng, Jianlong Fu, and Haibin Ling. Autoformer: Searching transformers for visual recognition. *arXiv preprint arXiv:2107.00651*, 2021c.

Wuyang Chen, Xinyu Gong, and Zhangyang Wang. Neural architecture search on imagenet in four gpu hours: A theoretically inspired perspective. *arXiv preprint arXiv:2102.11535*, 2021d.

Minsik Cho, Ulrich Finkler, Sameer Kumar, David Kung, Vaibhav Saxena, and Dheeraj Sreedhar. Powerai ddl. *arXiv preprint arXiv:1708.02188*, 2017.

Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 702–703, 2020.

Zhigang Dai, Bolun Cai, Yugeng Lin, and Junying Chen. Up-detr: Unsupervised pre-training for object detection with transformers. *arXiv preprint arXiv:2011.09094*, 2020.

Stéphane d'Ascoli, Hugo Touvron, Matthew Leavitt, Ari Morcos, Giulio Biroli, and Levent Sagun. Convit: Improving vision transformers with soft convolutional inductive biases. *arXiv preprint arXiv:2103.10697*, 2021.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Xuanyi Dong and Yi Yang. Searching for a robust neural architecture in four gpu hours. In *Proceedings of the IEEE Conference on computer vision and pattern recognition*, pp. 1761–1770, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Xianzhi Du, Tsung-Yi Lin, Pengchong Jin, Golnaz Ghiasi, Mingxing Tan, Yin Cui, Quoc V Le, and Xiaodan Song. Spinenet: Learning scale-permuted backbone for recognition and localization. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 11592–11601, 2020.

Yonggan Fu, Han Guo, Meng Li, Xin Yang, Yining Ding, Vikas Chandra, and Yingyan Lin. Cpt: Efficient deep neural network training via cyclic precision. *arXiv preprint arXiv:2101.09868*, 2021.

Priya Goyal, Piotr Dollár, Ross Girshick, Pieter Noordhuis, Lukasz Wesolowski, Aapo Kyrola, Andrew Tulloch, Yangqing Jia, and Kaiming He. Accurate, large minibatch sgd: Training imagenet in 1 hour. *arXiv preprint arXiv:1706.02677*, 2017.

Kai Han, An Xiao, Enhua Wu, Jianyuan Guo, Chunjing Xu, and Yunhe Wang. Transformer in transformer. *arXiv preprint arXiv:2103.00112*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Jiri Hron, Yasaman Bahri, Jascha Sohl-Dickstein, and Roman Novak. Infinite attention: Nngp and ntk for deep attention networks. In *International Conference on Machine Learning*, pp. 4376–4386. PMLR, 2020.

Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European conference on computer vision*, pp. 646–661. Springer, 2016.

Xianyan Jia, Shutao Song, Wei He, Yangzihao Wang, Haidong Rong, Feihu Zhou, Liqiang Xie, Zhenyu Guo, Yuanzhou Yang, Liwei Yu, et al. Highly scalable deep learning training system with mixed-precision: Training imagenet in four minutes. *arXiv preprint arXiv:1807.11205*, 2018.

John M Lee. *Riemannian manifolds: an introduction to curvature*, volume 176. Springer Science & Business Media, 2006.

Changlin Li, Tao Tang, Guangrun Wang, Jiefeng Peng, Bing Wang, Xiaodan Liang, and Xiaojun Chang. Bossnas: Exploring hybrid cnn-transformers with block-wisely self-supervised neural architecture search. *arXiv preprint arXiv:2103.12424*, 2021.

Yi-Lun Liao, Sertac Karaman, and Vivienne Sze. Searching for efficient multi-stage vision transformers. *arXiv preprint arXiv:2109.00642*, 2021.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. Darts: Differentiable architecture search. *arXiv preprint arXiv:1806.09055*, 2018.

Qiang Liu, Lemeng Wu, and Dilin Wang. Splitting steepest descent for growing neural architectures. *arXiv preprint arXiv:1910.02366*, 2019a.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019b.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *arXiv preprint arXiv:2103.14030*, 2021.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Joseph Mellor, Jack Turner, Amos Storkey, and Elliot J Crowley. Neural architecture search without training. *arXiv preprint arXiv:2006.04647*, 2020.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training, 2018.

Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10428–10436, 2020.

Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do vision transformers see like convolutional neural networks? *arXiv preprint arXiv:2108.08810*, 2021.

Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized evolution for image classifier architecture search. In *Proceedings of the aaai conference on artificial intelligence*, volume 33, pp. 4780–4789, 2019.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Chen Sun, Abhinav Shrivastava, Saurabh Singh, and Abhinav Gupta. Revisiting unreasonable effectiveness of data in deep learning era. In *Proceedings of the IEEE international conference on computer vision*, pp. 843–852, 2017.

Zhiqing Sun, Shengcao Cao, Yiming Yang, and Kris Kitani. Rethinking transformer-based set prediction for object detection. *arXiv preprint arXiv:2011.10881*, 2020.

Mingxing Tan and Quoc V Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *arXiv preprint arXiv:1905.11946*, 2019.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. *arXiv preprint arXiv:2012.12877*, 2020.

Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. *arXiv preprint arXiv:2103.17239*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30:5998–6008, 2017.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. *arXiv preprint arXiv:2102.12122*, 2021.

Yue Wang, Ziyu Jiang, Xiaohan Chen, Pengfei Xu, Yang Zhao, Yingyan Lin, and Zhangyang Wang. E2-train: Training state-of-the-art cnns with over 80% energy savings. *arXiv preprint arXiv:1910.13349*, 2019.

Yuqing Wang, Zhaoliang Xu, Xinlong Wang, Chunhua Shen, Baoshan Cheng, Hao Shen, and Huaxia Xia. End-to-end video instance segmentation with transformers. *arXiv preprint arXiv:2011.14503*, 2020.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Haiping Wu, Bin Xiao, Noel Codella, Mengchen Liu, Xiyang Dai, Lu Yuan, and Lei Zhang. Cvt: Introducing convolutions to vision transformers. *arXiv preprint arXiv:2103.15808*, 2021.

Lechao Xiao, Jeffrey Pennington, and Samuel S Schoenholz. Disentangling trainability and generalization in deep learning. *arXiv preprint arXiv:1912.13053*, 2019.

Greg Yang. Tensor programs ii: Neural tangent kernel for any architecture. *arXiv preprint arXiv:2006.14548*, 2020.

Yang You, Zhao Zhang, Cho-Jui Hsieh, James Demmel, and Kurt Keutzer. Imagenet training in minutes. *Proceedings of the 47th International Conference on Parallel Processing - ICPP 2018*, 2018. doi: 10.1145/3225058.3225069. URL http://dx.doi.org/10.1145/3225058.3225069.

Kun Yuan, Shaopeng Guo, Ziwei Liu, Aojun Zhou, Fengwei Yu, and Wei Wu. Incorporating convolution designs into visual transformers. *arXiv preprint arXiv:2103.11816*, 2021a.

Li Yuan, Francis EH Tay, Guilin Li, Tao Wang, and Jiashi Feng. Revisiting knowledge distillation via label smoothing regularization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3903–3911, 2020.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Francis EH Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. *arXiv preprint arXiv:2101.11986*, 2021b.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6023–6032, 2019.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. Big bird: Transformers for longer sequences. In *NeurIPS*, 2020.

Xiaohua Zhai, Alexander Kolesnikov, Neil Houlsby, and Lucas Beyer. Scaling vision transformers. *arXiv preprint arXiv:2106.04560*, 2021.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

Pengchuan Zhang, Xiyang Dai, Jianwei Yang, Bin Xiao, Lu Yuan, Lei Zhang, and Jianfeng Gao. Multi-scale vision longformer: A new vision transformer for high-resolution image encoding. *arXiv preprint arXiv:2103.15358*, 2021.

Minghang Zheng, Peng Gao, Xiaogang Wang, Hongsheng Li, and Hao Dong. End-to-end object detection with adaptive clustering transformer. *arXiv preprint arXiv:2011.09315*, 2020.

Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.

Zhengguang Zhou, Wengang Zhou, Xutao Lv, Xuan Huang, Xiaoyu Wang, and Houqiang Li. Progressive learning of low-precision networks. *arXiv preprint arXiv:1905.11781*, 2019.

Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. *arXiv preprint arXiv:2010.04159*, 2020.

Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. *arXiv preprint arXiv:1611.01578*, 2016.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8697–8710, 2018.

A   IMPLEMENTATIONS

Training-free Topology Search and Scaling.   We calculate $\mathcal{L}^E$ by uniformly sampling 10 θs in $[0, 2\pi)$. For one architecture, the calculation of $\mathcal{L}^E$ is repeated five times with different (random) network initializations, and $\mathcal{L}^E$ is set as their mean.

Image Classification.   We use 20 epochs of linear warm-up, a batch size of 1,024, an initial learning rate of 0.001, and a weight decay of 0.05. Augmentations including stochastic depth (Huang et al., 2016), Mixup (Zhang et al., 2017), Cutmix (Yun et al., 2019), RandAug (Cubuk et al., 2020), Exponential Moving Average (EMA) are also applied.

Object Detection.   Our training adopts a batch size of 256 for 36 epochs, with also stochastic depth. We do not use any stronger techniques like HTC (Chen et al., 2019), multi-scale testing, sotf-NMS (Bodla et al., 2017), etc.

B   CONVERGENCE OF TRAINING-FREE SEARCH

To demonstrate the convergence of the policy learned by our RL search, we show the entropy during learning the policy in Figure 5. We can see that a training of 500 steps is enough for the policy to converge to low entropy (high confidence).

Figure 5: Entropy of policy during our training free search (Section 3.3).