Can MLLMs Perceive and Describe Medical Image Quality Beyond Scores?

Abstract

Medical Image Quality Assessment (IQA) serves as a critical safety gate for clinical AI, yet existing approaches rely on scalar metrics that fail to capture the descriptive, expert-like evaluation process central to clinical practice. We introduce **MedQ-Bench**, a comprehensive benchmark for language-based medical IQA evaluation with MLLMs, establishing a *perception–description* paradigm across 5 imaging modalities and over 40 quality attributes. The benchmark comprises two complementary tasks: *MedQ-Perception* probes low-level visual attribute discrimination via 2,600 expert-annotated perceptual queries; *MedQ-Description* covers both no-reference and comparison description sub-tasks with 708 expert-annotated samples, evaluated through a four-dimensional judging protocol. Comprehensive evaluation of 23 state-of-the-art MLLMs reveals that current models exhibit only preliminary and unstable capabilities, and highlights the urgent need for targeted optimization of MLLMs in medical IQA. Project & Dataset: https://anonymous.4open.science/r/MedQ-Bench-EMNLP-code

1 Introduction

Medical Image Quality Assessment (IQA) examines whether medical images satisfy basic quality requirements for reliable downstream analysis and interpretation (Tejani et al., 2024). In practice, degradations in low-level attributes such as contrast, noise, and artifacts affect image readability and result stability (Liu et al., 2026).

Current medical IQA approaches predominantly produce scalar scores using (1) no-reference methods (Xun et al., 2025; Herath et al., 2025), which infer perceptual quality of an image through statistical feature extraction without a reference, and (2) full-reference similarity metrics such as PSNR, SSIM (Wang et al., 2004), and LPIPS (Zhang et al.,

Figure 1: Comparison of Description-IQA with score-based IQA paradigm. Unlike purely numerical scores, Description-IQA identifies distortion types and their relative impact, yielding results more consistent with Human-IQA.

2018). These methods provide standardized evaluation metrics and enable automated IQA. However, they exhibit the following fundamental deficiencies. (1) *Poor generalization* (Herath et al., 2025). Medical image quality is influenced by complex and heterogeneous factors, including modality-specific degradations across magnetic resonance imaging (MRI), computed tomography (CT), fundus photography (Fundus), histopathology, and endoscopy. Yet, existing methods typically rely on simple regression models (Su et al., 2023) or handcrafted statistical indices (Dohmen et al., 2024), which generalize poorly to unseen distortions, new modalities, or different imaging protocols. (2) *Lack of human-like description process for result interpretation*. Most methods produce scalar IQA scores, which do not fully reflect the causes of image quality degradation and may be unreasonable in certain cases. As illustrated in Figure 1, clinicians identify specific degradations and assess their clinical

Figure 2: **MedQ-Bench** overview. (1) Comprehensive coverage: 3,308 samples across 5 modalities with 40+ degradation types. (2) Multi-faceted evaluation: perception-description paradigm.

impact before making quality judgments. Traditional score-based metrics may contradict human judgment by favoring superficially smoother images. Such description requires understanding the quality factors, which current paradigm approaches cannot effectively capture.

Recent advances in multimodal large language models (MLLMs) have shown promising capabilities in medical visual description tasks (Liu et al., 2023a; Dai et al., 2023; Sellergren et al., 2025; Su et al., 2025). Theoretically, MLLMs could potentially address existing IQA challenges by decomposing quality assessment into interconnected subtasks: degradation identification, severity quantification, impact analysis, and comparative description. Unlike traditional approaches that yield scores, MLLM-based assessment can provide explicit chains of thought (Wu et al., 2023; You et al., 2024), offering interpretable and clinically meaningful evaluations. However, critical questions remain unanswered about MLLMs' actual capabilities in medical IQA: Can they truly generalize to the fine-grained, diverse, and complex quality factors spanning different imaging modalities? Do they possess genuine description abilities to understand the clinical significance of various degradations? Existing MLLM evaluation frameworks focus mainly on natural images (Wu et al., 2024a) or high-level medical semantics (Ye et al., 2024), lacking systematic benchmarks that assess quality-related perceptual and description skills across diverse medical modalities. This absence of specialized benchmarks has been a major barrier to

developing and validating effective frameworks.

To bridge the gap between existing medical IQA methods, we propose a novel *perception–description paradigm*. This paradigm mirrors clinicians' cognitive workflow: first perceiving quality-related attributes in images, assessing their severity, and evaluating their potential impact on clinical diagnosis, and then making overall quality judgments through logical description. Building on this paradigm, we introduce **MedQ-Bench**, the first comprehensive benchmark that systematically evaluates the medical IQA capabilities of MLLMs (Figure 2). Our primary contributions are as follows:

- **MedQ-Bench** proposes a comprehensive methodology to assess MLLMs' perceptual and description abilities on medical images, supporting both no-reference and full-reference paradigms across various discrimination tasks.

- Covering 5 imaging modalities and 40+ quality attributes, the dataset includes real, degraded, and AI-generated images across a wide range of clinical and controlled scenarios.

- We introduce a four-axis scoring protocol for description evaluation and validate its reliability through comparison with radiologist assessments.

- Evaluation of both general-purpose and specialized MLLMs reveals significant gaps in Medical IQA, highlighting the need for improvements.

Figure 3: Examples of question types in MedQ-Bench, covering MCQA perception tasks, open-ended description, and pair comparison.

2 Constructing the MedQ-Bench

This section presents MedQ-Bench construction and task design: one MCQA perception task and two description tasks, as illustrated in Figure 3.

2.1 Benchmark Scope and Modalities

Image quality is a fundamental factor in medical imaging analysis, yet existing evaluation methods still rely primarily on score-based metrics and do not fully characterize quality perception and description capabilities. MedQ-Bench is specifically designed to systematically evaluate the visual quality perception and description capabilities of multimodal large language models (MLLMs) within the medical imaging domain. Let $\mathcal{M} = \{M_1, M_2, \ldots, M_m\}$ represent the set of medical imaging modalities, where each modality M_i is associated with a distinct set of quality attributes $\mathcal{A}_i = \{a_{i,1}, a_{i,2}, \ldots, a_{i,k}\}$. The quality assessment task can be formulated as learning a mapping function $f : \mathcal{I} \times \mathcal{Q} \to \mathcal{R}$ that takes an image $I \in \mathcal{I}$ and question $q \in \mathcal{Q}$ as input and produces a response $r \in \mathcal{R}$.

To capture the diversity and complexity of real-world clinical imaging, MedQ-Bench encompasses five representative modalities: Magnetic Resonance Imaging (MRI), Computed Tomography (CT), endoscopy, histopathology imaging, and fundus photography. Let $\mathcal{D}_i = \{d_{i,1}, d_{i,2}, \ldots, d_{i,n}\}$ denote the set of degradation types specific to modality M_i. Each modality exhibits distinct degradation characteristics due to its physical acquisition principles, where degradations can be modeled as transformations $T_d : \mathcal{I} \to \mathcal{I}'$ that modify the original image I based on degradation type $d \in \mathcal{D}_i$. For instance, MRI is particularly susceptible to motion and magnetic susceptibility artifacts, and CT is prone to low-dose noise and metal-induced streak artifacts. This multi-modality design ensures that the benchmark reflects the broad spectrum of perceptual challenges encountered in practice.

For each modality, MedQ-Bench incorporates images from three complementary sources: authentic clinical images containing naturally occurring artifacts; synthetically degraded images that replicate modality-specific distortions in a controlled manner; and AI-generated or reconstructed images produced by enhancement, translation, or reconstruction models, which may introduce hallucinations or subtle structural inconsistencies. This tri-source strategy enables the benchmark to cover both naturally occurring degradations and algorithm-induced artifacts, ensuring a balanced evaluation of MLLM robustness across real-world and algorithmic distortion scenarios.

2.2 Benchmark on IQA Perception Ability

Before evaluating sophisticated description capabilities, it is essential to establish whether MLLMs possess fundamental perceptual abilities to recog-

nize basic quality attributes.

2.2.1 Question Types

The perception-focused MCQA setting evaluates direct visual perception using single-image prompts, without requiring domain-specific diagnostic description. These tasks represent the most basic level of quality assessment capability, asking models to simply identify "what they see" rather than explain "why they see it." For each image, three canonical subtypes of questions are included: *(1) Yes-or-No*: Binary classification tasks where $\mathcal{R}_{\text{YN}} = \{0, 1\}$ and the model predicts $\hat{y} = \arg\max_{y \in \{0,1\}} P(y \mid I, q)$. Examples include "Is this image clear?" or "Does this image contain artifacts?" *(2) What*: Multi-class identification tasks where $\mathcal{R}_{\text{What}} = \{c_1, c_2, \ldots, c_K\}$ represents K possible degradation types, and the model selects $\hat{c} = \arg\max_{c \in \mathcal{R}_{\text{What}}} P(c \mid I, q)$. These tasks ask models to identify specific types of artifacts or degradations present in the image. *(3) How*: Severity assessment tasks where $\mathcal{R}_{\text{How}} = \{s_1, s_2, \ldots, s_L\}$ represents L severity levels, and the model predicts $\hat{s} = \arg\max_{s \in \mathcal{R}_{\text{How}}} P(s \mid I, q)$. These tasks evaluate the model's ability to assess the degree or intensity of observed quality issues.

2.2.2 Quadrants for Low-Level Visual Concerns

Axis 1: No Degradation vs Degradation Severity Levels. The primary axis differentiates medical images based on their quality degradation status: 1) *No Degradation* refers to medical images that maintain optimal quality standards without artifacts or distortions, and 2) degradation with Severity Levels encompasses images with varying degrees of quality issues, further subdivided into *mild Degradation* and *severe Degradation*.

Axis 2: General Medical Questions vs Modality-specific Questions. Quality perception in medical imaging intertwines with modality-specific technical characteristics. For instance, motion artifacts manifest differently in MRI versus CT scans. We curate *modality-specific questions* that require understanding unique technical characteristics of specific imaging modalities (e.g., "Does this MRI show susceptibility artifacts?"), while *general medical questions* focus on universal quality concepts applicable across modalities (e.g., "Is this image clear?"). This distinction evaluates both fundamental quality perception and specialized modality knowledge.

2.3 Benchmark on IQA Description Ability

2.3.1 No-reference Description Tasks

Building on MCQA ability evaluation, we further construct description tasks to assess whether a model can autonomously describe and explain quality-related observations in natural language. These tasks require generating comprehensive responses $w_{1:T} = \{w_1, w_2, \ldots, w_T\}$ that systematically detail multiple aspects of image quality assessment: *(1)* modality and anatomical region identification; *(2)* specific quality degradation characterization including type and severity; *(3)* technical attribution of underlying causes; *(4)* assessment of diagnostic impact and clinical implications; and *(5)* definitive quality judgment with good/usable/reject recommendation. The description tasks evaluate whether models can perform structured quality analysis that mirrors expert clinical assessment, moving beyond simple classification to demonstrate understanding of the relationship between technical image properties and degradation mechanisms.

2.3.2 Comparison Description Tasks

Many clinical workflows require comparative quality assessment between two versions of the same study, such as "original vs. reconstructed" or outputs from competing reconstruction algorithms. For image pairs (I_A, I_B), the comparative task seeks to determine preference $P(I_A \succ I_B)$ based on overall quality assessment. Models must identify which image exhibits higher diagnostic quality and provide detailed explanations for their judgment, such as explaining why one reconstruction algorithm preserves anatomical detail better than another.

Comparative tasks are further categorized by the perceptual gap between images. *1) Coarse-grained* comparisons involve clearly visible quality differences, making them straightforward for both humans and models. *2) Fine-grained* comparisons involve subtle differences in noise patterns, contrast, or structure fidelity, requiring sensitivity to nuanced quality cues that may only be apparent upon careful inspection. This design enables separate evaluation of basic discrimination ability and advanced perceptual subtlety that approaches expert-level assessment sensitivity

2.3.3 Evaluation Metrics

Multi-dimensional judging protocol Description tasks are open-ended and inherently subjective,

Sub-categories	Perception				Description				
Model (variant)	Yes-or-No↑	What↑	How↑	Overall↑	Comp.↑	Prec.↑	Cons.↑	Qual.↑	Overall↑
random guess	50.00%	28.48%	33.30%	37.94%					
Non-experts	67.50%	57.50%	57.50%	62.50%	-	-	-	-	-
Human experts	88.50%	77.50%	77.50%	82.50%	1.524	1.483	1.887	1.623	6.502
Open-Source General Models									
Qwen2.5-VL-Instruct (7B)	57.89%	48.45%	54.40%	54.71%	0.715	0.670	1.855	1.127	4.367
Qwen2.5-VL-Instruct (32B)	67.38%	43.02%	58.69%	59.31%	1.077	0.928	**1.977**	1.290	5.272
InternVL3 (8B)	72.04%	47.67%	52.97%	60.08%	0.928	0.878	1.858	1.317	4.983
InternVL3 (38B)	69.71%	57.36%	52.97%	61.00%	0.964	0.824	1.860	1.317	4.965
Qwen3-VL-235B	55.44%	67.82%	66.27%	62.45%	0.946	0.720	1.629	1.471	4.765
Qwen2.5-VL-Instruct (72B)	78.67%	42.25%	56.44%	63.14%	0.905	0.860	1.896	1.321	4.982
Qwen3.5 (397B)	65.78%	67.17%	65.46%	66.67%	0.923	0.733	1.396	1.466	4.518
Quality-Oriented Models									
Q-Instruct	78.32%	36.43%	46.22%	58.01%	0.398	0.330	1.498	1.167	3.394
Q-Insight	65.05%	45.74%	61.35%	59.85%	0.597	0.502	0.340	0.977	2.416
VisualQuality-R1	61.65%	46.12%	55.01%	56.09%	0.747	0.665	1.783	1.172	4.367
Medical-Specialized Models									
BiMediX2 (8B)	44.98%	27.52%	27.81%	35.10%	0.376	0.394	0.281	0.670	1.721
Lingshu (32B)	50.36%	50.39%	51.74%	50.88%	0.624	0.697	1.932	1.059	4.312
MedGemma (27B)	67.03%	48.06%	50.72%	57.16%	0.742	0.471	1.579	1.262	4.054
Commercial MLLMs									
Mistral-Medium-3	65.95%	48.84%	52.97%	57.70%	0.923	0.729	1.566	1.339	4.557
Claude-4-Sonnet	71.51%	46.51%	54.60%	60.23%	0.742	0.633	1.778	1.376	4.529
Gemini-2.5-Pro	75.13%	55.02%	50.54%	61.88%	0.878	0.891	1.688	**1.561**	5.018
Claude-Sonnet-4.6	66.67%	59.83%	58.63%	62.99%	1.109	0.873	1.498	1.489	4.968
Gemini-3.1-Pro	66.13%	58.32%	64.26%	63.07%	0.765	0.760	1.647	1.557	4.729
Grok-4	73.30%	48.84%	**59.10%**	63.14%	0.982	0.846	1.801	1.389	5.017
Kimi-K2.5	64.35%	64.36%	63.05%	64.06%	0.846	0.615	1.312	1.348	4.122
GPT-4o	78.48%	49.64%	57.32%	64.79%	1.009	1.027	1.878	1.407	5.321
GPT-5.4	64.35%	68.03%	67.87%	66.59%	0.977	0.783	1.620	1.453	4.833
GPT-5	**82.26%**	**60.47%**	58.28%	**68.97%**	**1.195**	**1.118**	1.837	1.529	**5.679**

Table 1: Performance of different models on the MCQA perception and description tasks.

so we use an LLM-based automatic judging protocol. Following prior LLM-as-a-judge practice (Liu et al., 2023b), we adopt GPT-4o as the judge model. Under a unified prompt and rubric, each response is scored on four dimensions with a three-level scale (0, 1, 2): **(1) Completeness**, whether the response covers key low-level visual information in the reference answer; **(2) Preciseness**, whether the response is consistent with the reference answer without clear factual or semantic contradictions; **(3) Consistency**, whether the description reasoning is logically aligned with the final quality conclusion; and **(4) Quality Accuracy**, whether the final quality conclusion matches the reference answer, or correctly identifies the higher-quality image in comparison tasks. The four dimension scores are aggregated as the overall result. To ensure reliability, we further validate human-judge alignment, with details reported in Section D.4.

2.4 Dataset Construction and Annotation

Medical imaging experts designed structured seed templates defining the semantic intent and question structure for each question type. These seeds were expanded using GPT-4o as a template instantiation tool under strict semantic constraints, with

each generated question reviewed by three independent experts to eliminate model-specific linguistic biases. All question-answer pairs underwent multi-round expert validation: *(1)* independent annotation by three specialists following standardized protocols and modality-specific checklists; *(2)* cross-validation sessions where annotators identified divergent cases and conducted structured discussions; and *(3)* consensus resolution with majority voting for conflicts. Complete details are provided in Appendix A.

3 Results

To investigate MLLMs' image quality perception ability, we present a comprehensive evaluation of MedQ-Bench across 23 up-to-date models under zero-shot settings. We evaluate these models across four categories: open-source MLLMs (Qwen2.5-VL-Instruct variants (Wang et al., 2024), InternVL3 models (Chen et al., 2024), and Qwen3-family models), quality-oriented models (Q-Instruct (Wu et al., 2024a), Q-Insight (Li et al., 2026), and VisualQuality-R1 (Wu et al., 2026)), medical-specialized MLLMs (BiMediX2 (Mullappilly et al., 2024), Lingshu (Xu et al., 2025b),

a) Different degradation level

b) General vs modality-specific

Figure 4: Performance analysis of MLLMs across different evaluation dimensions. (a) Different degradation level performance . (b) General vs modality-specific question.

MedGemma (Sellergren et al., 2025)), and general-purpose commercial systems (GPT-5 and GPT-5.4 (OpenAI, 2025), GPT-4o (Achiam et al., 2023), Gemini-2.5-Pro and Gemini-3.1-Pro (Comanici et al., 2025), Grok-4, Claude-4-Sonnet and Claude-Sonnet-4.6 (Anthropic, 2025), Mistral-Medium-3 (Jiang et al., 2023), and Kimi-K2.5 (Team et al., 2026)).

3.1 Findings on Perception

Conclusion 1. Clear performance hierarchy emerges across model categories: Our analysis reveals that most MLLMs perform above random guessing across all sub-tasks, indicating promising potential for domain generalization. The results demonstrate a clear performance hierarchy: closed-source frontier models achieve the highest scores, with GPT-5 leading at 68.97%. Among open-source models, Qwen3.5 (397B) achieves the best performance, outperforming most commercial models, while *the medical models and quality-oriented models underperform expectations*. More details are in Section D.1.

Insufficiency 1. Substantial human-AI performance gap remains: Another key finding emerges from our comparison with human performance, where we include both **human experts** (medical imaging technicians and medical imaging PhDs) and **non-experts** as reference points. The best AI model (GPT-5) significantly underperforms human experts, yet outperforms non-experts by 6.47%.

Given that these models have not undergone specialized training for medical image quality assessment, this suggests substantial potential for improvement in these MLLMs through further fine-tuning.

Insufficiency 2. The MLLMs are not robust among different perceptual types: Task-specific analysis reveals distinct patterns across different evaluation dimensions. Performance analysis across different degradation levels (Figure 4 (a)) demonstrates that mild degradation represents the most challenging scenario, with average accuracy dropping to 56% compared to 72% for no degradation and 67% for severe degradation. This indicates that subtle quality issues are harder to identify than obvious artifacts. Top-performing models like GPT-5 demonstrate a degree of consistency in performance across degradation levels. We further investigate the difference between general and modality-specific medical questions. As shown in Figure 4(b), most models perform better on general questions than on modality-specific tasks, whereas GPT-5 demonstrates the most balanced performance across question types. This suggests that robust medical image quality assessment requires understanding of modality-specific visual features.

3.2 Findings on No-reference Description

Conclusion 2. Limited low-level visual description capabilities across all models: For no-reference description capabilities (Table 1), GPT-

5 still demonstrates the best performance, particularly excelling in the relevance dimension. However, even the most advanced MLLMs fail to achieve excellent scores in completeness and preciseness, with the highest scores being only 1.293/2.0 for completeness and 1.556/2.0 for preciseness. In general, most models only reach an acceptable baseline level. Current MLLM models possess relatively limited and elementary low-level visual description abilities, struggling to provide complete and accurate descriptions of low-level visual information. The consistently high consistency scores indicate that most MLLMs can follow abstract instructions reasonably well, suggesting that the main bottleneck for improving MLLM descriptive capabilities lies in the perception of low-level attributes rather than instruction following.

3.3 Findings on Comparison Description

Insufficiency 3. Paired comparison reveals fundamental limitations in fine-grained analysis: Paired image comparison tasks pose the greatest challenge to current multimodal large language models (MLLMs), requiring models to perform fine-grained quality comparisons between similar images that may only differ by varying degrees. We evaluate model performance across two difficulty levels: fine-grained differences and coarse-grained differences. Figure 5 presents detailed performance analysis across different difficulty levels, with more complete tabular results available in Table 9 in the appendix. Overall, most models perform better under coarse-grained differences, while a few models, such as Grok-4 and Qwen2.5-VL-7B/32B, perform better under fine-grained differences but lose performance on coarse-grained tasks. Among them, GPT-5 achieved the highest overall score, while medical-specialized models such as BiMediX2 showed notably insufficient performance.

3.4 Human–AI Alignment Validation

To validate the reliability of our automated LLM evaluation framework, we conducted a rigorous human-AI alignment study in which 200 randomly sampled cases were independently assessed by three medical imaging specialists under a double-blind protocol. Confusion matrix analysis demonstrated strong agreement across all scoring dimensions, with accuracy rates of 83.3% for completeness, 87.0% for preciseness, and 90.5% for consistency, and quadratic weighted Cohen's κ_w values

Model	Comp.↑	Prec.↑	Cons.↑	Qual.↑	Overall↑
Human experts	1.653	1.682	1.963	1.714	7.003
Open-Source General Models					
Qwen2.5-VL-7B	0.714	0.902	1.316	1.143	4.075
Qwen2.5-VL-32B	0.692	0.752	1.895	0.962	4.301
Qwen2.5-VL-72B	0.737	0.977	1.233	1.113	4.060
InternVL3-8B	0.985	1.278	1.797	1.474	5.534
InternVL3-38B	1.075	1.083	1.571	1.414	5.143
Qwen3-VL-235B	1.023	1.331	1.790	1.489	5.632
Qwen3.5-397B	1.038	1.414	1.880	1.684	6.015
Quality-Oriented Models					
Q-Instruct	0.481	0.541	1.564	0.526	3.113
Q-Insight	0.459	0.602	0.772	0.913	2.745
VisualQuality-R1	0.586	0.662	1.444	0.850	3.541
Medical-Specialized Models					
BiMediX2-8B	0.474	0.549	0.639	0.511	2.173
MedGemma-27B	0.684	0.692	1.128	1.000	3.504
Lingshu-32B	0.729	1.015	1.586	1.323	4.653
Commercial MLLMs					
Mistral-Medium-3	0.872	1.203	1.827	1.338	5.240
Claude-4-Sonnet	0.857	1.083	**1.910**	1.481	5.331
Gemini-2.5-Pro	1.053	1.233	1.774	1.534	5.594
Claude-Sonnet-4.6	1.083	1.316	1.977	1.474	5.850
Gemini-3.1-Pro	0.962	1.376	1.887	1.609	5.835
Grok-4	1.150	1.233	1.820	1.459	5.662
Kimi-K2.5	1.113	1.489	1.993	1.699	6.293
GPT-4o	1.105	1.414	1.632	1.562	5.713
GPT-5.4	1.053	1.293	1.955	1.399	5.699
GPT-5	**1.293**	**1.556**	1.925	**1.564**	**6.338**

Table 2: Detailed comparison description performance scores across four evaluation dimensions for all models.

Figure 5: Visual comparison of overall description performance patterns across model categories.

ranging from 0.774 to 0.985, which confirm that the automated scoring serves as a reliable surrogate for expert judgment. Full detailed are provided in Appendix D.4.

4 Related Work

Medical Multimodal Large Language Models and Benchmarks. Multimodal Large Language Models (MLLMs) have demonstrated remarkable capabilities in understanding and description about visual content through natural language. General-purpose models like LLaVA (Liu et al., 2023a), and Qwen-VL (Wang et al., 2024) have shown strong performance across diverse vision-language tasks. To address healthcare-specific requirements, medical-specialized variants such as (Xu et al.,

2025b; Sellergren et al., 2025; Mullappilly et al., 2024; Su et al., 2025; Xu et al., 2025a) have emerged through domain-targeted pretraining and alignment. Recent medical benchmarks have been developed to evaluate these models systematically, including (Ye et al., 2024), which provides comprehensive multimodal evaluation for general medical AI. However, existing medical benchmarks focus primarily on high-level diagnostic tasks rather than low-level perceptual quality assessment (Wu et al., 2024b).

Score-based Image Quality Assessment. Traditional image quality assessment methods produce numerical scores to quantify image quality, categorized into No-Reference (NR), Full-Reference (FR), and Reduced-Reference approaches. NR methods like BRISQUE (Mittal et al., 2012), NIQE (Zhang et al., 2015), and deep learning approaches including CNNIQA (Kang et al., 2014) and MUSIQ (Ke et al., 2021) assess quality without reference images. FR methods compare against pristine references using metrics like PSNR, SSIM (Wang et al., 2004), VIF (Sheikh and Bovik, 2006), and learned perceptual metrics like LPIPS (Zhang et al., 2018). Recent advances include transformer-based approaches like TReS (Golestaneh et al., 2022) and quality-aware pretraining methods. However, these methods yield only scores, offering limited interpretability regarding specific quality factors, and such technical measures often show weak alignment with human workflows (Koçak et al., 2025; The Evidence-Based Radiology Working Group, 2001).

MLLM-based Image Quality Assessment. Recent advances have introduced multimodal language models for image quality assessment (IQA), which enable more interpretable and description-based evaluation. For example, Q-Instruct (Wu et al., 2023) and DepictQA (You et al., 2024) generate natural language descriptions of quality factors, while Q-Bench (Wu et al., 2024a) offers a systematic framework for evaluating low-level vision tasks. Building on this line, IQAGPT (Chen et al., 2023) integrates vision-language models with ChatGPT for CT image quality assessment, showing the feasibility of producing both quality scores and textual reports. However, its scope is limited to CT images and remains focused on score prediction rather than comprehensive description. Likewise, Ultrasound-QBench (Miao et al., 2025) provides evaluation for ultrasound imaging but restricts tasks to scoring within a single modality.

5 Conclusion

We introduced **MedQ-Bench**, the first benchmark that systematically evaluates medical image quality assessment capabilities of multimodal large language models under a perception and description paradigm. The benchmark covers five imaging modalities and more than forty degradation types, with three task tracks: perception, no-reference description, and paired comparison description. Our zero-shot evaluation of 14 representative models shows clear gaps between current systems and human experts, especially in mild degradation detection and fine-grained comparison. Model outputs also remain limited in completeness and precision for quality description. Notably, several medical-specialized models underperform general-purpose models. Quality-Oriented Models also show limited transfer in this medical setting. Across categories, general-purpose frontier models are currently the most consistent performers, while robustness on modality-specific degradations remains limited for most systems. These findings suggest that improving medical IQA in MLLMs requires joint advances in low-level perception, quality-aware description alignment, and comparison reasoning. Overall, **MedQ-Bench** provides a interpretable evaluation standard for medical IQA and offers a practical basis for improving model reliability in medical image quality control workflows.

Limitations

Several limitations should be considered when interpreting the results of **MedQ-Bench**. Although the benchmark spans five representative medical imaging modalities and more than forty quality attributes, it is not exhaustive. Our evaluation is also conducted under a zero-shot setting, which enables controlled comparison across model categories but does not measure the upper bound achievable through task-specific tuning or domain adaptation for medical IQA. In addition, the description evaluation relies on automated judge. While we validate this protocol against expert assessments rated by three medical imaging specialists, automated judging may still inherit model-specific biases. Finally, **MedQ-Bench** is intended as a research benchmark rather than a clinical decision system.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Anthropic. 2025. System card: Claude opus 4 & claude sonnet 4. Technical report, Anthropic.

Amir Beck and Marc Teboulle. 2009. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM journal on imaging sciences*, 2(1):183–202.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, and 1 others. 2024. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 24185–24198.

Zhihao Chen, Bin Hu, Chuang Niu, Tao Chen, Yuxin Li, Hongming Shan, and Ge Wang. 2023. Iqagpt: Image quality assessment with vision-language and chatgpt models. *arXiv preprint arXiv:2312.15663*.

Jacob Cohen. 1968. Weighted kappa: Nominal scale agreement provision for scaled disagreement or partial credit. *Psychological bulletin*, 70(4):213.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, and 1 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale N Fung, and Steven Hoi. 2023. Instructblip: Towards general-purpose vision-language models with instruction tuning. *Advances in neural information processing systems*, 36:49250–49267.

Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, and 1 others. 2025. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*.

Melanie Dohmen, Tuan Truong, Ivo M Baltruschat, and Matthias Lenga. 2024. Five pitfalls when assessing synthetic medical images with reference metrics. In *MICCAI Workshop on Deep Generative Models*, pages 150–159. Springer.

Huazhu Fu, Boyang Wang, Jianbing Shen, Shanshan Cui, Yanwu Xu, Jiang Liu, and Ling Shao. 2019. Evaluation of retinal image quality assessment networks in different color-spaces. In *International conference on medical image computing and computer-assisted intervention*, pages 48–56. Springer.

Moritz Fuchs, Ssharvien Kumar R Sivakumar, Mirko Schöber, Niklas Woltering, Marie-Lisa Eich, Leonille Schweizer, and Anirban Mukhopadhyay. 2024. Harp: Unsupervised histopathology artifact restoration. In *Medical Imaging with Deep Learning*, pages 465–479. PMLR.

S Alireza Golestaneh, Saba Dadsetan, and Kris M Kitani. 2022. No-reference image quality assessment via transformers, relative ranking, and self-consistency. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 1220–1230.

Matthieu Guerquin-Kern, M Haberlin, Klaas Paul Pruessmann, and Michael Unser. 2011. A fast wavelet-based reconstruction method for magnetic resonance imaging. *IEEE transactions on medical imaging*, 30(9):1649–1660.

Eri Haneda, Nils Peters, Jiayong Zhang, Grigorios Karageorgos, Wenjun Xia, Harald Paganetti, Ge Wang, Yi Guo, Jianhua Ma, Hyoung Suk Park, and 1 others. 2025. Aapm ct metal artifact reduction grand challenge. *Medical physics*, 52(10):e70050.

HMSS Herath, HMKKMB Herath, Nuwan Madusanka, and Byeong-Il Lee. 2025. A systematic review of medical image quality assessment. *Journal of Imaging*, 11(4):100.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *Preprint*, arXiv:2310.06825.

Avinash C Kak and Malcolm Slaney. 2001. *Principles of computerized tomographic imaging*. SIAM.

Le Kang, Peng Ye, Yi Li, and David Doermann. 2014. Convolutional neural networks for no-reference image quality assessment. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1733–1740.

Junjie Ke, Qifei Wang, Yilin Wang, Peyman Milanfar, and Feng Yang. 2021. Musiq: Multi-scale image quality transformer. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 5148–5157.

Burak Koçak, Andrea Ponsiglione, Arnaldo Stanzione, Christian Bluethgen, João Santinha, Lorenzo Ugga, Merel Huisman, Michail E Klontzas, Roberto Cannella, and Renato Cuocolo. 2025. Bias in artificial intelligence for medical imaging: fundamentals, detection, avoidance, mitigation, challenges, ethics, and prospects. *Diagnostic and interventional radiology*, 31(2):75.

Weiqi Li, Xuanyu Zhang, Shijie Zhao, Yabin Zhang, Junlin Li, Jian Zhang, and 1 others. 2026. Q-insight:

Understanding image quality via visual reinforcement learning. *Advances in Neural Information Processing Systems*, 38:36802–36827.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023a. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916.

Jiyao Liu, Junzhi Ning, Chenglong Ma, Wanying Qu, Jianghan Shen, Siqi Luo, Jinjie Wei, Jin Ye, Pengze Li, Tianbin Li, and 1 others. 2026. Medq-deg: A multidimensional benchmark for evaluating mllms across medical image quality degradations. *arXiv preprint arXiv:2603.07769*.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023b. G-eval: NLG evaluation using gpt-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, Singapore. Association for Computational Linguistics.

Hongyi Miao, Jun Jia, Yankun Cao, Yingjie Zhou, Yanwei Jiang, Zhi Liu, and Guangtao Zhai. 2025. Ultrasound-qbench: Can llms aid in quality assessment of ultrasound imaging? *arXiv preprint arXiv:2501.02751*.

Anish Mittal, Anush Krishna Moorthy, and Alan Conrad Bovik. 2012. No-reference image quality assessment in the spatial domain. *IEEE Transactions on image processing*, 21(12):4695–4708.

Sahal Shaji Mullappilly, Mohammed Irfan Kurpath, Sara Pieri, Saeed Yahya Alseiari, Shanavas Cholakkal, Khaled Aldahmani, Fahad Khan, Rao Anwer, Salman Khan, Timothy Baldwin, and 1 others. 2024. Bimedix2: Bio-medical expert lmm for diverse medical modalities. *arXiv preprint arXiv:2412.07769*.

Ádám Nárai, Petra Hermann, Tibor Auer, Péter Kemenczky, János Szalma, István Homolya, Eszter Somogyi, Pál Vakli, Béla Weiss, and Zoltán Vidnyánszky. 2022. Movement-related artefacts (mr-art) dataset of matched motion-corrupted and clean structural mri brain scans. *Scientific data*, 9(1):630.

OpenAI. 2025. Gpt-5 system card. Technical report, OpenAI.

Gorkem Polat, Deniz Sen, Alperen Inci, and Alptekin Temizel. 2020. Endoscopic artefact detection with ensemble of deep neural networks and false positive elimination. In *EndoCV@ ISBI*, pages 8–12.

Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, Atilla Kiraly, Madeleine Traverse, Timo Kohlberger, Shawn Xu, Fayaz Jamil, Cían Hughes, Charles Lau, and 1 others. 2025. Medgemma technical report. *arXiv preprint arXiv:2507.05201*.

Hamid R Sheikh and Alan C Bovik. 2006. Image information and visual quality. *IEEE Transactions on image processing*, 15(2):430–444.

Jialin Su, Meifang Li, Yongping Lin, Liu Xiong, Caixing Yuan, Zhimin Zhou, and Kunlong Yan. 2023. Deep learning-driven multi-view multi-task image quality assessment method for chest ct image. *BioMedical Engineering OnLine*, 22(1):117.

Yanzhou Su, Tianbin Li, Jiyao Liu, Chenglong Ma, Junzhi Ning, Cheng Tang, Sibo Ju, Jin Ye, Pengcheng Chen, Ming Hu, and 1 others. 2025. Gmai-vl-r1: Harnessing reinforcement learning for multimodal medical reasoning. *arXiv preprint arXiv:2504.01886*.

Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, SH Cai, Yuan Cao, Y Charles, HS Che, Cheng Chen, Guanduo Chen, and 1 others. 2026. Kimi k2. 5: Visual agentic intelligence. *arXiv preprint arXiv:2602.02276*.

Ali S Tejani, Michail E Klontzas, Anthony A Gatti, John T Mongan, Linda Moy, Seong Ho Park, Charles E Kahn Jr, and CLAIM 2024 Update Panel. 2024. Checklist for artificial intelligence in medical imaging (claim): 2024 update. *Radiology: Artificial Intelligence*, 6(4):e240300.

The The Evidence-Based Radiology Working Group. 2001. Evidence-based radiology: a new approach to the practice of radiology. *Radiology*, 220(3):566–575.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, and 1 others. 2024. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*.

Yinhuai Wang, Jiwen Yu, and Jian Zhang. 2022. Zero-shot image restoration using denoising diffusion null-space model. *arXiv preprint arXiv:2212.00490*.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. 2004. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612.

Haoning Wu, Zicheng Zhang, Erli Zhang, Chaofeng Chen, Liang Liao, Annan Wang, Chunyi Li, Wenxiu Sun, Qiong Yan, Guangtao Zhai, and 1 others. 2023. Q-bench: A benchmark for general-purpose foundation models on low-level vision. *arXiv preprint arXiv:2309.14181*.

Haoning Wu, Zicheng Zhang, Erli Zhang, Chaofeng Chen, Liang Liao, Annan Wang, Kaixin Xu, Chunyi Li, Jingwen Hou, Guangtao Zhai, and 1 others. 2024a. Q-instruct: Improving low-level visual abilities for multi-modality foundation models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 25490–25500.

Tianhe Wu, Kede Ma, Jie Liang, Yujiu Yang, and Lei Zhang. 2024b. A comprehensive study of multi-modal large language models for image quality assessment. In *European Conference on Computer Vision*, pages 143–160. Springer.

Tianhe Wu, Jian Zou, Jie Liang, Lei Zhang, and Kede Ma. 2026. Visualquality-r1: Reasoning-induced image quality assessment via reinforcement learning to rank. *Advances in Neural Information Processing Systems*, 38:88167–88190.

Huihui Xu, Yuanpeng Nie, Hualiang Wang, Ying Chen, Wei Li, Junzhi Ning, Lihao Liu, Hongqiu Wang, Lei Zhu, Jiyao Liu, and 1 others. 2025a. Medground-r1: Advancing medical image grounding via spatial-semantic rewarded group relative policy optimization. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 391–401. Springer.

Weiwen Xu, Hou Pong Chan, Long Li, Mahani Aljunied, Ruifeng Yuan, Jianyu Wang, Chenghao Xiao, Guizhen Chen, Chaoqun Liu, Zhaodonghui Li, and 1 others. 2025b. Lingshu: A generalist foundation model for unified multimodal medical understanding and reasoning. *arXiv preprint arXiv:2506.07044*.

Siyi Xun, Yue Sun, Jingkun Chen, Zitong Yu, Tong Tong, Xiaohong Liu, Mingxiang Wu, and Tao Tan. 2025. Mediqa: A scalable foundation model for prompt-driven medical image quality assessment. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 339–349. Springer.

Jin Ye, Junlong Cheng, Jianpin Chen, Zhongying Deng, Tianbin Li, Haoyu Wang, Yanzhou Su, Ziyan Huang, Jilong Chen, Lei Jiang, and 1 others. 2023. Sa-med2d-20m dataset: Segment anything in 2d medical imaging with 20 million masks. *arXiv preprint arXiv:2311.11969*.

Jin Ye, Guoan Wang, Yanjun Li, Zhongying Deng, Wei Li, Tianbin Li, Haodong Duan, Ziyan Huang, Yanzhou Su, Benyou Wang, and 1 others. 2024. Gmai-mmbench: A comprehensive multimodal evaluation benchmark towards general medical ai. *Advances in Neural Information Processing Systems*, 37:94327–94427.

Zhiyuan You, Zheyuan Li, Jinjin Gu, Zhenfei Yin, Tianfan Xue, and Chao Dong. 2024. Depicting beyond scores: Advancing image quality assessment through multi-modal language models. In *European Conference on Computer Vision*, pages 259–276. Springer.

Jure Zbontar, Florian Knoll, Anuroop Sriram, Tullie Murrell, Zhengnan Huang, Matthew J Muckley, Aaron Defazio, Ruben Stern, Patricia Johnson, Mary Bruno, and 1 others. 2018. fastmri: An open dataset and benchmarks for accelerated mri. *arXiv preprint arXiv:1811.08839*.

Lin Zhang, Lei Zhang, and Alan C Bovik. 2015. A feature-enriched completely blind image quality evaluator. *IEEE Transactions on Image Processing*, 24(8):2579–2591.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. 2018. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 586–595.

Appendix

A Data Construction Pipeline and Quality Control

The construction of MedQ-Bench involved a systematic multi-stage pipeline for collecting, curating, and annotating medical images across five modalities. This section provides detailed information about our comprehensive data sourcing strategies, quality control measures, and annotation protocols, with particular emphasis on the diverse sources and label types that enable robust evaluation of low-level visual perception capabilities.

Comprehensive Data Sources and Acquisition Strategy. We employed a three-channel data collection strategy: public datasets + imaging department collaboration + synthetic generation. On one hand, we conducted comprehensive internet searches for 2D/3D medical quality-related datasets; on the other hand, we collaborated with hospitals to obtain ethically approved clinical data. From this massive data pool, we ultimately selected the datasets shown in Table 3, covering 5 medical imaging modalities to ensure universality and clinical relevance of data sources. For images, we adhere to the SA-Med2D-20M (Ye et al., 2023) protocol, transforming all 2D/3D medical images into 2D RGB images for further evaluation. Table 3 provides a complete overview of all datasets integrated into MedQ-Bench, including specific modalities, sample quantities, label types, and acquisition status. The table demonstrates the comprehensive scope of our data collection effort, spanning established clinical research datasets and custom synthetic degradation collections, and AI-generated images. All collected images were anonymized, with all patient-identifying information systematically removed using automated de-identification pipelines validated against clinical privacy requirements.

Expert-designed Seed Perception Questions. The construction process began with a panel of medical imaging specialists who designed seed questions covering diverse modalities, degradation types, and task formats. Each seed is a structured template with predefined placeholders (e.g., `[artifact_type]`, `[quality_attribute]`) whose values are constrained by expert-defined taxonomies. These `[QUESTION_SEEDS]` are defined as:

```
Type 0 (Yes-No):
  T0.1: "Does this image show evidence of [artifact_type]?"
  T0.2: "Is the [artifact_type] fully visible?"

Type 1 (What):
  T1.1: "What is the primary [assessment_target]?"
  T1.2: "What [quality_dimension] issue is most prominent?"

Type 2 (How):
  T2.1: "How would you rate the severity of
  ↪  [artifact_type]?"
  T2.2: "How would you rate the overall
  ↪  [quality_dimension]?"
```

Controlled Question Expansion. To generate questions for each sample, we employed GPT-4o as a controlled question generator. GPT-4o served solely as a template instantiation tool under strict constraints, receiving explicit system prompts:

```
System: You are a [modality] image quality assessment
↪  expert.
Task: As an [modality] image quality assessment expert,
↪  please questions based on the following information:

Given:
- Image path: [IMAGE_PATH]
- Artifacts of this image: [ARTIFACT]
- Modality-specific assessment criteria: [ARTIFACT_LIST],
[TECHNICAL_QUALITY_ASSESSMENT_CRITERIA], and other
↪  information.

Your task is to generate EXACTLY 3 questions that assess the
image quality based on the criteria and the provided image.
Consider the following question seeds and constrains:

Question seeds:
[QUESTION_SEEDS]

Constraints:
1. Preserve each seed's semantic intent and structure
↪  exactly
2. Substitute [artifact_type] with detected artifacts
3. Generate one Yes-or-No, one What, and one How question,
↪  with each question focusing on one of four quality
↪  concerns
0:technical distortion, 1:global visual quality, 2:local
↪  structure visibility, 3:lighting / brightness / color /
↪  others
4. Only focus on low-level attributes.
```

This ensures expansion is limited to placeholder substitution and minimal paraphrasing. Every expanded question underwent review and revision by medical imaging experts to eliminate model-specific biases and ensure alignment with expert-designed seeds.

Multi-round Expert Validation. We manually annotated the answers for the generated questions to ensure correctness, consistency, and alignment with the intended low-level quality assessment labels. All question–answer pairs underwent rigorous multi-stage human annotation and verification using a structured annotation interface, as shown in Figure 6 and 7. The multi-round validation process consisted of three phases: *(1)* Independent annotation by three medical imaging specialists,

Modality	Source Type	Dataset	Samples	% of Modality	Total Samples
CT	Authentic	Radiopaedia	239	27.2%	
	Simulate	AAPM CT-MAR (Haneda et al., 2025)	613	69.8%	
	AI-generated	AIsynthesis (subset)	26	3.0%	878
MRI	Authentic	Radiopaedia	130	15.0%	
	Authentic	MR-ART (Nárai et al., 2022)	68	7.9%	
	Authentic	FSL Example MRI Artifacts	43	5.0%	
	Simulate	FastMRI (Zbontar et al., 2018)	454	54.4%	
	Simulate	5T MRI Data	55	6.4%	
	AI-generated	AIsynthesis	98	11.3%	848
Histopathology	Authentic	HistoArtifacts (Fuchs et al., 2024)	220	29.0%	
	AI-generated	HARP (Fuchs et al., 2024)	470	62.0%	
	AI-generated	AIsynthesis	68	9.0%	758
Endoscopy	Authentic	EndoCV2020 (Polat et al., 2020)	470	84.7%	
	AI-generated	AIsynthesis	85	15.3%	555
Retinal	Authentic	EyeQ (Fu et al., 2019)	197	73.2%	
	AI-generated	AIsynthesis	72	26.8%	269
		Overall Total	**3,308**		

Table 3: Comprehensive breakdown of dataset composition.

each following the standardized perception and description annotation protocols as well as modality-specific checklists to minimize arbitrary judgments; *(2)* Cross-validation sessions in which annotators reviewed each other's labels, identified divergent cases, and conducted structured discussions based on explicit visual and clinical evidence. For description tasks in particular, discrepancies were further examined by aligning observation-level evidence, rechecking modality-specific rules, reconciling classification boundaries (e.g., "usable" versus "reject"), and harmonizing description chains to ensure logical consistency between visual attributes, modality rules, and textual explanations; *(3)* Consensus resolution, in which labels and descriptions were revised once agreement was reached, and the validated evidence and description sequence were consolidated into a single final description. For the rare cases where conflicts persisted, whether in evidential interpretation or in final conclusions, the final label and description statement were determined by majority voting. This unified protocol reduces idiosyncratic variability across annotators and establishes a stable and clinically grounded expert standard.

Description Annotation Standards and Workflow. For the MedQ-Description tasks, we established specific annotation standards to ensure consistent and clinically relevant quality assessment descriptions. Expert annotators followed a structured description workflow that emphasized systematic analysis and transparent decision-making

Figure 6: Interface for the MedQ-MCQA dataset.

Figure 7: Interface for the MedQ-Description dataset.

processes. The description annotation protocol involved a sequential four-step process: *(1)* Visual Analysis Phase: Systematic examination of perceptual attributes such as noise, blur, artifacts, contrast, and resolution, avoiding any high-level diagnostic interpretation; *(2)* Modality-Specific Assessment: Targeted evaluation of quality dimensions specific

to each imaging modality (e.g., streak artifacts in CT, motion artifacts in MRI, staining uniformity in histopathology), following standardized checklists for each modality type; *(3)* Quality Classification: Application of a three-tier system based on accumulated evidence from steps 1-2: "good" (no significant quality issues affecting clinical utility), "usable" (minor quality issues that do not compromise diagnostic accuracy), and "reject" (severe quality degradation requiring repeat imaging); *(4)* Structured Description Generation: Creation of comprehensive yet concise descriptions (3-5 sentences) that logically connect the observed visual attributes to the final quality judgment, ensuring clear description traceability from observation to conclusion. This step-by-step description flow ensures that all quality assessments follow a consistent analytical framework, with each conclusion being explicitly grounded in observable visual evidence rather than subjective impressions.

Dataset Composition and Balance. Each modality contributes proportionally to maintain representational balance, and degradation types are systematically distributed to avoid bias toward any particular quality issue.

Fine-Grained vs. Coarse-Grained Definition. The fine-grained versus coarse-grained distinction for comparison tasks was defined through a structured expert review process. Three board-certified radiologists independently reviewed all image pairs and categorized them based on how difficult the quality difference is to perceive: coarse-grained pairs exhibit clear, immediately noticeable degradations, whereas fine-grained pairs involve subtle differences that require deliberate inspection. After independent labeling, disagreements were resolved through discussion and consensus, ensuring a stable expert standard.

B   Detailed Benchmark Statistics

B.1   Dataset Composition by Source and Modality

Dataset Composition. The MedQ-Bench dataset consists of 3,308 samples distributed across three primary source types (Table 4). The dataset covers five major medical imaging modalities with detailed breakdown by source type and specific datasets shown in Table 3.

Detailed Simulation Methods for Synthetic Degradations. The simulated CT degradations in

Source Type	Authentic	Simulate	AI-Generated
Percentage	41.3%	33.9%	24.8%

Table 4: Distribution of MedQ-Bench dataset by source type.

AAPM CT-MAR were reconstructed using several algorithms: SIRT, FBP (Kak and Slaney, 2001), and FISTA (Beck and Teboulle, 2009). Specifically, CT artifacts were systematically simulated to include three primary degradation types: *(1)* limited-angle artifacts, *(2)* metal artifact reduction, and *(3)* sparse-view artifacts. For MRI degradations, we primarily simulated acceleration artifacts and motion artifacts using established computational frameworks. Acceleration artifacts were generated using SigPy[1] and TorchIO[2], implementing both DDNM (Wang et al., 2022) and wavelet-based reconstruction methods (Guerquin-Kern et al., 2011). Additionally, our 5T MRI data were acquired from private clinical collections using the uMR Jupiter 5T system, obtained under institutional ethical approval with comprehensive patient anonymization protocols.

To generate synthetic images across diverse medical imaging modalities, we employed BAGEL fine-tuned on domain-specific medical datasets (Deng et al., 2025). This approach ensured that synthetic degradations maintained clinical realism while providing controlled quality variations essential for comprehensive benchmark evaluation.

B.2   Distributions of Task Types and Degradation Levels in MedQ-Perception

Question Type	Percentage
Modality-specific	57.2%
General	42.8%
Total	**100.0%**

Table 5: MedQ-Perception: Distribution of tasks by question type.

Table 5 and Table 6 present the distribution of MedQ-Perception tasks across question types and degradation severity levels.

B.3   Distribution of low-level attributions

Figure 8 illustrates the comprehensive distribution of low-level quality attributes across five medical

---

[1]https://sigpy.readthedocs.io/en/latest/
[2]https://github.com/TorchIO-project/torchio

Figure 8: Distribution of low-level attributions across imaging modalities and distortion types in MedQ-Bench.

Degradation Level	Percentage
No Degradation	23.8%
Mild Degradation	44.6%
Severe Degradation	31.6%
Total	**100.0%**

Table 6: MedQ-Perception: Distribution of degradation severity levels.

imaging modalities, covering over 40 distinct degradation types including modality-specific artifacts and general quality issues.

C Complete Experimental Results

C.1 Experimental Setup

In this study, we evaluated various large vision-language models (LVLMs), encompassing medical-specialized models, open-source models, and closed-source API general-purpose models. Model weights were obtained from their respective official Hugging Face repositories. The evaluation work was conducted using the VLMEvalKit framework[3].

The evaluation was performed under a "zero-shot" setting. Specifically, our evaluation prompts contained no example demonstrations, and models had to complete task description without any related training or examples. This approach better tests the models' generalization capabilities and understanding abilities, examining their performance when faced with novel problems. All tests were executed on NVIDIA A100 GPUs with 80GB memory.

The configurations used for all reported results

---

[3]https://github.com/open-compass/VLMEvalKit

are as follows. API-based models use temperature $= 0$ and $n = 1$ (greedy decoding). Open-source models use top-$k = 1$, top-$p = 0.001$, and temperature $= 0.01$. All local models are deployed with vLLM with a parallel sample size of 8.

C.2 Detailed Model Performance

Few-Shot Evaluation for Context Calibration. To further calibrate the models' internal quality standards on the No-Reference Description tasks, we additionally perform few-shot evaluations. For each test sample, we provide three carefully selected demonstration examples spanning different imaging modalities and the three quality levels (Good / Usable / Reject). These modality-aware reference examples serve two purposes: *(1)* providing medical context to help models understand how visual degradations influence diagnostic utility across different imaging scenarios; and *(2)* establishing concrete anchors that allow models to interpret subjective quality categories more reliably, rather than relying on abstract definitions alone. Table 7 presents the few-shot evaluation results on the No-Reference Description tasks. Compared with the zero-shot results in Table 1, modality-aware reference examples yield consistent improvements across most evaluation dimensions. These results show that few-shot demonstrations enhance models' interpretation of the quality labels and improve calibration in medical image quality assessment.

Paired Comparison Task Performance Breakdown. Table 9 provides the complete numerical breakdown of model performance across different comparison difficulty levels and evaluation dimen-

Model	Comp.↑	Prec.↑	Cons.↑	Qual.↑	Overall↑
Qwen2.5-VL-Instruct (7B)	0.769	0.723	1.878	1.168	4.538
Qwen2.5-VL-Instruct (32B)	1.082	0.959	**1.982**	1.335	5.358
InternVL3 (8B)	1.005	0.950	1.905	1.421	5.281
InternVL3 (38B)	0.996	0.973	1.932	1.448	5.349
Qwen2.5-VL-Instruct (72B)	0.932	0.923	1.896	1.412	5.163
BiMediX2 (8B)	0.405	0.428	0.315	0.715	1.863
Lingshu (32B)	0.678	0.751	1.955	1.105	4.489
MedGemma (27B)	0.796	0.523	1.687	1.314	4.320
Mistral-Medium-3	0.987	0.878	1.742	1.445	5.052
Claude-4-Sonnet	0.914	0.787	1.869	1.476	5.046
Gemini-2.5-Pro	0.905	0.860	1.710	1.605	5.080
Grok-4	1.095	1.005	1.823	1.550	5.473
GPT-4o	1.077	1.036	1.860	1.520	5.493
GPT-5	**1.220**	**1.145**	1.850	**1.630**	**5.845**

Table 7: Few-shot evaluation results on No-reference Description tasks.

Model	CT	Histo.	MRI	Endos.	Retinal
GPT-5	71.47%	**65.43%**	**75.90%**	60.89%	**70.09%**
GPT-4o	**72.85%**	58.33%	64.75%	60.44%	66.67%
Grok-4	70.14%	59.37%	65.93%	64.49%	61.40%
Gemini-2.5-Pro	67.04%	53.40%	60.79%	60.89%	59.83%
Mistral-Medium-3	65.93%	38.58%	61.51%	**65.33%**	61.54%
Claude-4-Sonnet	64.27%	54.63%	55.04%	**65.33%**	65.81%
Qwen2.5-VL-72B	65.65%	47.53%	74.82%	66.22%	64.96%
InternVL3-38B	68.14%	48.46%	62.95%	60.44%	70.09%
InternVL3-8B	60.66%	51.54%	61.87%	67.56%	63.25%
Qwen2.5-VL-32B	59.00%	46.30%	66.55%	67.56%	63.25%
Qwen2.5-VL-7B	56.79%	35.49%	65.47%	60.44%	64.96%
MedGemma-27B	66.57%	46.60%	57.55%	56.00%	59.83%
Lingshu-32B	57.89%	35.19%	61.15%	50.67%	48.72%
BiMediX2-8B	41.99%	23.38%	44.36%	38.74%	47.62%

Table 8: Detailed perception accuracy results across five imaging modalities.

D Qualitative Analysis and Case Studies

To ground the analyses in this section, we first illustrate the typical question-answer format used in MedQ-Bench. Figure 9 shows representative QA pairs spanning different imaging modalities and quality assessment scenarios, providing a concrete reference for the perception-task structure discussed throughout this section.

Figure 9: Representative QA examples demonstrating typical question-answer patterns in MedQ-Bench across different medical imaging modalities and quality assessment scenarios.

Model	Group	Comp.	Prec.	Cons.	Qual. Acc.	Total
GPT-5	Overall	1.293	1.556	1.925	1.564	6.338
	Fine-grained	1.301	1.495	1.903	1.476	6.175
	Coarse-grained	1.267	1.767	2.000	1.867	6.900
GPT-4o	Overall	1.105	1.414	1.632	1.564	5.714
	Fine-grained	1.155	1.388	1.583	1.534	5.660
	Coarse-grained	0.933	1.500	1.800	1.667	5.900
Grok-4	Overall	1.150	1.233	1.820	1.459	5.662
	Fine-grained	1.214	1.350	1.825	1.495	5.883
	Coarse-grained	0.933	0.833	1.800	1.333	4.900
Gemini-2.5-Pro	Overall	1.053	1.233	1.774	1.534	5.594
	Fine-grained	1.039	1.262	1.709	1.476	5.485
	Coarse-grained	1.100	1.133	2.000	1.733	5.967
InternVL3-8B	Overall	0.985	1.278	1.797	1.474	5.534
	Fine-grained	0.971	1.155	1.748	1.359	5.233
	Coarse-grained	1.033	1.700	1.967	1.867	6.567
Claude-4-Sonnet	Overall	0.857	1.083	1.910	1.481	5.331
	Fine-grained	0.835	1.107	1.883	1.495	5.320
	Coarse-grained	0.933	1.000	2.000	1.433	5.367
Mistral-Medium-3	Overall	0.872	1.203	1.827	1.338	5.241
	Fine-grained	0.893	1.252	1.786	1.282	5.214
	Coarse-grained	0.800	1.033	1.967	1.533	5.333
InternVL3-38B	Overall	1.075	1.083	1.571	1.414	5.143
	Fine-grained	1.117	1.184	1.466	1.359	5.126
	Coarse-grained	0.933	0.733	1.933	1.600	5.200
Lingshu-32B	Overall	0.729	1.015	1.586	1.323	4.654
	Fine-grained	0.699	0.990	1.505	1.243	4.437
	Coarse-grained	0.833	1.100	1.867	1.600	5.400
Qwen2.5-VL-32B	Overall	0.692	0.752	1.895	0.962	4.301
	Fine-grained	0.786	0.922	1.864	1.068	4.641
	Coarse-grained	0.367	0.167	2.000	0.600	3.133
Qwen2.5-VL-7B	Overall	0.714	0.902	1.316	1.143	4.075
	Fine-grained	0.757	1.000	1.320	1.175	4.252
	Coarse-grained	0.567	0.567	1.300	1.033	3.467
Qwen2.5-VL-72B	Overall	0.737	0.977	1.233	1.113	4.060
	Fine-grained	0.699	0.903	1.029	0.971	3.602
	Coarse-grained	0.867	1.233	1.933	1.600	5.633
MedGemma-27B	Overall	0.684	0.692	1.128	1.000	3.504
	Fine-grained	0.650	0.641	0.942	0.854	3.087
	Coarse-grained	0.800	0.867	1.767	1.500	4.933
BiMediX2-8B	Overall	0.474	0.549	0.639	0.511	2.173
	Fine-grained	0.359	0.379	0.641	0.311	1.689
	Coarse-grained	0.867	1.133	0.633	1.200	3.833

Table 9: Detailed numerical results for paired comparison description tasks across models, corresponding to Figure 5.

D.1 Why Do Medical-Specialized and Quality-Oriented Models Underperform General-Purpose Models?

The finding that both medical-specialized and quality-oriented models underperform general-purpose models across key dimensions warrants closer analysis. As summarized in Table 1 and Table 9, their weaknesses are not uniform: medical-specialized models mainly struggle with low-level quality perception and robust quality judgment, while quality-oriented models show limited transfer from generic quality assessment to medical description tasks. Figure 10 provides representative cases that illustrate these limitations.

Insufficient Low-Level Visual Attribute Training. Medical-specialized models appear to prioritize high-level diagnostic description over fundamental visual perception skills. In the CT scan example (Figure 10), MedGemma-27B correctly

User: As a medical image quality assessment expert, provide a concise description focusing on low-level appearance of the image in details. Conclude with "Overall, the quality of this image is [good/usable/reject]".

Golden Description: This is a CT scan of the abdominal region. The image exhibits moderate clarity and contrast, but the presence of significant noise reduces overall resolution. Metal artifacts are prominent, creating streaks that obscure anatomical details and hinder accurate interpretation of the abdominal structures. Overall, the quality of this image is reject.

InternVL3-8B: This abdominal CT scan shows severe streak artifacts radiating from the center, likely due to beam hardening or metal. While overall contrast is adequate and major structures like vertebrae and soft tissues are visible, the artifacts obscure finer details and reduce clarity. Some noise is present but less problematic than the artifacts. Overall, the image quality is poor and judged as reject.

MedGemma-27B: This abdominal CT scan shows bones, soft tissues, and air with adequate brightness and contrast. However, streak artifacts from dense structures, such as bone or metal, obscure fine details. Moderate noise adds a grainy texture, further reducing clarity. While the image remains interpretable for basic anatomical identification, the artifacts and noise limit diagnostic precision. Overall, the quality is usable but not optimal.

Lingshu-32B: This CT scan of the abdomen or pelvis shows the vertebral column, soft tissues, and possible lesions. However, it is heavily degraded by bright streak artifacts that obscure much of the anatomy. These distortions suggest poor acquisition parameters or technical issues. As a result, the image is of low quality and not reliable for diagnostic purposes.

BiMediX2-8B: This CT scan of the liver shows clear structures with good contrast and minimal noise. The organ and surrounding tissues are well-defined, supporting accurate anatomical assessment. No significant artifacts are visible, and the overall resolution is sufficient for clinical use. Overall, the image quality is good and suitable for diagnosis.

GPT-4o: The abdominal CT image contains multiple bright streak artifacts, likely from metal or dense materials. These streaks obscure anatomical details and reduce clarity. Uneven brightness and contrast further complicate interpretation. Due to the severity of these distortions, the overall image quality is reject.

Claude4 Sonnet: This CT scan is heavily degraded by extensive streak artifacts radiating across the field of view, creating a star-like pattern. The artifacts, likely from metallic implants, obscure soft tissue structures and organ boundaries. Contrast is poor, noise is elevated, and diagnostic interpretation is nearly impossible in affected regions. While a few landmarks remain visible, the image quality overall is reject.

InternVL3-38B: This abdominal CT scan shows vertebrae, soft tissues, and organs with adequate contrast and sharpness. However, background noise is high, which reduces the clarity of smaller structures and subtle abnormalities. No major artifacts obstruct critical regions, and the field of view is appropriate. Overall, the image is usable but limited by noise.

GPT-5: This axial CT image shows moderate noise and acceptable sharpness, with organ edges reasonably defined. However, severe metal-induced streak artifacts radiate across the field, producing alternating bright and dark bands that obscure anatomy. Global shading and banding further reduce uniformity. While centered and properly cropped, the distortions make diagnostic interpretation unreliable. Overall, the quality is reject.

Qwen2.5-VL-72B-Instruct: The CT scan is degraded by strong streak artifacts, likely from metallic implants or dense objects. These streaks obscure anatomical details and compromise evaluation of affected regions. Contrast and brightness remain acceptable in unaffected areas, preserving partial visibility of tissues. Despite this, the diagnostic utility is poor. Overall, the quality is reject.

Figure 10: Representative no-reference reasoning image examples demonstrating typical question-answer patterns in MedQ-Bench across different models.

User: As a medical image quality assessment expert, provide a concise description comparing two images focusing on low-level appearance. Conclude with which image has higher quality.

Golden Description: The first image demonstrates excellent clarity and sharpness with minimal motion artifacts, allowing for clear visualization of anatomical structures. In contrast, the second image exhibits severe motion artifacts, including blurring and ghosting, which significantly obscure anatomical details and reduce diagnostic quality. The brain tissue boundaries and ventricular structures are clearly visible in the first image, while they are severely degraded in the second. Overall, the first image has higher quality.

InternVL3-8B: The comparison of the two images shows clear quality differences. Image 1 has better contrast and clarity, with gray and white matter well-differentiated and minimal noise, making structures like gyri and sulci more distinct. Its resolution is higher, and artifacts are minimal, ensuring reliable diagnostic value. Image 2, by contrast, suffers from lower contrast and clarity, higher noise, and poorer resolution, making brain structures harder to interpret. It also contains more artifacts, which further obscure details. Conclusion: Image 1 offers superior diagnostic quality, providing clearer visualization of anatomical structures.

MedGemma-27B: Image 1 shows clearer brain structures with better gray–white matter contrast and less noise. Image 2 appears blurrier, with weaker contrast and more graininess, making details harder to identify. Overall, Image 1 demonstrates superior clarity and quality.

Lingshu-32B: The first image is a coronal T1-weighted MRI with clear anatomical structures, good signal-to-noise ratio, and strong contrast between gray and white matter. These qualities make it suitable for accurate interpretation. The second image, however, is heavily corrupted by noise, which obscures anatomical details and reduces clarity. The poor visibility significantly limits its diagnostic value. Overall, the first image is of much higher quality.

BiMediX2-8B: The left image demonstrates a higher signal-to-noise ratio, producing a clearer and more detailed view of anatomical structures. In contrast, the right image shows lower SNR, resulting in reduced clarity and less visible details. This difference strongly impacts the ability to detect and diagnose subtle abnormalities. Overall, the left image provides superior quality and greater diagnostic reliability.

GPT-4o: The first image shows higher contrast, clearer anatomical structures, and less noise, with well-defined edges. The second image has lower contrast and more noise, causing structures to appear blurred and less distinct. Overall, the first image demonstrates superior quality due to its clarity and better contrast.

Claude4 Sonnet: The left MRI image has higher contrast, sharper anatomical boundaries, and a better signal-to-noise ratio, with clear visualization of brain parenchyma and ventricles. Its signal is more uniform and details are well-preserved. The right image, however, appears grainier with lower contrast, more noise, and blurred structures, showing reduced diagnostic value. Overall, the left image is of higher quality and more suitable for clinical interpretation.

InternVL3-38B: The first MRI image shows clear brain structures with distinct tissue contrasts and high resolution, making fine details easy to visualize. In comparison, the second image appears lower in quality, with weaker tissue contrast and less distinct details. Its resolution is reduced, making fine anatomical features harder to discern. Overall, the first image demonstrates higher quality due to sharper details and better contrast.

GPT-5: The left image has sharp cortical and orbital boundaries, low noise, and strong gray–white matter contrast. Its background is smooth and uniform, with minimal artifacts. By contrast, the right image is blurred, noisy, and shows reduced contrast with visible mottling and ghosting. These issues obscure fine details and reduce diagnostic value. Overall, the left image is of clearly higher quality.

Qwen2.5-VL-72B-Instruct: Image 1 has lower contrast, less differentiation between tissues, and smoother appearance with reduced sharpness. Image 2 shows higher contrast and clearer anatomical details, though it also contains more visible noise. Despite the noise, the sharper features and stronger tissue contrast make Image 2 more suitable for diagnostic use. Overall, Image 2 is of higher quality.

Figure 11: Representative paired image examples demonstrating typical question-answer patterns in MedQ-Bench across different models.

identifies anatomical structures and acknowledges the presence of streak artifacts, but fails to appropriately assess their clinical significance. The model describes the image as "usable but not optimal" despite prominent metal artifacts that would necessitate repeat scanning in clinical practice. This suggests that medical fine-tuning datasets may inadequately represent the full spectrum of image quality degradations encountered in clinical workflows.

Diagnostic Bias Over Quality Assessment. BiMediX2-8B demonstrates a critical failure mode by describing the same severely degraded CT scan as having "good quality and suitable for diagnosis." This systematic misalignment indicates that medical-specialized training may inadvertently optimize models for diagnostic confidence rather than quality assessment accuracy. The model's focus on anatomical identification overshadows its ability to detect quality-compromising artifacts, suggesting that current medical training paradigms may not adequately distinguish between diagnostic content recognition and image quality evaluation.

Limited Transfer of Quality-Oriented Models to Medical Description. Compared with both general-purpose and medical-specialized MLLMs, the three quality-oriented models (Q-Instruct, Q-Insight, and VisualQuality-R1) exhibit limited generalization to medical image quality assessment. Although Q-Instruct achieves a competitive MCQA perception score in Table 1, all three models obtain relatively low no-reference description scores, indicating that prior quality assessment training does not directly translate to accurate low-level medical quality description. This weakness is more evident in paired comparison description, where their overall performance trails most frontier general-purpose models, as shown in Table 9 and Figure 5.

D.2 Error Pattern Analysis of Top-Performing Models

To identify which inputs contribute most to errors in state-of-the-art MLLMs, we analyzed GPT-5's failure patterns across different modalities and artifact types on the perception tasks. Table 10 shows that the highest error rates appear in Endoscopy (39.11%) and Histopathology (34.57%) modalities. These modalities contain complex textures, heterogeneous visual structures, and tissue-level variations that increase the difficulty of fine-grained

quality assessment compared to volumetric imaging modalities such as CT and MRI.

At the artifact level, the most challenging categories for GPT-5 are Air Bubbles (95.23% error rate), Specularity (90.48%), and Blood-related artifacts (84.62%). These failures arise because such artifacts exhibit irregular spatial distributions, high-frequency visual patterns, and often co-occur with other degradations. Notably, these challenging artifacts predominantly appear in endoscopy and histopathology images, where strong localized degradations and complex tissue backgrounds make accurate identification particularly difficult even for top-performing models. This analysis reveals that current MLLMs still struggle with modality-specific artifacts that require fine-grained visual discrimination in texturally complex medical imaging contexts.

Modality	Error Rate
Endoscopy	39.11%
Histopathology	34.57%
Fundus	29.91%
CT	25.76%
MRI	24.10%

Table 10: GPT-5 error rates across imaging modalities on perception tasks, ranked by difficulty.

D.3 Example of Description Tasks

Beyond the perception-task QA pairs in Figure 9, the description tasks reveal richer failure patterns that span both single-image and paired comparison settings. Figure 10 presents representative no-reference description cases highlighting how different models produce diverging quality judgments on the same image, while Figure 11 shows paired comparison cases that surface subtle reasoning differences across models when ranking image pairs. Together these case studies expose the practical limitations of current MLLMs that the aggregate metrics in Section B summarize.

D.4 Human Expert Evaluation Protocol

Expert Recruitment and Qualification Criteria. Human experts in our evaluation consisted of medical imaging technicians with a minimum of 3 years of clinical experience in medical imaging quality assessment and medical imaging PhDs with specialized training in image quality evaluation. Medical imaging technicians were recruited from certified clinical facilities and possessed active professional

certifications in their respective imaging modalities. PhDs were selected from accredited medical imaging research programs and had completed at least 2 years of coursework, including medical image processing and quality assessment methodologies. All experts demonstrated proficiency in identifying common imaging artifacts and quality issues across multiple medical imaging modalities through a standardized pre-evaluation assessment.

Human-Human Annotation Alignment Analysis. To quantify the reliability achieved by our multi-round expert validation protocol, we computed Cohen's κ between each annotator and the consensus label obtained via majority voting. For the description tasks, Table 11 presents the inter-annotator agreement statistics. For the perception tasks, agreement between individual annotators and the majority-vote labels was $\kappa = 0.873$. These κ values indicate substantial to almost perfect agreement under our structured expert protocol, confirming that the annotation process minimizes bias and ensures reliability.

Metric	Completeness	Preciseness	Consistency	Quality Accuracy
Cohen's κ	0.843	0.817	0.856	0.884

Table 11: Inter-annotator agreement (Cohen's κ) for description task.

Human-AI Alignment Analysis. To ensure the reliability and validity of our automated evaluation, we conducted a rigorous alignment validation between GPT-4o judgments and expert assessments. A total of 200 cases were randomly sampled and independently evaluated by three board-certified medical imaging specialists under a double-blinded protocol. We employed quadratic weighted Cohen's κ_w (Cohen, 1968) for ordinal ratings:

$$\kappa_w = 1 - \frac{\sum_{i,j} w_{ij} O_{ij}}{\sum_{i,j} w_{ij} E_{ij}}, \quad (1)$$

where O_{ij} is the observed agreement matrix, E_{ij} the expected agreement matrix, and $w_{ij} = \frac{(i-j)^2}{(k-1)^2}$ the quadratic weights penalizing larger disagreements more severely. We further conducted iterative prompt refinement to maximize concordance between GPT-4o and expert consensus.

The confusion matrices shown in Figure 12 demonstrate strong alignment between human expert scores and GPT-4o automated evaluation across all three evaluation dimensions, with over 80% accuracy in each dimension. Quadratic weighted κ_w accounts for the ordinal nature of the evaluation labels, penalizing larger discrepancies more heavily than adjacent category differences. The consistently high κ_w values (0.774–0.985) detailed in Table 12 indicate substantial agreement beyond chance between human expert scores and GPT-4o automated evaluation, reflecting that the automated system is not only accurate but also aligned with the fine-grained ordinal structure of human expert judgments.

Metric	Completeness	Preciseness	Consistency	Quality Accuracy
κ_w	0.774	0.876	0.840	0.985

Table 12: Quadratic weighted Cohen's κ_w values for human–AI alignment across evaluation dimensions.

To assess whether human–AI alignment remains stable across quality levels, we partitioned the 200 sampled outputs into three tiers by human-score quantiles and examined the lowest third, which contains more low-quality or failed predictions. Table 13 presents the alignment metrics in this challenging subset. While the weighted κ_w values show some decrease compared to overall alignment, the automated evaluation does not substantially degrade even under these challenging cases, with κ_w values remaining above 0.7 for most dimensions and achieving 0.952 for Quality Accuracy. This confirms that our automated evaluation framework maintains robust alignment with human expert annotations, strengthening confidence in its use as a reliable surrogate for large-scale human evaluation.

Metric	Completeness	Preciseness	Consistency	Quality Accuracy
κ_w	0.702	0.791	0.755	0.952

Table 13: Human–AI alignment in the lowest-quality tier (bottom third by human score). Despite challenging cases, alignment remains robust across all evaluation dimensions.

Multi-Judge Validation for Self-Preference Analysis. To investigate potential self-preference bias when using GPT-4o as the evaluation judge, we conducted a multi-judge validation study using three independent LLM judges: GPT-4o, Claude-4-Sonnet, and Gemini-2.5-Pro. Each judge independently scored all model outputs on the No-Reference description tasks. Table 14 presents the overall scores assigned by each judge and inter-judge consistency metrics. The results show min-

Figure 12: Confusion matrices showing alignment between human expert scores and GPT-4o automated evaluation across four evaluation dimensions.

Model	GPT-4o	Claude	Gemini	ICC	ICC 95% CI	MAD (Claude)	MAD (Gemini)
Qwen2.5-VL-Instruct (7B)	4.367	4.376	4.371	0.984	[0.980, 0.987]	0.009	0.004
Qwen2.5-VL-Instruct (32B)	5.272	5.294	5.308	0.992	[0.990, 0.994]	0.022	0.036
InternVL3 (8B)	4.983	4.995	4.968	0.986	[0.982, 0.989]	0.012	0.015
InternVL3 (38B)	4.965	4.977	4.977	0.990	[0.988, 0.992]	0.012	0.012
Qwen2.5-VL-Instruct (72B)	4.982	4.932	4.959	0.988	[0.985, 0.990]	0.050	0.023
BiMediX2 (8B)	1.721	1.692	1.719	0.954	[0.942, 0.963]	0.029	0.002
Lingshu (32B)	4.312	4.344	4.317	0.987	[0.984, 0.990]	0.032	0.005
MedGemma (27B)	4.054	4.036	4.036	0.978	[0.973, 0.983]	0.018	0.018
Mistral-Medium-3	4.557	4.529	4.520	0.988	[0.985, 0.990]	0.028	0.037
Claude-4-Sonnet	4.529	4.529	4.570	0.981	[0.976, 0.985]	0.000	0.041
Gemini-2.5-Pro	5.018	5.014	5.005	0.985	[0.981, 0.988]	0.004	0.013
GPT-4o	5.321	5.335	5.321	0.989	[0.986, 0.991]	0.014	0.000
GPT-5	5.679	5.679	5.652	0.987	[0.983, 0.989]	0.000	0.027

Table 14: Multi-judge validation results showing overall description scores from three independent LLM judges and inter-judge consistency metrics. MAD (Claude) and MAD (Gemini) represent MAD between GPT-4o scores and Claude/Gemini scores respectively. Score differences across judges are minimal, and high ICC values (>0.95) confirm excellent agreement, indicating no systematic self-preference bias.

imal variation between judges, with score differences typically within 0.05 points. Notably, GPT-4o does not assign systematically higher scores to OpenAI models (GPT-4o, GPT-5) compared to scores from Claude or Gemini judges. All models achieve Intraclass Correlation Coefficient (ICC) values above 0.95, indicating excellent agreement among judges. The mean absolute deviation (MAD) between GPT-4o scores and other judges remains below 0.05 for most models, confirming that GPT-4o's evaluations are consistent with independent judges and do not exhibit self-preference bias.

E   Potential Risks

Although MedQ-Bench is intended for benchmark evaluation rather than direct clinical deployment, careful interpretation is still important. Because the benchmark is task-agnostic by design, strong performance should be viewed as evidence of foundational quality reasoning, not as direct proof of

task-specific clinical readiness. In addition, current MLLMs may show variable performance on subtle degradations, fine-grained comparisons, and complex quality descriptions, and this variability should be considered when generalizing results. We also observe that some model families emphasize different strengths, for example stronger perception with relatively weaker description in certain settings. Overall, benchmark outcomes are most informative when combined with task-aware validation and expert review in downstream scenarios.

F   Artifact Licensing and Intended Use

All public datasets reused in **MedQ-Bench** (Radiopaedia, AAPM CT-MAR (Haneda et al., 2025), MR-ART (Nárai et al., 2022), FSL Example MRI Artifacts, FastMRI (Zbontar et al., 2018), HistoArtifacts and HARP (Fuchs et al., 2024), EndoCV2020 (Polat et al., 2020), EyeQ (Fu et al., 2019)) are accessed under their original licenses (research-only or CC-BY variants) and used strictly

within those terms. The private 5T MRI subset was collected under institutional ethical approval with full patient anonymization. All evaluated MLLMs are queried via their official APIs or Hugging Face checkpoints in accordance with each provider's terms of service. **MedQ-Bench** itself, including the curated images, generated questions, and expert annotations, is released for non-commercial academic research only, inheriting the most restrictive upstream license; derivatives may not be used in clinical deployment or commercial products. This usage is consistent with the intended research purpose of every upstream artifact, namely advancing medical image quality assessment and the evaluation of MLLMs.

G   Evaluation Prompt

Single-Image Perception Task Prompts

Yes-No / What / How Question Template:

> You are an expert in medical image quality assessment. Please carefully observe this medical image and answer the following question:

Description Task Prompts

No-reference Description Template:

> As a medical image quality assessment expert, provide a concise description focusing on low-level appearance of the image in details. Conclude with "Overall, the quality of this image is [good/usable/reject]". Please provide a comprehensive but concise assessment in 3-5 sentences.

Comprehensive Description Template:

> As a medical image quality assessment expert, provide a concise description comparing two images focusing on low-level appearance. Conclude with which image has higher quality. Please provide comprehensive but concise assessment in 3-5 sentences.

```
#User: Evaluate the internal consistency between the
↪   description path (description of image problems)
↪   and the final quality judgment in [MLLM DESC]. The
↪   description should logically support the final
↪   quality conclusion. For example, if many serious
↪   problems are described, the final quality should
↪   be "reject"; if minor problems are described, it
↪   should be "usable"; if no or very few problems are
↪   described, it should be "good". Compare with the
↪   reference [GOLDEN DESC] to understand the
↪   expected description-conclusion relationship.
↪   Please rate score 2 for highly consistent
↪   description and conclusion, 1 for partially
↪   consistent with minor logical gaps, and 0 for
↪   major inconsistency between described problems
↪   and quality judgment. Please only provide the
↪   result in the following format: Score:
```

Quality Accuracy Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: Evaluate the accuracy of the final quality
↪   judgment in [MLLM DESC] compared to the reference
↪   [GOLDEN DESC]. The quality levels have a
↪   progressive relationship: reject < usable < good.
↪   Consider the distance between predicted and
↪   reference quality: Please rate score 2 for exactly
↪   matching the reference quality level, 1 for
↪   adjacent level difference (e.g., usable vs good,
↪   or reject vs usable), and 0 for distant level
↪   difference (reject vs good) or completely
↪   incorrect quality assessment. Please only provide
↪   the result in the following format: Score:
```

Complete Evaluation Prompt Templates for No-reference Description Tasks

Completeness Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: Evaluate whether the description [MLLM DESC]
↪   completely includes the low-level visual
↪   information in the reference description [GOLDEN
↪   DESC]. Please rate score 2 for completely or
↪   almost completely including reference information,
↪   0 for not including at all, 1 for including part
↪   of the information or similar description. Please
↪   only provide the result in the following format:
↪   Score:
```

Preciseness Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: The precision metric evaluates whether the
↪   low-level description is consistent with the
↪   reference and reasonably aligned with the final
↪   quality judgment. Minor wording differences or
↪   small omissions that do not change the overall
↪   meaning should still be considered consistent.
↪   Only penalize clear contradictions with the
↪   reference, such as describing blur for clear,
↪   noisy for clean, motion-free for motion artifacts,
↪   noise-free for low-dose noise, etc. Evaluate
↪   whether output [MLLM DESC] reasonably reflects
↪   reference [GOLDEN DESC]. Please rate score 2 for
↪   overall consistency and no major contradictions
↪   with the quality conclusion, 1 for partial
↪   consistency or very few minor contradictions, and
↪   0 for obvious contradictions or misalignment with
↪   the quality conclusion. Please only provide the
↪   result in the following format: Score:
```

Consistency Evaluation Prompt:

```
#System: You are a helpful assistant.
```

Complete Evaluation Prompt Templates for Comparison Description Tasks

Completeness Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: Evaluate whether the description [MLLM DESC]
↪   completely includes the low-level visual
↪   information in the reference description [GOLDEN
↪   DESC]. Please rate score 2 for completely or
↪   almost completely including reference information,
↪   0 for not including at all, 1 for including part
↪   of the information or similar description. Please
↪   only provide the result in the following format:
↪   Score:
```

Preciseness Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: The precision metric evaluates whether the
↪   low-level description is consistent with the
↪   reference and reasonably aligned with the final
↪   quality judgment. Minor wording differences or
↪   small omissions that do not change the overall
↪   meaning should still be considered consistent.
↪   Only penalize clear contradictions with the
↪   reference, such as describing blur for clear,
↪   noisy for clean, motion-free for motion artifacts,
↪   noise-free for low-dose noise, etc. Evaluate
↪   whether output [MLLM DESC] reasonably reflects
↪   reference [GOLDEN DESC]. Please rate score 2 for
↪   overall consistency and no major contradictions
↪   with the quality conclusion, 1 for partial
↪   consistency or very few minor contradictions, and
↪   0 for obvious contradictions or misalignment with
↪   the quality conclusion. Please only provide the
↪   result in the following format: Score:
```

Consistency Evaluation Prompt:

```
#System: You are a helpful assistant.
```

```
#User: Evaluate the internal consistency between the
↪  description path (comparative description of
↪  image problems) and the final quality comparison
↪  judgment in [MLLM DESC]. The description should
↪  logically support the final comparison conclusion.
↪  Compare with the reference [GOLDEN DESC] to
↪  understand the expected description-conclusion
↪  relationship for image comparison. Please rate
↪  score 2 for highly consistent description and
↪  comparison conclusion, 1 for partially consistent
↪  with minor logical gaps, and 0 for major
↪  inconsistency between described comparative
↪  problems and quality comparison judgment. Please
↪  only provide the result in the following format:
↪  Score:
```

Quality Accuracy Evaluation Prompt:

```
#System: You are a helpful assistant.
#User: Evaluate the accuracy of the final quality
↪  comparison judgment in [MLLM DESC] compared to the
↪  reference [GOLDEN DESC]. The comparison should
↪  correctly identify which image has higher quality
↪  based on the described visual characteristics.
↪  Please rate score 2 for exactly matching the
↪  reference quality comparison, and 0 for completely
↪  incorrect quality comparison (opposite conclusion)
↪  or unreasonable assessment. Please only provide
↪  the result in the following format: Score:
```