Soft Sequence Policy Optimization

Abstract

A significant portion of recent research on Large Language Model (LLM) alignment focuses on developing new policy optimization methods based on Group Relative Policy Optimization (GRPO). Two prominent directions have emerged: (i) a shift toward sequence-level importance sampling weights that better align with the sequence-level rewards used in many tasks, and (ii) alternatives to PPO-style clipping that aim to avoid the associated loss of training signal and entropy collapse. We introduce Soft Sequence Policy Optimization, an off-policy reinforcement learning objective that incorporates soft gating functions over token-level probability ratios within sequence-level importance weights. We provide theoretical motivation for SSPO and investigate practical modifications to improve optimization behavior. Empirically, we show that SSPO improves training stability and performance in mathematical reasoning tasks.

1 Introduction

Reinforcement learning (RL) has become a central ingredient in enhancing the reasoning abilities of large language models (LLMs), particularly for tasks requiring long chains of thought (CoT), multi-step decision making, and delayed rewards. While supervised fine-tuning excels at imitating local patterns present in static datasets, RL enables optimization over entire generated sequences, making it especially attractive for complex reasoning, program synthesis, and decision-centric language modeling.

Among modern RL approaches for LLM alignment, group-based policy optimization methods have emerged as a practical and effective strategy. These methods sample multiple candidate responses per input prompt and normalize sequence-level rewards within each group, yielding a reliable prompt value estimate without relying on an auxiliary critic network. Representative algorithms such as Group Relative Policy Optimization (GRPO) (Shao et al., 2024) and REINFORCE Leave-One-Out (RLOO) (Ahmadian et al., 2024) demonstrate that relative comparisons within a group can significantly stabilize training, reduce computational overhead, and improve reasoning performance across a wide range of domains.

Despite their empirical success, existing group-based methods face important limitations when deployed at scale. In particular, off-policy learning becomes unavoidable in realistic training pipelines. As model sizes increase, architectures incorporate sparsity (e.g., Mixture-of-Experts), and generated sequences become longer, large rollout batches are required to fully utilize modern hardware. To improve sample efficiency, these batches are typically partitioned into multiple mini-batches for gradient updates. This practice inevitably induces an off-policy setting, where responses are sampled from a behavior policy while updates are applied to a newer policy, a regime in which GRPO-like algorithms increasingly dominate current practice.

In off-policy group-based optimization, policy updates are usually weighted by importance sampling (IS) ratios between the current and behavior policies. These ratios are well known to suffer from high variance, especially for long sequences where token-level likelihood ratios compound multiplicatively. Uncontrolled IS weights can destabilize training and ultimately degrade performance. Two broad strategies have emerged to mitigate this issue. First, many methods apply hard clipping to large importance weights, limiting their influence on the gradient (Schulman et al., 2017; Shao et al., 2024; MiniMax et al., 2025). While effective at reducing variance, hard clipping introduces a difficult tradeoff: aggressive clipping improves stability but reduces sample efficiency and limits exploration (Chen et al., 2023; Dwyer et al., 2025), whereas loose clipping preserves learning signal at the cost of noisy and brittle updates.

Second, in accordance with insights from RLOO and motivated by the prevalence of sequence-level rewards in LLM alignment (e.g., RLHF and RLVR), recent work proposes enforcing the sequence-level coherence of importance weights rather than treating token-level contributions independently. This perspective motivates objectives such as Group Sequence Policy Optimization (GSPO) (Zheng et al., 2025) and Geometric-Mean Policy Optimization (GMPO) (Zhao et al., 2025), which replace arithmetic aggregation of token-level ratios with multiplicative or geometric formulations that better respect the structure of sequence probabilities. A key innovation of GMPO is the combination of sequence-level weighting with token-level probability ratio clipping.

However, existing solutions remain incomplete. Sequence-coherent objectives, such as GSPO, improve stability but do not fully address the interaction between off-policy learning and entropy-regularized objectives commonly used in modern RL for LLMs. In parallel, soft policy optimization methods — such as Soft Adaptive Policy Optimization (SAPO) (Gao et al., 2025) — highlight the importance of entropy-aware objectives that smoothly interpolate between exploitation and exploration. However, they are not explicitly designed for sequence-level optimization.

In this paper, we propose *Soft Sequence Policy Optimization (SSPO)*, a new off-policy reinforcement learning objective that unifies and extends insights from reward coherent sequence weights and soft policy optimization. SSPO introduces a soft sequence-level weighting mechanism with token-level weight attenuation that controls importance sampling variance without resorting to hard clipping while preserving coherent credit assignment to entire responses. By operating at the sequence level and incorporating entropy-aware regularization, SSPO achieves a more favorable exploration – exploitation tradeoff than prior approaches in off-policy group-based RL.

Our contributions are as follows:

- We analyze the properties of token-wise gate functions when importance weights are aggregated via the geometric mean.

- We propose Soft Sequence Policy Optimization (SSPO), a sequence-level objective with soft clipping for off-policy reinforcement learning.

- We demonstrate improved training stability and performance on mathematical reasoning tasks.

2 Preliminaries

Since we do not modify the additive KL-divergence regularization term in the loss, we omit it for brevity.

Notation Following standard conventions in the literature, an autoregressive language model parameterized by θ is defined by a policy π_θ. x denotes a query and $\mathcal{D}$ denotes the set of queries. Given a response y to a query x, the likelihood of y under the policy π_θ is defined as

$$\pi_\theta(y \mid x) = \prod_{t=1}^{|y|} \pi_\theta(y_t \mid x, y_{<t}),$$

where $|y|$ denotes the number of tokens in y. Each query–response pair (x, y) is assigned a reward $r(x, y)$ by a verifier r.

Throughout this paper, we adopt a compact notation for advantage-dependent clipping operators commonly used in policy optimization objectives. Rather than explicitly writing expressions of the form

$$\min\left(\rho \cdot \widehat{A}, \ \text{clip}(\rho, 1 - \varepsilon_{\text{low}}, 1 + \varepsilon_{\text{high}}) \cdot \widehat{A}\right),$$

we define the advantage-aware clipping function

$$f_{\text{Clip}}(\rho; \widehat{A}) \triangleq \begin{cases} \min(\rho, 1 + \varepsilon_{\text{high}}), & \widehat{A} > 0, \\ \max(\rho, 1 - \varepsilon_{\text{low}}), & \widehat{A} \leq 0, \end{cases} \quad (1)$$

and write the clipped weights compactly as $f_{\text{Clip}}(\rho; \widehat{A}) \cdot \widehat{A}$.

This notation enables a unified presentation of hard and soft clipping mechanisms in the subsequent sections.

Group Relative Policy Optimization Building on Proximal Policy Optimization (PPO) (Schulman et al., 2017), Group Relative Policy Optimization (GRPO) (Shao et al., 2024) enables off-policy learning by leveraging samples generated by an older (behavior) policy $\pi_{\theta_{\text{old}}}$. Following PPO, GRPO employs a clipping mechanism to constrain policy updates within a proximal region around the behavior policy. The key difference is that GRPO replaces computationally and memory-intensive advantage estimators based on a critic network —-

whose reliability may be questionable (Kazemnejad et al., 2025) — with a relative advantage computed among responses to the same query. The GRPO optimization objective is

$$\mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$

$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|y_i|} \sum_{t=1}^{|y_i|} f_{\text{Clip}}(\rho_{i,t}(\theta); \widehat{A}_{i,t}) \cdot \widehat{A}_{i,t} \right]. \quad (2)$$

Here, G denotes the group size, i.e., the number of responses generated for a single query. The importance ratio $\rho_{i,t}(\theta)$ and the advantage $\widehat{A}_{i,t}$ for token $y_{i,t}$ are defined as

$$\rho_{i,t}(\theta) = \frac{\pi_\theta(y_{i,t}|x, y_{i,<t})}{\pi_{\theta_{\text{old}}}(y_{i,t}|x, y_{i,<t})}, \quad (3)$$

$$\widehat{A}_{i,t} = \widehat{A}_i = \frac{r(x, y_i) - \text{mean}\left(\{r(x, y_i)\}_{i=1}^{G}\right)}{\text{std}\left(\{r(x, y_i)\}_{i=1}^{G}\right)}. \quad (4)$$

The notation $\widehat{A}_i = \widehat{A}_{i,t}$ is valid since all tokens in the sequence y_i share the same advantage.

Group Sequence Policy Optimization Group Sequence Policy Optimization (GSPO) (Zheng et al., 2025) identifies a primary problem of GRPO: a mismatch between the unit of optimization and the unit of reward. In GRPO, importance sampling weights for off-policy correction and clipping are applied at the token level, whereas the advantage remains constant across all tokens in a sequence. In contrast, GSPO performs optimization — and in particular clipping — directly at the sequence level. Its objective is given by

$$\mathcal{J}_{\text{GSPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$

$$\left[\frac{1}{G} \sum_{i=1}^{G} f_{\text{Clip}}(s_i(\theta); \widehat{A}_i) \cdot \widehat{A}_i \right], \quad (5)$$

where the importance ratio $s_i(\theta)$ is computed based on the sequence likelihood, with length normalization to control variance (Zheng et al., 2023):

$$s_i(\theta) = \left(\frac{\pi_\theta(y_i|x)}{\pi_{\theta_{\text{old}}}(y_i|x)} \right)^{\frac{1}{|y_i|}} \quad (6)$$

GSPO has been shown to improve training stability for large models and to increase sample efficiency compared to GRPO, although the fraction of clipped tokens grows.

Geometric-Mean Policy Optimization Geometric-Mean Policy Optimization (GMPO) (Zhao et al., 2025) combines response-level importance sampling with token-level probability ratio clipping. GMPO adopts the same sequence-length normalization as GSPO but is motivated by a different intuition: reducing variance in token-level importance sampling weights and sensitivity to outliers by replacing the arithmetic mean over tokens in the GRPO objective with a geometric mean. Specifically, GMPO optimizes the following objective:

$$\mathcal{J}_{\text{GMPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$

$$\left[\frac{1}{G} \sum_{i=1}^{G} \left[\prod_{t=1}^{|y_i|} \left| f_{\text{Clip}}(\rho_{i,t}(\theta); \widehat{A}_i) \right| \right]^{\frac{1}{|y_i|}} \cdot \widehat{A}_i \right]. \quad (7)$$

This geometric aggregation improves robustness to tokens with disproportionately large importance weights and reduces the range of the loss values, leading to more stable updates. The authors further observe that token-level clipping is less aggressive than sequence-level clipping and more effectively constrains the range of importance sampling ratios.

Soft Adaptive Policy Optimization In existing group-based policy optimization methods, high variance in importance sampling weights is typically mitigated through hard clipping. This introduces a trade-off between update stability and sample efficiency and may also reduce exploration abilities. As an alternative, Soft Adaptive Policy Optimization (SAPO) (Gao et al., 2025) employs a smooth, temperature-controlled gating mechanism that preserves the learning signal for all sampled tokens. The SAPO objective is defined as:

$$\mathcal{J}_{\text{SAPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$

$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|y_i|} \sum_{t=1}^{|y_i|} f_{\text{Soft}}(\rho_{i,t}(\theta); \widehat{A}_{i,t}) \cdot \widehat{A}_{i,t} \right], \quad (8)$$

where

$$f_{\text{Soft}}(x; \widehat{A}) = \sigma\left(\tau(\widehat{A}) \cdot (x - 1) \right) \cdot \frac{4}{\tau(\widehat{A})}, \quad (9)$$

$$\tau(\widehat{A}) = \begin{cases} \tau_{\text{pos}}, & \text{if } \widehat{A} > 0 \\ \tau_{\text{neg}}, & \text{otherwise} \end{cases}. \quad (10)$$

Here, τ_{pos} and τ_{neg} denote the temperatures for positive and negative advantages, respectively, and $\sigma(x) = 1/(1 + e^{-x})$ is the sigmoid function.

By construction, the sigmoid-shaped gating function preserves gradients during on-policy updates while remaining bounded. Attenuating the contribution of outlier tokens, rather than truncating it entirely, allows SAPO to maintain informative learning signals throughout training and induces a continuous trust region.

3 Soft Sequence Policy Optimization

While Soft Adaptive Policy Optimization (SAPO) preserves token-level adaptivity through smooth gating, it is sequence-coherent only under two mild assumptions: (i) small policy updates, i.e., $\rho_{i,t}(\theta) \approx 1$, and (ii) low intra-sequence dispersion of importance ratios, $\frac{1}{|y_i|} \sum_{t=1}^{|y_i|} (\log \rho_{i,t}(\theta) - \log s_i(\theta))^2$. These assumptions may be violated in practice, particularly for long sequences or during the early stages of training. We therefore aim to redesign the SAPO objective to relax these assumptions while retaining token-level adaptivity.

In the absence of clipping, the geometric mean of token-wise importance ratios coincides with the length-normalized sequence-level importance ratio used in GSPO. GMPO can therefore be interpreted as a relaxation of sequence-level policy optimization that preserves token-level adaptivity.

Building on this observation, we propose *Soft Sequence Policy Optimization* (SSPO). SSPO aggregates token-level gating functions using a geometric mean, yielding the objective

$$\mathcal{J}_{\text{SSPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \left(\prod_{t=1}^{|y_i|} f\left(\rho_{i,t}(\theta); \widehat{A}_i\right) \right)^{\frac{1}{|y_i|}} \cdot \widehat{A}_i \right]. \quad (11)$$

Here, $f(\cdot; \widehat{A})$ is a non-negative gating function whose properties are specified below.

Gradient Analysis To analyze the optimization behavior of SSPO, we compare its gradient to that of SAPO.

Differentiating the SAPO objective in Eq. (8) with respect to the model parameters θ yields the weighted policy gradient

$$\nabla_\theta \mathcal{J}_{\text{SAPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|y_i|} \sum_{t=1}^{|y_i|} f'_{\text{Soft}}\left(\rho_{i,t}(\theta); \widehat{A}_{i,t}\right) \rho_{i,t}(\theta) \cdot \right.$$
$$\left. \cdot \nabla_\theta \log \pi_\theta(y_{i,t} \mid x, y_{i,<t}) \widehat{A}_{i,t} \right]. \quad (12)$$

For the sigmoid-shaped gate in SAPO,

$$f'_{\text{Soft}}(\rho; \widehat{A}) = 4 g(\rho; \widehat{A})(1 - g(\rho; \widehat{A})), \quad (13)$$
$$g(\rho; \widehat{A}) = \sigma\left(\tau(\widehat{A})(\rho - 1)\right),$$

the derivative peaks at $\rho = 1$ and exponentially decays as ρ deviates from unity, inducing a soft trust region while preserving on-policy behavior.

Differentiating the SSPO objective in Eq. (11) yields

$$\nabla_\theta \mathcal{J}_{\text{SSPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \left(\prod_{t=1}^{|y_i|} f(\rho_{i,t}(\theta); \widehat{A}_i) \right)^{\frac{1}{|y_i|}} \cdot \widehat{A}_i \cdot \right.$$
$$\cdot \frac{1}{|y_i|} \sum_{t=1}^{|y_i|} \frac{f'(\rho_{i,t}(\theta); \widehat{A}_i)}{f(\rho_{i,t}(\theta); \widehat{A}_i)} \rho_{i,t}(\theta)$$
$$\left. \nabla_\theta \log \pi_\theta(y_{i,t} \mid x, y_{i,<t}) \right]. \quad (14)$$

Thus, each token-level policy gradient is modulated by two factors: (i) a sequence-level geometric aggregation of token gates, and (ii) a local soft importance weight defined as $w(\rho; \widehat{A}) \triangleq \frac{f'(\rho; \widehat{A})}{f(\rho; \widehat{A})} \rho$.

Gate Design Motivated by Eq. (14) and the Scopic objective (Chen et al., 2023), we require the gating function family $f(\rho; \widehat{A}) : \mathbb{R}_{++} \to \mathbb{R}_+$ to satisfy the following conditions: (i) f is continuously differentiable; (ii) $f(1; \widehat{A}) = 1$ and $f'(1; \widehat{A}) = 1$; (iii) the local weight multiplier $w(\rho; \widehat{A})$ forms a bell-shaped curve centered at $\rho = 1$ to suppress outlier importance ratios; (iv) f is monotonically non-decreasing.

Condition (ii) ensures that when $\rho_{i,t}(\theta) = 1$, the gradient contribution coincides with the standard on-policy update. Conditions (ii) and (iv) ensure that the gating function preserves the ordinal relationship of the importance ratios, maintaining consistency with sequence-level importance weighting. Condition (iii) enforces controlled attenuation for samples deviating from $\rho = 1$, stabilizing training

by discouraging aggressive updates from off-policy samples. Furthermore, requiring $w(\rho; \widehat{A}) \to 0$ as $\rho \to \infty$ guarantees that samples with extreme importance ratios contribute negligibly to the gradient, effectively mitigating instability caused by heavy-tailed ratio distributions.

We explore two formalizations of condition (iii). The first (iii.1) requires the weight multiplier $\frac{f'}{f}$ to attain a global maximum at $\rho = 1$ and decrease monotonically as ρ deviates from 1, with $\frac{f'}{f} \to 0$ as $\rho \to \infty$. The second (iii.2) imposes the same properties on the full token-wise weight $w(\rho; \widehat{A}) = \frac{f'(\rho; \widehat{A})}{f(\rho; \widehat{A})} \cdot \rho$, adding $w(0; \widehat{A}) = 0$. We discuss the trade-offs between these formulations in Subsection 4.1.

Based on empirical results provided further, we instantiate the gate as

$$f_{\text{SSPO}}(\rho; \widehat{A}) = \exp\left(\tau(\widehat{A}) \cdot \arctan\left(\frac{\log \rho}{\tau(\widehat{A})} \right) \right), \tag{15}$$

where $\tau(\widehat{A})$ is an advantage-dependent temperature. This choice yields a local weight:

$$w(\rho; \widehat{A}) = \frac{1}{1 + \left(\frac{\log \rho}{\tau(\widehat{A})} \right)^2}, \tag{16}$$

which peaks at unity when $\rho = 1$ and decays for large deviations. Consequently, SSPO yields bounded gradients without hard clipping while preserving unbiased on-policy updates. Specifically, the induced weight $w(\rho; \widehat{A})$ urges a Cauchy-shaped attenuation in log-ratio space. Its heavy tails preserve contributions from rather off-policy tokens, while geometric aggregation and a gentle slope simultaneously suppress outliers in sequence-level product.

Other Design Choices A central design challenge in SSPO is balancing update stability and policy expressiveness. Following SAPO, we employ distinct temperatures for positive and negative advantages. To cause the gradients associated with negative advantage tokens to decay more rapidly, $\tau_{\text{neg}} \geqslant \tau_{\text{pos}}$ is set in accordance with the proposed gate behavior. First, DAPO (Yu et al., 2025) demonstrates that relaxing the effective upper bound on policy updates (Clip-Higher) improves exploration and mitigates entropy collapse. Second, negative-advantage tokens are empirically more destabilizing (Gao et al., 2025): their gradients redistribute probability mass toward many unsampled and often irrelevant tokens, whereas positive advantages primarily sharpen the sampled token's logit.

The final SSPO objective is

$$\mathcal{J}_{\text{SSPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, \{y_i\}_{i=1}^G \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$

$$\left[\frac{1}{G} \sum_{i=1}^G \left(\prod_{t=1}^{|y_i|} f_{\text{SSPO}}\left(\rho_{i,t}(\theta); \widehat{A}_i \right) \right)^{\frac{1}{|y_i|}} \cdot \widehat{A}_i \right]. \tag{17}$$

4 Experiments

4.1 Gate options

Let $\tau_{\widehat{A}} := \tau(\widehat{A})$ for brevity. We evaluate several candidate non-negative gating functions $f(\rho; \widehat{A})$ that satisfy the on-policy constraints $f(1; \widehat{A}) = 1$ and $f'(1; \widehat{A}) = 1$, but differ in how they suppress off-policy ratios:

$$f_{\text{expsig}}(\rho; \widehat{A}) = \exp\left(4\tau_{\widehat{A}} \cdot \sigma(\tfrac{\rho-1}{\tau_{\widehat{A}}}) - 2\tau_{\widehat{A}} \right), \tag{18}$$

$$f_{\text{expatan}}(\rho; \widehat{A}) = \exp\left(\tau_{\widehat{A}} \cdot \arctan(\tfrac{\rho-1}{\tau_{\widehat{A}}}) \right), \tag{19}$$

$$f_{\text{Gumbel}}(\rho) = \exp\left(-\exp(-(\rho-1)) + 1 \right), \tag{20}$$

$$f_{\text{atanlog}}(\rho; \widehat{A}) = \exp\left(\tau_{\widehat{A}} \cdot \arctan(\tfrac{\log \rho}{\tau_{\widehat{A}}}) \right), \tag{21}$$

$$f_{\text{siglog}}(\rho; \widehat{A}) = \exp\left(4\tau_{\widehat{A}} \cdot \sigma(\tfrac{\log \rho}{\tau_{\widehat{A}}}) - 2\tau_{\widehat{A}} \right). \tag{22}$$

We group these gates by the formalization of the condition (iii) they satisfy. Gates f_{expsig} and f_{expatan} enforce unimodality on the ratio-level multiplier $\frac{f'(\rho; \widehat{A})}{f(\rho; \widehat{A})}$ (condition (iii.1)). In contrast, f_{Gumbel}, f_{atanlog}, and f_{siglog} enforce unimodality on the full token-wise weight $w(\rho; \widehat{A})$ (condition (iii.2)).

Figure 1 visualizes (i) how each $f(\cdot)$ affects the sequence-level geometric aggregation and (ii) the corresponding token-wise attenuation profiles. All gates behave close to the identity in a neighborhood of $\rho = 1$, preserving on-policy updates.

The gate f_{Gumbel} is parameter-free: it cannot be temperature-parameterized while simultaneously preserving the on-policy constraints above and maintaining the requirement (iii). Empirically, this makes it a strong "no-extra-hyperparameters" baseline among SSPO gates.

4.2 Experimental Setup

We fine-tune Qwen2.5-7B-Instruct from a cold-start initialization. We focus on mathematical reasoning tasks with verifiable outcome-level rewards.

Figure 1: Visualization of gating functions and their induced weight multipliers. The first column shows the effect of the gate on sequence-level ratios; all gates behave close to the identity function near $\rho = 1$. The second column highlights gates satisfying condition (iii.1), while the third column emphasizes gates satisfying condition (iii.2).

Training data The training dataset comprises problems from GSM8K (Cobbe et al., 2021) and DeepMath-103K (He et al., 2025). GSM8K contains curated grade-school math problems requiring multi-step reasoning. DeepMath-103K spans a diverse spectrum of mathematical subjects, including algebra, calculus, number theory, geometry, probability, and discrete mathematics, providing problems of widely varying difficulty.

As for the reward, we use $r = r_{\text{answer}} + r_{\text{format}}$, where $r_{\text{answer}} = \mathbb{I}[\hat{a} = a]$ and $\hat{a}$ is extracted from the response between special tokens `<answer>` and `</answer>`. The formatting reward encourages the template `<think>` $\cdots$ `</think>` `<answer>` $\cdots$ `</answer>`. $r_{\text{format}} \in \{1, 0.5, 0.25, 0\}$ with scores assigned as fully correct format/ correct edge tokens (both) / correct edge (either) / otherwise.

We implement all algorithms with the Hugging Face TRL library. SSPO is compared against GRPO, GMPO, and SAPO. We use the standard GRPO and SAPO trainers provided in TRL and implement GMPO as a lightweight modification of the GRPO trainer.

Hyperparameters We use group size $G = 8$ responses per prompt and the maximum completion length of 512 tokens. We do not apply the KL regularization term and update the reference policy every 2 steps. Clipping hyperparameters are selected via grid search: ε for GRPO and GMPO in $\{0.1, 0.2, 0.3\}$; $(\tau_{\text{neg}}, \tau_{\text{pos}})$ for SAPO in

$\{(1, 1.05), (3, 4), (7, 8)\}$; and $(\tau_{\text{neg}}, \tau_{\text{pos}})$ for each SSPO gate in $\{(0.3, 0.2), (0.6, 0.5)\}$. Unless noted otherwise, we report results for the best configuration per method.

Evaluation protocol We report Pass@1 on GSM8K test set (Cobbe et al., 2021), MATH-500 (Lightman et al., 2023), and AIME 2025. For evaluation, we use zero-shot prompting and greedy decoding for all models. We extract and verify the final answer using the same procedure as in training.

4.3 Results

Table 1 reports Pass@1 on three math reasoning benchmarks. For each method, we evaluate the checkpoint that achieves the highest average training reward.

Across all objectives, fine-tuning improves over the base Qwen2.5-7B-Instruct model. Among the baselines, GMPO is the strongest overall: it improves performance at GSM8K from 77.9 to 88.8 (+10.9), MATH-500 from 56.6 to 65.0 (+8.4), and at AIME 2025 from 10.0 to 13.3 (+3.3), corresponding to one additional solved problem.

SSPO improves upon GMPO on all three benchmarks. The best-performing instantiation, SSPO with the f_{atanlog} gate, reaches 91.6 on GSM8K, 66.6 on MATH-500, and 20.0 on AIME 2025, yielding an average absolute improvement of +11.2 points over the base model. Compared to GMPO,

Model	GSM8K	MATH-500	AIME 2025	Δ Avg
Qwen2.5-7B-Instruct	77.9	56.6	10.0	–
+ GRPO	84.5	64.2	10.0	+4.7
+ GMPO	*88.8*	*65.0*	*13.3*	+7.5
+ SAPO	82.8	58.6	10.0	+2.3
+ SSPO (f_{expsig})	89.2	64.8	16.7	+8.7
+ SSPO (f_{expatan})	89.6	65.8	16.7	+9.2
+ SSPO (f_{Gumbel})	88.9	63.8	16.7	+8.3
+ SSPO (f_{siglog})	88.9	64.8	16.7	+8.8
+ SSPO (f_{atanlog})	**91.6**	**66.6**	**20.0**	**+11.2**

Table 1: Pass@1 on mathematical reasoning benchmarks. Responses are generated with temperature 0 using zero-shot prompting. The best results are shown in bold, the second-best are underlined and the strongest baseline in italics. Δ Avg reports the average absolute improvement over the base model across the three benchmarks.

this corresponds to +2.8 on GSM8K, +1.6 on MATH-500, and +6.7 on AIME 2025.

Notably, the relative gains are largest on AIME 2025, the most difficult benchmark in our suite: SSPO increases Pass@1 from 13.3 to 20.0 (i.e., from 4/30 to 6/30 solved problems). This is consistent with our motivation that sequence-level geometric aggregation combined with token-level soft weighting is particularly beneficial when long, high-variance reasoning trajectories make off-policy updates less stable.

4.4 Discussion

Figure 2 shows the smoothed training reward and token entropy for the best hyperparameter setting of each method. We observe that SAPO may suffer from reward collapse in our setting, whereas SSPO maintains stable learning dynamics and achieves consistently higher rewards throughout training.

Gate choice introduces two largely independent design axes. The first is defined by bell-shaped multiplier: on the ratio-level multiplier $\frac{f'}{f}$ (formalization (iii.1)) versus on the full token-wise weight $w(\rho) = \frac{f'}{f}\rho$ with $w(0) = 0$ (formalization (iii.2)). The second is the attenuation profile: sigmoid-based gates suppress off-policy tokens with exponentially decaying weights as the (log-)ratio deviates from 1, whereas arctan-based gates induce a Cauchy-shaped attenuation in log-ratio space with heavier tails.

Empirically, arctan-based gates are more robust than sigmoid-based gates across benchmarks. We hypothesize that this behavior reflects a better trade-off: the sequence-level geometric aggregation in SSPO already reduces sensitivity to extreme out-

Figure 2: Training curves for reward and entropy. Values are reported after exponential smoothing with $\alpha = 0.02$ for best configurations of each objective selected by grid search.

liers, so a heavier-tailed token gate can retain useful learning signal from quite off-policy tokens without destabilizing updates. In contrast, aggressively down-weighting such tokens can reduce effective sample reuse and slow down improvement on harder problems.

Overall, these findings support our hypothesis that combining sequence-level geometric aggregation with heavy-tailed token-wise gating yields a more favorable stability–efficiency trade-off for off-

policy sequence optimization.

5 Related Works

Group-based policy optimization has become a strong baseline for reinforcement learning with large language models, particularly in alignment and reasoning tasks. Methods such as GRPO (Shao et al., 2024) and RLOO (Ahmadian et al., 2024) estimate advantages by sampling multiple responses per prompt and computing relative rewards within each group, avoiding an auxiliary critic network. GRPO further enables off-policy updates leveraging importance-weighted updates, making it a practical default in large-scale RL pipelines and inducing various modifications (Yu et al., 2025; Liu et al., 2025b,a).

In realistic training setups, off-policy learning is unavoidable due to large rollout buffers and mini-batch gradient steps. However, applying token-level importance sampling ratios to sequence-level rewards introduces a policy–reward mismatch that can destabilize training. Recent work addresses this issue by enforcing sequence-level coherence in policy updates. GSPO (Zheng et al., 2025) and GMPO (Zhao et al., 2025) substitute arithmetic mean of token-level ratios with sequence-consistent formulations, improving stability and variance control.

Hard clipping of importance ratios, originally introduced in PPO (Schulman et al., 2017), remains a common strategy for variance reduction in off-policy optimization (Shao et al., 2024; MiniMax et al., 2025). While effective, clipping induces a fundamental bias–variance tradeoff: aggressive clipping improves stability but harms sample efficiency and exploration, whereas loose clipping leads to noisy updates (Chen et al., 2023; Dwyer et al., 2025). Several works explore alternatives, including asymmetric clipping (Yu et al., 2025) and gradient-preserving approaches (Su et al., 2025a), but these methods remain sensitive to hyperparameters.

An alternative line of work advocates for soft, entropy-aware objectives that avoid hard clipping. SAPO (Gao et al., 2025) and related soft trust-region methods (Dwyer et al., 2025) demonstrate improved robustness in off-policy settings by smoothly attenuating large importance ratios. Recent work also explores global soft constraints on policy distributions, such as Entropy Ratio Clipping (Su et al., 2025b), which uses the ratio of policy entropies between updates to constrain distributional drift beyond standard importance clipping. However, these approaches are primarily developed for token-level objectives and do not explicitly address sequence-level credit assignment in group-based learning.

6 Conclusion

We introduced Soft Sequence Policy Optimization (SSPO), a sequence-level objective for off-policy reinforcement learning fine-tuning of LLMs. SSPO aligns the unit of reward with the unit of importance correction by aggregating token-wise gates through a geometric mean, yielding a length-normalized sequence update while retaining token-level adaptivity. We analyzed the resulting gradients and derived practical design criteria for non-negative, monotone, differentiable gates that preserve on-policy behavior and softly down-weight outlier importance ratios. Empirically, SSPO improves training stability and consistently outperforms strong group-based baselines on verifiable mathematical reasoning benchmarks. Overall, our findings suggest that combining sequence-level geometric aggregation with heavy-tailed bounded token gating provides a favorable stability-efficiency trade-off for off-policy sequence optimization. Future work includes scaling SSPO to larger and mixture-of-experts models, extending evaluation beyond mathematical reasoning, and studying robustness to verifier noise and alternative reward designs.

Limitations

This work proposes a modification of policy gradient objectives for off-policy reinforcement learning in LLMs. The design of the objective assumes sequence-level rewards assigned to the full generated response. While this setting aligns with many RLHF and RLVR setups, the current formulation is not directly tailored for settings with fine-grained or token-level reward models.

Our empirical study focuses on mathematical reasoning benchmarks with verifiable rewards and thus reflects a limited domain; evaluating SSPO on other complex-reasoning settings (e.g., code generation and multimodal tasks) is necessary to assess generality. In addition, SSPO introduces gate and temperature choices that require hyperparameter tuning: while we observe robustness across several gate variants in our experiments, a more systematic sensitivity analysis remains an important direction for future work.

References

Arash Ahmadian, Chris Cremer, Matthias Gallé, Marzieh Fadaee, Julia Kreutzer, Olivier Pietquin, Ahmet Üstün, and Sara Hooker. 2024. Back to basics: Revisiting reinforce-style optimization for learning from human feedback in llms. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12248–12267.

Xing Chen, Dongcui Diao, Hechang Chen, Hengshuai Yao, Haiyin Piao, Zhixiao Sun, Zhiwei Yang, Randy Goebel, Bei Jiang, and Yi Chang. 2023. The sufficiency of off-policyness and soft clipping: Ppo is still insufficient according to an off-policy measure. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pages 7078–7086.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Madeleine Dwyer, Adam Sobey, and Adriane Chapman. 2025. It's not you, it's clipping: A soft trust-region via probability smoothing for llm rl. *Preprint*, arXiv:2509.21282.

Chang Gao, Chujie Zheng, Xiong-Hui Chen, Kai Dang, Shixuan Liu, Bowen Yu, An Yang, Shuai Bai, Jingren Zhou, and Junyang Lin. 2025. Soft adaptive policy optimization. *Preprint*, arXiv:2511.20347.

Zhiwei He, Tian Liang, Jiahao Xu, Qiuzhi Liu, Xingyu Chen, Yue Wang, Linfeng Song, Dian Yu, Zhenwen Liang, Wenxuan Wang, Zhuosheng Zhang, Rui Wang, Zhaopeng Tu, Haitao Mi, and Dong Yu. 2025. Deepmath-103k: A large-scale, challenging, decontaminated, and verifiable mathematical dataset for advancing reasoning. *Preprint*, arXiv:2504.11456.

Amirhossein Kazemnejad, Milad Aghajohari, Eva Portelance, Alessandro Sordoni, Siva Reddy, Aaron Courville, and Nicolas Le Roux. 2025. Vineppo: Refining credit assignment in rl training of llms. *Preprint*, arXiv:2410.01679.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's verify step by step. In *The twelfth international conference on learning representations*.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025a. Understanding r1-zero-like training: A critical perspective. *Preprint*, arXiv:2503.20783.

Zihe Liu, Jiashun Liu, Yancheng He, Weixun Wang, Jiaheng Liu, Ling Pan, Xinyu Hu, Shaopan Xiong, Ju Huang, Jian Hu, Shengyi Huang, Johan Obando-Ceron, Siran Yang, Jiamang Wang, Wenbo Su, and Bo Zheng. 2025b. Part i: Tricks or traps? a deep dive into rl for llm reasoning. *Preprint*, arXiv:2508.08221.

MiniMax, :, Aili Chen, Aonian Li, Bangwei Gong, Binyang Jiang, Bo Fei, Bo Yang, Boji Shan, Changqing Yu, Chao Wang, Cheng Zhu, Chengjun Xiao, Chengyu Du, Chi Zhang, Chu Qiao, Chunhao Zhang, Chunhui Du, Congchao Guo, and 109 others. 2025. Minimax-m1: Scaling test-time compute efficiently with lightning attention. *Preprint*, arXiv:2506.13585.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *Preprint*, arXiv:1707.06347.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.

Zhenpeng Su, Leiyu Pan, Minxuan Lv, Yuntao Li, Wenping Hu, Fuzheng Zhang, Kun Gai, and Guorui Zhou. 2025a. Ce-gppo: Coordinating entropy via gradient-preserving clipping policy optimization in reinforcement learning. *Preprint*, arXiv:2509.20712.

Zhenpeng Su, Leiyu Pan, Minxuan Lv, Tiehua Mei, Zijia Lin, Yuntao Li, Wenping Hu, Ruiming Tang, Kun Gai, and Guorui Zhou. 2025b. Entropy ratio clipping as a soft global constraint for stable reinforcement learning. *Preprint*, arXiv:2512.05591.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, and 16 others. 2025. Dapo: An open-source llm reinforcement learning system at scale. *Preprint*, arXiv:2503.14476.

Yuzhong Zhao, Yue Liu, Junpeng Liu, Jingye Chen, Xun Wu, Yaru Hao, Tengchao Lv, Shaohan Huang, Lei Cui, Qixiang Ye, Fang Wan, and Furu Wei. 2025. Geometric-mean policy optimization. *Preprint*, arXiv:2507.20673.

Chujie Zheng, Pei Ke, Zheng Zhang, and Minlie Huang. 2023. Click: Controllable text generation with sequence likelihood contrastive learning. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 1022–1040.

Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong Liu, Rui Men, An Yang, Jingren Zhou, and Junyang Lin. 2025. Group sequence policy optimization. *Preprint*, arXiv:2507.18071.