LEARNING AND EVALUATING REPRESENTATIONS FOR DEEP ONE-CLASS CLASSIFICATION

ABSTRACT

We present a two-stage framework for deep one-class classification. We first learn self-supervised representations from one-class data, and then build classifiers using generative or discriminative models on learned representations. In particular, we present a novel distribution-augmented contrastive learning that extends training distributions via data augmentation to obstruct the uniformity of vanilla contrastive representations, yielding more suitable representations for one-class classification. Moreover, we argue that classifiers inspired by the statistical perspective in generative or discriminative models are more effective than existing approaches, such as an average of normality scores from a surrogate classifier. In experiments, we demonstrate state-of-the-art performance on visual domain one-class classification benchmarks. The framework does not only learn a better representation, but it also permits building one-class classifiers that are more faithful to the target task. Finally, we present visual explanations, confirming that the decision-making process of our deep one-class classifier is intuitive to humans.

1 INTRODUCTION

One-class classification aims to identify if an example belongs to the same distribution as the training data. There are several applications of one-class classification, such as anomaly detection or outlier detection, where we learn a classifier that distinguishes the anomaly/outlier data without access to them from the normal/inlier data accessible at training. The data could come from various domains, such as industrial manufacturing (defect detection), finance (fraudulent transaction detection), etc.

Generative models, such as kernel density estimation (KDE), have been popular for one-class classification [1, 2] as they model the distribution by assigning high density to the training data. At test time, low density examples are determined as outliers. Unfortunately, the curse of dimensionality hinders estimating the density of the high-dimensional data accurately [3]. Deep generative models (e.g. [4, 5, 6]), have demonstrated success in modeling high-dimensional data (e.g., images) and have been applied to anomaly detection [7, 8, 9, 10, 11]. However, learning deep generative models on raw inputs remains as challenging as they appear to assign high density to background pixels [10] or learn local pixel correlations [12]. A good representation might still be beneficial to those models.

Alternately, discriminative models like one-class SVM (OC-SVM) [13] or support vector data description (SVDD) [14] learn classifiers describing the support of one-class distributions to distinguish them from outliers. Specifically, these methods become more powerful with non-linear kernel functions that implicitly transform the raw data into a high-dimensional feature space. However, the performance of discriminative models is still limited by the quality of data representations.

The fundamental limitation of one-class classification centers on learning good high-level data representations. Following the success of deep learning [15], deep one-class classifications [16, 17, 18], which extend the discriminative one-class classification using trainable deep neural networks, have shown promising results compared to their kernel counterparts. However, a naive training of deep one-class classifiers leads to a degenerate solution that maps all data into a single representation, also known as "hypersphere collapse" [16]. Previous works circumvent such issues by constraining network architectures [16], autoencoder pretraining [16, 17], training with a surrogate multi-class classification loss by introducing simulated outliers [19, 20, 21, 22] or injecting noise [18].

In this work, we present a two-stage framework for building deep one-class classifiers. As shown in Figure 1, in the first stage, we train a deep neural network to obtain a high-level data representation.

(a) Self-supervised representation learning   (b) One-class classifier

Figure 1: Overview of our two-stage framework for building deep one-class classifier. (a) In the first stage, we learn representations from one-class training distribution using self-supervised learning methods, and (b) in the second stage, we train one-class classifiers using learned representations.

Then, in the second stage, we build a one-class classifier, such as OC-SVM or KDE, using representations from the first stage. Comparing to those using surrogate losses [20, 21], our framework allows to build a classifier that is more faithful to one-class classification. Decoupling representation learning from classifier construction further opens up opportunities of using state-of-the-art representation learning methods, such as self-supervised contrastive learning [23]. While vanilla contrastive representations are less compatible with one-class classification as they are uniformly distributed on the hypersphere [24], we show that, with proper fixes, it provides representations achieving competitive one-class classification performance to previous state-of-the-arts. Furthermore, we propose a distribution-augmented contrastive learning, a novel variant of contrastive learning with distribution augmentation [25]. This is particularly effective in learning representations for one-class classification, as it reduces the class collision between examples from the same class [26] and uniformity [24]. Lastly, although representations are not optimized for one-class classification as in end-to-end trainable deep one-class classifiers [16], we demonstrate state-of-the-art performance on visual one-class classification benchmarks. We summarize our contributions as follows:

- We present a two-stage framework for building deep one-class classifiers using unsupervised and self-supervised representations followed by shallow one-class classifiers.
- We systematically study representation learning methods for one-class classification, including augmentation prediction, contrastive learning, and the proposed distribution-augmented contrastive learning method that extends training data distributions via data augmentation.
- We show that, with a good representation, both discriminative (OC-SVM) and generative (KDE) classifiers, while being competitive with each other, are better than surrogate classifiers based on the simulated outliers [20, 21].
- We achieve strong performance on visual one-class classification benchmarks, such as CIFAR-10/100 [27], Fashion MNIST [28], Cat-vs-Dog [29] and CelebA [30]. In addition to comprehensive analysis on one-class contrastive learning, we present visual explanations of self-supervised deep one-class classifiers to better understand their decision making processes.

2   A Two-stage Framework for Deep One-Class Classification

In Section 2.1, we review self-supervised representation learning algorithms, discuss how they connect to existing one-class classification methods, raise issues of state-of-the-art contrastive representation learning [23] for one-class classification, and propose ways to resolve these issues. Then, in Section 2.2, we study how to leverage the learned representations for one-class classification.

2.1   Learning Representations for One-Class Classification

Let $\mathcal{A}$ be the stochastic data augmentation process, which is composed of resize and crop, horizontal flip, color jittering, gray-scale and gaussian blur, following [23], for image data. As in Figure 1, self-supervised learning methods consist of a feature extractor f parameterized by deep neural networks and the proxy loss $\mathcal{L}$. Below, we discuss details of different self-supervised learning methods.

2.1.1   Augmentation Prediction

One popular method for learning representations learns by discriminating the type of augmentation applied to the data. Rotation prediction [31], which is one of the most representative of kinds, learns deep representations by predicting the degree of rotation augmentations. The training objective of the rotation prediction proxy task is written as follows:

$$\mathcal{L}_{\text{rot}} = \mathbb{E}_{x \sim P_{\mathcal{X}}, \mathcal{A}} \Big[\text{CrossEntropy} \big(y, p_{q \circ f} \big(y | \text{rot90} \left(\mathcal{A}(x), y \right) \big) \big) \Big] \tag{1}$$

	Proxy Task	Normality Score at Test Time (x_t)
Golan and El-Yaniv [20] Hendrycks et al. [21]	$\mathcal{L}_{\text{rot}}$	$p_q\left(0|f(x_t)\right)$ or $\sum_{y\in\{0,1,2,3\}} p_q\left(y|f(\text{rot90}(x_t,y))\right)$
Ours	$\mathcal{L}_{\text{rot}}, \mathcal{L}_{\text{clr}}, \mathcal{L}_{\text{clr}}^{\text{distaug}}, ...$	$\text{KDE}\left(f(x_t)\right)$ or $\text{OC-SVM}\left(f(x_t)\right)$

Table 1: A comparison between one-class classifiers based on self-supervised learning. Previous works [20, 21] train one-class classifiers using augmentation prediction with geometric transformations (e.g. $\mathcal{L}_{\text{rot}}$) and determine outliers using augmentation classifiers (p_q). We learn representations using proxy tasks of different self-supervised learning methods, such as contrastive learning $(\mathcal{L}_{\text{clr}})$, and build simple one-class classifiers, such as KDE or OC-SVM, on learned inlier representations.

where $y \in \{0, 1, 2, 3\}$ is a prediction target representing the rotation degree, and $\text{rot90}(x, y)$ rotates an input x by 90 degree y times. We represent the classifier $p_{q \circ f}(y|x)$ as $p_q(y|f(x)) \propto \exp(q \circ f(x))[y]$ which contains the representation f and a linear layer q with 4 output units for rotation degrees. The learned network f yields a good representation for classification tasks [31].

Application to One-Class Classification. While proposed for learning representations, augmentation prediction has been successfully adopted to learn deep one-class classifiers [20, 21, 22]. Although it is not trained to do so, the likelihood of learned rotation classifiers[1] $p_q(y=0|f(x))$ is shown to well approximate normality score. Plausible explanation is via outlier exposure [19], where the classifier learns a decision boundary distinguishing original images from simulated outliers created by image rotation. However, it assumes inlier images are not rotated. Moreover, the classifier may not generalize to one-class classification task if it overfits to the proxy task (e.g., rotation prediction).

2.1.2 CONTRASTIVE LEARNING

Unlike augmentation prediction that learns discriminative representations to data augmentation, contrastive learning [23] learns representation by distinguishing different views (e.g., augmentations) of itself from other data instances. Let $\phi(x) = \text{normalize}(f(x))$, i.e., $\|\phi(x)\| = 1$. Following the formulation of [32], the proxy task loss of contrastive learning is written as:

$$\mathcal{L}_{\text{clr}} = -\mathbb{E}_{x,x_i \sim P_{\mathcal{X}}, \mathcal{A}, \mathcal{A}'}\left[\log \frac{\exp\left(\frac{1}{\tau}\phi(\mathcal{A}(x))^\top\phi(\mathcal{A}'(x))\right)}{\exp\left(\frac{1}{\tau}\phi(\mathcal{A}(x))^\top\phi(\mathcal{A}'(x))\right) + \sum_{i=1}^{M-1}\exp\left(\frac{1}{\tau}\phi(\mathcal{A}(x))^\top\phi(\mathcal{A}(x_i))\right)}\right] \quad (2)$$

where $\mathcal{A}$ and $\mathcal{A}'$ are identical but independent stochastic augmentation processes for two different views of x. $\mathcal{L}_{\text{clr}}$ regularizes representations of the same instance with different views $(\mathcal{A}(x), \mathcal{A}'(x))$ to be similar, while those of different instances $(\mathcal{A}(x), \mathcal{A}'(x'))$ to be unlike.

Class Collision and Uniformity for One-Class Classification. While contrastive representations have achieved state-of-the-art performance on visual recognition tasks [23, 24, 33, 34] and have been theoretically proved to be effective for multi-class classification [26, 35], we argue that it could be problematic for one-class classification.

First, a class collision [26]. The contrastive loss in Equation (2) is minimized by *maximizing* the distance between representations of negative pairs $(x, x_i), x \neq x_i$, even though they are from the same class when applied to the one-class classification. This seems to contradict to the idea of deep one-class classification [16], which learns representations by *minimizing* the distance between representations with respect to the center: $\min_f \mathbb{E}_x\|f(x) - c\|^2$.

Second, a uniformity of representations [24]. It is proved that the optimal solution for the denominator of Equation (2) is *perfect uniformity* as $M \to \infty$ [24], meaning that $\phi(x)$ follows a uniform distribution on the hypersphere. This is problematic since one can always find an inlier $x \in \mathcal{X}$ in the proximity to any outlier $x' \notin \mathcal{X}$ on the hypersphere, as shown in Figure 2a. In contrast, with reduced uniformity as in Figure 2b, it is easier to isolate outliers from inliers.

One-Class Contrastive Learning. First, to reduce the uniformity of representations, we propose to use a moderate M (batch size). This is in contrast with previous suggestions to train with large M for contrastive representations to be most effective on multi-class classification tasks [23, 34, 36]. The impact of batch size M for one-class classification will be discussed in Section 5.1.

---

[1]For presentation clarity, we use the rotation as an example for augmentations. Note that one may use more geometric transformations, such as rotation, translation, or flip of an image, as in [20, 21, 22].

(a) Perfect uniformity. (b) Reduced uniformity. (c) Distribution augmentation.

Figure 2: One-class classification on different levels of uniformity of inlier distributions. (a) When representations are uniform, isolating outliers is hard. (b) Reducing uniformity makes boundary between inlier and outlier clear. (c) Distribution augmentation allows inlier distribution more compact.

Figure 3: Distribution-augmented contrastive learning. Not only learning to discriminate different instances from an original distribution (e.g., two images of different dogs on the left), it also learns to discriminate instances from different distributions created via augmentations, such as rotations (e.g., two images of the same dog with different rotation degrees on the top).

In addition, we propose *distribution augmentation*[2] for one-class contrastive learning. The idea is that, instead of modeling the training data distribution $P_\mathcal{X}$, we model the union of augmented training distribution $P_{\bigcup_a a(\mathcal{X})}$, where $a(\mathcal{X}) = \{a(x) | x \in \mathcal{X}\}$. Note that augmentation a for augmenting distribution is disjoint from those for data augmentation $\mathcal{A}$ that generates views. Inspired by Golan and El-Yaniv [20], we employ geometric transformations, such as rotation or horizontal flip, for distribution augmentation. For example, as in Figure 3, x and $\mathrm{rot}90(x)$ (German shepherds in the top row) are considered as two separate instances and therefore are encouraged to be distant in the representation space. Not only increasing the number of data instances to train on (e.g., distribution augmentation by rotating $90°, 180°, 270°$ increases the dataset by 4 times), but it also eases the uniformity of representations on the resulted hypersphere. A pictorial example is in Figure 2c, where thanks to augmented distribution, the inlier distribution may become more compact.

2.1.3 EXTRACTING RICHER REPRESENTATION BY LEARNING WITH PROJECTION HEAD

Self-supervised representations are prone to overfitting to the proxy task. Gidaris et al. [31] show that f is not the best representation for downstream tasks as f becomes overly discriminative to augmentation prediction while losing useful information of the data. Lower-layer representations are suggested for downstream tasks. While the output of f trained by contrastive loss has been theoretically proven to be useful for multi-class classification [26, 35, 37], the efficacy of projection head parameterized by MLP has been confirmed in practice [23, 38].

The effect of projection heads may be explained from the information theory perspective. To illustrate, we extend the network structure of augmentation prediction as $q \circ g \circ f$, where q is the linear classification head, g is the projection head, and f outputs self-supervised representations used for downstream tasks. We note that using an identity head $g(x) = x$ recovers the network structure of previous works [20, 21, 31]. The data processing inequality [39] $I(g \circ f(x); x) \le I(f(x); x)$ tells that f can retain more information than g, thus more suitable for downstream tasks that are not necessarily correlated with the proxy tasks. The effectiveness of deep MLP projection head is empirically shown for both augmentation prediction and contrastive learning in Section 4.

2.2 BUILDING DEEP ONE-CLASS CLASSIFIERS WITH LEARNED REPRESENTATIONS

We present a two-stage framework for deep one-class classification that builds one-class classifiers on learned representations as in Figure 1. Compared to end-to-end training [16, 20, 21, 22], our

---

[2]We note that the distribution augmentation has been applied to generative modeling [25] as a way of improving regularization and generalization via multi-task learning.

framework provides flexibility in using various representations as the classifier is not bound to representation learning. It also allows the classifier consistent with one-class classification objective.

To construct a classifier, we revisit an old wisdom which considers the full spectrum of the distribution of the learned data representation. For generative approaches, we propose to use nonparametric kernel density estimation (KDE) to estimate densities from learned representations. For discriminative approaches, we train one-class SVMs [13]. Both methods work as a black-box and in experiment we use the default training setting except the kernel width where we reduce by 10 times than default. We provide detailed classifier formulations in Appendix A.1.

2.2.1 GRADIENT-BASED EXPLANATION OF DEEP ONE-CLASS CLASSIFIER

Explaining the decision making process helps users to trust deep learning models. There have been efforts to visually explain the reason for model decisions of multi-class classifiers [40, 41, 42, 43, 44, 45, 46] using the gradients computed from the classifier. In this work, we introduce a gradient-based visual explanation of one-class classification that works for any deep representations. To construct an end-to-end differentiable decision function, we employ a KDE detector, whose formulation is in Appendix A.1, built on top of any differentiable deep representations: $\frac{\partial \mathrm{KDE}(f(x))}{\partial x} = \frac{\partial \mathrm{KDE}(f(x))}{\partial f(x)} \frac{\partial f(x)}{\partial x}$.

3 RELATED WORK

One-class classification [47] has broad use cases, including fraud detection [48], spam filtering [49], medical diagnosis [50], manufacturing defect detection [51], to name a few. Due to the lack of granular semantic information for one-class data, methods for learning from unlabeled data have been employed for one-class classification. Generative models, which model the density of training data distribution, are able to determine outlier when the sample shows low density [8, 50, 52]. These include simple methods such as kernel density estimation or mixture models [53], as well as advanced ones [4, 5, 6, 54, 55, 56, 57]. However, the density from generative models for high-dimensional data could be misleading [9, 12, 58, 59]. New detection mechanisms based on the typicality [60] or likelihood ratios [10] have been proposed to improve out-of-distribution detection.

Self-supervised learning is commonly used for learning representations from unlabeled data by solving proxy tasks, such as jigsaw puzzle [61], rotation prediction [31], clustering [62], instance discrimination [63] and contrastive learning [23, 33, 64]. The learned representations are then used for multi-class classification, or transfer learning, all of which require labeled data for downstream tasks. They have also been extended to one-class classification. For example, contrastive learning is adopted to improve the out-of-distribution detection under multi-class setting [65], whereas our work focuses on learning from a single class of examples, leading to propose a novel distribution-augmented contrastive learning. Notably, learning to predict geometric transformations [20, 21, 22] extends the rotation prediction [31] to using more geometric transformations as prediction targets. Unlike typical applications of self-supervised learning where the classifier or projection head [23] are discarded after training, the geometric transformation classifier is used as a surrogate for one-class classification. As in Section 4.1, however, the surrogate classifier optimized for the self-supervised proxy task is suboptimal for one-class classification. We show that replacing it with simple one-class classifiers consistently improve the performance. Furthermore, we propose strategies for better representation learning for both augmentation prediction and contrastive learning.

Distribution-augmented contrastive learning is concurrently developed in [66] as a part of their multi-task ensemble model. While sharing a similar technical formulation, we motivate from fixing the uniformity of contrastive representations. We note that our study not only focuses on representation learning, but also on the importance of detection algorithms, which is under explored before.

4 EXPERIMENTS

Following Golan and El-Yaniv [20], we evaluate on one-class classification benchmarks, including CIFAR-10, CIFAR-100[3] [27], Fashion-MNIST [28], and Cat-vs-Dog [29]. Images from one class are given as inlier and those from remaining classes are given as outlier. We further propose a new protocol using CelebA eyeglasses dataset [30], where face images with eyeglasses are denoted as an outlier. It is more challenging since the difference between in and outlier samples is finer-grained. We resize images into $64{\times}64$ for cat-vs-dog and CelebA datasets and $32{\times}32$ for the rest.

---

[3]20 super class labels are used for CIFAR-100 experiments [20].

Representation	Classifier	CIFAR-10	CIFAR-100	f-MNIST	Cat-vs-Dog	CelebA	Mean
ResNet-50 (ImageNet)	OC-SVM	80.0	83.7	91.8	74.5	81.4	84.0
	KDE	80.0	83.7	90.5	74.6	82.4	83.7
RotNet [20]	Rotation Classifier	$86.8_{\pm 0.4}$	$80.3_{\pm 0.5}$	$87.4_{\pm 1.7}$	$86.1_{\pm 0.3}$	$51.4_{\pm 3.9}$	83.1
	KDE	$89.3_{\pm 0.3}$	$81.9_{\pm 0.5}$	$94.6_{\pm 0.3}$	$86.4_{\pm 0.2}$	$77.4_{\pm 1.0}$	86.6
Denoising	OC-SVM	$83.4_{\pm 1.0}$	$75.2_{\pm 1.0}$	$93.9_{\pm 0.4}$	$57.3_{\pm 1.3}$	$66.8_{\pm 0.9}$	80.4
	KDE	$83.5_{\pm 1.0}$	$75.2_{\pm 1.0}$	$93.7_{\pm 0.4}$	$57.3_{\pm 1.3}$	$67.0_{\pm 0.7}$	80.4
Rotation Prediction	OC-SVM	$90.8_{\pm 0.3}$	$82.8_{\pm 0.6}$	$94.6_{\pm 0.3}$	$83.7_{\pm 0.6}$	$65.8_{\pm 0.9}$	87.1
	KDE	$91.3_{\pm 0.3}$	$84.1_{\pm 0.6}$	$\mathbf{95.8}_{\pm 0.3}$	$86.4_{\pm 0.6}$	$69.5_{\pm 1.7}$	88.2
Contrastive	OC-SVM	$89.0_{\pm 0.7}$	$82.4_{\pm 0.8}$	$93.9_{\pm 0.3}$	$87.7_{\pm 0.5}$	$83.5_{\pm 2.4}$	86.9
	KDE	$89.0_{\pm 0.7}$	$82.4_{\pm 0.8}$	$93.6_{\pm 0.3}$	$87.7_{\pm 0.4}$	$84.6_{\pm 2.5}$	86.8
Contrastive (DA)	OC-SVM	$\mathbf{92.5}_{\pm 0.6}$	$\mathbf{86.5}_{\pm 0.7}$	$94.8_{\pm 0.3}$	$\mathbf{89.6}_{\pm 0.5}$	$84.5_{\pm 1.1}$	$\mathbf{89.9}$
	KDE	$92.4_{\pm 0.7}$	$\mathbf{86.5}_{\pm 0.7}$	$94.5_{\pm 0.4}$	$\mathbf{89.6}_{\pm 0.4}$	$85.6_{\pm 0.5}$	$\mathbf{89.8}$

Table 2: We report the mean and standard deviation of one-class classification AUCs averaged over classes over 5 runs. The best methods are bold-faced for each setting. The per-class AUCs are reported in Appendix A.4. All methods are implemented and evaluated under the same condition.

	CIFAR-10	CIFAR-100	f-MNIST	cat-vs-dog
Ruff et al. [16]	64.8	–	–	–
Golan and El-Yaniv [20][†]	86.0	78.7	93.5	88.8
Bergman and Hoshen [22][†]	88.2	–	94.1	–
Hendrycks et al. [21][†]	90.1	–	–	–
Huang et al. [52][†]	86.6	78.8	93.9	–
Ours: Rotation prediction	$91.3_{\pm 0.3}$	$84.1_{\pm 0.6}$	$\mathbf{95.8}_{\pm 0.3}$	$86.4_{\pm 0.6}$
Ours: Contrastive (DA)	$\mathbf{92.5}_{\pm 0.6}$	$\mathbf{86.5}_{\pm 0.7}$	$94.8_{\pm 0.3}$	$\mathbf{89.6}_{\pm 0.5}$

Table 3: Comparison to previous works on one-class classification. [†] denotes evaluation methods using test time data augmentation. Our methods are both more accurate and computationally efficient.

We evaluate the performance of (1) representations trained with unsupervised and self-supervised learning methods, including denoising autoencoder [67], rotation prediction [31], contrastive learning [23, 63], and (2) using different one-class classifiers, such as OC-SVM or KDE. We use rotation augmentations for distribution-augmented contrastive learning, denoted as Contrastive (DA). We train a ResNet-18 [68] for feature extractor f and a stack of linear, batch normalization, and ReLU, for MLP projection head g. More experiment details can be found in Appendix A.3.

4.1 MAIN RESULTS

We report the mean and standard deviation of AUCs averaged over classes over 5 runs in Table 2. The mean of 5 datasets is weighted by the number of classes for each dataset. Besides those using self-supervised representations, we provide results using ImageNet pretrained ResNet-50 to highlight the importance of learning representations from in-domain distribution.

ImageNet pretrained ResNet-50 achieves the best performance of 84.0 mean AUC over 5 datasets. Compared to representations learned with denoising objective, it works particularly well on datasets such as CIFAR-100, cat-vs-dog, and CelebA, which we attribute it to the subset of ImaegNet classes is closely related to the classes of these datasets.

Similar to the findings from [20, 21], we observe significant performance gains with self-supervised learning. Moreover, while RotNet [20], an end-to-end trained classifier using rotation prediction, achieves 83.1 AUC, the RotNet *representation* evaluated with the *KDE detector* achieves 86.6, emphasizing the importance of a proper detector in the second stage. Finally, the quality of RotNet representation improves when trained with the MLP projection head, resulting in 88.2 AUC.

The representations learned with vanilla contrastive loss achieve 86.9 AUC with OC-SVM, which under-perform those trained with rotation prediction loss (88.2). The distribution-augmented contrastive loss achieves the highest mean AUC of $\mathbf{89.9}$ among all methods, demonstrating performance gains on all datasets by a large margin upon its vanilla counterparts.

Comparison to Previous Works. We make comparisons to previous works in Table 3. While some comparisons may not be apples-to-apples as different works use different implementations of networks, optimizers, etc., we note that our implementation is based on the common choices of network (e.g., ResNet-18) and optimizer (e.g., momentum SGD) for image classification. We advance the previous state-of-the-art on one-class classification benchmarks by a large margin without test-time augmentation nor ensemble of models. We further improve the performance with model ensemble, which we report in Appendix A.2.2.

(a) MMDs with various batch sizes. (b) AUCs with various batch sizes. (c) AUCs with various MLP depths.

Figure 4: Ablation study of contrastive representations trained with different batch sizes. We use (a) the MMD distance between the representations and the data sampled from uniform distributions to measure uniformity. Small MMD distance means being similar to uniform distribution. We also report (b) one-class classification performance in AUCs evaluated by kernel OC-SVMs and (c) the performance with MLP heads of different depths.

5 ANALYSIS AND ABLATION STUDY

In Section 5.1, we analyze behaviors of one-class contrastive representations and in Section 5.3, we report visual explanations of various deep one-class classifiers. Due to a space constraint, more studies, including an in-depth study on distribution-augmented contrastive representations and data efficiency of self-supervised learning for one-class classification, are in Appendix A.2.

5.1 UNIFORMITY, BATCH SIZE AND DISTRIBUTION AUGMENTATION

[23, 33, 34, 36] have shown substantial improvement on contrastive representations evaluated on multi-class classification using very large batch sizes, which results in uniformity. However, uniformity [24] and class collision [26] can be an issue for one-class classification as discussed in Section 2.1.2. Here we investigate the relations between performance and uniformity, and how we can resolve the issue via batch size, MLP head and distribution-augmented contrastive learning.

We measure the uniformity via MMD distance [69] between the learned representation and samples from uniform distributions on hyperspheres. Smaller MMD distance implies the distribution of representation is closer to uniform distributions. We train models with various batch sizes $\{2^3, \ldots, 2^9\}$. We report in Figure 4 the average and standard deviation over 5 runs on CIFAR-10 validation set.

Distribution Augmentation. In Figure 4a, the representations from the projection head $g \circ f$ trained by standard contrastive learning (Contrastive $g \circ f$) are closer to be uniformly distributed when we increase the batch size as proven by [24]. Therefore, in one-class classification, the nearly uniformly distributed representation from contrastive learning is only slightly better than random guess (50 AUC) as in Figure 4b. In contrast, with distribution augmentations, the learned representations (Contrastive (DA) $g \circ f$) are less uniformly distributed and result in a significant performance gain.

Batch Size. Following the discussion, large batch sizes result in nearly uniformly distributed representations ($g \circ f$), which is harmful to the one-class classification. On the other hand, small batch sizes (≤ 16), though less uniform, hinders us learning useful representations via information maximization [70]. As in Figure 4b, there is a trade-off of batch size for one-class classification, and we find batch size of 32 results in the best one-class classification performance.

MLP Projection Head. As discussed in Section 2.1.3, f, an input to projection head, contains no less information than the output $g \circ f$, but overfits less to the proxy task. As in Figure 4a, f's are not at all uniformly distributed and results in significantly better performance than $g \circ f$, as in Figure 4b.

Lastly, we emphasize that all these fixes contribute to an improvement of contrastive representations for one-class classification. As in Figure 4 AUC drops when any of these components are missing.

5.2 ANALYSIS ON DIFFERENT DISTRIBUTION AUGMENTATIONS

The choice of distributions affects the performance. The ablation study using horizontal flip (hflip) and rotation augmentations is reported in Figure 6. Note that hflip is used only to augment distribution in this experiment. Interestingly, simply adding hflip improves the AUC to 90.7. This suggests a different insight from [66] who augments distribution as a means to outlier exposure [19]. Although we report the numbers with rotation augmentations in Table 2, with hflip, rot90, rot90+hflip as

(a) Input   (b) Ours   (c) RotNet   (d) RotNet*   (e) DAE   (f) Ours   (g) RotNet   (h) RotNet*   (i) DAE

Figure 5: Visual explanations of deep one-class classifiers on cat-vs-dog and CelebA eyeglasses datasets. (a) input images, (b–e) images with heatmaps using integrated gradients [44], and (f–i) those using GradCAM [43]. RotNet*: RotNet + KDE. More examples are in Appendix A.5.

Figure 6: AUCs of contrastive representations trained from various augmented distributions on CIFAR-10. From left to right, we train by accumulating distributions. For example, an entry with "+rot90, hflip" is trained with 4 distributions, i.e., original, hflip, rot90 and rot90, hflip.

augmented distributions, we achieve the best mean AUC, 93.7, on CIFAR-10, without any test-time augmentation. Additional study on distribution augmentation follows in Appendix A.2.2.

5.3 VISUAL EXPLANATION OF DEEP ONE-CLASS CLASSIFIERS

We investigate the decision making process of our deep one-class classifiers using the tools described in Section 2.2.1. Specifically, we inspect by highlighting the most influential regions using two popular visual explanation algorithms, namely, integrated gradients (IG) [44] and GradCAM [43], for distribution-augmented contrastive representation, as well as RotNet and DAE on images from cat-vs-dog and CelebA eyeglasses datasets. For RotNet, we test using both a rotation classifier and KDE (RotNet* in Figure 5) to compute gradients.

As in Figure 5, the proposed visual explanation method based on the KDE one-class classifier permits highlighting human-intuitive, meaningful regions in the images, such as dog faces or eyeglasses instead of spurious background regions (Figure 5b). On the other hand, even though the classification AUC is not too worse (86.1 AUC on cat-vs-dog as opposed to 89.6 for ours), the visual explanation based on the rotation classifier (Figure 5c) suggests that the decision may be made sometimes based on the spurious features (e.g., human face in the background). We present more examples for visual explanation in Appendix A.5.

6 CONCLUSION

Inspired by an old wisdom of learning representations followed by building classifiers, we present a two-stage framework for deep one-class classification. We emphasize the importance of decoupling building classifiers from learning representations, which allows classifier to be consistent with the target task, one-class classification. Moreover, it permits applications of various self-supervised representation learning methods, including contrastive learning [23] with proper fixes, for one-class classification, achieving strong performance on visual one-class classification benchmarks. Finally, we exhibit visual explanation capability of our two-stage self-supervised deep one-class classifiers.

REFERENCES

[1] Markus M Breunig, Hans-Peter Kriegel, Raymond T Ng, and Jörg Sander. Lof: identifying density-based local outliers. In *Proceedings of the 2000 ACM SIGMOD international conference on Management of data*, pages 93–104, 2000. 1

[2] Longin Jan Latecki, Aleksandar Lazarevic, and Dragoljub Pokrajac. Outlier detection with kernel density functions. In *International Workshop on Machine Learning and Data Mining in Pattern Recognition*, pages 61–75. Springer, 2007. 1

[3] Alexandre B Tsybakov. *Introduction to nonparametric estimation*. Springer Science & Business Media, 2008. 1, 13

[4] Aäron Van Den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning-Volume 48*, pages 1747–1756, 2016. 1, 5

[5] Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in neural information processing systems*, pages 10215–10224, 2018. 1, 5

[6] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013. 1, 5

[7] Shuangfei Zhai, Yu Cheng, Weining Lu, and Zhongfei Zhang. Deep structured energy based models for anomaly detection. *arXiv preprint arXiv:1605.07717*, 2016. 1

[8] Bo Zong, Qi Song, Martin Renqiang Min, Wei Cheng, Cristian Lumezanu, Daeki Cho, and Haifeng Chen. Deep autoencoding gaussian mixture model for unsupervised anomaly detection. In *International Conference on Learning Representations*, 2018. 1, 5

[9] Hyunsun Choi, Eric Jang, and Alexander A Alemi. Waic, but why? generative ensembles for robust anomaly detection. *arXiv preprint arXiv:1810.01392*, 2018. 1, 5

[10] Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pages 14707–14718, 2019. 1, 5

[11] Warren R Morningstar, Cusuh Ham, Andrew G Gallagher, Balaji Lakshminarayanan, Alexander A Alemi, and Joshua V Dillon. Density of states estimation for out-of-distribution detection. *arXiv preprint arXiv:2006.09273*, 2020. 1

[12] Polina Kirichenko, Pavel Izmailov, and Andrew Gordon Wilson. Why normalizing flows fail to detect out-of-distribution data. *arXiv preprint arXiv:2006.08545*, 2020. 1, 5

[13] Bernhard Schölkopf, Robert C Williamson, Alex J Smola, John Shawe-Taylor, and John C Platt. Support vector method for novelty detection. In *Advances in neural information processing systems*, pages 582–588, 2000. 1, 5, 13

[14] David MJ Tax and Robert PW Duin. Support vector data description. *Machine learning*, 54 (1):45–66, 2004. 1

[15] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015. 1

[16] Lukas Ruff, Robert Vandermeulen, Nico Goernitz, Lucas Deecke, Shoaib Ahmed Siddiqui, Alexander Binder, Emmanuel Müller, and Marius Kloft. Deep one-class classification. In *International conference on machine learning*, pages 4393–4402, 2018. 1, 2, 3, 4, 6

[17] Raghavendra Chalapathy, Aditya Krishna Menon, and Sanjay Chawla. Anomaly detection using one-class neural networks. *arXiv preprint arXiv:1802.06360*, 2018. 1

[18] Poojan Oza and Vishal M Patel. One-class convolutional neural network. *IEEE Signal Processing Letters*, 26(2):277–281, 2018. 1

[19] Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*, 2018. 1, 3, 7, 14

[20] Izhak Golan and Ran El-Yaniv. Deep anomaly detection using geometric transformations. In *Advances in Neural Information Processing Systems*, pages 9758–9769, 2018. 1, 2, 3, 4, 5, 6, 13, 14, 15, 16, 17

[21] Dan Hendrycks, Mantas Mazeika, Saurav Kadavath, and Dawn Song. Using self-supervised learning can improve model robustness and uncertainty. In *Advances in Neural Information Processing Systems*, pages 15637–15648, 2019. 1, 2, 3, 4, 5, 6, 14

[22] Liron Bergman and Yedid Hoshen. Classification-based anomaly detection for general data. In *Eighth International Conference on Learning Representations*, 2020. 1, 3, 4, 5, 6, 14

[23] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*, 2020. 2, 3, 4, 5, 6, 7, 8, 13

[24] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. *arXiv preprint arXiv:2005.10242*, 2020. 2, 3, 7

[25] Heewoo Jun, Rewon Child, Mark Chen, John Schulman, Aditya Ramesh, Alec Radford, and Ilya Sutskever. Distribution augmentation for generative modeling. In *Proceedings of Machine Learning and Systems 2020*, pages 10563–10576, 2020. 2, 4

[26] Nikunj Saunshi, Orestis Plevrakis, Sanjeev Arora, Mikhail Khodak, and Hrishikesh Khande-parkar. A theoretical analysis of contrastive unsupervised representation learning. In *International Conference on Machine Learning*, pages 5628–5637, 2019. 2, 3, 4, 7

[27] Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009. 2, 5

[28] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017. 2, 5

[29] Jeremy Elson, John R Douceur, Jon Howell, and Jared Saul. Asirra: a captcha that exploits interest-aligned manual image categorization. In *ACM Conference on Computer and Communications Security*, volume 7, pages 366–374, 2007. 2, 5

[30] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pages 3730–3738, 2015. 2, 5

[31] Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. In *Sixth International Conference on Learning Representations*, 2018. 2, 3, 4, 5, 6

[32] Kihyuk Sohn. Improved deep metric learning with multi-class n-pair loss objective. In *Advances in neural information processing systems*, pages 1857–1865, 2016. 3

[33] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018. 3, 5, 7

[34] Olivier J Hénaff, Aravind Srinivas, Jeffrey De Fauw, Ali Razavi, Carl Doersch, SM Eslami, and Aaron van den Oord. Data-efficient image recognition with contrastive predictive coding. *arXiv preprint arXiv:1905.09272*, 2019. 3, 7

[35] Christopher Tosh, Akshay Krishnamurthy, and Daniel Hsu. Contrastive learning, multi-view redundancy, and linear models. *arXiv preprint arXiv:2008.10150*, 2020. 3, 4, 13

[36] Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. In *Advances in Neural Information Processing Systems*, pages 15535–15545, 2019. 3, 7

[37] Jason D Lee, Qi Lei, Nikunj Saunshi, and Jiacheng Zhuo. Predicting what you already know helps: Provable self-supervised learning. *arXiv preprint arXiv:2008.01064*, 2020. 4

[38] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020. 4

[39] Thomas M Cover. *Elements of information theory*. John Wiley & Sons, 1999. 4

[40] Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pages 818–833. Springer, 2014. 5

[41] Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10(7):e0130140, 2015. 5

[42] Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2921–2929, 2016. 5

[43] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017. 5, 8, 17, 18, 19, 20

[44] Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pages 3319–3328, 2017. 5, 8, 17, 18, 19, 20

[45] Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Advances in Neural Information Processing Systems*, pages 9505–9515, 2018. 5

[46] Andrei Kapishnikov, Tolga Bolukbasi, Fernanda Viégas, and Michael Terry. Xrai: Better attributions through regions. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 4948–4957, 2019. 5

[47] Mary M Moya, Mark W Koch, and Larry D Hostetler. One-class classifier networks for target recognition applications. *STIN*, 93:24043, 1993. 5

[48] Clifton Phua, Vincent Lee, Kate Smith, and Ross Gayler. A comprehensive survey of data mining-based fraud detection research. *arXiv preprint arXiv:1009.6119*, 2010. 5

[49] Igor Santos, Carlos Laorden, Xabier Ugarte-Pedrero, Borja Sanz, and Pablo G Bringas. Spam filtering through anomaly detection. In *International Conference on E-Business and Telecommunications*, pages 203–216. Springer, 2011. 5

[50] Thomas Schlegl, Philipp Seeböck, Sebastian M Waldstein, Ursula Schmidt-Erfurth, and Georg Langs. Unsupervised anomaly detection with generative adversarial networks to guide marker discovery. In *International conference on information processing in medical imaging*, pages 146–157. Springer, 2017. 5

[51] Paul Bergmann, Michael Fauser, David Sattlegger, and Carsten Steger. Mvtec ad–a comprehensive real-world dataset for unsupervised anomaly detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9592–9600, 2019. 5

[52] Chaoqing Huang, Jinkun Cao, Fei Ye, Maosen Li, Ya Zhang, and Cewu Lu. Inverse-transform autoencoder for anomaly detection. *arXiv preprint arXiv:1911.10676*, 2019. 5, 6

[53] Christopher M Bishop. *Pattern recognition and machine learning*. springer, 2006. 5

[54] Yoshua Bengio, Pascal Lamblin, Dan Popovici, and Hugo Larochelle. Greedy layer-wise training of deep networks. In *Advances in neural information processing systems*, pages 153–160, 2007. 5

[55] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014. 5

[56] Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. In *Advances in neural information processing systems*, pages 4790–4798, 2016. 5

[57] Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016. 5

[58] Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? *arXiv preprint arXiv:1810.09136*, 2018. 5

[59] Vít Škvára, Tomáš Pevnỳ, and Václav Šmídl. Are generative deep models for novelty detection truly better? *arXiv preprint arXiv:1807.05027*, 2018. 5

[60] Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, and Balaji Lakshminarayanan. Detecting out-of-distribution inputs to deep generative models using a test for typicality. *arXiv preprint arXiv:1906.02994*, 5, 2019. 5

[61] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pages 69–84. Springer, 2016. 5

[62] Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 132–149, 2018. 5

[63] Mang Ye, Xu Zhang, Pong C Yuen, and Shih-Fu Chang. Unsupervised embedding learning via invariant and spreading instance feature. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 6210–6219, 2019. 5, 6

[64] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020. 5

[65] Jim Winkens, Rudy Bunel, Abhijit Guha Roy, Robert Stanforth, Vivek Natarajan, Joseph R Ledsam, Patricia MacWilliams, Pushmeet Kohli, Alan Karthikesalingam, Simon Kohl, et al. Contrastive training for improved out-of-distribution detection. *arXiv preprint arXiv:2007.05566*, 2020. 5

[66] Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. *arXiv preprint arXiv:2007.08176*, 2020. 5, 7, 14

[67] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th international conference on Machine learning*, pages 1096–1103, 2008. 6

[68] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016. 6

[69] Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012. 7

[70] Ben Poole, Sherjil Ozair, Aaron Van Den Oord, Alex Alemi, and George Tucker. On variational bounds of mutual information. In *International Conference on Machine Learning*, pages 5171–5180, 2019. 7

[71] Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial intelligence and statistics*, pages 370–378, 2016. 13

[72] Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabás Póczos. Mmd gan: Towards deeper understanding of moment matching network. In *Advances in Neural Information Processing Systems*, pages 2203–2213, 2017. 13

[73] Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *Fifth International Conference on Learning Representations*, 2017. 15

[74] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011. 15

[75] Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 16)*, pages 265–283, 2016. 16

A APPENDIX

A.1 FORMULATIONS OF ONE-CLASS CLASSIFIERS

For completeness, we provide formulations of one-class classifiers, such as one-class support vector machine (OC-SVM) [13] and kernel density estimator, used in our work.

One-Class Support Vector Machine solves the following optimization problem to find support vectors describing the boundary of one-class distribution:

$$\min_{w,\rho,\xi_i} \frac{\|w\|^2}{2} + \frac{1}{\nu n} \sum_{i=1}^{n} \xi_i - \rho \tag{3}$$

$$\text{subject to } w^\top f_i \geq \rho - \xi_i, \, \xi_i \geq 0, \forall i = 1, \cdots, n \tag{4}$$

where $f_i = f(x_i)$ is a feature map. The decision score is given as follows:

$$s(x) = \sum_{i=1}^{n} \alpha_i k(x_i, x) - \rho \tag{5}$$

with coefficients $\alpha_i > 0$ for support vectors. Linear or RBF ($k_\gamma(x, y) = \exp\left(-\gamma\|x - y\|^2\right)$) kernels are used for experiments.

Kernel Density Estimation is a nonparametric density estimation algorithm. The normality score of KDE with RBF kernel parameter γ is written as follows:

$$\text{KDE}_\gamma(x) = \frac{1}{\gamma} \log \Big[\sum_y \exp\left(-\gamma\|x - y\|^2\right) \Big] \tag{6}$$

A.2 ADDITIONAL ABLATION STUDY

A.2.1 WELL BEHAVED CONTRASTIVE REPRESENTATION

Linear Separability. A common belief is the good representations are linearly separable with respect to some underlying labels, which is supported by several empirical success [23]. The linear classifiers are proven to be nearly optimal [35] when we learn representations on data with *all possible labels* along with some additional assumptions. In one-class classification, although we violate the assumptions that we only train on one class of data, we are interested in the linear separability of the data to understand the characteristics of the learned embedding. To this end, in addition to training RBF kernel OC-SVM, we train OC-SVM with linear kernels on the learned embedding. We note that it is atypical to use linear OC-SVM, which is usually considered to be suboptimal for describing decision boundaries of one-class classification problems. However, with good representations, linear classifiers show good performance on one-class classification as shown in Table 4, and are better than existing works [20] in Table 2. Lastly, we note that OC-SVM with nonlinear RBF kernel is still better than linear models in Table 4. Similar observations are found in other problems such as regression [71] and generative models [72].

Parametric Models. In addition to studying from the perspective of discriminative model, we also dive into the generative model side. Instead of using the nonparametric KDE for density estimation, we use a parametric model, single multivariate Gaussian, whose density is defined as

$$p(x) \propto \det\left(\Sigma\right)^{-\frac{1}{2}} \exp\left\{ -\frac{1}{2}(f(x) - \mu)^\top \Sigma^{-1}(f(x) - \mu)\right\}. \tag{7}$$

A shown in Table 4, the Gaussian density estimation (GDE) model shows competitive performance as KDE. It suggests the learned representations from distribution-augmented contrastive learning is *compact* as our expectation, which can be well approximated by a simple parametric model with single Gaussian. Compared with nonparametric methods, although parametric models have strong assumptions on the underlying data distributions, using parametric model is more data efficient if the assumption holds[4]. In addition, parametric models have huge advantage in computation during

---

[4]The error convergence rate is $O(n^{-1/2})$, while that of nonparametric KDE is $O(n^{-1/d})$ [3].

testing. Therefore, there is trade-off between assumptions of the data as well as model flexibility and computational efficiency. We note that the single Gaussian parametric model may not be a good alternative of KDE universally. A candidate with good trade-off is Gaussian Mixture Models, which can be treated as a middle ground of nonparametric KDE and parametric single Gaussian model. We leave the study for future works.

Representation	Classifier	CIFAR-10	CIFAR-100	f-MNIST	Cat-vs-Dog	CelebA	Mean
Contrastive (DA)	OC-SVM (linear)	$90.7_{\pm0.8}$	$81.1_{\pm1.3}$	$93.7_{\pm0.8}$	$86.3_{\pm0.7}$	$88.4_{\pm1.4}$	86.7
	OC-SVM (kernel)	$\mathbf{92.5}_{\pm0.6}$	$\mathbf{86.5}_{\pm0.7}$	$94.8_{\pm0.3}$	$\mathbf{89.6}_{\pm0.5}$	$84.5_{\pm1.1}$	**89.9**
	KDE	$92.4_{\pm0.7}$	$\mathbf{86.5}_{\pm0.7}$	$94.5_{\pm0.4}$	$\mathbf{89.6}_{\pm0.4}$	$85.6_{\pm0.5}$	89.8
	GDE	$92.0_{\pm0.5}$	$86.0_{\pm0.8}$	$\mathbf{95.5}_{\pm0.3}$	$88.9_{\pm0.3}$	$90.6_{\pm0.4}$	89.8

Table 4: One-class classification results using different one-class classifiers on rotation-augmented contrastive representations. In addition to OC-SVM and KDE, both of which with RBF kernels, we test with the linear OC-SVM and the Gaussian density estimator (GDE).

A.2.2 ANALYSIS ON DISTRIBUTION AUGMENTED CONTRASTIVE REPRESENTATIONS

Relation to Outlier Exposure [19]. Distribution augmentation shares a similarity to outlier exposure [19] in that both methods introduce new data distributions for training. However, outlier exposure requires a stronger assumption on the data distribution that introduced outlier should not overlap with inlier distribution, while such an assumption is not required for distribution augmentation. For example, let's consider rotation prediction as an instance of outlier exposure. When training the model on randomly-rotated CIFAR-10, where we randomly rotate images of CIFAR-10, the performance of rotation prediction representation drops to 60.7 AUC, which is slightly better than a random guess. On the other hand, rotation-augmented contrastive representation is not affected by random rotation and achieves 92.4 AUC.

Ensemble of Contrastive Representations. We note that most previous methods have demonstrated improved performance via extensive test-time data augmentation [20, 21, 22, 66]. While already achieving state-of-the-art one-class classification performance without test-time data augmentation, we observe marginal improvement using test time data augmentation. Instead, we find that an ensemble of classifiers built on different representations significantly improve the performance. In Table 5, we report the performance of distribution-augmented contrastive representations trained with different sets of augmented distributions on CIFAR-10. We observe that ensemble of 5 models trained with different seeds consistently improves the performance. Moreover, not only we improve one-class classification AUCs when aggregating scores across models trained with different distribution augmentations, we also observe lower standard deviation across different seeds. Finally, when ensemble over $5\times5 = 25$ models, we achieve 94.6 AUC.

Representations	+hflip,+rot90	+rot90,hflip	+rot180	+rot180,hflip	+rot270	Ensemble of 5
single model	$93.1_{\pm0.4}$	$93.7_{\pm0.6}$	$93.6_{\pm0.4}$	$93.5_{\pm0.5}$	$93.1_{\pm0.8}$	$\mathbf{94.4}_{\pm0.2}$
ensemble of 5 models	93.9	94.4	94.3	94.2	93.9	**94.6**

Table 5: Performance of single and ensemble models of distribution augmented contrastive representations on CIFAR-10. For each augmented distribution, we report the mean and standard deviation of single model performance ("single model") and that of ensemble model whose ensemble score is aggregated from 5 models trained with different random seeds ("ensemble of 5 models"). "Ensemble of 5" aggregates score from 5 models with different augmentation distributions.

A.2.3 DATA EFFICIENCY OF SELF-SUPERVISED REPRESENTATION LEARNING

While previous works on self-supervised learning have demonstrated the effectiveness on learning from large-scale unlabeled data, not much has shown for the data efficiency of these methods. Unlike multi-class classification tasks where the amount of data could scale multiplicative with the number of classes, data efficiency of representation learning becomes of particular interest for one-class classification as it is hard to collect large-scale data even without an annotation.

We present one-class classification AUCs of representations with various training data sizes, along with two baseline representations such as ResNet-18 using random weights or ImageNet-pretrained

Figure 7: Self-supervised representations are trained from different data sizes, from 50 to 5000, on CIFAR-10. Standard deviations are obtained by sampling subsets 5 times. Classifiers are trained with the full (5000) train set for fair evaluation of representations. We provide baseline representations of ResNet-18 using random weights and ImageNet-pretrained ResNet-50. Standard deviations are computed by running 5 times with different seeds.

ResNet-50 in Figure 7. Note that we vary the training set sizes at representation learning phase only, but use a fixed amount (5000) to train classifiers for fair evaluation of the representation quality. We find that even with 50 examples, classifiers benefit from self-supervised learning when comparing against raw or deep features with random weights. The proposed distribution-augmented contrastive loss could match the performance of ImageNet-pretrained ResNet-50 with only 100 examples, while rotation prediction loss and vanilla contrastive loss require 250 and 1000 examples, respectively.

Representation	Classifier	CIFAR-10	CIFAR-100	f-MNIST	cat-vs-dog	CelebA	Mean
ResNet-18 (Random)	OC-SVM (linear)	$50.1_{\pm0.9}$	$50.1_{\pm1.7}$	$50.3_{\pm0.9}$	$50.0_{\pm0.4}$	$49.9_{\pm0.3}$	50.1
	OC-SVM (kernel)	$61.2_{\pm2.3}$	$59.6_{\pm1.9}$	$89.8_{\pm0.9}$	$50.7_{\pm0.5}$	$57.1_{\pm0.6}$	66.5
	KDE	$60.5_{\pm2.4}$	$58.7_{\pm2.2}$	$89.4_{\pm1.0}$	$50.8_{\pm0.6}$	$57.3_{\pm0.8}$	65.9
ResNet-50 (ImageNet)	OC-SVM (linear)	67.9	71.0	77.0	61.0	58.0	70.9
	OC-SVM (kernel)	80.0	83.7	91.8	74.5	81.4	84.0
	KDE	80.0	83.7	90.5	74.6	82.4	83.7
RotNet [20]	Rotation Classifier	$86.8_{\pm0.4}$	$80.3_{\pm0.5}$	$87.4_{\pm1.7}$	$86.1_{\pm0.3}$	$51.4_{\pm3.9}$	83.1
	KDE	$89.3_{\pm0.3}$	$81.9_{\pm0.5}$	$94.6_{\pm0.3}$	$86.4_{\pm0.2}$	$77.4_{\pm1.0}$	86.6
Denoising	OC-SVM (linear)	$72.6_{\pm1.8}$	$62.4_{\pm2.1}$	$55.0_{\pm3.9}$	$61.0_{\pm1.5}$	$59.8_{\pm4.0}$	62.9
	OC-SVM (kernel)	$83.4_{\pm1.0}$	$75.2_{\pm1.0}$	$93.9_{\pm0.4}$	$57.3_{\pm1.3}$	$66.8_{\pm0.9}$	80.4
	KDE	$83.5_{\pm1.0}$	$75.2_{\pm1.0}$	$93.7_{\pm0.4}$	$57.3_{\pm1.3}$	$67.0_{\pm0.7}$	80.4
Rotation Prediction	OC-SVM (linear)	$88.5_{\pm0.8}$	$72.3_{\pm1.7}$	$89.0_{\pm1.5}$	$81.4_{\pm1.4}$	$62.6_{\pm4.1}$	80.1
	OC-SVM (kernel)	$90.8_{\pm0.3}$	$82.8_{\pm0.6}$	$94.6_{\pm0.3}$	$83.7_{\pm0.6}$	$65.8_{\pm0.9}$	87.1
	KDE	$91.3_{\pm0.3}$	$84.1_{\pm0.6}$	$\mathbf{95.8}_{\pm0.3}$	$86.4_{\pm0.6}$	$69.5_{\pm1.7}$	88.2
Contrastive	OC-SVM (linear)	$85.6_{\pm1.2}$	$74.9_{\pm1.4}$	$92.3_{\pm1.1}$	$82.8_{\pm1.1}$	$\mathbf{91.7}_{\pm0.7}$	82.2
	OC-SVM (kernel)	$89.0_{\pm0.7}$	$82.4_{\pm0.8}$	$93.9_{\pm0.3}$	$87.7_{\pm0.5}$	$83.5_{\pm2.4}$	86.9
	KDE	$89.0_{\pm0.7}$	$82.4_{\pm0.8}$	$93.6_{\pm0.3}$	$87.7_{\pm0.4}$	$84.6_{\pm2.5}$	86.8
Contrastive (DA)	OC-SVM (linear)	$90.7_{\pm0.8}$	$81.1_{\pm1.3}$	$93.7_{\pm0.8}$	$86.3_{\pm0.7}$	$88.4_{\pm1.4}$	86.7
	OC-SVM (kernel)	$\mathbf{92.5}_{\pm0.6}$	$\mathbf{86.5}_{\pm0.7}$	$94.8_{\pm0.3}$	$\mathbf{89.6}_{\pm0.5}$	$84.5_{\pm1.1}$	$\mathbf{89.9}$
	KDE	$\mathbf{92.4}_{\pm0.7}$	$\mathbf{86.5}_{\pm0.7}$	$94.5_{\pm0.4}$	$\mathbf{89.6}_{\pm0.4}$	$85.6_{\pm0.5}$	$\mathbf{89.8}$

Table 6: One-class classification results using different representations and one-class classifiers. We report the mean and standard deviation over 5 runs of AUCs averaged over classes. The best methods are bold-faced for each setting.

A.3 DETAILS OF EXPERIMENTAL SETTING

Unless otherwise stated, models are trained for 2048 epochs with momentum (0.9) SGD and a single cycle of cosine learning rate decay [73]. L2 weight regularization with coefficient of 0.0003 is applied. We use scikit-learn [74] implementation of OC-SVMs with default value of ν. We use $\gamma = {}^{10}/_{|f| \cdot \mathrm{Var}(f)}$, which is 10 times larger than the default value for kernel OC-SVM. Same value of γ is used for KDE. We use scikit-learn implementation of Gaussian mixture model using a single

component for Gaussian density estimator (GDE). No hyperparameters are tuned for GDE. Finally, all experiments are conducted using TensorFlow [75].

Other hyperparameters, such as learning rate or the MLP projection head depth, are cross-validated using small labeled data. While this may violate the assumption of one-class classification, supervised model selection is inevitable for deep learning models as their behaviors may be largely dependent on hyperparameters. To this end, we use 10% of inlier (500) and the same number of outlier examples of CIFAR-10 for hyperparameter selection, and use the same set of hyperparameters to test methods on other datasets, which could demonstrate the algorithm robustness. Learning rate $\in\{0.1, 0.03, 0.01, 0.003, 0.001\}$ and the depth $\in\{0, \cdots, 8\}$ of an MLP projection head are tuned for all methods. In addition, the temperature $\tau \in \{1, 0.5, 0.2, 0.1\}$ and the batch size $\in \{2^n, n = 3, ..., 9\}$ of contrastive loss are tuned. To this end, we train all models across all datasets using the same hyperparameter configurations, such as learning rate of 0.01, projection head of depth 8 ($[512 \times 8, 128]$), temperature τ of 0.2, or batch size of 32.

A.4 PER-CLASS AUCS

Representation	RotNet [20]		Denoising		Rot. Prediction		Contrastive		Contrastive (DA)	
Classifier	Rot. Cls	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE
airplane	$80.3_{\pm0.4}$	$81.4_{\pm0.3}$	$81.6_{\pm0.7}$	$81.6_{\pm0.7}$	$83.6_{\pm0.6}$	$88.5_{\pm0.3}$	$88.8_{\pm0.3}$	$88.8_{\pm0.2}$	$90.9_{\pm0.5}$	$91.0_{\pm0.5}$
automobile	$91.2_{\pm0.3}$	$96.7_{\pm0.1}$	$92.4_{\pm0.4}$	$92.4_{\pm0.4}$	$96.9_{\pm0.2}$	$97.5_{\pm0.3}$	$97.5_{\pm0.2}$	$97.5_{\pm0.2}$	$98.9_{\pm0.1}$	$98.9_{\pm0.1}$
bird	$85.3_{\pm0.3}$	$86.4_{\pm0.3}$	$75.9_{\pm1.3}$	$75.9_{\pm1.3}$	$87.9_{\pm0.4}$	$88.2_{\pm0.3}$	$87.7_{\pm0.4}$	$87.7_{\pm0.4}$	$88.1_{\pm0.1}$	$88.0_{\pm0.2}$
cat	$78.1_{\pm0.3}$	$78.9_{\pm0.3}$	$72.3_{\pm1.9}$	$72.3_{\pm1.9}$	$79.0_{\pm0.6}$	$78.3_{\pm1.0}$	$82.0_{\pm0.4}$	$82.1_{\pm0.4}$	$83.1_{\pm0.8}$	$83.2_{\pm0.9}$
deer	$85.9_{\pm0.5}$	$88.0_{\pm0.6}$	$82.3_{\pm0.6}$	$82.4_{\pm0.6}$	$90.5_{\pm0.2}$	$90.2_{\pm0.2}$	$82.4_{\pm1.8}$	$82.3_{\pm1.8}$	$89.9_{\pm1.3}$	$89.4_{\pm1.8}$
dog	$86.7_{\pm0.4}$	$88.1_{\pm0.3}$	$83.1_{\pm0.6}$	$83.1_{\pm0.6}$	$89.5_{\pm0.4}$	$88.2_{\pm0.6}$	$89.2_{\pm0.4}$	$89.2_{\pm0.5}$	$90.3_{\pm1.0}$	$90.2_{\pm1.2}$
frog	$89.6_{\pm0.5}$	$90.7_{\pm0.4}$	$86.7_{\pm0.6}$	$86.8_{\pm0.6}$	$94.1_{\pm0.3}$	$94.6_{\pm0.3}$	$89.7_{\pm1.4}$	$89.8_{\pm1.4}$	$93.5_{\pm0.6}$	$93.5_{\pm0.6}$
horse	$93.3_{\pm0.6}$	$95.7_{\pm0.3}$	$91.2_{\pm0.4}$	$91.2_{\pm0.4}$	$96.7_{\pm0.1}$	$97.0_{\pm0.1}$	$95.6_{\pm0.2}$	$95.6_{\pm0.2}$	$98.2_{\pm0.1}$	$98.1_{\pm0.1}$
ship	$91.8_{\pm0.5}$	$94.0_{\pm0.2}$	$78.0_{\pm2.6}$	$78.0_{\pm2.6}$	$95.0_{\pm0.2}$	$95.7_{\pm0.1}$	$86.0_{\pm0.7}$	$85.8_{\pm0.6}$	$96.5_{\pm0.3}$	$96.5_{\pm0.3}$
truck	$86.0_{\pm0.6}$	$93.0_{\pm0.3}$	$91.0_{\pm0.6}$	$91.0_{\pm0.6}$	$94.9_{\pm0.2}$	$94.9_{\pm0.2}$	$90.6_{\pm0.9}$	$90.7_{\pm0.9}$	$95.2_{\pm1.3}$	$95.1_{\pm1.3}$
mean	$86.8_{\pm0.4}$	$89.3_{\pm0.3}$	$83.4_{\pm1.0}$	$83.5_{\pm1.0}$	$90.8_{\pm0.3}$	$91.3_{\pm0.3}$	$89.0_{\pm0.7}$	$89.0_{\pm0.7}$	$92.5_{\pm0.6}$	$92.4_{\pm0.7}$

Table 7: Per-class one-class classification AUCs on CIFAR-10.

Representation	RotNet [20]		Denoising		Rot. Prediction		Contrastive		Contrastive (DA)	
Classifier	Rot. Cls	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE
0	$77.7_{\pm0.6}$	$79.1_{\pm0.6}$	$74.6_{\pm0.7}$	$74.4_{\pm0.8}$	$77.1_{\pm0.8}$	$78.8_{\pm0.6}$	$79.9_{\pm1.0}$	$79.9_{\pm1.0}$	$83.0_{\pm1.4}$	$82.9_{\pm1.4}$
1	$73.0_{\pm0.9}$	$75.4_{\pm0.8}$	$71.8_{\pm1.6}$	$71.8_{\pm1.7}$	$75.2_{\pm0.9}$	$77.9_{\pm1.1}$	$81.1_{\pm0.7}$	$81.1_{\pm0.8}$	$84.6_{\pm0.3}$	$84.3_{\pm0.4}$
2	$72.9_{\pm0.6}$	$76.1_{\pm0.7}$	$81.4_{\pm0.5}$	$81.4_{\pm0.5}$	$84.4_{\pm0.3}$	$85.7_{\pm0.4}$	$87.4_{\pm0.4}$	$87.5_{\pm0.4}$	$88.5_{\pm0.6}$	$88.6_{\pm0.6}$
3	$79.6_{\pm0.6}$	$81.3_{\pm0.3}$	$77.6_{\pm1.6}$	$77.6_{\pm1.6}$	$85.1_{\pm0.6}$	$87.3_{\pm0.4}$	$84.7_{\pm0.8}$	$84.7_{\pm0.8}$	$86.3_{\pm0.8}$	$86.4_{\pm0.8}$
4	$78.4_{\pm0.4}$	$80.8_{\pm0.5}$	$76.1_{\pm1.5}$	$76.1_{\pm1.5}$	$81.1_{\pm0.8}$	$84.8_{\pm0.8}$	$89.8_{\pm0.6}$	$89.9_{\pm0.6}$	$92.6_{\pm0.3}$	$92.6_{\pm0.3}$
5	$73.1_{\pm0.9}$	$73.7_{\pm0.5}$	$70.2_{\pm0.5}$	$70.2_{\pm0.5}$	$72.0_{\pm1.3}$	$78.6_{\pm1.0}$	$82.6_{\pm1.2}$	$82.7_{\pm1.2}$	$84.4_{\pm1.3}$	$84.5_{\pm1.3}$
6	$89.8_{\pm0.5}$	$90.4_{\pm0.4}$	$68.5_{\pm2.4}$	$68.4_{\pm2.3}$	$88.6_{\pm0.3}$	$87.5_{\pm0.4}$	$77.0_{\pm1.6}$	$77.0_{\pm1.6}$	$73.4_{\pm0.9}$	$73.4_{\pm0.9}$
7	$64.1_{\pm0.7}$	$66.1_{\pm0.6}$	$77.6_{\pm0.4}$	$77.6_{\pm0.4}$	$73.0_{\pm1.0}$	$76.2_{\pm0.6}$	$80.5_{\pm0.3}$	$80.4_{\pm0.3}$	$84.3_{\pm0.6}$	$84.2_{\pm0.6}$
8	$83.5_{\pm0.6}$	$85.3_{\pm0.4}$	$81.7_{\pm0.6}$	$81.7_{\pm0.6}$	$87.8_{\pm0.1}$	$86.4_{\pm0.2}$	$85.2_{\pm0.6}$	$85.2_{\pm0.6}$	$87.5_{\pm0.9}$	$87.7_{\pm0.9}$
9	$91.4_{\pm0.2}$	$91.7_{\pm0.4}$	$73.7_{\pm1.1}$	$73.7_{\pm1.1}$	$88.0_{\pm0.7}$	$88.8_{\pm0.5}$	$89.1_{\pm0.9}$	$89.2_{\pm0.9}$	$94.1_{\pm0.3}$	$94.1_{\pm0.3}$
10	$86.1_{\pm0.6}$	$87.0_{\pm0.6}$	$58.6_{\pm2.2}$	$58.5_{\pm2.2}$	$79.5_{\pm1.1}$	$82.4_{\pm0.7}$	$60.0_{\pm2.0}$	$59.8_{\pm2.0}$	$85.1_{\pm1.1}$	$85.2_{\pm1.1}$
11	$83.7_{\pm0.5}$	$85.0_{\pm0.3}$	$76.5_{\pm0.7}$	$76.5_{\pm0.7}$	$87.2_{\pm0.2}$	$84.9_{\pm0.4}$	$84.3_{\pm0.2}$	$84.2_{\pm0.1}$	$87.8_{\pm0.6}$	$87.8_{\pm0.6}$
12	$82.8_{\pm0.4}$	$84.3_{\pm0.4}$	$79.0_{\pm1.1}$	$79.1_{\pm1.1}$	$85.8_{\pm0.3}$	$85.2_{\pm0.7}$	$84.4_{\pm0.5}$	$84.4_{\pm0.5}$	$82.0_{\pm1.0}$	$82.0_{\pm1.1}$
13	$61.8_{\pm1.2}$	$64.1_{\pm0.8}$	$70.2_{\pm0.7}$	$70.2_{\pm0.7}$	$70.8_{\pm0.7}$	$73.6_{\pm0.6}$	$79.3_{\pm1.4}$	$79.2_{\pm1.4}$	$82.7_{\pm0.4}$	$82.7_{\pm0.4}$
14	$89.7_{\pm0.3}$	$90.3_{\pm0.2}$	$73.1_{\pm1.0}$	$73.1_{\pm1.0}$	$91.3_{\pm0.3}$	$90.2_{\pm0.6}$	$89.1_{\pm0.7}$	$89.1_{\pm0.6}$	$93.4_{\pm0.2}$	$93.4_{\pm0.2}$
15	$69.4_{\pm0.4}$	$70.6_{\pm0.3}$	$71.2_{\pm0.7}$	$71.1_{\pm0.7}$	$73.4_{\pm0.5}$	$74.9_{\pm0.5}$	$71.5_{\pm1.2}$	$71.4_{\pm1.2}$	$76.1_{\pm1.3}$	$75.8_{\pm1.4}$
16	$78.0_{\pm0.3}$	$79.4_{\pm0.4}$	$74.7_{\pm1.0}$	$74.8_{\pm1.0}$	$79.8_{\pm0.9}$	$80.5_{\pm0.9}$	$79.3_{\pm0.2}$	$79.3_{\pm0.2}$	$80.4_{\pm0.7}$	$80.3_{\pm0.7}$
17	$92.5_{\pm0.4}$	$93.7_{\pm0.2}$	$88.8_{\pm0.5}$	$88.8_{\pm0.5}$	$93.9_{\pm0.3}$	$94.6_{\pm0.2}$	$91.2_{\pm0.3}$	$91.2_{\pm0.3}$	$97.5_{\pm0.1}$	$97.5_{\pm0.1}$
18	$90.8_{\pm0.3}$	$92.5_{\pm0.3}$	$80.3_{\pm0.7}$	$80.2_{\pm0.7}$	$93.4_{\pm0.3}$	$93.1_{\pm0.1}$	$87.4_{\pm0.3}$	$87.2_{\pm0.3}$	$94.4_{\pm0.2}$	$94.4_{\pm0.2}$
19	$88.4_{\pm0.4}$	$90.3_{\pm0.3}$	$78.0_{\pm0.8}$	$77.8_{\pm0.8}$	$89.3_{\pm0.1}$	$89.8_{\pm0.2}$	$84.0_{\pm1.6}$	$83.9_{\pm1.6}$	$92.5_{\pm0.7}$	$92.4_{\pm0.6}$
mean	$80.3_{\pm0.5}$	$81.9_{\pm0.5}$	$75.2_{\pm1.0}$	$75.2_{\pm1.0}$	$82.8_{\pm0.6}$	$84.1_{\pm0.6}$	$82.4_{\pm0.8}$	$82.4_{\pm0.8}$	$86.5_{\pm0.7}$	$86.5_{\pm0.7}$

Table 8: Per-class one-class classification AUCs on CIFAR-20.

Representation	RotNet [20]		Denoising		Rot. Prediction		Contrastive		Contrastive (DA)	
Classifier	Rot. Cls	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE
0	$83.7_{\pm2.2}$	$94.5_{\pm0.3}$	$91.8_{\pm0.7}$	$92.3_{\pm0.7}$	$94.5_{\pm0.3}$	$95.2_{\pm0.5}$	$93.4_{\pm0.2}$	$93.3_{\pm0.2}$	$93.0_{\pm0.9}$	$92.3_{\pm1.6}$
1	$96.2_{\pm1.9}$	$99.5_{\pm0.1}$	$97.4_{\pm0.4}$	$97.7_{\pm0.4}$	$99.4_{\pm0.1}$	$99.7_{\pm0.1}$	$98.1_{\pm0.2}$	$98.3_{\pm0.2}$	$99.2_{\pm0.4}$	$99.1_{\pm0.6}$
2	$78.1_{\pm2.0}$	$93.8_{\pm0.2}$	$91.6_{\pm0.4}$	$91.6_{\pm0.4}$	$93.1_{\pm0.3}$	$94.2_{\pm0.3}$	$93.3_{\pm0.2}$	$93.5_{\pm0.2}$	$93.1_{\pm0.2}$	$93.4_{\pm0.1}$
3	$83.7_{\pm2.1}$	$95.0_{\pm0.4}$	$91.1_{\pm1.1}$	$91.0_{\pm1.1}$	$93.3_{\pm0.5}$	$95.4_{\pm0.4}$	$92.2_{\pm0.5}$	$91.4_{\pm0.7}$	$93.2_{\pm0.3}$	$92.2_{\pm0.3}$
4	$83.5_{\pm2.1}$	$91.9_{\pm0.1}$	$93.3_{\pm0.2}$	$92.7_{\pm0.2}$	$92.1_{\pm0.2}$	$93.9_{\pm0.2}$	$93.4_{\pm0.1}$	$92.5_{\pm0.2}$	$94.2_{\pm0.2}$	$93.4_{\pm0.3}$
5	$87.6_{\pm1.5}$	$94.3_{\pm0.4}$	$94.9_{\pm0.4}$	$94.7_{\pm0.5}$	$95.1_{\pm0.3}$	$97.3_{\pm0.3}$	$93.8_{\pm0.1}$	$93.0_{\pm0.2}$	$94.3_{\pm0.2}$	$94.3_{\pm0.3}$
6	$77.3_{\pm1.2}$	$83.4_{\pm0.2}$	$86.1_{\pm0.5}$	$85.5_{\pm0.4}$	$82.5_{\pm0.4}$	$85.9_{\pm0.4}$	$88.3_{\pm0.1}$	$87.4_{\pm0.1}$	$87.6_{\pm0.2}$	$86.2_{\pm0.1}$
7	$96.9_{\pm0.8}$	$99.2_{\pm0.1}$	$96.9_{\pm0.3}$	$96.9_{\pm0.3}$	$98.7_{\pm0.1}$	$99.4_{\pm0.1}$	$97.3_{\pm0.2}$	$97.0_{\pm0.2}$	$98.5_{\pm0.1}$	$98.4_{\pm0.1}$
8	$92.2_{\pm1.5}$	$96.2_{\pm0.5}$	$90.9_{\pm0.8}$	$90.0_{\pm0.9}$	$98.5_{\pm0.3}$	$98.3_{\pm0.3}$	$92.3_{\pm1.2}$	$92.3_{\pm1.2}$	$97.6_{\pm0.3}$	$97.6_{\pm0.3}$
9	$95.0_{\pm1.3}$	$98.1_{\pm0.3}$	$93.3_{\pm0.5}$	$92.9_{\pm0.5}$	$99.0_{\pm0.1}$	$98.6_{\pm0.2}$	$96.9_{\pm0.3}$	$96.9_{\pm0.3}$	$97.9_{\pm0.3}$	$98.0_{\pm0.3}$
mean	$87.4_{\pm1.7}$	$94.6_{\pm0.3}$	$92.7_{\pm0.5}$	$92.5_{\pm0.5}$	$94.6_{\pm0.3}$	$95.8_{\pm0.3}$	$93.9_{\pm0.3}$	$93.6_{\pm0.3}$	$94.8_{\pm0.3}$	$94.5_{\pm0.4}$

Table 9: Per-class one-class classification AUCs on Fashion MNIST.

Representation	RotNet [20]		Denoising		Rot. Prediction		Contrastive		Contrastive (DA)	
Classifier	Rot. Cls	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE	OC-SVM	KDE
cat	$86.4_{\pm0.3}$	$86.1_{\pm0.2}$	$41.3_{\pm1.7}$	$41.2_{\pm1.8}$	$81.9_{\pm0.7}$	$84.1_{\pm0.8}$	$89.8_{\pm0.4}$	$89.7_{\pm0.4}$	$91.6_{\pm0.3}$	$91.7_{\pm0.3}$
dog	$85.8_{\pm0.3}$	$86.6_{\pm0.2}$	$60.6_{\pm1.1}$	$60.3_{\pm1.0}$	$85.5_{\pm0.6}$	$88.7_{\pm0.4}$	$85.7_{\pm0.5}$	$85.7_{\pm0.5}$	$87.5_{\pm0.6}$	$87.5_{\pm0.6}$
mean	$86.1_{\pm0.3}$	$86.4_{\pm0.2}$	$51.0_{\pm1.4}$	$50.7_{\pm1.4}$	$83.7_{\pm0.6}$	$86.4_{\pm0.6}$	$87.7_{\pm0.5}$	$87.7_{\pm0.4}$	$89.6_{\pm0.5}$	$89.6_{\pm0.4}$

Table 10: Per-class one-class classification AUCs on Cat-vs-Dog.

A.5 More Examples for Visual Explanation of Deep One-class classifiers

(a) Input   (b) Ours   (c) RotNet   (d) RotNet*   (e) DAE   (f) Ours   (g) RotNet   (h) RotNet*   (i) DAE

Figure 8: Visual explanations on CelebA eyeglasses dataset. (a) input images, (b–e) images with heatmaps using integrated gradients [44], and (f–i) those using GradCAM [43]. RotNet*: RotNet + KDE.

(a) Input   (b) Ours   (c) RotNet (d) RotNet* (e) DAE   (f) Ours   (g) RotNet (h) RotNet* (i) DAE

Figure 9: Visual explanations on CelebA eyeglasses dataset. (a) input images, (b–e) images with heatmaps using integrated gradients [44], and (f–i) those using GradCAM [43]. RotNet*: RotNet + KDE.

(a) Input   (b) Ours   (c) RotNet (d) RotNet* (e) DAE   (f) Ours   (g) RotNet (h) RotNet*   (i) DAE

Figure 10: Visual explanations on cat-vs-dog dataset. (a) input images, (b–e) images with heatmaps using integrated gradients [44], and (f–i) those using GradCAM [43]. RotNet*: RotNet + KDE.

(a) Input   (b) Ours   (c) RotNet   (d) RotNet*   (e) DAE   (f) Ours   (g) RotNet (h) RotNet*   (i) DAE

Figure 11: Visual explanations on cat-vs-dog dataset. (a) input images, (b–e) images with heatmaps using integrated gradients [44], and (f–i) those using GradCAM [43]. RotNet*: RotNet + KDE.