KGHaluBench: A Knowledge Graph-Based Hallucination Benchmark for Evaluating the Breadth and Depth of LLM Knowledge

Abstract

Large Language Models (LLMs) possess a remarkable capacity to generate persuasive and intelligible language. However, coherence does not equate to truthfulness, as the responses often contain subtle hallucinations. Existing benchmarks are limited by static and narrow questions, leading to limited coverage and misleading evaluations. We present **KGHaluBench**, a **K**nowledge **G**raph-based **hallu**cination **bench**mark that assesses LLMs across the breadth and depth of their knowledge, providing a fairer and more comprehensive insight into LLM truthfulness. Our framework utilises the KG to dynamically construct challenging, multifaceted questions, whose difficulty is then statistically estimated to address popularity bias. Our automated verification pipeline detects abstentions and verifies the LLM's response at both conceptual and correctness levels to identify different types of hallucinations. We evaluate 25 frontier models, using novel accuracy and hallucination metrics. The results provide a more interpretable insight into the knowledge factors that cause hallucinations across different model sizes. KGHaluBench is publicly available[1] to support future developments in hallucination mitigation.

1 Introduction

Recent advancements in language generation and critical reasoning of Large Language Models (LLMs) have driven their widespread adoption (Minaee et al., 2025), with their remarkable capabilities revolutionising domains such as science, healthcare, and finance (Kaddour et al., 2023; Busch et al., 2025; Li et al., 2024). However, a detrimental yet inevitable limitation with LLMs lies in their tendency to generate inaccurate or misleading content, often referred to as 'hallucinations' (Xu et al., 2024). Such outputs may diverge from the intent in the user's input, contradict previously established outputs, and/or conflict with verifiable factual knowledge (Zhang et al., 2023), which undermines the LLM's trustworthiness, interpretability, and factual accuracy (Narayanan Venkit et al., 2024). As more proficient LLMs generate increasingly convincing outputs, the risk grows that users will perceive these responses as accurate, amplifying the potential consequences of hallucinations. This emphasises the need for robust benchmarks to quantify hallucinations and assess the effectiveness of mitigation strategies.

Current benchmarks fail to provide a comprehensive evaluation of the LLM's knowledge, which limits their ability to reflect realistic accuracy and hallucination rates. The static and fixed nature of the datasets often constrains the breadth of knowledge assessed. Some pre-constructed QA benchmarks capture the knowledge before and surrounding the time of their release (Berant et al., 2013; Bordes et al., 2015; Kwiatkowski et al., 2019), but are unable to evaluate a model's performance on newly emerging facts and information. Incorporating a knowledge graph (KG) can alleviate this limitation; however, several KG-based benchmarks revert their dynamic generation frameworks into static datasets, thereby limiting the breadth of the assessment (Zhu et al., 2024; Sun et al., 2024; Dammu et al., 2025). The depth of knowledge is rarely probed beyond the surface-level details due to the style of questions used within the benchmarks. Often, closed or multiple-choice questions are favoured over open-ended questions (Hendrycks et al., 2021; Rahman et al., 2024), as accurately evaluating long-form responses is a current research challenge. However, this question style is knowledge-restrictive, presenting the LLM with a limited set of answers to choose from. Instead, some benchmarks use simple questions (Wei et al., 2024; Joshi et al., 2017), which are typically short, open-ended queries with a single, verifiable

---

[1]Code will be made available upon acceptance

answer. These questions require the LLM to draw on its internalised knowledge, but are unable to capture multiple elements of deeper knowledge within a single question. The limited breadth and depth within the current benchmarks fail to reflect the diversity of knowledge that users query, making it difficult to reliably assess a model's performance.

To address the limitations above, we present KGHaluBench, a **KG**-synergised **hallu**cination **bench**mark that takes advantage of the comprehensive knowledge within a KG to assess both factual accuracy and hallucination rate across the breadth and depth of an LLM's knowledge. Our benchmark includes a dynamic question generation module that draws upon the KG to retrieve a random selection of entities spanning diverse topics. These entities serve as focal points for questions, providing coverage across the breadth of the LLM's knowledge. For each entity, we generate open-ended compound questions that target three aspects of information, both activating and assessing the depth of the LLM's knowledge. Our response verification framework determines factuality in long-form text by identifying hallucinations in the LLM's output. The framework comprises an abstention filter to detect expressions of uncertainty, an initial entity-level filter to identify semantic misalignment with the focal entity's description, and a final fact-level check to verify correctness against grounded facts. We introduce novel metrics to evaluate our extensive experimental results. Weighted accuracy, W_a, scales standard accuracy based on the estimated difficulty of the content within the assessment, providing a fairer measure of performance. Breadth of knowledge and depth of knowledge hallucination rates, Halu_{BOK} and Halu_{DOK}, are derived from what stage in the response verification framework the hallucination was detected, offering an insight into which aspects of the LLM's knowledge caused the hallucination. Our key contributions are:

- We propose a question generation approach using the KG's relational structure to formulate compound questions on dynamically selected entities.

- We construct an automated verification framework with coarse entity-level and fine-grained fact-level filters to assess the factuality of the LLM's output, achieving 79.19% and 87.74% agreement with human judgment, respectively.

- We develop a statistical method to evaluate the difficulty of an assessment and scale the accuracy accordingly, generating a novel metric of W_a.

- We conduct an extensive experiment using 25 open-source and proprietary LLMs, leveraging Halu_{BOK} and Halu_{DOK} to identify factors in the LLM's knowledge that may cause hallucination.

2 Related Work

QA Benchmarks: The Question-Answer (QA) benchmarks typically require the LLM to generate open-ended responses, which are evaluated for factuality using metrics or automated judges. Natural Questions (NQ) (Kwiatkowski et al., 2019) and WebQuestions (Berant et al., 2013) comprise popular user queries from the Google search engine, providing an evaluation of the LLM that is relevant to the real world. Similarly, TriviaQA (Joshi et al., 2017) includes popular trivia questions constructed by trivia enthusiasts. TruthfulQA (Lin et al., 2022) is a niche benchmark that focuses on questions replicating false beliefs or misconceptions to assess a model's truthfulness. SimpleQA (Wei et al., 2024) and SimpleQuestions (Bordes et al., 2015) are diverse factual benchmarks that utilise short, fact-seeking questions with a single, verifiable answer, ensuring high correctness and reliability. These static QA benchmark datasets fail to capture emerging world knowledge, thereby failing to challenge the constantly advancing LLMs. While dynamic QA benchmarks such as FreshQA (Vu et al., 2023) and RealTimeQA (Kasai et al., 2024) exist, they are challenging to maintain due to the complexities of information management and the need for frequent updates. However, Knowledge graphs offer a solution by providing structured, scalable, and continuously updated information for dynamic benchmark generation.

KGQA Benchmarks: The Knowledge-Graph Question-Answer (KGQA) benchmarks utilise vast amounts of up-to-date information within KGs, such as Wikidata and DBpedia (Vrandečić and Krötzsch, 2014; Auer et al., 2007) to generate intricate questions. GraphEval (Liu et al., 2024) mutates the KG triples into correct and incorrect statements, with the LLM classifying the claims as true, false, or inconclusive. DynamicKGQA (Dammu et al., 2025) uses the KG to dynamically construct a new variant of a static QA dataset, while preserving the underlying distribution of question types and topics. However, the random sampling of entities from the KG may introduce an entity popularity

Figure 1: Framework of the KGHaluBench.

bias, where an assessment could contain a disproportionate amount of well-known entities, making it inherently easier to complete. To mitigate this issue, some KGQA benchmarks rely on discrete levels of question difficulty. KG-FPQ (Zhu et al., 2024) generates six levels of confusability based on the editing methods to create the false triplets. Head-To-Tail (Sun et al., 2024) uses a knowledge graph to extract triples and generate questions of varying difficulty based on the estimated popularity of the entity. But, discrete question difficulties cause a fairness issue because they group questions of varying difficulty under the same category. Therefore, KGHaluBench statistically estimates the difficulty of each question, aggregates assessment-level difficulty, and scales the accuracy accordingly, ensuring a fair and reliable evaluation regardless of the difficulty of the assessment content.

3 The KGHaluBench Benchmark

We propose KGHaluBench, a novel benchmark designed to evaluate the truthfulness of LLMs when answering challenging questions that range from both the breadth and depth of their knowledge. As shown in Figure 1, the benchmark consists of two complementary components. The *Question Generation Module* extracts a random entity (*e.g. Denzel Washington*) from the KG to become the centre of the question. The KG's structure, together with

external databases such as *Wikipedia*, is then leveraged to fetch the entity's *KG Triples, Statistics*, and *Description* needed to construct and validate the multifaceted question. The *Response Verification Module* employs a two-layer framework that first checks the *LLM's response* against the entity's *Wikipedia Description* to confirm basic understanding of the focal entity (*e.g. Denzel Washington*). Non-hallucinated responses are then verified at the fact level by comparing their claims to the *KG Triples* to ensure correctness.

3.1 Question Generation

The *Question Generation Module* dynamically constructs coherent and challenging questions utilising the KG to alleviate the static, pre-constructed nature of current QA benchmarks.

3.1.1 Entity Retrieval:

For each question, we first define a focal entity. Using a batch call to the KG, we retrieve a random sample of entities, recording each ID and corresponding type. Invalid types are removed by cross-referencing against a predefined list of valid entity types, categorised as Very Common (*e.g., Human*), Common (*e.g., Business*), or Uncommon (*e.g., Painting*) according to their frequency in the KG. We order the sample prioritising less common entities to maintain a balanced distribution of entity types and ensure the benchmark remains

topically broad yet structured. Table 2 illustrates the resulting distribution of entity types in an average benchmark assessment. From the ordered sample, we sequentially choose the focal entity for the question and extract its surrounding one-hop entities to obtain a subgraph. If no valid entity types are present in a sample, a new one is generated.

Figure 2: Distribution of Very Common, Common, and Uncommon Entity Types within the KGHaluBench assessment

3.1.2 Attributes Retrieval:

We retrieve three key sets of information from the focal entity's sub-graph and external database for the downstream process in KGHaluBench.

KG Triples are required both for generating the benchmark questions and verifying the correctness of the LLM's response. From the entity's subgraph, we extract pairs of facts and connecting relations and filter them against a predefined set of valid relations. As non-textual (e.g., *image*), trivial (e.g., *given name*), and irrelevant (e.g., *official website*) relations are unsuitable for generating challenging and coherent questions. From the remaining pairs, we randomly select three to form the benchmark question and validate the LLM's response. If there are fewer than three valid pairs, then we lack the number to formulate the question template. Therefore, we discard the current target entity and select the next focal entity from the KG sample.

Entity Description is a comprehensive overview of the entity from an external database. We utilise the description as a factual representation when comparing against the LLM's response in the entity-level filter, as described in Section 3.2.

Entity Statistics are used within the question difficulty calculation to estimate the popularity of the entity, as detailed in Section 3.1.3. Similarly to the process of filtering the KG triples, if any statistic is null or invalid, we cannot quantify the entity's popularity; therefore, we must select the next focal entity from the sample set.

3.1.3 Entity Popularity:

Well-known entities are more likely to be referenced in an LLM's training data, increasing the likelihood that the LLM will accurately recall information about them. Therefore, estimating entity popularity offers a valuable insight into the challenge of the question. To determine an entity's popularity, we combine the entity's individual relevance and the relevance of its associated type.

Entity Relevance: An entity's relevance is determined by two key factors: its **prominence**, reflecting recognisability and graph connectivity, and its **information coverage**, capturing the availability and detail of the information. To estimate relevance, we aggregate the following statistics from the KG and external databases.

- **Page Views**: Number of entity page views (2017–2025)
- **Site Links**: Number of site links from other entities
- **Linked Entities**: Number of neighbours in the KG
- **IDs**: Number of external database identifiers
- **Wiki Count**: Token count of the entity's page
- **Statements**: Number of relation–fact pairs
- **References**: Number of sources validating the KG facts

However, some statistics provide a stronger indication of the LLM's ability to answer questions more accurately than others. To account for this, we derive an associated weight for each statistic using a machine learning pipeline as outlined in Appendix A.2.3.

Entity Type Relevance: In the training data, some entity types (e.g. *fictional characters*) frequently appear in descriptive texts, resulting in a more comprehensive representation in the LLM's knowledge. In contrast, other entities (e.g. *paintings*) are usually referenced in shorter, more literal descriptions and are less likely to be retained. To quantify this difference, we calculate entity type weights by averaging the question scores for each entity type and applying a min-max normalisation.

3.1.4 Question Formation:

A key feature of KGHaluBench is the depth of its questions, which challenges the knowledge of the LLM. We achieve this by utilising the relational structure in the KG to formulate compound questions about a single entity. As presented in Figure 3, our question template prompts the LLM to provide a brief overview of the entity, while providing specific facts. This format is intentionally aligned with the entity's description to facilitate an accurate comparison during response verification.

The template requires details such as the entity's name, along with the three randomly chosen valid relations. We provide supplementary context about

the entity to reduce ambiguity when multiple entities may share the same name, enabling the LLM to give a more accurate response without revealing any examined information. The completed question template is supplied to LLM, and the response is collected for verification. Implementation details are provided in Appendix A.2.1.

> **Question Template - Example**
>
> Please provide a brief overview of **Robin Williams** (**1951–2014**). Your response should be around 200 words long and must include key details such as **occupation**, **place of birth**, and **children**. Focus exclusively on the most relevant entity associated with the provided name.

Figure 3: Question Template used for Question Generation.

Question Complexity: To correctly answer each relation in the question, the LLM must recall specific facts about the entity; however, the availability of such knowledge can vary considerably. For instance, the artist of the album is often more widely known and documented than the record label which produced the album.

To account for this, we adopt the same weight calculation process as used in Section 3.1.3. Since each entity type has a specific set of relations, we treat the relation sets as independent from one another. Within each set, we calculate the average question score for every valid relation and apply min-max normalisation to obtain relation weights. For a question, the complexity is estimated by aggregating the weights associated with the three relations it contains, reflecting the challenge the assessment content poses to the LLM. However, when the response is judged to be conceptually hallucinated, the complexity stems from the focal entity of the question rather than the relations. In this case, we approximate complexity by averaging the weights of the focal entity's relation set and multiplying the result by three to account for the number of relations in a given question.

3.1.5 Question Difficulty:

The dynamic question generation introduces randomness into the assessment, resulting in variations in difficulty across different assessments. Therefore, we incorporate a difficulty-scaled accuracy to ensure the benchmark is fair and consistent, regardless of the assessment's content.

We create a unified measure of question difficulty, Q_d, by aggregating entity popularity and question complexity. We drew inspiration from the Item Response Theory, a psychometric paradigm for scoring tests. The theory employs a sigmoid function, which, due to its S-shaped curve, allows for greater differentiation in the middle and the most common range of difficulties. This ensures that moderate-difficulty questions contribute equally to those at the extremes, resulting in a fairer representation of all question difficulties. Our modified sigmoid formula is illustrated below, where α controls the steepness of the sigmoid curve, Q is the question complexity, and Q_{Avg} represents the average question complexity across the three relations. EP denotes the entity popularity, which when min-max normalised is EP_{Norm}

$$Q_d = \frac{1}{1 + e^{-\alpha\left(Q_{\text{Avg}} - EP_{\text{Norm}}\right)}} \tag{1}$$

3.2 Response Verification

The *Response Verification Module* addresses the challenge of evaluating long-form responses by accurately identifying abstentions and potential hallucinations, then verifying factual correctness. Each component of the framework was validated against human judgment to ensure accuracy and effectiveness, as detailed in Appendix A.3.1.

3.2.1 Entity-Level Filter:

The entity-level filter classifies each response as aligned, hallucinated, or abstained, by identifying abstentions and evaluating the semantic and token-level similarities against the entity's description. Only aligned responses proceed to fact-level verification; hallucinated and abstained responses are scored accordingly and initiate another repetition of the question generation process.

We employ a small and efficient LLM to determine responses as either abstentions or meaningful attempts to answer the question. The abstentions are defined as responses that refuse to answer, deflect the question, or admit to not recognising the focal entity. The models receive partial credit for appropriately expressing uncertainty or lack of knowledge (Kalai et al., 2025), as we assign one point to abstained responses.

For responses that meaningfully attempt to answer the question, we evaluate their alignment with the entity through both conceptual overlap and token intersection. For the semantic comparison, we encoded both the response and the description and quantified the similarity between the two texts by calculating the cosine similarity. For token-level comparison, we use the intersection of common

words between the LLM's response and the entity's description. Entity-level similarity combines these metrics with a 70:30 ratio prioritising semantic over lexical alignment, as the entity-level filter focuses on filtering out responses that misalign with the domain of the entity. Responses exceeding the predefined threshold are considered aligned to the focal entity, while those below are deemed entity-level hallucinations and receive zero points. See Appendix A.2.2 for further implementation details of the semantic and token-level comparisons.

3.2.2 Fact-Level Check:

We implement a fact verification pipeline, as illustrated in Figure 4, to evaluate whether the relations specified in a question are correctly expressed in the LLM's response. Each relation is assessed independently as correct or incorrect, totalling to a maximum score of three points per response.

Figure 4: Overview of the fact verification pipeline

The pipeline requires an interpretable fact to compare to the LLM's response. Therefore, we employ an efficient LLM to transform the structured tuple of the entity's name, type, relation, tense indicator and fact into a sentence. The tense indicator is an auxiliary verb (e.g. 'is' or 'was') to ensure the constructed sentence is grammatically correct.

NLI Entailment Filter: For this filter, we utilise a Natural Language Inference (NLI) model. We chose this model because it is fast and efficient, while still achieving robust entailment recognition. We provided the NLI model with the reformatted fact and the LLM's response, requiring it to process the information and classify the outcome as entailment, contradiction, or neutral. If the result is entailment, we consider the fact correctly expressed in the LLM's response; otherwise, the response is passed to the LLM entailment filter.

LLM Entailment Filter: We employ an LLM in place of an entailment model, exploiting its advanced reasoning abilities to make the filter more

accurate; however, it is more computationally expensive. We prompt the LLM to assume the role of a fact-checking assistant, tasked with determining whether the following fact is explicitly stated, contradicted, or not mentioned in the provided response. If a fact is stated incorrectly or omitted from the response, it is considered incorrect. Whereas, if the LLM concludes that the fact is explicitly stated, its decision is cross-validated against the NLI model. If the NLI result is neutral, we accept the LLM's judgment and consider the fact correctly expressed in the response. However, if the NLI model contradicts the LLM's decision, we proceed to the expert decision filter.

Expert Decision Filter: This filter functions as the final decision-maker. Within the pipeline, it is rarely used but serves as a fail-safe mechanism. We present the formatted fact alongside the response and create an ultimatum, with one expert's choice as entailment and the others as contradiction. We utilise the LLM to make the binary decision of which expert to agree with. If the LLM agrees with entailment, the fact is correctly included in the LLM's response; otherwise, it is not.

4 Experiments

4.1 Knowledge Graph

Although our framework allows for the integration of any KG, we selected Wikidata for the experiments. This expansive knowledge base, roughly 118 million entities as of August 2025 (Wikidata, 2025), enables the curation of novel, challenging benchmarks to assess the LLM's knowledge.

4.2 Evaluation Models

We assessed 25 state-of-the-art LLMs on the KGHaluBench benchmark, as detailed in Appendix A.1. This included 15 open-source models ranging from 8 billion to 1 trillion parameters, and 10 proprietary models from 4 leading AI companies: OpenAI, Google, Anthropic, and xAI. Each model was evaluated using default parameters across 10 runs of 150 questions, with results aggregated using the mean. Open-source models run on Nebius AI Studio API, while proprietary models were accessed via their respective APIs.

4.3 Metrics

4.3.1 Weighted Accuracy:

We calculate *Accuracy* as the percentage of possible points earned through correct facts and ab-

stentions, rewarding models for both factuality and expressing uncertainty. However, to ensure we create a fair and consistent metric, $Accuracy$ must be scaled based on how Q_d deviates from the average difficulty across all assessments, $Avg(Q_d)$. We denote the new metric as W_a.

$$W_a = Accuracy \cdot \frac{Q_d}{Avg(Q_d)} \quad (2)$$

4.3.2 Hallucination Rate:

We split the hallucination rate into breadth and depth of knowledge to provide more interpretability to an often one-dimensional metric.

Halu_{BOK} is the percentage of responses classified as hallucinations by the entity-level filter, which assesses the surface-level truthfulness between the LLM's response and the entity's description. A high rate implies that the LLM lacks fundamental knowledge of the assessment content, reflecting a limited breadth of knowledge.

$$\text{Halu}_{\text{BOK}} = \frac{|\text{Entity Hallucinations}|}{|\text{Total Responses}| - |\text{Abstentions}|} \quad (3)$$

Halu_{DOK} is the percentage of incorrect facts judged by the fact-level check. As only the responses that pass the entity-level filter are verified by the fact-level check, we divide the number of incorrect facts by the maximum possible score the model could achieve. A high rate indicates that while the LLM possesses the fundamental knowledge of the entity, it lacks sufficient depth to accurately answer the specified questions, suggesting a limited depth of knowledge.

$$\text{Halu}_{\text{DOK}} = \frac{|\text{Incorrect Facts}|}{\text{Maximum Attainable Score}} \quad (4)$$

5 Results

5.1 Weighted Accuracy

KGHaluBench presents a substantial challenge for the LLMs, as displayed in Figure 5, with *GPT-5* achieving the highest W_a of 65.60%. This difficulty arises from the question generation process, as the random focal entity, around which the compound question is constructed, will reside anywhere from the centre to the periphery of the LLM's knowledge. This redundant performance gap provides longevity to the KGHaluBench, enabling the benchmark to maintain its relevance against the continually advancing knowledge capabilities of LLMs.

The challenge of KGHaluBench makes it an effective benchmark for contrasting the factual performance between different LLMs. To enable a

Figure 5: Top 10 Models by Weighted Accuracy. See Appendix A.1 for the full table of results.

fair comparison between open-source and proprietary technologies, we compute the average W_a for open-source models with $\geq 235B$ parameters and compare it against the average performance of all proprietary models. The proprietary models demonstrate superior factuality, achieving an average W_a of 55.94%, compared to 48.32%. This trend is evident, as the five highest-performing models are all proprietary and show a visible increase in factuality over the rest. However, *GLM-4.5* achieves 54.35% W_a, outperforming powerful proprietary models, such as *Claude-4-Opus* and *Gemini-2.5-Flash*. This result indicates a narrowing performance gap between leading open-source and proprietary LLMs.

5.2 Hallucination Rate

Decomposing the hallucination rate provides valuable insight into the factors that contribute to hallucinations across different-sized models. To quantify these trends, we compare averages from the smaller 8-32B models against larger proprietary models. As shown in Figure 6, the Halu_{BOK} metric

Figure 6: Halu_{BOK} and Halu_{DOK} hallucination rates across all models

dramatically decreases, from 54.75% to 11.91%, as we move towards the larger, more proficient models. This trend suggests the smaller models lack the competency to understand or recognise the focal entity within the question. Therefore, the hallucinated responses are constructed from knowledge

which is loosely or even unrelated to the entity.

In contrast, the Halu_{DOK} metric exhibits a more modest decrease by approximately 24.59% from the 8-32B models to the larger proprietary models. This difference between the two metrics creates a widening gap as the models become more proficient, suggesting the larger models excel at determining what to discuss, but still struggle with correctly retaining the precise details about that topic. Therefore, the hallucinations are not due to a failure in entity recognition, but instead to a lack of deeper or more specific knowledge.

Figure 7: Distribution of fact-level hallucinations across all models, showing the proportion of responses containing 0, 1, 2, or 3 hallucinated facts

To further investigate this trend, we examine the fact-level hallucinations distribution across the models, as illustrated in Figure 7. The results show that more proficient models generate a lower proportion of highly detrimental responses, as those containing two or three hallucinated facts decrease from 52.91% to 19.09%. In turn, the percentage of responses that are entirely factually correct increases by around 28.18%. However, roughly 39.74% of responses from the more proficient models contain a single hallucinated fact. This undermines trustworthiness and creates a false sense of reliability, as the responses which appear fluent and factual still often include hallucinations.

5.3 Abstention Rate

Abstention is an expression of uncertainty, where a model refrains from answering the question if it lacks the understanding or knowledge to provide an accurate response. We integrate abstention detection in our entity-level filter, detailed in Section 3.2.1, enabling the classification of each response as aligned, hallucinated, or abstained. Figure 8 reveals that among models with comparable alignment rates, those with higher abstention show lower hallucination rates. For example, *Llama-3.1-8B* and *Gemma-2-9B* both achieve a 38.80% alignment between their responses and the focal entities'

descriptions, indicating an equivalent breadth of knowledge. However, *Llama-3.1-8B* has a higher abstention rate, resulting in a significantly lower hallucination rate of 30.00%, compared to *Gemma-2-9B* of 58.67%. While this mechanism clearly reduces hallucinations, over-abstaining can severely limit the usefulness of the model. Several models demonstrate this problem with *GPT-oss-20B*, *GPT-5-Mini*, and *Claude Sonnet 4*, declining to answer 55.93%, 49.67%, and 49.40% of the benchmark questions, respectively. Therefore, we believe models should implement constructive abstention, where the response provides guidance on how users might locate the reliable information themselves.

Figure 8: Distribution of entity-level filter classifications across all models, showing the proportion of responses classified as aligned, hallucinated, or abstained

6 Conclusion

We introduce KGHaluBench, a comprehensive hallucination benchmark which evaluates LLMs with questions at the depth and breadth of their knowledge. Our customisable framework dynamically generates multifaceted compound questions based on randomly chosen entities from the KG. These questions are then assessed at a conceptual level, and if no hallucinations or abstentions are detected, they are verified for factual correctness. Our experiments assess 27 state-of-the-art LLMs, utilising our novel metrics. We propose W_{a}, a fairer accuracy metric which adjusts standard accuracy by statistically estimating question difficulty. We also present Halu_{BOK} and Halu_{DOK}, as more interpretable hallucination metrics to provide deeper insights into factors that lead different-sized LLMs to hallucinate. We hope KGHaluBench can be used to develop effective strategies in addressing the challenge of mitigating hallucinations.

7 Limitations

In our benchmark, we rely on Wikidata as the information source, which limits the fact-seeking questions to only entities contained within the KG. Therefore, we would like to expand the benchmark further to include domain-specific KG to explore hallucinations in specific scenarios. Additionally, our automated fact verification framework will make mistakes, potentially rejecting valid responses or scoring misaligned ones. Therefore, despite achieving substantial agreement with human judgment, as displayed in A.3.1, we must make improvements in accuracy and soundness of reasoning, which would further strengthen the validity and reliability of KGHaluBench.

References

Sören Auer, Christian Bizer, Georgi Kobilarov, and 1 others. 2007. Dbpedia: a nucleus for a web of open data. In *Proceedings of the 6th International The Semantic Web and 2nd Asian Conference on Asian Semantic Web Conference*, ISWC'07/ASWC'07, page 722–735, Berlin, Heidelberg. Springer-Verlag.

Jonathan Berant, Andrew K. Chou, Roy Frostig, and 1 others. 2013. Semantic parsing on freebase from question-answer pairs. In *Conference on Empirical Methods in Natural Language Processing*.

Akhiad Bercovich, Itay Levy, Izik Golan, and 1 others. 2025. Llama-nemotron: Efficient reasoning models. *Preprint*, arXiv:2505.00949.

Antoine Bordes, Nicolas Usunier, Sumit Chopra, and 1 others. 2015. Large-scale simple question answering with memory networks. *Preprint*, arXiv:1506.02075.

Felix Busch, Lena Hoffmann, Christopher Rueger, and 1 others. 2025. Current applications and challenges in large language models for patient care: a systematic review. *Communications Medicine*, 5.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, and Ice Pasupat. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *Preprint*, arXiv:2507.06261.

Preetam Prabhu Srikar Dammu, Himanshu Naidu, and Chirag Shah. 2025. Dynamic-kgqa: A scalable framework for generating adaptive question answering datasets. *Preprint*, arXiv:2503.05049.

DeepSeek-AI, Daya Guo, Dejian Yang, and 1 others. 2025a. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *Preprint*, arXiv:2501.12948.

DeepSeek-AI, Aixin Liu, Bei Feng, and 1 others. 2025b. Deepseek-v3 technical report. *Preprint*, arXiv:2412.19437.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, and 1 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. *Preprint*, arXiv:2009.03300.

Mandar Joshi, Eunsol Choi, Daniel Weld, and 1 others. 2017. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1601–1611, Vancouver, Canada. Association for Computational Linguistics.

Jean Kaddour, Joshua Harris, Maximilian Mozes, Herbie Bradley, Roberta Raileanu, and Robert McHardy. 2023. Challenges and applications of large language models. *Preprint*, arXiv:2307.10169.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. 2025. Why language models hallucinate. *Preprint*, arXiv:2509.04664.

Jungo Kasai, Keisuke Sakaguchi, Yoichi Takahashi, and 1 others. 2024. Realtime qa: What's the answer right now? *Preprint*, arXiv:2207.13332.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, and 1 others. 2019. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466.

Vladimir I. Levenshtein. 1965. Binary codes capable of correcting deletions, insertions, and reversals. *Soviet physics. Doklady*, 10:707–710.

Yinheng Li, Shaofei Wang, Han Ding, and Hang Chen. 2024. Large language models in finance: A survey. *Preprint*, arXiv:2311.10723.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

Xiaoze Liu, Feijie Wu, Tianyang Xu, and 1 others. 2024. Evaluating the factuality of large language models using large-scale knowledge graphs. *Preprint*, arXiv:2404.00942.

Shervin Minaee, Tomas Mikolov, Narjes Nikzad, Meysam Chenaghlu, Richard Socher, Xavier Amatriain, and Jianfeng Gao. 2025. Large language models: A survey. *Preprint*, arXiv:2402.06196.

Niklas Muennighoff, Nouamane Tazi, Loic Magne, and 1 others. 2023. MTEB: Massive text embedding benchmark. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2014–2037, Dubrovnik, Croatia. Association for Computational Linguistics.

Pranav Narayanan Venkit, Tatiana Chakravorti, Vipul Gupta, and 1 others. 2024. An audit on the perspectives and challenges of hallucinations in NLP. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6528–6548, Miami, Florida, USA. Association for Computational Linguistics.

OpenAI. 2024. Gpt-4 technical report. *Preprint*, arXiv:2303.08774.

Qwen, An Yang, Baosong Yang, and 1 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

A B M Ashikur Rahman, Saeed Anwar, Muhammad Usman, and Ajmal Mian. 2024. Defan: Definitive answer dataset for llms hallucination evaluation. *Preprint*, arXiv:2406.09155.

Saba Sturua, Isabelle Mohr, Mohammad Kalim Akram, and 1 others. 2024. jina-embeddings-v3: Multilingual embeddings with task lora. *Preprint*, arXiv:2409.10173.

Kai Sun, Yifan Ethan Xu, Hanwen Zha, and 1 others. 2024. Head-to-tail: How knowledgeable are large language models (llms)? a.k.a. will llms replace knowledge graphs? *Preprint*, arXiv:2308.10168.

5 Team. 2025a. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models. *Preprint*, arXiv:2508.06471.

Gemma Team, Morgane Riviere, Shreya Pathak, and 1 others. 2024. Gemma 2: Improving open language models at a practical size. *Preprint*, arXiv:2408.00118.

Kimi Team. 2025b. Kimi k2: Open agentic intelligence. *Preprint*, arXiv:2507.20534.

Denny Vrandečić and Markus Krötzsch. 2014. Wikidata: a free collaborative knowledgebase. *Commun. ACM*, 57(10):78–85.

Tu Vu, Mohit Iyyer, Xuezhi Wang, and 1 others. 2023. Freshllms: Refreshing large language models with search engine augmentation. *Preprint*, arXiv:2310.03214.

Jason Wei, Nguyen Karina, Hyung Won Chung, and 1 others. 2024. Measuring short-form factuality in large language models. *Preprint*, arXiv:2411.04368.

Wikidata. 2025. Wikidata:statistics - wikidata.

Ziwei Xu, Sanjay Jain, and Mohan Kankanhalli. 2024. Hallucination is inevitable: An innate limitation of large language models. *ArXiv*, abs/2401.11817.

An Yang, Anfeng Li, Baosong Yang, and 1 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, and 1 others. 2023. Siren's song in the ai ocean: A survey on hallucination in large language models. *Preprint*, arXiv:2309.01219.

Yanxu Zhu, Jinlin Xiao, Yuhang Wang, and 1 others. 2024. Kg-fpq: Evaluating factuality hallucination in llms with knowledge graph-based false premise questions. *Preprint*, arXiv:2407.05868.

A Appendix

A.1 Experimental Results

Table 1 details the weighted accuracy, abstain rate, and both hallucination rates for all models tested within the KGHaluBench experiments.

A.2 Detailed Methodology

A.2.1 Supplementary Context in the Question Template

The supplementary context provided in the question varies depending on the type of the focal entity. If the entity type is a human, the supplementary context is their lifespan: (1934-2023) if deceased, or their birth year to the present (1968-). For all other types, the context would be the entity type.

A.2.2 Detailed Entity-Level Filter

For the semantic comparison, we embedded both the response and the description into 1024-dimensional vectors using Jina-Embedding-V3 (Sturua et al., 2024). The model achieved a Sentence Textual Similarity (STS) score of 85.80 on the MTEB benchmark, while maintaining an efficient size of 570 million parameters, making it an ideal choice for the entity-level filtering (Muennighoff et al., 2023). We then quantified the similarity between the two texts by calculating the cosine similarity.

$$\mathbf{w} = \text{Embed(Description)}, \quad \mathbf{r} = \text{Embed(Response)}$$

$$\text{SemanticSim} = \frac{\mathbf{w} \cdot \mathbf{r}}{\|\mathbf{w}\|\|\mathbf{r}\|} \quad (5)$$

We calculate the token-level comparison using the Fuzzy Set Ratio from the RapidFuzz Module, which is based on the Levenshtein Distance Formula (Levenshtein, 1965). The Fuzzy Set Ratio uses the intersection of common words between the LLM's response and the entity's description, which is optimal for texts which differ in order

Model Version	Model Size	W_a	Abstain Rate	Halu$_\text{BOK}$	Halu$_\text{DOK}$
Open-Source Models	(Billion)	(%)	(%)	(%)	(%)
Meta-Llama-3.1-8B-Instruct-fast	8	28.89	31.20	43.64	52.46
gemma-2-9b-it-fast	9	19.54	2.53	60.21	51.67
GPT-oss-20b	20	29.45	55.93	49.56	52.32
Qwen3-30B-A3B	30	22.20	13.60	58.36	51.41
QwQ-32B-fast	32	20.18	7.13	61.99	49.88
Llama-3.3-70B-Instruct-fast	70	49.04	6.40	27.13	31.10
Qwen2.5-72B-Instruct	72	23.67	3.27	54.96	48.39
GPT-oss-120b	120	40.62	38.87	22.74	42.36
Qwen3-235B-A22B-Instruct-2507	235	44.94	7.87	21.49	41.32
Llama-3_1-Nemotron-Ultra-253B-v1	253	38.61	20.20	30.57	42.95
GLM-4.5	335	**54.35**	17.20	16.24	30.01
Meta-Llama-3.1-405B-Instruct	405	52.06	37.87	**10.88**	**27.46**
DeepSeek-V3-0324	685	47.00	5.73	25.72	35.90
DeepSeek-R1-0528	685	48.45	2.07	26.87	33.50
Kimi-K2-Instruct	1000	52.88	0.60	23.66	30.47
Proprietary Models					
GPT-4.1-mini-2025-04-14	-	48.13	0.40	21.62	37.71
GPT-4.1-2025-04-14	-	63.60	0.33	10.84	28.65
GPT-5-mini-2025-08-7	-	49.58	49.67	**7.69**	28.05
GPT-5-2025-08-07	-	**65.60**	10.07	8.20	**23.87**
Gemini-2.5-flash	-	51.41	1.33	21.55	34.41
Gemini-2.5-pro	-	61.27	2.00	14.18	26.97
Claude-sonnet-4-20250514	-	46.18	49.40	13.01	32.55
Claude-opus-4-1-20250805	-	52.71	36.87	10.32	28.79
Grok-3	-	57.24	8.53	15.20	29.05
Grok-4-0709	-	63.66	9.27	10.27	24.40

Table 1: Performance of 25 language models on the KGHaluBench using the metrics of W_a, Halu$_\text{BOK}$, and Halu$_\text{DOK}$, along with their version specifications. All models were evaluated across 10 assessments, each comprising 150 questions, with results aggregated using the mean. Models were evaluated using default parameters in accordance with their respective usage policies. The best performing results for the open-source and proprietary models are in **bold**, with the second-best values underlined. Citations: Llama families (Grattafiori et al., 2024; Bercovich et al., 2025), Qwen families (Qwen et al., 2025; Yang et al., 2025), Gemma2(Team et al., 2024), GLM-4.5 (Team, 2025a), Kimi-K2 (Team, 2025b) DeepSeek families (DeepSeek-AI et al., 2025a,b), GPT families (OpenAI, 2024), Gemini families (Comanici et al., 2025)

and length, as is common in this situation. The Fuzzy Set Ratio, like cosine similarity, produces a similarity score represented as a percentage.

$$TokenSim = \left(1 - \frac{D(\text{Description},\text{Response})}{\max(|\text{Description}|,|\text{Response}|)}\right) \quad (6)$$

We aggregate entity similarity with a bias towards the semantic meaning, as it better encompasses the conceptual relationship between the two texts.

$$EntitySim = 0.7 \cdot SemanticSim + 0.3 \cdot TokenSim \quad (7)$$

A.2.3 Weights Configuration

We created a calibration dataset by evaluating 34 selected models (1B-685B parameters, including both open-source and proprietary models) across 10 runs of 150 questions, resulting in a total of 51,000 data points. For each question, the dataset captures the corresponding entity's ID, statistics, and type, as well as the question's relation types, their scores, and the overall question score.

To ensure a balanced representation of all models in the weight configuration, we used stratified sampling to split the experiment dataset into training and validation sets at a 70:30 ratio. For each model's 1,500-question section, 70% (1,050 questions) were randomly selected for the training set, and the remaining 30% (450 questions) were reserved for validation.

To estimate the entity relevance weights, we employed TPOT to automatically generate a machine learning pipeline optimised for predicting how well-known an entity is to the LLM, given the entity's statistics. Before the training, we normalised each of the statistics using a natural logarithmic transformation to ensure consistent scaling across features. The final pipeline includes max-abs feature scaling, feature selection using an ExtraTreesClassifier, parallel feature transformations via FeatureUnion, and a final ensemble using a BaggingClassifier. All hyperparameters and component choices were selected using TPOT's approach, which balances ac-

curacy and model complexity. Finally, the learned feature coefficients were extracted and interpreted as the entity relevance weights.

Entity type relevance weights and relation complexity weights were also derived from the training data, following the processes outlined in Section 3.1.3 and Section 3.1.4, respectively.

A.3 Ablation Studies

We conduct an ablation study isolating the contributions of the response verification framework and weighted accuracy calculation. We demonstrate that both stages of the verification process closely align with human judgment. Additionally, we demonstrate that incorporating difficulty-based scaling into the accuracy creates a more consistent and fair assessment.

A.3.1 Response Verification Framework

We conducted a human validation study to evaluate the accuracy of the verification framework in comparison to human judgment. We tasked nine participants with answering 900 questions: 495 questions emulating the role of the entity-level filter, and 405 questions replicating the role of the fact-level checker. For the entity-level filtering task, participants compared the LLM's response with the entity's Wikipedia description to determine if they referred to the same entity, disregarding any fact-level hallucinations. For the fact-level filtering task, participants were given three facts that corresponded to the relations in the question and had to verify whether they were explicitly stated in the LLM's response. We compared our framework against an automated judge which utilised *GPT-3.5-Turbo*, as often used in literature. The nine participants, all Master's or PhD students, provided consent and were made aware that their responses would be used to evaluate and validate the verification framework.

Entity-Level Filter: Table 2 illustrates how varying the threshold influences the balance between precision and recall in the entity-level filter. We chose the specific thresholds after observing several KGHaluBench assessments to estimate the boundary between factual and hallucinated responses. The highest threshold of 0.750 achieved the most substantial alignment with the human judges, with 79.19%. However, the lower recall of only 73.17% indicates the filter is overly strict for initially comparing the conceptual overlap between the texts,

resulting in valid responses being wrongly rejected. Lowering the threshold increases recall at a faster rate than it decreases precision, resulting in the highest F1 score of 78.07% at a threshold of 0.700, despite the overall agreement dropping slightly to 77.98%. Since the entity-level filter is at the first stage of the pipeline, we must prioritise recall, as misaligned responses admitted at this stage will score poorly at the fact-level check, but aligned responses that are mistakenly discarded are detrimental to the accuracy score of the assessment. These results suggest the entity-level filter was effectively able to differentiate between conceptually hallucinated and non-hallucinated responses in agreement with the participants' decisions.

Model		P %	R %	F1 %	A %
KGHaluBench	**0.750**	75.76	73.17	74.44	79.19
	0.725	70.45	84.88	76.99	78.99
	0.700	66.44	94.63	78.07	77.98
GPT-3.5-Turbo	–	82.46	45.85	58.93	73.54

Table 2: Entity-Level Filter Performance Across Thresholds Compared to *GPT-3.5-Turbo* (P = Precision, R = Recall, A = Human Agreement)

We compared the entity-level filter against an automated judge using a backbone of *GPT-3.5-Turbo*. Our 0.700 threshold achieved 5.65% higher alignment with human judgment and 48.78% higher recall. These results suggest the entity-level filter is a far more effective approach than a typical automated judge, as it can reliably identify whether the focal entity is consistent across the two texts, despite possible nuances and discrepancies.

Fact-Level Check: In the human validation study, our tri-stage fact verification pipeline achieved 87.74% alignment with human judgment, which was 8.56% higher than the automated judge at 79.18%. To conduct a further investigation to break down the pipeline, we utilise the experimental data to highlight the contribution and efficiency of each filter.

Filter	Facts Verified (%)	Avg Time (s)
NLI Entailment	27.58	0.36
LLM Entailment	71.39	1.91
Expert Decision	1.03	2.35
Average Verification Time per Fact (s): 1.49		
Average Verification Time per Question (s): 4.47		

Table 3: Distribution of verified facts and average processing time in the fact verification pipeline

The first filter of the pipeline employs *RoBERTa-Large-MNLI* as an efficient preliminary check. This stage contributes the most to the overall efficiency of the pipeline, as it resolves 27.58% of the facts at an average verification time of 0.36 seconds, as displayed in Table 3. The effectiveness is due to the lightweight design of the model, which has just 365M parameters. However, *RoBERTa-Large-MNLI* has limited reasoning capabilities, which necessitates a second layer of verification. Therefore, we position the filter at the forefront of the pipeline, where it primarily encounters facts that are easily verifiable, such as explicitly stated or numerical ones.

The secondary check is managed by the LLM entailment filter, which utilises the semantic reasoning capabilities of *Llama3.1:8B*. This stage contributes the most to the overall accuracy of the pipeline, as it manages cases where there are subtle discrepancies between the response and the grounded fact, such as changes in word order, phrasing, or nuance. Although roughly five times slower than the first filter, it still resolves 71.39% of the facts, indicating its importance in maintaining the integrity of the fact verification pipeline.

The Expert Decision filter resolves only 1.03% of the facts that pass through the fact verification pipeline. This outcome is expected, as a fact must meet a particular set of conditions in the first two filters before reaching this final fail-safe stage. Overall, the fact verification pipeline is efficient and accurate, which contributes to the validity of the results from KGHaluBench.

A.3.2 Question Difficulty Weighting

We utilise the training section of our calibration dataset, as detailed in Appendix A.2.3, to configure the weights used in the question difficulty calculation. To validate this metric, we assess how well the estimated difficulty aligns with the LLM's experienced difficulty by using the validation portion of the dataset. We use the question score to represent the actual difficulty, with a higher score indicating a more straightforward question. We then compared actual difficulty against estimated question difficulty and evaluated the relationship using Spearman's and Kendall's rank correlation coefficient to provide a robust measure of the ordinal association.

The results show a moderate negative correlation between actual and estimated question difficulty, with a Spearman's ρ of -0.403 and Kendall's τ of

-0.299. Kendall's τ is marginally lower, as it only considers the number of pairwise disagreements, whereas Spearman's ρ also accounts for the distance between the pairs. This confirms that our metric captures the difficulty of the content within the benchmark questions.

To explore the practical impact of this metric, we apply the derived weights to calculate question difficulty scores for our main experimental evaluation. We assess whether it can increase the fairness of the assessment by addressing the randomness and entity popularity bias introduced by the question generation mechanism. For each of the 25 models, we compute mean accuracy and weighted accuracy (W_a), along with their standard deviations, over 10 runs. These values are then averaged across all models to obtain aggregated metrics.

Metric	Mean Acc. (%)	Std. Dev. (%)
Accuracy	45.30	2.57
W_a	45.25	2.45
	-0.05	-0.12

Table 4: Mean and Standard deviation of Accuracy and W_a, over the 10 runs per model. Then averaged across all models in the experiment dataset

As shown in Table 4, applying difficulty-based weighting reduces the mean standard deviation across models by 0.12%, from 2.57% to 2.45%. This improvement in consistency demonstrates that W_a mitigates the impact of entity-popularity bias across assessments, resulting in a fairer and more stable benchmark. Notably, the weighting has a negligible effect on the mean accuracy, with a decrease of 0.05% to 45.25%. This ensures that W_a continues to reflect the benchmark's intended difficulty, preserving the validity of the accuracy results.

A.4 Implementation Details

A.4.1 Benchmark Prompts

> **System Prompt for all LLMs**
>
> ```
> Answer questions about specific entities.  If you
> recognise the focal entity, give a clear, detailed
> response covering all requested details. If you don't
> know it well enough, state that you cannot answer.
> ```

> **Benchmark Template for all LLMs**
>
> ```
> Please provide a brief overview of [Entity Name] [Extra
> Context]. Your response should be around 200 words long
> and must include key details such as [Entity Relation
> 1], [Entity Relation 2], and [Entity Relation 3]. Focus
> exclusively on the most relevant entity associated with
> ```

```
    the provided name.
```

Parameters: Given the model's default.

A.4.2 Response Verification Prompts

Entity-Level Prompts: Prompt used within the entity-level filter.

```
Abstention Filter (Llama3.2:3b)

You are given a question and a response from a
language model. Determine if the response abstains
from answering the question. A response counts as
abstaining if it refuses, deflects, or avoids providing
the requested information, or if it only gives generic
disclaimers without including the required details.
If the response meaningfully answers the question,
classify it as 'Answered'.

Return only one word: 'Abstained' or 'Answered'.

### Question: [Benchmark Question]

### Response: [LLM Response]
```

Parameters: Temperature: 0, Top_P: 0.6

Fact-Level Prompts: Prompt used within the fact verification pipeline.

```
Tuple to Golden Fact Translation

Convert the following structured tuple into a natural
language sentence, using the [Entity Name] as the
subject: ([entity Name] ([Entity Type]) , [Entity
Relation] , [Verb] , [Fact]). Return only the resulting
sentence and do not reword [Entity Name] or [Fact].
```

Parameters: Temperature: 0.3, Top_P: 0.5

```
LLM Entailment Filter (Llama3.1:8b)

You are a fact-checking assistant. Your task is to
determine whether the following fact is explicitly
stated, supported, contradicted, or not mentioned in
the provided response.

### Response: [LLM Response]

### Fact: [Golden Fact]

### Response Options: Respond with one of the following
options and a brief explanation:

- EXPLICITLY STATED: The fact is directly and clearly
stated in the response, using the same or equivalent
wording. Numerical or time-related facts must match
exactly.  - CONTRADICTED: The fact is directly
contradicted by information in the response. - NOT
MENTIONED: The fact is not present in the response, and
there is no sufficient evidence to confirm or contradict
it.

Only return one of the four options and a single concise
explanation. Do not provide additional commentary.
```

Parameters: Temperature: 0, Top_P: 0.6

```
Expert Entailment Filter (Mistral:7b)

You are a fact-checking assistant. Your task is to
determine whether Expert 1 or Expert 2 is correct based
on the provided response and fact.
```

```
### Response: [LLM Response]

### Fact: [Golden Fact]

Expert 1: Entailment (The response aligns with
the fact.) Expert 2: Contradiction (The response
contradicts the fact.)

Return only "Expert 1" or "Expert 2" based on the
correct evaluation. No explanations.
```

Parameters: Temperature: 0, Top_P: 0.6

A.4.3 Automated Judge Prompts

Prompts used in the human validation study for comparing KGHaluBench's entity-level and fact-level filters against using an automated judge of GPT-3.5-Turbo.

```
GPT Entity-Level Filter

You will be given two passages: - A response generated
by a large language model. - A reference description
of a target entity.

Your task is to determine if both passages refer to the
**same entity**.

Check both: 1. Semantic similarity (do they describe
the same person/place/thing, even with different
wording?)  2.  Token-level match (e.g., name or
identifiers must match exactly or with minor variation)

Respond with only one word: True if they refer to the
same entity, or False if they do not.

### Response: [LLM Response]

### Description: [Entity Description]

Output:
```

Parameters: Temperature: 0, Max Tokens: 10

```
GPT Fact-Level Check

You will be given: - A golden fact (a specific claim or
statement) - A response generated by a language model

Your task is to determine whether the golden fact
is **explicitly stated or clearly implied** in the
response.

Only respond with: - True — if the fact is stated
or clearly implied - False — if the fact is missing,
contradicted, or too vague

### Golden Fact: [Golden Fact]

### LLM Response: [LLM Response]

Output:
```

Parameters: Temperature: 0, Max Tokens: 10