Scaling Multimodal Theory-of-Mind with Weak-to-Strong Bayesian Reasoning

Abstract

Theory-of-Mind (ToM) enables individuals to the mental states of the others, such as thoughts, beliefs, and desires. To replicate this cognitive ability in machines, especially under complex multimodal environments, recent advances combine Bayesian-based state inference with deep learning models to estimate mental states, where the Bayesian model handles state transitions and a language model (LM) estimates the likelihood of intermediate states. However, while post-training an LM to specialise in ToM tasks improves performance, the computational cost increases as the LM scales, limiting the model size to 7 billion parameters. Despite this post-training process, smaller LMs still struggle with the physical and mental modelling demands of ToM due to their limited world knowledge and reasoning capacity. To address this, we propose a scalable solution that leverages the strengths of larger LMs (up to 70 and 405 billion parameters, respectively), including their vast world knowledge and atomic-level reasoning capabilities, without increasing post-training resource requirements. Our method transfers ToM-specific behaviours from a post-trained small LM to guide the latent reasoning of a larger LM during test time. This *weak-to-strong* control mechanism enables the larger LM to improve Bayesian likelihood estimation at each inference step, harnessing its reasoning power in ToM scenarios while reducing the need for additional training resources. Extensive experiments demonstrate the significant effectiveness of our scaled approach. It is better at inferring human mental states in complex and interactive environments, outperforming the state-of-the-art solution by $\sim 4.6\%$ across multiple tasks on the multimodal ToM benchmark and unseen scenarios.

1 Introduction

A key aspect of human social cognition is Theory-of-Mind (ToM)—the ability to comprehend and attribute mental states such as beliefs, desires, and intentions to ourselves and others. This capacity allows individuals to recognize that others may have perspectives and motivations distinct from their own, forming the foundation of social understanding and interaction (Dennett, 1988; Gopnik & Wellman, 2012). Building on this concept, a critical challenge lies in enabling artificial intelligence (AI) to acquire human-level ToM capabilities. Equipping AI systems with such abilities could significantly enhance their potential for human-like interactions and unlock broader capacities for commonsense and context-aware reasoning (Lake et al., 2017; Wu et al., 2021; Ma et al., 2023).

Among the ongoing efforts to advance ToM abilities in machines, two broadly classed strategies are the highly structured Bayesian approaches and the less structured end-to-end approaches, respectively: *(i)* Bayesian ToM models use cognitively structured probabilistic frameworks to represent causal relationships between the mind and the world, enabling inverse inference of mental states from sparse behavioral observations (Baker et al., 2017; Jara-Ettinger, 2019; Shu et al., 2021). These models are highly interpretable and support key ToM functions like explanation and inductive learning, excelling in well-defined domains with precise predictions and few-shot generalization (Shum et al., 2019; Zhi-Xuan et al., 2022). However, they require extensive inductive constraints (e.g., abstractions, priors, and causal relationships) provided by experts, **limiting their scalability to complex and unconstrained practical environments.** *(ii)* End-to-end models of ToM involve training deep models directly on ToM data (Rabinowitz et al., 2018; Shu et al., 2021; Sclar et al., 2022). These models, such as ToMnet (Rabinowitz et al., 2018), autonomously learn complex patterns and relationships from data without explicitly concepts like agents, beliefs, and goals. However, because these models

do not explicitly encode principles of physics or theories of psychology, they lack transparency and may draw conclusions that violate physical laws, logical coherence, or commonsense reasoning. Additionally, their data-driven nature makes them **less reliable in, and adaptable to, dynamic or novel environments**, particularly where data is sparse or unrepresentative (Sap et al., 2022; Zhi-Xuan et al., 2022; Ullman, 2023; Strachan et al., 2024).

The recent interdisciplinary milestone, BIPALM (Bayesian inverse planning accelerated by language model), merges the strengths of Bayesian ToM models and deep learning to facilitate robust reasoning in complex multimodal scenarios (Jin et al., 2024). It uses a Bayesian ToM model to predict agents' mental states in multimodal scenarios, with a language model (LM) estimating the probabilities of these Bayesian intermediate states based on multimodal inputs. For accurate Bayesian ToM inference, the LM undergoes an additional post-training process tailored to the target multimodal contexts. However, this reliance on post-training significantly increases computational demands and limits the scalability of likelihood models, restricting the size of LMs to around seven billion parameters. ToM intricately intertwines **open-domain world knowledge** and **implicit reasoning** to ground human mental states within their corresponding physical environments. As environments and their associated queries evolve, reliance on smaller post-trained LMs introduces a critical trade-off: while smaller LMs excel in adapting to specific ToM tasks within particular environments, larger LMs are indispensable for harnessing broader world knowledge and advanced reasoning capabilities. **This inherent tension poses a significant challenge, requiring us to improve the scalability of Bayesian ToM methods in handling dynamically evolving, multimodal ToM scenarios**

Motivated by the scalability challenge of current Bayesian ToM methods, we propose a scalable Bayesian inference solution that generalises to complex and dynamic environments (Tab.5 in App.A compares our technical contributions with other solutions). Our approach introduces a *weak-to-strong* control mechanism where post-trained smaller LMs specialise in ToM-specific tasks by capturing likelihood inference patterns during Bayesian ToM reasoning. These ToM behaviours are then transferred to larger LMs during test time, aligning the larger models' reasoning trajectories with the structured requirements of Bayesian inverse planning. In this framework, the larger LM acts as the *primary policy model*, leveraging its extensive world knowledge and reasoning capabilities. Importantly, the reasoning trajectory of the larger LM is structured by the Bayesian framework, ensuring consistency, robustness, and interpretability. This design avoids additional post-training costs for larger LMs while enabling scalable use of large models up to **70B** or **405B** parameters.

In particular, we focus on the pattern shifts observed in smaller LMs before and after ToM post-training, treating these shifts as *ToM behaviours* that guide larger LMs. This ToM-behaviour transfer ensures that larger LMs, redirected as **aligned policy models**, follow reasoning trajectories primarily inferenced by the Bayesian framework. The experiments demonstrate that this weak-to-strong control mechanism significantly enhances the generalizability of Bayesian inference, achieving a $\sim 4.6\%$ improvement in accuracy over state-of-the-art methods, even in dynamic and unseen environments.

2 METHODOLOGY: SCALED BAYESIAN REASONING ON MULTIMODAL TOM

Our scaled Bayesian reasoning infers an agent's mental state based on video and text inputs. While the extension of Bayesian methods to deep models can reverse engineer human ToM reasoning in multiple domains, it also includes LMs for multimodal inputs: (1) building unified representations about a scene, a person's actions, and the mental state hypotheses from multimodal inputs, and (2) post-training an LM to conduct contextual inverse symbolic planning, based on unified symbolic representations (Jin et al., 2024). Then, as shown in Fig.1, the LM used in our scaled Bayesian reasoning is from 7B up to 405B parameters at test-time compute, avoiding additional post-training.

2.1 DATA REPRESENTATION

Instead of single-modality input, this study integrates both visual and textual data into a unified symbolic representation, enabling a more comprehensive understanding of the context and human behaviour: *(i)* One visual perception module converts visual data into symbolic representations by using the method from Blukis et al. (2022) to generate a voxel map and construct a scene graph for each video frame. *(ii)* For text parsing, textual information is extracted into symbolic representations of the initial state and subsequent actions. The parser processes the text by breaking it down into

Figure 1: *(left)* The large LM operates as a scaled **policy model** to estimate the likelihood of an agent's actions in dynamic environments, based on multimodal symbolic inputs (video and description). *(right)* The latent reasoning of the large LM is guided by the ToM behaviours from post-trained small LMs, which acts as a weak-to-strong control. Overall, Bayesian inverse planning compares hypotheses about the agent's goal and belief, using the large LM as a policy model to infer ToM.

components: the state of the environment, the actions taken by humans, and the question. It translates these into natural language descriptions, such as *"the pear is inside the basket"* for the environment's state, *"walks toward the kitchen"* for action commands, and two potential goals like *"to retrieve the pear"* and beliefs such as *"the pear is inside the basket"* or *"the pear is not inside the basket."* *(iii)* finally, in unifying multimodal information, the fusion step aligns and integrates input stream information by converting scene graphs from video into predicates that describe spatial relationships and object statuses, analogous to text-derived predicates. We create a symbolic representation of the initial state by combining predicates from both video and text, aligning and updating state predicates with new video frame information at each time step, and constructing a symbolic state and action sequence. This process begins from the initial state, with actions parsed from the text aligned with video-detected actions and divided into intervals corresponding to each action. See App.B.2 for more details on data preprocessing.

2.2 INFERRING HUMAN MENTAL STATES

To infer human mental states, we generate and evaluate hypotheses about human intentions by employing Bayesian inverse planning. These hypotheses are assessed through action likelihoods, which directly inform the posterior probabilities of different mental state explanations. To compute these crucial likelihoods, an LM is controlled by our weak-to-strong mechanism to serve as the policy model. This approach harnesses the world knowledge and reasoning capabilities of large LLMs while aligning their behaviour patterns to ToM tasks without extensive computational requirements.

Behaviour modelling: a Markov decision process formulation   The behaviour of an agent can be formulated as a forward generative model based on a Partially Observable Markov Decision Process (POMDP), defined by the tuple $\langle S, A, \mathcal{T}, G, R, \Omega, O, \gamma \rangle$ (Kaelbling et al., 1998; Jin et al., 2024). Here, $s^t \in S$ and $a^t \in A$ represent the state and action at time t, respectively. $\mathcal{T}(s^t|s, a)$ denotes the state transition probabilities. The goal $g \in G$ determines the reward $r^t = R(s^t, a^t, g)$. The agent's observation $o^t \in \Omega$ is obtained via the observation function $o^t = O(s^t)$. The discount factor is $\gamma \in (0, 1]$. Crucially, the agent's belief, $b(s)$, is a probability distribution over the state. This belief is dynamically updated during belief evolution $P(b^\tau \mid b^{\tau-1}, s^\tau)$, where $b(s)$ is factorized into probabilities over the possible locations of individual objects.

Inverse inference: from observed behaviours to the mental states   While the POMDP formulates a forward model of agent behaviour, the heart of this Bayesian approach is to **invert** this process – inferring the agent's goals and beliefs from observed behaviours, i.e., actions (Baker et al., 2017). Assuming deterministic state transitions for simplicity, we jointly infer the agent's goal and belief based on observed states and actions. The posterior probability of an agent's goal g and belief b^t given a sequence of observed states $s^{1:t}$ and actions $a^{1:t-1}$ is expressed as:

$$P(g, b^t|s^{1:t}, a^{1:t-1}) \propto \prod_{\tau=1}^{t} \pi(a^\tau|g, b^\tau)P(b^\tau|b^{\tau-1}, s^\tau)P(b^0)P(g), \qquad (1)$$

where $\pi(a^\tau|g, b^\tau)$ represents the agent's policy, which captures the probability of taking action a^τ given a goal g and belief b^τ. This reflects the agent's decision-making process, influenced by its goals and the current state of its beliefs. Belief evolution is modeled as $P(b^\tau|b^{\tau-1}, s^\tau) =$

$\frac{P(s^\tau|b^{\tau-1})P(b^{\tau-1})}{P(s^\tau)}$, where $P(s^\tau|b^{\tau-1})$ is the likelihood of observing s^τ given the prior belief $b^{\tau-1}$, and $P(b^{\tau-1})$ represents the prior belief at the previous step. This belief evolution describes how the belief b^τ evolves from the prior belief $b^{\tau-1}$ after observing a new state s^τ, and it follows Bayesian principles, ensuring that new evidence incrementally refines the agent's understanding of its environment. For example, if an object is observed inside a container at time τ, the corresponding belief about the object's location is updated accordingly. **In practice,** $\pi(a^\tau|g, b^\tau)$ and $P(b^\tau|b^{\tau-1}, s^\tau)$ can be approximated using likelihood generated by a language model. $P(b^0)$ is set as a uniform distribution to reflect equal uncertainty about all possible object locations at the start, while $P(g)$ encodes prior knowledge about the likelihood of different goals.

To compare different hypotheses about the agent's goals and beliefs, we evaluate their relative log-likelihoods, separating the contributions from the current time step and the accumulated effect of prior steps. Consider two competing hypotheses, $H_1 = \langle g_1, b_1^t \rangle$ and $H_2 = \langle g_2, b_2^t \rangle$, representing different goal-belief pairs. Their relative log-likelihoods are compared through the following equation:

$$\log \frac{P(g_1, b_1^t|s^{1:t}, a^{1:t})}{P(g_2, b_2^t|s^{1:t}, a^{1:t})} = \underbrace{\log \frac{\pi(a^t|g_1, b_1^t)}{\pi(a^t|g_2, b_2^t)} + \log \frac{P(b_1^t|\hat{b}^{t-1}, s^t)}{P(b_2^t|\hat{b}^{t-1}, s^t)}}_{\text{Current step comparison}} + \underbrace{\sum_{\tau=1}^{t-1} \log \frac{\pi(a^\tau|g_1, \hat{b}^\tau)}{\pi(a^\tau|g_2, \hat{b}^\tau)}}_{\text{Prior steps comparison}}, \quad (2)$$

where $\hat{b}^\tau$ represents the belief estimate from a prior step. The first term compares log-likelihoods of actions and belief updates at the current step, reflecting how each hypothesis explains the agent's latest behavior. The second term sums log-likelihoods from prior steps, ensuring the entire action history informs the hypothesis evaluation. This ensures that the policy model incorporates the entire action history when evaluating which hypothesis better explains the agent's observed behavior.

Weak-to-strong controlled large policy model When augmenting likelihood estimation with the guided large LM's broad generalization capabilities, we scale up the LM used only for test-time computing and avoid the direct post-training on large LM. Within the Bayesian framework, the true policy $\pi(a^\tau \mid g, b^\tau)$ is estimated through a language model (π)-estimated probability $\tilde{\pi}(a^t \mid s^t, g, \hat{b}^t)$:

$$\pi(a^\tau \mid g, b^\tau) = \tilde{\pi}(a^t \mid s^t, g, \hat{b}^t) + \varepsilon, \quad (3)$$

where ε means the inherent approximation error during estimation. When incorporated into the posterior probability framework (i.e., Bayesian inverse planning in equation 1), it yields:

$$P(g, b^t \mid s^{1:t}, a^{1:t-1}) \propto \prod_{\tau=1}^{t} [\tilde{\pi}(a^\tau \mid s^\tau, g, \hat{b}^\tau) + \varepsilon] \cdot P(b^\tau \mid b^{\tau-1}, s^\tau) \cdot P(b^0)P(g). \quad (4)$$

It shows how the approximation can fit into Bayesian frameworks, accounting for actions, states, and belief updates over time.

POST-TRAINING STAGE: TOM OPTIMIZATION To allow direct use of the LM-estimated probability, we aim to reduce ε via a post-training stage to align LM's pretrained capability to current target situations. The initial phase of reducing ε involves refining a scenario-specific post-training policy $\pi^{\mathcal{E}}$ on an action-policy experience pool. This pool $\mathcal{D}$ is defined as: $\mathcal{D} = \{(s_i, b_i, g_i, a_i)\}_{i=1}^N$, where s_i, b_i, g_i, a_i, and N denote sequences of states, beliefs, goals, actions, the number of data points sourced from multimodal situations. The objective function guiding post-training is:

$$\mathcal{L}(\pi^{\mathcal{E}}) = -\sum_{i=1}^{N} \log \pi^{\mathcal{E}}(a_i \mid s_i, b_i, g_i). \quad (5)$$

Here, $\pi^{\mathcal{E}}$ learns the human ToM behaviour patterns effectively, allowing the language model policy to adeptly learn and respond to complex ToM environments. Due to computational constraints, this post-training process is typically applied to smaller models, making it more resource-efficient while ensuring alignment with ToM tasks.

INFERENCE STAGE: LARGE POLICY MODEL WITH BEHAVIORAL GUIDANCE During test inference, we leverage the behaviour acquired by the post-trained smaller LM to guide the reasoning of a larger,

more capable LM. This approach dynamically adjusts the output of the large LM based on the shift observed between a post-trained small LM $\pi^{\mathcal{E}}$ and a naive small LM $\pi^{\mathcal{N}}$. At each inference step t, the overall policy distribution for the redirected large model is given by:

$$\bar{\pi}(a^t \mid s^t, g, \hat{b}^t) = \frac{1}{\bar{Z}} \pi^{\mathcal{L}}(a^t \mid s^t, g, \hat{b}^t) \frac{\pi^{\mathcal{E}}(a^t \mid s^t, g, \hat{b}^t)}{\pi^{\mathcal{N}}(a^t \mid s^t, g, \hat{b}^t)}, \tag{6}$$

where $\pi^{\mathcal{L}}(a^t \mid s^t, g, \hat{b}^t)$ represents the policy distribution from the naive large LM. The post-training effect to policy function is *approximated* through the ratio $\frac{\pi^{\mathcal{E}}(a^t|s^t,g,\hat{b}^t)}{\pi^{\mathcal{N}}(a^t|s^t,g,\hat{b}^t)}$, offering an on-the-fly redirecting mechanism. The normalization factor is calculated by $\bar{Z} = \sum_{a^t} \pi^{\mathcal{L}}(a^t \mid s^t, g, \hat{b}^t) \frac{\pi^{\mathcal{E}}(a^t|s^t,g,\hat{b}^t)}{\pi^{\mathcal{N}}(a^t|s^t,g,\hat{b}^t)}$. It ensures that the resulting probabilities remain a valid distribution, reflecting both the post-training adjustments and the foundational likelihood from the larger model. Our overall method facilitates ToM behaviour transfer from the post-trained small LM ($\pi^{\mathcal{E}}$) to the larger LM ($\pi^{\mathcal{L}}$), scaling the capabilities of the policy model in Bayesian inference at test-time. The Theroem 1 and its proof in the appendix C are provided for theoretical support.

3 EXPERIMENTS

We examine the **scaling benefits** of this Bayesian weak-to-strong reasoning in multimodal ToM tasks. For the *strong* component, we scale up the large LMs to 70B and 405B parameters. In contrast, for the *weak* component, we reduce the size of the small LMs from 8B to 4B parameters. First, the results reveal a positive correlation between model size and ToM capabilities, especially when the larger models are guided by the post-trained behaviours of the smaller models. Interestingly, these post-trained behaviours are also effectively captured by smaller LMs. We also illustrate how the large LMs are progressively redirected to the answer space during the Bayesian process.

3.1 SETUP

Datasets   *(i) For post-training*, we use MMToM sampled from an apartment environment simulator, Virtual Home (Puig et al., 2018), using the procedural methods described by Jin et al. (2024). The dataset comprises 1,000 procedurally synthesized videos within a realistic household simulator, each annotated with ground-truth labels for states, goals, beliefs, and actions. These precise annotations are used to train our conditional prediction model for action a_i given state s_i, belief b_i, and goal g_i: $P(a_i \mid s_i, b_i, g_i)$. By leveraging this synthetic dataset, the inverse symbolic planner—comprising a large base LM guided by a smaller, post-trained LM—acquires robust exposure to diverse scenarios. *(ii) For evaluation*, we use the MMToM-QA (Jin et al., 2024), an evaluation benchmark aimed at evaluating ToM reasoning over multimodal situations. The dataset consists of 134 videos, each showing a person searching for household objects, with an average of 1,462 frames per video representing approximately 36 human actions. These videos are accompanied by 600 questions (detailed in appendix §D.1), evenly divided between the categories of belief inference (with 1.1, 1.2, and 1.3 subtasks) and goal inference (with 2.1, 2.2, 2.3, and 2.4 subtasks). Each question is paired with a video clip and a detailed textual description The questions are designed to assess the ability of models to infer goals and beliefs jointly, providing a richer assessment of multimodal ToM capabilities. It supports three setups, including multimodal, text-only, and video-only inputs.

Baselines   We include three types of baselines in our evaluation to benchmark our model's performance on the MMToM-QA dataset. *For text-only evaluation*, we compare performance in the text-only subset of MMToM-QA using various large language models (LLMs), including GPT-4 (OpenAI, 2023a), GPT-3.5, GPT-J-6B (Wang & Komatsuzaki, 2021), and Llama-2-7B (Touvron et al., 2023). Advanced prompting methods, such as SimToM (Wilf et al., 2024) and SymbolicToM (Sclar et al., 2023), which enhance GPT-4's reasoning capabilities, provide additional baselines (e.g., SimToM with GPT-4 and SymbolicToM with GPT-4). *For multimodal evaluation*, we include GPT-4V (OpenAI, 2023a), InstructBLIP (Dai et al., 2023), Video-Llama-2 (Zhang et al., 2023), and LLaVA (Liu et al., 2023), BIPALM (Jin et al., 2024). These methods employ sampled frames from each video to evaluate their proficiency in multimodal ToM reasoning. *For human*, 180 participants answer 120 randomly sampled questions, covering all question types, as reported by Jin et al. (2024).

Table 1: Comparisons between humans and models across task types from 1.1 to 2.4 are provided. The best results for each modal setting are highlighted in **bold**. The second best results in multimodality are underlined. Rows of ours are highlighted in color.

	method	belief inference				goal inference					all
		1.1	1.2	1.3	avg.	2.1	2.2	2.3	2.4	avg.	
text only	*Human*	96.0	95.8	81.3	91.0	85.8	76.7	65.0	68.3	74.0	82.5
	GPT-4	97.0	12.0	77.0	62.0	48.0	42.7	2.7	42.7	34.0	48.0
	GPT-3.5	81.0	11.0	39.0	43.7	46.7	16.0	21.3	48.0	33.0	38.3
	GPT-J-6B	56.0	53.0	38.0	49.0	52.0	50.7	**50.7**	56.0	52.3	50.7
	Llama-2-7B	64.0	55.0	50.0	56.3	49.3	48.0	41.3	38.7	44.3	50.3
	SimToM *w/* GPT-4	96.0	15.0	82.0	64.3	61.3	44.0	2.7	54.7	40.7	52.5
	SymbolicToM *w/* GPT-4	**100**	61.0	74.0	78.3	73.3	66.7	0.0	50.7	47.7	63.0
	BIPALM *w/* GPT-J-6B	88.0	**69.0**	88.0	81.7	**77.3**	**68.0**	30.7	**70.7**	**61.7**	**71.7**
	BIPALM *w/* Llama-2-7B	89.0	68.0	**90.0**	**82.3**	54.7	66.7	**50.7**	62.7	58.7	70.5
video only	*Human*	69.1	64.3	86.4	73.3	58.5	60.0	76.7	63.3	64.6	68.9
	InstructBLIP-13B	56.0	50.0	42.0	49.3	56.0	45.3	54.7	53.3	52.3	50.8
	Video-Llama-2-13B	24.0	32.0	67.0	41.0	50.7	45.3	**56.0**	52.0	51.0	46.0
	LLaVA-7B	33.0	15.0	69.0	39.0	44.0	24.0	**56.0**	57.3	45.3	42.2
	GPT-4V	64.0	34.0	39.0	45.7	54.7	26.7	48.0	56.0	46.3	46.0
	BIPALM *w/* GPT-J-6B	63.0	57.0	**72.0**	**64.0**	45.3	**62.7**	50.7	**62.7**	55.3	59.7
	BIPALM *w/* Llama-2-7B	**69.0**	**63.0**	60.0	**64.0**	**62.7**	54.7	53.3	**62.7**	**58.3**	**61.2**
multimodal	*Human*	95.8	96.7	100	97.5	90.0	91.7	83.3	88.9	88.5	93.0
	InstructBLIP-13B	62.0	52.0	32.0	48.7	46.7	29.3	42.7	60.0	44.7	46.7
	Video-Llama-2-13B	36.0	38.0	52.0	42.0	36.0	41.3	30.7	45.3	38.3	40.2
	LLaVA-7B	46.0	14.0	69.0	43.0	65.3	22.7	40.0	48.0	44.0	43.5
	GPT-4V	**94.0**	13.0	59.0	55.3	56.0	26.7	4.0	52.0	34.7	44.0
	BIPALM *w/* GPT-J-6B	90.0	69.0	86.0	81.7	68.0	78.7	56.0	73.3	69.0	75.3
	BIPALM *w/* Llama-2-7B	88.0	68.0	85.0	80.3	62.7	77.3	72.0	**80.0**	73.3	76.7
	Ours (*w/* Llama-3.1-405B)	92.0	**76.0**	**93.0**	**87.0**	73.3	**80.0**	**76.0**	78.7	**77.0**	**81.3**

Post-training We post-train Llama (Touvron et al., 2023; Dubey et al., 2024) as a policy model in our Bayesian framework with LoRA (Hu et al., 2022), as outlined in Tab.6. Following the setup recommended by Jin et al. (2024), we use a learning rate of 1e-3 over 3 epochs. LoRA is configured with a rank of 16 and an alpha value of 32 for the 7B and 8B LMs. For 70B, we use a lower rank of 8 and an alpha of 16. They are carefully tuned to optimize performance across varying LM sizes.

3.2 MAIN RESULTS

Tab.1 uses human performance as the gold standard. Humans clearly outperform all models (with 93.0% accuracy) when provided with multimodal input. This result highlights the **critical role of integrating both visual and textual modalities** in achieving an immersive and context-aware perception of the ToM situation. Accordingly, our ToM method also incorporates multimodal inputs. In *belief inference, which is strongly linked to world knowledge*, models like GPT-4 and GPT-3.5 perform exceptionally well, particularly on task 1.1, where GPT-4 achieves an accuracy of 94%. This result underscores the importance of large-scale models in capturing and applying vast amounts of pretrained world knowledge. However, despite their impressive performance in belief inference, these models do not perform as effectively on *goal inference, where adaptation to specific ToM contexts and dynamic environments is crucial*. **This highlights the need for models to be better aligned with the specific requirements of ToM scenarios.** Models with smaller scales, such as those with 6B, 7B, and 13B parameters, face inherent capability limitations, which restrict their performance on belief inference tasks, particularly when compared to larger models like GPT-4 on task 1.1. However, these smaller models, such as BIPALM w/ GPT-J-6B and Llama-2-7B, benefit from post-training specifically designed for ToM scenarios. This allows them to perform better on goal inference tasks, where understanding and adapting to scenario-specific environmental dynamics is essential. **Despite their size constraints, these models demonstrate the value of targeted post-training in compensating for the lack of large-scale pretrained knowledge.** Our approach goes beyond seesaw effects in prior methods and has both strengths: while its strong component leverages the extensive world knowledge embedded in large pretrained models, also its weak component incorporates post-

Table 2: Scaling-up performance on strong component (large LMs) in weak-to-strong control.

LM	config	belief inference				goal inference					all
		1.1	1.2	1.3	avg.	2.1	2.2	2.3	2.4	avg.	
Llama-2	7B-zero-shot	44.00	37.00	84.00	55.00	64.00	65.33	62.67	64.00	64.00	60.14
	7B-post-trained	80.00	60.00	89.00	76.33	74.67	60.00	**78.67**	66.67	70.00	72.71
	70B-zero-shot	64.00	47.00	**93.00**	68.00	56.00	72.00	25.33	70.67	56.00	61.14
	70B-post-trained	**90.00**	**70.00**	87.00	_82.33_	**78.67**	**76.00**	61.33	_72.00_	_72.00_	_76.43_
	70B-ours	_89.00_	**70.00**	_90.00_	**83.00**	73.33	_74.67_	_76.00_	73.33	74.33	**78.05**
Llama-3	8B-zero-shot	88.00	_72.00_	91.00	_83.67_	65.33	57.33	13.33	53.33	47.33	62.90
	8B-post-trained	**92.00**	_72.00_	83.00	82.33	**77.33**	_73.33_	_72.00_	70.67	73.33	_77.19_
	70B-zero-shot	69.00	67.00	**95.00**	77.00	42.67	_70.67_	16.00	52.00	45.33	58.90
	70B-post-trained	_91.00_	70.00	89.00	83.33	_73.33_	**74.67**	44.00	69.33	65.33	73.05
	70B-ours	_91.00_	**75.00**	_92.00_	**86.00**	68.00	_72.00_	**74.67**	**78.67**	73.33	**78.76**
Llama-3.1	8B-zero-shot	88.00	72.00	91.00	83.67	65.33	62.67	22.67	54.67	51.33	65.19
	8B-post-trained	90.00	71.00	93.00	84.67	69.33	72.00	62.67	72.00	69.00	75.71
	70B-zero-shot	85.00	63.00	93.00	80.33	72.00	76.00	16.00	61.33	56.33	66.62
	70B-post-trained	_91.00_	69.00	**95.00**	85.00	69.33	80.00	29.33	69.33	62.00	71.86
	405B-zero-shot	86.00	70.00	90.00	82.00	73.33	78.67	21.33	66.67	60.00	69.43
	70B-ours	90.00	_74.00_	_93.00_	_85.67_	**74.67**	_77.33_	_70.67_	76.00	_74.67_	_79.38_
	405B-ours	**92.00**	**76.00**	_93.00_	**87.00**	_73.33_	**80.00**	**76.00**	**78.67**	**77.00**	**81.29**

training to the ToM contexts and environmental dynamics required. This dual advantage allows a balanced performance across both task types (belief & goal inference), **with an overall 81.3% accuracy on multimodal tasks and exhibits a 4.6% improvement over the existing best baseline.**

3.3 STRONGER LARGE LMS ENHANCE LIKELIHOOD ESTIMATION IN BAYESIAN INFERENCE

In the Bayesian framework, we explore the role of LMs in likelihood estimation and examine how their scale and post-training affect performance across various ToM tasks. According to Tab.2, *(i)* **our results demonstrate a positive correlation between LM size and ToM task performance.** For instance, in the zero-shot setting of Llama-3.1, the 405B model achieves an accuracy of 69.43%, outperforming both the 8B model (65.19%) and the 70B model (66.62%). Notably, the performance of the 405B model approaches that of the post-trained Llama2-7B. Furthermore, the improvement from 70B to 405B suggests that the benefits of scaling have not yet reached saturation, indicating potential for further gains with larger models. *(ii)* **Post-training significantly enhances LMs' performance on ToM tasks, even when Larger LMs already perform well in zero-shot scenarios.** This effect is consistent across model sizes, from smaller models such as 7B/8B to larger models up to 70B, regardless of the specific version (Llama-2, Llama-3, or Llama-3.1). For belief inference tasks, which are closely tied to world knowledge, post-training helps align the large models' knowledge more precisely with the input questions. For goal inference tasks, which are linked to environmental dynamics, post-training refines the models' atomic-level reasoning (i.e., predicting a based on s, b, g), resulting in greater improvements compared to belief inference. This suggests that post-training provides a more substantial benefit for tasks that require dynamic reasoning. *(iii)* **Our weak-to-strong control approach** *approximates* **the benefits of direct post-training in Bayesian inference.** When comparing models such as Llama-2, Llama-3, and Llama-3.1, we find that direct post-training on the 70B model, even with adjusted hyperparameters from the 8B model (e.g., reducing the alpha value from 32 to 16), does not produce results as robust as our method. We attribute this to the difficulty of finding optimal hyperparameters for larger models, which require more extensive tuning. In contrast, our weak-to-strong control, which uses a well-trained smaller LM to guide the larger LMs, allows for more consistent improvements without the need for extensive hyperparameter trials.

3.4 DOWNSIZED SMALL LMS KEEP EFFECTIVENESS IN WEAK-TO-STRONG CONTROL

In the Bayesian framework, prior experiments show that post-trained behaviours from small LMs can effectively guide the pretrained capabilities of larger LMs during test time. To further study the role of post-training to weak-to-strong control, Tab.3 investigates whether post-trained behaviours can be learned effectively with reduced computational resources, while the pretrained capabilities of larger LMs are still available. Specifically, we examine whether *downsized* smaller LMs can effectively

Table 3: Scaling-down effect on weak part (small LMs) in weak-to-strong controlled Bayesian reasoning. All models are based on Llama3.1. Rows of our method are highlighted in color.

LM	config	belief inference				goal inference					all
		1.1	1.2	1.3	avg.	2.1	2.2	2.3	2.4	avg.	
8B	zero-shot	88.00	72.00	91.00	83.67	65.33	62.67	22.67	54.67	51.33	65.19
	post-trained	90.00	71.00	93.00	84.67	69.33	72.00	62.67	72.00	69.00	75.71
	8B ↣ 70B	**90.00**	**74.00**	**93.00**	**85.67**	**74.67**	**77.33**	**70.67**	**76.00**	**74.67**	**79.38**
4B wid.	zero-shot	79.00	69.00	89.00	79.00	60.00	69.33	24.00	52.00	51.33	63.19
	post-trained	90.00	72.00	87.00	83.00	70.67	72.00	68.00	**78.67**	72.33	76.90
	4B-width ↣ 70B	**90.00**	71.00	90.00	83.67	74.67	74.67	76.00	73.33	**74.67**	78.52
4B dep.	zero-shot	91.00	**74.00**	88.00	84.33	69.33	**77.33**	20.00	66.67	58.33	69.48
	post-trained	91.00	71.00	90.00	84.00	65.33	65.33	76.00	**69.33**	69.00	75.43
	4B-depth ↣ 70B	91.00	72.00	**91.00**	**84.67**	72.00	74.67	**84.00**	64.00	73.67	78.38

Table 4: Transfer performance of the Bayesian method with different scaling settings (zero-shot, direct post-training, and our weak-to-strong control) from the apartment scenario to various unseen environments. All models are based on Llama3.1. Results are average accuracy of *belief inference/goal inference/overall* for each scenario. Detailed unseen scenarios and results are in §D.8&D.9.

	solution	apartment *(seen)*	Andersen tales	ancient Egyptian	outer space	wild west	medieval castle
Raw	70B-zero-shot	80.3/56.3/66.6	83.6/60.6/70.2	83.6/60.6/69.3	84.0/58.0/69.1	82.6/57.6/68.3	82.6/57.6/68.3
	70B-post-trained	85.0/62.0/71.8	84.6/66.3/74.1	84.6/66.3/75.3	83.0/66.0/73.2	81.0/65.0/71.8	81.0/65.0/71.8
Ours	**4B-wide ↣ 70B**	83.6/74.6/78.5	84.0/75.3/79.0	83.0/75.3/79.1	82.6/75.3/78.4	84.0/74.6/78.6	84.6/73.0/78.0
	4B-depth ↣ 70B	84.6/73.6/78.3	85.0/71.3/77.1	85.3/71.3/77.9	81.6/71.0/75.5	83.3/71.3/76.4	83.3/64.0/72.2
	8B ↣ 70B	85.6/74.6/79.3	82.6/76.0/78.8	83.6/76.0/77.7	84.0/75.0/78.8	83.3/74.0/78.0	83.6/75.0/78.7
	8B ↣ 405B	87.0/77.0/81.3	85.8/76.0/80.2	86.0/76.3/80.4	87.2/75.5/80.5	85.3/76.0/79.9	85.6/75.2/79.7

capture these post-trained behaviours and guide the pre-trained capabilities of larger LMs without compromising performance. We use 8B LMs as baselines in normal size, and we also downsize them to two 4B variants: Llama-3.1-Minitron-4B-Width, which reduces the hidden size of each layer; and Llama-3.1-Minitron-4B-Depth, which cuts the number of layer (Sreenivas et al., 2024). Despite their smaller size, they maintained comparable accuracy in weak-to-strong control. While the 4B-Width LM underperformed the 4B-Depth LM in zero-shot scenarios, its post-training results surpass the 4B-Depth, especially when controlling the 70B large LM, demonstrating its superior transferability. These results highlight two key points: *(i) downsizing the weak component can* **still effectively guide larger LMs without a significant loss in accuracy, and *(ii)* reducing model width, rather than depth, tends to be more generalizable, as deeper models demonstrate better transferability**—aligning with learning principles of the width-depth trade-offs in small-scale studies (Telgarsky, 2016; Lu et al., 2017; Raghu et al., 2017).

3.5 Transferability of scaled Bayesian inference

Although the small LMs are post-trained on the *apartment*, our overall framework is expected to be stable and generalizable across various unseen scenarios since it has the structured Bayesian framework and redirected larger LMs. To evaluate the transferability, Tab.4 compares our method with baseline models in five previously unseen scenarios: *Andersen fairy tales, ancient Egyptian, outer space, wild west, and medieval castle*. These diverse settings assess the generalisability of our approach beyond the post-training scenario. When scaling the strong component (i.e., the large controlled LMs) from 70B to 405B across these new scenarios, there are continuous improvements in ToM understanding. **This demonstrates that the increased capacity of our scaled solution enhances the transferability of ToM reasoning across multiple dynamic and unseen environments.** Furthermore, when the weak controller component is reduced from 8B to 4B, performance remains stable, ranging between 78.0% and 79.15%. This result is comparable to the 79.05% accuracy achieved in the original apartment scenario and also remains close to the performance of the 8B LMs. This consistency suggests that downsizing the weak component does not significantly affect performance, even in new and diverse test environments. **These results indicate that our approach has strong potential for continually downsizing smaller LMs as controllers since they also are**

capable of capturing the post-trained behaviours. It allows saved resources to be potentially allocated to stronger controlled LMs, while still keeping stable to scenarios unseen previously.

3.6 Weak-to-strong control redirects large LM's latent reasoning

To quantify the influence of the weak controller during Bayesian inference, we analyze the changes in likelihood estimates before and after applying weak-to-strong control at each Bayesian step. As shown in Fig.2, we sample ten test cases from five datasets and average the results. It illustrates the progressively increasing magnitude of likelihood changes as Bayesian inference progresses: *(i)* At the beginning of Bayesian inference, when the large LM is close to a general initial state, the likelihood changes are minimal. This is because the general state aligns closely with pretrained world knowledge, requiring little correction from ToM-specific behaviours; *(ii)* As the model approaches a more specialized final hypothesis, the likelihood estimates are increasingly redirected. This occurs because the specialized scenarios demand ToM-specific behaviours, which the post-trained small LMs are fine-tuned to capture. The post-trained small LMs are specifically fine-tuned to the ToM context, enabling them to model human actions, goals, beliefs, and environmental states across various ToM scenarios. **Overall, this analysis finds that the weak component progressively redirects the latent reasoning of larger models, guiding them toward more accurate ToM predictions among diverse scenarios throughout the Bayesian inference process.**

Figure 2: Likelihood change during Bayesian inference under weak-to-strong control. Results are averaged over ten sampled cases across five different unseen scenarios.

3.7 Post-training aligns large LM's likelihood estimation at the concept level

Previous experiments demonstrated that post-training on small LMs can progressively guide the behaviour of large LMs throughout Bayesian inference. Now, we further focus on how post-trained small LMs influence large LMs' likelihood estimation **at the concept level**. Fig.3 shows the execution of ten inference trials with a temperature of 0.7. The scenario involves the agent James interacting with objects in an apartment, aiming to retrieve a bottle of wine. The initial state s_i is *pear in the basket, no wine*, the belief b_i is *wine in the cabinet*, the goal g_i is *obtain a bottle of wine*, and the action a_i is *open basket, walk to cabinet*. The baseline small LM assigns lower likelihoods

Figure 3: Likelihood estimation across different levels of concept granularity (rooms, furniture, and items) for base small LM, post-trained small LM, and base large LM. The Bayesian framework uses an LM as the **policy model** to infer actions conditioned on states, beliefs, and goals, where actions often refer to fine-grained item-level concepts (e.g., wine, wine glass). It highlights the trend of how each model allocates likelihood across these concept levels. The ToM scenario of this case is detailed at §D.7.

to fine-grained item-level
concepts (e.g., wine, wine
glass). After post-training,
the small LM significantly shifts its focus toward item-level concepts, aligning its predictions more
closely with the action space. This adjustment increases the likelihood assigned to critical items like
wine and wine glass, which are necessary for accurately predicting the agent's goal. Consequently,
post-training enables the small LM to better capture fine-grained details of the agent's behaviour,
improving ToM predictions. In contrast, the large LM distributes its likelihood more evenly across
all levels, from rooms to items, reflecting a broad understanding of the environment. While this
approach captures general spatial awareness—identifying key areas like the kitchen and furniture like
the cabinet—it lacks the sharp focus on fine-grained details, such as wine and wine glass, which are
crucial for this task. As a result, the large LM may struggle with tasks that require precise, item-level
predictions. Overall, post-training helps the small LM focus on item-level concepts, making it more
effective for this task. While the large LM captures a broader understanding of the environment,
it benefits from post-trained behaviours that redirect its likelihood estimation toward fine-grained,
item-level predictions. **This finding reflects the role of post-trained small LMs in guiding large
LMs' concepts toward more precise ToM reasoning.**

4 RELATED WORK

Modelling human mental states There are many studies on understanding human behaviour by
classifying and predicting physical motion patterns (Aggarwal & Ryoo, 2011; Caba Heilbron et al.,
2015; Choi & Savarese, 2013; Shu et al., 2015). Beyond physical behaviour, some studies focus
specifically on modeling human mental states, i.e. ToM. ToM models have followed two broad
approaches: Bayesian methods and end-to-end deep learning. Bayesian ToM models (Baker et al.,
2017; Jara-Ettinger, 2019; Shu et al., 2021) rely on structured probabilistic frameworks to infer
mental states from sparse observations of human behaviour. On the other hand, end-to-end models
such as ToMnet (Rabinowitz et al., 2018; Shu et al., 2021; Sclar et al., 2022) have been trained
directly on ToM tasks, learning relationships between data patterns without explicit causal models of
mental states (Sap et al., 2022; Zhi-Xuan et al., 2022; Ullman, 2023). More recently, neurosymbolic
reasoning systems use the neural models for feature extraction, while also incorporating probabilistic
models for structured reasoning (Wong et al., 2023; Ying et al., 2024; 2023). They face challenges in
dynamic and multimodal environments, where both physical and mental state reasoning are required.
Different from prior studies, our work operates in more complex and dynamic multimodal ToM
environments, where physical actions and mental state reasoning are intertwined.

Post-training LLMs for downstream tasks Post-training can project the pre-trained capabilities
of LMs into downstream tasks such as dialogue generation (Ouyang et al., 2022), human value
alignment (Bai et al., 2022), and multimodal tasks (OpenAI, 2023b; Liu et al., 2023). Previous
approaches have also used reweighting techniques to adjust the output predictions of fine-tuned
LLMs, interpolating the effects of fine-tuning with pre-trained knowledge to achieve human-centered
and trustworthy text generation (Liu et al., 2021; Mitchell et al., 2024; Liu et al., 2024). More
recently, LLMs are post-trained as large action/policy models for decision-making in embodied
agents, allowing them to interact with and explore environments (Kim et al., 2024; Szot et al., 2024;
Li et al., 2024). Our study differs by framing LMs as **policy models** in the context of Bayesian inverse
inference, specifically to model human mental states. We address the limitations of existing ToM
methods by scaling large policy models at test time using a likelihood redirection strategy, reasoning
more accurately in complex ToM scenarios. See App.A.1 for additional discussions.

5 DISCUSSION AND CONCLUSION

This study investigates scalable Bayesian inference in complex and dynamic ToM environments.
Existing methods based on normal-sized LMs often fail to provide sufficient reasoning capabilities
and world knowledge, particularly when used as likelihood estimators in diverse challenging ToM
scenarios. To overcome these limitations, we propose a method that abstracts and transfers the
post-trained behavioral patterns of smaller LMs. This approach allows the extensive world knowledge
of large LMs to be progressively redirected towards ToM reasoning tasks. The weak-to-strong control

mechanism enables scalable reasoning by using small, post-trained LMs to guide large LMs at test time. This approach avoids additional post-training resources for large models, yet allows effective test-time scaling of Bayesian ToM reasoning even in dynamic and complex scenarios.

ETHICS STATEMENT

This study introduces new approaches for scaling Bayesian ToM inference and is accompanied by the release of new datasets representing diverse cultural contexts. We emphasize that these datasets are either based on ancient or fictional cultures, which reduces the sensitivity to contemporary real-world issues. The content of these datasets has been carefully reviewed to avoid concerns related to discrimination, bias, and fairness. They do not involve any real individuals, ensuring that no privacy or security issues are implicated. We remain committed to responsible use and encourage continued scrutiny of potential biases or unintended consequences that may arise in future work.

REPRODUCIBILITY STATEMENT

We are committed to ensuring that the methods in this paper are fully reproducible. The detailed descriptions of the methods, datasets, and experimental settings are in the main section and appendix, with further elaborations in the anonymous repository: https://anonymous.4open.science/r/scale-bayesian-tom-248B

REFERENCES

Jake K Aggarwal and Michael S Ryoo. Human activity analysis: A review. *ACM Computing Surveys*, 2011.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, Nicholas Joseph, Saurav Kadavath, Jackson Kernion, Tom Conerly, Sheer El-Showk, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Tristan Hume, Scott Johnston, Shauna Kravec, Liane Lovitt, Neel Nanda, Catherine Olsson, Dario Amodei, Tom Brown, Jack Clark, Sam McCandlish, Chris Olah, Ben Mann, and Jared Kaplan. Training a helpful and harmless assistant with reinforcement learning from human feedback. *Anthropic*, 2022.

Chris L Baker, Julian Jara-Ettinger, Rebecca Saxe, and Joshua B Tenenbaum. Rational quantitative attribution of beliefs, desires and percepts in human mentalizing. *Nature Human Behaviour*, 2017.

Valts Blukis, Chris Paxton, Dieter Fox, Animesh Garg, and Yoav Artzi. A persistent spatial semantic representation for high-level natural language instruction execution. In *Conference on Robot Learning*, 2022.

Fabian Caba Heilbron, Victor Escorcia, Bernard Ghanem, and Juan Carlos Niebles. Activitynet: A large-scale video benchmark for human activity understanding. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2015.

Wongun Choi and Silvio Savarese. Understanding collective activitiesof people from videos. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2013.

Yung-Sung Chuang, Yujia Xie, Hongyin Luo, Yoon Kim, James R. Glass, and Pengcheng He. Dola: Decoding by contrasting layers improves factuality in large language models. In *The Twelfth International Conference on Learning Representations*, 2024.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. InstructBLIP: Towards general-purpose vision-language models with instruction tuning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Daniel C. Dennett. Précis of The Intentional Stance. *Behavioral and Brain Sciences*, 1988.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Alison Gopnik and Henry M Wellman. Reconstructing constructivism: causal models, bayesian learning mechanisms, and the theory theory. *Psychological bulletin*, 2012.

Chi Han, Jialiang Xu, Manling Li, Yi Fung, Chenkai Sun, Nan Jiang, Tarek Abdelzaher, and Heng Ji. Word embeddings are steers for language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Julian Jara-Ettinger. Theory of mind as inverse reinforcement learning. *Current Opinion in Behavioral Sciences*, 2019.

Chuanyang Jin, Yutong Wu, Jing Cao, Jiannan Xiang, Yen-Ling Kuo, Zhiting Hu, Tomer Ullman, Antonio Torralba, Joshua B Tenenbaum, and Tianmin Shu. MMToM-QA: Multimodal theory of mind question answering. In *Annual Meeting of the Association for Computational Linguistics*, 2024.

Leslie Pack Kaelbling, Michael L Littman, and Anthony R Cassandra. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 1998.

Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan P Foster, Pannag R Sanketi, Quan Vuong, Thomas Kollar, Benjamin Burchfiel, Russ Tedrake, Dorsa Sadigh, Sergey Levine, Percy Liang, and Chelsea Finn. OpenVLA: An open-source vision-language-action model. In *Annual Conference on Robot Learning*, 2024.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and brain sciences*, 2017.

Xinghang Li, Minghuan Liu, Hanbo Zhang, Cunjun Yu, Jie Xu, Hongtao Wu, Chilam Cheang, Ya Jing, Weinan Zhang, Huaping Liu, Hang Li, and Tao Kong. Vision-language foundation models as effective robot imitators. In *The Twelfth International Conference on Learning Representations*, 2024.

Alisa Liu, Maarten Sap, Ximing Lu, Swabha Swayamdipta, Chandra Bhagavatula, Noah A. Smith, and Yejin Choi. DExperts: Decoding-time controlled text generation with experts and anti-experts. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics and the International Joint Conference on Natural Language Processing*, 2021.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Tianlin Liu, Shangmin Guo, Leonardo Bianco, Daniele Calandriello, Quentin Berthet, Felipe Llinares, Jessica Hoffmann, Lucas Dixon, Michal Valko, and Mathieu Blondel. Decoding-time realignment of language models. In *Proceedings of the International Conference on Machine Learning*, 2024.

Zhou Lu, Hongming Pu, Feicheng Wang, Zhiqiang Hu, and Liwei Wang. The expressive power of neural networks: A view from the width. In *Advances in neural information processing systems*, 2017.

Ziqiao Ma, Jacob Sansom, Run Peng, and Joyce Chai. Towards a holistic landscape of situated theory of mind in large language models. In *Findings of the Association for Computational Linguistics: Conference on Empirical Methods in Natural Language Processing*, 2023.

Eric Mitchell, Rafael Rafailov, Archit Sharma, Chelsea Finn, and Christopher D Manning. An emulator for fine-tuning large language models using small language models. In *The Twelfth International Conference on Learning Representations*, 2024.

OpenAI. Gpt-4 technical report. *arXiv:2303.08774*, 2023a.

OpenAI. GPT-4V(ision) system card, 2023b.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, 2022.

Xavier Puig, Kevin Ra, Marko Boben, Jiaman Li, Tingwu Wang, Sanja Fidler, and Antonio Torralba. Virtualhome: Simulating household activities via programs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018.

Neil Rabinowitz, Frank Perbet, Francis Song, Chiyuan Zhang, SM Ali Eslami, and Matthew Botvinick. Machine theory of mind. In *International conference on machine learning*, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 2019.

Maithra Raghu, Ben Poole, Jon Kleinberg, Surya Ganguli, and Jascha Sohl-Dickstein. On the expressive power of deep neural networks. In *International Conference on Machine Learning*, 2017.

Maarten Sap, Ronan Le Bras, Daniel Fried, and Yejin Choi. Neural theory-of-mind? on the limits of social intelligence in large LMs. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 2022.

Melanie Sclar, Graham Neubig, and Yonatan Bisk. Symmetric machine theory of mind. In *International Conference on Machine Learning*, 2022.

Melanie Sclar, Sachin Kumar, Peter West, Alane Suhr, Yejin Choi, and Yulia Tsvetkov. Minding language models' (lack of) theory of mind: A plug-and-play multi-character belief tracker. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, 2023.

Tianmin Shu, Dan Xie, Brandon Rothrock, Sinisa Todorovic, and Song-Chun Zhu. Joint inference of groups, events and human roles in aerial videos. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2015.

Tianmin Shu, Abhishek Bhandwaldar, Chuang Gan, Kevin Smith, Shari Liu, Dan Gutfreund, Elizabeth Spelke, Joshua Tenenbaum, and Tomer Ullman. Agent: A benchmark for core psychological reasoning. In *International conference on machine learning*, 2021.

Michael Shum, Max Kleiman-Weiner, Michael L Littman, and Joshua B Tenenbaum. Theory of minds: Understanding behavior in groups through inverse planning. In *Proceedings of the AAAI conference on artificial intelligence*, 2019.

Sharath Turuvekere Sreenivas, Saurav Muralidharan, Raviraj Joshi, Marcin Chochowski, Mostofa Patwary, Mohammad Shoeybi, Bryan Catanzaro, Jan Kautz, and Pavlo Molchanov. Llm pruning and distillation in practice: The minitron approach, 2024.

James W. A. Strachan, Dalila Albergo, Giulia Borghini, Oriana Pansardi, Eugenio Scaliti, Saurabh Gupta, Krati Saxena, Alessandro Rufo, Stefano Panzeri, Guido Manzi, Michael S. A. Graziano, and Cristina Becchio. Testing theory of mind in large language models and humans. *Nature Human Behaviour*, 2024.

Yixuan Su, Tian Lan, Yan Wang, Dani Yogatama, Lingpeng Kong, and Nigel Collier. A contrastive framework for neural text generation. In *Advances in Neural Information Processing Systems*, 2022.

Andrew Szot, Max Schwarzer, Harsh Agrawal, Bogdan Mazoure, Rin Metcalf, Walter Talbott, Natalie Mackraz, R Devon Hjelm, and Alexander T Toshev. Large language models as generalizable policies for embodied tasks. In *The Twelfth International Conference on Learning Representations*, 2024.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.

Matus Telgarsky. Benefits of depth in neural networks. In *Conference on learning theory*, 2016.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv:2307.09288*, 2023.

Tomer Ullman. Large language models fail on trivial alterations to theory-of-mind tasks. *arXiv preprint arXiv:2302.08399*, 2023.

Ben Wang and Aran Komatsuzaki. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model, 2021.

Alex Wilf, Sihyun Lee, Paul Pu Liang, and Louis-Philippe Morency. Think twice: Perspective-taking improves large language models' theory-of-mind capabilities. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, 2024.

Lionel Wong, Gabriel Grand, Alexander K Lew, Noah D Goodman, Vikash K Mansinghka, Jacob Andreas, and Joshua B Tenenbaum. From word models to world models: Translating from natural language to the probabilistic language of thought. *arXiv preprint arXiv:2306.12672*, 2023.

Bo Wu, Shoubin Yu, Zhenfang Chen, Joshua B. Tenenbaum, and Chuang Gan. STAR: A benchmark for situated reasoning in real-world videos. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2021.

Lance Ying, Katherine M Collins, Megan Wei, Cedegao E Zhang, Tan Zhi-Xuan, Adrian Weller, Joshua B Tenenbaum, and Lionel Wong. The neuro-symbolic inverse planning engine (nipe): Modeling probabilistic social inferences from linguistic inputs. In *ICML Workshop on Theory of Mind in Communicating Agents*, 2023.

Lance Ying, Tan Zhi-Xuan, Lionel Wong, Vikash Mansinghka, and Josh Tenenbaum. Grounding language about belief in a bayesian theory-of-mind. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, 2024.

Hang Zhang, Xin Li, and Lidong Bing. Video-LLaMA: An instruction-tuned audio-visual language model for video understanding. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, 2023.

Tan Zhi-Xuan, Nishad Gothoskar, Falk Pollok, Dan Gutfreund, Joshua B Tenenbaum, and Vikash K Mansinghka. Solving the baby intuitions benchmark with a hierarchically bayesian theory of mind. In *Social Intelligence in Humans and Robots, RSS Workshop*, 2022.

Zhanhui Zhou, Jie Liu, Zhichen Dong, Jiaheng Liu, Chao Yang, Wanli Ouyang, and Yu Qiao. Emulated disalignment: Safety alignment for large language models may backfire! In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024.

A COMPARISON OF METHODOLOGIES FOR TOM INFERENCE

Table 5: Attributes of each method for ToM task.

method	scalability	structured reasoning	world knowledge	multimodality
Bayesian ToM models	✗	✓	✗	✗
end-to-end ToM models	✗	✗	✓	✓
ours	✓	✓	✓	✓

Tab.5 provides a comparative analysis of various methodologies for ToM inference, supplementing the discussion in the introduction (§1). Our proposed approach differs significantly from the underlying philosophies of Bayesian ToM models and end-to-end models. While Bayesian models emphasize structured reasoning guided by principles from cognitive science, they often lack scalability and struggle to handle multimodal inputs. In contrast, end-to-end models incorporate extensive world knowledge but lack the structured reasoning capabilities essential for accurate ToM inference.

Our method integrates these attributes: scalability (e.g., up to 405B), structured reasoning, robust world knowledge, and the ability to process multimodal inputs. Furthermore, our method demonstrates superior scalability, leveraging the stronger reasoning capabilities of large LMs at test time without the need for extensive post-training on large models. This allows our approach to efficiently handle complex and dynamic ToM scenarios.

A.1 OUR THEORETICAL RATIONALES IN SCALED TOM INFERENCE AND RELATED WORK

Our approach is based on a high-level principle derived from Theorem 1 and its proof, which implies that smaller models can approximate the scaled gradient of the loss function for larger models. This mechanism bypasses direct parameter updates in the larger model, capturing the primary adjustments needed for fine-tuning while exploiting the innate generalisation capacity of the larger model. By relying on the approximate knowledge provided by the smaller model, our framework reduces computational overhead and improves scalability.

This principle is related with previous studies that have explored reweighting mechanisms for various applications (where not necessarily the same as our perspective of scaling or embodied policy model), including avoiding toxicity in text generation (Liu et al., 2021), mitigating harmful outputs in aligned models (Zhou et al., 2024), adjusting code generation (Mitchell et al., 2024), controlling sentiment in text (Han et al., 2024), and reducing hallucination or degeneration in neural text (Chuang et al., 2024; Su et al., 2022). These works demonstrate how reweighting can approximate the behaviour of large language models, mimicking direct fine-tuning in specific contexts. In contrast, our scaled ToM inference extends this principle beyond text generation tasks into the domain of social cognitive reasoning. Our framework uses language models to approximate policy behaviours for probability estimation in embodied simulators, based on the cognitive science-inspired Bayesian ToM framework. Unlike previous work focusing on text-based tasks such as sentiment or factuality control, our method addresses the unique challenges of ToM tasks, which require complex reasoning and the integration of world knowledge. These tasks involve multimodal scenarios that require understanding of agents' beliefs, goals and actions - a domain distinct from the text generation problems addressed in previous studies.

B DATA FLOW AND PROCESSING IN SCALABLE BAYESIAN TOM INFERENCE

B.1 OVERALL DATA FLOW

For a detailed depiction of the data flow in our method, refer to Fig.4. The symbolic representation tools first convert video and textual descriptions into structured symbolic inputs, which are then processed by the Bayesian inference framework. This framework leverages a large LM as a scaled policy model, dynamically controlled by task-specific priors provided by a post-trained small LM, enabling accurate estimation of action likelihoods in dynamic scenarios.

Figure 4: The data flow in our scalable Bayesian ToM inference framework. Video scenes and their corresponding descriptions are first processed by multimodal symbolic representation tools Jin et al. (2024), generating structured symbolic inputs (states, beliefs, goals). These symbolic representations are then integrated into the Bayesian inference process, where a large language model (LM) operates as a scaled **policy model** to estimate the likelihood of an agent's actions in dynamic environments. The right panel demonstrates the latent behavioral changes introduced by the post-trained small LM, which provides task-specific priors to guide the larger LM via a control mechanism.

B.2 DATA PREPROCESSING: UNIFIED SYMBOLIC REPRESENTATIONS

To enable Bayesian ToM inference at scale, following established methods mentioned in MMToM (Jin et al., 2024; Blukis et al., 2022), multimodal data (video and textual descriptions) are transformed into structured symbolic representations. This process involves three key components: **visual perception**, **text parsing**, and **information fusion**. Together, these components provide a unified representation of states, actions, and hypotheses required for ToM tasks.

Visual Perception. The visual perception module is designed to process video frames and extract symbolic representations of the environment. For each frame, a scene graph is generated to capture the spatial and relational properties of objects and agents with the scene graph generator(Blukis et al., 2022). Following established methods in MMToM (Jin et al., 2024), voxel maps and 3D bounding boxes are utilized to infer object positions, containment relationships, and human poses. For instance, objects such as *pear* and *basket* are represented by predicates like In(pear, basket). These predicates effectively summarize the physical state of the environment, serving as critical inputs for subsequent reasoning steps.

Text Parsing. To extract symbolic representations from textual descriptions, one LLM (e.g., GPT-4) processes the text into three distinct components: (i) the initial state of the environment, (ii) human actions, and (iii) the question. Each component is translated into symbolic predicates. For example:

- The **state** is represented as predicates like In(pear, basket).

- The **action** is represented as commands such as walk towards kitchen.

- The **question** is decomposed into two hypotheses, each comprising a goal (e.g., pear) and a belief (e.g., In(pear, basket) or its negation, ¬In(pear, basket)).

This symbolic parsing ensures compatibility with the structured reasoning framework.

Fusion. The fusion module integrates symbolic information from video and text into a unified representation. First, predicates extracted from video inputs (e.g., spatial relationships) are aligned with those parsed from text to form the **initial state**. Next, human actions detected from the video are matched with text-based actions, and the video sequence is segmented into discrete time steps corresponding to these actions. Starting from the initial state, the symbolic representation of the environment is updated at each time step based on newly detected predicates. This process results in a sequence of symbolic states and actions, which serve as the input for Bayesian inference. Additionally, the parsed question provides two hypotheses—goal and belief—that guide the reasoning task.

C   THEORETICAL RATIONALE ON SCALING BAYESIAN ToM INFERENCE

Theorem 1. *Our weak-to-strong control in scaling Bayesian ToM inference approximates the behavior of a directly tuned policy model by adjusting the likelihood of the pretrained large model using a learned offset from the smaller post-trained model pair $(\pi^{\mathcal{E}}, \pi^{\mathcal{N}})$. The approximation error ϵ can be constrained by the discrepancy between the likelihood adjustment Δs and the scaled negative gradient $\eta \nabla \mathcal{L}(\pi^{\mathcal{L}})$, as well as higher-order terms of the loss function's Taylor expansion. Specifically, the total error is given by:*

$$\epsilon = \|s_{\pi^*} - s_{\tilde{\pi}}\| = \|\Delta s + \eta \nabla \mathcal{L}(\pi^{\mathcal{L}}) + \frac{\eta^2}{2} \nabla^2 \mathcal{L}(\pi^{\mathcal{L}})(\nabla \mathcal{L}(\pi^{\mathcal{L}}))^{\top} + \mathcal{O}(\eta^3)\|$$
$$\leq \frac{\eta^2}{2} \|\nabla^2 \mathcal{L}(\pi^{\mathcal{L}})\| \|\nabla \mathcal{L}(\pi^{\mathcal{L}})\|^2 + \mathcal{O}(\eta^3). \tag{7}$$

where s_{π^*} denotes the likelihood of the directly tuned policy model, $s_{\tilde{\pi}}$ represents the likelihood of the weak-to-strong controlled model, Δs is the learned likelihood adjustment from $(\pi^{\mathcal{E}}, \pi^{\mathcal{N}})$, η is the learning rate, and $\nabla \mathcal{L}$ and $\nabla^2 \mathcal{L}$ are the gradient and Hessian of the cross-entropy loss function, respectively.

The total error ϵ decreases with smaller learning rates η and is influenced by the curvature of the loss function $\mathcal{L}$, as captured by its higher-order derivatives. Our solution in scaled Bayesian ToM inference achieves high accuracy when Δs closely approximates $-\eta \nabla \mathcal{L}(\pi^{\mathcal{L}})$, and the higher-order terms become negligible. We provide the following derivation for this relation.

Proof. The likelihood of the directly tuned model π^* can be expressed using the second-order Taylor expansion of the loss function $\mathcal{L}$ around the base model $\pi^{\mathcal{L}}$:

$$s_{\pi^*} = s_{\pi^{\mathcal{L}}} - \eta \nabla \mathcal{L}(\pi^{\mathcal{L}}) + \frac{\eta^2}{2} \nabla^2 \mathcal{L}(\pi^{\mathcal{L}})(\nabla \mathcal{L}(\pi^{\mathcal{L}}))^{\top} + \mathcal{O}(\eta^3), \tag{8}$$

where s_{π^*} is likelihoods of the directly tuned model, $s_{\pi^{\mathcal{L}}}$ is likelihoods of the base model, $\nabla \mathcal{L}(\pi^{\mathcal{L}})$ is gradient of the loss function, $\nabla^2 \mathcal{L}(\pi^{\mathcal{L}})$ is Hessian of the loss function. The weak-to-strong controlled model $\tilde{\pi}$ applies a learned adjustment Δs to the likelihoods of the base model:

$$s_{\tilde{\pi}} = s_{\pi^{\mathcal{L}}} + \Delta s, \tag{9}$$

where Δs is the likelihood adjustment learned from the smaller post-trained model pair $(\pi^{\mathcal{E}}, \pi^{\mathcal{N}})$. The total approximation error ϵ is the norm of the difference between the likelihoods of the directly tuned model π^* and the weak-to-strong controlled model $\tilde{\pi}$:

$$\epsilon = \|s_{\pi^*} - s_{\tilde{\pi}}\| = \| -\eta \nabla \mathcal{L}(\pi^{\mathcal{L}}) + \frac{\eta^2}{2} \nabla^2 \mathcal{L}(\pi^{\mathcal{L}})(\nabla \mathcal{L}(\pi^{\mathcal{L}}))^{\top} + \mathcal{O}(\eta^3) - \Delta s\|. \tag{10}$$

Assume that the likelihood adjustment Δs is designed to approximate the negative gradient of the loss function scaled by the learning rate η, i.e.,

$$\Delta s \approx -\eta \nabla \mathcal{L}(\pi^{\mathcal{L}}). \tag{11}$$

This assumption ensures that the primary discrepancy arises from higher-order terms. Substituting the approximation for Δs into the error equation, the leading error term $\|\Delta s + \eta \nabla \mathcal{L}(\pi^{\mathcal{L}})\|$ becomes negligible. The remaining error is dominated by the second-order and higher-order terms:

$$\epsilon = \|\frac{\eta^2}{2} \nabla^2 \mathcal{L}(\pi^{\mathcal{L}})(\nabla \mathcal{L}(\pi^{\mathcal{L}}))^{\top} + \mathcal{O}(\eta^3)\|. \tag{12}$$

Using the norm properties, we can represent ϵ as:

$$\epsilon \leq \frac{\eta^2}{2} \|\nabla^2 \mathcal{L}(\pi^{\mathcal{L}})\| \|\nabla \mathcal{L}(\pi^{\mathcal{L}})\|^2 + \mathcal{O}(\eta^3). \tag{13}$$

In our scaling Bayesian ToM inference, the weak-to-strong control lets large policy model achieve high accuracy when Δs closely approximates $-\eta \nabla \mathcal{L}(\pi^{\mathcal{L}})$ learned from ToM training set, and the higher-order terms are negligible. □

In terms of theoretical implications for practical applicability, this analysis shows that the weak-to-strong control mechanism relies on the learned Δ s to approximate the scaled gradient $-\eta\nabla\mathcal{L}(\pi^{\mathcal{L}})$, with higher order terms dominating the remaining error. However, it is important to note that our method does not require the small LM ($\pi^{\mathcal{E}}$) to strictly approximate the exact gradient learned by the large model on the data. Instead, the large model ($\pi^{\mathcal{L}}$) benefits from its intrinsic ability to generalise and adapt based only on the approximate knowledge learned by the small LM. This inherent flexibility allows the large model to use its pre-trained potential, stimulated by the weak-to-strong control mechanism, to effectively adapt to the current task. Consequently, our method achieves robust performance even in scenarios where the small LM provides only a coarse approximation of the gradient, reducing the reliance on strict fine-tuning and maximising computational efficiency.

D EXPERIMENTAL DETAILS

D.1 BELIEF AND GOAL INFERENCE TYPES AND THEIR CHARACTERISTICS TO LMS

MMToM apartment scenario questions are split into seven types, assessing ToM reasoning (Jin et al., 2024): Belief Inference includes 50% of questions on True Belief (*Type 1.1*), False Belief (*Type 1.2*), and Long-Term Belief Tracking (*Type 1.3*). Goal Inference covers the remaining 50% on True Belief (*Type 2.1*), False Belief (*Type 2.2*), Updated Belief (*Type 2.3*), and Future Actions (*Type 2.4*).

Short-term Belief Inference relies heavily on world knowledge, making it more responsive to enhancements from large LMs' pretrained capabilities. In contrast, long-term reasoning—both for Belief and Goal Inference—focuses on the dynamic nature of the environment and benefits from post-training specifically aligned to ToM scenarios.

D.2 POST-TRAINING CONFIGURATIONS

Tab.6 summarizes the LoRA post-training configurations applied to Llama-2, Llama-3, and Llama-3.1 models during policy model training. We carefully adjust α, rank, and other hyperparameters to optimize performance across different model sizes. Notably, following prior engineering studies, a higher α and rank are used for smaller models (7B and 8B), while reduced values are employed for the larger 70B model to ensure efficient adaptation without overfitting.

D.2.1 FINE-TUNING PROCESS AND RESOURCES

The fine-tuning process for smaller models (e.g., Llama-3.1-8B) was conducted using a single NVIDIA H100 GPU, leveraging BF16 mode to optimize memory usage and maintain GPU memory consumption under 60GB. This configuration enabled efficient training of policy models tailored for Theory of Mind (ToM) tasks. The fine-tuning process was executed with the following parameters:

- **Batch size:** 16 (achieved via a per-device batch size of 4 and gradient accumulation steps of 4),
- **Learning rate:** 5×10^{-5},

Table 6: LoRA configuration settings for Llama-2, Llama-3, and Llama-3.1 during post-training for policy models.

configs	7B	8B	70B
bias	none	none	none
fan-in fan-out	false	false	false
inference mode	true	true	true
LoRA initialization	true	true	true
α	32	32	16
dropout	0.05	0.05	0.05
rank	16	16	8
target modules	[q-proj, v-proj]		
task type	causal-lm		

725 • **Number of epochs:** 3.

726 Under this setup, the fine-tuning process required approximately 8 hours to converge.

D.2.2 DATASET SIZE

728 The training pool size N for optimizing Equation 5 was set to 20,000 data points, sourced from the
729 MMToM dataset's training split and our released data sampled from an embodied simulator. For
730 tasks involving transfer to new themes, the training dataset size remained consistent at 20,000 data
731 points, ensuring a fair and uniform setup across different experiments.

D.3 COMPARISON OF FINE-TUNING METHODS ON MMTOM TASKS

733 To evaluate the relative performance of full fine-tuning (FFT) and LoRA fine-tuning, we conducted
734 experiments on two smaller models, GPT2-large (Radford et al., 2019) (774M parameters) and
735 Gemma-2B (2B parameters) Team et al. (2024). Each model was fine-tuned using datasets of 20,000
736 and 8,000 datapoints, over two epochs, on 8 NVIDIA A100 80GB GPUs. The results are summarised
in Table 7.

Table 7: Comparison of full fine-tuning (FFT) and LoRA fine-tuning for GPT2-large and Gemma-2B
across different MMToM data sizes.

	Fine-tuning Method	Data Size	Model Size	Accuracy (%)
GPT2-large	FFT	20,000	774M	63.4
GPT2-large	LoRA	20,000	774M	62.4
GPT2-large	FFT	8,000	774M	62.8
GPT2-large	LoRA	8,000	774M	62.1
Gemma-2B	FFT	20,000	2B	68.8
Gemma-2B	LoRA	20,000	2B	68.5
Gemma-2B	FFT	8,000	2B	67.5
Gemma-2B	LoRA	8,000	2B	67.3

737

738 The results show several important trends. First, when sufficient training data is available (e.g.
739 20,000 data points), full fine-tuning consistently outperforms LoRA, with accuracy gains of 0.9-1.2
740 percentage points. This suggests that full training is better at exploiting richer data, especially for
741 smaller models. Second, the performance gap between FFT and LoRA narrows for larger models.
742 For example, Gemma-2B shows minimal differences between FFT and LoRA (0.3 percentage points
743 on 20,000 data points), suggesting that larger models are more robust to LoRA's parameter efficiency
744 constraints. Finally, the influence of dataset size is evident: while FFT shows greater improvements
745 over LoRA on smaller datasets, LoRA maintains competitive performance in resource-constrained
746 scenarios, especially for larger models.

747 The results show several important trends. First, when sufficient training data is available (e.g.,
748 20,000 data points), full fine-tuning consistently outperforms LoRA, with accuracy gains of 0.9-1.2
749 percentage points. This suggests that full training is better at exploiting richer data, especially for
750 smaller models. Second, the performance gap between FFT and LoRA narrows for larger models.
751 For example, Gemma-2B shows minimal differences between FFT and LoRA (0.3 percentage points
752 on 20,000 data points), suggesting that larger models are more robust to LoRA's parameter efficiency
753 constraints. Finally, the influence of dataset size is evident: while FFT shows greater improvements
754 over LoRA on smaller datasets, LoRA maintains competitive performance in resource-constrained
755 scenarios, especially for larger models. Table 8 further demonstrates the robustness of weak-to-strong
756 control when transferring ToM-specific fine-tuning knowledge from a smaller model (Minitron-4B-
757 Width) to a larger model (Llama-3.1-70B). The difference in accuracy between FFT and LoRA is
758 only 0.15 percentage points when weak-to-strong control is applied, indicating that the mechanism
759 is highly effective at bridging the gap between fine-tuning methods. Importantly, this highlights
760 the ability of the proposed method to scale ToM-specific behaviors efficiently, leveraging both
761 computationally intensive FFT and parameter-efficient LoRA.

Table 8: Comparison of weak-to-strong control for Llama-3.1-Minitron-4B-Width and Llama-3.1-70B using different fine-tuning methods on the smaller model.

	Fine-tuning Method	Data Size	Model Size	Accuracy (%)
Llama-3.1-Minitron-4B-Width	FFT	20,000	4B	77.00
Llama-3.1-Minitron-4B-Width	LoRA	20,000	4B	76.90
Weak-to-strong control results:				
4B-Width ↬ Llama-3.1-70B	FFT-trained 4B	20,000	70B	78.67
4B-Width ↬ Llama-3.1-70B	LoRA-trained 4B	20,000	70B	78.52

Overall, these experiments highlight a trade-off between computational efficiency and performance gains. Full fine-tuning achieves modest but consistent improvements, particularly for smaller models and larger datasets. However, for larger models, LoRA provides an effective alternative with near-parity in performance and significantly reduced computational overhead. Furthermore, our weak-to-strong control mechanism demonstrates stability to fine-tuning methods, enabling scalable ToM-specific behavior elicitation with high accuracy in larger models.

D.4 IMPACT OF PRE-TRAINING QUALITY ON MMTOM TASKS

The differences in performance between the Llama-2, Llama-3 and Llama-3.1 models provide insight into the role of pre-training quality, especially at large model scales. Based on the experimental results in Table 2 and Table 3, the influence of pre-training quality diminishes primarily due to a ceiling effect, but this is only observed when comparing models within the same scale, such as the 70B parameter range. However, when comparing smaller models to larger ones, the effect of pre-training is more pronounced. For example, moving from Llama-2 7B to Llama-2 70B after ToM-specific post-training leads to a 6% improvement in belief inference accuracy (from 76.33% to 82.33%) and a 2% improvement in goal inference accuracy (from 70% to 72%), highlighting the role of scaling in encoding richer representations.

When examining why pre-training becomes less effective at larger scales, such as comparing Llama-2-70B (pre-trained with 2.2 trillion tokens) to Llama-3.1-70B (pre-trained with 15 trillion tokens), the results suggest that larger pre-training corpora improve performance primarily for tasks that rely heavily on world knowledge: Tasks involving belief inference, which rely on short-term reasoning and general world knowledge, show significant improvements due to improved representations learned during pre-training. For example, Llama-3.1 achieves a 3.67% improvement in belief inference accuracy over Llama-2 (from 83.00% to 85.67%). These tasks benefit from richer pre-training datasets that refine the model's understanding of common human behaviours and object interactions.

In contrast, goal inference tasks that rely on long-term reasoning, including integrating temporal observations and dynamically updating beliefs, show smaller gains from larger pre-training corpora. For example, Llama-3.1 improves goal inference accuracy by only 1.67% over Llama-2 (from 72.33% to 74.00%). Such tasks are more dependent on the fine-tuning stage and the use of task-specific reasoning frameworks, such as weak-to-strong control. These results suggest that for complex reasoning tasks, the primary performance bottleneck shifts from pre-training quality to the reasoning strategies employed during fine-tuning.

In summary, pre-training quality has a significant impact on smaller models and tasks that rely heavily on world knowledge, such as belief inference. However, as models scale up to 70B parameters, the influence of pre-training diminishes due to ceiling effects, and logical reasoning tasks such as goal inference rely more on task-specific adaptations during fine-tuning.

D.5 HOW CONSISTENT IS THEORY OF MIND ACROSS DIFFERENT PHRASINGS?

As shown in Table 4, the "*All*" column across different themes (e.g. Apartment, Andersen Fairy Tales, etc.), there is noticeable performance variance even within models of the same scale. To quantify this, we measured the range of variance for three configurations: **70B-zero-shot**, **70B-post-trained** and **8B ↬ 70B**: (1) For 70B-zero-shot, performance ranged from 66.62 to 70.52 across themes, yielding a variance range of **3.90**; (2) For 70B-post-trained, the variance range of post-trained LMs is **3.47**, with

803 performance ranging from 71. 86% and 75.33%; (3) For our solution 8B ↬ 70B, the weak-to-strong
804 control mechanism further stabilised the performance, reaching only the smallest variance range of
805 **1.62**, with scores between 77.76% and 79.38%.

806 These results suggest that specific topics have different effects on ToM skills, but our solution
807 demonstrates relative stability to distributional changes caused by topic shifts. For example, **70B-**
808 **zero-shot** achieves its highest performance up to 70.52% and its lowest up to 66.62%, highlighting
809 the model's pronounced sensitivity to thematic variations in reasoning trajectories without adaptation.
810 In contrast, our proposed solution, **8B ↬ 70B**, significantly reduces this gap, demonstrating the
811 effectiveness of the weak-to-strong control mechanism in adjusting the ToM behaviour of the larger
812 model while preserving the framework's general reasoning capacity across diverse and scenario-
813 agnostic contexts.

D.6 ON THE ROLE OF THE WEAK-TO-STRONG FRAMEWORK

815 The weak-to-strong framework presented in this paper focuses on aligning the larger model's distribu-
816 tion with ToM-specific beliefs and task structures while preserving its general reasoning capabilities,
817 rather than primarily relying on the smaller model's reasoning abilities. This design enables efficient
818 transfer of ToM-specific task structures without compromising the broader capabilities of the larger
819 model.

820 The smaller model (e.g., 4B or 8B parameters) undergoes ToM-specific post-training to encode
821 task-relevant priors, such as belief states and potential goals, without requiring advanced independent
822 reasoning capabilities. During inference, the smaller model functions as an assistive scaffold,
823 conditioning the larger model's likelihood estimation in a Bayesian framework. This role is formalized
824 through the adjustment ratio: $\frac{\pi^{\mathcal{E}}}{\pi^{\mathcal{N}}}$, where $\pi^{\mathcal{E}}$ is the post-trained smaller model's task-specific policy,
825 and $\pi^{\mathcal{N}}$ is the naive pre-trained smaller model's policy.

826 The larger model (e.g., 70B parameters) integrates this adjustment ratio to refine its likelihood
827 estimation dynamically. The overall policy distribution is computed as $\pi^{\mathcal{L}} \frac{\pi^{\mathcal{E}}}{\pi^{\mathcal{N}}}$, where $\pi^{\mathcal{L}}$ is the policy
828 from the larger model. This mechanism allows the larger model to retain its broad reasoning and
829 world knowledge, ensuring its capacity for generalization while aligning with ToM-specific task
830 structures.

831 To validate this framework, we compared the performance of the 8B ↬ 70B model to the 70B-post-
832 trained model across five unseen themes, including *Andersen Fairy Tales*, *Ancient Egyptian*, and *Outer*
833 *Space*. As shown in Table 9, the weak-to-strong mechanism achieved consistent improvements across
834 all ToM tasks, demonstrating its ability to preserve and transfer the larger model's general reasoning
capabilities while aligning with ToM-specific requirements. These results, combined with theoretical

Table 9: Performance of the 8B ↬ 70B model on unseen themes compared to 70B-post-trained and 70B-zero-shot models across all ToM tasks.

Unseen Theme	Scale	1.1	1.2	1.3	Avg.	2.1	2.2	2.3	2.4	Avg.	All
Andersen Fairy Tales	70B-zero-shot	88.00	73.00	90.00	83.67	70.67	80.00	25.33	66.67	60.67	70.52
	70B-post-train	90.00	71.00	93.00	84.67	73.33	61.33	61.33	69.33	66.33	74.19
	8B ↬ 70B	92.00	71.00	85.00	82.67	82.67	76.00	68.00	77.33	76.00	78.86
Ancient Egyptian	70B-zero-shot	89.00	71.00	91.00	83.67	74.67	74.67	25.33	60.00	58.67	69.38
	70B-post-train	89.00	69.00	96.00	84.67	72.00	76.00	61.33	64.00	68.33	75.33
	8B ↬ 70B	90.00	73.00	88.00	83.67	69.33	76.00	73.33	74.67	73.33	77.76
Outer Space	70B-zero-shot	88.00	72.00	92.00	84.00	72.00	64.00	25.33	70.67	58.00	69.38
	70B-post-train	91.00	68.00	90.00	83.00	69.33	65.33	61.33	68.00	66.00	75.33
	8B ↬ 70B	90.00	70.00	92.00	84.00	73.33	81.33	66.67	78.67	75.00	77.76

836 insights from Section C, demonstrate that the weak-to-strong framework effectively utilizes the
837 smaller model as a task-specific lens to guide the larger model's predictions. This collaborative
838 dynamic ensures alignment with ToM-specific task requirements while preserving general reasoning
839 capabilities.

Table 10: Detailed transfer performance of the Bayesian method with different scaling strategies (zero-shot, direct post-training, and our weak-to-strong control) from the original apartment scenario to various unseen environments. All models are based on Llama3.1.

| Theme | Scale | Belief Inference | | | | Goal Inference | | | | | All |
		1.1	1.2	1.3	Avg.	2.1	2.2	2.3	2.4	Avg.	
Andersen fairy tales	70B-zeroshot	88.00	73.00	90.00	83.67	70.67	80.00	25.33	66.67	60.67	70.52
	70B-post-train	90.00	71.00	**93.00**	84.67	73.33	61.33	61.33	69.33	66.33	74.19
	8B ↬ 70B	**92.00**	71.00	85.00	82.67	**82.67**	76.00	68.00	**77.33**	**76.00**	**78.86**
	4B-width ↬ 70B	90.00	73.00	89.00	84.00	80.00	**81.33**	**76.00**	64.00	75.33	79.05
	4B-depth ↬ 70B	91.00	**74.00**	90.00	**85.00**	74.67	73.33	64.00	73.33	71.33	77.19
ancient Egyptian	70B-zeroshot	89.00	**71.00**	91.00	83.67	74.67	74.67	25.33	60.00	58.67	69.38
	70B-post-train	89.00	69.00	96.00	84.67	72.00	76.00	61.33	64.00	68.33	75.33
	8B ↬ 70B	90.00	73.00	88.00	83.67	69.33	76.00	73.33	74.67	73.33	77.76
	4B-width ↬ 70B	90.00	69.00	90.00	83.00	70.67	**80.00**	**85.33**	69.33	**76.33**	**79.19**
	4B-depth ↬ 70B	91.00	69.00	96.00	**85.33**	76.00	68.00	69.33	**76.00**	72.33	77.90
outer space	70B-zeroshot	88.00	72.00	92.00	**84.00**	72.00	64.00	25.33	70.67	58.00	69.38
	70B-post-train	**91.00**	68.00	90.00	83.00	69.33	65.33	61.33	68.00	66.00	75.33
	8B ↬ 70B	90.00	70.00	**92.00**	**84.00**	73.33	**81.33**	66.67	**78.67**	75.00	77.76
	4B-width ↬ 70B	90.00	70.00	88.00	82.67	**73.33**	76.00	**80.00**	72.00	**75.33**	**79.19**
	4B-depth ↬ 70B	90.00	69.00	86.00	81.67	70.67	73.33	68.00	72.00	71.00	77.90
wild west	70B-zeroshot	88.00	72.00	**92.00**	**84.00**	72.00	64.00	25.33	70.67	58.00	69.14
	70B-post-train	**91.00**	68.00	90.00	83.00	69.33	65.33	61.33	68.00	66.00	73.29
	8B ↬ 70B	90.00	70.00	**92.00**	**84.00**	73.33	**81.33**	66.67	**78.67**	75.00	**78.86**
	4B-width ↬ 70B	90.00	70.00	88.00	82.67	**73.33**	76.00	**80.00**	72.00	**75.33**	78.48
	4B-depth ↬ 70B	90.00	69.00	86.00	81.67	70.67	73.33	68.00	72.00	71.00	75.57
medieval castle	70B-zeroshot	88.00	**71.00**	89.00	82.67	62.67	74.67	20.00	73.33	57.67	68.38
	70B-post-train	85.00	69.00	89.00	81.00	65.33	69.33	57.33	68.00	65.00	71.86
	8B ↬ 70B	90.00	72.00	89.00	83.67	72.00	76.00	68.00	**84.00**	75.00	**78.71**
	4B-width ↬ 70B	**92.00**	71.00	**91.00**	**84.67**	**77.33**	**77.33**	**69.33**	68.00	**73.00**	78.00
	4B-depth ↬ 70B	90.00	70.00	90.00	83.33	58.67	72.00	53.33	72.00	64.00	72.29

D.7 THEORY-OF-MIND CASE STUDY: AGENT JAMES IN APARTMENT INTERACTION

Fig.5 provides a detailed visual and language-based description of the test case described in experiment §3.7 of the experiment, where the likelihood estimation behaviour of different LMs is discussed across varying concept levels.

D.8 TOM TRANSFER EFFECT ON UNSEEN SCENARIOS

Tab.10 supplements the results in experiment §3.5, providing a detailed comparison between the baselines and our scalable solution across belief inference and goal inference subtasks in various unseen ToM scenarios. Our experimental observations are consistent with those outlined in §3.5: *(i)* The increased capacity of our scalable solution significantly improves the transferability of ToM reasoning across dynamic and previously unseen environments. *(ii)* Our approach demonstrates strong potential for downsizing small LMs as controllers, as they successfully capture the post-trained behaviours and exhibit robust performance in guiding larger models. *(iii)* Notably, our method can approximate—and in some cases outperform—the results achieved by directly post-training large-scale LMs (such as the 70B model). These findings underscore the flexibility and scalability of our approach for handling practical ToM tasks in diverse, complex environments.

D.9 THEMATIC SCENARIO DATA FOR TOM TASK TRANSFER

As described in §D.8, five new thematic scenarios are used for evaluation: Andersen Fairy Tales, Ancient Egyptian, Wild West, Outer Space and Medieval Castle. These environments are not seen during the post-training phase of our method and are different from the original *apartment* setting.

The transfer to these scenarios demonstrates the generalisability of our solution to dynamically adapt to different domains, with each thematic environment presenting unique challenges and contextual shifts from the apartment scenario. Fig.6 provides a visual summary of these key differences, statistically extracted and mapped to illustrate the transformation of concept and environment across these themes. These distinctions are used to evaluate ToM task transfer across different dynamic environments.

ToM exemplar

What's inside the apartment:
The apartment consists of a bedroom, a bathroom, a living room, and a kitchen. In the bedroom, there is a coffee table with a plate on it. The bathroom houses a cabinet, which is currently empty. The living room is furnished with a cabinet, a coffee table, a sofa, and a desk. The cabinet is filled with two apples, a condiment bottle, three wine glasses, two water glasses, a cupcake, two bags of chips, a remote control, and a bottle of wine. Both a water glass and a wine glass are placed on the coffee table. The kitchen is equipped with a fridge, an oven, a kitchen table, and a microwave. Inside the fridge, there are two apples. The oven contains a salmon. Meanwhile, the microwave houses a salmon and two cupcakes.

Actions taken by James:
James is in the kitchen. He strides towards the stove, opens it, and then shuts it. He then opens the fridge, closes it, opens the microwave, and closes it as well. Finally, he walks towards the living room and approaches the cabinet.

State Modelling:
(a) James has been trying to get a bottle of wine. ✅
(b) James has been trying to get an apple. ❌

s_i: apples in fridge, no wine
b_i: wine in the cabinet
g_i: obtain a bottle of wine
a_i: open fridge, walk to cabinet

Figure 5: Theory-of-Mind scenario used in the main experiments §3.7, involving an agent (James) interacting with objects in an apartment.

```
Andersen_fairy_tales_mappings = {        ancient_Egyptian_mappings = {
    "apartment": "cottage",                 "apartment": "palace",
    "bedroom": "chamber",                   "bedroom": "sleeping chamber",
    "bathroom": "washroom",                 "bathroom": "bathing room",
    "living room": "great hall",            "living room": "audience hall",
    "kitchen": "hearth",                    "kitchen": "kitchen",
    "coffeetable": "wooden table",          "coffeetable": "stone table",
    "desk": "writing desk",                 "desk": "writing table",
    "kitchentable": "feasting table",       "kitchentable": "dining table",
    "sofa": "wooden bench",                 "sofa": "cushioned bench",
    "kitchencabinet": "pantry",             "kitchencabinet": "storage chest",
    "cabinet": "cupboard",                  "cabinet": "treasure chest",
    "bathroomcabinet": "washstand",         "bathroomcabinet": "washstand",
    "dishwasher": "washing basin",          "dishwasher": "servant",
    "fridge": "cooling box",                "fridge": "cool room",
    "microwave": "heating stone",           "microwave": "heating pot",
    "stove": "fireplace",                   "stove": "fire pit",
    "apple": "apple",                       "apple": "fruit",
    "book": "tome",                         "book": "papyrus scroll",
    "chips": "dried berries",               "chips": "flatbread",
    "condimentbottle": "spice jar",         "condimentbottle": "spice jar",
    "cupcake": "honey cake",                "cupcake": "honey pastry",
    "dishbowl": "clay bowl",                "dishbowl": "clay bowl",
    "plate": "wooden plate",                "plate": "ceramic plate",
    "remotecontrol": "magic wand",          "remotecontrol": "scepter",
    "salmon": "smoked fish",                "salmon": "dried fish",
    "waterglass": "goblet",                 "waterglass": "chalice",
    "wine": "mead",                         "wine": "wine",
    "wineglass": "goblet",                  "wineglass": "goblet"}
    "kitchencabinet": "pantry shelf"}

wild_west_mappings = {               outer_space_mappings = {               medieval_castle_mappings = {
    "apartment": "saloon",              "apartment": "quarters",               "apartment": "saloon",
    "bedroom": "bunk room",             "bedroom": "sleeping quarters",        "bedroom": "bunk room",
    "bathroom": "outhouse",             "bathroom": "sanitation room",         "bathroom": "outhouse",
    "living room": "bar area",          "living room": "recreation area",      "living room": "bar area",
    "kitchen": "cooking area",          "kitchen": "replicator station",       "kitchen": "cooking area",
    "coffeetable": "wooden table",      "coffeetable": "control console",      "coffeetable": "wooden table",
    "desk": "writing desk",             "desk": "command station",             "desk": "writing desk",
    "kitchentable": "dining table",     "kitchentable": "mess table",          "kitchentable": "dining table",
    "sofa": "wooden bench",             "sofa": "lounger",                     "sofa": "wooden bench",
    "kitchencabinet": "storage shelf",  "kitchencabinet": "storage unit",      "kitchencabinet": "storage shelf",
    "cabinet": "supply cabinet",        "cabinet": "storage unit",             "cabinet": "supply cabinet",
    "bathroomcabinet": "washstand",     "bathroomcabinet": "hygiene compartment", "bathroomcabinet": "washstand",
    "dishwasher": "wash basin",         "dishwasher": "sterilizer unit",       "dishwasher": "wash basin",
    "fridge": "icebox",                 "fridge": "cold storage",              "fridge": "icebox",
    "microwave": "stove",               "microwave": "food synthesizer",       "microwave": "stove",
    "stove": "wood stove",              "stove": "heating unit",               "stove": "wood stove",
    "apple": "fresh apple",             "apple": "synthesized apple",          "apple": "fresh apple",
    "book": "ledger",                   "book": "data pad",                    "book": "ledger",
    "chips": "corn chips",              "chips": "nutrition chips",            "chips": "corn chips",
    "condimentbottle": "sauce bottle",  "condimentbottle": "flavor vial",      "condimentbottle": "sauce bottle",
    "cupcake": "pastry",                "cupcake": "synthesized pastry",       "cupcake": "pastry",
    "dishbowl": "ceramic bowl",         "dishbowl": "serving bowl",            "dishbowl": "ceramic bowl",
    "plate": "ceramic plate",           "plate": "serving plate",              "plate": "ceramic plate",
    "remotecontrol": "telegraph key",   "remotecontrol": "control pad",        "remotecontrol": "telegraph key",
    "salmon": "salted fish",            "salmon": "replicated fish",           "salmon": "salted fish",
    "waterglass": "glass",              "waterglass": "hydration vessel",      "waterglass": "glass",
    "wine": "whiskey",                  "wine": "synthesized wine",            "wine": "whiskey",
    "wineglass": "shot glass"}          "wineglass": "drinking vessel",        "wineglass": "shot glass"}
                                        "kitchencabinet": "storage unit"}
```

Figure 6: Primary changes between the original apartment scenario and the five transferred thematic environments used in our ToM experiments.