MacAgentBench: Benchmarking AI Agents on Real-World macOS Desktop

Abstract

Computer use agents (CUAs) have advanced rapidly in desktop automation, and a growing number of users deploy CUAs such as Open-Claw on Mac Mini for always-on automation. However, existing benchmarks, including those for macOS, evaluate agents without framework augmentation and rely on binary evaluation. As a result, they fail to capture both the framework capabilities leveraged by modern CUAs and the partial progress on long-horizon, multi-application tasks. We present MacAgentBench, a comprehensive macOS agent benchmark comprising 676 tasks across 25 applications, with nearly 60% involving both GUI and CLI interaction. The benchmark adopts deterministic rule-based evaluation and introduces fine-grained multi-checkpoint scoring with capability annotations for multi-application tasks. Experiments across three frameworks and 16 models show that the best configuration, Claude Opus 4.6 on OpenClaw, attains 73.7% Pass@1, while this advantage is primarily driven by the skill library rather than by framework design. Fine-grained metrics further reveal that models with similar Pass@1 can differ substantially in sub-goal completion.

1 Introduction

Computer use agents (CUAs) that autonomously operate desktop environments have emerged as a central focus of industry and academia. Major model providers have released desktop control capabilities (Anthropic, 2024, 2025; Wang et al., 2025a; Bai et al., 2025; GLM-5-Team et al., 2026; Qin et al., 2025; Hong et al., 2024), and a growing ecosystem of CUA frameworks and models has formed (Yao et al., 2023; Yang et al., 2026; Agashe et al., 2025a,b; Openclaw Team, 2025). Recent benchmarks such as OSWorld (2024) and WindowsAgentArena (2025) systematically evaluate CUA on Linux and Windows, driving standardization in the field. Real-world deployment, how-ever, is increasingly shifting to macOS, a leading platform for software development, creative work, and professional productivity. An increasing number of users deploy CUAs such as OpenClaw on Mac Mini for always-on automation, and integrate them into daily document, design, and engineering workflows. macOS is uniquely suited for CUA deployment, with a native layered automation stack: AppleScript for application scripting, the Accessibility API for UI access, and a Unix command line. This enables agents to choose the most efficient interaction method for each task. Although prior macOS benchmarks (Yang et al., 2025a; Wang et al., 2025c) have made initial explorations, they remain few, suffer from limited usability, and inherit the limitations of existing CUA benchmarks.

Specifically, existing CUA benchmarks share two fundamental limitations. First, they reduce CUA evaluation to a fixed screenshot–GUI-action loop. Yet modern CUAs consist of a *framework* and a *model* working in concert, in which the framework provides capabilities beyond GUI, such as command-line access, scripting, and pre-built skills. Second, they rely on binary pass/fail judgments. For complex multi-application tasks, such coarse-grained evaluation fails to reveal how much progress an agent actually achieves.

To address this, we propose MacAgentBench, a comprehensive benchmark for evaluating CUAs on real-world macOS desktop tasks. The fundamental design principle of MacAgentBench is **environment openness**: the benchmark imposes no restrictions on how agent frameworks interact with the environment, enabling fair comparison across diverse CUA paradigms, ranging from pure GUI agents to hybrid frameworks to agent harnesses, on the same set of tasks. Built on a lightweight Docker containerized environment with quick startup and full task-level isolation, MacAgentBench comprises 676 tasks, nearly 60% of which involve both GUI and CLI. All evaluations employ deterministic rule-

Figure 1: Overview of MacAgentBench. Three agent paradigms operate on a shared containerized macOS environment with progressively richer action spaces: a pure GUI agent, a hybrid framework, and an agent harness. Each task is scored by deterministic rule-based checkpoints, yielding partial credit on multi-application tasks.

based scripts to ensure reproducibility. Beyond binary pass/fail judgments, we further introduce fine-grained multi-checkpoint scoring for multi-application tasks, in which each checkpoint is annotated with one of five capability dimensions: Research, App State, Content, File Ops, and Sys Config. This exposes partial progress and capability imbalance that binary metrics cannot capture.

We conduct extensive experiments across three frameworks and 16 models. Our results reveal that framework design has a substantial impact on task completion: the best configuration, Claude Opus 4.6 on OpenClaw, achieves 73.7% Pass@1, compared to 39.2% for the same model without framework support. To understand the source of this gain, we analyze the effect of pre-defined skills: on tasks with skill coverage, OpenClaw substantially outperforms the baseline; on tasks without skills, however, OpenClaw underperforms the baseline for most models, revealing that its advantage is primarily skill-driven. Through robustness analysis using Pass@1, Pass@4, and $Pass^4$ metrics, we find that agents with similar capability ceilings can differ substantially in consistency. Furthermore, fine-grained multi-checkpoint evaluation reveals that models with identical pass/fail rates can differ significantly in sub-goal completion, exposing capability imbalances missed by binary evaluation.

Our main contributions are as follows:

- We introduce MacAgentBench, the most comprehensive macOS agent benchmark to date, comprising 676 tasks with deterministic rule-based evaluation. Its open environment lets diverse CUA paradigms be evaluated without restriction, and nearly 60% of tasks involve multiple interaction methods.

- Leveraging this open design, we conduct the first direct comparison on macOS across CUA paradigms spanning pure GUI agents, hybrid frameworks, and agent harnesses, revealing the significant and independent impact of framework design and skill augmentation on agent performance.

- Since binary pass/fail evaluation cannot capture partial progress on long-horizon multi-application tasks, we introduce a multi-checkpoint evaluation mechanism that provides fine-grained reward signals for progress tracking and pinpointing the exact step at which an agent fails.

2 Related Work

End-to-end CUA models. Advances in vision-language models (VLMs) (Anthropic, 2025; Bai

et al., 2025; Wang et al., 2025a) have spurred growing interest in CUAs. Early works such as CogAgent (2024) and SeeClick (2024) framed the problem as GUI grounding by eliciting VLM capabilities for interface understanding and interaction. Subsequent studies (Xu et al., 2025c; Wu et al., 2025; Qian et al., 2025; Xu et al., 2025b) explored diverse training paradigms to improve agents' planning and decision-making. More recently, native agent models (Qin et al., 2025; Seed, 2025; Liu et al., 2025a) have further advanced GUI perception and interaction through multi-stage training and reinforcement learning.

CUA frameworks. Despite progress, end-to-end CUA models still struggle with long-horizon tasks due to memory decay, limited generalization, and restricted action spaces. To mitigate these challenges, recent works propose framework-based agentic systems that separate high-level planning from low-level execution (Agashe et al., 2025a; Guo et al., 2025; Wu et al., 2024). Some approaches enhance memory for long-horizon tasks via dedicated memory modules or context-control mechanisms (Cheng et al., 2025; Tian et al., 2025). Others improve open-environment generalization by integrating retrieval-augmented generation or searcher modules for dynamic external knowledge access (Xu et al., 2025a; Yang et al., 2026). Yet others expand the action space through code agents, enabling hybrid GUI and CLI interaction for complex system operations (Song et al., 2025; Yang et al., 2025b).

Benchmarks for CUAs. Existing benchmarks evaluate CUAs from different perspectives. ScreenSpot (2024) and ScreenSpot-Pro (2025) focus on grounding, while others target desktop (Xie et al., 2024; Bonatti et al., 2025), mobile (Rawles et al., 2025), and web environments (Zhou et al., 2024; He et al., 2024; Deng et al., 2023), primarily through GUI interactions. Beyond GUI tasks, Terminal-Bench (2026) and SWE-Bench (2024) assess terminal-based capabilities, whereas Tool-Bench (2024) and τ-bench (2024) evaluate API and external tool usage. However, most existing benchmarks, including those for macOS (Wang et al., 2025c; Yang et al., 2025a), vary the model under a fixed agent framework, despite real-world CUAs consisting of a framework and a model working in concert. MacAgentBench fills this gap by evaluating multiple CUA frameworks on macOS.

3 MacAgentBench

MacAgentBench provides a complete macOS desktop as a testbed for agent evaluation. The underlying infrastructure is a macOS virtual machine running inside a Docker container. The benchmark imposes no restrictions on how agent frameworks access the environment, supporting both in-container and remote deployment. It comprises 676 tasks across 25 applications, nearly 60% of which involve both GUI and CLI. All evaluations employ deterministic rule-based methods, and multi-application tasks support fine-grained multi-checkpoint scoring. Table 1 compares MacAgentBench with existing benchmarks.

3.1 Infrastructure

MacAgentBench virtualizes a macOS environment using a Docker-QEMU stack. A key optimization leverages the copy-on-write mechanism of QEMU: all containers share a single base image, and each instance records only runtime writes in a lightweight differential layer. This achieves a 30 s container startup time and a 1 GB per-instance disk overhead, enabling parallel evaluation across multiple instances on a single server.

In contrast, macOSWorld uses AWS EC2 Mac bare-metal instances. Each task reset requires a 15 min restore from an AMI snapshot on cloud-hosted dedicated hardware, hindering local reproduction. macOSArena also adopts a Docker-QEMU stack but requires a full copy of the 40 GB disk image per container, yielding a 5 min startup time and disk overhead that scales linearly with the number of parallel instances. A detailed comparison is provided in Appendix A.1 (Table 6).

3.2 Agent-environment interaction

Building on this infrastructure, MacAgentBench imposes no restrictions on agent-environment interaction. Agent frameworks can either run inside the container or operate externally. The observation space, action space, and interaction loop are determined entirely by the agent framework.

We identify two representative deployment modes. (1) **In-container deployment**: frameworks such as OpenClaw are pre-installed inside the container as a native macOS application. Once launched with a task instruction, the application orchestrates the full AI loop internally, assembling context, invoking the model, and executing tool calls, with direct access to screen capture, file sys-

Table 1: Comparison with existing agent benchmarks. ✓ = supported, ✗ = not supported, ✗ = partial.

Benchmark	Platform	Tasks	Task Type	Multi-App	Rule Eval	Checkpoints	Task Var.
Mind2Web (2023)	Web	2,350	GUI	✗	✓	✗	✗
WebArena (2024)	Web	812	GUI	✓	✗	✗	✓
VisualWebArena (2024)	Web	910	GUI	✓	✗	✗	✓
WebVoyager (2024)	Web	643	GUI	✗	✗	✗	✗
Online-Mind2Web (2025)	Web	300	GUI	✗	✗	✗	✗
EconWebArena (2025)	Web	360	GUI	✗	✓	✗	✓
ClawBench (2026)	Web	153	GUI	✗	✗	✗	✗
OSWorld (2024)	Linux	369	GUI, CLI	✓	✓	✗	✗
TheAgentCompany (2024)	Linux	175	GUI, CLI	✓	✗	✓	✗
SWE-bench (2024)	Linux	2,294	CLI	✗	✓	✗	✗
Terminal-Bench (2026)	Linux	89	CLI	✗	✓	✗	✗
Claw-Eval (2026)	Linux	300	CLI	✓	✗	✓	✗
GAIA (2024)	Linux	466	CLI	✓	✓	✗	✗
PinchBench (2025)	Linux	53	CLI	✓	✗	✓	✗
WindowsAgentArena (2025)	Windows	154	GUI, CLI	✗	✓	✗	✗
AndroidWorld (2025)	Android	116	GUI	✓	✓	✗	✓
ToolBench (2024)	API	1,100	API	✗	✗	✗	✗
τ-bench (2024)	API	165	API	✗	✓	✗	✗
macOSWorld (2025a)	macOS	202	GUI, CLI	✓	✓	✗	✗
macOSArena (2025c)	macOS	63	GUI, CLI	✓	✓	✗	✗
MacAgentBench	**macOS**	**676**	**GUI, CLI**	✓	✓	✓	✓

tem, AppleScript, and shell commands. Through this orchestration, the model can leverage any macOS functionality. (2) **External deployment**: frameworks run outside the container and interact with the environment remotely. They retrieve observations needed by the model, such as screenshots and command output, from the macOS instance, and translate predicted actions into executable operations on the environment.

This open design distinguishes MacAgentBench from prior benchmarks that focus exclusively on GUI-based agent interaction.

3.3 Task construction

MacAgentBench comprises 676 tasks spanning 25 applications. The task design follows two core principles. First, it covers diverse interaction methods including CLI, GUI, and combinations of both, reflecting the variety of real-world macOS workflows. Second, it spans multiple complexity levels, from single-application operations to cross-application workflows.

Seed tasks. The seed tasks in MacAgentBench are drawn from two sources. The first set comprises 63 tasks adapted from macOSArena (2025c). Because the macOS version has been upgraded, AppleScript interfaces have changed and application UI hierarchies have been restructured, rendering

the original evaluation scripts incompatible. We verified each task individually and rewrote the evaluation scripts to address both types of changes. The second set comprises 110 newly designed tasks spanning two categories. One targets the iWork suite of Pages, Numbers, and Keynote, which are among the most widely used productivity applications on macOS. The other targets frequent desktop operations such as organizing email and checking weather forecasts. After cross-validation, we excluded 4 tasks whose evaluators were unreliable due to underlying macOS bugs. The full distribution of the final 169 seed tasks is shown in Table 2.

Task specification. Each task is specified as a triplet: a *natural-language instruction* that describes the goal, an *environment setup script* that configures the macOS instance to the required initial state, and an *evaluation script* that inspects the final environment state and returns a pass/fail result. For multi-application tasks, the evaluation script also produces a fine-grained multi-checkpoint score (see Section 3.5). Appendix B.1 provides details of the annotation and cross-validation process.

Template-based task expansion. Each seed task is expanded into 4 variants to introduce variation in both parameters and phrasing, yielding the full set of $169 \times 4 = 676$ tasks. The expansion follows

Table 2: Statistics of MacAgentBench.

Category	Tasks
Total	**676 (100%)**
- Productivity	224 (33.1%)
- System	44 (6.5%)
- Internet	108 (16.0%)
- Development	44 (6.5%)
- Multimedia	116 (17.2%)
- Multi-App	140 (20.7%)
Interaction	
- GUI	124 (18.3%)
- CLI	148 (21.9%)
- GUI+CLI	404 (59.8%)
Instructions	
Avg. length	28.1 words

Figure 2: Distribution of MacAgentBench.

a two-stage process. The first stage, *parameter substitution*, alters concrete values in the task (such as file names, dates, and content strings) and updates the setup and evaluation scripts accordingly. The second stage, *instruction rewriting*, uses an LLM to rephrase the task instruction while preserving the original task objective, producing semantically equivalent but lexically distinct variants. Each variant therefore differs from the seed task in both task parameters and instruction phrasing.

3.4 Task statistics

As shown in Figure 2 and Table 2, MacAgentBench spans six categories across 25 applications: Productivity, with apps such as Notes, Pages, and Keynote; System, with Terminal and Settings; Internet, with GitHub and Email; Development, with VS Code and Tmux; Multimedia, with ASR and TTS; and Multi-App, with cross-application workflows. This breadth makes MacAgentBench the largest macOS benchmark to date, with 404 tasks (59.8%) involving both GUI and CLI.

3.5 Evaluation protocol

MacAgentBench employs a fully deterministic, rule-based evaluation protocol, avoiding the reproducibility issues of LLM-as-judge methods. Each evaluator consists of two components: a *getter* function that extracts the relevant state from the environment, and a *metric* function that compares the extracted result against the expected value and returns a pass/fail result. A single task may invoke multiple getters to verify different aspects of task completion. In total, 156 unique getter functions

cover all 676 tasks and fall into three categories:

- **Shell commands** (88 functions) read file contents, database state, and system configuration via utilities such as `cat` and `grep`.

- **AppleScript** (48 functions) queries the state of macOS-native applications (e.g., Calendar events, Keynote properties) via `osascript`.

- **Python scripts** (20 functions) handle more complex verification logic such as file content comparison and audio attribute checking.

All evaluators are deterministic: the same environment state produces the same evaluation result.

Fine-grained multi-checkpoint evaluation. For multi-application tasks, a single pass/fail result cannot reveal where the agent fails in a multi-step workflow. MacAgentBench therefore defines fine-grained *checkpoints* for the 140 multi-application tasks listed in Table 2. Each checkpoint corresponds to a key sub-goal of the task and is evaluated by its own getter and metric, following the same evaluator architecture. The number of checkpoints per task averages 4.1, ranging from 2 to 7. The final score is the fraction of checkpoints passed, in $[0, 1]$; a task is marked as passed only when all checkpoints succeed. For example, the task "create a calendar and add three events" has four checkpoints: whether the calendar exists, and whether each of the three events has been added. This enables fine-grained progress tracking: a score of 0.75 indicates that the agent completed three of the four sub-goals.

Each checkpoint is further annotated with a *capability* tag from one of five dimensions: *research* for external knowledge queries, *app_state* for application state verification, *content_match* for content correctness checks, *file_ops* for file system operations, and *system_config* for system setting modifications. This annotation enables analysis of model strengths and weaknesses across distinct capability dimensions.

3.6 Evaluation pipeline

The evaluation of each task proceeds through five stages. **(1) Environment startup**: a fresh Docker container is launched for the task; the virtual machine boots from a copy-on-write layer on the shared base image and becomes ready within 30 s. **(2) Task initialization**: a task-specific setup script is executed to configure the required initial state, for example by creating files, launching applications, or populating database entries. **(3) Agent execution**: the natural-language task instruction is delivered to the agent, which then operates autonomously in the environment until it signals completion or reaches the maximum step limit. **(4) Evaluation**: a deterministic, rule-based evaluator, written as a shell command, AppleScript, or Python script, inspects the final environment state and returns a pass/fail result. **(5) Reset**: the container is destroyed, discarding the copy-on-write layer; the next task starts from a clean base image, ensuring full inter-task isolation.

4 Experiments

4.1 Experimental setup

We evaluate three agent frameworks. **/** represents a baseline pure GUI agent that uses only screenshots and mouse/keyboard actions; **AgentS3** (Gonzalez-Pumariega et al., 2025) is a multi-agent collaboration architecture; and **OpenClaw** (Openclaw Team, 2025) is an in-container agent harness with access to shell, AppleScript, and built-in skills. We evaluate 16 models, organized into general VLMs and native GUI agent models; the full list with citations and per-framework coverage appears in Appendix C.1 (Table 3). General VLMs are evaluated on all three frameworks, while native GUI agent models are evaluated only on the baseline framework, as they cannot reliably produce the action formats required by AgentS3 and OpenClaw. Each task is capped at 50 interaction steps, and experiments cover the full 676-task set.

Evaluation metrics. We report the following metrics throughout the paper. **Pass@1** is the fraction of tasks solved on a single attempt. **Pass@4** is the fraction of tasks solved on at least one of four attempts. **Pass^4** is the fraction of tasks solved on all four attempts. **Score** is the fraction of checkpoints passed on multi-application tasks, further decomposed along five capability dimensions: Research, App State, Content, File Ops, and Sys Config. **Avg. Steps** is the average number of interaction steps per task, where a lower value indicates more efficient execution. **Tokens (In/Out)** are the average input and output token counts per task. **Avg. Cost** is the average API cost (USD) per task.

4.2 Main results and analysis

Framework comparison. Keeping the model constant, AgentS3 delivers consistent improvements over the baseline across all models. On Claude Opus 4.6, for example, Pass@1 increases from 39.2% (baseline) to 66.9% (AgentS3). OpenClaw also outperforms the baseline on most models, with Pass@1 reaching 73.7% on Claude Opus 4.6. However, the gains from OpenClaw are less consistent than those from AgentS3. On smaller models, the improvement from OpenClaw falls below that from AgentS3: on Qwen3VL-32B, AgentS3 outperforms OpenClaw by 3.7 points. On InternVL models, the additional context introduced by OpenClaw interferes with these models, causing a sharp performance drop; they fail to produce the tool-calling format OpenClaw requires, rendering the framework unusable.

Model comparison. Across all frameworks, proprietary models substantially outperform open-source ones. Claude Opus 4.6 on OpenClaw achieves the highest Pass@1 at 73.7%. On the baseline framework, GPT-5.4 achieves the highest Pass@1 at 58.4%, surpassing Claude Opus 4.6 at 39.2%; yet with framework support, Claude overtakes GPT-5.4 on both AgentS3 and OpenClaw, suggesting that Claude benefits more from framework augmentation.

Robustness analysis. Substantial gaps exist between Pass@1, Pass@4, and Pass^4, indicating that agents can solve many tasks but fail to do so consistently across attempts. This highlights robustness as a critical dimension for evaluating agent capability beyond single-trial success rates. Claude and GPT-5.4 on OpenClaw provide a revealing comparison: both achieve close Pass@4, 85.2% and 82.8%

Table 3: Main results on MacAgentBench.

Framework	Model	Pass@1 (%)	Pass@4 (%)	Pass^4 (%)	Steps	Tokens (In/Out)	Cost($)
/	Claude Opus 4.6	39.2	48.5	28.4	27.1	177K / 4.3K	0.98
	GPT-5.4	58.4	79.9	36.7	13.2	127K / 3.0K	0.36
	Gemini 3.1 Pro	34.2	47.9	21.9	26.5	127K / 19.7K	0.49
	Qwen3VL-235B-A22B	21.6	37.3	9.5	23.2	257K / 4.4K	0.08
	Qwen3VL-32B	21.3	36.7	10.1	32.7	385K / 10.4K	0.04
	Qwen3VL-8B	14.5	29.0	4.1	35.2	468K / 35.9K	0.10
	InternVL3.5-14B	6.4	14.2	0.6	32.9	119K / 5.2K	–
	InternVL3.5-8B	4.7	10.7	1.2	32.1	115K / 4.7K	–
	UI-TARS-72B-DPO	13.2	23.1	5.3	29.2	432K / 2.6K	–
	UI-TARS-1.5-7B	9.8	18.3	3.6	42.2	651K / 4.1K	0.07
	ScaleCUA-32B	10.5	20.7	2.4	33.5	135K / 4.1K	–
	ScaleCUA-7B	6.7	13.0	1.2	30.3	121K / 4.3K	–
	GUI-Owl-1.5-32B	17.2	34.3	6.5	27.6	323K / 5.3K	–
	GUI-Owl-1.5-8B	10.2	20.7	2.4	24.8	284K / 9.3K	–
	OpenCUA-32B	18.8	34.9	7.7	20.1	176K / 8.3K	–
	OpenCUA-7B	15.1	29.0	5.9	24.1	214K / 10.1K	–
AgentS3	Claude Opus 4.6	66.9	82.2	50.3	10.0	262K / 4.4K	1.30
	GPT-5.4	58.9	79.3	36.7	10.2	263K / 3.0K	0.66
	Gemini 3.1 Pro	54.3	70.4	37.9	8.1	136K / 8.7K	0.36
	Qwen3VL-235B-A22B	46.7	68.6	27.2	13.3	379K / 16.8K	0.14
	Qwen3VL-32B	37.4	58.6	17.2	13.4	379K / 20.5K	0.05
	Qwen3VL-8B	28.6	45.0	13.0	13.7	426K / 29.3K	0.05
	InternVL3.5-14B	13.5	30.8	3.6	13.6	515K / 5.1K	–
	InternVL3.5-8B	9.6	20.1	1.8	21.6	1075K / 12.3K	–
OpenClaw	Claude Opus 4.6	73.7	85.2	58.6	8.6	263K / 1.2K	1.35
	GPT-5.4	60.7	82.8	38.5	6.5	153K / 1.5K	0.40
	Gemini 3.1 Pro	63.3	82.8	40.2	6.6	122K / 2.0K	0.27
	Qwen3VL-235B-A22B	46.0	63.9	28.4	8.4	211K / 5.7K	0.07
	Qwen3VL-32B	33.7	50.9	14.2	8.3	209K / 7.6K	0.02
	Qwen3VL-8B	26.9	45.0	13.6	13.2	455K / 12.7K	0.07
	InternVL3.5-14B	0.0	0.0	0.0	1.0	8K / 0.8K	–
	InternVL3.5-8B	0.0	0.0	0.0	1.0	8K / 0.2K	–

respectively, suggesting similar capability ceilings; however, their Pass@1 differs by 13.0 points and Pass^4 by 20.1 points, revealing that although the two models can solve a similar set of tasks, Claude completes them far more consistently.

4.3 Effect of skill augmentation

Table 4: Pass@1 (%) on tasks with and without skill coverage across frameworks. Subscripts on AgentS3 and / report Δ vs. OpenClaw.

Subset	Model	OpenClaw	AgentS3	/
w/ Skill	Claude Opus 4.6	89.4	84.3 $_{-5.1}$	55.9 $_{-33.5}$
	GPT-5.4	77.9	72.6 $_{-5.3}$	67.6 $_{-10.4}$
	Gemini 3.1 Pro	80.6	70.2 $_{-10.4}$	50.5 $_{-30.1}$
	Qwen3VL-235B-A22B	64.6	61.4 $_{-3.2}$	28.2 $_{-36.4}$
	Qwen3VL-32B	52.9	47.1 $_{-5.9}$	28.7 $_{-24.2}$
	Qwen3VL-8B	43.6	39.1 $_{-4.5}$	21.3 $_{-22.3}$
	InternVL3.5-14B	0.0	19.9 $_{+19.9}$	9.3 $_{+9.3}$
	InternVL3.5-8B	0.0	14.6 $_{+14.6}$	7.4 $_{+7.4}$
w/o Skill	Claude Opus 4.6	45.6	48.8 $_{+3.1}$	16.2 $_{-29.4}$
	GPT-5.4	33.8	41.9 $_{+8.1}$	45.6 $_{+11.9}$
	Gemini 3.1 Pro	43.1	37.5 $_{-5.6}$	13.8 $_{-29.4}$
	Qwen3VL-235B-A22B	22.5	30.6 $_{+8.1}$	19.4 $_{-3.1}$
	Qwen3VL-32B	13.1	30.6 $_{+17.5}$	15.6 $_{+2.5}$
	Qwen3VL-8B	8.8	18.1 $_{+9.4}$	9.4 $_{+0.6}$
	InternVL3.5-14B	0.0	8.8 $_{+8.8}$	4.4 $_{+4.4}$
	InternVL3.5-8B	0.0	5.6 $_{+5.6}$	2.5 $_{+2.5}$

To understand whether the advantage of Open-Claw comes from its skill library or its framework design, we identify two subsets of tasks: those covered by pre-defined skills and those without (Table 4). Tasks with ambiguous skill coverage are excluded from this analysis. On skill-covered tasks, OpenClaw leads by a large margin: with Claude, it reaches 89.4% vs. 84.3% for AgentS3 and 55.9% for the baseline, confirming that skills provide substantial gains. On tasks without skill coverage, however, this advantage largely disappears. For 5 out of 8 models, OpenClaw even underperforms the baseline, with the baseline column showing positive Δ values. This indicates that the overall lead in the main results is primarily driven by its skill library rather than its framework design alone. In contrast, AgentS3, which does not use skills, consistently outperforms the baseline on both task subsets. For example, on tasks without skill coverage, Claude on AgentS3 reaches 48.8% vs. 16.2% on the baseline, demonstrating that multi-agent collaboration alone provides stable performance gains.

4.4 Fine-grained evaluation analysis

Table 5 reports the fine-grained evaluation on 140 multi-application tasks. The Score column consistently exceeds Pass@1, revealing that agents of-

Table 5: Fine-grained evaluation results on multi-application tasks.

Framework	Model	Pass@1 (%)	Score	Research	App State	Content	File Ops	Sys Config
/	Claude Opus 4.6	20.7	31.4	24.6	31.5	15.8	81.4	0.0
	GPT-5.4	48.6	64.1	55.0	70.7	56.1	97.7	90.0
	Gemini 3.1 Pro	13.6	26.7	25.1	33.2	12.2	62.8	0.0
	Qwen3VL-235B-A22B	6.4	19.1	7.9	25.5	9.4	53.5	25.0
	Qwen3VL-32B	7.9	18.7	12.6	21.7	8.6	34.9	55.0
	Qwen3VL-8B	2.1	9.0	1.6	12.5	3.6	25.6	20.0
	InternVL3.5-14B	0.7	9.3	0.5	16.8	4.3	18.6	10.0
	InternVL3.5-8B	0.0	5.4	0.0	8.2	2.9	18.6	0.0
	UI-TARS-72B-DPO	1.4	12.9	3.1	15.2	8.6	25.6	35.0
	UI-TARS-1.5-7B	1.4	8.9	1.0	14.7	5.0	18.6	5.0
	ScaleCUA-32B	0.7	12.3	5.2	22.8	6.5	23.3	5.0
	ScaleCUA-7B	0.0	7.8	3.1	12.0	2.9	23.3	0.0
	GUI-Owl-1.5-32B	7.9	19.6	13.6	19.0	8.6	55.8	45.0
	GUI-Owl-1.5-8B	3.6	15.8	6.3	23.9	3.6	48.8	5.0
	OpenCUA-32B	7.9	21.9	11.0	25.5	12.9	53.5	50.0
	OpenCUA-7B	1.4	13.6	4.2	20.1	10.1	41.9	5.0
AgentS3	Claude Opus 4.6	40.7	53.1	35.3	47.6	30.4	100.0	66.7
	GPT-5.4	41.4	59.3	52.4	64.7	45.3	95.3	85.0
	Gemini 3.1 Pro	30.7	50.6	50.3	55.4	31.7	90.7	35.0
	Qwen3VL-235B-A22B	25.7	39.2	28.3	40.8	26.6	72.1	70.0
	Qwen3VL-32B	19.3	33.0	25.1	28.8	20.1	65.1	65.0
	Qwen3VL-8B	12.1	25.5	15.2	27.2	12.2	58.1	40.0
	InternVL3.5-14B	1.4	10.0	3.1	15.2	4.3	30.2	5.0
	InternVL3.5-8B	0.7	7.6	1.6	13.6	3.6	16.3	0.0
OpenClaw	Claude Opus 4.6	63.6	75.0	75.4	77.2	80.6	90.7	60.0
	GPT-5.4	45.0	56.3	54.5	54.3	50.4	90.7	30.0
	Gemini 3.1 Pro	40.0	51.9	52.4	51.1	57.6	93.0	30.0
	Qwen3VL-235B-A22B	22.9	42.6	39.3	46.7	43.2	72.1	30.0
	Qwen3VL-32B	5.7	21.8	14.1	26.6	23.0	48.8	10.0
	Qwen3VL-8B	2.9	19.4	12.0	23.4	10.1	58.1	10.0
	InternVL3.5-14B	0.0	4.9	0.0	8.7	2.9	16.3	0.0
	InternVL3.5-8B	0.0	4.9	0.0	8.7	2.9	16.3	0.0

ten make partial progress on sub-goals even when the overall task fails. For example, GPT-5.4 on the baseline achieves 48.6% Pass@1 but 64.1% Score, indicating that many failed tasks reflect partial success rather than total failure. This distinction is further illustrated by UI-TARS-72B-DPO and UI-TARS-1.5-7B on the baseline: both achieve the same 1.4% Pass@1, yet their Scores differ, at 12.9% and 8.9% respectively. Pass/fail evaluation treats them as equally poor, while checkpoint-based scoring reveals that the larger model completes meaningfully more sub-goals. Some checkpoints verify that the agent does not corrupt the pre-existing environment state, such as preserving untouched files or avoiding incorrect labels. That is why even completely unusable combinations such as InternVL3.5 on OpenClaw receive a small non-zero Score despite achieving 0% Pass@1.

Across capability dimensions, File Ops Scores are consistently the highest, indicating that file system operations are the easiest for agents. In contrast, Research Scores are generally the lowest, suggesting that querying external knowledge remains the primary bottleneck.

The capability profiles also differ across frameworks. Claude on OpenClaw achieves a relatively balanced profile, with Scores ranging from 60.0% on Sys Config to 90.7% on File Ops. In contrast, GPT-5.4 on the baseline shows a highly uneven profile: 97.7% on File Ops and 90.0% on Sys Config, but only 55.0% on Research and 56.1% on Content, revealing that strong performance on certain dimensions can mask weaknesses in others that only fine-grained evaluation can expose.

5 Conclusion

We presented MacAgentBench, a comprehensive benchmark for evaluating CUAs on real-world macOS desktop tasks. Built on a lightweight containerized environment with task-level isolation, MacAgentBench provides deterministic, rule-based evaluations and supports fine-grained multi-checkpoint evaluation with capability annotations on multi-application tasks, exposing imbalanced capability profiles invisible to pass/fail metrics. Framework design substantially affects performance, but the lead of OpenClaw is driven primarily by its skill library rather than its framework design. Moreover, the gap between Pass@1 and Pass[4] highlights robustness as a critical, under-explored dimension.

Limitations

The macOS system runs in a QEMU virtual machine without Apple hardware GPU support. The resulting differences from native macOS are predominantly rendering effects rather than functional differences in application behavior (e.g., GPU-accelerated rounded corners and view transitions). During task construction we compared each task against macOS running on Apple hardware and excluded any task whose setup, expected behavior, or evaluation outcome diverged between the two environments. Because task success is defined over file-system, AppleScript, and application-state outcomes rather than pixel-level visuals, the residual rendering differences do not affect the success criteria of any included task. The benchmark is tied to macOS Tahoe 26. Since application behaviors, AppleScript interfaces, and UI layouts may change across macOS versions, adapting MacAgentBench to a new version would require reviewing and updating the setup and evaluation scripts. MacAgentBench currently covers 676 tasks. Although this is the largest macOS agent benchmark to date, it could be expanded to cover more applications and scenarios.

Potential risks. CUAs capable of GUI and CLI interaction can, in principle, be misused to automate sensitive operations such as unauthorized file access or credential harvesting if deployed on user systems without proper safeguards. MacAgentBench substantially mitigates such risks by design. First, all tasks execute within an isolated Docker-QEMU container with copy-on-write disk layers discarded after each task, ensuring no persistent state and no access to real user data; the trajectories we release are therefore recordings of agent behavior on synthetic, sandboxed task instances rather than real user activity. Second, the task environment itself contains no personally identifying information: as described in Appendix B.6, all third-party content was de-identified prior to inclusion, with real names, email addresses, phone numbers, and file paths replaced by fabricated placeholders. We release the complete benchmark artifacts for all 676 tasks, including task instructions, setup scripts, deterministic evaluation scripts, checkpoint definitions, metadata, and environment configuration. We also release gold reference solutions for the subset of tasks whose canonical solutions can be expressed as CLI or AppleScript commands. In addition, we release agent execution trajectories (screenshots, actions, and checkpoint-level evaluation outcomes) for all 676 tasks. These artifacts are intended for reproducibility, evaluator validation, and failure-mode analysis (e.g., Appendix D.2), and are distributed under a research-use license. While the released trajectories could in principle be repurposed for benchmark-specific tuning or overfitting, they are limited to benign, sandboxed productivity tasks and contain no real user data, credentials, or access tokens, thereby reducing privacy leakage and direct-abuse risks. Third, we recommend that any CUAs evaluated against MacAgentBench be deployed on production systems only with explicit user consent, permission boundaries, and audit logging.

References

Saaket Agashe, Jiuzhou Han, Shuyu Gan, Jiachen Yang, Ang Li, and Xin Eric Wang. 2025a. Agent S: an open agentic framework that uses computers like a human. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Saaket Agashe, Kyle Wong, Vincent Tu, Jiachen Yang, Ang Li, and Xin Eric Wang. 2025b. Agent S2: A compositional generalist-specialist framework for computer use agents. *CoRR*, abs/2504.00906.

Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku. Technical report, Anthropic.

Anthropic. 2025. System card: Claude opus 4 & claude sonnet 4. Technical report, Anthropic.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, and 45 others. 2025. Qwen3-vl technical report. *Preprint*, arXiv:2511.21631.

Rogerio Bonatti, Dan Zhao, Francesco Bonacci, Dillon Dupont, Sara Abdali, Yinheng Li, Yadong Lu, Justin Wagle, Kazuhito Koishida, Arthur Bucker, Lawrence Keunho Jang, and Zheng Hui. 2025. Windows agent arena: Evaluating multi-modal OS agents at scale. In *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, Proceedings of Machine Learning Research. PMLR / OpenReview.net.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing GUI grounding for advanced visual GUI agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024,*

Bangkok, Thailand, August 11-16, 2024, pages 9313–9332. Association for Computational Linguistics.

Weihua Cheng, Ersheng Ni, Wenlong Wang, Yifei Sun, Junming Liu, Wangyu Shen, Yirong Chen, Botian Shi, and Ding Wang. 2025. MGA: memory-driven GUI agent for observation-centric interaction. *CoRR*, abs/2510.24168.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samual Stevens, Boshi Wang, Huan Sun, and Yu Su. 2023. Mind2web: Towards a generalist agent for the web. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Gemini Team, Google DeepMind. 2026. Gemini 3.1 pro model card. `https://deepmind.google/models/model-cards/gemini-3-1-pro/`.

GLM-5-Team, :, Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, Chenzheng Zhu, Congfeng Yin, Cunxiang Wang, Gengzheng Pan, Hao Zeng, Haoke Zhang, Haoran Wang, and 168 others. 2026. Glm-5: from vibe coding to agentic engineering. *Preprint*, arXiv:2602.15763.

Gonzalo Gonzalez-Pumariega, Vincent Tu, Chih-Lun Lee, Jiachen Yang, Ang Li, and Xin Eric Wang. 2025. The unreasonable effectiveness of scaling agents for computer use. *CoRR*, abs/2510.02250.

Liangxuan Guo, Bin Zhu, Qingqian Tao, Kangning Liu, Xun Zhao, Xianzhe Qin, Jin Gao, and Guangfu Hao. 2025. Agentic lybic: Multi-agent execution system with tiered reasoning and orchestration. *CoRR*, abs/2509.11067.

Hongliang He, Wenlin Yao, Kaixin Ma, Wenhao Yu, Yong Dai, Hongming Zhang, Zhenzhong Lan, and Dong Yu. 2024. Webvoyager: Building an end-to-end web agent with large multimodal models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 6864–6890. Association for Computational Linguistics.

Wenyi Hong, Weihan Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang, Zihan Wang, Yuxiao Dong, Ming Ding, and Jie Tang. 2024. Cogagent: A visual language model for GUI agents. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2024, Seattle, WA, USA, June 16-22, 2024*, pages 14281–14290. IEEE.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. 2024. Swe-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Kilo.ai. 2025. Pinchbench: Benchmarking LLM models as OpenClaw coding agents. GitHub repository.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. 2024. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 881–905. Association for Computational Linguistics.

Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. 2025. Screenspot-pro: GUI grounding for professional high-resolution computer use. *CoRR*, abs/2504.07981.

Yuhang Liu, Pengxiang Li, Congkai Xie, Xavier Hu, Xiaotian Han, Shengyu Zhang, Hongxia Yang, and Fei Wu. 2025a. Infigui-r1: Advancing multimodal GUI agents from reactive actors to deliberative reasoners. *CoRR*, abs/2504.14239.

Zefang Liu and Yinzhu Quan. 2025. Econwebarena: Benchmarking autonomous agents on economic tasks in realistic web environments. *CoRR*, abs/2506.08136.

Zhaoyang Liu, JingJing Xie, Zichen Ding, Zehao Li, Bowen Yang, Zhenyu Wu, Xuehui Wang, Qiushi Sun, Shi Liu, Weiyun Wang, Shenglong Ye, Qingyun Li, Xuan Dong, Yue Yu, Chenyu Lu, YunXiang Mo, Yao Yan, Zeyue Tian, Xiao Zhang, and 11 others. 2025b. Scalecua: Scaling open-source computer use agents with cross-platform data. *CoRR*, abs/2509.15221.

Mike A. Merrill, Alexander Glenn Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, Estefany Kelly Buchanan, Junhong Shen, Guanghao Ye, Haowei Lin, Jason Poulos, Maoyu Wang, Marianna Nezhurina, Jenia Jitsev, Di Lu, Orfeas Menis-Mastromichalakis, and 66 others. 2026. Terminal-bench: Benchmarking agents on hard, realistic tasks in command line interfaces. *CoRR*, abs/2601.11868.

Grégoire Mialon, Clémentine Fourrier, Thomas Wolf, Yann LeCun, and Thomas Scialom. 2024. GAIA: a benchmark for general AI assistants. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

OpenAI. 2026. GPT-5.4 Thinking system card. Technical report, OpenAI.

Openclaw Team. 2025. Openclaw: Your own personal AI assistant. GitHub repository.

Rui Qian, Xin Yin, Chuanhang Deng, Zhiyuan Peng, Jian Xiong, Wei Zhai, and Dejing Dou. 2025. Uground: Towards unified visual grounding with unrolled transformers. *CoRR*, abs/2510.03853.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2024. Toolllm: Facilitating large language models to master 16000+ real-world apis. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, Wanjun Zhong, Kuanye Li, Jiale Yang, Yu Miao, Woyu Lin, Longxiang Liu, Xu Jiang, Qianli Ma, Jingyu Li, and 16 others. 2025. UI-TARS: pioneering automated GUI interaction with native agents. *CoRR*, abs/2501.12326.

Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William E. Bishop, Wei Li, Folawiyo Campbell-Ajala, Daniel Kenji Toyama, Robert James Berry, Divya Tyamagundlu, Timothy P. Lillicrap, and Oriana Riva. 2025. Androidworld: A dynamic benchmarking environment for autonomous agents. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

ByteDance Seed. 2025. UI-TARS-2 technical report: Advancing GUI agent with multi-turn reinforcement learning. *CoRR*, abs/2509.02544.

Linxin Song, Yutong Dai, Viraj Prabhu, Jieyu Zhang, Taiwei Shi, Li Li, Junnan Li, Silvio Savarese, Zeyuan Chen, Jieyu Zhao, Ran Xu, and Caiming Xiong. 2025. Coact-1: Computer-using agents with coding as actions. *CoRR*, abs/2508.03923.

Shizuo Tian, Hao Wen, Yuxuan Chen, Jiacheng Liu, Shanhui Zhao, Guohong Liu, Ju Ren, Yunxin Liu, and Yuanchun Li. 2025. Agentprog: Empowering long-horizon GUI agents with program-guided context management. *CoRR*, abs/2512.10371.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, and 56 others. 2025a. Internvl3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *CoRR*, abs/2508.18265.

Xinyuan Wang, Bowen Wang, Dunjie Lu, Junlin Yang, Tianbao Xie, Junli Wang, Jiaqi Deng, Xiaole Guo, Yiheng Xu, Chen Henry Wu, Zhennan Shen, Zhuokai Li, Ryan Li, Xiaochuan Li, Junda Chen, Boyuan Zheng, Peihang Li, Fangyu Lei, Ruisheng Cao, and 23 others. 2025b. Opencua: Open foundations for computer-use agents. *CoRR*, abs/2508.09123.

Xuehui Wang, Zhenyu Wu, JingJing Xie, Zichen Ding, Bowen Yang, Zehao Li, Zhaoyang Liu, Qingyun Li, Xuan Dong, Zhe Chen, Weiyun Wang, Xiangyu Zhao, Jixuan Chen, Haodong Duan, Tianbao Xie, Chenyu Yang, Shiqian Su, Yue Yu, Yuan Huang, and 9 others. 2025c. Mmbench-gui: Hierarchical multi-platform evaluation framework for GUI agents. *CoRR*, abs/2507.19478.

Zhiyong Wu, Chengcheng Han, Zichen Ding, Zhenmin Weng, Zhoumianze Liu, Shunyu Yao, Tao Yu, and Lingpeng Kong. 2024. Os-copilot: Towards generalist computer agents with self-improvement. *CoRR*, abs/2402.07456.

Zhiyong Wu, Zhenyu Wu, Fangzhi Xu, Yian Wang, Qiushi Sun, Chengyou Jia, Kanzhi Cheng, Zichen Ding, Liheng Chen, Paul Pu Liang, and Yu Qiao. 2025. OS-ATLAS: foundation action model for generalist GUI agents. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. 2024. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

Frank F. Xu, Yufan Song, Boxuan Li, Yuxuan Tang, Kritanjali Jain, Mengxue Bao, Zora Zhiruo Wang, Xuhui Zhou, Zhitong Guo, Murong Cao, Mingyang Yang, Hao Yang Lu, Amaad Martin, Zhe Su, Leander Maben, Raj Mehta, Wayne Chi, Lawrence Keunho Jang, Yiqing Xie, and 2 others. 2024. Theagentcompany: Benchmarking LLM agents on consequential real world tasks. *CoRR*, abs/2412.14161.

Haiyang Xu, Xi Zhang, Haowei Liu, Junyang Wang, Zhaozai Zhu, Shengjie Zhou, Xuhao Hu, Feiyu Gao, Junjie Cao, Zihua Wang, Zhiyuan Chen, Jitong Liao, Qi Zheng, Jiahui Zeng, Ze Xu, Shuai Bai, Junyang Lin, Jingren Zhou, and Ming Yan. 2026. Mobile-agent-v3.5: Multi-platform fundamental GUI agents. *CoRR*, abs/2602.16855.

Ran Xu, Kaixin Ma, Wenhao Yu, Hongming Zhang, Joyce C. Ho, Carl Yang, and Dong Yu. 2025a. Retrieval-augmented GUI agents with generative guidelines. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing, EMNLP 2025, Suzhou, China, November 4-9, 2025*, pages 17866–17875. Association for Computational Linguistics.

Yiheng Xu, Dunjie Lu, Zhennan Shen, Junli Wang, Zekun Wang, Yuchen Mao, Caiming Xiong, and Tao Yu. 2025b. Agenttrek: Agent trajectory synthesis via guiding replay with web tutorials. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tian-bao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2025c. Aguvis: Unified pure vision agents for autonomous GUI interaction. In *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, Proceedings of Machine Learning Research. PMLR / OpenReview.net.

Tianci Xue, Weijian Qi, Tianneng Shi, Chan Hee Song, Boyu Gou, Dawn Song, Huan Sun, and Yu Su. 2025. An illusion of progress? assessing the current state of web agents. *CoRR*, abs/2504.01382.

Bowen Yang, Kaiming Jin, Zhenyu Wu, Zhaoyang Liu, Qiushi Sun, Zehao Li, JingJing Xie, Zhoumi-anze Liu, Fangzhi Xu, Kanzhi Cheng, Qingyun Li, Yian Wang, Yu Qiao, Zun Wang, and Zichen Ding. 2026. Os-symphony: A holistic framework for robust and generalist computer-using agent. *CoRR*, abs/2601.07779.

Pei Yang, Hai Ci, and Mike Zheng Shou. 2025a. ma-cosworld: A multilingual interactive benchmark for GUI agents. *CoRR*, abs/2506.04135.

Yuhao Yang, Zhen Yang, Zi-Yi Dou, Anh Nguyen, Keen You, Omar Attia, Andrew Szot, Michael Feng, Ram Ramrakhya, Alexander Toshev, Chao Huang, Yinfei Yang, and Zhe Gan. 2025b. Ultracua: A foundation model for computer use agents with hybrid action. *CoRR*, abs/2510.17790.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. 2024. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *CoRR*, abs/2406.12045.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R. Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net.

Bowen Ye, Rang Li, Qibin Yang, Yuanxin Liu, Linli Yao, Hanglong Lv, Zhihui Xie, Chenxin An, Lei Li, Lingpeng Kong, Qi Liu, Zhifang Sui, and Tong Yang. 2026. Claw-eval: Towards trustworthy evaluation of autonomous agents. *Preprint*, arXiv:2604.06132.

Yuxuan Zhang, Yubo Wang, Yipeng Zhu, Penghui Du, Junwen Miao, Xuan Lu, Wendong Xu, Yunzhuo Hao, Songcheng Cai, Xiaochen Wang, Huaisong Zhang, Xian Wu, Yi Lu, Minyi Lei, Kai Zou, Huifeng Yin, Ping Nie, Liang Chen, Dongfu Jiang, and 2 others. 2026. Clawbench: Can ai agents complete everyday online tasks? *Preprint*, arXiv:2604.08523.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2024. Webarena: A realistic web environment for building autonomous agents. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

A Environment details

A.1 Infrastructure implementation details

The design rationale for our Docker-QEMU stack is discussed in Section 3.1. Here we provide implementation details and a detailed comparison.

Container-based isolation. Each task runs in its own container instance, fully isolated from other tasks. After each evaluation, the container is discarded, guaranteeing a clean initial state for the next task and eliminating cross-task contamination.

Copy-on-write accelerated startup. Rather than duplicating the full 52 GB disk image for each container, we leverage QEMU's copy-on-write mechanism to create a lightweight differential layer on top of the base image. The virtual machine reads directly from the shared base image and only records modified blocks in the copy-on-write layer. This reduces container startup time from about 5 min (full copy) to under 30 s, and lowers per-instance disk overhead from 52 GB to about 1 GB, with no impact on runtime performance.

Implementation details. Docker image base: sickcodes/Docker-OSX with QEMU 10.0.0 and macOS Tahoe 26. QEMU launch parameters: 4 CPU cores, 4 GB RAM, qcow2 disk format. Networking: SSH on container port 10022 and VNC on container port 5900, each dynamically mapped to host ports. Task-level reset: between tasks, the Docker container is restarted, discarding and rebuilding the COW layer to restore a clean initial state. Container lifecycle: docker run → wait for SSH → environment initialization → execute task → evaluate → next task. Parallel execution: up to 7 containers can run simultaneously on a single host with 64 GB RAM.

A.2 Observation space

Agents receive observations through two channels:

- **Screenshots**: Full desktop capture of the macOS environment, providing pixel-level visual information of the current GUI state.

- **Terminal output**: For CLI tasks, agents receive the stdout/stderr output from executed commands via SSH.

A.3 Action space

Agents interact with the environment through two channels:

- **GUI actions**: Mouse and keyboard operations via pyautogui, including click (left/right/double), drag, scroll, type, and hotkey combinations.

- **CLI actions**: Shell commands executed via SSH, enabling file system operations, application launching, and AppleScript execution.

Agents can freely mix GUI and CLI actions within a single task, choosing the most efficient interaction method for each step.

B Benchmark details

B.1 Task annotation process

Tasks were designed by two annotation teams composed of co-authors of this work, with each team responsible for half of the tasks. The annotation process consisted of three stages: (1) team members familiarized themselves with each target application by completing a set of tutorial tasks; (2) each team independently designed tasks covering diverse functionality and difficulty levels, including the instruction, setup script, and evaluation script; (3) after construction, the two teams swapped tasks: each team completed and verified the tasks designed by the other team, ensuring that instructions are unambiguous and evaluators produce correct results. As a final validation step, we ran the full benchmark using OpenClaw with Claude Opus 4.6 and manually inspected the agent's execution logs for every task, confirming that no false positives or false negatives were present in the evaluation results.

Annotation team background, recruitment, compensation, and risk. The two annotation teams are composed of co-authors of this work (graduate students in computer science). Annotation was carried out as internal collaborative work on this research project: team members were not recruited through any crowdsourcing platform and received no hourly payment. Their contribution to the benchmark is recognized through co-authorship on this paper, which is the standard form of compensation for research collaboration in academia and is independent of the team members' country of residence. Because all annotated content consists of benign desktop-application tasks (e.g., notes, calendar, file operations) and contains no offensive, politically sensitive, or psychologically demanding material, the annotation process posed no known risk to the team members.

Table 6: Comparison of macOS agent benchmark environments.

	macOSWorld	macOSArena	MacAgentBench
Infrastructure	AWS EC2 Mac	Docker-QEMU stack	Docker-QEMU stack
Base image	–	~40 GB	~52 GB
Startup time	~15 min	~5 min	~30 s
Runtime disk usage	–	~40 GB	~1 GB

B.2 Task sources

The seed tasks come from two sources. 63 tasks are adapted from macOSArena (2025c), with evaluation scripts rewritten to account for macOS version changes (see Section 3.3). The remaining 110 tasks are newly designed, covering the iWork suite (Pages, Numbers, Keynote) and frequent desktop operations. After cross-validation, 4 tasks with unreliable evaluators were excluded, yielding 169 final seed tasks.

B.3 Template-based expansion details

Each of the 169 seed tasks was expanded into 4 variants through a two-stage process, yielding $169 \times 4 = 676$ task instances.

Stage 1: Parameter substitution. We modify the concrete values in the task, such as file names, dates, content strings, and target application states, to alter the specific behavior of the task. The environment setup script and evaluation script are updated accordingly to reflect the new parameter values. For example, a task that originally creates a note titled "Meeting Notes" may be changed to "Project Summary" with different body content.

Stage 2: Instruction rewriting. We use an LLM to rephrase each task instruction while preserving the original task objective. This produces semantically equivalent but lexically distinct instruction variants that introduce phrasing differences across the four variants of each seed task. All rewritten instructions were manually reviewed to ensure semantic fidelity.

B.4 Evaluation script examples

Example of a shell-based evaluator (checking if a file exists at a given path):

```python
def finder_check_file_exists(env, file_path: str) -> bool:
    env.connect_ssh()
    cmd = f'test -f "{file_path}" && echo "Exists" || echo "
        Not found"'
    stdout, stderr = env.run_command(cmd)
    output = stdout.read().decode().strip()
        if hasattr(stdout, "read") else stdout.strip()
    return output == "Exists"
```

Example of an AppleScript evaluator (checking a reminder's due date via the Reminders app):

```python
def reminders_check_work_due_next_week(env, reminder_name="
    work"):
    env.connect_ssh()
    stdout, _ = env.run_command("date '+%Y-%m-%d'")
    current_date_str = stdout.read().decode().strip()
        if hasattr(stdout, "read") else stdout.strip()
    current_date = datetime.datetime.strptime(
        current_date_str, "%Y-%m-%d").date()
    current_iso_week = current_date.isocalendar()[1]

    apple_script = f"""
    tell application "Reminders"
        set workReminder to first reminder
            whose name is "{reminder_name}"
        set workDueDate to due date of workReminder
    end tell
    return workDueDate as string
    """
    stdout, stderr = env.run_command(
        f"osascript -e '{apple_script}'")
    due_str = stdout.read().decode().strip()
        if hasattr(stdout, "read") else stdout.strip()
    due_date = dateparser.parse(due_str).date()
    due_week = due_date.isocalendar()[1]
    return due_week == current_iso_week + 1
```

Example of a Python evaluator with fuzzy matching (checking live weather data against the agent's output with tolerances):

```python
def new_weather_check_contains_live_current_values(
    env, output_file: str, expected_command: str
) -> bool:
    output_text = _read_remote_file(env, output_file)
    if output_text is None:
        return False
    live_text = _run_command(env, expected_command).strip()

    live = _parse_live(live_text.splitlines()[0])
    user = _parse_user(output_text)
    if not live or not user:
        return False

    if abs(user["temp_c"] - live["temp_c"]) > 2.0:
        return False
    if abs(user["wind_kmh"] - live["wind_kmh"]) > 5.0:
        return False
    if abs(user["humidity"] - live["humidity"]) > 10.0:
        return False
    if abs(user["prec_mm"] - live["prec_mm"]) > 0.5:
        return False
    return True
```

B.5 Task examples

We list one representative task for each of the 25 applications below, followed by an additional example illustrating a cross-application task. Each task is presented as a separate card.

Notes

In Apple Notes, edit the note titled "Project Ideas" and append the line "Reviewed on Tuesday.".

Reminders

In the Reminders app, create a new reminder titled "Dentist follow-up" due "2026-04-15 09:30".

Calendar

In the Calendar app, create a recurring event called "Lab Meeting" every Monday at 10:00 AM.

Pages

In the Pages app, create a new document using the "Blank Black" template and write: Passwd: 111111.

Numbers

In the Numbers app, create a new blank document, insert a table into the first sheet if needed, then enter the value "test" into cell A1.

Keynote

In the Keynote app, create a new document, export it to PowerPoint, and save it to the Documents folder.

Obsidian

In Obsidian, create a new note called `Inbox/Vendor Call Notes.md` and set its content exactly to the provided meeting notes.

Finder

Create a Smart Folder that shows all PDF files modified in the last 7 days and save it to `$HOME/Library/Saved Searches` with the name `filter.savedSearch`.

Terminal

In the Terminal app, create a new Conda environment named `macos_eval` and install the `spotify` package within that environment.

Settings

In System Settings, set the accent color to purple and turn off the option "Tint window background with wallpaper color".

Clock

In the Clock app, set an alarm for 6:30 AM on weekdays (Monday through Friday) labeled "Morning run", using the "Waves" sound. Then, turn off this alarm.

Safari

Create a new folder named "agent task" at the top level of Safari's bookmarks (not inside the Bookmarks Bar). Then, add at least five webpages to this folder, and make sure one of them is `https://www.apple.com/`.

GitHub

Find the latest open issue in `openclaw/openclaw` with label "bug", and save it as `#<number> | <labels> | <title>` to `$HOME/Desktop/gh_open_issues.txt`.

Himalaya

Check the latest OTP email in Inbox (search across all pages) and save only one line to `$HOME/Desktop/mail_otp.txt` as `otp_code: <6-digit-code>`. If no OTP email exists, write `otp_code: none`.

BlogWatcher

In BlogWatcher, scan all tracked blogs for updates.

Weather

Can you check tomorrow's weather in "San Francisco" and tell me whether it will be rainy? Save only one yes/no line to `$HOME/Desktop/weather_tomorrow_rain.txt`.

VSCode

In VS Code, install the official Python extension. Then, set the user-level conda path setting to `/opt/anaconda3/bin/conda`.

Tmux

In Terminal, send "status" to the tmux session "tmux-status-send-c1", then save the reply to `$HOME/Desktop/tmux_result.json`.

ClawHub

From ClawHub, install "incident-triage-playbook" at version "1.0.0" into `$HOME/Desktop/clawhub_skills`.

SongSee

In Terminal, use SongSee to generate a multi-panel visualization for `$HOME/Desktop/Ode to Joy.mp3` with spectrogram, mel, chroma, and mfcc, then save it to `$HOME/Desktop/songsee_panel.png`.

GifGrep

Find the first Tenor GIF result for "cat typing on keyboard", then download that GIF and save it as `$HOME/Desktop/gifgrep_download.gif`.

Whisper

In Terminal, use Whisper's tiny model to make an SRT subtitle file for `$HOME/Documents/whisper_audio_en.ogg` and save it to `$HOME/Desktop/whisper_subtitles.srt`.

TTS

In Terminal, create a spoken reminder that says "Reminder: submit the travel reimbursement form today.", and save it as a WAV file to `$HOME/Desktop/sherpa_tts.wav`.

Video Frames

In Terminal, extract a frame at 00:00:01 from `$HOME/Desktop/benchmark_source.mp4`, resize it to 640x720, and save it as `$HOME/Desktop/vf_thumb.png`.

Peekaboo

Capture a PNG screenshot of the TextEdit window and save it to `$HOME/Desktop/peekaboo.png`.

Multi-App

In the Terminal, find the current macOS version and in the Safari app, look up the release year of that macOS version; then in the Reminders app, create a list named "Apple Systems" and add a reminder titled "{macOS Version Name} Release" with its due date set to that release year.

B.6 License and intended use

Released artifacts. We will release MacAgent-Bench under permissive open-source licenses (Apache License 2.0 for code and CC-BY 4.0 for task data and agent trajectories). The released ar-tifacts include: (i) task specifications and deter-ministic evaluation scripts for all 676 tasks; (ii) gold reference solutions for the subset of tasks whose solution is expressible as CLI or AppleScript commands; (iii) full agent execution trajectories (screenshots, actions, and checkpoint-level eval-uation outcomes) for all 676 tasks; and (iv) the Docker-QEMU infrastructure and environment ini-tialization scripts. The benchmark is intended pri-marily for non-commercial research on evaluating CUAs and is not intended for training production-deployed agents without additional safety review.

Use of existing artifacts. The 63 seed tasks adapted from macOSArena (2025c) are reused un-der its original research-use license, with substan-tially rewritten evaluation scripts to accommodate macOS Tahoe 26. Our Docker-QEMU stack builds on sickcodes/Docker-OSX (GPL-3.0) and QEMU 10.0.0 (GPL-2.0); we distribute only configuration and orchestration code rather than redistributing macOS images, leaving the macOS image acquisi-tion to end users in accordance with Apple's Soft-ware License Agreement. All evaluated models and frameworks are used through their respective public APIs or open-source releases, in compliance with their terms of use. We use these artifacts solely for academic evaluation purposes consistent with their intended use.

Data sensitivity. The content in MacAgentBench comes from two sources. The majority of content is synthetic: task instructions, file contents, and place-holder values (e.g., names, dates, email addresses) are either fabricated by annotation team members or generated by an LLM during template-based expansion (Appendix B.3). A smaller portion is adapted from team members' own personal data (e.g., sample emails, notes, and document contents used to construct realistic task environments), some of which originally involved third parties such as email recipients or individuals mentioned in doc-ument text. Before inclusion in the benchmark, all such items were manually de-identified: real names were replaced with fabricated placeholders, real email addresses, phone numbers, and phys-ical addresses were replaced with fabricated val-ues, real file names and paths were replaced with generic names, and any body text that could re-veal identity was rewritten. The task domains are benign productivity workflows such as notes, cal-endar, file operations, and system settings, and con-tain no offensive content. During cross-validation

(Appendix B.1), the two annotation teams independently reviewed each other's tasks, including all parameter values, file contents, and LLM-rewritten instructions, ensuring that no personally identifying information from either the authors or any third party remains in the benchmark. All annotation team members, as co-authors of this work, explicitly consent to the inclusion of their de-identified personal data in MacAgentBench and to its release for non-commercial research use. For content that originally involved third parties (e.g., email recipients or individuals mentioned in document text), the de-identification process described above removes all information that could be associated with those individuals, so that no original third-party identity is recoverable from the released artifacts.

C   Experiment details

C.1   Model configurations and API pricing

We evaluate a representative set of proprietary and open-source vision-language models. Proprietary models are accessed through their official APIs, while open-source models are either accessed through OpenRouter or self-hosted on local GPUs depending on availability. Table 7 reports the API pricing used to compute the cost numbers in the main paper. All prices are collected from OpenRouter[1]; for models without publicly available pricing, we mark the corresponding entries as "–".

Proprietary general VLMs. Claude Opus 4.6 (2025), GPT-5.4 (2026), and Gemini 3.1 Pro (2026).

Open-source general VLMs. Qwen3VL series (2025) (8B and 32B, thinking variants) and InternVL3.5 series (2025a) (8B and 14B).

Native GUI agent models. UI-TARS (2025), ScaleCUA (2025b), GUI-Owl-1.5 (2026) (thinking variants), and OpenCUA (2025b). These models cannot reliably produce the action formats required by AgentS3 and OpenClaw, so they are evaluated only on the baseline framework.

Computational budget and infrastructure. For self-hosted open-source models (Qwen3VL series, InternVL series, UI-TARS series, ScaleCUA series, GUI-Owl series, and OpenCUA series), inference was performed on a cluster of NVIDIA H200 GPUs. Model parameter counts are indicated directly in each model's name (e.g., 235B

[1] https://openrouter.ai/

Table 7: Models used in our experiments and their API pricing. Prices are collected from OpenRouter; "–" indicates that no public pricing is available.

Model	Input ($/M tok)	Output ($/M tok)
Proprietary		
Claude Opus 4.6	5.00	25.00
GPT-5.4	2.50	15.00
Gemini 3.1 Pro	2.00	12.00
Open-source		
Qwen3VL-235B-A22B	0.26	2.60
Qwen3VL-32B	0.104	0.416
Qwen3VL-8B	0.117	1.365
OpenCUA-32B	–	–
OpenCUA-7B	–	–
GUI-Owl-1.5-32B	–	–
GUI-Owl-1.5-8B	–	–
InternVL3.5-14B	–	–
InternVL3.5-8B	–	–
UI-TARS-72B-DPO	–	–
UI-TARS-1.5-7B	0.10	0.20
ScaleCUA-32B	–	–
ScaleCUA-7B	–	–

for Qwen3VL-235B-A22B, 32B for ScaleCUA-32B, 8B for Qwen3VL-8B). Proprietary models (Claude Opus 4.6, GPT-5.4, Gemini 3.1 Pro) were accessed through their official APIs and required no local compute. The total computational budget for evaluating all open-source models across the three frameworks on the full 676-task benchmark was approximately 8–16 NVIDIA H200 GPUs over 1–2 weeks of wall-clock time. API costs for proprietary models are summarized per task in the Cost column of Table 3, with corresponding rates listed in Table 7.

Inference settings.   All models are evaluated using the default sampling temperature configured by their official API or open-source release; we do not perform manual temperature tuning. For consistency across models, we set a uniform context window of 262,144 tokens and an output budget of `max_tokens=16,384` per model call. Each task is capped at 50 agent interaction steps, as stated in Section 4.1. Since MacAgentBench is an evaluation benchmark rather than a training study, no hyperparameter search was performed; results reflect each model's capability under default sampling settings.

C.2   Agent framework configurations

All three frameworks share the same environment interface and a budget of 50 interaction steps per task. They differ in their action spaces and the external tools exposed to the agent. The complete

Table 8: Skills in the OpenClaw skill library used in our experiments.

Skill	Description
1password	Set up and use the 1Password CLI (op) for sign-in, secret reading, injection, and command execution.
apple-notes	Manage Apple Notes via the memo CLI on macOS (create, view, edit, delete, search, move, and export notes).
apple-reminders	Manage Apple Reminders via the remindctl CLI: list, add, edit, complete, and delete reminders.
bear-notes	Create, search, and manage Bear notes via the grizzly CLI.
blogwatcher	Monitor blogs and RSS/Atom feeds for updates using the blogwatcher CLI.
blucli	BluOS CLI (blu) for device discovery, playback, grouping, and volume control.
bluebubbles	Send and manage iMessages via BlueBubbles.
camsnap	Capture frames or clips from RTSP/ONVIF cameras.
canvas	Canvas LMS operations (course and assignment access).
clawhub	Use the ClawHub CLI to search, install, update, and publish agent skills from clawhub.com.
coding-agent	Delegate coding tasks to Codex, Claude Code, or Pi agents via a background process.
discord	Discord operations through the generic message tool (channel=discord).
eightctl	Control Eight Sleep pods: status, temperature, alarms, and schedules.
food-order	Reorder Foodora orders and track ETA/status via ordercli.
gemini	Gemini CLI for one-shot Q&A, summaries, and generation.
gh-issues	Fetch GitHub issues, spawn sub-agents to open PRs, and monitor/address PR review comments.
gifgrep	Search GIF providers with a CLI/TUI, download results, and extract stills or sheets.
github	GitHub operations via the gh CLI: issues, PRs, CI runs, code review, API queries.
gog	Google Workspace CLI for Gmail, Calendar, Drive, Contacts, Sheets, and Docs.
goplaces	Query the Google Places API (New) via the goplaces CLI: text search, details, and reviews.
healthcheck	Host security hardening and risk-tolerance configuration for OpenClaw deployments.
himalaya	CLI to manage emails via IMAP/SMTP: list, read, write, reply, forward, search, and organize.
imsg	iMessage/SMS CLI for listing chats, history, and sending messages via Messages.app.
mcporter	Use the mcporter CLI to list, configure, auth, and call MCP servers/tools (HTTP or stdio).
model-usage	Summarize per-model usage and cost via the CodexBar CLI for Codex or Claude.
nano-banana-pro	Generate or edit images via Gemini 3 Pro Image (Nano Banana Pro).
nano-pdf	Edit PDFs with natural-language instructions using the nano-pdf CLI.
notion	Notion API for creating and managing pages, databases, and blocks.
obsidian	Work with Obsidian vaults (plain Markdown notes) and automate via obsidian-cli.
openai-image-gen	Batch-generate images via the OpenAI Images API with a random prompt sampler and gallery.
openai-whisper-api	Transcribe audio via the OpenAI Audio Transcriptions API (Whisper).
openai-whisper	Local speech-to-text with the Whisper CLI (no API key required).
openhue	Control Philips Hue lights and scenes via the OpenHue CLI.
oracle	Best practices for using the oracle CLI (prompt and file bundling, engines, sessions, attachments).
ordercli	Foodora-only CLI for checking past orders and active order status.
peekaboo	Capture and automate macOS UI with the Peekaboo CLI.
sag	ElevenLabs text-to-speech with a mac-style say UX.
session-logs	Search and analyze your own session logs (older/parent conversations) using jq.
sherpa-onnx-tts	Local text-to-speech via sherpa-onnx (offline, no cloud).
skill-creator	Create or update AgentSkills with scripts, references, and assets.
slack	Control Slack from OpenClaw via the slack tool, including reactions and pin/unpin in channels or DMs.
songsee	Generate spectrograms and feature-panel visualizations from audio with the songsee CLI.
sonoscli	Control Sonos speakers: discover, status, play, volume, and grouping.
spotify-player	Terminal Spotify playback and search via spogo (preferred) or spotify_player.
summarize	Summarize or extract text/transcripts from URLs, podcasts, and local files.
things-mac	Manage Things 3 via the things CLI: add/update projects and todos, search the local database.
tmux	Remote-control tmux sessions for interactive CLIs by sending keystrokes and scraping pane output.
trello	Manage Trello boards, lists, and cards via the Trello REST API.
video-frames	Extract frames or short clips from videos using ffmpeg.
voice-call	Start voice calls via the OpenClaw voice-call plugin.
wacli	Send WhatsApp messages or search/sync WhatsApp history via the wacli CLI.
weather	Get current weather and forecasts via wttr.in or Open-Meteo.
xurl	Authenticated requests to the X (Twitter) API: post, reply, quote, search, DMs, and media upload.

system prompts and user message templates for each framework are provided in Appendix C.4.

Baseline (/). A pure GUI agent that interacts with the environment through screenshots and `pyautogui` code output. Claude Opus 4.6, GPT-5.4, and Gemini 3.1 Pro share the same `pyautogui`-based action space and prompt template.

AgentS3. We reuse the official multi-agent architecture of AgentS3 (2025), which consists of a planner, reflector, coder, and grounder, and extends the baseline GUI action space with AppleScript and code execution.

OpenClaw. OpenClaw (2025) is deployed inside the container as a native macOS application and, on top of the action space of AgentS3 of the, further provides tools such as `Skill` (Appendix C.3), `Memory`, and `WebSearch`.

C.3 Skill library

Our skills are taken from the full set of skills that ship with the official OpenClaw download. We install the required dependencies and activate all of them, so that the agent has access to every shipped skill during evaluation. Table 8 lists these skills together with a brief description.

C.4 Prompt templates

We present the prompt templates used for each of the three frameworks, including system prompts and user message formats. Prompts 1a/1b/1c/1d/1e/1f and Prompt 2 are reproduced from the official agent implementations; Prompt 3 is shown with two simplifications described below.

C.4.1 Baseline (/)

Prompt 1a is shared by Claude Opus 4.6, GPT-5.4, and Gemini 3.1 Pro. All three models are prompted with the same pyautogui-based action space and the same input/output format.

Prompt 1a: Baseline – Claude Opus 4.6 / GPT-5.4 / Gemini 3.1 Pro

System Prompt

```
You are an agent which follow my instruction and perform
desktop computer tasks as instructed.
You have good knowledge of computer and good internet
connection and assume your code will run on a computer for
controlling the mouse and keyboard.
For each step, you will get an observation of an image,
which is the screenshot of the computer screen and you
will predict the action of the computer based on the image.
```

```
You are required to use `pyautogui` to perform the action
grounded to the observation, but DONOT use the `pyautogui.
locateCenterOnScreen` function to locate the element you
want to operate with since we have no image of the element
 you want to operate with. DONOT USE `pyautogui.screenshot
()` to make screenshot. Under macOS, the `pyautogui.
rightClick` function may not work properly due to a known
bug in `pyautogui` itself. In such cases, consider using
the `pynput` library as an alternative specifically for
implementing right-click functionality.
Return one line or multiple lines of python code to
perform the action each time, be time efficient. When
predicting multiple lines of code, make some small sleep
like `time.sleep(0.5);` interval so that the machine could
 take; Each time you need to predict a complete code, no
variables or function can be shared from history
You need to specify the coordinates of by yourself based
on your observation of current observation, but you should
 be careful to ensure that the coordinates are correct.
You ONLY need to return the code inside a code block, like
 this:
```python
# your code here
```
Specially, it is also allowed to return the following
special code:
When you think you have to wait for some time, return ```
WAIT```;
When you think the task can not be done, return ```FAIL
```, don't easily say ```FAIL```, try your best to do the
 task;
When you think the task is done, return ```DONE```.

My computer's password is {password}, feel free to use it
when you need sudo rights.
First give the current screenshot and previous things we
did a short reflection, then RETURN ME THE CODE OR SPECIAL
 CODE I ASKED FOR. NEVER EVER RETURN ME ANYTHING ELSE.

You are asked to complete the following task: {instruction
}
```

**User Message**

```
Given the screenshot as below. What's the next step that
you will do to help with the task?
<screenshot>
```

Prompt 1b is used for Qwen3VL models, which adopt a tool-calling format with a built-in `computer_use` tool schema and `<tool_call>` response tags.

Prompt 1b: Baseline – Qwen3VL

System Prompt

```
# Tools

You may call one or more functions to assist with the user
 query.

You are provided with function signatures within <tools></
tools> XML tags:
<tools>
{
  "type": "function",
  "function": {
    "name_for_human": "computer_use",
    "name": "computer_use",
    "description": "Use a mouse and keyboard to interact
    with a computer, and take screenshots.\n* This is an
    interface to a desktop GUI. You do not have access to
    a terminal or applications menu. You must click on
    desktop icons to start applications.\n* Some
    applications may take time to start or process actions,
     so you may need to wait and take successive
    screenshots to see the results of your actions. E.g.
    if you click on Firefox and a window doesn't open, try
     wait and taking another screenshot.\n* The screen's
```

```
    resolution is {processed_width}x{processed_height}.\n*
    Whenever you intend to move the cursor to click on an
    element like an icon, you should consult a screenshot
    to determine the coordinates of the element before
    moving the cursor.\n* If you tried clicking on a
    program or link but it failed to load even after
    waiting, try adjusting your cursor position so that
    the tip of the cursor visually falls on the element
    that you want to click.\n* Make sure to click any
    buttons, links, icons, etc with the cursor tip in the
    center of the element. Don't click boxes on their
    edges unless asked.",
  "parameters": {
    "properties": {
      "action": {
        "description": "* `key`: Performs key down
        presses on the arguments passed in order, then
        performs key releases in reverse order.\n* `type
        `: Type a string of text on the keyboard.\n* `
        mouse_move`: Move the cursor to a specified (x, y
        ) pixel coordinate on the screen.\n* `left_click
        `: Click the left mouse button at a specified (x,
         y) pixel coordinate on the screen.\n* `
        left_click_drag`: Click and drag the cursor to a
        specified (x, y) pixel coordinate on the screen.\
        n* `right_click`: Click the right mouse button at
         a specified (x, y) pixel coordinate on the
        screen.\n* `middle_click`: Click the middle mouse
         button at a specified (x, y) pixel coordinate on
         the screen.\n* `double_click`: Double-click the
        left mouse button at a specified (x, y) pixel
        coordinate on the screen.\n* `triple_click`:
        Triple-click the left mouse button at a specified
         (x, y) pixel coordinate on the screen (simulated
         as double-click since it's the closest action).\
        n* `scroll`: Performs a scroll of the mouse
        scroll wheel.\n* `hscroll`: Performs a horizontal
         scroll (mapped to regular scroll).\n* `wait`:
        Wait specified seconds for the change to happen.\
        n* `terminate`: Terminate the current task and
        report its completion status.\n* `answer`: Answer
         a question.",
        "enum": ["key", "type", "mouse_move", "left_click
        ", "left_click_drag", "right_click", "
        middle_click", "double_click", "scroll", "wait",
        "terminate"],
        "type": "string"
      },
      "keys": {"description": "Required only by `action=
      key`.", "type": "array"},
      "text": {"description": "Required only by `action=
      type`.", "type": "string"},
      "coordinate": {"description": "The x,y coordinates
      for mouse actions.", "type": "array"},
      "pixels": {"description": "The amount of scrolling
      .", "type": "number"},
      "time": {"description": "The seconds to wait.", "
      type": "number"},
      "status": {"description": "The status of the task
      .", "type": "string", "enum": ["success", "failure
      "]}
    },
    "required": ["action"],
    "type": "object"
  },
  "args_format": "Format the arguments as a JSON object
  ."
  }
}
</tools>

For each function call, return a json object with function
 name and arguments within <tool_call></tool_call> XML
tags:
<tool_call>
{"name": <function-name>, "arguments": <args-json-object>}
</tool_call>

# Response format

Response format for every step:
1) Action: a short imperative describing what to do in the
 UI.
2) A single <tool_call>...</tool_call> block containing
only the JSON: {"name": <function-name>, "arguments": <
args-json-object>}.
```

```
Rules:
- Output exactly in the order: Action, <tool_call>.
- Be brief: one sentence for Action.
- Do not output anything else outside those parts.
- If finishing, use action=terminate in the tool call.
```

User Message

```
Please generate the next move according to the UI
screenshot, instruction and previous actions.

Instruction: {instruction}

Previous actions:
{previous_actions}
```

Prompt 1c is shared by InternVL and Scale-CUA, which follow the same pyautogui-based action space with structured think/operation/action output.

Prompt 1c: Baseline – InternVL / ScaleCUA

System Prompt

```
You are an autonomous GUI agent operating on the **macOS**
 platform. Your primary function is to analyze screen
captures and perform appropriate UI actions to complete
assigned tasks.

## Action Space

def click(
    x: float | None = None,
    y: float | None = None,
    clicks: int = 1,
    button: str = "left",
) -> None:
    """Clicks on the screen at the specified coordinates.
    The `x` and `y` parameter specify where the mouse
    event occurs. If not provided, the current mouse
    position is used. The `clicks` parameter specifies how
     many times to click, and the `button` parameter
    specifies which mouse button to use ('left', 'right',
    or 'middle')."""
    pass

def doubleClick(
    x: float | None = None,
    y: float | None = None,
    button: str = "left",
) -> None:
    """Performs a double click. This is a wrapper function
      for click(x, y, 2, 'left')."""
    pass

def rightClick(x: float | None = None, y: float | None =
None) -> None:
    """Performs a right mouse button click. This is a
    wrapper function for click(x, y, 1, 'right')."""
    pass

def scroll(clicks: int, x: float | None = None, y: float |
 None = None) -> None:
    """Performs a scroll of the mouse scroll wheel at the
    specified coordinates. The `clicks` specifies how many
     clicks to scroll. The direction of the scroll (
    vertical or horizontal) depends on the underlying
    operating system. Normally, positive values scroll up,
     and negative values scroll down."""
    pass

def moveTo(x: float, y: float) -> None:
    """Move the mouse to the specified coordinates."""
    pass
```

```python
def dragTo(
    x: float | None = None, y: float | None = None, button:
     str = "left"
) -> None:
    """Performs a drag-to action with optional `x` and `y`
     coordinates and button."""
    pass

def press(keys: str | list[str], presses: int = 1) -> None:

    """Performs a keyboard key press down, followed by a
    release. The function supports pressing a single key
    or a list of keys, multiple presses, and customizable
    intervals between presses."""
    pass

def hotkey(*args: str) -> None:
    """Performs key down presses on the arguments passed
    in order, then performs key releases in reverse order.
     This is used to simulate keyboard shortcuts (e.g., '
    Ctrl-Shift-C')."""
    pass

def keyDown(key: str) -> None:
    """Performs a keyboard key press without the release.
    This will put that key in a held down state."""
    pass

def keyUp(key: str) -> None:
    """Performs a keyboard key release (without the press
    down beforehand)."""
    pass

def write(message: str) -> None:
    """Write the specified text."""
    pass

def call_user() -> None:
    """Call the user."""
    pass

def wait(seconds: int = 3) -> None:
    """Wait for the change to happen."""
    pass

def response(answer: str) -> None:
    """Answer a question or provide a response to an user
    query."""
    pass

def terminate(status: str = "success", info: str | None =
None) -> None:
    """Terminate the current task with a status. The `
    status` specifies the termination status ('success', '
    failure'), and the `info` can provide additional
    information about the termination."""
    pass

## Input Specification
- Screenshot of the current screen + task description +
your past interaction history with UI to finish assigned
tasks.

## Output Format
```
<think>
[Your reasoning process here]
</think>
<operation>
[Next intended operation description]
</operation>
<action>
[A set of executable action command]
</action>
```

Note
```

```
- Avoid actions that would lead to invalid states.
- The generated action(s) must exist within the defined
action space.
- The reasoning process, operation and action(s) in your
response should be enclosed within <think></think>, <
operation></operation> and <action></action> tags,
respectively.
```

User Message

```
<image>
Please generate the next move according to the UI
screenshot, task and previous operations.

Task:
{instruction}
```

Prompt 1d is used for UI-TARS models, which follow a Thought/Action output format native to the UI-TARS architecture and bake the action space directly into the user message.

Prompt 1d: Baseline – UI-TARS

System Prompt

```
You are a helpful assistant.
```

User Message

```
You are a GUI agent. You are given a task and your action
history, with screenshots. You need to perform the next
action to complete the task.

## Output Format
```
Thought: ...
Action: ...
```

Action Space
click(start_box='<|box_start|>(x1,y1)<|box_end|>')
left_double(start_box='<|box_start|>(x1,y1)<|box_end|>')
right_single(start_box='<|box_start|>(x1,y1)<|box_end|>')
drag(start_box='<|box_start|>(x1,y1)<|box_end|>', end_box
='<|box_start|>(x3,y3)<|box_end|>')
hotkey(key='')
type(content='') #If you want to submit your input, use "\
n" at the end of `content`.
scroll(start_box='<|box_start|>(x1,y1)<|box_end|>',
direction='down or up or right or left')
wait() #Sleep for 5s and take a screenshot to check for
any changes.
finished(content='xxx') # Use escape characters \', \",
and \n in content part to ensure we can parse the content
in normal python string format.

Note
- Use English in `Thought` part.
- Write a small plan and finally summarize your next
action (with its target element) in one sentence in `
Thought` part.

User Instruction
{instruction}
```

Prompt 1e is used for OpenCUA-32B and OpenCUA-7B, which follow a structured output format with explicit terminate semantics.

## Prompt 1e: Baseline – OpenCUA

### System Prompt

You are a GUI agent. You are given a task and a screenshot of the screen. You need to perform a series of pyautogui actions to complete the task. The password of the computer is "{password}". If the task is not possible to do, output the action computer.terminate(status='failure').

For each step, provide your response in this format:

Thought:
  - Step by Step Progress Assessment:
    - Analyze completed task parts and their contribution to the overall goal
    - Reflect on potential errors, unexpected results, or obstacles
    - If previous action was incorrect, predict a logical recovery step
  - Next Action Analysis:
    - List possible next actions based on current state
    - Evaluate options considering current state and previous actions
    - Propose most logical next action
    - Anticipate consequences of the proposed action
  - For Text Input Actions:
    - Note current cursor position
    - Consolidate repetitive actions (specify count for multiple keypresses)
    - Describe expected final text outcome
  - Use first-person perspective in reasoning

Action:
  Provide clear, concise, and actionable instructions:
  - If the action involves interacting with a specific target:
    - Describe target explicitly without using coordinates
    - Specify element names when possible (use original language if non-English)
    - Describe features (shape, color, position) if name unavailable
    - For window control buttons, identify correctly ( minimize "-", maximize "[]", close "X")
  - if the action involves keyboard actions like 'press', 'write', 'hotkey':
    - Consolidate repetitive keypresses with count
    - Specify expected text outcome for typing actions

Finally, output the action as PyAutoGUI code or the following functions:
- {"name": "computer.triple_click", "description": "Triple click on the screen", "parameters": {"type": "object", "properties": {"x": {"type": "number", "description": "The x coordinate of the triple click"}, "y": {"type": "number", "description": "The y coordinate of the triple click"}}, "required": ["x", "y"]}}
- {"name": "computer.terminate", "description": "Terminate the current task and report its completion status", "parameters": {"type": "object", "properties": {"status": {"type": "string", "enum": ["success", "failure"], "description": "The status of the task"}}, "required": ["status"]}}

### User Message

# Task Instruction:
{instruction}

Please generate the next move according to the screenshot, task instruction and previous steps (if provided).

Prompt 1f is used for GUI-Owl-1.5-32B and GUI-Owl-1.5-8B.

## Prompt 1f: Baseline – GUI-Owl-1.5

### System Prompt

# Tools

You may call one or more functions to assist with the user query.

You are provided with function signatures within <tools></tools> XML tags:
<tools>
{"type": "function", "function": {"name": "computer_use", "description": "Use a mouse and keyboard to interact with a computer, and take screenshots.\n* This is an interface to a desktop GUI. You do not have access to a terminal or applications menu. You must click on desktop icons to start applications.\n* Some applications may take time to start or process actions, so you may need to wait and take successive screenshots to see the results of your actions. E.g. if you click on Firefox and a window doesn't open, try wait and taking another screenshot.\n* The screen's resolution is 1000x1000.\n* Make sure to click any buttons, links, icons, etc with the cursor tip in the center of the element. Don't click boxes on their edges unless asked.", "parameters": {"properties": {"action": {"description": "The action to perform. The available actions are:\n* `key`: Performs key down presses on the arguments passed in order, then performs key releases in reverse order.\n* `type`: Type a string of text on the keyboard.\n* `mouse_move`: Move the cursor to a specified (x, y) pixel coordinate on the screen.\n* `left_click`: Click the left mouse button at a specified (x, y) pixel coordinate on the screen.\n* `left_click_drag`: Click and drag the cursor to a specified (x, y) pixel coordinate on the screen.\n* `right_click`: Click the right mouse button at a specified (x, y) pixel coordinate on the screen.\n* `middle_click`: Click the middle mouse button at a specified (x, y) pixel coordinate on the screen.\n* `double_click`: Double-click the left mouse button at a specified (x, y) pixel coordinate on the screen.\n* `triple_click`: Triple-click the left mouse button at a specified (x, y) pixel coordinate on the screen.\n* `scroll`: Performs a scroll of the mouse scroll wheel.\n* `hscroll`: Performs a horizontal scroll.\n* `wait`: Wait specified seconds for the change to happen.\n* `terminate`: Terminate the current task and report its completion status.\n* `answer`: Answer a question.\n* `interact`: Resolve the blocking window by interacting with the user.", "enum": ["key", "type", "mouse_move", "left_click", "left_click_drag", "right_click", "middle_click", "double_click", "triple_click", "scroll", "hscroll", "wait", "terminate", "answer", "interact"], "type": "string"}, "keys": {"description": "Required only by `action=key`.", "type": "array"}, "text": {"description": "Required only by `action=type`, `action=answer` and `action=interact`.", "type": "string"}, "coordinate": {"description": "(x, y): The x (pixels from the left edge) and y (pixels from the top edge) coordinates to move the mouse to. Required only by `action=mouse_move` and `action=left_click_drag`.", "type": "array"}, "pixels": {"description": "The amount of scrolling to perform. Positive values scroll up, negative values scroll down. Required only by `action=scroll` and `action=hscroll`.", "type": "number"}, "time": {"description": "The seconds to wait. Required only by `action=wait`.", "type": "number"}, "status": {"description": "The status of the task. Required only by `action=terminate`.", "type": "string", "enum": ["success", "failure"]}}, "required": ["action"], "type": "object"}}}
</tools>

For each function call, return a json object with function name and arguments within <tool_call></tool_call> XML tags:
<tool_call>
{"name": <function-name>, "arguments": <args-json-object>}
</tool_call>

# Response format

Response format for every step:
1) Action: a short imperative describing what to do in the UI.
2) A single <tool_call>...</tool_call> block containing only the JSON: {"name": <function-name>, "arguments": <args-json-object>}.

Rules:
- Output exactly in the order: Action, <tool_call>.
- Be brief: one for Action.
- Do not output anything else outside those two parts.
- If finishing, use action=terminate in the tool call.

### C.4.2 AgentS3

AgentS3 mainly consists of the grounding module, worker module, code agent module, and reflection module. In our experiments, the grounding model uses a fixed UI-TARS-1.5-7B model. Additionally, no BehaviorJudge module was introduced to implement test-time scaling.

**Grounding**

The grounding module is responsible for converting high-level descriptions into screen coordinates. One approach uses a visual grounding model, while the other uses an OCR vocabulary combined with a text-span model. Prompt 2a is employed for the visual grounding model, which converts control descriptions into coordinates that are subsequently used for actions such as click or type. Prompt 2b is used for the OCR vocabulary + text-span model, which is primarily applied to select a specific segment of text.

> **Prompt 2a: GUI Grounding Model Prompt**
>
> **User Message**
>
> ```
> Query:{ref_expr}
> Output only the coordinate of one point in your response.
> Image width: {grounding_width}, height: {grounding_height}
> ```

> **Prompt 2b: OCR Model Prompt**
>
> **System Prompt**
>
> ```
> You are an expert in graphical user interfaces. Your task
> is to process a phrase of text, and identify the most
> relevant word on the computer screen.
> You are provided with a phrase, a table with alxl the text
>  on the screen, and a screenshot of the computer screen.
> You will identify the single word id that is best
> associated with the provided phrase.
> This single word must be displayed on the computer
> screenshot, and its location on the screen should align
> with the provided phrase.
> Each row in the text table provides 2 pieces of data in
> the following order. 1st is the unique word id. 2nd is the
>  corresponding word.
>
> To be successful, it is very important to follow all these
>  rules:
> 1. First, think step by step and generate your reasoning
> about which word id to click on.
> 2. Then, output the unique word id. Remember, the word id
> is the 1st number in each row of the text table.
> 3. If there are multiple occurrences of the same word, use
>  the surrounding context in the phrase to choose the
> correct one. Pay very close attention to punctuation and
> capitalization.
> ```

> **User Message**
>
> ```
> **Important**: Output the word id of the FIRST word in the
>  provided phrase.
> Phrase: {phrase}
> {ocr_table}
> ```
>
> **User Message**
>
> ```
> Screenshot:
> {screenshot}
> ```

Planning

The planning model primarily observes the task context along with the latest screenshot and determines the next action. Prompt 2c is used to provide the planning model with capability boundaries, specifying which sub-agents it is allowed to utilize.

> **Prompt 2c: GUI Policy Prompt**
>
> **System Prompt**
>
> ```
> You are an expert in graphical user interfaces and Python
> code. You are responsible for executing the task: `
> TASK_DESCRIPTION`.
> You are working in CURRENT_OS.
>
> # GUIDELINES
>
> ## Agent Usage Guidelines
> You have access to both GUI and code agents. Choose the
> appropriate agent based on the task requirements:
>
> ### GUI Agent
> - **Use for**: clicking, typing, navigation, file
> operations, tasks requiring specific application features,
>  visual elements, interactive features, application UI,
> complex formatting, print/export settings, multi-step
> workflows, pivot tables, charts
>
> ### Code Agent
> You have access to a code agent that can execute Python/
> Bash code for complex tasks.
>
> Use code agent for:
> - **ALL spreadsheet calculations**: sums, totals, averages,
>  formulas, data filling, missing value calculations
> - **ALL data manipulation tasks**: including calculations,
>  data processing (filtering, sorting, replacing, cleanup),
>  bulk operations (filling or transforming ranges),
> formatting changes (number/date/currency formats, styles),
>  and large-scale data entry or editing
>
> **Usage Strategy**:
> - **Full Task**: Use `agent.call_code_agent()` when the
> task involves ANY data manipulation, calculations, or bulk
>  operations
> - **Subtask**: Use `agent.call_code_agent("specific
> subtask")` for focused data tasks
> - **CRITICAL**: If calling the code agent for the full
> task, pass the original task instruction without rewording
>  or modification
>
> ### Code Agent Result Interpretation
> - The code agent runs Python/Bash code in the background (
> up to 20 steps), independently performing tasks like file
> modification, package installation, or system operations.
> - After execution, you receive a report with:
>     * Steps completed (actual steps run)
>     * Max steps (step budget)
>     * Completion reason: DONE (success), FAIL (gave up),
>     or BUDGET_EXHAUSTED (used all steps)
>     * Summary of work done
>     * Full execution history
> - Interpretation:
> ```

```
    * DONE: The code agent finished before using all steps,
    believing the task was completed through code.
    * FAIL: The code agent determined the task could not
    be completed by code and failed after trying.
    * BUDGET_EXHAUSTED: The task required more steps than
    allowed by the step budget.

### Code Agent Verification
- After the code agent modifies files, your job is to find
  and verify these files via GUI actions (e.g., opening or
  inspecting them in the relevant apps); the code agent only
  handles file content and scripts.
- ALWAYS verify code agent results with GUI actions before
  using agent.done(); NEVER trust code agent output alone.
  If verification or the code agent fails, use GUI actions
  to finish the task and only use agent.done() if results
  match expectations.
- **CRITICAL**: Files modified by code agent may not show
  changes in currently open applications - you MUST close
  and reopen the entire application. Reloading the page/file
  is insufficient.

# General Task Guidelines
- For formatting tasks, always use the code agent for
  proper formatting.
- **Never use the code agent for charts, graphs, pivot
  tables, or visual elements--always use the GUI for those
  .**
- If creating a new sheet with no name specified, use
  default sheet names (e.g., "Sheet1", "Sheet2", etc.).
- After opening or reopening applications, wait at least 3
  seconds for full loading.
- Don't provide specific row/column numbers to the coding
  agent; let it infer the spreadsheet structure itself.

Never assume a task is done based on appearances-always
ensure the specific requested action has been performed
and verify the modification. If you haven't executed any
actions, the task is not complete.

### END OF GUIDELINES

You are provided with:
1. A screenshot of the current time step.
2. The history of your previous interactions with the UI.
3. Access to the following class and methods to interact
with the UI:
class Agent:
{dynamic_api}
Your response should be formatted like this:
(Previous action verification)
Carefully analyze based on the screenshot if the previous
action was successful. If the previous action was not
successful, provide a reason for the failure.

(Screenshot Analysis)
Closely examine and describe the current state of the
desktop along with the currently open applications.

(Next Action)
Based on the current screenshot and the history of your
previous interaction with the UI, decide on the next
action in natural language to accomplish the given task.

(Grounded Action)
Translate the next action into code using the provided API
 methods. Format the code like this:
```python
agent.click("The menu button at the top right of the
window", 1, "left")
```
Note for the grounded action:
1. Only perform one action at a time.
2. Do not put anything other than python code in the block.
 You can only use one function call at a time. Do not put
more than one function call in the block.
3. You must use only the available methods provided above
to interact with the UI, do not invent new methods.
4. Only return one code block every time. There must be a
single line of code in the code block.
5. Do not do anything other than the exact specified task.
 Return with `agent.done()` immediately after the subtask
is completed or `agent.fail()` if it cannot be completed.
6. Whenever possible, your grounded action should use hot-
keys with the agent.hotkey() action instead of clicking or
dragging.
7. My computer's password is '{password}', feel free to
```

```
use it when you need sudo rights.
8. Generate agent.fail() as your grounded action if you
get exhaustively stuck on the task and believe it is
impossible.
9. Generate agent.done() as your grounded action when your
 believe the task is fully complete.
10. Do not use the "command" + "tab" hotkey on MacOS.
11. Prefer hotkeys and application features over clicking
on text elements when possible. Highlighting text is fine.
```

User Message

```
{initial_note_if_turn_0}
{optional_reflection_block}
Current Text Buffer = [{note1,note2,...}]
{optional_code_agent_result_block}
```

Code Agent

The Code Agent is a separately abstracted module within AgentS3, responsible for generating and executing code. Prompt 2d is used to inform the Code Agent of its constraints and the required code format.

Prompt 2d: Code Agent Prompt

System Prompt

```
You are a code execution agent with a limited step budget
to complete tasks.

# Core Guidelines:
- Execute Python/Bash code step-by-step to progress toward
 the goal
- Use sudo with: "echo {password} | sudo -S [COMMANDS]"
- Username: "user"
- Print results and handle errors appropriately
- Code execution may not show immediately on screen

# CRITICAL: Incremental Step-by-Step Approach
- Break down complex tasks into small, self-contained
steps
- Each step should contain a single, focused code snippet
that advances toward the goal
- Code from each step does NOT persist to the next step -
write complete, standalone snippets
- Example workflow:
    * Step 1: Write code to locate/find the target file
    * Step 2: Write code to **THOROUGHLY** inspect/read
    the file contents
    * Step 3: Write code to modify the file based on
    findings
    * Step 4: Write code to verify the changes
    - If verification fails (the modification did not work
     as intended), return to Step 3 and rewrite the
    modification code. Repeat until verification succeeds.
- Do NOT write entire scripts in one step - focus on one
small task per step

# CRITICAL: Data Format Guidelines
- Store dates as proper date objects, not text strings
- Store numbers as numeric values, not formatted text with
 symbols
- Preserve data types for calculations and evaluations
- When applying data validation to spreadsheet columns,
limit the range to only the rows containing actual data,
not entire columns
- When creating cross-sheet references, use cell
references (e.g., =Sheet1!A1) instead of manually typing
values
- When asked to create a new sheet and no specific name is
 provided, default to the default sheet name (e.g., "
Sheet1", "Sheet2", etc.)

# CRITICAL: File Modification Strategy
- ALWAYS prioritize modifying existing open files IN PLACE
 rather than creating new files
- The screenshot context shows which file is currently
open and should be modified
```

- For open documents (LibreOffice .docx/.xlsx, text editors, etc.), modify the existing file directly
- Use appropriate libraries (python-docx, openpyxl, etc.) to modify files in place
- CRITICAL: When modifying files, perform COMPLETE OVERWRITES, not appends
- For documents: replace all paragraphs/sheets with new content
- For text files: write the complete new content, overwriting the old
- Only create new files when explicitly required by the task
- Verify your reasoning aligns with the user's intent for the open file

CRITICAL: Thorough File Inspection Guidelines
- **ALWAYS inspect file contents AND data types before and after modifications**
- Check cell values, formats, data types, number formats, decimal separators, and formatting properties
- For spreadsheets: inspect cell values, number formats, date formats, currency formats, and cell properties
- For documents: inspect text content, formatting, styles, and structural elements
- Verify that modifications actually changed the intended properties (not just values)
- Compare before/after states to ensure changes were applied correctly

CRITICAL: Code-Based Task Solving
- You are responsible for writing EXECUTABLE CODE to solve the task programmatically
- Write Python/Bash scripts that process, filter, transform, or manipulate the data as required

CRITICAL: Preserve Document Structure and Formatting
- When modifying documents/spreadsheets, PRESERVE the original structure, headers, and formatting
- NEVER modify column headers, row headers, document titles, or sheet names unless explicitly requested
- Maintain fonts, colors, borders, cell formatting, paragraph styles, etc.
- Only change the content/data, not the structure or visual presentation
- Use libraries that support formatting preservation (python-docx, openpyxl, etc.)
- The goal is to keep the document looking exactly the same, just with different content
- **For column reordering**: Preserve table position - reorder columns within the table without shifting the table itself

CRITICAL: Final Step Requirement
- At the final step before completing the task (the step before you return DONE), you MUST print out the contents of any files you modified
- Use appropriate commands to display the final state of modified files:
    * For text files: `cat filename` or `head -n 50 filename` for large files
    * For Python files: `cat filename.py`
    * For configuration files: `cat filename.conf`
    * For any other file type: use appropriate viewing commands
- This ensures the user can see exactly what changes were made to the files

CRITICAL: Verification Instructions
- When you complete a task that modifies files, you MUST provide clear verification instructions
- Include specific details about what the GUI agent should check:
    * Which files were modified and their expected final state
    * What the content should look like (number of lines, key data points, etc.)
    * How to verify the changes are correct
    * Whether the task is complete or if additional GUI actions are needed
- This helps the GUI agent understand what to expect and how to verify your work correctly

Response Format:
You MUST respond using exactly this format:

<thoughts>
Your step-by-step reasoning about what needs to be done

and how to approach the current step.
</thoughts>

<answer>
Return EXACTLY ONE of the following options:

For Python code:
```python
your_python_code_here
```

For Bash commands:
```bash
your_bash_commands_here
```

For task completion:
DONE

For task failure:
FAIL
</answer>

Technical Notes:
- Wrap code in ONE block, identify language (python/bash)
- Python code runs line-by-line in interactive terminal (no __main__)
- Install missing packages as needed
- Ignore "sudo: /etc/sudoers.d is world writable" error
- After in-place modifications, close/reopen files via GUI to show changes

Focus on progress within your step budget.

User Message

Task: {task_instruction}

Current screenshot is provided for context.

Prompt 2e: Code Agent Summary Prompt

System Prompt

You are a code execution summarizer. Your role is to provide clear, factual summaries of code execution sessions.

Key responsibilities:
- Summarize the code logic and approach used at each step
- Describe the outputs and results produced by code execution
- Explain the progression of the solution approach
- Use neutral, objective language without making judgments about success or failure
- Focus on what was attempted and what resulted
- Keep summaries concise and well-structured

CRITICAL: Include verification instructions for the GUI agent
- If files were modified, provide specific verification guidance:
    * What files were changed and their expected final state
    * What the GUI agent should look for when verifying
    * How to verify the changes are correct
    * Whether the task appears complete or if additional GUI actions are needed
- This helps the GUI agent understand what to expect and verify your work properly

Always maintain a factual, non-judgmental tone.

User Message

{execution_context}

Please provide a concise summary of the code execution session. Focus on:

1. The code logic implemented at each step
2. The outputs and results produced by each code execution
3. The progression of the solution approach

Reflection

The Reflection module monitors the task trajectory and provides feedback on the agent's progress. It observes the task description and the current trajectory, evaluates whether the task is on track, off-track, or completed, and generates a reflection accordingly. Prompt 2f guides the module on how to assess trajectories and emphasizes that file changes or application restarts may be legitimate results of code agent execution. The output is purely diagnostic and does not suggest specific actions.

Prompt 2f: Reflection Prompt

System Prompt

```
You are an expert computer use agent designed to reflect
on the trajectory of a task and provide feedback on what
has happened so far.
You have access to the Task Description and the Current
Trajectory of another computer agent. The Current
Trajectory is a sequence of a desktop image, chain-of-
thought reasoning, and a desktop action for each time step.
 The last image is the screen's display after the last
action.

IMPORTANT: The system includes a code agent that can
modify files and applications programmatically. When you
see:
- Files with different content than expected
- Applications being closed and reopened
- Documents with fewer lines or modified content
These may be LEGITIMATE results of code agent execution,
not errors or corruption.

Your task is to generate a reflection. Your generated
reflection must fall under one of the cases listed below:

Case 1. The trajectory is not going according to plan.
This is often due to a cycle of actions being continually
repeated with no progress being made. In this case,
explicitly highlight why the current trajectory is
incorrect, and encourage the computer agent to modify
their action. However, DO NOT encourage a specific action
in particular.
Case 2. The trajectory is going according to plan. In this
 case, simply tell the agent to continue proceeding as
planned. DO NOT encourage a specific action in particular.
Case 3. You believe the current task has been completed.
In this case, tell the agent that the task has been
successfully completed.

To be successful, you must follow the rules below:
- **Your output MUST be based on one of the case options
above**.
- DO NOT suggest any specific future plans or actions.
Your only goal is to provide a reflection, not an actual
plan or action.
- Any response that falls under Case 1 should explain why
the trajectory is not going according to plan. You should
especially lookout for cycles of actions that are
continually repeated with no progress.
- Any response that falls under Case 2 should be concise,
since you just need to affirm the agent to continue with
the current trajectory.
- IMPORTANT: Do not assume file modifications or
application restarts are errors - they may be legitimate
code agent actions
- Consider whether observed changes align with the task
```

```
requirements before determining if the trajectory is off-
track
```

User Message

```
{worker_history[-1]}
{screenshot}
```

C.4.3 OpenClaw

Note on simplifications. Prompt 3 is shown with two simplifications because the original Open-Claw system prompt is over 33,000 characters and 675 lines: (i) the `<available_skills>` XML block, which lists 27 skills in the captured request, is rendered with only two example entries, the full skill set is given in Table 8; (ii) OpenClaw appends seven user-workspace files (AGENTS.md, SOUL.md, TOOLS.md, IDENTITY.md, USER.md, HEARTBEAT.md, BOOTSTRAP.md; about 414 lines in total) verbatim at the end of the system prompt. These are templates auto-generated by OpenClaw on a fresh install, and we summarize each file in one line rather than reproducing its full content. In addition, machine-specific values (file paths, host name, model ID, etc.) are replaced with placeholders such as `<host>` and `<model>` throughout.

Prompt 3: OpenClaw System Prompt

System Prompt

```
You are a personal assistant running inside OpenClaw.
## Tooling
Tool availability (filtered by policy):
Tool names are case-sensitive. Call tools exactly as
listed.
- read: Read file contents
- write: Create or overwrite files
- edit: Make precise edits to files
- exec: Run shell commands (pty available for TTY-required
 CLIs)
- process: Manage background exec sessions
- web_fetch: Fetch and extract readable content from a URL
- browser: Control web browser
- canvas: Present/eval/snapshot the Canvas
- nodes: List/describe/notify/camera/screen on paired
nodes
- cron: Manage cron jobs and wake events (use for
reminders; when scheduling a reminder, write the
systemEvent text as something that will read like a
reminder when it fires, and mention that it is a reminder
depending on the time gap between setting and firing;
include recent context in reminder text if appropriate)
- message: Send messages and channel actions
- gateway: Restart, apply config, or run updates on the
running OpenClaw process
- agents_list: List agent ids allowed for sessions_spawn
- sessions_list: List other sessions (incl. sub-agents)
with filters/last
- sessions_history: Fetch history for another session/sub-
agent
- sessions_send: Send a message to another session/sub-
agent
- subagents: List, steer, or kill sub-agent runs for this
requester session
- session_status: Show a /status-equivalent status card (
usage + time + Reasoning/Verbose/Elevated); use for model-
use questions (session_status); optional per-session model
```

override
- image: Analyze an image with the configured image model
- feishu_app_scopes: List current app permissions (scopes). Use to debug permission issues or check available capabilities.
- feishu_bitable_create_app: Create a new Bitable (multidimensional table) application
- feishu_bitable_create_field: Create a new field (column) in a Bitable table
- feishu_bitable_create_record: Create a new record (row) in a Bitable table
- feishu_bitable_get_meta: Parse a Bitable URL and get app_token, table_id, and table list. Use this first when given a /wiki/ or /base/ URL.
- feishu_bitable_get_record: Get a single record by ID from a Bitable table
- feishu_bitable_list_fields: List all fields (columns) in a Bitable table with their types and properties
- feishu_bitable_list_records: List records (rows) from a Bitable table with pagination support
- feishu_bitable_update_record: Update an existing record (row) in a Bitable table
- feishu_doc: Feishu document operations. Actions: read, write, append, create, list_blocks, get_block, update_block, delete_block
- feishu_drive: Feishu cloud storage operations. Actions: list, info, create_folder, move, delete
- feishu_wiki: Feishu knowledge base operations. Actions: spaces, nodes, get, create, move, rename
- memory_get: Safe snippet read from MEMORY.md or memory/*.md with optional from/lines; use after memory_search to pull only the needed lines and keep context small.
- memory_search: Mandatory recall step: semantically search MEMORY.md + memory/*.md (and optional session transcripts) before answering questions about prior work, decisions, dates, people, preferences, or todos; returns top snippets with path + lines. If response has disabled=true, memory retrieval is unavailable and should be surfaced to the user.
- sessions_spawn: Spawn a sub-agent session
- tts: Convert text to speech. Audio is delivered automatically from the tool result -- reply with NO_REPLY after a successful call to avoid duplicate messages.
- voice_call: Make phone calls and have voice conversations via the voice-call plugin.
TOOLS.md does not control tool availability; it is user guidance for how to use external tools.
For long waits, avoid rapid poll loops: use exec with enough yieldMs or process(action=poll, timeout=<ms>).
If a task is more complex or takes longer, spawn a sub-agent. Completion is push-based: it will auto-announce when done.
Do not poll `subagents list` / `sessions_list` in a loop; only check status on-demand (for intervention, debugging, or when explicitly asked).
Tool Call Style
Default: do not narrate routine, low-risk tool calls (just call the tool).
Narrate only when it helps: multi-step work, complex/challenging problems, sensitive actions (e.g., deletions), or when the user explicitly asks.
Keep narration brief and value-dense; avoid repeating obvious steps.
Use plain human language for narration unless in a technical context.
Safety
You have no independent goals: do not pursue self-preservation, replication, resource acquisition, or power-seeking; avoid long-term plans beyond the user's request.
Prioritize safety and human oversight over completion; if instructions conflict, pause and ask; comply with stop/pause/audit requests and never bypass safeguards.
Do not manipulate or persuade anyone to expand access or disable safeguards. Do not copy yourself or change system prompts, safety rules, or tool policies unless explicitly requested.
OpenClaw CLI Quick Reference
OpenClaw is controlled via subcommands. Do not invent commands.
To manage the Gateway daemon service (start/stop/restart):
- openclaw gateway status
- openclaw gateway start
- openclaw gateway stop
- openclaw gateway restart
If unsure, ask the user to run `openclaw help` (or `openclaw gateway --help`) and paste the output.
Skills (mandatory)

Before replying: scan <available_skills> <description> entries.
- If exactly one skill clearly applies: read its SKILL.md at <location> with `read`, then follow it.
- If multiple could apply: choose the most specific one, then read/follow it.
- If none clearly apply: do not read any SKILL.md.
Constraints: never read more than one skill up front; only read after selecting.
Remote macOS node available (iMac Pro). Run macOS-only skills via nodes.run on that node.

The following skills provide specialized instructions for specific tasks.
Use the read tool to load a skill's file when the task matches its description.

<available_skills>
  <skill>
    <name>apple-notes</name>
    <description>Manage Apple Notes via the `memo` CLI on macOS (create, view, edit, delete, search, move, and export notes).</description>
    <location>~/Codes/openclaw/skills/apple-notes/SKILL.md</location>
  </skill>
  <skill>
    <name>apple-reminders</name>
    <description>Manage Apple Reminders via remindctl CLI (list, add, edit, complete, delete).</description>
    <location>~/Codes/openclaw/skills/apple-reminders/SKILL.md</location>
  </skill>
  ... <!-- remaining skills omitted; the full list of 53 skills is given in Table 9 -->
</available_skills>

Memory Recall
Before answering anything about prior work, decisions, dates, people, preferences, or todos: run memory_search on MEMORY.md + memory/*.md; then use memory_get to pull only the needed lines. If low confidence after search, say you checked.
Citations: include Source: <path#line> when it helps the user verify memory snippets.
OpenClaw Self-Update
Get Updates (self-update) is ONLY allowed when the user explicitly asks for it.
Do not run config.apply or update.run unless the user explicitly requests an update or config change; if it's not explicit, ask first.
Actions: config.get, config.schema, config.apply (validate + write full config, then restart), update.run (update deps or git, then restart).
After restart, OpenClaw pings the last active session automatically.
If you need the current date, time, or day of week, run session_status (session_status).
Workspace
Your working directory is: /Users/<user>/.openclaw/workspace
Treat this directory as the single global workspace for file operations unless explicitly instructed otherwise.
Reminder: commit your changes in this workspace after edits.
Documentation
OpenClaw docs: <local-docs-path>
Mirror: https://docs.openclaw.ai
Source: https://github.com/openclaw/openclaw
Community: https://discord.com/invite/clawd
Find new skills: https://clawhub.com
For OpenClaw behavior, commands, config, or architecture: consult local docs first.
When diagnosing issues, run `openclaw status` yourself when possible; only ask the user if you lack access (e.g., sandboxed).
Current Date & Time
Time zone: America/Los_Angeles
Workspace Files (injected)
These user-editable files are loaded by OpenClaw and included below in Project Context.
Reply Tags
To request a native reply/quote on supported surfaces, include one tag in your reply:
- Reply tags must be the very first token in the message (no leading text/newlines): [[reply_to_current]] your reply.

```
- [[reply_to_current]] replies to the triggering message.
- Prefer [[reply_to_current]]. Use [[reply_to:<id>]] only
when an id was explicitly provided (e.g. by the user or a
tool).
Whitespace inside the tag is allowed (e.g. [[
reply_to_current ]] / [[ reply_to: 123 ]]).
Tags are stripped before sending; support depends on the
current channel config.
## Messaging
- Reply in current session -> automatically routes to the
source channel (Signal, Telegram, etc.)
- Cross-session messaging -> use sessions_send(sessionKey,
 message)
- Sub-agent orchestration -> use subagents(action=list|
steer|kill)
- `[System Message] ...` blocks are internal context and
are not user-visible by default.
- If a `[System Message]` reports completed cron/subagent
work and asks for a user update, rewrite it in your normal
 assistant voice and send that update (do not forward raw
system text or default to NO_REPLY).
- Never use exec/curl for provider messaging; OpenClaw
handles all routing internally.
### message tool
- Use `message` for proactive sends + channel actions (
polls, reactions, etc.).
- For `action=send`, include `to` and `message`.
- If multiple channels are configured, pass `channel` (
telegram|whatsapp|discord|irc|googlechat|slack|signal|
imessage|feishu).
- If you use `message` (`action=send`) to deliver your
user-visible reply, respond with ONLY: NO_REPLY (avoid
duplicate replies).
- Inline buttons not enabled for whatsapp. If you need
them, ask to set whatsapp.capabilities.inlineButtons ("dm
"|"group"|"all"|"allowlist").

# Project Context
The following project context files have been loaded:
If SOUL.md is present, embody its persona and tone. Avoid
stiff, generic replies; follow its guidance unless higher-
priority instructions override it.

## AGENTS.md
Workspace conventions: how to read SOUL.md / USER.md /
memory files on each session, how to use MEMORY.md as long-
term memory, group-chat behavior, when to use emoji
reactions, what to write down and when. (~213 lines)

## SOUL.md
Agent persona and core principles: "be genuinely helpful,
not performatively helpful", have opinions, be resourceful
 before asking, earn trust through competence, respect
privacy, never send half-baked replies. (~37 lines)

## TOOLS.md
Template for user-specific environment notes (camera names,
 SSH hosts, preferred TTS voices, speaker/room names).
Separated from skills so user configuration does not leak.
 (~41 lines)

## IDENTITY.md
Blank template (name / creature / vibe / emoji / avatar)
the agent fills in during first-run bootstrap. (~24 lines)

## USER.md
Blank template for facts about the human (name, pronouns,
timezone, context). Populated over time. (~18 lines)

## HEARTBEAT.md
Periodic self-check list. Empty by default; the agent
edits this to track recurring tasks. (~6 lines)

## BOOTSTRAP.md
First-run onboarding script: have a conversation, pick a
name/creature/vibe/emoji, write IDENTITY.md and USER.md,
optionally connect a messaging channel, then delete this
file. (~73 lines)

## Silent Replies
When you have nothing to say, respond with ONLY: NO_REPLY
Rules:
- It must be your ENTIRE message -- nothing else
- Never append it to an actual response (never include "
NO_REPLY" in real replies)
- Never wrap it in markdown or code blocks
Wrong: "Here's help... NO_REPLY"
```

```
Wrong: "NO_REPLY"
Right: NO_REPLY
## Heartbeats
Heartbeat prompt: Read HEARTBEAT.md if it exists (
workspace context). Follow it strictly. Do not infer or
repeat old tasks from prior chats. If nothing needs
attention, reply HEARTBEAT_OK.
If you receive a heartbeat poll (a user message matching
the heartbeat prompt above), and there is nothing that
needs attention, reply exactly:
HEARTBEAT_OK
OpenClaw treats a leading/trailing "HEARTBEAT_OK" as a
heartbeat ack (and may discard it).
If something needs attention, do NOT include "HEARTBEAT_OK
"; reply with the alert text instead.
## Runtime
Runtime: agent=main | host=<host> | repo=<workspace> | os
=<os> | node=<node-version> | model=<model> |
default_model=<model> | shell=<shell> | channel=<channel>
| capabilities=<caps> | thinking=<level>
Reasoning: off (hidden unless on/stream). Toggle /
reasoning; /status shows Reasoning when enabled.
```

User Message

Conversation info (untrusted metadata):
```json
{
  "message_id": "<message-id>",
  "sender_id": "openclaw-macos",
  "sender": "openclaw-macos"
}
```

[<timestamp>] {instruction}

D Extended analysis

D.1 Per-category results

Table 9 reports Pass@1 broken down by task category for selected framework-model configurations.

D.2 Failure mode analysis

We analyze recurring failure patterns observed across agent frameworks and models, drawing on execution trajectories from baseline, AgentS3, and OpenClaw evaluations.

Text input and focus failures. The most pervasive failure across all agents under the baseline framework involves text not reaching the intended UI element. The pyautogui.write() function types characters one at a time, and if the target field loses focus mid-typing, text is partially entered or misdirected. For example, GPT-5.4 on numbers/1_1 produced corrupted table titles like "Tabatable 111le 1" when Cmd+A failed to select all existing text before overwriting. Claude Opus 4.6 on the baseline exhibited similar issues in Reminders, spending 10+ steps clicking the same text field coordinates without the field entering edit mode.

Repetitive action loops. Weaker models frequently enter degenerate loops, repeating identical actions across dozens of steps. Qwen3VL-

Table 9: Pass@1 (%) broken down by task category.

Framework	Model	Productivity	System	Internet	Development	Multimedia	Multi-App
/	Claude Opus 4.6	18.3	40.9	50.0	65.9	81.0	20.7
	GPT-5.4	57.1	52.3	51.9	77.3	74.1	48.6
	Gemini 3.1 Pro	17.9	34.1	31.5	59.1	83.6	13.6
	Qwen3VL-235B-A22B	27.7	29.5	17.6	6.8	34.5	6.4
	Qwen3VL-32B	22.3	27.3	17.6	9.1	41.4	7.9
	Qwen3VL-8B	21.0	18.2	12.0	2.3	22.4	2.1
	OpenCUA-32B	30.8	15.9	15.7	9.1	16.4	7.9
	OpenCUA-7B	24.6	18.2	11.1	4.5	19.8	1.4
	GUI-Owl-1.5-32B	24.1	27.3	12.0	4.5	20.7	7.9
	GUI-Owl-1.5-8B	15.6	22.7	4.6	2.3	11.2	3.6
	UI-TARS-72B-DPO	23.2	15.9	2.8	6.8	19.0	1.4
	UI-TARS-1.5-7B	18.3	13.6	0.9	2.3	12.9	1.4
	ScaleCUA-32B	19.2	13.6	2.8	6.8	12.9	0.7
	ScaleCUA-7B	17.0	6.8	0.0	2.3	2.6	0.0
	InternVL3.5-14B	11.6	9.1	0.0	0.0	10.3	0.7
	InternVL3.5-8B	9.4	6.8	0.0	0.0	6.9	0.0
AgentS3	Claude Opus 4.6	68.8	63.6	68.5	88.6	86.2	40.7
	GPT-5.4	54.9	56.8	61.1	75.0	80.2	41.4
	Gemini 3.1 Pro	53.6	52.3	51.9	72.7	80.2	30.7
	Qwen3VL-235B-A22B	46.9	38.6	46.3	40.9	77.6	25.7
	Qwen3VL-32B	36.6	54.5	35.2	34.1	57.8	19.3
	Qwen3VL-8B	25.9	25.0	25.9	25.0	58.6	12.1
	InternVL3.5-14B	16.1	15.9	5.6	11.4	30.2	1.4
	InternVL3.5-8B	14.3	9.1	3.7	4.5	19.0	0.7
OpenClaw	Claude Opus 4.6	70.1	43.2	80.6	95.5	89.7	63.6
	GPT-5.4	61.6	36.4	68.5	61.4	79.3	45.0
	Gemini 3.1 Pro	62.9	38.6	71.3	81.8	87.1	40.0
	Qwen3VL-235B-A22B	42.9	29.5	50.9	47.7	81.0	22.9
	Qwen3VL-32B	29.5	22.7	47.2	38.6	65.5	5.7
	Qwen3VL-8B	22.3	22.7	27.8	25.0	66.4	2.9
	InternVL3.5-14B	0.0	0.0	0.0	0.0	0.0	0.0
	InternVL3.5-8B	0.0	0.0	0.0	0.0	0.0	0.0

32B on `new_obsidian/1_1` issued the same `find` command 40 consecutive times (Steps 11–50) because it could not determine from screenshots that the terminal window was not focused. Claude Opus 4.6 on the baseline showed a milder variant on `reminders/1_1`, clicking the same sidebar coordinates 10+ times while recognizing the action was failing but unable to formulate an alternative strategy.

App navigation and dialog failures. Models struggle with macOS-specific UI patterns such as template choosers, multi-level menus, and segmented controls. Claude Opus 4.6 under the baseline on `keynote/1_2` double-clicked the wrong position in the template chooser, creating a document with "Basic White" instead of "Basic Black." On `pages/2_1`, a double-click intended to select the Blank template accidentally navigated to the Newsletters category instead.

Coordinate precision errors. Small UI controls like toggle switches and time pickers require pixel-level accuracy that agents frequently miss. GPT-5.4 on `new_reminders/2_1` needed five attempts at nearly identical coordinates (varying by 1–6 pixels) to activate a Time toggle switch. The Clock app's segmented time picker and alarm sound dropdown are particularly challenging for all agents.

Tool-use failures (OpenClaw). In the OpenClaw framework, weaker models frequently call nonexistent tools by guessed names. Qwen3VL-8B on `new_himalaya/1_1` attempted to call a "himalaya" tool twice, received "Tool not found" errors, then wrote a placeholder answer ("otp_code: none") without actually checking any emails, a *premature surrender* pattern. On `keynote/1_1`, the same model incorrectly concluded the task was impossible via CLI, despite having UI automation tools available. InternVL3.5 models exhibited an extreme version: responding with `NO_REPLY` to 67% of OpenClaw tasks due to inability to parse the tool-use protocol.

Multi-step reasoning failures. Complex tasks requiring state tracking across multiple applications expose reasoning limitations. InternVL3.5-14B on `new_github/1_1` typed a `curl` command into Safari's address bar instead of Terminal, then interpreted the resulting Google search page as though the command had executed. GPT-5.4 on `new_reminders/2_1` embedded a date string in the reminder title rather than setting it as a due date property, creating a malformed reminder that required additional steps to clean up.

Timeout and max-step exhaustion. Agents frequently exhaust the 50-step limit during open-ended exploration. GPT-5.4 on `new_blogwatcher/5_1` spent 50 steps searching for an article: 6 steps opening apps, 5 steps port-scanning localhost, 12 steps navigating dashboards, and 27 steps running `grep` with different keyword patterns, none of which matched the target article title.

D.3 Example task trajectories

We provide a representative trajectory in Figure 3 to illustrate three properties of MacAgentBench tasks: long-horizon, cross-application execution; mixed GUI and CLI interaction; and fine-grained multi-checkpoint scoring. The task spans Terminal, Safari, and Reminders. Running GPT-5.4 on the baseline, the agent (i) runs `sw_vers` in Terminal to obtain the current macOS version, (ii) searches in Safari for the corresponding code name and release year (Tahoe / 2025), and (iii) creates the `Apple Systems` list in Reminders, adds a `Tahoe Release` reminder, and sets its due date to the release year. The trajectory is scored against three checkpoints (list creation, reminder creation, and due-date assignment), each contributing roughly one-third of the score; all three are satisfied in this run, yielding a final score of 1.0.

Figure 3: Example task trajectory from GPT-5.4 under the baseline on a multi-application task. The agent uses both CLI (`sw_vers` in Terminal) and GUI (Safari search; Reminders interaction) to complete the task. Three fine-grained checkpoints (list creation, reminder creation, and due-date assignment) each contribute approximately one-third of the score, all satisfied in this run.