Learning Energy-Based Models in High-Dimensional Spaces with Multi-scale denoising score matching

Abstract

Energy-Based Models (EBMs) output unnormalized log-probability values given data samples. Such an estimation is essential in a variety of applications such as sample generation, denoising, sample restoration, outlier detection, Bayesian reasoning, and many more. However, standard maximum likelihood training is computationally expensive due to the requirement of sampling the model distribution. Score matching potentially alleviates this problem, and denoising score matching (Vincent, 2011) is a particularly convenient version. However, previous works do not produce models capable of high quality sample synthesis in high dimensional datasets from random initialization. We believe that is because the score is only matched over a single noise scale, which corresponds to a small set in high-dimensional space. To overcome this limitation, here we instead learn an energy function using denoising score matching over all noise scales. When sampled from random initialization using Annealed Langevin Dynamics and single step denoising jump, our model produced high-quality samples comparable to state-of-the-art techniques such as GANs. The learned model also provide density information and set a new sample quality baseline in energy-based models. We further demonstrate that the proposed method generalizes well with an image inpainting task.

1 Introduction and Motivation

Treating data as stochastic samples from a probability distribution and developing models that can learn such distributions is at the core for solving a large variety of application problems, such as error correction/denoising (Vincent et al., 2010), outlier/novelty detection (Zhai et al., 2016; Choi and Jang, 2018), invariant pattern recognition, Bayesian reasoning (Welling and Teh, 2011) which relies on good data priors, and many others.

Energy-Based Models (EBMs) (LeCun et al., 2006; Ngiam et al., 2011) assign an energy $E(\boldsymbol{x})$ to each data point $\boldsymbol{x}$ which implicitly defines a probability by the Boltzmann distribution $p_m(\boldsymbol{x}) = e^{-E(\boldsymbol{x})}/Z$. Sampling from this distribution can be used as a generative process that yield plausible samples of $\boldsymbol{x}$. Compared to other generative models, like GANs (Goodfellow et al., 2014), flow-based models (Dinh et al., 2015; Kingma and Dhariwal, 2018), or auto-regressive models (van den Oord et al., 2016; Ostrovski et al., 2018), energy-based models have significant advantages. First, they provide explicit (unnormalized) density information, compositionality (Hinton, 1999; Haarnoja et al., 2017), better mode coverage (Kumar et al., 2019) and flexibility (Du and Mordatch, 2019). Secondly, they do not require special model architecture, unlike auto-regressive and flow-based models. Recently, Energy-based models has been successfully trained with maximum likelihood (Nijkamp et al., 2019; Du and Mordatch, 2019), but training can be very computationally demanding due to the need of sampling model distribution. Variants with a truncated sampling procedure have been proposed, such as contrastive divergence (Hinton, 2002). Such models learn much faster with the draw back of not exploring the state space thoroughly (Tieleman, 2008).

1.1 SCORE MATCHING, DENOISING SCORE MATCHING AND DEEP ENERGY ESTIMATOR

Score matching (SM) (Hyvärinen, 2005) circumvents the requirement of sampling the model distribution. In score matching, the score function is defined to be the gradient of log-density or the negative energy function. The expected $L2$ norm of difference between the model score function and the data score function are minimized. One convenient way of using score matching is learning the energy function corresponding to a Gaussian kernel Parzen density estimator (Parzen, 1962) of the data: $p_{\sigma_0}(\tilde{\boldsymbol{x}}) = \int q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})dx$. Though hard to evaluate, the data score is well defined: $s_d(\tilde{\boldsymbol{x}}) = \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}}))$. And the corresponding objective is:

$$L_{SM}(\theta) = \mathbb{E}_{p_{\sigma_0}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2 \tag{1}$$

Vincent (2011) studied the connection between denoising auto-encoder and score matching, and proved a remarkable result that the following objective, named *Denoising Score Matching* (DSM), is equivalent to the objective above:

$$L_{DSM}(\theta) = \mathbb{E}_{p_{\sigma_0}(\tilde{\boldsymbol{x}}, \boldsymbol{x})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2 \tag{2}$$

Note that the Parzen density score is replaced by the derivative of log density of the single noise kernel $\nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}))$, which is much easier to evaluate. In the particular case of Gaussian noise $\log(q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) = -\frac{(\tilde{\boldsymbol{x}} - \boldsymbol{x}_i)^2}{2\sigma_0^2} + C$ and:

$$L_{DSM}(\theta) = \mathbb{E}_{p_{\sigma 0}(\tilde{\boldsymbol{x}}, \boldsymbol{x})} \parallel \boldsymbol{x}_i - \tilde{\boldsymbol{x}}_i + {\sigma_0}^2 \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}_i; \theta) \parallel^2 \tag{3}$$

This objective (3) forces the energy gradient to align with the vector pointing from the noisy sample to the clean data sample, therefore it is named *Denoising score matching*. To optimize such an objective involving derivative of a function defined by a neural network, double backpropagation (Drucker and Le Cun, 1991) is needed, e.g. in (Kingma and LeCun, 2010). *Deep energy estimator networks* (Saremi et al., 2018) first applied the same technique to learn an energy function defined by a deep neural network. While learning the Parzen kernel density estimator under small noise was only proposed to analyze denoising autoencoder, Saremi et al. (2018) learned an energy-based model to match a Parzen estimator with a particular noise magnitude. Later, Song and Ermon (2019) learned a series of score estimators, each matching the score of a Parzen estimator with a different noise magnitude.

In this work, we combine some of the key ideas from Saremi et al. (2018); Saremi and Hyvarinen (2019); Song and Ermon (2019) and aim to learn an energy-based model using denoising score matching with multiple noise magnitudes. In Section 2, we first provide a geometric view to illustrate the training process of denoising score matching in high dimensional space, analyze its potential issues, and to motivate our own approach. Then we formulate *Multiscale Denoising Score Matching* (MDSM), which is followed by a series of empirical results.

2 A GEOMETRIC VIEW

In Saremi and Hyvarinen (2019), author arrived at Equation 2 using a different theory based on Empirical Bayes estimator in the case of Gaussian noise. In the same paper the behavior of noise corrupted distribution was analyzed in high-dimensional case using measure concentration results. Here we develop upon this picture to further understand denoise score matching learning process.

We adopt the common assumption that the data distribution to be learned is high-dimensional, but only has support around a relatively low-dimensional manifold (Tenenbaum et al., 2000; Roweis and Saul, 2000; Lawrence, 2005). This causes a problem that density, or the gradient of the density for data distribution is not defined outside the manifold, making it difficult to train a valid density model for the data distribution defined on the entire space. In Saremi and Hyvarinen (2019) and Song and Ermon (2019), authors analyzed this problem and motivated smoothing the data distribution with Gaussian kernel to alleviate this issue.

To understand the learning process in relation to the data manifold $\mathcal{X}$, we recall two elementary properties of random Gaussian vectors in high-dimensional spaces: First, the length distribution of

Figure 1: Illustration of anneal denoising score matching. A. During training, derivative of log-likelihood is forced to point toward data manifold, establishing energy difference between points within manifold and points outside. Note that energy is negative log-likelihood therefore energy is higher for point further away from data manifold. B. During annealed Langevin sampling, sample travel from outside data manifold to data manifold. Shown are singled step denoised sample during sampling of an energy function trained with MDSM on Fashion-MNIST (see text for details).

random vectors becomes concentrated at $\sqrt{d}\sigma$ (Vershynin, 2018), where σ^2 is the variance of a single dimension. Second, a random vector is always close to orthogonal to a fixed vector (Tao, 2012). With these premises one can visualize the configuration of noisy and noiseless data points used in the learning of denoising score matching: A data point $\boldsymbol{x}$ sampled from $\mathcal{X}$ and its noisy version $\tilde{\boldsymbol{x}}$ always lie on a line which is almost perpendicular to the tangent space $T_{\boldsymbol{x}}\mathcal{X}$ and intersects $\mathcal{X}$ at $\boldsymbol{x}$. Further, the distance vectors between $(\boldsymbol{x}, \tilde{\boldsymbol{x}})$ pairs all have similar length $\sqrt{d}\sigma$. As a consequence, the set of noisy data points concentrate on a set $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$ that has a distance with $(\sqrt{d}\sigma - \epsilon, \sqrt{d}\sigma + \epsilon)$ from the data manifold $\mathcal{X}$, where $\epsilon \ll \sqrt{d}\sigma$.

All told, performing denoising score matching learning with $(\boldsymbol{x}, \tilde{\boldsymbol{x}})$ pairs generated with a fixed noise level σ, which is the approach taken previously except in Song and Ermon (2019), will match the score on the set $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$ and enable denoising of noisy points in $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$. However, the learning provides little information about the density outside this set, farther or closer to the data manifold, as noisy samples outside $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$ rarely appear in the training process. An illustration is presented in Figure 1A. Denoting the complement of the set $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$ as $\tilde{\mathcal{X}}^C_{\sqrt{d}\sigma,\epsilon}$, though $p_{\sigma_0}(\tilde{\boldsymbol{x}} \in \tilde{\mathcal{X}}^C_{\sqrt{d}\sigma,\epsilon})$ is very small in high-dimensional space, the score in $\tilde{\mathcal{X}}^C_{\sqrt{d}\sigma,\epsilon}$ still plays a critical role in sampling from random noise. This may explain the difficulty previous models based on denoising score matching with single noise scale encountered when sampled with noise initialization. We demonstrate this experiment in Appendix B with multiple single noise magnitudes. This phenomenon in high-dimensional space is not sufficiently appreciated by the classical score matching objective, where the expectation almost confines score estimation to $\tilde{\mathcal{X}}_{\sqrt{d}\sigma,\epsilon}$. To remedy this problem, we propose modifying the expectation in score matching objective to a distribution consist of mixture of Gaussian noise scales which will sample the ambient space more evenly, avoiding issue caused by measure concentration, see Section 3.1 and Appendix A for more detailed discussions. Song and Ermon (2019) also used multiple noise scales in denoise score-matching, but they did not motivate this choice in the context of high-dimensional geometry, and a low dimensional picture would suggest that a single noise scale large enough to cover entire space would be sufficient.

Another property of denoising score matching was observed in the denoising auto-encoder literature (Vincent et al., 2010; Karklin and Simoncelli, 2011) that with higher noise level the learned representation tend to have larger spatial scale. An plausible explanation is that a lot of natural signals have multi-scale structure with $1/f$ power characteristic, meaning that features at low spatial frequencies have larger signal power than features at high spacial frequencies (Field, 1987). Thus, a higher noise levels will wash away features above certain spacial frequencies, but insufficiently corrupting features below certain spacial frequencies to drive learning. Thus, a model trained with only one noise level will only learn structures roughly of a single scale.

To illustrate this point, in Figure 1B we show some examples of intermediate samples during annealed sampling process. Displayed are samples obtained by single step denoising from the noisy

sample carrying different levels of noise. One can see that as the sample point approach the data manifold, more and more details are present in the denoised sample. We provide more result from this and similar experiment in Figure 3 and Figure E.1.

The analysis above suggest that it is not sufficient to learn energy-based model with denoising score matching using a single noise scale, at least if high-quality sample synthesis is part of the goal for the learning. To achieve this while maintaining the speed advantage of score matching, we propose *multiscale denoising score matching* (MDSM), a denoising score matching procedure using multiple noise levels. We expect this sampling-free learning method to shape an energy function that can drive samples anywhere in the state space towards high probability regions of the data. For sampling from the learned model, we propose *annealed Langevin dynamics* and additionally use single step denoise jump. We show that our model generates high-quality samples similar in quality to the-state-of-the-art image generation techniques, such as GANs (Goodfellow et al., 2014), as well as providing density information.

3 LEARNING ENERGY-BASED MODEL WITH MULTISCALE DENOISING SCORE MATCHING

3.1 MULTISCALE DENOISING SCORE MATCHING

Motivated by the geometric view, we strive to learn an energy function corresponding to the Parzen density estimator of the data $p_{\sigma_0}(\tilde{\boldsymbol{x}}) = \int q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})dx$ by minimizing the difference between derivative of the energy function with the score of p_{σ_0} under the expectation $\mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})}$ rather than $\mathbb{E}_{p_{\sigma_0}(\tilde{\boldsymbol{x}})}$, where $p_{\sigma'}(\tilde{\boldsymbol{x}}) = \int q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})dx$ covers the signal space better than $p_{\sigma_0}(\tilde{\boldsymbol{x}})$. This new expectation avoids the measure concentration issue and leads to the following *Multiscale Score Matching* (MSM) objective:

$$L_{MSM}(\theta) = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 \tag{4}$$

Note that the only thing has changed in Equation 4 is the expectation compared to Equation 1. In the asymptotic case, they are consistent if $p_{\sigma'}(\tilde{\boldsymbol{x}})$ and $p_{\sigma_0}(\tilde{\boldsymbol{x}})$ have the same support. We show this formally in Proposition 1 of Appendix A. In Proposition 2, we prove that Equation 4 is equivalent to the following denoising score matching objective:

$$L_{MDSM^*} = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 \tag{5}$$

The above results apply to any noise kernel $q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$, but Equation 5 has a reversed expectation form that is not easy to work with. To proceed, we consider the case $q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$ is Gaussian in which we can choose the distribution $q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$ to be a Gaussian scale mixture: $q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) = \int q_{\sigma}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\sigma)d\sigma$ and $q_{\sigma}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) = \mathcal{N}(\boldsymbol{x}, \sigma^2 I_d)$. After some manipulation and approximation (See analysis following Proposition 2 in Appendix A), we can change Equation 5 into a more convenient form, which we call *Multiscale Denoising Score Matching* (MDSM):

$$L_{MDSM} = \mathbb{E}_{p(\sigma)q_{\sigma}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 \tag{6}$$

The the square loss term evaluated at noisy points $\tilde{\boldsymbol{x}}$ at larger distances from true data points $\boldsymbol{x}$ will have larger magnitude. Therefore, in practice we add an extra monotonic decreasing term $l(\sigma)$ to balance different noise scales, e.g. $l(\sigma) = \frac{1}{\sigma^2}$. Ideally we want our model to learn the correct gradient everywhere so we need to add noise of all levels, but applying denoising score matching to very large or very small noise is rather pointless. For very large noise the original sample's information is completely lost. Conversely, in the limit of small noise, the noisy sample is virtually indistinguishable from real data. In neither case can one expect to learn an informative gradient. Thus, the noise range needs only be chosen broad enough to encourage learning of data features over all scales. Particularly, we do not sample σ but instead choose a series of fixed σ values in a range. We also substitute $\log(q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) = -\frac{(\tilde{\boldsymbol{x}}-\boldsymbol{x}_i)^2}{2\sigma_0^2} + C$ into Equation 6 and arrive the the final objective:

$$L(\theta) = \mathbb{E}_{p(\sigma)q_\sigma(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})} l(\sigma) \parallel \boldsymbol{x}_i - \tilde{\boldsymbol{x}}_i + \sigma_0^2 \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}_i; \theta) \parallel^2 \tag{7}$$

On the surface, this objective looks similar to the one in Song and Ermon (2019), but the important difference is that we match the score to a *single* distribution, while Song and Ermon (2019) learns the score of *multiple* distributions. Our model also does not require noise magnitude as input since there's only one target distribution $p_{\sigma_0}(\tilde{\boldsymbol{x}})$ to be learned.

3.2 SAMPLING BY ANNEALED LANGEVIN DYNAMICS AND JUMP

In Saremi and Hyvarinen (2019), the energy function corresponding to Parzen density estimator of a single noise scale is sampled by Langevin dynamics, and clean sample can be obtained using single step denoise jump. We extend this approach to sample from our learned energy function with annealed Langevin dynamics, as our energy function is trained over all noise levels. Additionally we use the same single step denoise jump.

Simulated annealing (Kirkpatrick et al., 1983; Neal, 2001) has been successfully applied to challenging computational problems, such as combinatorial optimization. In essence, the mode exploration in an objective function can be improved by sampling first at high temperature and then cooling down gradually. Langevin dynamics has been applied to sampling from neural network energy functions (Du and Mordatch, 2019; Nijkamp et al., 2019). However, they reported difficulty with mode exploration or the need for very large number of sampling steps. To improve mode exploration even with small numbers of sampling steps, we propose Annealed Langevin dynamics. In this sampling process the temperature parameter in the Langevin dynamics is adjusted from high to low according to an annealing schedule.

In the model of a physical particle undergoing Brownian motion, temperature in its Langevin equation enters as a $\sqrt{T}$ factor in front of the noise term, some literature use β^{-1} where $\beta = 1/T$ (Jordan et al., 1998). Adopting the $\sqrt{T}$ convention yields the following sampling process:

$$\boldsymbol{x}_{t+1} = \boldsymbol{x}_t - \frac{\epsilon^2}{2} \nabla_{\boldsymbol{x}} E(\boldsymbol{x}_t; \theta) + \epsilon \sqrt{T_t} \mathcal{N}(0, I_d) \tag{8}$$

where T_t follows some annealing schedule, and ϵ denotes step length, which is fixed. In the NCSN model (Song and Ermon, 2019), author also proposed annealed Langevin dynamics, which is best interpreted as sequentially sampling a series of different distributions. Our formulation differs as our algorithm samples the same energy function at different temperatures, and correspond exactly to the form of damped Langevin dynamics in physics and statistics literature. During sampling, samples behave very much like physical particles under Brownian motion in a potential field. Because the particles have average energies close to the their current thermic energy, they explore the state space at different distances from data manifold depending on temperature. Eventually, they settle somewhere on the data manifold. The behavior of the particle's energy value during a typical annealing process is depicted in Appendix Figure F.1B. If the obtained sample is still noisy, we can make a single step gradient denoise jump to improve sample quality:

$$\boldsymbol{x}_{clean} = \boldsymbol{x}_{noisy} - \sigma_0^2 \nabla_{\boldsymbol{x}} E(\boldsymbol{x}_{noisy}; \theta) \tag{9}$$

This denoising procedure can be applied to noisy sample with any level of Gaussian noise because in our model the gradient automatically has the right magnitude to denoise the sample. This process is also justified by the Empirical Bayes interpretation of this denoising process, as studied in Saremi and Hyvarinen (2019).

4 IMAGE MODELING RESULTS

Training and Sampling Details. The proposed energy-based model is trained on standard image datasets, namely MNIST, Fashion MNIST, CelebA (Liu et al., 2015) and CIFAR-10 (Krizhevsky et al., 2009). During training we set $\sigma_0 = 0.1$ and train over a noise range of $\sigma \in [0.05, 1.2]$, with the different noise uniformly spaced on the batch dimension, for MNIST and Fashion MNIST we used geometrically distributed noise in the range $[0.1, 3]$. $l(\sigma)$ is set to $1/(\sigma^2)$ at all times to make the square term roughly independent of σ. We fix batch size at 128 and use the Adam optimizer with

Figure 2: Samples from our model trained on Fashion MNIST, CelebA and CIFAR-10. See Figure E.3 and Figure E.4 in Appendix for more samples and comparison with training data.

a learning rate of 5×10^{-5}. For MNIST and Fashion MNIST, we use a 12-Layer ResNet with 64 filters, for the CelebA and CIFAT-10 data sets we used a 18-Layer ResNet with 128 filters (He et al., 2016; Zagoruyko and Komodakis, 2016). No normalization layer was used in any of the networks. We designed the output layer of all networks to take a generalized quadratic form (Fan et al., 2018), because the energy function is anticipated to be approximately quadratic with respect to the noise level, we found this modification to boost the performance significantly. For more detail on training and model architecture, see Appendix D. One notable result is that since our training method does not involve sampling, we achieved a speed up of roughly an order of magnitude compared to the common maximum-likelihood training [1]. Our method thus enables the training of energy-based models even when limited computational resources prohibit maximum likelihood methods.

We found that the choice of the maximum noise level has little effect on learning as long as it is large enough to encourage learning of the longest range features in the data. However, as expected, learning with too small or too large noise levels is not beneficial and can even destabilize the training process. Further, our method appeared to be relatively insensitive to how the noise levels are distributed over a chosen range. Geometrically spaced noise as in (Song and Ermon, 2019) and linearly spaced noise both work, although in our case learning with linearly spaced noise was somewhat more robust.

For sampling the learned energy function we used annealed Langevin dynamics with an empirically optimized annealing schedule,see Figure F.1 B for the particular shape of annealing schedule we used. In contrast, annealing schedules with theoretical guaranteed convergence property takes extremely long (Geman and Geman, 1984). Range of temperatures to use in the sampling process depends on ones choice of σ_0, as the equilibrium distribution is roughly images with Gaussian noise of magnitude $\sqrt{T}\sigma_0$ added on top. To ease traveling between modes far apart and ensure even sampling, the initial temperature need to be high enough to inject noise of sufficient magnitude. In our case $T = 100$, which correspond to added noise of magnitude $\sqrt{100} * 0.1 = 1$ seems to be sufficient starting point. For step length ϵ we generally used 0.02, although any value within the range $[0.015, 0.05]$ seemed to work fine. After annealing process we perform a single step denoising jump to further enhance sample quality.

Unconditional Image Generation. We demonstrate the generative ability of our model by displaying samples obtained by annealed Langevin sampling and single step denoise jump. We evaluated 50k sampled images after training on CIFAR-10 with two performance scores, Inception (Salimans et al., 2016) and FID (Heusel et al., 2017). We achieved Inception Score of 8.31 and FID of 31.7, comparable to modern GAN approaches. Scores for CelebA dataset are not reported here as they are not commonly reported and may depend on the specific pre-processing used. More samples and training images are provided in Appendix for visual inspection. We believe that visual assessment is still essential because of issues with the Inception score (Barratt and Sharma, 2018). Indeed, we also found that the visually impressive samples was not the one achieving the highest Inception Score.

---

[1]For example, on a single GPU, training MNIST with 12-layer Resnet takes ~0.3s per batch with our method, while maximum likelihood training with a modest 30 Langevin step per weight update takes 3s per batch.

[2]Author reported difficulties evaluating Likelihood

[3]Upper Bound obtained by Reverse AIS

Table 1: Unconditional Inception score, FID scores and Likelihoods for CIFAR-10

Model	IS	FID	Likelihood	NNL (bits/dim)
iResNet (Behrmann et al., 2019)	-	65.01	Yes	3.45
PixelCNN (van den Oord et al., 2016)	4.60	65.93	Yes	**3.14**
PixelIQN (Ostrovski et al., 2018)	5.29	49.46	Yes	-
Residual Flow (Chen et al., 2019)	-	46.37	Yes	3.28
GLOW (Kingma and Dhariwal, 2018)	-	46.90	Yes	3.35
EBM (ensemble) (Du and Mordatch, 2019)	6.78	38.2	Yes(density)	- [2]
SNGAN (Miyato et al., 2018)	8.22	**21.7**	No	-
MDSM(Ours)	8.31	31.7	Yes(density)	-0.96 [3]
NCSN (Song and Ermon, 2019)	**8.91**	25.32	No	-

Although overfitting is not a common concern for generative models, we still tested our model for overfitting. We found no indication for overfitting by comparing model samples with their nearest neighbors in the data set, see Figure C.1 in Appendix.

Mode Coverage. We repeated with our model the 3 channel MNIST mode coverage experiment similar to the one in Kumar et al. (2019). An energy-based model was trained on 3-channel data where each channel is a random MNIST digit. Then 8000 samples were taken from the model and each channel is classified using a small MNIST classifier network. We obtained results of the 966 modes, comparable to GAN approaches. Training was successful and our model assigned low energy to all the learned modes, but some modes were not accessed during sampling, likely due to the Langevin Dynamics failing to explore these modes. A better sampling technique such as HMC Neal et al. (2011) or a Maximum Entropy Generator (Kumar et al., 2019) could improve this result.

Image Inpainting. Image impainting can be achieved with our model by clamping part of the image to ground truth and performing the same annealed Langevin and Jump sampling procedure on the missing part of the image. Noise appropriate to the sampling temperature need to be added to the clamped inputs. The quality of inpainting results of our model trained on CelebA and CIFAR-10 can be assessed in Figure 3. For CIFAR inpainting we used test set,

Figure 3: Demonstration of the sampling process (left), and image inpainting (right). The sampling process is shown with Gaussian noise (top left), and denoised by single step gradient jump (lower left). The column next to sampling process shows samples after the last denoising jump at the end of sampling. Inpainting results are shown next to initial image (left column) and the ground truth image (right column).

Log likelihood estimation. For energy-based models the log density can be obtained after estimating the partition function with Annealed Importance Sampling (AIS) (Salakhutdinov and Murray, 2008) or Reverse AIS (Burda et al., 2015). In our experiment on CIFAR-10 model, similar to report

in Du and Mordatch (2019), there's still a substantial gap between AIS and Reverse AIS estimation after very substantial computational effort. In Table 1, We report result from Reverse AIS as it tends to over-estimate the partition function thus underestimate the density. Note that although density values and likelihood values are not directly comparable, we list them together due to the sheer lack of density model on CIFAR-10.

We also report density of 1.21 bits/dim on MNIST dataset, and we refer readers to Du and Mordatch (2019) for comparison to other models on this dataset. More details on this experiment is provided in the Appendix.

Outlier Detection. Choi and Jang (2018) and Nalisnick et al. (2019) have reported intriguing behavior of high dimensional density models on out of distribution samples. Specifically, they showed that a lot of models assign higher likelihood to out of distribution samples than real data samples. We investigated whether our model behaves similarly.

Our energy function is only trained outside the data manifold where samples are noisy, so the energy value at clean data points may not always be well behaved. Therefore, we added noise with magnitude σ_0 before measuring the energy value. We report that our network behaves similarly to previous likelihood models that it assigns lower energy, thus higher density, to some OOD samples. We show one example of this phenomenon in Appendix Figure F.1A.

We also attempted to use the denoise performance, or the objective function to perform outlier detection. Intriguingly, it also behaves similarly as using energy value, as denoise performance seems to correlate more with the variance of original image rather than the content of the image.

5 DISCUSSION

Our approach is conceptually similar to the idea of combining denoising autoencoder and annealing (Geras and Sutton, 2015; Chandra and Sharma, 2014; Zhang and Zhang, 2018) though they were proposed in the context of pre-training neural networks for classification applications. Previous efforts of learning energy-based models with score matching (Kingma and LeCun, 2010; Song et al., 2019) were either computationally intensive or unable to produce high-quality samples comparable to those obtained by other generative models such as GANs. Saremi et al. (2018) and Saremi and Hyvarinen (2019) trained energy-based model with denoising score matching objective but the resulting models cannot perform sample synthesis from random noise initializations.

We provide analysis and empirical results both suggesting that the limitation of previous denoising score matching models is due to the objective doesn't sufficiently appreciate low-density regions. To remedy this issue we proposed a learning procedure using a wide range of different noise scales, which we named *Multiscale Denoising Score Matching*. Models learned with MDSM is capable of denoising, producing high-quality samples from random noise, and performing image inpainting. They achieve those while providing density information, being an order of magnitude faster over maximum likelihood method during training, and admitting a more efficient annealed Langevin sampling procedure.

Our approach is perhaps most closely related to the NCSN model (Song and Ermon, 2019), a network that is also trained by denoising score matching with Gaussian noise corruption of different scales. This model essentially learns $p_\sigma(\tilde{\boldsymbol{x}})$ for a series of σ values. Our method instead learn the energy function correspond to $p_{\sigma_0}(\tilde{\boldsymbol{x}})$ for one specific σ_0 value. Our model provide density information and is able to perform single step denoising because it doesn't require noise magnitude input like the NCSN model. In conclusion, our model provides an unique combination of density information with high-quality sample generation.

REFERENCES

Shane Barratt and Rishi Sharma. A note on the inception score. *arXiv preprint arXiv:1801.01973*, 2018.

Jens Behrmann, Will Grathwohl, Ricky T. Q. Chen, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, pages 573–582, 2019.

Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Accurate and conservative estimates of mrf log-likelihood using reverse annealing. In *Artificial Intelligence and Statistics*, pages 102–110, 2015.

B Chandra and Rajesh Kumar Sharma. Adaptive noise schedule for denoising autoencoder. In *International conference on neural information processing*, pages 535–542. Springer, 2014.

Ricky TQ Chen, Jens Behrmann, David Duvenaud, and Jörn-Henrik Jacobsen. Residual flows for invertible generative modeling. *arXiv preprint arXiv:1906.02735*, 2019.

Hyunsun Choi and Eric Jang. Generative ensembles for robust anomaly detection. *arXiv preprint arXiv:1810.01392*, 2018.

Laurent Dinh, David Krueger, and Yoshua Bengio. NICE: non-linear independent components estimation. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Workshop Track Proceedings*, 2015.

Harris Drucker and Yann Le Cun. Double backpropagation increasing generalization performance. In *IJCNN-91-Seattle International Joint Conference on Neural Networks*, volume 2, pages 145–150. IEEE, 1991.

Yilun Du and Igor Mordatch. Implicit generation and generalization in energy-based models. *arXiv preprint arXiv:1903.08689*, 2019.

Fenglei Fan, Wenxiang Cong, and Ge Wang. A new type of neurons for machine learning. *International journal for numerical methods in biomedical engineering*, 34(2):e2920, 2018.

David J. Field. Relations between the statistics of natural images and the response properties of cortical cells. *J. Opt. Soc. Am. A*, 4(12):2379–2394, Dec 1987.

Stuart Geman and Donald Geman. Stochastic relaxation, gibbs distributions, and the bayesian restoration of images. *IEEE Transactions on pattern analysis and machine intelligence*, (6): 721–741, 1984.

Krzysztof J. Geras and Charles A. Sutton. Scheduled denoising autoencoders. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 1352–1361. JMLR. org, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, pages 6626–6637, 2017.

Geoffrey E Hinton. Products of experts. 1999.

Geoffrey E Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 14(8):1771–1800, 2002.

Aapo Hyvärinen. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6(Apr):695–709, 2005.

Richard Jordan, David Kinderlehrer, and Felix Otto. The variational formulation of the fokker–planck equation. *SIAM journal on mathematical analysis*, 29(1):1–17, 1998.

Yan Karklin and Eero P Simoncelli. Efficient coding of natural images with a population of noisy linear-nonlinear neurons. In *Advances in neural information processing systems*, pages 999–1007, 2011.

Diederik P. Kingma and Yann LeCun. Regularized estimation of image statistics by score matching. In *Advances in Neural Information Processing Systems 23: 24th Annual Conference on Neural Information Processing Systems 2010. Proceedings of a meeting held 6-9 December 2010, Vancouver, British Columbia, Canada.*, pages 1126–1134, 2010.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in Neural Information Processing Systems*, pages 10215–10224, 2018.

Scott Kirkpatrick, C Daniel Gelatt, and Mario P Vecchi. Optimization by simulated annealing. *science*, 220(4598):671–680, 1983.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Rithesh Kumar, Anirudh Goyal, Aaron Courville, and Yoshua Bengio. Maximum entropy generators for energy-based models. *arXiv preprint arXiv:1901.08508*, 2019.

Neil Lawrence. Probabilistic non-linear principal component analysis with gaussian process latent variable models. *Journal of machine learning research*, 6(Nov):1783–1816, 2005.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pages 3730–3738, 2015.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018.

Eric T. Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Görür, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019.

Radford M Neal. Annealed importance sampling. *Statistics and computing*, 11(2):125–139, 2001.

Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of markov chain monte carlo*, 2(11):2, 2011.

Jiquan Ngiam, Zhenghao Chen, Pang W Koh, and Andrew Y Ng. Learning deep energy models. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 1105–1112, 2011.

Erik Nijkamp, Mitch Hill, Tian Han, Song-Chun Zhu, and Ying Nian Wu. On the anatomy of mcmc-based maximum likelihood learning of energy-based models. *arXiv preprint arXiv:1903.12370*, 2019.

Georg Ostrovski, Will Dabney, and Rémi Munos. Autoregressive quantile networks for generative modeling. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, pages 3933–3942, 2018.

Emanuel Parzen. On estimation of a probability density function and mode. *The Annals of Mathematical Statistics*, 33(3):1065–1076, 1962.

Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500):2323–2326, 2000.

Stuart J Russell and Peter Norvig. *Artificial intelligence: a modern approach*. Malaysia; Pearson Education Limited,, 2016.

Ruslan Salakhutdinov and Iain Murray. On the quantitative analysis of deep belief networks. In *Proceedings of the 25th international conference on Machine learning*, pages 872–879. ACM, 2008.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *Advances in neural information processing systems*, pages 2234–2242, 2016.

Saeed Saremi and Aapo Hyvarinen. Neural empirical bayes. *arXiv preprint arXiv:1903.02334*, 2019.

Saeed Saremi, Arash Mehrjou, Bernhard Schölkopf, and Aapo Hyvärinen. Deep energy estimator networks. *arXiv preprint arXiv:1805.08306*, 2018.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *arXiv preprint arXiv:1907.05600*, 2019.

Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. Sliced score matching: A scalable approach to density and score estimation. In *Proceedings of the Thirty-Fifth Conference on Uncertainty in Artificial Intelligence, UAI 2019, Tel Aviv, Israel, July 22-25, 2019*, page 204, 2019.

Terence Tao. *Topics in random matrix theory*, volume 132. American Mathematical Soc., 2012.

Joshua B Tenenbaum, Vin De Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500):2319–2323, 2000.

Tijmen Tieleman. Training restricted boltzmann machines using approximations to the likelihood gradient. In *Proceedings of the 25th international conference on Machine learning*, pages 1064–1071. ACM, 2008.

Aäron van den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, pages 1747–1756, 2016.

Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge University Press, 2018.

Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural computation*, 23(7):1661–1674, 2011.

Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, and Pierre-Antoine Manzagol. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *Journal of machine learning research*, 11(Dec):3371–3408, 2010.

Martin J Wainwright and Eero P Simoncelli. Scale mixtures of gaussians and the statistics of natural images. In *Advances in neural information processing systems*, pages 855–861, 2000.

Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 681–688, 2011.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Shuangfei Zhai, Yu Cheng, Weining Lu, and Zhongfei Zhang. Deep structured energy based models for anomaly detection. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, pages 1100–1109, 2016.

Qianjun Zhang and Lei Zhang. Convolutional adaptive denoising autoencoders for hierarchical feature extraction. *Frontiers of Computer Science*, 12(6):1140–1148, 2018.

A MDSM OBJECTIVE

In this section, we provide a formal discussion of the MDSM objective and suggest it as an improved score matching formulation in high-dimensional space.

Vincent (2011) illustrated the connection between the model score $-\nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta)$ with the score of Parzen window density estimator $\nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}}))$. Specifically, the objective is Equation 1 which we restate here:

$$L_{SM}(\theta) = \mathbb{E}_{p_{\sigma 0}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2 \tag{10}$$

Our key observation is: in high-dimensional space, due the concentration of measure, the expectation w.r.t. $p_{\sigma 0}(\tilde{\boldsymbol{x}})$ over weighs a thin shell at roughly distance $\sqrt{d}\sigma$ to the empirical distribution $p(x)$. Though in theory this is not a problem, in practice this leads to results that the score are only well matched on this shell. Based on this observation, we suggest to replace the expectation w.r.t. $p_{\sigma 0}(\tilde{\boldsymbol{x}})$ with a distribution $p_{\sigma'}(\tilde{\boldsymbol{x}})$ that has the same support as $p_{\sigma 0}(\tilde{\boldsymbol{x}})$ but can avoid the measure concentration problem. We call this *multiscale score matching* and the objective is the following:

$$L_{MSM}(\theta) = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2 \tag{11}$$

Proposition 1. $L_{MSM}(\theta) = 0 \iff L_{SM}(\theta) = 0 \iff \theta = \theta^*$.

Given that $p_{\sigma'}(\tilde{\boldsymbol{x}})$ and $p_{\sigma 0}(\tilde{\boldsymbol{x}})$ has the same support, it's clear that $L_{MSM} = 0$ would be equivalent to $L_{SM} = 0$. Due to the proof of the Theorem 2 in Hyvärinen (2005), we have $L_{SM}(\theta) \iff \theta = \theta^*$. Thus, $L_{MSM}(\theta) = 0 \iff \theta = \theta^*$.

$\square$

Proposition 2. $L_{MSM}(\theta) \smile L_{MDSM^*} = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma 0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2$.

We follow the same procedure as in Vincent (2011) to prove this result.

$$J_{MSM}(\theta) = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})) + \nabla_{\tilde{x}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2$$
$$= \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{x}} E(\tilde{\boldsymbol{x}}; \theta) \parallel^2 + 2S(\theta) + C$$

$$S(\theta) = \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \langle \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle$$
$$= \int_{\tilde{\boldsymbol{x}}} p_{\sigma'}(\tilde{\boldsymbol{x}}) \langle \nabla_{\tilde{\boldsymbol{x}}} \log(p_{\sigma_0}(\tilde{\boldsymbol{x}})), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} p_{\sigma'}(\tilde{\boldsymbol{x}}) \langle \frac{\nabla_{\tilde{\boldsymbol{x}}} p_{\sigma_0}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})}, \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} \langle \nabla_{\tilde{\boldsymbol{x}}} p_{\sigma_0}(\tilde{\boldsymbol{x}}), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} \langle \nabla_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} p(\boldsymbol{x}) q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) d\boldsymbol{x}, \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} \langle \int_{\boldsymbol{x}} p(\boldsymbol{x}) \nabla_{\tilde{\boldsymbol{x}}} q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) d\boldsymbol{x}, \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} \langle \int_{\boldsymbol{x}} p(\boldsymbol{x}) q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) \nabla_{\tilde{\boldsymbol{x}}} \log q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) d\boldsymbol{x}, \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}}$$
$$= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} p(\boldsymbol{x}) q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}) \langle \nabla_{\tilde{\boldsymbol{x}}} \log q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}} d\boldsymbol{x}$$
$$= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} \frac{p_{\sigma'}(\tilde{\boldsymbol{x}})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})} p_{\sigma_0}(\tilde{\boldsymbol{x}}, \boldsymbol{x}) \langle \nabla_{\tilde{\boldsymbol{x}}} \log q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}} d\boldsymbol{x}$$
$$= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} p_{\sigma'}(\tilde{\boldsymbol{x}}) q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}}) \langle \nabla_{\tilde{\boldsymbol{x}}} \log q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}}; \theta) \rangle \, d\tilde{\boldsymbol{x}} d\boldsymbol{x}$$

Thus we have:

$$
\begin{aligned}
L_{MSM}(\theta) &= \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 + 2S(\theta) + C \\
&= \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 + 2\mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}\langle \nabla_{\tilde{\boldsymbol{x}}} \log q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x}), \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta)\rangle + C \\
&= \mathbb{E}_{p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma 0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 + C'
\end{aligned}
$$

So $L_{MSM}(\theta) \smile L_{MDSM^*}$.

$\square$

The above analysis applies to any noise distribution, not limited to Gaussian. but L_{MDSM^*} has a reversed expectation form that is not easy to work with. To proceed further we study the case where $q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$ is Gaussian and choose $q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$ as a Gaussian scale mixture (Wainwright and Simoncelli, 2000) and $p_{\sigma'}(\tilde{\boldsymbol{x}}) = \int q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x})dx$. By Proposition 1 and Proposition 2, we have the following form to optimize:

$$
\begin{aligned}
L_{MDSM^*}(\theta) &= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}}) \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 d\tilde{\boldsymbol{x}} d\boldsymbol{x} \\
&= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} \frac{q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}{q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} p_{\sigma'}(\tilde{\boldsymbol{x}})q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}}) \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 d\tilde{\boldsymbol{x}} d\boldsymbol{x} \\
&= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} \frac{q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}{q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} p_{\sigma'}(\boldsymbol{x}, \tilde{\boldsymbol{x}}) \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 d\tilde{\boldsymbol{x}} d\boldsymbol{x} \\
&= \int_{\tilde{\boldsymbol{x}}} \int_{\boldsymbol{x}} \frac{q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}{q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}})} q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})p(\boldsymbol{x}) \parallel \nabla_{\tilde{\boldsymbol{x}}} \log(q_{\sigma 0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})) + \nabla_{\tilde{\boldsymbol{x}}} E(\tilde{\boldsymbol{x}};\theta) \parallel^2 d\tilde{\boldsymbol{x}} d\boldsymbol{x} \quad (*) \\
&\approx L_{MDSM}(\theta)
\end{aligned}
$$

To minimize Equation (*), we can use the following importance sampling procedure (Russell and Norvig, 2016): we can sample from the empirical distribution $p(\boldsymbol{x})$, then sample the Gaussian scale mixture $q_{\sigma'}(\tilde{\boldsymbol{x}}|\boldsymbol{x})$ and finally weight the sample by $\frac{q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}{q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}})}$. We expect the ratio to be close to 1 for the following reasons: Using Bayes rule, $q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}}) = \frac{p(\boldsymbol{x})q_{\sigma_0}(\tilde{\boldsymbol{x}}|\boldsymbol{x})}{p_{\sigma_0}(\tilde{\boldsymbol{x}})}$ we can see that $q_{\sigma_0}(\boldsymbol{x}|\tilde{\boldsymbol{x}})$ only has support on discret data points $\boldsymbol{x}$, same thing holds for $q_{\sigma'}(\boldsymbol{x}|\tilde{\boldsymbol{x}})$. because in $\tilde{\boldsymbol{x}}$ is generated by adding Gaussian noise to real data sample, both estimators should give results highly concentrated on the original sample point $\boldsymbol{x}$. Therefore, in practice, we ignore the weighting factor and use Equation **??**. Improving upon this approximation is left for future work.

B   PROBLEM WITH SINGLE NOISE DENOISING SCORE MATCHING

To compare with previous method, we trained energy-based model with denoising score matching using one noise level on MNIST, initialized the sampling with Gaussian noise of the same level, and sampled with Langevin dynamics at $T = 1$ for 1000 steps and perform one denoise jump to recover the model's best estimate of the clean sample, see Figure B.1. We used the same 12-layer ResNet as other MNIST experiments. Models were trained for 100000 steps before sampling.

C   OVERFITTING TEST

We demonstrate that the model does not simply memorize training examples by comparing model samples with their nearest neighbors in the training set. We use Fashion MNIST for this demonstration because overfitting can occur there easier than on more complicated datasets, see Figure C.1.

D   DETAILS ON TRAINING AND SAMPLING

We used a custom designed ResNet architecture for all experiments. For MNIST and Fashion-MNIST we used a 12-layer ResNet with 64 filters on first layer, while for CelebA and CIFAR dataset

Figure B.1: Denoised samples from energy-based model trained with denoising score matching with single magnitude Gaussian noise on MNIST. Noise magnitude used in training is shown above samples.

Figure C.1: Samples from energy-based model trained on Fashion MNIST (Left column) next to 10 (L2) nearest neighbors in the training set.

we used a 18-layer ResNet with 128 filters on the first layer. All network used the ELU activation function. We did not use any normalization in the ResBlocks and the filer number is doubled at each downsampling block. Details about the structure of our networks used can be found in our code release Here. All mentioned models can be trained on 2 GPUs within 2 days.

Since the gradient of our energy model scales linearly with the noise, we expected our energy function to scale quadratically with noise magnitude. Therefore, we modified the standard energy-based network output layer to take a flexible quadratic form (Fan et al., 2018):

$$E_{out} = (\sum_i a_i h_i + b_1)(\sum_i c_i h_i + b_2) + \sum_i d_i h_i^2 + b_3 \tag{12}$$

where a_i, c_i, d_i and b_1, b_2, b_3 are learnable parameters, and h_i is the (flattened) output of last residual block. We found this modification to significantly improve performance compared to using a simple linear last layer.

For CIFAR and CelebA results we trained for 300k weight updates, saving a checkpoint every 5000 updates. We then took 1000 samples from each saved networks and used the network with the lowest

FID score. For MNIST and fashion MNIST we simply trained for 100k updates and used the last checkpoint. During training we pad MNIST and Fashion MNIST to 32*32 for convenience and randomly flipped CelebA images. No other modification was performed. We only constrained the gradient of the energy function, the energy value itself could in principle be unbounded. However, we observed that they naturally stabilize so we did not explicitly regularize them. The annealing sampling schedule is optimized to improve sample quality for CIFAR-10 dataset, and consist of a total of 2700 steps. For other datasets the shape has less effect on sample quality, see Figure F.1 B for the shape of annealing schedule used.

For the Log likelihood estimation we initialized reverse chain on test images, then sample 10000 intermediate distribution using 10 steps HMC updates each. Temperature schedule is roughly exponential shaped and the reference distribution is an isotropic Gaussian. The variance of estimation was generally less than 10% on the log scale. Due to the high variance of results, and to avoid getting dominated by a single outlier, we report average of the log density instead of log of average density.

E EXTENDED SAMPLES AND INPAINTING RESULTS

We provide more inpainting examples and further demonstrate the mixing during sampling process in Figure E.1. We also provide more samples for readers to visually judge the quality of our sample generation in Figure E.2, E.3 and E.4. All samples are randomly selected.

Figure E.1: Denoised Sampling process and inpainting results. Sampling process is from left to right.

Figure E.2: Extended Fashion MNIST and MNIST samples

F SAMPLING PROCESS AND ENERGY VALUE COMPARISONS

Here we show how the average energy of samples behaves vs the sampling temperature. We also show an example of our model making out of distribution error that is common in most other likelihood based models (Nalisnick et al., 2019) Figure F.1.

Figure E.3: Samples (left panel) from network trained on CelebA, and training examples from the dataset (right panel).

Figure E.4: Samples (left panel) from energy-based model trained on CIFAR-10 next to training examples (right panel).

Figure F.1: A. Energy values for CIFAR-10 train, CIFAR-10 test and SVHN datasets for a network trained on CIFAR-10 images. Note that the network does not over fit to the training set, but just like most deep likelihood model, it assigns lower energy to SVHN images than its own training data. B. Annealing schedule and a typical energy trace for a sample during Annealed Langevin Sampling. The energy of the sample is proportional to the temperature, indicating sampling is close to a quasi-static process.