ADAPTIVE GENERATION OF PROGRAMMING PUZZLES

ABSTRACT

AI today is far from being able to write complex programs. What type of problems would best teach computers programming, and how should such problems be generated? We suggest programming *puzzles* as a domain for teaching computers programming. A programming puzzle is a short program for a Boolean function $f(x)$ with the goal of finding an input that makes f return `True`. Puzzles are *objective* in that one can easily test the correctness of a candidate solution, in contrast to other common specifications for program synthesis like input-output pairs or English problem descriptions. To address automatic puzzle generation, we propose a GAN-like algorithm called "Troublemaker" which can generate puzzles *adaptively* targeted at any given puzzle-solver. Rather than generating a single dataset of puzzles at random, it generates a diverse set of puzzles that are difficult for the solver. In our experiments, Troublemaker learns to generate challenging problems for a variety of state-of-the-art puzzle-solving techniques.

1   INTRODUCTION

Computers still perform worse than humans at elementary programming and mathematical reasoning problems, let alone the AI grand challenge of designing, analyzing, and implementing sophisticated algorithms. For example, many symbolic mathematical software packages fail to solve $n^{n^n} = 10^{10^{10}}$ for n. While programs can be taught to immediately answer such puzzles, it points to a fundamental lack of understanding that limits their ability to perform complex programming and mathematics.

The first question faced in the daunting task of teaching computers to program is, *how should one represent programming problems to teach computers?* The ideal representation may be different from what suits humans. Consider a question "What number follows the sequence 1-2-1-4-1-6-1?" (Barrett et al., 2018; Saxton et al., 2019). It requires: (a) understanding some English and (b) guessing which sequence the test-writer considers most natural among the many consistent ones. We refer to these biases as *human priors*. Program synthesis problems involve human priors as well. They are usually specified in English and/or by examples (Gulwani et al., 2012) such as *"Extract the area code from a phone number"* and/or "`(212)123-4567`" → "`212`". These involve prior knowledge about phone numbers, which may impede computers from learning the fundamentals of programming and math.[1]

In summary, to advance artificial reasoning, the ideal programming problem representation should be:

Objective: a candidate solution ought to be unambiguously validated as to whether or not it satisfies the specification. In particular, a problem-solving algorithm should be able to determine correctness without knowledge of English or consulting an answer key.

Challenging: Capture problems that human programmers can solve easily but which foil computers.

Diverse: Capture a rich range of useful programming problems from easy to hard.

Unbiased: Avoid dependence on human priors, such as language or spatio-temporal biases.

Programming Puzzles   As a better standard for evaluating and advancing artificial reasoning, we propose *Programming Puzzles*. In a puzzle, given the source code of a function f in a fixed programming language (*e.g.* Python), the goal is to find an input x such that $f(x)$ returns `True`.

---

[1] After creating NAPS (Zavershynskyi et al., 2018), a "Natural Programming Synthesis" dataset of programming contest problems with English descriptions and input-output examples, one of the authors later conceded that "ML, specifically natural language understanding, is not there yet." (Polosukhin, 2018)

```python
def f1(n: int, prefix=123456789): #   find an integer n whose square begins with 123456789
    return str(n*n).startswith(str(prefix))

def f2(S: Set[int], n=11010010): #      find a set S of powers of 10 summing to 11010010
    return sum({10**i for i in S}) == n

def f3(s: str): #                        find a string s with 1,000 As but no two consecutive As
    return s.count("A")==1000 and s.count("AA")==0

def f4(x: List[Boolean]): #                         solve a classic Boolean SAT CNF formula
    return (x[0] or x[1]) and (not x[1] or not x[2])

def f5(m: int, n=10987654321): #             find a nontrivial integer factor of 10987654321
    return 1 < m < n and n % m == 0
```

Figure 1: Sample programming puzzles with valid answers $n = 111111111$ (Python: `int("1"*9)`), $S = \{1, 4, 6, 7\}$, s = a concatenation of 1000 copies of "AB" (Python: `s="AB"*1000`), $x =$ `[True, True, False]`, and $m = 7$. Problems range from easy to hard to unsolvable.

As Figure 1 illustrates, short puzzles can capture extremely difficult problems such as factoring or subset-sum as well as easy questions such as list reversal or solving $(x + 1)^{x+1} == 100^{100}$ for x. Importantly, such puzzles are objective – a candidate solution can easily be evaluated for correctness.

Not all programming problems can be nicely defined as puzzles. In some problems, writing the puzzle is as hard as solving the problem, *e.g.* long addition of two numbers. Other problems involve human priors, *e.g.* alphabetizing a list of names by last names, where language rules determine whether "`Mary De Leon`" is sorted under "`D`" or "`L`". However, puzzles with polynomial-time definitions constitute the complexity class NP, which contains P problems such as shortest-path as well as hard problems such as factoring and finding a neural network with a sufficiently low training loss.

Troublemaker Our second main contribution is a "Troublemaker" algorithm that automatically generates puzzles in an *adaptive* manner to challenge any given puzzle-solving system. A primitive system may be given easy puzzles, while an advanced system may be given hard puzzles (or puzzles targeting a specific discovered weakness). Automatic problem generation has been applied to train program synthesis systems (Balog et al., 2016; Christakopoulou & Kalai, 2018) and in numerous related domains such as mathematical problems (Saxton et al., 2019) and IQ tests (Barrett et al., 2018). However, these problems were generated non-adaptively, often via random sampling. In this work, we use a host of state-of-the-art neural and symbolic machine intelligence techniques as target solvers, and show that Troublemaker learns to generate challenging puzzle datasets for all of them.

Troublemaker operates by *searching* for puzzles in a given grammar that would be hard for a given solver. The search process is made adaptive by guiding it with a trained neural network. The network is optimized to balance (a) difficulty of the puzzle w.r.t. the solver runtime, (b) diversity of generated puzzles, and (c) puzzle brevity. When the solver is trainable, this generation process results in an *adversarial* setup, where Troublemaker finds increasingly hard problems as the training progresses.

Contributions This paper introduces (1) programming *puzzles*, a class of objective problems that can be used to evaluate and improve the reasoning ability of existing AI systems; (2) an *adaptive* puzzle generator that can be targeted at any given puzzle solver(s). Note that we do *not* set out to create novel approaches for puzzle solving – we evaluate our puzzle generation on state-of-the-art neural and symbolic solvers. We focus on adaptive problem generation and establishing the puzzle domain as suitable for teaching machines how to program, leaving the improvements of puzzle solving techniques to future work.

2 RELATED WORK

Program Synthesis The prior work on program synthesis is too large to survey here (see the survey by Gulwani et al., 2017). As mentioned, prior work on program synthesis largely works from input-output examples x_i, y_i where the goal is to find a "natural" function f such that $f(x_i) = y_i$.

This representation is *subjective* – the issue is not that there are multiple correct programs but rather that the correctness of a given solution f is debatable and cannot be determined from examples alone. Similarly, the research on *semantic parsing* (Liang, 2016) describes problems in natural language such as English, for which program correctness is even more debatable. From the point of view of expressing the intent of an end user, these representations may be quite natural and the ambiguity may be inherent to the problem. However, for the purpose of teaching computers programming and reasoning basics, such ambiguity impedes learning.

An exception is a closely-related work of Christakopoulou & Kalai (2018), which inspired this paper. They consider a specification that is itself a program that takes a whole problem-solving program as input. The specification program then generates a number of random inputs to the candidate program and ensures that the candidate satisfies them all. Similarly to our work, this specification in the form of source code is given to the problem solver.

A dual view of puzzles in that their solutions are programs, and the puzzle itself serves as a simple *formal specification*. Every puzzle solution can be then viewed as a constant program that satisfies this specification. In the programming languages community, the intent is often defined by a *formal specification* with the goal of finding any program that satisfies it (Manna & Waldinger, 1980; Bornholt & Torlak, 2017; Alur et al., 2018). The greater expressive power in some languages inherently means that it is not always trivial to determine whether a solution satisfies the specification.

Evaluating Intelligence and Reasoning   Program synthesis systems that employ machine learning models are often trained on automatically generated programming problems (Balog et al., 2016; Christakopoulou & Kalai, 2018; Devlin et al., 2017; Parisotto et al., 2016). However, the way they generated problems was non-adaptive, *i.e.* independently of the solver. Recent work (Shin et al., 2019) has noted that such randomly generated datasets often fail to capture important properties of the desired program distribution, and thus result in a biased program synthesizer. Our Troublemaker framework allows adapting the dataset to the evaluation metric of a particular synthesizer.

As mentioned in Section 1, other tasks for evaluating and motivating progress in machine intelligence have been proposed, including mathematical word problems (Saxton et al., 2019) and IQ tests (Barrett et al., 2018). None of them achieve our desiderata of objectivity and independence of human priors. One notable example is the ARC task (Chollet, 2019), developed concurrently with this work. While it is also designed to establish a new standard in measuring intelligence and intentionally forgoes all human priors, its problem specification is still given by input-output pairs and thus is subjective.

Adversarial and Curriculum Learning   The Troublemaker framework aims to generate short and diverse puzzles that are difficult for a given puzzle solver. As such, its main goal is to evaluate the solver and set an adaptive milestone to facilitate AI progress. However, a similar technique can be used to adaptively generate a training set, aiming to improve a given solver after discovering its weaknesses. In the machine learning community this is known as *curriculum learning* (Bengio et al., 2009; Graves et al., 2017; Sukhbaatar et al., 2018). The Alice-Bob framework of Sukhbaatar et al. (2018) is particularly relevant. In it, a *teacher agent* and a *student agent* engage in self-play where the teacher generates tasks for the student right at the edge of the student's "comfort zone", thus encouraging the student to continually improve. This is in contrast to Troublemaker, which over time generates problems *just beyond* the solver's comfort zone to expose its limitations. When a solver is trainable, Troublemaker proceeds by iterating between improving the solver and the puzzle generator.

Troublemaker, Alice-Bob, and similar iterative frameworks drive inspiration from *generative adversarial networks* (GANs) (Goodfellow et al., 2014). In addition to wide usage in improving generative models via learned adversarial objectives, the GAN ideas have also been recently used to improve robustness of trained agents (Pinto et al., 2017) or to automatically adapt their reward functions (Durugkar & Stone, 2018). These works are typically applied to reinforcement learning based environments, while Troublemaker focuses on the problem of generating hard and diverse puzzles without any assumptions on the target solver.

3   Problem Generation as a Zero-Sum Game

Our goal is to find a distribution over a diverse set of hard problems. The framework can be defined abstractly in terms of set $\mathcal{P}$ of problems and set $\mathcal{S}$ of solvers, where each problem $p \in \mathcal{P}$ computes a

Boolean function $p : \mathcal{X} \to \{\top, \bot\}$ for on some set $\mathcal{X}$, and each solver $S \in \mathcal{S}$ computes a function $S : \mathcal{P} \to \mathcal{X}$. Problem p is said to be easy for S if $p(S(p)) = \top$ and *hard* for S otherwise. The set $\mathcal{S}$ captures the resource constraints on solvers (e.g., our experiments have a time budget B by wrapping each solver in an appropriate timeout), and the set $\mathcal{P}$ captures restrictions on problems such as length limit and any other restrictions of interest such as solvability.

The Problem-generation game is a two-player zero-sum game between a *Generator* that chooses an arbitrary distribution $D \in \Delta(\mathcal{P})$ over $\mathcal{P}$, where $\Delta(T)$ denotes the set of probability distributions over set T, and a *Learning Solver* who chooses $S \in \mathcal{S}$. For example, we implement $\mathcal{S}$ as a set of neural guided solvers whose parameters are trained by the Learning Solver. The *payoff* to the Generator is $v(D, S) = \mathbb{E}_{p \sim D}[r(p, S, D)]$, where, r is a *reward* function and $D(p)$ is the probability of generating problem p:

$$r(p, S, D) = \begin{cases} \lambda(-\log_2 D(p)) + (1 - \lambda) & \text{if } p(S(p)) \neq \top \\ 0 & \text{if } p(S(p)) = \top. \end{cases} \quad (1)$$

The reward is parameterized by $\lambda \in [0, 1]$ which offers a trade-off: at $\lambda = 0$, any hard problem earns the Generator a reward of 1, while at $\lambda = 1$ the reward is the expected negative log-likelihood over hard problems. The reward function may seem peculiar at first since it depends not only on problem's hardness but also on its probability of being generated. At $\lambda = 0$ the reward does not account for the diversity of the distribution of problems—against any solver S a generator could maximize v with the distribution that always outputs a single hard problem $p \in S$, yet we want D to generate diverse hard problems. To account for diversity, the reward therefore depends on D as well. As one varies λ from 0 to 1, one expects the fraction of hard problems to decrease but the entropy of the hard problems to increase, a measure of greater diversity.

3.1 STATIC SOLVER

We consider two types of solvers. First, consider a fixed Solver S, i.e., the Learning Solver does not learn but instead just plays S, and let $H_S = \{p \in \mathcal{P} \mid p(S(p)) \neq \top\}$ denote the set of problems that are hard for S. It is not difficult to see that if the Generator only generates hard problems support$(D) \subseteq H_S$, then $v(D, S) = 1 - \lambda - \lambda H(D)$, where $H(D)$ is the *entropy* of distribution D. Entropy is a standard notion of diversity of a distribution, though other notions may be used.

Lemma 1. *For any $\lambda \in (0, 1]$ and any solver S with $|H_S| \geq 3$ hard problems, the uniform distribution $\mathcal{U}_{H_S}$ over H_S uniquely maximizes the Generator's payoff $v(\mathcal{U}_{H_S}, S) = 1 - \lambda + \lambda \log_2 |H_S|$.*

All proofs are deferred to Appendix B. In practice, of course the Generator may not find this uniform distribution but $|H_S| \geq 2^{v(D,S)}$ remains a lower bound for whatever D is found.

3.2 LEARNING SOLVER

Next, consider an adaptive solver that can tailor its choice of $S \in \mathcal{S}$ by adjusting its parameters. Based on the theory of zero-sum games (Myerson, 2013), the game has a unique "value" that can be achieved by possibly different optimal "mixed strategies" which are probability distributions themselves. In the Problem-generation game, this is somewhat confusing as mixed strategies for the Generator are distributions over distributions of problems in $\Delta(\Delta(\mathcal{P}))$, and mixed strategies for the solver are distributions over solvers in $\Delta(\mathcal{S})$.

However, we next show that there is a single optimal strategy for the Generator (as long as each solver has 3 hard problems). Fortunately, this optimal Generator strategy is a "pure strategy", a single distribution $D^* \in \Delta(D)$ over problems rather than a distribution over distributions. Nonetheless, there may be multiple optimal strategies for the Learning Solver.

Theorem 1. *For any set $\mathcal{S}$ and $\lambda \in (0, 1]$, as long as each solver S fails on at least $|H_S| \geq 3$ problems, there is a unique distribution D^* that achieves the value of the zero-sum Problem-generation game.*

In particular, D^* is simply the distribution that maximizes $J(D) = \min_{S \in \mathcal{S}} v(D, S)$. As mentioned, $\lambda = 0$ can admit multiple (degenerate) optimal solutions. Like Lemma 1, this Theorem is a theoretical statement as it is not clear that the Generator will find D^*.

Algorithm 1: The Troublemaker algorithm for finding parameters for the generator distribution. If a learning solver cannot accommodate weights, subsampling can be used to simulate weights.

Input: sample size n, number of steps N, step size η, a function that generates samples for any given D_θ, a differentiable function that computes log-probabilities for D_θ and either: (a) fixed solver S or, (b) Learning Solver that maps a weighted set of problems to solver S.

1   Choose $\theta_1 \in \Theta$
2   **for** $i \leftarrow 1$ **to** N **do**
3   Create a problems sample $p_{i1}, p_{i2}, \ldots, p_{in}$ by independent draws from D_{θ_i}
4   **if** S *is a fixed solver* **then** $S_i \leftarrow S$
5   **else** feed problems $p_{i1}, \ldots p_{in}$ with weights $w_{ij} = 1 - \lambda - \lambda \log D_{\theta_i}(p_{ij})$ on problem p_{ij} into the Learning Solver and let S_i be its output. (In practice, the parameters of S_{i-1} can be used as a warm start.)
6     $U_i \leftarrow$ the set of sample problems that S_i failed to solve
7   Update by summing over problems that S_i doesn't solve:
$$\theta_{i+1} = \theta_i + \frac{\eta}{n} \sum_{p \in U_i} \big(1 - 2\lambda - \lambda \log D_{\theta_i}(p)\big) \nabla_\theta \log D_{\theta_i}(p)$$
8   **end**
9   **return** generator parameters θ_N

3.3   TROUBLEMAKER ALGORITHM FOR SOLVING THE PROBLEM-GENERATION GAME

To find the distribution D^*, one may maximize $J(D) = \min_{S \in \mathcal{S}} v(D, S)$, which is concave in D:

Observation 1. *The function $J(D) = \min_{S \in \mathcal{S}} v(D, S)$ is concave in D.*

Hence, as a concave function, it can be theoretically maximized to within arbitrary precision, using the standard gradient-projection ascent, namely:

---

1   Choose D_1 to be uniform over $\mathcal{P}$
2   **for** $i \leftarrow 1$ **to** N **do**
3   Find solver S_i to minimize $v(D_i, S)$
4   Update $D_{i+1} = \Pi_{\Delta(\mathcal{P})}\big(D_i + \eta \nabla_D v(D_i, S_i)\big)$
5   **end**

Here we have used the fact that a gradient of a minimum of functions is the gradient of whichever function is minimal at that point. Note that minimizing $v(D_i, S)$ over $S \in \mathcal{S}$ is equivalent to finding the solver that solves the most problems where each problem p has a non-negative *weight* $w_p = 1 - \lambda - \lambda \log D_i(p)$. Also, Π_T denotes the projection on to the closest point in convex Euclidean set T, in this case the closest probability distribution. This gradient-projection method is known to converge at a rate that depends on N and step size $\eta > 0$ (*e.g.* Zinkevich, 2003). However, this again is a theoretical algorithm assuming that one can represent an arbitrary distribution and can evaluate $v(S, D)$ over *all problems*, which is computationally intractable. In practice, one represents a Generator D_θ by parameters $\theta \in \mathbb{R}^n$ and optimizes them w.r.t. the samples drawn from the generator.

The TM algorithm, described in Algorithm 1, follows the alternating gradient ascent procedure above procedure except that, using a sampling approximation similar to the REINFORCE algorithm (Williams, 1992) except that the gradient calculation is changed since the reward depends on the probability of generation. It requires sampling from D_θ and computing gradients $\nabla_\theta \log D_\theta(p)$ of log-probabilities, as is standard for sequential neural generation procedures. One also needs to be able to compute a best solver in response to a distribution of problems, which a Learning Solver can also approximate from problems sampled from D_θ. The analysis showing how the update in Step 4 is an unbiased estimate of the gradient of J is given in Lemma 2 in Appendix B.

4   TROUBLEMAKER: GENERATING PROGRAMMING PUZZLES

Having derived a general form of the puzzle generation problem, we turn our attention to its instantiation in the Troublemaker framework. In this section, we first define a program representation for puzzles used by our generator D_θ, and then describe the architecture of the trainable generator.

```
bool  equation  ≔  term  ==  term
float  term  ≔  0.1  term  +  term  |  0.2  term  *  term
              |  0.05  term  −  term  |  0.05  term  /  term
              |  . . .
              |  0.15  float(term  ==  0)  // evaluates to 1.0 if equality holds, 0.0 otherwise
              |  0.05  π  |  0.05  e  |  0.05  0.0  // constants
              |  0.3  x  // variable
```

Figure 2: An excerpt from our Probabilistic Context Free Grammar (PCFG) that defines a family of puzzles with floating-point solutions. Each production rule is annotated with a weight, automatically learned by the generator (see main text).

We assume a language of *programs* L defined as a Context Free Grammar (CFG). Each abstract syntax tree (AST) $T \in L$ describes a programming puzzle problem $p_T : \mathcal{X} \to \{\top, \bot\}$, as defined in Section 3. When T is clear from context, we write p instead of p_T. For the purpose of this paper, we assume interesting problems are *hard* puzzles whose solution a solver cannot obtain within the given time budget *i.e.* time$(S, p_T) > B$. However, our framework is agnostic to this assumption and can be trivially modified to generate problems for different notions of "interesting."

To generate puzzles that involve complex reasoning patterns, the language L needs to be expressive enough to represent a wide range of puzzles. For example, Figure 2 shows an excerpt from our grammar for generating floating-point puzzles (full definition in Appendix A). Due to its expressiveness, sampling programs from L uniformly at random is not useful as it may generate overly simple problems or even unsolvable ones like $x^2 = -1$. We will first describe our core procedure for generating puzzles in L, and will then turn our attention to ensuring their complexity and solvability.

4.1 GENERATION MODEL

Generation with Probabilistic Grammars   The first generation strategy we consider is to employ a probabilistic grammar as shown in Fig. 2. As can be seen, depending on the solver, different rules can be encouraged to bias the production of problems. For instance, the weights in Fig. 2 display a higher preference for multiplication of terms – this lends itself conveniently to the generation of puzzles with higher-degree polynomials. Note that the probability of generating a program p factorizes into its constituent production rules:

$$\Pr(p_T) = \prod_{r \in T} \Pr(r)$$

which constructively corresponds to a standard sampling procedure that builds the AST T one production at a time by sampling a production to expand each nonterminal using its corresponding weight as an unnormalized probability. Further, as mentioned, we aim to produce *hard* problems, *i.e.* maximize $\log$ time(S, T) or, in general, any reward that fits into the framework described in Section 3. It is now easy to see that the weights θ of the probabilistic grammar can be learnt via REINFORCE (Williams, 1992) using Algorithm 1.

Neural Guided Generation   While this strategy allows us to tailor generation for a given solver, it only tunes global preferences (*i.e.* encourages certain rules *always*) as opposed to context-dependent changes (*i.e.* rule A is preferred conditioned on the current partial AST). To enable finer-grained control over the generation process, we propose a more versatile generation strategy that conditions prediction of a rule on the rules in a partial AST produced so far. The context-dependent conditioning model is parameterized as a trainable neural network, whose parameters guide the generation process.

Let $T_{<t}$ be a partial AST generated so far at the generation timestep t, assuming some fixed ordering of nonterminal expansions to generate the whole AST (we use the pre-order traversal). The *neural-guided generation strategy* parameterized the probability of the puzzle as

$$\Pr(p_T) = \prod_t \Pr(r_t \mid T_{<t})$$

where r_t is the production rule expanded in the AST T at the t^{th} timestep. The probability $\Pr(r_t \mid T_{<t})$ is, in turn, parameterized as a neural network that takes as input a *partial tree embedding* $\phi(T_{<t})$ and outputs a distribution of probabilities for each syntactically valid production rule.

```
lhs == rhs → p**lhs == p**rhs
lhs == rhs → p+lhs == p+rhs
lhs == rhs → p*lhs == p*rhs
```

Figure 3: Tree rewrite rules for `float` puzzles. Here p is also $term$ from the grammar in Figure 2.

We consider two state-of-the-art approaches to parameterize the tree embedding model ϕ. The first parameterization is a naïve baseline – encoding a traversal of the tree $T_{<t}$ with an LSTM (Hochreiter & Schmidhuber, 1997). While straightforward, it does not explicitly makes use of the syntax structure present in the AST. Motivated by recent research in program representation (Allamanis et al., 2017; Brockschmidt et al., 2018), we choose *graph neural networks* (GNNs) as a second tree embedding model. Specifically, the model employed is GNN-FiLM (Brockschmidt, 2019), a recent GNN architecture that allows for feature-wise linear modulations, achieving state-of-the-art performance on a range of graph tasks like node classification.

4.2 COMPLEX AND SOLVABLE PUZZLES

Generating Solvable Programs In order to generate solvable puzzles, we use domain-specific knowledge to *convert* a puzzle sampled from L to a solvable one. To continue with the `float`-puzzle example, we first select a random solution x_0. Then given an equation $a(x) == b(x)$ where both $a, b \in L_{term}$, we can convert it to a *solvable* puzzle at x_0 by modifying the program to be $a(x) = b(x) - k$ where $k = a(x_0) - b(x_0)$.

Generating Complex Puzzles A standard strategy employed by experts for posing mathematical problems is *chaining* (Silver, 1994). Chaining expands on an existing problem (and solution) such that finding the solution for the modified problem requires solving the original problem as an intermediate step. For instance, in the case of our `float`-puzzle problems, exponentiating both sides of the equation is a good example of *chaining* – while preserving the *solvability*, it requires solving the original problem as an intermediate step (after taking log of both sides). In this work, we incorporate this strategy to generate *complex* puzzles that potentially require multiple steps of reasoning. In our setting of generating programming puzzles, we incorporate this problem posing strategy via tree-rewriting rules that transform an existing tree to another tree in the language – formally, a tree-rewriting rule $R : L \rightarrow L$ For the example of `float`-puzzles, Fig. 3 provides a bank of tree-rewrite rules that can be used to produce complex solvable puzzles.

This approach is sufficiently general to apply to other domains such as `int`-puzzles or `set`-puzzles. For example, consider the sub-set sum problem – find set $\mathcal{B} \subseteq \mathcal{A}$ such that the sum of elements in $\mathcal{B}$ is a given integer K. If this `set`-puzzle is solvable, chaining can be used to produce more complex puzzles by replacing $\mathcal{A}$ with $\mathcal{A} \cup \mathcal{C}$ for some non-empty integer set $\mathcal{C}$. This transformation preserves solvability but can also make the puzzle harder, *e.g.* if the entire set $\mathcal{B} = \mathcal{A}$ is initially a solution.

4.3 TRAINABLE SOLVERS

Finally, while the Troublemaker framework as presented in Algorithm 1 is applicable for an arbitrary solver, it is particularly interesting for *trainable* solvers that can be improved with data produced by the generator. For them, the Troublemaker generation leads to an *adversarial* optimization process where the weights of the puzzle generator are updated to produce harder problems for the solver and similarly, the solver's weights are updated based on the newly generated *hard* problems. In this work, we study two variants of trainable solvers:

Induction Solver (IS): This neural solver directly outputs the solution x of the puzzle p_T given some embedding of the puzzle $\psi(T)$. In the case of structured outputs (like sets), the solver sequentially outputs elements along with a stop token to signal the end of generation.

Synthesis Solver (SS): This solver is similar to the neural generator – given a grammar L along with a bank of useful constants, it constructs a solution x as an *constant expression* in the grammar. The construction procedure is similar to puzzle generation – at each timestep t, it uses an encoding of the puzzle $\psi(T)$ and the current partial expression to select the next production rule to expand in the expression. Notably, while the generator emits the puzzle

p_T using an end-to-end differentiable LSTM, we found that synthesis of solutions x is best parameterized as a discrete *search process* guided by the rule-prioritizing neural network as described above. This is similar to other state-of-the-art neuro-symbolic program synthesis techniques such as DeepCoder (Balog et al., 2016) and NGDS (Kalyan et al., 2018).

In both solvers, the puzzle embedding model $\psi(T)$ is a GNN-FiLM network, parameterized identically to the generator's embedding model (Section 4.1).

5 EXPERIMENTS

In this section, we present results for the TroubleMaker approach to generate hard problems for a given solver. We consider `float`, `int` and `intset` puzzles to demonstrate the flexibility of the proposed puzzle generation framework. We provide the full grammar and tree-rewrites in Appendix A.

Puzzle Generators. As discussed earlier, we study both probabilistic grammar based and neural-guided problem generators. Further, in the grammars used, we allow a new *copy* operator that can copy a node of type τ from the partial tree generated so far as opposed to generating a tree from L_{NT} where NT is of type τ. The introduction of this operator increases the likelihood of generating puzzles with recursive structure (*e.g.* $10^{10} - x^x = 0$) – a desirable quality that often results in interesting reasoning patterns. As discussed in Sec. 4.1, both generators are trained using REINFORCE. Finally, note that the recursion depth was capped at 10 for the production of all puzzles (from the grammar and including tree rewrite rules).

Solvers. In this work, we consider multiple solvers and in fact, use TM to produce programs that are in general *hard* for all solvers. The solvers used are as follows:

1. Enumerative Solver (ES): Given a grammar to generate the solution, this solver performs enumerative search to find a satisfying solution. For the sake of simplicity, we provide the solver with the same grammar used to generate a puzzle (of the same solution type). However, a significant difference is that the bank of constants available to the solver is *large* and corresponds to all the unique constants generated so far.

2. Guided Solver (GS): This solver builds on top of the enumerative solver by using a neural network to guide the search process conditioned on the puzzle, as described in Section 4.3. By learning heuristics from data, this solver learns to accelerate enumerative search by pruning away large portions of the search space. This is the only *trainable* solver.

3. Grid Search (GrS): This solver, as the name suggests, searches in the solution space, narrowing down to a satisfying solution based on comparisons. Unlike other solvers, being ϵ close to a satisfying solution is sufficient for the grid solver. (We set $\epsilon = 10^{-10}$ in our experiments.) This solver is not a general-purpose puzzle solver and is used only in the context of floating point and integer puzzles.

4. Sympy[2]: Sympy is a python library for symbolic mathematics and similar to GrS, it is used to only solve floating point and integer problems.

Metrics. To evaluate the performance of the generators, we use the following two metrics:

1. Time taken by the solvers (`time`): This is computed as the *average* (log) time taken to solve a set of 1000 generated problems. This metric (higher is better) corresponds to the "hardness" of the produced solutions.

2. Number of Unique Rules used (`unique-rules`): This is computed as the number of unique rules present in a problem, averaged over a set of 1000 generated problems. While not something we optimize for, an increase in this metric corresponds to an increase in the diversity of the problems generated.

Both solvers and puzzle generators, when trainable, were optimized using Adam (Kingma & Ba, 2014) with a learning rate of 10^{-4}. All the LSTM networks used a hidden size of 256 and in the case of GNN-FiLM architectures, 3 propagation steps and a node representation size of 256 were used.

---

[2] https://www.sympy.org

Puzzle Generators	float-puzzles			
	Solvers			
	Enumerative Solver	Guided Solver	Grid Solver	Sympy
Random	1.21	0.92	1.5	0.05
Prob	2.47	1.95	2.22	1.02
Guided	2.78	1.99	2.34	1.45
	int-puzzles			
Random	3.06	2.93	3.78	4.21
Prob	3.22	2.95	3.82	4.33
Guided	3.45	3.15	3.85	4.54
	int-set-puzzles			
Random	4.12	3.83	-	-
Prob	4.33	4.02	-	-
Guided	4.51	4.19	-	-

Table 1: As can be seen from the table, both generators – probabilistic grammar based (Prob) and neural guided (Guided) lead to improvements (over randomly sampled puzzles) in the **time** required for the solvers, with the guided solver showing the highest gains. Note that randomly sampled puzzles can sometimes be unsolvable – in which case the solver just times out. Further, all values are measured in seconds and solvers have a time bound $B = 5s$.

Puzzle Generators	float-puzzles			
	Solvers			
	Enumerative Solver	Guided Solver	Grid Solver	Sympy
Random	5.42	5.43	5.39	5.42
Prob	4.84	4.29	3.95	4.11
Guided	4.81	4.45	3.67	4.07

Table 2: Observe that `unique-rules` metric for both probabilistic grammar based and Guided search is only slightly lesser than random sampling – indicating that the outputted programs are sufficiently "diverse", employing different strategies to "trouble" solvers.

Results. As can be seen from Table 1, the guided generator finds puzzles with the highest (average) time required across all solvers. Note that in the case of the guided solver, the only trainable solver, the numbers shown are after $K = 100$ iterations with each iteration sampling ~ 2000 puzzles. From Tab 2, we can see that the puzzles produced by both probabilistic and neural-guided generators are reasonably diverse across all solvers – as the proposed generators obtain a score slightly lesser than randomly generated puzzles. Further, the generators are relatively less diverse when trained against the grid solver – from a qualitative inspection of the results, this is because of the frequent usage of the rule $term := \_float(term == 0)$ (see Fig 2), that is hard for a grid solver when the solutions are random floating point numbers.

Further, we observe that induction solvers that directly regress to the output are significantly worse than synthesis-based solvers (solving less than 20% of the problems). For them, TM does not lead to improvements as even small improvements overwhelm the solver. We provide some examples of generated problems in Fig 4.

6   CONCLUSIONS

This work suggests a new type of problem called Programming Puzzles and a framework for generating a large set of hard problems that can both expose the weaknesses of existing solvers (including for numerical problems such as those in Sympy) and which can be used in a GAN-like

```python
# float puzzle
def f1(x: float):
    return ((x + x) + (float(x == x / (x + 2.)))) == -0.1474945082398796

# int puzzle
def f2(x: int):
    return 2**(x**2)) == 16

# int-set puzzle
def f3(x: set):
    return sum(x) == 47 and x in union({-2,-1,0}, range(40,103))
```

Figure 4: Sample generations corresponding to each type considered in this work. The `float` sample uses tree-rewrites to substitute a constant in the equation with another term and a constant. Similarly, the `int` puzzle uses exponentiation and `int-set` example applies a tree rewrite of replacing the ground set with a union of itself and another set.

setup to train better solvers. Our system differs from prior work on data sets of problems, in that: (1) our puzzles are short, interpretable problems which may have multiple solutions but for which it is trivial to validate the accuracy of any solution, and (2) the puzzles are targeted specifically at any given solver. While it would be useful to have a ground-truth dataset of puzzles drawn from, say, programming contests such as ICPC (see Appendix C for an example), such a dataset is not strictly necessary for our worst-case approach.

One of the technical challenges that arises is that, in addition to optimizing for hardness, we also seek a large set of problems. Hence the reward of the puzzle generator takes into account the probability of each generated puzzle, which is uncommon in most GAN's or reinforcement learning problems. Nonetheless, we show that the problem can be made well-defined in a differentiable pipeline, with a unique optimum solution that can be shown to converge. While our system is far from the final word on this problem, we believe these two ideas may initiate a line of work in which it is easier to make progress on the grand challenge of teaching computers to write complex programs.

REFERENCES

Miltiadis Allamanis, Marc Brockschmidt, and Mahmoud Khademi. Learning to represent programs with graphs. *arXiv preprint arXiv:1711.00740*, 2017.

Rajeev Alur, Rishabh Singh, Dana Fisman, and Armando Solar-Lezama. Search-based program synthesis. *Communications of the ACM*, 61(12):84–93, 2018.

Matej Balog, Alexander L Gaunt, Marc Brockschmidt, Sebastian Nowozin, and Daniel Tarlow. Deepcoder: Learning to write programs. *arXiv preprint arXiv:1611.01989*, 2016.

David GT Barrett, Felix Hill, Adam Santoro, Ari S Morcos, and Timothy Lillicrap. Measuring abstract reasoning in neural networks. *arXiv preprint arXiv:1807.04225*, 2018.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pp. 41–48. ACM, 2009.

James Bornholt and Emina Torlak. Synthesizing memory models from framework sketches and litmus tests. In *Proceedings of the 38th ACM SIGPLAN Conference on Programming Language Design and Implementation*, PLDI 2017, pp. 467–481, New York, NY, USA, 2017. ACM. ISBN 978-1-4503-4988-8. doi: 10.1145/3062341.3062353.

Marc Brockschmidt. GNN-FiLM: Graph neural networks with feature-wise linear modulation. *arXiv preprint arXiv:1906.12192*, 2019.

Marc Brockschmidt, Miltiadis Allamanis, Alexander L Gaunt, and Oleksandr Polozov. Generative code modeling with graphs. *arXiv preprint arXiv:1805.08490*, 2018.

François Chollet. The measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

Konstantina Christakopoulou and Adam Tauman Kalai. Glass-box program synthesis: A machine learning approach. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Jacob Devlin, Jonathan Uesato, Surya Bhupatiraju, Rishabh Singh, Abdel-rahman Mohamed, and Pushmeet Kohli. Robustfill: Neural program learning under noisy i/o. *arXiv preprint arXiv:1703.07469*, 2017.

Ishan Durugkar and Peter Stone. Adversarial goal generation for intrinsic motivation. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Alex Graves, Marc G Bellemare, Jacob Menick, Remi Munos, and Koray Kavukcuoglu. Automated curriculum learning for neural networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1311–1320. JMLR. org, 2017.

Sumit Gulwani, William R Harris, and Rishabh Singh. Spreadsheet data manipulation using examples. *Communications of the ACM*, 55(8):97–105, 2012.

Sumit Gulwani, Oleksandr Polozov, Rishabh Singh, et al. Program synthesis. *Foundations and Trends® in Programming Languages*, 4(1-2):1–119, 2017.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Ashwin Kalyan, Abhishek Mohta, Oleksandr Polozov, Dhruv Batra, Prateek Jain, and Sumit Gulwani. Neural-guided deductive search for real-time program synthesis from examples. *arXiv preprint arXiv:1804.01186*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Percy Liang. Learning executable semantic parsers for natural language understanding. *Commun. ACM*, 59(9):68–76, August 2016. ISSN 0001-0782. doi: 10.1145/2866568.

Zohar Manna and Richard Waldinger. A deductive approach to program synthesis. *TOPLAS*, 2(1): 90–121, 1980.

Roger B Myerson. *Game theory*. Harvard university press, 2013.

J v Neumann. Zur theorie der gesellschaftsspiele. *Mathematische annalen*, 100(1):295–320, 1928.

Emilio Parisotto, Abdel-rahman Mohamed, Rishabh Singh, Lihong Li, Dengyong Zhou, and Pushmeet Kohli. Neuro-symbolic program synthesis. *arXiv preprint arXiv:1611.01855*, 2016.

Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2817–2826. JMLR. org, 2017.

Illia Polosukhin. NEAR.ai → NEAR Protocol, August 2018. https://nearprotocol.com/blog/near-ai-near-protocol/, Last accessed on 2019-09-24.

David Saxton, Edward Grefenstette, Felix Hill, and Pushmeet Kohli. Analysing mathematical reasoning abilities of neural models. *CoRR*, abs/1904.01557, 2019. URL http://arxiv.org/abs/1904.01557.

Richard Shin, Neel Kant, Kavi Gupta, Chris Bender, Brandon Trabucco, Rishabh Singh, and Dawn Song. Synthetic datasets for neural program synthesis. In *International Conference on Learning Representations*, 2019.

Edward A Silver. On mathematical problem posing. *For the learning of mathematics*, 14(1):19–28, 1994.

Sainbayar Sukhbaatar, Zeming Lin, Ilya Kostrikov, Gabriel Synnaeve, Arthur Szlam, and Rob Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. In *International Conference on Learning Representations*, 2018.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Maksym Zavershynskyi, Alexander Skidanov, and Illia Polosukhin. NAPS: natural program synthesis dataset. *CoRR*, abs/1807.03168, 2018. URL http://arxiv.org/abs/1807.03168.

Martin Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pp. 928–936, 2003.

```
(a) bool equation := term == term
    float term := term + term | term * term
               | term - term | term / term
               | term**term | -term
               | float(term == 0) | float(term != 0)
               | copy_float() // copies a float node from current partial tree
               | π | 0.0 | e
               | x // variable

(b) bool equation := int in term | sum(term) == int
    set term := ∅ | {int_term} | {int_term, int_term}
               | {int_term, int_term, int_term}
               | union(term, term) | intersection(term, term)
               | difference(term, term)
               | {e for e in range(int_term, int_term)}
    int int_term := ... // integer grammar
```

Figure 5: Grammars that define programming puzzles with (a) `float` and (b) `int-set` solutions.

A   GRAMMARS AND TREE-REWRITE RULES

We present the full grammars for the `float` and `int-set` domains used in this work in Figure 5. The integer rules are similar to the `float` domain except with additional functions `factorial` and `modulo`.

B   THEORETICAL ANALYSIS AND PROOFS

Proof of Lemma 1. We can write the payoff as

$$v(D, S) = \sum_{p \in H_S} D(p)\big(\lambda(-\log D(p)) + 1 - \lambda\big) = (1 - \lambda)D(H_S) - \lambda \sum_{p \in H_S} D(p) \log D(p).$$

Clearly $(1 - \lambda)D(H_S) \le 1 - \lambda$ is maximized if and only if all problems generated are hard for S. The second term $-\sum_{p \in H_S} D(p) \log D(p)$, is the entropy which is known to be maximized over the uniform distribution but is only summed over H_S. For example, if $\lambda = 1$ and $|H_S| = 1$, then the uniform distribution over H_S would have a payoff of 0 because it has 0 entropy, and a distribution which put probability $1/e$ on this hard problem and probability $1 - 1/e$ on an easy problem would actually be optimal. However, whatever probability $D(H_S)$ is assigned to hard problems, it is straightforward to see optimality requires distributing this uniformly over H_S: by the strict concavity of the $-z \log z$ function there is a unique optimum and by symmetry it is uniform. Finally, since $-z \log z$ is increasing up to $z = 1/e > 1/3$, this quantity is only increasing in $D(H_S)$ as long as there are at least three hard problems, so the optimum is $D(H_S) = 1$ only over hard problems.   □

To prove Theorem 1, a key technical observation is that $v(D, S) = \sum_{p \in H_S} D(p)\big(\lambda(-\log D(p)) + 1 - \lambda\big)$ is concave in D, which follows from the concavity of $-z \log z$ for $z \in [0, 1]$. Hence, as a zero-sum game with actions $D \in \Delta(\mathcal{P})$ and $S \in \mathcal{S}$, if the game were played with "mixed strategies" in which players could randomize amongst D and S, it is a dominant strategy for the Generator never to randomize—instead it could achieve an expected payoff at least as large as any distribution over D's by choosing the mean of the distributions. Hence, the "value" of this zero-sum game, given $\mathcal{P}, \mathcal{S}$ (and λ), is:

$$v(\mathcal{P}, \mathcal{S}) = \max_{D \in \Delta(\mathcal{P})} \min_{S \in \mathcal{S}} v(D, S).$$

In fact, this optimization has a unique optimal distribution D (which is not true of zero-sum games in general, and there may be multiple optimal mixed strategies for the Solver):

Proof of Theorem 1. The minimax theorem (Neumann, 1928) implies that,

$$v(\mathcal{P}, \mathcal{S}) = \max_{D \in \Delta(\mathcal{P})} \min_{S \in \mathcal{S}} v(D, S) = \min_{\mu \in \Delta(\mathcal{S})} \max_{D \in \Delta(\mathcal{P})} \mathbb{E}_{S \sim \mu}[v(D, S)],$$

where we have simplified again by the concavity of v in D in not consider distributions over D's. In particular, let μ^* be any minimizer of the right-hand-side above. Any maximum D^* of $\min_{S \in \mathcal{S}} v(D, S)$ must also maximize $\mathbb{E}_{S \sim \mu^*}[v(D, S)]$, which we denote by,

$$v(D, \mu^*) = \mathbb{E}_{S \sim \mu^*}[v(D, S)] = \sum_p \mu^*(\{p \mid p \in H_S\})D(p)\big(\lambda(-\log_2 D(p)) + 1 - \lambda\big).$$

It remains to argue that there is a unique D^* which maximizes the above quantity. Note that $-\log_2 D(p) \geq 0$ so the quantity in the right-hand parentheses is non-negative. Also note that $-D(p) \log D(p)$ is increasing for $0 \leq D(p) < 1/e$.

Let $h_p = \mu^*(\{p \mid p \in H_S\})$ be the hardness of p, the probability a random solver from μ doesn't solve p. We do this by arguing, first, that any maximal D^* would assign $D(p) = 0$ to any "easy" puzzle p such that $h_p = 0$. To see this, note that since every solver has three puzzles that are hard for it, there must be at least three puzzles for which $h_p > 0$ and at least one of these call it p' must have $D(p') \leq 1/3 < 1/e$ and $h_{p'} > 0$. Hence, $v(D, \mu^*)$ could be increased by taking an amount of probability $D(p)$ assigned to a p with $h_p = 0$ and moving it to p'.

Therefore D distributes its probability only over p with $h_p > 0$. Since $-D(p) \log D(p)$ is strictly concave and $D(p)$ is trivially concave (as a linear function), the quantity of interest,

$$\sum_{p : h_p > 0} h_p D(p)\big(\lambda(-\log_2 D(p)) + 1 - \lambda\big)$$

is strictly concave in D and hence has a unique maximum. To see why you need some lower-bound on the number of hard puzzles, note that if only one puzzle p' was hard for all solvers $\forall S\ H_S = \{p'\}$, $\lambda = 1$, and all other puzzles were easy, then the optimum solution would not put all D on the hard puzzle. Instead it would be optimal to assign $D(p') = 1/e$ and spread the remaining $1 - 1/e$ fraction of probability arbitrarily among the puzzles where $h_p = 0$. $\qquad\square$

We now discuss how Step 4 of the TM algorithm (see Figure 1) yields an unbiased estimate of the gradient $\nabla_\theta J(D_\theta)$ from samples.

Lemma 2. *For any Generator D_θ and solver S, over random iid samples $p_1, \ldots, p_n$ from D,*

$$\nabla_\theta v(D_\theta, S) = \mathbb{E}_{p_1, \ldots, p_n \sim D}\left[\frac{1}{n}\sum_{j : p_j \in H_S}\big(1 - 2\lambda - \lambda \log D_\theta(p_j)\big)\nabla_\theta \log D_\theta(p_j)\right].$$

Again, $p_j \in H_S$ means that solver S did not solve problem p_j.

Proof. We first compute the gradient of $J(D_\theta)$ with respect to θ:

$$\nabla_\theta J(D_\theta) = \nabla_\theta \mathbb{E}_{p \sim D_\theta}[r(p, S, D_\theta)]$$

$$= \sum_p \nabla_\theta\big(D_\theta(p)r(p, S, D_\theta)\big)$$

$$= \sum_p r(p, S, D_\theta)\nabla_\theta D_\theta(p) + D_\theta(p)\nabla_\theta r(p, S, D_\theta)$$

$$= \sum_p r(p, S, D_\theta)D_\theta(p)\nabla_\theta \log D_\theta(p) + D_\theta(p)\nabla_\theta r(p, S, D_\theta)$$

$$= \mathbb{E}_{p \sim D_\theta}\big[r(p, S, D_\theta)\nabla_\theta \log D_\theta(p) + \nabla_\theta r(p, S, D_\theta)\big]$$

In the second-to-last line above, we have used the standard "REINFORCE trick" writing $\nabla f(\theta) = f(\theta)\nabla \log f(\theta)$ to make it writable as an expectation. Also note that above applies to an arbitrary reward whose gradients may be computed by automatic differentiation, so the approach generalizes to other reward functions.

Now, for our specific reward function defined in Eq. (1), $\nabla_\theta r(p, S, D_\theta) = -\mathbf{1}_{p \in H_S}\lambda\nabla_\theta \log D_\theta(p)$, where $\mathbf{1}_P$ for proposition P is the indicator function that is 1 if P holds and 0 otherwise. Using this notation, $r(p, S, D_\theta) = \mathbf{1}_{p \in H_S}(1 - \lambda - \lambda \log D_\theta(p))$. Hence, we have,

$$\nabla_\theta J(D_\theta) = \mathbb{E}_{p \sim D_\theta}\big[\mathbf{1}_{p \in H_S}(1 - \lambda - \lambda \log D_\theta(p))\nabla_\theta \log D_\theta(p) - \mathbf{1}_{p \in H_S}\lambda\nabla_\theta \log D_\theta(p)\big]$$

$$= \mathbb{E}_{p \sim D_\theta}\big[\mathbf{1}_{p \in H_S}(1 - 2\lambda - \lambda \log D_\theta(p))\nabla_\theta \log D_\theta(p)\big]$$

```python
def score_azulejos(s: List[int], t: List[int],
                   p1=[3, 2, 1, 2], h1=[2, 3, 4, 3],
                   p2=[2, 1, 2, 1], h2=[2, 2, 1, 3]):
    n = len(p1)
    return (
        sorted(s) == sorted(t) == list(range(n))
        and
        all(h1[s[i]]>h2[t[i]] for i in range(n))
        and
        all(p1[s[i]]<=p1[s[i+1]] for i in range(n-1))
        and
        all(p2[t[i]]<=p2[t[i+1]] for i in range(n-1))
    )
```

Figure 6: ICPC Problem 2019A in English (left) and programming puzzle (right). In the PSAT, `p1`, `p2` are arrays of n prices, `h1`, `h2` are arrays of n heights. The goal is to find `s`, `t`, required to be lists of integers in the function specification. They are further tested to be permutations by checking if sorting them yields `list(range(n))`, the list of numbers from 1 to `n`.

By summing over those samples for which $p_j \in H_S$, the quantity in the lemma is seen to be equal to the above in expectation. □

C   ICPC PROBLEM

As a somewhat complicated but illuminating example, consider the first problem of the 2019 International Collegiate Programming Contest (ICPC). At its core, the goal is, given input two matrices $P, H \in \mathbb{R}^{2 \times n}$, to find a pair of permutations σ, τ on $\{1, 2, \ldots, n\}$ such that,

$$h_{1\sigma_i} < h_{2\tau_i} \text{ and } p_{1\sigma_i} \le p_{1\sigma_{i+1}} \text{ and } p_{2\tau_i} \le p_{2\tau_{i+1}} \text{ for all } i$$

The permutations σ and τ are to be applied to the two rows of P, which correspond to prices. When permuted, the prices are to be non-decreasing. If there are duplicate values in P, this constraint leaves flexibility in σ and τ which must be chosen so as to that when heights, encoded in H, are also permuted by σ and τ, the first row is greater than the second coordinate-wise. Figure 6 shows the problem in English and our PSAT version.

Note that there are a few important differences:

Input parsing. First, the problem like many requires reading and parsing the data from a file rather than receiving it as lists of integers. However, much prior work has successfully shown how to automatically parse such data (see the survey by Gulwani et al., 2017), so we focus on the algorithmic questions.

Solvability. Second, the problem posed in the contest asks users to print "impossible" if the problem has no solution. For such problems, the corresponding puzzle is unsolvable – there simply aren't any valid input which makes it return True. If one wanted to have an objective question where one could verify that an answer of "impossible" was correct, the puzzle would need some sort of proof that the problem is unsolvable which is much more difficult. However, the uncertainty of knowing whether an unsolved puzzle is solvable is not critical for optimization. For example, imagine a solver takes a test with 1,000 problems and knows with certainty that one solved 300 of them and didn't solve the remaining 700. Now, suppose changing a parameter of the system makes it so that it solves an additional 20 problems. This increase in objective is desirable, and even though a humans may be frustrated and even slower to solve a problem without knowing whether or not it is solvable, a computer algorithm will experience no such frustration or slowdown.

Solving instances. For people, there is a difference between submitting a program that solves a given problem with varied inputs and just submitting solutions for a number of given inputs – the latter may be easier as they may identify peculiarities in the inputs which make them easier to solve (or they may even solve them by hand). However, for computers this distinction is not crucial. Given a program

that is only capable of solving individual instances, that same program can itself be submitted as a solution to the general problem. This distinction is similar to a classification problem in which a binary classifier must be returned versus one in which unlabeled test data is provided and the labels alone must be submitted. Similar techniques are often used for computers to solve these two closely-related problems if the test set is sufficiently large.