Local Image-to-Image Translation via Pixel-wise Highway Adaptive Instance Normalization

Abstract

Recently, image-to-image translation has seen a significant success. Among many approaches, image translation based on an exemplar image, which contains the target style information, has been popular, owing to its capability to handle multimodality as well as its suitability for practical use. However, most of the existing methods extract the style information from an entire exemplar and apply it to the entire input image, which introduces excessive image translation in irrelevant image regions. In response, this paper proposes a novel approach that jointly extracts out the local masks of the input image and the exemplar as targeted regions to be involved for image translation. In particular, the main novelty of our model lies in (1) co-segmentation networks for local mask generation and (2) the local mask-based highway adaptive instance normalization technique. We demonstrate the quantitative and the qualitative evaluation results to show the advantages of our proposed approach. Finally, the code is available at `https://github.com/WonwoongCho/Highway-Adaptive-Instance-Normalization`.

1 Introduction

Unpaired image-to-image translation (or in short, image translation) based on generative adversarial networks (Goodfellow et al., 2014) aims to transform an input image from one domain to another, without using paired data between different domains (Zhu et al., 2017; Liu et al., 2017; Kim et al., 2017; Choi et al., 2017; Liu et al., 2017). An unpaired setting, however, is inherently multimodal, meaning that a single input image can be mapped to multiple different outputs within a target domain. For example, when translating the hair color of a given image into a blonde color, the detailed hair region (e.g., upper vs. lower, and partial vs. entire) and color (e.g., golden, platinum, and silver) may vary.

Previous studies (Huang et al., 2018; Lee et al., 2018; Ma et al., 2018) have achieved such multimodal outputs by adding a random noise sampled from a pre-defined prior distribution. However, these approaches have a drawback of obtaining just a random output within the target domain, which is beyond ones control.

Other alternative approaches, including MUNIT (Huang et al., 2018) and DRIT (Lee et al., 2018), have taken a user-selected exemplar image as additional input, which contains the detailed information of an intended target style, along with an input image to translate (Huang et al., 2018; Lee et al., 2018; Ma et al., 2018; Chang et al., 2018; Lin et al., 2018). These approaches are typically built upon two different encoder networks separating (i.e., disentangling) content and style information of a given image.

However, existing exemplar-based image translation method has several limitations as follows. First, the style information is typically extracted and encoded from the entire region of a given exemplar, thus being potentially noisy due to those regions involved with respect to the target attribute to transfer. Suppose we translate the hair color of an image using an exemplar image. Since the hair color information is available only in the hair region of an image, the style information extracted from the entire region of the exemplar may contain the irrelevant information (e.g., color of the wall and edge pattern of the floor), which should not be reflected in the intended image translation.

(a) Intra-domain translation   (b) Inter-domain translation

Figure 1: Image translation settings. (a) Each domain $\mathcal{X}_i$ is defined as the subset of data that shares a particular attribute. An image from each domain $\mathcal{X}_i$ is decomposed into a content space $\mathcal{C}$, a foreground style space $\mathcal{S}^f$, and a background style space $\mathcal{S}_b$. After merging them, our model learns to reconstruct the original image. (b) For the cross domain translation $\mathcal{X}_1 \to \mathcal{X}_2$, our method combines a foreground style extracted from $\mathcal{X}_2$ with a content, background style code extracted from $\mathcal{X}_1$.

On the other hand, the extracted style is then applied to the entire region of the target image, even though particular regions should be kept as it is. Due to this limitation, some of the previous approaches (Huang et al., 2018; Lee et al., 2018) often distort irrelevant regions of an input image such as the background.

Furthermore, when multiple attributes are involved in an exemplar image, one has no choice but to impose all of them when translating a given image. For example, in a person's facial image translation, if the exemplar image has two attributes, (1) a smiling expression and (2) a blonde hair, then both attributes have to be transferred with no other options.

To tackle these issues, we propose a novel, local image translation approach that jointly generates a local, pixel-wise soft binary mask of an exemplar (i.e., the source region to extract out the style information from) and that of an input image to translate (i.e., the target region to apply the extracted style to). This approach has something in common with those recent approaches that have attempted to leverage an attention mask in image translation (Pumarola et al., 2018; Chen et al., 2018; Yang et al., 2018; Ma et al., 2018; Mejjati et al., 2018). In most approaches, the attention mask plays a role of determining the region to apply a translation.

Our main novelty is that in order to jointly obtain the local masks of two images, we utilize the co-segmentation networks (Rother et al., 2006), which aim (1) to extract the targeted style information without noise introduced from irrelevant regions and (2) to translate only the necessary region of a target image while minimizing its distortion. While co-segmentation approaches were originally proposed to capture the regions of a common object existing in multiple input images (Rother et al., 2006; Li et al., 2018), we adopt and train co-segmentation networks for our own purpose.

Once obtained local masks, our approach extends a recently proposed technique for image translation, called adaptive instance normalization, using highway networks (Srivastava et al., 2015), which computes the weighted average of the input and the translated pixel values using the above-mentioned pixel-wise local mask values as different linear combination weights per pixel location. Our proposed approach has an additional advantage of being able to manipulate the computed masks to selectively transfer an intended style, e.g., choosing either a hair region (to transfer the hair color) or a facial region (to transfer the facial expression).

The effectiveness of our approach is verified on two facial datasets, both qualitatively (through user study) and quantitatively (using the inception score).

2 Basic Setup

As shown in Fig. 1, we assume that an image x can be represented as $x = c \oplus s$, where c is a domain-invariant content code in a content space (e.g., pose of a face, location and shape of eyes, nose, mouth, and hair), s is a style code in a style space (e.g., facial expression, skin tone, and hair color), and the operator $\oplus$ combines and converts the content code c and the style code s into a complete image x.

By considering the local mask indicating the relevant region (or simply, the foreground) to extract the style from or to apply it to, we further assume that s is decomposed into $s = s_f \oplus s_b$, where s_f is the style code extracted from the foreground region and s_b is that from the background region. Separating a domain-invariant (integrated) style space $\mathcal{S}$ into a foreground style space $\mathcal{S}_f$ and a background style space $\mathcal{S}_b$ play a role of disentangling style feature representation.

The pixel-wise soft binary mask m of an image x is represented as a matrix with the same spatial resolution of x. Each entry of m lies between 0 and 1, which indicates the degree of the corresponding pixel belonging to the foreground. Then, the local foreground/background regions x^f/x^b of x is obtained as

$$x^f = m \odot x, \quad x^b = (1 - m) \odot x, \tag{1}$$

where $\odot$ is an element-wise multiplication. Finally, our assumption is extended to $x = c \oplus s_f \oplus s_b$, where c, s_f, and s_b are obtained by the content encoder E_c:, the foreground style encoder E_s^f, and the background style encoder E_s^b, respectively, which are all shared across multiple domains in our proposed model, i.e.,

$$\{c, s_f, s_b\} = \{E_c(x), E_s^f(x^f), E_s^b(x^b)\} \qquad c_x \in \mathcal{C}, s_x^f \in \mathcal{S}_f, s_x^b \in \mathcal{S}_b \tag{2}$$

It is critical in our approach to properly learn to generate the local mask involved in image translation. To this end, we propose to combine the mask generation networks with our novel highway adaptive instance normalization, as will be described in Section 3.2.

3 Local Image Translation Model

We first denote $x_1 \in \mathcal{X}_1$ and $x_2 \in \mathcal{X}_2$ as images from domains $\mathcal{X}_1$ and $\mathcal{X}_2$, respectively. As shown in Fig. 2, our image translation model converts a given image x_1 to $\mathcal{X}_2$ and vice versa, i.e., $x_{1\to2} = G(h(E_c(x_1), E_s^f(x_2^f), E_s^b(x_1^b)))$, and $x_{2\to1} = G(h(E_c(x_2), E_s^f(x_1^f), E_s^b(x_2^b)))$, where G is decoder networks and h is our proposed, local mask-based highway adaptive instance normalization (or in short, HAdaIN), as will be described in detail in Section 3.2.

For a brevity purpose, we omit the domain index notation in, say, $m = \{m_1, m_2\}$ and $x = \{x_1, x_2\}$, unless needed for clarification.

(a) The local masks, m_1 and m_2, are generated via the co-segmentation networks given both input images, x_1 and x_2. (b) Then we compute the hadamard product between an image x and the upsampled local mask m and $(1 - m)$ to result in foreground image x^f and the background image x^b, respectively. (c) Two encoders, foreground and the background style encoder E_s^f, E_s^b extract its style code s_f, s_b respectively from the corresponding foreground image x^f, background image x^b. HAdaIN then takes a content code c, background style code s_b from the target image (to be maintained), and a foreground style code s_f from the exemplar (to be translated). (d) G takes the output of HAdaIN and attempts to fool the discriminator as if the style of a generated image is the foreground style of the exemplar.

3.1 Local Mask Extraction

Our approach utilizes the local mask m to separate the image x into the foreground and the background regions, x^f and x^b. That is, we jointly extract the local masks of the input and the exemplar images, as those effectively involved in image translation, via co-segmentation networks. For example, given the input image and the exemplar, if our image translation model identifies the the hair color difference of a facial image, e.g., blonde vs. black, then, our local masks should be obtained as the hair regions from the two images.

Figure 2: Image translation workflow. (a) First, our model jointly generates masks for the input and the exemplar images through co-segmentation networks. (b) Next, we separate each image of x_1 and x_2 into the foreground and the background regions, depending on how much each pixel is involved in image translation. (c,d) By combining the content and the background style code from x_1 with the foreground style code x_2, we obtain a translated image output $x_{1 \rightarrow 2}$. Note that our method also learns the opposite-directional image translation $x_{2 \rightarrow 1}$ by interchanging x_1 and x_2. Finally, our model learns iamge translation using the cycle consistency loss from $\mathcal{X}_1 \rightarrow \mathcal{X}_2 \rightarrow \mathcal{X}_1$ and $\mathcal{X}_2 \rightarrow \mathcal{X}_1 \rightarrow \mathcal{X}_2$.

Figure 3: Local mask extraction via co-segmentation networks. The blue arrows indicate the forward propagation path in generating the mask m_2 of x_2, which relies on the global average pooled vector c_1^{attn} of the content activation map c_1. The local masks of two images are jointly computed in an inter-dependent manner so that their style codes are interchangeable.

As shown in Fig. 3, given two images x_1 and x_2, the co-segmentation networks first encode the content of each as c_1 and c_2 via the content encoder E_c. Next, in the case of computing the segmentation of x_2, after average-pooling c_1 globally, we forward it to an MLP to obtain the channel-wise soft binary mask c_1^{attn}, which is then multiplied with c_2 in a channel-wise manner, i.e., $c_1^{attn} \odot c_2$. This step works as transferring the objects information from x_1 to x_2. Finally, we forward-propagate this output into the attention network A to obtain the local mask m_2 of x_2, i.e., $m_2 = A(c_1^{attn} \odot c_2)$. The same process applies to the opposite case in a similar manner, resulting in $m_1 = A(c_2^{attn} \odot c_1)$.

Note that our co-segmentation networks are trained in an end-to-end manner with no direct supervision.

3.2 Highway Adaptive Instance Normalization

Adaptive instance normalization is an effective style transfer technique (Huang & Belongie, 2017). Generally, it matches the channel-wise statistics, e.g., the mean and the variance, of the activation map of an input image with those of a style image. In the context of image translation, MU-NIT (Huang et al., 2018) extends AdaIN in a way that the target mean and the variance are computed as the outputs of the trainable functions β and γ of a given style code, i.e.,

$$\text{AdaIN}_{x_1 \rightarrow x_2}(c_1, s_2) = \beta(s_2) \left(\frac{c_1 - \mu(c_1)}{\sigma(c_1)} \right) + \gamma(s_2), \tag{3}$$

As we pointed out earlier, such a transformation is applied globally over the entire region of an image, which may unnecessarily distort irrelevant regions. Hence, we formulate our local mask-based highway AdaIN (HAdaIN) as

$$\text{HAdaIN}_{x_1 \rightarrow x_2}(m_1, c_1, s_2^f, s_1^b) = m_1 \odot \text{AdaIN}_{x_1 \rightarrow x_2}(c_1, s_2^f) + (1 - m_1) \odot \text{AdaIN}_{x_1 \rightarrow x_1}(c_1, s_1^b), \tag{4}$$

where each of β and γ in Eq. (3) is defined as a multi-layer perceptron (MLP), i.e., $[\beta(s_f); \gamma(s_f)] = \text{MLP}_f(s_f)$ and $[\beta(s_b); \gamma(s_b)] = \text{MLP}_b(s_b)$. Note that we use different MLPs for the foreground and the background style code inputs. The first term of Eq. (4) corresponds to the local region of an input image translated by the foreground style, while the second corresponds to the complementary region where the original style of the input is kept as it is.

4 Training Objectives

This section describes each of our loss terms in the objective function used for training our model.

4.1 Style and Content Reconstruction Loss

The foreground style of the translated output should be close to that of the exemplar, while the background style of the translated output should be close to that of the original input image. We formulate this criteria as the following style reconstruction loss terms:

$$\mathcal{L}_{s_f}^{1 \rightarrow 2} = \mathbb{E}_{x_{1 \rightarrow 2}^f, x_2^f} \left[\| E_s^f(x_{1 \rightarrow 2}^f) - E_s^f(x_2^f) \|_1 \right] \tag{5}$$

$$\mathcal{L}_{s_b}^{1 \rightarrow 2} = \mathbb{E}_{x_{1 \rightarrow 2}^b, x_1^b} \left[\| E_s^b(x_{1 \rightarrow 2}^b) - E_s^b(x_1^b) \|_1 \right]. \tag{6}$$

From the perspective of content information, the content feature of an input image should be consistent with its translated output, which is represented as the content reconstruction loss as

$$\mathcal{L}_c^{1 \rightarrow 2} = \mathbb{E}_{x_{1 \rightarrow 2}, x_1} [\| E_c(x_{1 \rightarrow 2}) - E_c(x_1) \|_1]. \tag{7}$$

Note that the content reconstruction is imposed across the entire region of the input image, regardless of the local mask.

4.2 Image Reconstruction Loss

As an effective supervision approach in an unpaired image translation setting, we adopt the image-level cyclic consistency loss (Zhu et al., 2017) between an input image and its output through two consecutive image translations of $\mathcal{X}_1 \rightarrow \mathcal{X}_2 \rightarrow \mathcal{X}_1$ (or $\mathcal{X}_2 \rightarrow \mathcal{X}_1 \rightarrow \mathcal{X}_2$), i.e.,

$$\mathcal{L}_{cyc}^{1 \rightarrow 2 \rightarrow 1} = \mathbb{E}_{x_1} \left[\| x_{1 \rightarrow 2 \rightarrow 1} - x_1 \|_1 \right]. \tag{8}$$

Meanwhile, similar to previous studies (Huang et al., 2018; Lee et al., 2018), we translate not only $(x_1 \rightarrow x_{1 \rightarrow 2})$ but also $(x_1 \rightarrow x_{1 \rightarrow 1})$. This intra-domain translation $(x_1 \rightarrow x_{1 \rightarrow 1})$ should work similarly to auto-encoder (Larsen et al., 2015), and the corresponding loss term is written as

$$\mathcal{L}_x^{1 \rightarrow 1} = \mathbb{E}_{x_1} \left[\| x_{1 \rightarrow 1} - x_1 \|_1 \right] \tag{9}$$

4.3 DOMAIN ADVERSARIAL LOSS

To approximate the real-data distribution via our model, we adopt the domain adversarial loss by introducing the discriminator networks $D_s rc$. Among the loss terms proposed in the original GAN(Goodfellow et al., 2014), LSGAN(Mao et al., 2017), and WGAN-GP(Arjovsky et al., 2017; Gulrajani et al., 2017), we chose WGAN-GP, which is shown to empirically work best, as an adversarial method. That is, our adversarial loss is writtend as

$$\mathcal{L}_{adv}^{1\to2} = \mathbb{E}_{x_1}\left[D_{src}(x_1)\right] - \mathbb{E}_{x_{1\to2}}\left[D_{src}(x_{1\to2})\right] - \lambda_{gp}\,\mathbb{E}_{\hat{x}}[(\|\nabla_{\hat{x}}D_{src}(\hat{x})\|_2 - 1)^2], \qquad (10)$$

where $x_{1\to2} = G(h(c_1, s_2^f, s_1^b))$, $\hat{x}$ is a sampled value from the uniform distribution, and $\lambda_{gp} = 10$. Also, we apply the loss proposed in patchGAN (Isola et al., 2017; Zhu et al., 2017).

4.4 MULTI-ATTRIBUTE TRANSLATION LOSS

we use an auxiliary classifier (Odena et al., 2016) to cover multi-attribute translation with a single shared model, similar to StarGAN (Choi et al., 2017). The auxiliary classifier D_{cls}, which shares the parameters with the discriminator $D_s rc$ except for the last layer, classifies the domain of a given image. In detail, its loss term is defined as

$$\mathcal{L}_{cls_r}^{1\to2} = \mathbb{E}_{x_1}\left[-\log D_{cls}(y_{x_1}|x_1)\right] \qquad (11)$$

$$\mathcal{L}_{cls_f}^{1\to2} = \mathbb{E}_{x_{1\to2}}\left[-\log D_{cls}(y_{x_2}|x_{1\to2})\right], \qquad (12)$$

where y_x is the domain label of an input image x. Similar to the concept of weakly supervised learning (Zhou et al., 2016; Selvaraju et al., 2017), This loss term plays a role of supervising the local mask m to point out the proper region of the corresponding domain y through the HAdaIN module, allowing our model to extract out the style from its proper region of the exemplar.

4.5 MASK REGULARIZATION LOSSES

We impose several additional regularization losses on local mask generation to improve the overall image generation performance as well as the interpretability of the generated mask.

The first regularization is to minimize the difference of the mask values of those pixels that have similar content information. This helps the local mask consistently capture a semantically meaningful region as a whole, e.g., capturing the entire hair region even when the lightinig conditions and the hair color vary significantly within the exemplar. In detail, we design this regularization as minimizing

$$\mathcal{R}_1 = \mathbb{E}\left[\sum_{i=1,\cdots,W,j=1,\cdots,H}\left[|(m\cdot\vec{1}^T) - (\vec{1}\cdot m^T)|\odot(\hat{c}\cdot\hat{c}^T)\right]_{ij}\right] \qquad (13)$$

where $\vec{1}$ is a vector whose elements are all ones, $\{\vec{1}, m\}\in\mathbb{R}^{WH\times1}$, and $\hat{c}\in\mathbb{R}^{WH\times C}$ where $\hat{c} = \frac{c}{\|c\|}$. The first term is the distance matrix of all the pairs of pixel-wise mask values in m, and the second term is the cosine similarity matrix of all the pairs of C-dimensional pixel-wise content vectors. Note that we backpropagate the gradients generated by this regularization term only through m to train the co-segmentation networks, but not through $\hat{c}$, which does not affect our encoder E.

The second regularization is to make the local masks of the two images capture only those regions having contrasting styles. This regularization is useful especially when multiple attributes are involved in image translation. For example, if the two facial images have different hair colors but common facial expressions, then the local mask should indicate only the hair region. We formulate this regularization by minimizing the style difference between the local mask of two images, which is written as

$$\mathcal{R}_2 = -\mathbb{E}\left[\|s_1^f - s_2^f\|_1\right] \qquad (14)$$

The third regularization is simply to minimize the local mask region (Chen et al., 2018; Pumarola et al., 2018) to encourage the model to focus only on a necessary region involved in image translation, by minimizing

$$\mathcal{R}_3 = \mathbb{E}\,\|m\|_1 \qquad (15)$$

4.6 FULL LOSS

Finally, our full loss is defined as

$$\mathcal{L}_D = -\mathcal{L}_{adv} + \lambda_{cls}\mathcal{L}_{cls_r},$$
$$\mathcal{L}_G = \mathcal{L}_{adv} + \lambda_{cls}\mathcal{L}_{cls_f} + \lambda_{s,c}(\mathcal{L}_{s_f} + \mathcal{L}_{s_b} + \mathcal{L}_c) + \lambda_x(\mathcal{L}_{cyc} + \mathcal{L}_x^{1\to1} + \mathcal{L}_x^{2\to2}) \qquad (16)$$
$$+\lambda_1\mathcal{R}_1 + \lambda_2\mathcal{R}_2 + \lambda_3\mathcal{R}_3,$$

where $\mathcal{L}$ without superscript denotes $(1 \to 2, 2 \to 1)$, $\lambda_{cls} = 1$, $\lambda_{s,c} = 1$, $\lambda_x = 10$, $\lambda_1 = 0.1$, $\lambda_2 = 0.01$, and $\lambda_3 = 0.0001$. Note that our training process contains both intra-domain translation, $(x_1 \to x_{1\to1}$ and $x_2 \to x_{2\to2})$, and inter-domain translation, $(x_1 \to x_{1\to2}$ and $x_2 \to x_{2\to1})$.

5 IMPLEMENTATION

In this section, we discuss the model architecture and training details.

5.1 MODEL ARCHITECTURES

Content Encoder. Similar to MUNIT (Huang et al., 2018), our content encoder E_c is composed of two strided-convolutional layers and four residual blocks (He et al., 2016). Following the previous apporaches (Huang & Belongie, 2017; Nam & Kim, 2018), IN is used across all the layers in the content encoder.

Style Encoders. Our style encoders E_s^f, E_s^b have the same architecture but with different parameters. They consist of four strided-convolutional layers, a global average pooling layer, and a fully-connected layer. The style codes s_f, s_b are eight-dimensional vectors. Also, style encoders E_s^f, E_s^b share first few layers as the first few layers detect low-level feature. To maintain the style information, we do not use IN in the style encoders.

Co-segmentation Networks. Co-segmentation networks are composed of six convolutional layers with a batch normalization (Ioffe & Szegedy, 2015). MLP in Fig. 3 has two linear layers with tanh and sigmoid activation functions, respectively.

Decoder. Decoder G has four residual blocks and two convoultional layers with an upsampling layer each. Because the layer normalization (LN) (Ba et al., 2016) normalizes the entire feature map, maintaining the differences between the channels, we use LN in the residual blocks for stable training.

Discriminator. Following StarGAN (Choi et al., 2017), our discriminator D is composed of six strided-convolutional layers, followed by the standard discriminator and the auxiliary classifier.

5.2 TRAINING DETAILS

We utilize the Adam optimier (Kingma & Ba, 2014) with $\beta_1 = 0.5$ and $\beta_2 = 0.999$. Following the state-of-the-art approach (Choi et al., 2017) in multi-attribute translation, we load the data with a horizontal flip with 0.5 percentage5. For stable training, we update $\{E_c, E_s^f, E_s^b, G\}$ in every five updates of D (Gulrajani et al., 2017). We initialize the weights of D from a normal distribution and apply the initialization (He et al., 2015) on others. Also, we use a batch size of eight and the learning rate of 0.0001. We linearly decay the learning rate by half in every 10,000 iterations from 100,000 iterations. All the models used in the experiments are trained for 200,000 iterations using a single NVIDIA TITAN Xp GPU for 30 hours each.

6 EXPERIMENTS

We compare our model with other baselines mainly on two facial datasets, CelebA (Liu et al., 2015) and EmotioNet (Fabian Benitez-Quiroz et al., 2016). We first report the user study results to validate

the human-perceived quality of the translated results. Second, we evaluate the performances of our model using the inception score (Salimans et al., 2016) and the classification accuracy. Third, we present the qualitative comparisons of both multi- and single-attribute translation results against baseline methods. Lastly, we show the 2D embeddig results of the content and the style codes to verify the effectiveness of our model.

6.1 DATASETS

CelebA. The CelebA dataset consists of 202,599 face images of celebrities and 40 attribute annotations per image. We pick 10 of all attributes (i.e., black_hair, blond_hair, brown_hair, smiling, goatee, mustache, no_beard, male, heavy_makeup, wearing_lipstick) that would convey meaningful local masks. We randomly select 2,000 images for testing and use the others for training. Images are center-cropped and scaled down to 128128.

EmotioNet. The EmotioNet dataset contains 975,000 URLs for images of facial expressions in the wild, each annotated with 12 Action Units. We crop faces in the images using a face detector [1] and resize them to 128128. We use 2,000 images for testing and 200,000 images for training.

6.2 BASELINE METHODS

MUNIT. MUNIT (Huang et al., 2018) decomposes an image into the domain-invariant content code and the domain-specific style code. Involving random sampling for latent style codes while training, MUNIT attempts to reflect the multimodal nature of various style domains. We implement MUNIT to be trained on facial datasets and report results for our comparison.

DRIT. DRIT (Lee et al., 2018) employs two encoders of which each extracts the domain-invariant content information and domain-specific style information, respectively. The model is trained using the content discriminator that integrates the content code. It is shown to guarantee the content code to have domain-invariant information. Loss functions and training processes are largely similar to MUNIT.

6.3 QUALITATIVE RESULTS

We report qualitative results in Fig. 5. The first four rows correspond to input images, their generated masks, exemplar images, and their generated masks. Each of the last three rows provides comparisons between our model and the baselines. The bottommost labels denote class names for each column. We denote Facial Hair when belonging to any of the three classes, Beard, Goatee or Mustache. Class labels in red indicates that both of the former two classes are applied. Our LOMIT tends to keep the background intact across various classes, while transferring adequate attributes from the exemplar images. With compared to our LOMIT, the other two models suffer from either some undesirable distortion in the background or severe quality degradations when multiple attributes are transferred, which justifies our initial motivations.

6.4 QUANTITATIVE RESULTS

2D Embedding Analysis. We encode 2,000 test images to extract the content code c, foreground style code s_f, and background style code s_b for the three hair attributes. Figs. 6(a)-(c) visualize each of them in a separate, two-dimensional space using t-SNE (Maaten & Hinton, 2008). Foreground style codes are shown to form meaningful clusters on each of the hair attributes (Figs. 6(b)). On the contrary, the content codes $\mathcal{C}$ (Figs. 6(a)) and background style codes $\mathcal{S}_b$ (Figs. 6(c)) do not exhibit noticeable clusters with respect to hair colors, which is consistent with our intuition that the hair color is the foreground style of interest.

User Study. To evaluate the effectiveness of the proposed method, we conduct a user study composed of two AB tests. In the first test we evaluate how realistic translated images of each model are. Each time participants are shown a pair of images, composed of a real image and a translated

---

[1]`https://github.com/ageitgey/face_recognition`

Figure 4: Comparison with the baselines on CelebA dataset.

Figure 5: The result of Action Unit translation using EmotioNet dataset. In each section, the first, the third, and the last iamges are an input image, an exemplar image, and a translated output, respectively.

Figure 6: t-SNE visualization of the content code c and foreground, background style code s_f, s_b. Note that only the foreground style code agrees with the class information.

(a) **(b)**

Model	Realism Rate (%)
DRIT	12.3
MUNIT	11.5
LOMIT	25.6

■ LOMIT ■ DRIT ■ MUNIT

Q1 Which one has better applied the style to the image? **(%)**

| 67.7 | 32.3 |
| 66.3 | 33.7 |

Q2. Which one has better kept the background unchanged?

| 95.7 | 4.3 |
| 96.7 | 3.2 |

Figure 7: User study results. (a) (b)

Class	DRIT			MUNIT			LOMIT		
	IS		CA	IS		CA	IS		CA
	Mean	Std	(%)	Mean	Std	(%)	Mean	Std	(%)
Facial Hair	**0.3295**	0.24	23.8	0.1804	0.29	60.0	0.3105	0.27	**71.4**
Gender	**0.2703**	0.21	11.1	0.0514	0.11	50.7	0.2348	0.22	**83.9**
Wearing Lipstick	**0.2685**	0.20	19.9	0.2171	0.21	70.9	0.2528	0.20	**73.7**
Facial Hair + Gender	**0.3805**	0.24	14.3	0.0144	0.04	33.0	0.2069	0.23	**68.1**
Makeup + Wearing Lipstick	**0.2853**	0.21	16.1	0.2402	0.23	71.8	0.2834	0.22	**72.8**

Table 1: Comparisons for Inception Score (IS) and Classification Accuracy (CA)

image, from which to choose one that looks more realistic. The second test also involves a pair of translated images from two different models. Given a certain question, users chose one that answers the question best. The superior Realism Rate of LOMIT reported in Fig. 7 (a) indicates that the translated results based on our model look more natural in human eyes. Given specific questions such as Q1 or Q2 as in Fig. 7 (b), users confirm that our model not only applies exemplar styles better, but also maintains the background region unaffected.

Inception score and classification accuracy. Inception score is higher if translated images are diverse and of high quality. We compare our models with the baselines using an inception score (IS) (Salimans et al., 2016) and classification accuracy (CA). For the classification, We use the pretrained Inception-v3 (Szegedy et al., 2016) and fine-tune with celebA (Liu et al., 2015) dataset, following (Huang et al., 2018). To be classified well with high accuracy, a translated image must have attributes in the examplar. Table 1 lists the resulting scores and accuracies. In terms of the CA, LOMIT achieves the highest across all classes evaluated by large margins. DRIT achieves slightly higher IS than LOMIT, but in the cost of the CA. It indicates that DRIT produces diverse outputs, however with less recognizable image outputs.

7 CONCLUSION

In this works, we propose the novel highway adaptive instance normalization which can raise the performance of exemplar based image translation using a local mask. Our model achieves outstanding results comparing with state of the art (Huang et al., 2018; Lee et al., 2018). Also, we verify our models through both qualitative and quantitative results. As a future work, we will expand our module which can be used as a general normalization method.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *ICML*, pp. 214–223, 2017.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Huiwen Chang, Jingwan Lu, Fisher Yu, and Adam Finkelstein. Pairedcyclegan: Asymmetric style transfer for applying and removing makeup. In *CVPR*, 2018.

Xinyuan Chen, Chang Xu, Xiaokang Yang, and Dacheng Tao. Attention-gan for object transfiguration in wild images. *arXiv preprint arXiv:1803.06798*, 2018.

Yunjey Choi, Minje Choi, Munyoung Kim, Jung-Woo Ha, Sunghun Kim, and Jaegul Choo. Stargan: Unified generative adversarial networks for multi-domain image-to-image translation. *arXiv preprint*, 1711, 2017.

C Fabian Benitez-Quiroz, Ramprakash Srinivasan, and Aleix M Martinez. Emotionet: An accurate, real-time algorithm for the automatic annotation of a million facial expressions in the wild. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5562–5570, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NIPS*, pp. 2672–2680, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *NIPS*, pp. 5767–5777, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *ICCV*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.

Xun Huang and Serge J Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *ICCV*, pp. 1510–1519, 2017.

Xun Huang, Ming-Yu Liu, Serge Belongie, and Jan Kautz. Multimodal unsupervised image-to-image translation. *arXiv preprint arXiv:1804.04732*, 2018.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. *arXiv preprint*, 2017.

Taeksoo Kim, Moonsu Cha, Hyunsoo Kim, Jung Kwon Lee, and Jiwon Kim. Learning to discover cross-domain relations with generative adversarial networks. *arXiv preprint arXiv:1703.05192*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. *arXiv preprint arXiv:1512.09300*, 2015.

Hsin-Ying Lee, Hung-Yu Tseng, Jia-Bin Huang, Maneesh Kumar Singh, and Ming-Hsuan Yang. Diverse image-to-image translation via disentangled representations. *arXiv preprint arXiv:1808.00948*, 2018.

Weihao Li, Omid Hosseini Jafari, and Carsten Rother. Deep object co-segmentation. *arXiv preprint arXiv:1804.06423*, 2018.

Jianxin Lin, Yingce Xia, Tao Qin, Zhibo Chen, and Tie-Yan Liu. Conditional image-to-image translation. In *CVPR*, 2018.

Ming-Yu Liu, Thomas Breuel, and Jan Kautz. Unsupervised image-to-image translation networks. In *NIPS*, pp. 700–708, 2017.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *ICCV*, pp. 3730–3738, 2015.

Liqian Ma, Xu Jia, Stamatios Georgoulis, Tinne Tuytelaars, and Luc Van Gool. Exemplar guided unsupervised image-to-image translation. *arXiv preprint arXiv:1805.11145*, 2018.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *JMLR*, 9(Nov):2579–2605, 2008.

Xudong Mao, Qing Li, Haoran Xie, Raymond YK Lau, Zhen Wang, and Stephen Paul Smolley. Least squares generative adversarial networks. In *ICCV*, pp. 2813–2821. IEEE, 2017.

Youssef A Mejjati, Christian Richardt, James Tompkin, Darren Cosker, and Kwang In Kim. Unsupervised attention-guided image to image translation. *arXiv preprint arXiv:1806.02311*, 2018.

Hyeonseob Nam and Hyo-Eun Kim. Batch-instance normalization for adaptively style-invariant neural networks. *arXiv preprint arXiv:1805.07925*, 2018.

Augustus Odena, Christopher Olah, and Jonathon Shlens. Conditional image synthesis with auxiliary classifier gans. *arXiv preprint arXiv:1610.09585*, 2016.

Albert Pumarola, Antonio Agudo, Aleix M Martinez, Alberto Sanfeliu, and Francesc Moreno-Noguer. Ganimation: Anatomically-aware facial animation from a single image. *arXiv preprint arXiv:1807.09251*, 2018.

Carsten Rother, Tom Minka, Andrew Blake, and Vladimir Kolmogorov. Cosegmentation of image pairs by histogram matching-incorporating a global constraint into mrfs. In *CVPR*, volume 1, pp. 993–1000. IEEE, 2006.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *NIPS*, pp. 2234–2242, 2016.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, Dhruv Batra, et al. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *ICCV*, pp. 618–626, 2017.

Rupesh Kumar Srivastava, Klaus Greff, and Jürgen Schmidhuber. Training very deep networks. In *NIPS*, pp. 2377–2385, 2015.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *CVPR*, pp. 2818–2826, 2016.

Chao Yang, Taehwan Kim, Ruizhe Wang, Hao Peng, and C-C Jay Kuo. Show, attend and translate: Unsupervised image translation with self-regularization and attention. *arXiv preprint arXiv:1806.06195*, 2018.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *CVPR*, pp. 2921–2929, 2016.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. *arXiv preprint*, 2017.

Figure 8: Diverse translation result. The first row is the target image, the third row is the exemplar. the last row is the generated result. Reflecting the foreground style from the exemplar, our model can generate diverse outputs.

Figure 9: Additional result. First row is the target image, second row is the exemplar, third row is a translated result. Note that the translated attributes are Facial Hair and gender.

Figure 10: Additional result. First row is the target image, second row is the exemplar, third row is a translated result. Note that the translated attributes are Facial Hair and gender.

Figure 11: Additional result. First row is the target image, second row is the exemplar, third row is a translated result. Note that the translated attributes are Facial Hair and gender.