A MULTI-MODAL ONE-CLASS GENERATIVE ADVERSARIAL NETWORK FOR ANOMALY DETECTION IN MANUFACTURING

ABSTRACT

One class anomaly detection on high-dimensional data is one of the critical issue in both fundamental machine learning research area and manufacturing applications. A good anomaly detection should accurately discriminate anomalies from normal data. Although most previous anomaly detection methods achieve good performances, they do not perform well on high-dimensional imbalanced dataset 1) with a limited amount of data; 2) multi-modal distribution; 3) few anomaly data. In this paper, we develop a multi-modal one-class generative adversarial network based detector (MMOC-GAN) to distinguish anomalies from normal data (products). Apart from a domain-specific feature extractor, our model leverage a generative adversarial network(GAN). The generator takes in a modified noise vector using a pseudo latent prior and generate samples at the low-density area of the given normal data to simulate the anomalies. The discriminator then is trained to distinguish the generate samples from the normal samples. Since the generated samples simulate the low density area for each modal, the discriminator could directly detect anomalies from normal data. Experiments demonstrate that our model outperforms the state-of-the-art one-class classification models and other anomaly detection methods on both normal data and anomalies accuracy, as well as the F1 score. Also, the generated samples can fully capture the low density area of different types of products.

1 INTRODUCTION

Anomaly detection is one of the fundamental problems in machine learning, with critical applications in many industrial areas, e.g., manufacturing anomaly detection where it ensures a product meets all standards and requirements, fraud detection citepzheng2018one where it discriminate a vandal user from normal users, and etc. Failure to discriminate anomalies would incur a huge cost. Compared with supervised based anomaly detection methods where simulated data sample (Nakazawa & Kulkarni, 2018), or a plethora of perfectly labeled data are available (Lee et al., 2017; He & Wang, 2007), we focus on the anomaly detection problem that detects if a new data sample follows a known normal data distribution with high confidence, i.e. resides in high probability density area, or not. This is also known as novelty detection problem (Pimentel et al., 2014). Plenty of works have been done in this area. There are generally three directions: 1) density estimation methods 2) reconstruction loss based methods 3) one-class classification. These methods present strong performances on various dataset and tasks.

Different from most existing anomaly detection problem, e.g. (Rayana & Akoglu, 2015; Stolfo et al., 2000; McAuley & Leskovec, 2013; Wienke et al., 2016; Poll et al., 2007), in the area of most practical manufacturing industry, we usually suffers from inadequate amount of normal and anomaly data. More specifically, the anomaly detection task in manufacturing features: 1) a limited amount of data samples since labeling is expensive; 2) imbalanced dataset with less than 1% anomalies since most products pass the quality check; 3) multi-modal, diverse distribution due to different types, settings of products; and 4) high dimensional time-series data samples that record the production processes. An example of normal and anomaly data samples are shown in Figure 1.

Figure 1: Low dimensional representations for samples from the manufacturing production dataset using principal component analysis (PCA): (1) each data sample denotes a piece of product that has 63 sensors for 314 time-steps each, (2) the red/blue points are non-pass/pass products respectively, (3) there exists several differ-ence clusters of products. (4) the non-pass data samples are very close the to the pass data samples.

Thus, in this paper, to overcome these challenges, we propose to use the multi-modal one-class generative adversarial network (MMOC-GAN) to address the aforementioned challenges. The primary idea to capture the distribution of different modal of data samples, and generate different possible outliers for these different modals using only the normal samples as the training dataset. A similar work could be found in one-class adversarial nets (OCAN) (Zheng et al., 2018) . Their idea is to generate a malicious user with only given benign users by using generative adversarial networks. However, directly using this model is not desired since we have a very limited amount of data samples for several different modals. To handle these challenges: 1) Firstly, we apply a domain-specific pretrained feature extractor to reduce the high-dimensional time-series sensory data into low-dimension space. 2) Secondly, our MMOC-GAN leverage a modified GAN model. In the GAN model, instead of taking a noise sampled from a fixed distribution, the generator takes in a modified noise vector using given pseudo prior information (a latent code) to generate samples that are complementary to the distribution of the normal data samples. We expect the generator could generate the complementary data samples for different modals by adding this latent code. 3) The discriminator takes in the normal data and the generated complementary data samples and is trained to discriminate the normal data samples from generated data samples. Since the generated complementary data samples approximate the low-density distribution of the normal data samples, we expect the discriminator could tell normal data samples and anormalies for different types of products. Therefore the challenges mentioned previously can be minimized by 1) complementary GAN to better distinguish normal data and anomalies; 2) one-class training that does not require anomaly data samples; 3) adding pseudo-prior information to generate data samples for each modal; and 4) the domain-specific feature extractor accordingly. The property of MMOC-GAN method makes it applicable to anomaly detection in the practical manufacturing industry.

The experiment on our manufacturing production dataset demonstrates that MMOC-GAN has superior performance over several types of the anomaly detection methods. Additionally, we observe that the generator could successfully generate complementary data samples for each existing modals.

The rest of the paper is organized as follows: the related work is shown in section 2. A review of GAN is given in section 3. We then describe our model MMOC-GAN in section 4. The experimental result is shown in section 5. We then conclude the paper in section 6.

2 RELATED WORK

Lots of efforts have been done in the anomaly detection area. There are primarily three directions: 1) density estimation methods 2) reconstruction loss based methods 3) one-class classification (Pimentel et al., 2014).

Density estimation methods are primarily based on clustering analysis, such as the Gaussian mixture model (GMM) (Markou & Singh, 2003; Lauer, 2001). However, it is hard to apply these methods directly on high-dimensional data. Therefore, various methods adopt a two-stage approach that reduces the dimension of data as the first step and then uses the density estimation method for anomaly detection as the second step (Chandola et al., 2009; Sabahi & Movaghar, 2008). However, the two-stage approach has multiple drawbacks. Recently, an end-to-end deep auto-encoding Gaussian mixture model (DAGMM) (Zong et al., 2018) model is proposed that combines a compression

network to extract latent feature and an estimation network using latent feature and reconstruction loss to estimate the sample density.

Reconstruction loss based methods assume that anomaly data samples cannot be reconstructed from low-dimensional space (Shyu et al., 2003; Sakurada & Yairi, 2014). Many recent works presented to use the reconstruction loss by auto-encoder (Marchi et al., 2015), variational auto-encoder (An & Cho, 2015), as well as generative adversarial network based reconstruction loss (Schlegl et al., 2017). These works demonstrate a promising result. However, this assumption does not hold in every case. As shown in Figure 2, most of the anomalies have similar reconstruction loss as the normal data samples. This might due to that production process of anomalies and normal samples in the dataset are very similar.

Figure 2: Distribution of reconstruction loss by using anomaly GAN (ANOGAN) (Schlegl et al., 2017) method. The X-axis is the reconstruction loss. The Y-axis is the percentage. Blue is pass data and orange is non-pass data.

One class classification method tries to build a classifier using only one class of data samples, i.e. normal data samples. This method learns a discriminative boundary surrounding the normal instances thus to detect anomalies (Chen et al., 2001; Zhang et al., 2006). One-class support vector machine (OC-SVM) is one of the widely adopted methods that construct a decision hyper-plane around the normal sample (Erfani et al., 2016). However, OC-SVM usually suffers from the curse of dimensionality. One class neural network (OCNN network) is an end-to-end method that is developed based on OC-SVM (Chalapathy et al., 2018). It combines a neural network to learn the latent distribution and use the objective function similar to SVM, thus, to detect anomalies. Also, some other distance-based methods have extended to this category as well. One class nearest neighbor (OCNN neighbor) has also been used to predict the anomalies based on the distance to its nearest neighbors (Janssens, 2013; Zhao & Saligrama, 2009). In some other works, the discriminator in the GAN model has also been used as an anomaly detector (Zenati et al., 2018; Sabokrou et al., 2018). One class adversarial network is recently developed based on the GAN model by using LSTM auto-encoder to compress the data and the complementary GAN to learn the possible distribution of anomaly data (Zheng et al., 2018).

Most of these methods performs well on most of the dataset. However, in our case, there exists multiple modal in the distributions over data samples from different types, as well as different production time, which might related to production equipment settings over time. According to the characteristic of our dataset, we develop our algorithm MMOC-GAN based on the one class classification method. Based on our knowledge, this is the first one-class classification model for multi-modal distributions anomaly detection.

3   BACKGROUND INFORMATION

3.1   GENERATIVE ADVERSARIAL NETWORK

Generative adversarial networks (GANs) (Chen et al., 2016; Goodfellow et al., 2014) have recently received a lot of attention. It is a framework for training deep generative models using mini-max optimization. A GAN framework consists of two components, a generator G and a discriminator D. In practice, these two components are usually multi-perceptron neural networks. The generator generates fake samples x_G from a noise vector z sampled from a prior distribution p_z, i.e. $x_G = G(z)$. G is trained to learn a distribution p_G that matches the real data distribution p_d. In other word, we try to maximize the $p_d(x_G)$.

The discriminator D is a binary classifier that takes in a sample x as input and output the probability that it is a real data or a generated fake data from $x_G = G(z)$. Thus, D acts as a detector to estimate to the probability that a sample is from the real data distribution.

The G and D are trained adversarially as competitors to each other by alternatively training G and D. G tries to fool D by making D predicts samples x_G generate by G is real. This is achieved by optimize the following objective function of G:

$$\min_G \mathbb{E}_{z \sim p_z} \left[\log \left(1 - D \left(G(z) \right) \right) \right] \tag{1}$$

On the contrary, D tries to minimize the chance that it being fooled by maximizing the probability that it predict the real data x is real and minimizing the probability that the generated data $G(z)$ is real:

$$\max_D E_{x \sim p_d} \left[\log \left(x \right) \right] + E_{z \sim p_z} \left[\log \left(1 - D \left(G(z) \right) \right) \right] \tag{2}$$

The GAN model is thus formalized as a mini-max problem with the following objective:

$$\min_G \max_D V(D, G) = E_{x \sim p_d} \left[\log \left(x \right) \right] + E_{z \sim p_z} \left[\log \left(1 - D \left(G(z) \right) \right) \right] \tag{3}$$

The GAN model theoretically aims to minimize the Jensen-Shannon (JS) divergence between the data distribution P_d and the generated distribution P_G. The minimization of JS divergence is achieved when $p_D(G(z)) = p_d(x)/(p_d(x) + P_G(x))$ that the generated samples are indistinguishable from real data samples. Therefore, the GAN model captures the distribution of the real data.

4 METHODOLOGY

4.1 OVERVIEW

The generator G in the GAN model uses a simple noise vector z as input, and maps it to a complicated data distribution x_G. This mapping requires a generator that disentangle the underlying factors of variations in the data distribution and enables multi-modal diversity. However, in practice, regular GAN is known to have the model collapse problems (Salimans et al., 2016; Berthelot et al., 2017). This is not desired in our case, where there are multiple modals of distributions in the dataset, as shown in Figure 1. To detect anomalies for all product types, it is natural to decompose this into a set of meaningful factors of variations by injecting prior information, i.e. have the generator generate data samples for each modal. The idea of adding prior information can be found in various works as well (Chen et al., 2016; Gurumurthy et al., 2017). Thus, our G takes in both noise vector z and prior information.

The discriminator D is used to detect the anomalies from the normal data. Different from regular GAN, our generator G tries to generate complementary data samples which lies in the low density region of the normal data samples. The discriminator tries to separate the normal data samples and the generated complementary data samples, which should give itself the capability to detect anomalies from normal data samples since they are in the low-density region.

The overall framework of our method can be found in Figure 3.

4.2 PRIOR INFORMATION SELECTION

For the anomaly detection problem in manufacturing, it is natural to divide the data-set by using the potentially different modals (distributions/product types). We hope to generate data samples without any supervision simply by using a categorical latent variable to represent a potential distribution. We denote the latent variable by $c \in 1, 2, , m$, where m is the number of clusters. The latent variable for a data sample x is c_x.

To generate a data point, we adopt a new generator function $\hat{x} = G(\phi(z, c_x))$, that takes in both noise vector z and the latent variable c_x. We expect that $\hat{x}$ be in the same data space $\mathcal{H}$ and falls to the same modal as x. ϕ is a feature construction function. In this paper, we attempt two different feature construction function $\phi(z, c_x)$. The first feature function is direct concatenation:

$$\phi_{\text{cat}}(z, c_x) = \text{cat}(z, \text{one\_hot}(c_x)) \tag{4}$$

Figure 3: The generator takes in both noise vector and the prior information to generate a complementary sample. The discriminator takes in a generated sample and real data samples and output the probability if its real or not as well as the probability of the prior information.

where one_hot is the one-hot encoding function. The second one reparameterizes the noise vector z as Gaussian model. Each modal distribution follows a Gaussian model distribution. We denote this function as ϕ_{mix}:

$$\phi_{\text{mix}}(z, c_x) = \mu_{c_x} + \sigma_{c_x} z \tag{5}$$

where μ_{c_x} and σ_{c_x} are the mean and standard deviation of the Gaussian distribution. To avoid the collapse of the variance in the variance of each Gaussian model, a regularizer is adopted (Gurumurthy et al., 2017):

$$L_\sigma = \lambda \sum_{i=1}^{m} \frac{(1 - \sigma_{c_i})^2}{m} \tag{6}$$

where λ is a hyper-parameter. The mutual information $I(X, Y)$ measures the reduction of uncertainty in X when Y is observed (Chen et al., 2016). In this paper, the mutual information loss is defined as following:

$$L_{MI} = -E_{(c_x \sim p(c|\hat{x}), \hat{x} \sim G(\phi(z, c_x)), c_x \sim Q(c|x), x \sim p_d}[\log Q(c_{\hat{x}}|\hat{x}) + H(c_x)] \tag{7}$$

where Q is the auxiliary distribution that is used to approximate $p(c|x)$; H is the entropy function. Here, we also use the auxiliary distribution Q to sample the prior information that is provided to the generator.

4.3 COMPLEMENTARY GAN

Unlike the generator in regular GAN to approximate the distribution of normal data sample's distribution p_d, the generator G in complementary GAN learns a distribution p_G that close to the complementary distribution p^* (Zheng et al., 2018). More specifically, the generator tries to learn the distribution of samples of the outlier region of p_d, i.e. the low density areas distribution:

$$p^*(\hat{x}) = \begin{cases} \frac{1}{\tau p_d(\hat{x})}, & \text{if } p_d \geq \epsilon \\ C, & \text{if } p_d \leq \epsilon \end{cases}$$

where ϵ is the threshold to decide if the generated samples are in the high-density area or not. τ is a normalization constant; and C is a small constant. To learn the complementary distribution, the objective function is defined by using KL divergence. Since the τ and C are both constant, we omit them in the objective function as following:

$$L_{KL}(p_G \parallel p^*) = H(p_G) - E_{\hat{x} \sim p_G} \log p_d(\hat{x}) \, \mathbb{1}[p_d \geq \epsilon] \tag{8}$$

To ensure the generated samples are in the same space of the data samples $\mathcal{H}$, the feature matching loss is adopted as well (Salimans et al., 2016).

$$L_{fm} = E_{x \sim p_d} = [\| E_{x \sim p_G} f(\hat{x}) - f(x) \|_2^2] \tag{9}$$

where f is the hidden layer of the discriminator. However, estimate the p_data is expensive. A target network T is applied to detect the data distribution p_d

The entropy $H(p_G)$ is approximated by the pull-away loss that encourages the diversity of generated data samples (Zhao et al., 2016). The PT term is as following:

$$L_{pt} = \frac{1}{N(N-1)} \sum_{i}^{N} \sum_{j \neq i}^{N} \left(\frac{f(\hat{x}_i)(\hat{x}_j)}{\| \hat{x}_i \| \| \hat{x}_j \|} \right) \tag{10}$$

where N is the number of samples in a mini-batch. Thus, the overall objective function of the generator is as following:

$$L_G = \begin{cases} L_{fm} + L_{pt} + L_{KL} + L_{MI}, & \text{if use } \phi_{\text{cat}} \\ L_{fm} + L_{pt} + L_{KL} + L_{\sigma} + L_{MI}, & \text{if use } \phi_{\text{mix}} \end{cases}$$

The discriminator in the complementary GAN detects if a sample follows the real data distribution p_d or the generated distribution p_G by the generator. Here, since the generated distribution p_G is trained to capture the complementary data distribution p^*. The generator is thus used as a proxy to generate the low-density area data. The discriminators objective function is as following:

$$L_D = E_{x \sim p_d}[\log(D(x))] + E_{z \sim p_z, c_x \sim Q(c|x), x \sim p_d}[\log(1 - D(G(z, c_x)))] + E_{x \sim p_d}[H(D(x))] \quad (11)$$

The last term is to further push the decision boundary of discriminator toward the normal data samples with higher confidence. This would increase the false positive rate since the discriminator might classify some normal data samples as anomalies. However, this is desired in practice, e.g., since we hope to deliver only the pass product to customers.

5 EXPERIMENT

5.1 EXPERIMENT SETUP

5.1.1 DATASET

Our dataset is collected from one of Samsungs production lines in 2018. The dataset is limited and imbalance that contains 3936 pass products and 22 non-pass products. Each data sample is a multi-dimensional time-series data sample, composed of 63 channel sensor inputs for 314-time steps. We extract the features of the data samples into a feature vector $x \in mathbbR^{280}$ with the length of 280 by using a domain specific pre-trained feature extractor. The hyperparameter of our model could be found in Appendix.

5.1.2 BASELINE

To verify the effectiveness of our method, we compare our MMOC-GAN with several widely used anomaly detection methods including: 1) One class nearest neighbors (OCNN neighbor) (Zhao & Saligrama, 2009); 2) One class support vector machine (OCSVM) (Chen et al., 2001); 3) One class neural network (OCNN network) (Chalapathy et al., 2018); 4) Gaussian mixture model (GMM) (Chandola et al., 2009); 5) Robust deep auto-encoder (RDA) (Zhou & Paffenroth, 2017); 6) Deep auto-encoder Gaussian mixture model (DAGMM) (Zong et al., 2018); 7) Anomaly GAN (ANOGAN) (Schlegl et al., 2017); 8) Regular GAN (RGAN); and 9) One class adversarial network (OCAN)(Zheng et al., 2018).

Note that some of these methods require using part of the anomaly data for threshold tuning. In this work, for each fold, we fine-tune the threshold by using all non-pass product and still use all non-pass product for testing for all folds, which should greatly improve the performance of these baseline methods (each fold has a specific threshold value). Our method, in contrast, does not require such tuning and directly use the output of the discriminator as the detection result. The input to all methods are the extracted features using the domain-specific feature extractor. Note that simply using 1) raw time series features, or 2) the latent features from a trained deep auto-encoder using the raw time series signals as input to all anomaly detection models generates very low performances. Thus, we dont even include them for comparison in the paper.

Table 1: The result of different methods. Raw train only using the training dataset. Fine tune means using the test dataset to fine-tune the threshold.

Methods	Pass acc.	Non-pass Acc.	Acc.	F1 Score	Note
OCNN neighbor	$90.8 \pm 5.0\%$	$92.1 \pm 16.2\%$	91.0%	0.95	Fine tune
OCSVM	$97.9 \pm 1.1\%$	$26.3 \pm 41.4\%$	95.2%	0.97	Fine tune
OCNN network	$78.8 \pm 1.1\%$	$23.6 \pm 18\%$	77.3%	0.87	Fine tune
GMM	$63.6 \pm 9.6\%$	$16.3 \pm 11.4\%$	62.3%	0.76	Fine tune
DAGMM	$86.6 \pm 6.7\%$	$76.4 \pm 14.8\%$	86.3%	0.92	Fine tune
RDA	$69.3 \pm 8.3\%$	$39.4 \pm 12.7\%$	68.4%	0.81	Fine tune
ANOGAN	$60.6 \pm 8.4\%$	$51.3 \pm 17.2\%$	60.3%	0.73	Fine tune
RGAN	$94.3 \pm 1.3\%$	$9.3 \pm 4.7\%$	92.0%	0.95	Fine tune
OCAN	$91.8 \pm 1.1\%$	$100 \pm 0\%$	92.0%	0.97	Fine tune
OCAN	$94.5 \pm 1.5\%$	$89.1 \pm 13.9\%$	94.3%	0.97	Raw
MMOCGAN_cat	$96.4 \pm 0.5\%$	$100 \pm 0\%$	96.5%	0.98	Raw
MMOCGAN_mix	$90.3 \pm 2.1\%$	$100 \pm 0\%$	90.5%	0.97	Raw

Table 2: Influence of number of clusters on the MMOCGAN concatenation model

Number of classes	P Acc.	NP Acc.	F1 Score	AUROC
1	93.1%	86.9%	0.96	95.3
5	95.0%	94.5%	0.97	96.4
10	96.4%	100%	0.98	97.5
20	94.8%	100%	0.97	97.2

5.2 RESULT

The means and variances of the pass product accuracy, non-pass product accuracy, and the F1 score for five-fold experiments are reported in Table 1. The primary measurements that the company values most are the pass product accuracy and the non-pass product accuracy.

First, our MMOCGAN obtains the highest performance than other baseline methods in all measurements including pass accuracy, non-pass accuracy, and F1 score. Most of these baselines fail in this practical task. This shows the effectiveness of our method for anomaly detection in the practical manufacturing production line. Note that some of the methods have a high overall accuracy and f1 score. However, this is because they predict all samples as pass product for this imbalanced dataset, which is not desired in our task. Second, our method is relatively stable across five-fold cross-validation. Note that the OCAN method also provides high F1 score, however, the pass product accuracy and the non-pass product accuracy is limited. The variance of the accuracy of OCAN is higher than other methods, this is primarily due to the multi-modal distribution and instability of GAN training. Also, despite OCAN is a one-class model, fine-tuning is also required. Thus, our method shows superior performance over other methods in this practical task.

6 DISCUSSION

In our MMOCGAN model, the generator generates complementary samples that lie in the low-density area and the discriminator distinguishes the pass product from the generated samples. The probability of pass product, generated complementary samples, and non-pass product predicted by the discriminator of the GAN model is presented in Figure 4. We can see that our model converges around 200 epochs. The probability that non-pass product keeps decreasing during the training, which shows that the generated complementary data samples successfully help to detect different anomalies.

We use our generator to generate some complementary samples for both MMOCGAN model. The data samples are projected into a 2d space using the t-SNE method as shown in Figure 5. We can see

Figure 4: The training curve of our MMOCGAN model. The probability of non-passed product keeps decreasing all the time. The distribution is relatively stable.

our method successfully generate samples between passed and non-passed data. The MMOCGAN model could capture the distribution of all potential clusters. Therefore, we further confirm the discriminator could distinguish between pass and non-pass product for all different product types. Both feature construction functions ϕ_{mix} and ϕ_{cat} could yield satisfactory results. However, we can

Figure 5: t-SNE distribution of pass products (all colors except red and yellow), non-pass products (red), and generated complementary data (yellow).

see that using the Gaussian model for each latent variable does not help to improve the performance as shown in Table 1. This might be due to that the dimension of the feature vector z we use is high, which makes it hard to capture the distribution or that the data does not necessarily follow the Gaussian distribution.

We also investigate the influence of the number of latent variables. The result is shown in Table 2. By setting the number of cluster m as 1, our method essentially assumes there's only one type. We can see the number of latent variable does influence the result. The marginal performance gain decreases as the number of the latent variable increases.

7 CONCLUSION

In the paper, we developed the multi-modal one-class generative adversarial network for anomaly detection problem in manufacturing. This method takes in the time-series signal data during production and outputs the probability if a product is a pass or non-pass product. To deal with this limited imbalanced high-dimensional multi-modal task, this method 1) adopts a pretrained domain-specific feature extractor to reduce the dimension, 2) uses only pass product for training a GAN model, 3) injects pseudo prior information to the generator in the GAN model to generate samples 4) in the complementary distribution of pass product, and the discriminator in the GAN model is trained to discriminate the pass and non-pass product. Our model successfully detects non-pass product by using only the pass product as training. The experiment shows that our model outperforms most existing methods.

In practice, a production line produces different types of products and also accepts new types of products. The samples of the new type products might follow different distributions. Therefore, one critical problem is how to develop methods that can quickly transfer a well-trained detector to a new environment, i.e. a new production line with other types of products.

REFERENCES

Jinwon An and Sungzoon Cho. Variational autoencoder based anomaly detection using reconstruction probability. 2015.

David Berthelot, Thomas Schumm, and Luke Metz. Began: boundary equilibrium generative adversarial networks. *arXiv preprint arXiv:1703.10717*, 2017.

Raghavendra Chalapathy, Aditya Krishna Menon, and Sanjay Chawla. Anomaly detection using one-class neural networks. *arXiv preprint arXiv:1802.06360*, 2018.

Varun Chandola, Arindam Banerjee, and Vipin Kumar. Anomaly detection: A survey. *ACM computing surveys (CSUR)*, 41(3):15, 2009.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in neural information processing systems*, pp. 2172–2180, 2016.

Yunqiang Chen, Xiang Sean Zhou, and Thomas S Huang. One-class svm for learning in image retrieval. In *Image Processing, 2001. Proceedings. 2001 International Conference on*, volume 1, pp. 34–37. IEEE, 2001.

Sarah M Erfani, Sutharshan Rajasegarar, Shanika Karunasekera, and Christopher Leckie. High-dimensional and large-scale anomaly detection using a linear one-class svm with deep learning. *Pattern Recognition*, 58:121–134, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Swaminathan Gurumurthy, Ravi Kiran Sarvadevabhatla, and R Venkatesh Babu. Deligan: Generative adversarial networks for diverse and limited data. In *CVPR*, pp. 4941–4949, 2017.

Q Peter He and Jin Wang. Fault detection using the k-nearest neighbor rule for semiconductor manufacturing processes. *IEEE Transactions on Semiconductor Manufacturing*, 20(4):345–354, 2007.

Jeroen Henricus Marinus Janssens. Outlier selection and one-class classification. 2013.

Martin Lauer. A mixture approach to novelty detection using training data with outliers. In *European Conference on Machine Learning*, pp. 300–311. Springer, 2001.

Ki Bum Lee, Sejune Cheon, and Chang Ouk Kim. A convolutional neural network for fault classification and diagnosis in semiconductor manufacturing processes. *IEEE Transactions on Semiconductor Manufacturing*, 30(2):135–142, 2017.

Erik Marchi, Fabio Vesperini, Florian Eyben, Stefano Squartini, and Björn Schuller. A novel approach for automatic acoustic novelty detection using a denoising autoencoder with bidirectional lstm neural networks. In *Acoustics, Speech and Signal Processing (ICASSP), 2015 IEEE International Conference on*, pp. 1996–2000. IEEE, 2015.

Markos Markou and Sameer Singh. Novelty detection: a reviewpart 1: statistical approaches. *Signal processing*, 83(12):2481–2497, 2003.

Julian McAuley and Jure Leskovec. Hidden factors and hidden topics: understanding rating dimensions with review text. In *Proceedings of the 7th ACM conference on Recommender systems*, pp. 165–172. ACM, 2013.

Takeshi Nakazawa and Deepak V Kulkarni. Wafer map defect pattern classification and image retrieval using convolutional neural network. *IEEE Transactions on Semiconductor Manufacturing*, 31(2):309–314, 2018.

Marco AF Pimentel, David A Clifton, Lei Clifton, and Lionel Tarassenko. A review of novelty detection. *Signal Processing*, 99:215–249, 2014.

Scott Poll, Ann Patterson-Hine, Joe Camisa, David Garcia, David Hall, Charles Lee, Ole J Mengshoel, Christian Neukom, David Nishikawa, John Ossenfort, et al. Advanced diagnostics and prognostics testbed. In *Proceedings of the 18th International Workshop on Principles of Diagnosis (DX-07)*, pp. 178–185, 2007.

Shebuti Rayana and Leman Akoglu. Less is more: Building selective anomaly ensembles. *arXiv preprint arXiv:1501.01924*, 2015.

Farzad Sabahi and Ali Movaghar. Intrusion detection: A survey. In *Systems and Networks Communications, 2008. ICSNC'08. 3rd International Conference on*, pp. 23–26. IEEE, 2008.

Mohammad Sabokrou, Mohammad Khalooei, Mahmood Fathy, and Ehsan Adeli. Adversarially learned one-class classifier for novelty detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3379–3388, 2018.

Mayu Sakurada and Takehisa Yairi. Anomaly detection using autoencoders with nonlinear dimensionality reduction. In *Proceedings of the MLSDA 2014 2nd Workshop on Machine Learning for Sensory Data Analysis*, pp. 4. ACM, 2014.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *Advances in Neural Information Processing Systems*, pp. 2234–2242, 2016.

Thomas Schlegl, Philipp Seeböck, Sebastian M Waldstein, Ursula Schmidt-Erfurth, and Georg Langs. Unsupervised anomaly detection with generative adversarial networks to guide marker discovery. In *International Conference on Information Processing in Medical Imaging*, pp. 146–157. Springer, 2017.

Mei-Ling Shyu, Shu-Ching Chen, Kanoksri Sarinnapakorn, and LiWu Chang. A novel anomaly detection scheme based on principal component classifier. Technical report, MIAMI UNIV CORAL GABLES FL DEPT OF ELECTRICAL AND COMPUTER ENGINEERING, 2003.

Salvatore J Stolfo, Wei Fan, Wenke Lee, Andreas Prodromidis, and Philip K Chan. Cost-based modeling for fraud and intrusion detection: Results from the jam project. Technical report, COLUMBIA UNIV NEW YORK DEPT OF COMPUTER SCIENCE, 2000.

Johannes Wienke, Sebastian Meyer zu Borgsen, and Sebastian Wrede. A data set for fault detection research on component-based robotic systems. In *Conference Towards Autonomous Robotic Systems*, pp. 339–350. Springer, 2016.

Houssam Zenati, Chuan Sheng Foo, Bruno Lecouat, Gaurav Manek, and Vijay Ramaseshan Chandrasekhar. Efficient gan-based anomaly detection. *arXiv preprint arXiv:1802.06222*, 2018.

Tong Zhang, Jue Wang, Liang Xu, and Ping Liu. Fall detection by wearable sensor and one-class svm algorithm. In *Intelligent computing in signal processing and pattern recognition*, pp. 858–863. Springer, 2006.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

Manqi Zhao and Venkatesh Saligrama. Anomaly detection with score functions based on nearest neighbor graphs. In *Advances in neural information processing systems*, pp. 2250–2258, 2009.

Panpan Zheng, Shuhan Yuan, Xintao Wu, Jun Li, and Aidong Lu. One-class adversarial nets for fraud detection. *arXiv preprint arXiv:1803.01798*, 2018.

Chong Zhou and Randy C Paffenroth. Anomaly detection with robust deep autoencoders. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 665–674. ACM, 2017.

Bo Zong, Qi Song, Martin Renqiang Min, Wei Cheng, Cristian Lumezanu, Daeki Cho, and Haifeng Chen. Deep autoencoding gaussian mixture model for unsupervised anomaly detection. 2018.

HYPERPARAMETERS

Both discriminator and the generator are neural networks. The discriminator D is a four-layer feed-forward neural network that takes in the feature vector of a data sample and outputs the probability of the sample being real. Its latent dimensions are 128, 128 respectively. The auxiliary distribution Q shares the hidden layer with the discriminator and output the probability of the latent code. The generator is a three layer feed-forward neural network that takes in the random noise and outputs the generated feature vector. The dimension of the hidden layer in the generator is 128. The training epoch is 1000. If use ϕ_{mix}, we set $\lambda = 0.03$, as suggested in (Gurumurthy et al., 2017).The threshold is set as 99.5 percentile[1] of the real data predicted by the target network. The batch size is set as 100. We use five-fold cross validation to verify the models, more specifically, we divide the pass products data into five folds, use four of them for training and the left fold and the non-pass product data for testing.

BASELINE METHODS

Our MMOC-GAN are compared with following widely used anomaly detection methods including:

1. One class nearest neighbors (OCNN neighbor) (Zhao & Saligrama, 2009) detects anomaly data samples by using the average distance between the data samples and some of its nearest neighbors in the pass product dataset. A prede-fined threshold that is trained by using the validation dataset is required to determine if a product is pass or not.

2. One class support vector machine (OCSVM) (Chen et al., 2001) is based on the support vector machine to learn a compact decision hyper-plane around the pass product data, and data samples at the outlier of the hyperplane are classified as non-pass data.

3. One class neural network (OCNN network) (Chalapathy et al., 2018) applies a neural net-work to generate the tight en-velope around the normal data. It is developed based on OCSVM. The critical part is to develop an end-to-end neu-ral network based method to learn the data representation in the hidden layer driven by using a regularized objective similar to SVM, i.e. to learn the hyperplane.

4. Gaussian mixture model (GMM) (Chandola et al., 2009) is a density based model that can be used for anomaly detection.

5. Robust deep auto-encoder (RDA) (Zhou & Paffenroth, 2017) is based on auto-encoder with a combination of robust principal component analysis as a regularizer. The reconstruction error is used as the measurement to detect anomalies.

6. Deep auto-encoder Gaussian mixture model (DAGMM) (Zong et al., 2018) is an end-to-end unsuper-vised learning method that utilizes a deep auto-encoder to generate a low-dimensional representation and reconstruction error for each data sample, which is further input into a Gaussian mixture model. The joint optimization methods help the auto-encoder to escape from local optima.

7. Anomaly GAN (ANOGAN) (Schlegl et al., 2017) is a GAN based anomaly detection method by mapping the data sample space back to the latent space. The residual loss between the original data sample and the generated data sample from the perfectly remap-ping latent noise and the reconstruction loss together are used as the measurement to detect anomalies.

8. Regular GAN (RGAN) where discriminator in the GAN model is directly applied as the detector.

9. One class adversarial network (OCAN)(Zheng et al., 2018) method tries to generate the malicious users from benign users directly, thus to help discriminate the malicious users.

---

[1] $22/(3936 + 22) \approx 0.005$