Revisit Recurrent Attention Model
from an Active Sampling Perspective

1 Introduction

We revisit the Recurrent Attention Model (RAM, Mnih et al. (2014)), a recurrent neural network for visual attention, from an active information sampling perspective.

The RAM, instead of processing the input image for classification in full, only takes a *glimpse* at a small patch of the image at a time. The recurrent attention mechanism learns where to look at to obtain new information based on the internal state of the network. After a pre-defined number of glimpses, RAM finally makes a prediction as output. Compared with the attention mechanism which now dominates the AI/NLP research such as Transformer (Vaswani et al., 2017) and BERT (Devlin et al., 2018), this recurrent attention mechanism is fundamentally different, as it is used to obtain new information (active sampling of information), rather than processing information that is already fully observed.

In this paper, we identify three weaknesses of this widely-cited approach. First, the convergence of RAM training is slow. Second, RAM does not support dynamic number of glimpses per sample, but uses a fixed number of glimpses for every sample. Third and perhaps most importantly, the performance of the original RAM does not improve but rather decrease dramatically if it takes more glimpses, which is weird and against intuition.

We provide a simple solution of adding two extra terms in the objective function of RAM, in-sipred from neuroscience research (Gottlieb, 2018) which discusses the logic and neural substrates of information sampling policies in the context of visual attention and gaze. Base on the evidence available so far, Gottlieb (2018) suggested three kinds of motives for the active sampling strategies of decision-making while the original RAM only implements one of them. We incorporate the other two motives in the objective function, and by doing so we 1) achieve much faster convergence and 2) instantly enbale decision making with a dynamic number of glimpse for different samples with no loss of accuracy. 3) More importantly, we find that the modified RAM generalizes much better to longer sequence of glimpses which is not trained for. (We will also make the code public to easily reproduce the experiments.)

2 Related work

Recurrent Attention Model (Mnih et al., 2014). RAM combines a recurrent neural network with reinforcement learning to utilize visual attention for classification and is trained with policy gradient in a end-to-end manner. At each timestep, it takes a glimpse on a patch of the input image, processes the information and then uses its internal state to select the next location to focus. By adaptively selecting a sequence of patches of images and only processing the selected patches, it outperforms a convolutional neural network baseline while its computation cost is cheap and independent of the input image size. Due to page limit, we refer readers to the original paper (Mnih et al., 2014), online tutorials and high-starred implementation on Github.

The recurrent attention mechanism allows RAM to actively obtain new information for decision making. Note that though RAM is trained end-to-end through the help of the REINFORCE rule

(Williams, 1992), it is not a standard reinforcement learning problem where the objective is to maximize the cumulative reward (or, minimize the cumulative regret); instead, RAM maximizes the simple reward (minimizes the simple regret). The reward is given only to the final prediction action, but not to the glimpse actions. In a sense, a glimpse action is rewarded indirectly only if it obtains useful information that helps making a correct prediction. This is very similar to the problem of pure-exploration bandits (Bubeck et al., 2009), specifically best arm identification. We think this distinguishing feature of active sampling of information for decision making is not well addressed in deep learning, in reinforcement learning, as well as in neuroscience research (Gottlieb and Oudeyer, 2018; Gottlieb, 2018).

Weaknesses of Recurrent Attention Model (Mnih et al., 2014). First, the original RAM paper did not mention the exact convergence of RAM training. We inspect some Github implementations of RAM, one implementation (conan7882, 2018) takes 1000 epochs to achieve the paper accuracy; another (kevinzakka, 2017) claims to reach the paper accuracy in 30 epochs, but we find that it uses a technique to augment the test time accuracy, introduced in the followed work (Ba et al., 2014) of RAM, by processing an input multiple times and averaging the prediction. When we disable this technique in (kevinzakka, 2017), we find that the convergence is in fact much slower.

Second, RAM uses a fixed number of glimpses for each input sample, however we would like to see RAM terminates automatically as long as it is very certain about the prediction. It is possible that some samples are easier to predict and only need fewer glimpses. In the future work section of Mnih et al. (2014), the authors briefly mentioned that they trained a separate network to predict when to terminate. By this way RAM learns to do dynamic prediction "*once it has enough information to make a confident classification*".

Third, RAM does not generalize well when using a larger number of glimpses. This generalization issue comes in two different settings.

- When the number of glimpses is the same for training and testing, which is the experiment setting in the original RAM paper. The authors showed that RAM performs the best in MNIST trained with $N = 6$ glimpses per sample and more glimpses begin to weaken the accuracy.

- When the number of glimpses is not the same for training and testing. We set the number of glimpses to $N = 6$ to train the RAM and test the performance on $N \neq 6$. We find that the accuracy does not improve but decrease dramatically (see Figure 2).

In this paper we evaluate the second setting.

Implications from (Gottlieb, 2018). In (Gottlieb, 2018), the authors reviewed recent studies on attentional learning, and highlighted the role of active sampling through visual attention and gaze for decision making. Particularly, Gottlieb (2018) suggested three types of motives for implementing active sampling policies, " *One motive relates simply to the extent to which information is expected to increase the operant rewards of a task; a second motivation is related to reducing the uncertainty of belief states; and yet a third motive may be related to the intrinsic utility or dis-utility of anticipating a positive or a negative outcome (savoring or dread).* " In the context of RAM for classification, only the first motive is implemented by RAM as the reward of correct classification.

3   Modification of RAM

We propose to add two extra terms which represents the second and third motives mentioned above, on the original objective function of RAM.

We denote the MNIST dataset of in total M sample-label pairs as $\{X, Y\} = \{x, y\}^M$, the parameter of the RAM architecture is denoted as θ, the output 10-dimension softmax vector of RAM as $f_\theta(x)$, and the prediction of classification as $\hat{y} = argmax_i f_\theta(x)_i$.

The orginal objective function. Under the distribution of all possible sequences $s_{1:N}$ of actions (at length N), RAM maximizes the reward of correct classification as the objective function: $J_{original}(\theta) = E_{p(s_{1:N};\theta)}[\mathbb{1}_{\hat{y}=y}]$ where $p(s_{1:N};\theta)$ depends on the policy.

Mnih et al. (2014) employed two tricks to maximize $J_{original}(\theta)$ which is non-trival. First, Mnih et al. (2014) borrowed the REINFORCE rule (Williams, 1992) to maximize $J_{original}(\theta)$ through policy gradient. Second, because the policy gradient may have a high variance, Mnih et al. (2014)

90 trained an auxiliary network (one fully-connected layer) called baseline network taking the internal
91 state as input to mimic the value function, which helps the training. So the true objective function
92 the orignal RAM maximizes is $J_{original} + J_{auxiliary}$.

New objective function. We consider the new objective function to be

$$J_{new} = J_{original} + J_{uncertainty} + J_{intrinsic} + J_{auxiliary}$$

93 We use $J_{uncertainty}$ to model the motive to reduce uncertainty. However, since the uncertainty is
94 not available, we use a similar network like the baseline network to mimic the residual of er-
95 ror. In other words, we use another auxiliary network to predict the different between the clas-
96 sification and the ground truth. We call this predicted diffrence as self-uncertainty, denoted as
97 $u(x)$, which is a 10-dimensional vector. Since we wish to minimize this uncertainty, we have
98 $J_{uncertainty} = -\lambda_1 \sum_i |u(x)_i|$

99 We use $J_{intrinsic}$ to model the intrinsic utility of anticipating outcome. But in classification of MNIST
100 this belief is not binary (negative or positive) as implied by (Gottlieb, 2018). As in MNIST the least
101 assumption we could make is that a data sample must belong to exactly one class, the intrinsic belief
102 in the context of classification becomes the belief that *the prediction must be one of the ten class*.
103 In other words, we have an intrinsic belief of sparsity. We incorporate this intrinsic belief as L1
104 regularization on the output 10-dimension vector $f_\theta(x)$: $J_{intrinsic} = -\lambda_2 \sum_i |f_\theta(x)_i|$.

105 Note that for simplicity, we merge the objective of the self-uncertainty network and the objective of
106 the baseline network into $J_{auxiliary}$. The entire modified RAM could be trained end-to-end just as the
107 orignal one.

108 **How to do dynamic decision-making in test-time.** The introduction of self-uncertainty has a
109 side-effect. It gives us an opportunity to enable a dynamic number of glimpses for diffrence samples
110 because now we have an uncertainty measure. Borrowing ideas from pure-exploration bandits, we
111 use self-uncertainty to construct a upper and lower bound for each class, and let RAM terminate if the
112 lower bound of the highest class is higher than the upper bound of the rest classes. Given a timestep
113 t, denote the prediction as $f_\theta^t(x)$ and the self-uncertainty as $u^t(x)$, the upper and lower bound for a
114 class i is $Upper(i) = f_\theta^t(x)_i + \beta * u^t(x)_i$, $Lower(i) = f_\theta^t(x)_i - \beta * u^t(x)_i$ where the exploration
115 rate β is a hyperparameter. We take i^* to be the class of the highest $i^* = argmax_i f_\theta^t(x)_i$. RAM
116 terminates when the following condition is met: $Lower(i^*) > \max_{i \neq i^*} Upper(i)$. Given a larger β,
117 RAM will take more glimpses and when $\beta = 0$, RAM will terminate in only one glimpses.

4 Evaluation and Conclusion

119 We evaluate on MNIST dataset as in the orignal RAM paper. We set the train-time number of
120 glimpses $N = 6$ for it achieves the best test-time accuracy in Mnih et al. (2014). λ_1 and λ_2 in the
121 objective function is set to 0.01.

122 We first show in Figure 1 that the two new terms in the objective both contribute to a faster conver-
123 gence. We test four cases 1) the orignal objective, 2) add the $J_{intrinsic}$, 3) add $J_{uncertainty}$, 4) add both
124 new terms. We see in Figure 1 that our new objective gives the fastest convergence.

125 As in Figure 2, we test the trained models
126 with varying number of glimpses. We fisrt
127 evaluate the non-dynamic case (fixed num-
128 ber for all samples). The performance of
129 the original RAM decrease dramatically when
130 $N > 10$. Adding both terms, the modi-
131 fied RAM does not suffer the decrease any-
132 more even when N is large . Also, it is in-
133 teresting that adding only the uncertainty term,
134 we observe the improvement of accuracy when
135 N is smaller than 6. We also test the dy-
136 namic case by varying the exploration rate in
137 $\{0, 0.01, 0.1, 0.2, 0.4, 0.6, 0.8, 1, 2, 5\}$. We see
138 that dynamic number of glimpses does not hurt

Figure 1: Train Accuracy during traing (in total 60 epochs)

139 the performance, which confirms with the hypothesis that some samples are easier to discriminate
140 and thus need fewer glimpses.

Figure 2: Performance when given diffrent number of glimpses

Conclusion. We revisted RAM from an active sampling perspective (Gottlieb, 2018). The solution to three weaknesses of the orignal RAM is to add two very simple extra terms to the objective function. We believe the attentional learning for actively obtaining new information for decision making has a high potential for both AI and neuroscience research.

References

Jimmy Ba, Volodymyr Mnih, and Koray Kavukcuoglu. 2014. Multiple object recognition with visual attention. *arXiv preprint arXiv:1412.7755* (2014).

Sébastien Bubeck, Rémi Munos, and Gilles Stoltz. 2009. Pure exploration in multi-armed bandits problems. In *International conference on Algorithmic learning theory*. Springer, 23–37.

conan7882. 2018. A TensorFlow implementation of the recurrent models of visual attention. `https://github.com/conan7882/recurrent-attention-model`. (2018).

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *CoRR* abs/1810.04805 (2018). arXiv:1810.04805 `http://arxiv.org/abs/1810.04805`

Jacqueline Gottlieb. 2018. Understanding active sampling strategies: Empirical approaches and implications for attention and decision research. *Cortex* 102 (2018), 150–160.

Jacqueline Gottlieb and Pierre-Yves Oudeyer. 2018. Towards a neuroscience of active sampling and curiosity. *Nature Reviews Neuroscience* (2018), 1.

kevinzakka. 2017. A PyTorch Implementation of "Recurrent Models of Visual Attention". `https://github.com/kevinzakka/recurrent-visual-attention`. (2017).

Volodymyr Mnih, Nicolas Heess, Alex Graves, and Koray Kavukcuoglu. 2014. Recurrent Models of Visual Attention. *CoRR* abs/1406.6247 (2014). arXiv:1406.6247 `http://arxiv.org/abs/1406.6247`

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in neural information processing systems*. 5998–6008.

Ronald J Williams. 1992. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning* 8, 3-4 (1992), 229–256.