Learning powerful policies and better generative models by interaction

Abstract

Model-based reinforcement learning approaches have the promise of being sample efficient. Much of the progress in learning dynamics models in RL has been made by learning models via supervised learning. There is enough evidence that humans build a model of the environment, not only by observing the environment but also by interacting with the environment. Interaction with the environment allows humans to carry out *experiments*: taking actions that help uncover true casual relationships which in turn can be used for building better dynamics models. Analogously, we would expect such interaction to be helpful for a learning agent while it learns to model the dynamics of the environment. In this paper, we build upon this intuition, by using an auxiliary cost function to ensure consistency between what the agent observes (by actually performing actions in the real world) and what it hallucinates (by imagining to have taken actions in the environment). Our empirical analysis shows that the proposed approach helps to train powerful policies as well as better dynamics models.

1 Introduction

Reinforcement Learning consists of two fundamental problems: *learning* and *planning*. *Learning* comprises of improving the agent's current policy by interacting with the environment while *planning* involves improving the policy without interacting with the environment. These problems evolve into the dichotomy of *model-free* methods (which primarily rely on *learning*) and *model-based* methods (which primarily rely on *planning*). Recently, *model-free* methods have shown many successes, such as learning to play Atari games with pixel observations (Mnih et al., 2015b; Mnih et al., 2016) and learning complex motion skills from high dimensional inputs (Schulman et al., 2015a;b). But their high sample complexity is a still a major criticism of the *model-free* approaches.

In contrast, model-based reinforcement learning methods have been introduced in the literature where the goal is to improve the sample efficiency by learning a dynamics model of the environment. But model-based RL has several caveats. If the policy takes the learner to an unexplored state in the environment, the learner's model could make errors in estimating the environment dynamics, leading to sub-optimal behaviour. This problem is referred to as the model-bias problem (Deisenroth & Rasmussen, 2011).

In order to make prediction about the future, dynamics models are unrolled step by step which leads to the issue of "compounding errors" (Talvitie, 2014; Bengio et al., 2015; Lamb et al., 2016): an error in modeling the environment at time t affects the predicted observations at all subsequent time-steps and hence the dynamics model may no longer be grounded in reality. This problem is much more challenging for the environments where the agent observes high-dimensional image inputs and not compact state representations. On the other hand, model-free algorithms are not limited by the accuracy of the model, and therefore can achieve better final performance by trial and error, though at the expense of much higher sample complexity.

In the model-based approaches, the dynamics model is usually trained with supervised learning techniques i.e just by *observing the data*. On the other hand, there's enough evidence that humans learn the dynamics of the environment not just by observing the environment but also by interacting with the environment (Cook et al., 2011; Daniels & Nemenman, 2015). Interaction is useful as it allows the agent to carry out experiments in the real world to determine causality, which is clearly a desirable characteristic when building dynamics models.

This leads to an interesting possibility. The agent could consider two possible pathways: (i) Taking actions in the real world to generate new observations and (ii) Imagining to take actions and hallucinating the new observations. Consider the humanoid robot from the MuJoCo environment (Mordatch et al., 2015). In the first case, the humanoid agent actually takes a step into the environment, observes the change in its position (and location), takes another step and so on. In the second case, the agent imagines taking a step, hallucinates what the observation would look like, imagines taking another step and so on. The first case is a *close-loop* setup, where the humanoid observes the state of the world, and then takes an action, gets the true observation from the environment, which is used to choose the next action, and so on. The second case is a *open-loop* setup, where the agent imagines for multiple time steps into the future without interacting with the environment. The two cases have been summarized in Figure 1.

As such, the two pathways may not to be "consistent" given the challenges in learning a multi-step dynamics model. By "consistent", we mean the behaviour of state transitions along the two paths should be indistinguishable. Had they been consistent, the learner's model would be grounded in reality (in terms of being consistent with observations from the environment over a long time horizon). In this work, we propose to ensure consistency by using an auxiliary loss which explicitly seeks to match the generative behaviour (from open loop) and the observed behaviour (from closed loop) as closely as possible. More generally, we show that the proposed approach helps to simultaneously train more powerful policies as well as better generative models, by using a training objective that is not solely focused on predicting the next observation. Our evaluation protocol consists of learning both observation-space models and state-space models. We consider various continuous control tasks from the OpenAI Gym suite (Brockman et al., 2016), and RLLab (Duan et al., 2016) and show that using the proposed auxiliary loss helps in achieving better performance across tasks.

2   ENVIRONMENT MODEL

Consider a learning agent which is training to optimize a reward signal r in a given environment. At a given timestep t, the agent is in some state $s_t \in S$. It takes an action $a_t \in A$ according to its policy $a_t \sim \pi_t(a_t|s_t)$, receives a reward r_t (from the environment) and transitions to a new state s_{t+1}. The agent is trying to maximize its expected reward and has two pathways for improving its behaviour:

1. *Close-loop* path, where the learner interacts with the environment at every step. The agent starts at time t in a state s_t, chooses an action a_t to perform (using its policy π_t), actually performs the action, and receives a reward r_t. It then again observes the environment to obtain the new state s_{t+1}, uses this state to decide which action a_{t+2} to perform next.

2. *Open-loop* path, where the learner imagines interacting with the environment. The agent starts at time t in a state s_t, chooses an action a_t to perform (using its policy π_t), imagines that it has performed the action and hallucinates the new state s_{t+1}^{imag} of the environment. This imagined state is used to choose action a_{t+1} to perform next. During these "imagined" roll-outs, the agent does not interact with the environment but interacts with its "imagined" version of the environment which we call as its dynamics model or the learner's "world".

As an alternative, the agent could use both the pathways simultaneously. The agent could, in parallel, (i) build a model of the environment and (ii) engage in an interaction with the environment as shown in Figure 1. This could allow the agent to learn the environment dynamics not just by only observing the environment by also interacting with it.

We propose to make the two pathways consistent with each other so as to ensure that the predictions from the learner's dynamics model are grounded in the observations from the environment. We show that such a "consistency constraint" helps the agent to learn a powerful policy and a better dynamics model for the environment.

2.1   CONSISTENCY CONSTRAINT

We want the generative behaviour (from the open loop) to be consistent with the observed behaviour (from the close loop). We want to make sure that the prediction from the learner's dynamics model (or the "world") are similar to the observations from the environment. The learner's dynamics model could either be in observation space (pixel space or feature space) or it could be in state

Figure 1: The agent, in parallel, (i) builds a model of the world and (ii) engages in an interaction with the world. The agent can now learn the model dynamics while interacting with the environment. We show that making these two pathways consistent helps in simultaneously learning a better policy and a more powerful generative model.

space. State space models are generally more efficient as they model dynamics at some higher level of abstraction. In the case of state space models, the learner predicts transitions in the state space (representing the learner's "world"). In this case, the learner first encode the actual observations from the environment into the state space of the learner and then impose the consistency constraint in the state space.

When we want to apply the consistency constraint in the open loop setup, we need to obtain the corresponding state transitions in the environment. For each "imagined" action, a_t, we perform that action in the real environment to obtain the new environment state. This environment state is only used for computing the consistency loss and is not used by the agent while imagining the subsequent state transitions. Once we have the imagined transitions and the actual transitions, several possibilities exist for imposing the "consistency constraint":

1. Minimize the prediction error between the future predictions as a result of running the learner's dynamics model and the real observation coming from the environment. Here, the consistency loss would encourage the per-step predictions from the learner's "world" and environment to be similar to each other.

2. Encode the open-loop prediction sequence (from the learner's imagination) and the closed-loop prediction sequence (from the environment) into fixed size representations using RNNs. A GAN discriminator could be trained on the output of the RNN to predict if the trajectory corresponds to the learner's "world" or the environment. The dynamics function is trained with an auxiliary consistency loss which encourages it to fool the discriminator. This setup has previously also beein used in Professor Forcing (Lamb et al., 2016).

2.2 Observation Space Model

For the observation space models, we represent the environment as a Markov Decision Process with an unknown state transition function $f : S \times A \to S$. Given a starting state $s_t \in S$, the agent learns a policy function π_t to choose an action $a_t \in A$ and a dynamics model $\hat{f}$ to predict the next state s_{t+1} given a state-action pair (s_t, a_t). Both the transition function and the policy are parameterized using neural networks (Gaussian Policies) as $\hat{f}_\theta(s_t, a_t)$ and $\pi_\phi(s_t)$ where θ and ϕ denote the parameters of the dynamics model and the policy respectively. The details about model and policy implementation are provided in the appendix 6.1.1.

In the close loop setup, the agent starts in a state s_t, chooses an action $a_t \sim \pi_t(a_t|s_t)$, receives a reward r_t and observes the next state s_{t+1} which it uses to choose the next action a_{t+1}. In the open loop setup, the agent starts in a state s_t, chooses an $a_t \sim \pi_t(s_t)$, imagines the next state s_{t+1}^{imag} which it uses to choose the next action $a_{t+1} \sim \pi_t(s_t^{imag})$. External to the agent, we simulate the actions a_t in the environment to obtain the next environment state s_{t+1}. Note that the learning agent does not use these environment observations while it is "imagining" to perform actions. These environment

states are needed to ensure consistency between the learner's imagination and the state transitions grounded in the real environment.

Let $a_{1:T}^{imag}$ denote the sequence of actions that the agent imagines to have taken from time $t = 1$ to T. Then, $s_{2:T+1}^{imag}$ denotes the sequence of states that the learner hallucinates as a consequence of taking actions $a_{1:T}^{imag}$. Similarly, $s_{2:T+1}$ denote the sequence of states that would have the learner would have visited in the environment had he actually taken those actions in the environment (instead of just imagining them).

By the means of consistency constraint, we want to make the behaviour of sequence $s_{2:T+1}$ indistinguishable from $s_{2:T+1}^{imag}$. In the empirical evaluation, we compare the average rewards obtained by the agent and the average model loss with and without the consistency constraint and show that our proposed consistency constraint helps to learn a more powerful policy and a better dynamics model.

2.3 STATE SPACE MODEL

In case the observation space is high dimensional, as in case of pixel-wise observations(from high dimensional image data), state space models may be used to model the dynamics of the environment. These models can be computationally more efficient than the observation space models (as in pixel space) as they make predictions at a higher level of abstraction and learn a compact representation of the observation. Further, it may be easier to model the environment dynamics in the latent space as compared to the high dimensional pixel space.

Consider a learning agent operating in an environment that produces an observation o_t at every time-step t. These observations can be high-dimensional and highly redundant (for modelling the dynamics of the environment). The agent learns to encode these observations (o_t) into compact state-space representations (s_t) using an encoder e. The agent learns a policy function π_t to choose actions $a_t \sim \pi(a_t|s_t)$.

The environment dynamics is given by an unknown observation transition function $f : O \times A \to O$ and the agent aims to learn the model dynamics in state-space representation using a state transition function $\hat{f}$. Both the policy and state transition functions are parameterized using neural networks as π_ϕ and $\hat{f}_\theta$ where ϕ and θ represents the parameters of the policy and the transition function respectively. The observation space decoding o_{t+1} can be obtained from the pixel space encoding as $o_{t+1} \sim p(o_{t+1}|s_t, z_t)$. We now describe the steps in the closed loop and open loop setup.

Close Loop:

1. The agent is in a state s_{t-1} and receives an observation o_t from the environment.
2. $z_t \sim q(z_t|e(o_t), s_{t-1}, a_{t-1})$
3. Transition to a new state, $s_t = \hat{f}_\theta(z_t, s_{t-1}, a_{t-1})$
4. Choose an action $a_t = \pi(a_t|s_t)$
5. Decode the state s_t into observation $o_{t+1} \sim p(o_{t+1}|s_t, z_t)$

Open Loop:

1. The agent is in a state s_{t-1}.
2. $z_t \sim p(z_t|s_{t-1}, a_{t-1})$
3. Transition to a new state, $s_t = \hat{f}_\theta(z_t, s_{t-1}, a_{t-1})$
4. Choose an action $a_t = \pi(a_t|s_t)$

The open loop setup for the state space models is quite similar to the case of observation space models. The agent starts in a state s_t, chooses an $a_t = \pi_t(a_t|s_t)$, imagines the next state s_{t+1}^{imag} (using the transition function) which it uses to choose the next action $a_{t+1} = \pi_t(s_t^{imag})$. External to the agent, we simulate the actions a_t in the environment to obtain the next environment observation o_{t+1}. These environment observations are then encoded into the latent state and are needed to ensure consistency between the learner's imagination and the state transitions in the real environment.

$s_{2:T+1}^{imag}$ denotes the sequence of states that the learner hallucinates and $s_{2:T+1}$ denote the sequence of encoded environment observations that the learner would have received from the environment had he actually taken actions in the environment (instead of just imagining them). Like the previous case, we want to make the behaviour of sequence $s_{2:T+1}$ indistinguishable from $s_{2:T+1}^{imag}$. The agent is trained by imitation learning using trajectories sampled using an expert policy. The details about the model and policy implementation are provided in the appendix 6.1.2. In the empirical evaluation, we compare the imitation learning loss and the model log-likelihood with and without the consistency constraint. We show that our proposed consistency constraint helps to learn a strong policy and a better dynamics model.

3 RELATED WORK

Model based RL   A large majority of the literature in policy search relies on model-free methods, where no prior knowledge of the environment is required to find an optimal policy, through either policy improvement (value-based methods, Rummery & Niranjan (1994); Mnih et al. (2015a)), or direct policy optimization (policy gradient methods, Mnih et al. (2016); Schulman et al. (2015a)). Although this is conceptually simple, these algorithms have a high sample complexity. To improve their sample-efficiency, one can learn a model of the environment alongside the policy, to sample experience from. PILCO (Deisenroth & Rasmussen, 2011) is a model-based method that learns a probabilistic model of the dynamics of the environment, and incorporates the uncertainty provided by the model for planning on long-term horizons.

This model of the dynamics induces a bias on the policy search though. Previous work has tried to address the model-bias issue of model-based methods, by having a way to characterize the uncertainty of the models, and by learning a more robust policy (Deisenroth & Rasmussen, 2011; Rajeswaran et al., 2016; Lim et al., 2013). Model Predictive Control (MPC, Lenz et al., 2015) has also been proposed in the literature to account for imperfect models by re-planning at each step, but it suffers from a high computational cost.

There is no sharp separation between model-free and model-based reinforcement learning, and often model-based methods are used in conjunction with model-free algorithms. One of the earliest example of this interaction is the classic Dyna algorithm (Sutton, 1991), which takes advantage of the model of the environment to generate simulated experiences, which get included in the training data of a model-free algorithm (like Q-learning, with Dyna-Q). Extensions of Dyna have been proposed (Silver et al., 2008; Sutton et al., 2012), including deep neural-networks as function approximations. Recently, the Model-assisted Bootstrapped DDPG (MA-DDPG, Kalweit & Boedecker, 2017) was proposed to incorporate model-based rollouts into a Deep Deterministic Policy Gradient method. Recently, (Weber et al., 2017) used a predictive model in Imagination-Augmented Agents to provide additional context to a policy network.

Off-policy learning   There are different approaches which combine on-policy learning algorithms with off-policy samples. Recent examples of this approach include the interpolated policy gradient (Gu et al.), PGQ (O'Donoghue et al., 2016) and ACER (Wang et al., 2016), which combine policy gradient learning with ideas from off-policy learning, and a methodology inspired by Q-learning. While we can incorporate experience from a behaviour policy to learn both the model of the environment as well as the policy (see Section 4.2.2), our method remains orthogonal to these works. We propose to ensure consistency between the open-loop and the closed-loop pathways as a means to learn a stronger policy, and better dynamics model. As such, our approach can be applied to a wide range of existing RL setups.

4 RESULTS

The learning agent has two pathways for improving its behavior: (i) the close loop path, where it interacts with the environment by taking actions and observing the state transitions and (ii) the open loop path, where it imagines taking actions and hallucinates the state transitions that could happen. We show that ensuring "consistency" between what the learner predicts from the environment (with the dynamics model) and the actual observations from the environment helps to:

1. Learn a more powerful policy: we quantify the effect of the consistency constraint on the the policy by comparing the average episodic reward for observation space models, and the imitation learning loss for the state space models.

2. Learn a better dynamics model: we evaluate the effect of the consistency constraint on the dynamics model by comparing the model loss, with and without consistency, for the observation space models, and the log-likelihood of trajectories from the real environment, under the model we learn.

4.1 OBSERVATION SPACE MODELS

We consider a model-based training approach (without the consistency constraint) as the baseline where the dynamics model and the policy are learnt jointly. Details about the baselines are described in Appendix 6.1.1. We quantify the advantage of using consistency constraint by considering 4 classical Mujoco environments from RLLab (Duan et al., 2016): Ant ($S \in R^{41}$, $A \in R^8$), Humanoid ($S \in R^{142}$, $A \in R^{21}$), Half-Cheetah ($S \in R^{23}$, $A \in R^6$) and Swimmer ($S \in R^{17}$, $A \in R^3$). The batch size is fixed to 50000 for all the cases. The dynamics model is unrolled for $k = 20$ steps for obtaining the sequence of imagined observations from the dynamics model, and actual observations from the environment (over which the consistency constraint is applied). We describe the effect of changing the unrolling length in the subsequent sections.

4.1.1 AVERAGE EPISODIC RETURN

The average episodic return (and the average discounted episodic return) is a good estimate of the effectiveness of the jointly trained dynamics model and policy. To show that consistency constraint helps in learning a more powerful policy and a better dynamics model, we compare the average episodic rewards for the cases where the agent is trained with and without consistency. We expect that using consistency would either lead to higher rewards or would enable the agent to achieve the same level of rewards (as no-consistency case) but in fewer updates.

Figure 2 compares the average episodic returns for the agents trained with and without consistency. We observe that using consistency helps to learn a better policy in fewer updates for all the 4 environments. Similar trends are obtained with when we plot the average discounted returns (as shown in Figure 8 in Appendix 6.2.1). Since we are learning both the policy and the model of the environment at the same time, these results indicate that using the consistency constraint helps to jointly learn a more powerful policy and a better dynamics model.

Figure 2: Comparison of the average episodic returns, for agents trained with and without consistency on the Ant, Humanoid, Half-Cheetah and Swimmer environments (respectively). Vertical lines in the rightmost figure show the points of saturation with equal return.

4.1.2 EFFECT OF CHANGING THE OPEN-LOOP UNROLLING LENGTH k

During the open-loop setup, the dynamics model is unrolled for k timesteps. The choice of k could be a critical hyper-parameter for controlling the effect of consistency constraint. In the extreme case, setting $k = 1$ is equivalent to a setup where the dynamics model is used for one-step predictions.

We study the effect of changing k (during training) on the average episodic return for the Ant and Humanoid tasks, by training the agents with $k \in \{5, 20\}$. As an ablation, we also include the case of training the policy without using a model, in a fully model-free fashion. We would expect that a

smaller value of k would push the average episodic return closer to the no-consistency case. Figure 3 (Left) shows that a higher value of k ($k = 20$) leads to better returns for both tasks.

Figure 3: (Left) Average episodic return on Ant and Humanoid environments, for an agent without a model of the environment (model-free), an agent with a model of the environment without any consistency constraint, and agents with a model of the environment and trained with a consistency constraint over time horizons of length 5 and 20. (Right) Average loss (negative log-likelihood) of the dynamics model on Ant and Humanoid. Note that no loss is reported for the model-free agent, since it does not have any dynamics model. The loss for Humanoid was clipped for visualization.

We further explore the effect of different values of k on the model loss. This loss corresponds to an approximation (one-step ahead) of the log-likelihood of trajectories sampled from the true environment under our dynamics model. We expect a smaller value of k to have a lower one-step ahead prediction loss, compared to a larger value of k. The agent learns a high-level abstract representation of the states at the cost of low level details. The larger is the value of k, the longer is the prediction horizon for the agent, and so it is more likely to miss out on the low level details. Figure 3 (Right) shows that for one-step ahead predictions, the model with the consistency constraint and $k = 5$ obtains a lower loss than the one with $k = 20$.

4.2 STATE SPACE MODELS

State space models are useful in scenarios where the observation space is high-dimensional and possibly redundant (eg. pixels-space observations). In such cases, the state space models may be used to learn the model dynamics in a condensed latent space. These setups are more challenging than the observation space setup as here the agent also needs to learn an encoder and a decoder.

We train an expert policy for sampling high-reward trajectories from the environment. The details about the training setup are described in Appendix 6.1.2. In the baseline agent, the trajectories are used to train the policy π_ϕ using imitation learning and the dynamics model by maximum likelihood. We consider 3 continuous control tasks from the OpenAI Gym suite (Brockman et al., 2016): Half-Cheetah, Fetch-Push (Plappert et al., 2018) and Reacher. The dynamics model is unrolled for $k = 10$ steps for Half-Cheetah and $k = 5$ for Fetch-Push and Reacher.

4.2.1 EVALUATING DYNAMICS MODELS

We want to show that the consistency constraint helps to learn a better dynamics model of the environment. Since we learn a dynamics model over the states, we also need to jointly learn an observation model (decoder, see Appendix 6.1.2) conditioned on the states. We can then compute the log-likelihood of trajectories in the real environment (sampled with the expert policy) under this observation model. We compare the log-likelihoods corresponding to these observations for the agents trained with and without the consistency loss. We expect that the consistency constrained agent would achieve a higher log likelihood.

Figure 4 shows that for the consistency constrained agent, the dynamics model out-perform the baseline in all the 3 cases, which indicates that the agent learns a more powerful dynamics model of the environment. Note that in case of Fetch-Push and Reacher, we see improvements in the log-likelihood, even though the dynamics model is unrolled for just 5 steps.

Figure 4: Comparison of the average log likelihood for the open loop setup. The agents are trained with and without consistency on Half-Cheetah, Reacher and Fetch-Push environments (respectively). Using consistency constraint leads to a better dynamics model for all the 3 tasks.

4.2.2 LEARNING THE POLICY BY IMITATION LEARNING

For the state-space models, we used the expert trajectories to train our policy π_ϕ using imitation learning. To show that the consistency constraint helps to learn a more powerful policy, we compare the imitation learning loss for the agent trained with and without the consistency constraint.

Figure 5 shows that for the consistency constrained agent, the imitation learning loss is smaller for 2 environments, and on par with the loss of the agent trained without this constraint on the third environment. This indicates that using the consistency constraint helps the agent to learn a more powerful policy in some cases and equally-powerful policy in other cases.

Figure 5: Comparison of the imitation learning loss for the agent trained with and without consistency, on Half-Cheetah, Reacher and Fetch-Push environments (respectively).

5 CONCLUSION

In this paper, we formulate a way to ensure consistency between the predictions of a dynamics model and the real observations from the environment thus allowing the agent to learn powerful policies, as well as better dynamics models. The learning agent, in parallel, (i) builds a model of the environment and (ii) engages in an interaction with the environment. This results in two sequences of state transitions: one in the real environment where the agent actually performs actions and other in the agent's dynamics model (or the "world") where it imagines taking actions, and hallucinates the state transitions. We apply an auxiliary loss which encourages the behaviour of state transitions across the two sequences to be indistinguishable from each other. We evaluate our proposed approach for both observation space models, and state space models and show that the agent learns more a powerful policy and a better generative model. Future work would consider how these 2 interaction pathways could lead to more targeted exploration. Furthermore, having more flexibility over the length over which we unroll the model could allow the agent to take these decisions over multiple timescales.

REFERENCES

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5048–5058. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7090-hindsight-experience-replay.pdf`.

Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In *Advances in Neural Information Processing Systems*, pp. 1171–1179, 2015.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Claire Cook, Noah D Goodman, and Laura E Schulz. Where science starts: Spontaneous experiments in preschoolers exploratory play. *Cognition*, 120(3):341–349, 2011.

Bryan C Daniels and Ilya Nemenman. Automated adaptive inference of phenomenological dynamical models. *Nature communications*, 6:8133, 2015.

Marc Deisenroth and Carl E Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *Proceedings of the 28th International Conference on machine learning (ICML-11)*, pp. 465–472, 2011.

Prafulla Dhariwal, Christopher Hesse, Oleg Klimov, Alex Nichol, Matthias Plappert, Alec Radford, John Schulman, Szymon Sidor, Yuhuai Wu, and Peter Zhokhov. Openai baselines. `https://github.com/openai/baselines`, 2017.

Y. Duan, X. Chen, R. Houthooft, J. Schulman, and P. Abbeel. Benchmarking Deep Reinforcement Learning for Continuous Control. *ArXiv e-prints*, April 2016.

Shixiang Gu, Timothy Lillicrap, Zoubin Ghahramani, Richard E Turner, Bernhard Schölkopf, and Sergey Levine. Interpolated policy gradient.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Gabriel Kalweit and Joschka Boedecker. Uncertainty-driven imagination for continuous deep reinforcement learning. In *Conference on Robot Learning*, pp. 195–206, 2017.

A. Lamb, A. Goyal, Y. Zhang, S. Zhang, A. Courville, and Y. Bengio. Professor Forcing: A New Algorithm for Training Recurrent Networks. *ArXiv e-prints*, October 2016.

Ian Lenz, Ross A Knepper, and Ashutosh Saxena. Deepmpc: Learning deep latent features for model predictive control. In *Robotics: Science and Systems*, 2015.

Shiau Hong Lim, Huan Xu, and Shie Mannor. Reinforcement learning in robust markov decision processes. In *Advances in Neural Information Processing Systems*, pp. 701–709, 2013.

V. Mnih, A. Puigdomènech Badia, M. Mirza, A. Graves, T. P. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu. Asynchronous Methods for Deep Reinforcement Learning. *ArXiv e-prints*, February 2016.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015a.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015b.

Igor Mordatch, Kendall Lowrey, and Emanuel Todorov. Ensemble-cio: Full-body dynamic motion planning that transfers to physical humanoids. In *Intelligent Robots and Systems (IROS), 2015 IEEE/RSJ International Conference on*, pp. 5307–5314. IEEE, 2015.

A. Nagabandi, G. Kahn, R. S. Fearing, and S. Levine. Neural Network Dynamics for Model-Based Deep Reinforcement Learning with Model-Free Fine-Tuning. *ArXiv e-prints*, August 2017.

Brendan O'Donoghue, Remi Munos, Koray Kavukcuoglu, and Volodymyr Mnih. Combining policy gradient and q-learning. *arXiv preprint arXiv:1611.01626*, 2016.

Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, Vikash Kumar, and Wojciech Zaremba. Multi-goal reinforcement learning: Challenging robotics environments and request for research, 2018.

Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. Epopt: Learning robust neural network policies using model ensembles. *arXiv preprint arXiv:1610.01283*, 2016.

Gavin A Rummery and Mahesan Niranjan. *On-line Q-learning using connectionist systems*, volume 37. University of Cambridge, Department of Engineering Cambridge, England, 1994.

J. Schulman, S. Levine, P. Moritz, M. I. Jordan, and P. Abbeel. Trust Region Policy Optimization. *ArXiv e-prints*, February 2015a.

J. Schulman, P. Moritz, S. Levine, M. Jordan, and P. Abbeel. High-Dimensional Continuous Control Using Generalized Advantage Estimation. *ArXiv e-prints*, June 2015b.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017. URL http://arxiv.org/abs/1707.06347.

David Silver, Richard S Sutton, and Martin Müller. Sample-based learning and search with permanent and transient memories. In *Proceedings of the 25th international conference on Machine learning*, pp. 968–975. ACM, 2008.

Richard S. Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *SIGART Bull.*, 2(4):160–163, July 1991. ISSN 0163-5719. doi: 10.1145/122344.122377. URL http://doi.acm.org/10.1145/122344.122377.

Richard S. Sutton, Csaba Szepesvári, Alborz Geramifard, and Michael Bowling. Dyna-style planning with linear function approximation and prioritized sweeping. *CoRR*, abs/1206.3285, 2012. URL http://arxiv.org/abs/1206.3285.

Erik Talvitie. Model regularization for stable sample rollouts. In *UAI*, 2014.

Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Remi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. *arXiv preprint arXiv:1611.01224*, 2016.

Théophane Weber, Sébastien Racanière, David P Reichert, Lars Buesing, Arthur Guez, Danilo Jimenez Rezende, Adria Puigdomenech Badia, Oriol Vinyals, Nicolas Heess, Yujia Li, et al. Imagination-augmented agents for deep reinforcement learning. *arXiv preprint arXiv:1707.06203*, 2017.

6 Appendix

6.1 Environment Model

6.1.1 Observation Space Model

We use the experimental setup and environments as described in (Nagabandi et al., 2017)[1]. We consider two training scenarios: training a model-based learning agent with and without the consistency constraint. The consistency constraint is applied by unrolling the model for multiple steps using the observations predicted by the learner's dynamics model (closed-loop setup). We train an on-policy RL algorithm for Cheetah, Humanoid, Ant and Swimmer tasks from RLLab (Duan et al., 2016) control suite. We report the average reward obtained by the learner in the two cases: with and without consistency constraint. The model and policy architectures for the observation space models are as follows:

1. *Transition Model*: The transition model $\hat{f}_\theta(s_t, a_t)$ has a Gaussian distribution with diagonal covariance, where the mean and covariance are parametrized by MLPs (Schulman et al., 2015a), which maps an observation vector s_t and an action vector a_t to a vector μ which specifies a distribution over observation space. During training, the log likelihood $p(s|\mu)$ is maximized and state-representations can be sampled from $p(s|\mu)$.

2. *Policy*: The learner's policy $\hat{\pi}_\phi(s_t)$ is also a Gaussian MLP which maps an observation vector s to a vector μ_{policy} which specifies a distribution over action space. Like before, the log-likelihood $p(a|\mu)$ is maximized and actions can be sampled from $p(a|\mu)$.

Learner's policy and the dynamics model are implemented as Gaussian policies with MLPs as function approximations, and are trained using TRPO (Schulman et al., 2015a). Following (Nagabandi et al., 2017), we normalize the states and actions. The dynamics model is trained to predict the change in state ΔS_t as it can be difficult to learn the state transition function when the states s_t and s_{t+1} are very similar and the action a_t has a small effect on the output.

Figure 6: Open-loop and closed-loop pathways in the Observation Space Models. The consistency constraint aims to make the behaviour of the open loop predictions indistinguishable from the close loop behaviour

---

[1]Code available here: https://github.com/nagaban2/nn_dynamics

6.1.2 STATE SPACE MODEL

The model and policy architecture for the state space models is as follows:

1. *Encoder*: The learner encodes the pixel-space observations ($64 \times 64 \times 3$) from the environment into state-space observations (256 dimensional vectors) with a convolutional encoder (4 convolutional layers with 4×4 kernels, stride 2 and 64 channels). To model the velocity information, a stack of the latest 4 frames is used as the observation. The pixel-space observation at time $t - 1$ is denoted as o_{t-1}, and is encoded into state-space observation s_{t-1}.

2. *Transition Model*: The transition model is a Long Short-Term Memory model (LSTM, Hochreiter & Schmidhuber, 1997), that predicts the transitions in the state space. For every time-step t, latent variables z_t are introduced, whose distribution is a function of previous state-space observation s_{t-1} and previous action a_{t-1}. ie $z_t \sim p(z_t|s_{t-1}, a_{t-1})$. The output of the transition model is then a deterministic function of z_t, s_{t-1}, and a_{t-1}. ie $s_t = f(z_t, s_{t-1}, a_{t-1})$.

3. *Stochastic Decoder*: The learner can decode the state-space observations back into the pixel-space observations by use of stochastic convolutional decoder. The decoder takes as input the current state-space observation s_t and the current latent variable z_t and generates the current observation-space distribution from which the learner could sample an observation. ie $o_{t+1} \sim p(o_{t+1}|s_t, z_t)$. This observation model is Gaussian, with a diagonal covariance.

In the closed-loop trajectory, when the learner cannot interact with the environment, the latent variables are sampled from the prior distribution $p(z_t|s_{t-1}, a_{t-1})$. The latent variables are sampled from Normal distributions with diagonal covariance matrices. Since we cannot compute the log-likelihood $L(\theta)$ in a close form for the latent variable models, we minimize the evidence lower bound $\text{ELBO}(p_{posterior}) \leq L(\theta)$. As discussed previously, the consistency constraint is applied between the open-loop and closed-loop predictions with the aim of making their behaviour as similar as possible. Figure 7 shows a graphical representation of the open-loop and close-loop pathways in the state-space model.

Expert policy   Having access to some policy trained on a large number of experience is required to sample high-quality trajectories with pixel-observations. To train these expert policies, we used policy-based methods such as Proximal Policy Optimization (PPO, Schulman et al., 2017) for the half-cheetah and reacher environments, or Deep Deterministic Policy Gradient with Hindsight Experience Replay (DDPG with HER, Andrychowicz et al., 2017) for the pushing task. The architectures and hyper-parameters used are similar to the ones given by the Baselines library (Dhariwal et al., 2017). Note that these expert policies were trained on the state representation of the agents (ie. the positions and velocities of their joints), while the trajectories were generated with pixel-observations captured from a view external to the agent.

6.2 RESULTS

6.2.1 OBSERVATION SPACE MODELS

Figure 7: Open-loop and closed-loop pathways in the State Space Models. The consistency constraint aims to make the behaviour of the open loop predictions indistinguishable from the close loop behaviour

Figure 8: Comparison of the average episodic discounted rewards, for agents trained with and without consistency for the Ant, Humanoid, Half-Cheetah and Swimmer environments (respectively). Using consistency constraint leads to better rewards in a fewer number of updates for all the cases. Vertical lines in the rightmost figure show the points of saturation with equal return.