Efficient Riemannian Optimization on the Stiefel Manifold via the Cayley Transform

Abstract

Strictly enforcing orthonormality constraints on parameter matrices has been shown advantageous in deep learning. This amounts to Riemannian optimization on the Stiefel manifold, which, however, is computationally expensive. To address this challenge, we present two main contributions: (1) A new efficient retraction map based on an iterative Cayley transform for optimization updates, and (2) An implicit vector transport mechanism based on the combination of a projection of the momentum and the Cayley transform on the Stiefel manifold. We specify two new optimization algorithms: Cayley SGD with momentum, and Cayley ADAM on the Stiefel manifold. Convergence of the Cayley SGD is theoretically analyzed. Our experiments for CNN training demonstrate that both algorithms: (a) Use less running time per iteration relative to existing approaches which also enforce orthonormality of CNN parameters; and (b) Achieve faster convergence rates than the baseline SGD and ADAM algorithms without compromising the CNN's performance. The Cayley SGD and Cayley ADAM are also shown to reduce the training time for optimizing the unitary transition matrices in RNNs.

1 Introduction

Orthonormality has recently gained much interest, as there are significant advantages of enforcing orthonormality on parameter matrices of deep neural networks. For CNNs, Bansal et al. (2018) show that this improves accuracy and gives a faster empirical convergence rate, Huang et al. (2018a) show that orthonormality stabilizes the distribution of neural activations in training, and Cogswell et al. (2015) show that orthonormality reduces overfitting and improves generalization. For RNNs, Arjovsky et al. (2016); Zhou et al. (2006) show that the orthogonal hidden-to-hidden matrix alleviates the vanishing and exploding-gradient problems.

Riemannian optimization on the Stiefel manifold, which represents a set of orthonormal matrices of the same size, is an elegant framework for optimization under orthonormality constraints. But its high computational cost is limiting in many applications, including deep learning. Recent efficient approaches incorporate orthogonality in deep learning only for square parameter matrices (Arjovsky et al., 2016; Dorobantu et al., 2016), or indirectly through regularization (Bansal et al., 2018).

To address the aforementioned limitations, our first main contribution is an efficient estimation of the retraction mapping based on the Cayley transform for updating large *non-square* matrices of parameters on the Stiefel manifold. We specify an efficient iterative algorithm for estimating the Cayley transform that consists of only a few matrix multiplications, while the closed-form Cayley transform requires costly matrix inverse operations (Vorontsov et al., 2017; Wisdom et al., 2016).

Our second main contribution is aimed at improving convergence rates of training by taking into account the momentum in our optimization on the Stiefel manifold. We derive a new approach to move the tangent vector between tangent spaces of the manifold, instead of using the standard parallel transport. Specifically, we regard the Stiefel manifold as a submanifold of a Euclidean space. This allows for representing the vector transport (Absil et al., 2009) as a projection onto the tangent space. As we show, since the Cayley transform implicitly projects gradients onto the tangent space, the momentum updates result in an implicit vector transport. Thus, we first compute a linear combination of the momentum and gradient in the Euclidean space, and then update the network parameters using the Cayley transform, without explicitly performing the vector transport.

We apply the above two contributions to generalize the standard SGD with momentum and ADAM (Kingma & Ba, 2014) to the Stiefel manifold, resulting in our two new optimization algorithms called Cayley SGD with momentum and Cayley ADAM. A theoretical analysis of convergence of the Cayley SGD is presented. Similar analysis for the Cayley ADAM is omitted, since it is very similar to the analysis presented in (Becigneul & Ganea, 2019).

The Cayley SGD and Cayley ADAM are empirically evaluated on image classification using VGG and Wide Resnet on the CIFAR-10 and CIFAR-100 datasets (Krizhevsky & Hinton, 2009). The experiments show that the Cayley SGD and Cayley ADAM achieve better classification performance and faster convergence rate than the baseline SGD with momentum and ADAM. While the baselines take less time per epoch since they do not enforce the orthonormality constraint, they take more epochs until convergence than the Cayley SGD and Cayley ADAM. In comparison with existing optimization methods that also account for orthonormality – e.g., Polar decomposition, QR decomposition, or closed-form Cayley transform – our Cayley SGD and Cayley ADAM run much faster and yield equally good or better performance in image classification.

Finally, we apply the aforementioned two contributions to training of the unitary RNNs. Wisdom et al. (2016) proposes the full capacity unitary RNN that updates the hidden-to-hidden transition matrix with the closed-form Cayley transform. In contrast, for our RNN training, we use the more efficient Cayley SGD with momentum and Cayley ADAM. The results show that our RNN training takes less running time per iteration without compromising performance.

2 RELATED WORK

This section reviews closely related work on using orthonormal constraints in neural-network training, which can be broadly divided in two groups: regularization and Riemannian optimization.

Regularization approaches can be divided as hard, which strictly enforce orthonormality, and soft. Hard regularizations are computationally expensive. For example, Huang et al. (2018b) extend Batch Normalization (Ioffe & Szegedy, 2015) with the ZCA, and hence require costly eigenvalue decomposition. Huang et al. (2018a) derive a closed-form solution that also requires eigenvalue decomposition. Bansal et al. (2018); Cisse et al. (2017); Xiong et al. (2016) introduce mutual coherence regularization and spectral restricted isometry regularization; however, these regularizations are soft.

Riemannian optimization guarantees that the solution respects orthonormality constraints. For example, Cho & Lee (2017) replace Batch Normalization layers in a CNN with Riemannian optimization on the Grassmann manifold $G(n, 1)$, where the parameters are normalized but not orthonormalized. Also, Vorontsov et al. (2017); Wisdom et al. (2016); Lezcano-Casado & Martínez-Rubio (2019); Helfrich et al. (2017) perform Riemannian optimization on the unitary group matrices to stablize RNNs training, but their technique cannot be applied to non-square parameter matrices. Becigneul & Ganea (2019) introduce a more general Riemannian optimization, but do not show how to efficiently perform this optimization on the Stiefel manifold.

The key challenge of Riemannian optimization is that exponential mapping — the standard step for estimating the next update point — is computationally expensive on the Stiefel manifold. Some methods use an efficient pseudo-geodesic retraction instead of the exponential mapping. For example, Absil & Malick (2012); Gawlik & Leok (2018); Manton (2002) use a projection-based method to map the gradient back to the Stiefel manifold that rely on computational expensive SVD. Other approaches are based on the closed-form Cayley transform (Fiori et al., 2012; Jiang & Dai, 2015; Nishimori & Akaho, 2005; Zhu, 2017), but require the costly matrix inversion. Also, Wen & Yin (2013) reduce the cost of the Cayley transform by making the restrictive assumption that the matrix size $n \times p$ is such that $2p \ll n$. Unfortunately, this algorithm is not efficient when $2p \geq n$.

3 PRELIMINARY

This section briefly reviews some well-known properties of the Riemannian and Stiefel manifolds. The interested reader is referred to Boothby (1986); Edelman et al. (1998) and references therein.

3.1 RIEMANNIAN MANIFOLD

Definition 1. *Riemannian Manifold: A Riemannian manifold $(\mathcal{M}, \rho)$ is a smooth manifold $\mathcal{M}$ equipped with a Riemannian metric ρ defined as the inner product on the tangent space $T_x\mathcal{M}$ for each point x, $\rho_x(\cdot, \cdot) : T_x\mathcal{M} \times T_x\mathcal{M} \to \mathbb{R}$.*

Definition 2. *Geodesic, Exponential map and Retraction map: A geodesic is a locally shortest curve on a manifold. An exponential map, $Exp_x(\cdot)$, maps a tangent vector, $v \in T_x$, to a manifold, $\mathcal{M}$. $Exp_x(tv)$ represents a geodesic $\gamma(t) : t \in [0, 1]$ on a manifold, s.t. $\gamma(0) = x, \dot{\gamma}(0) = v$. A retraction map is defined as a smooth mapping $R_x : T_x\mathcal{M} \to \mathcal{M}$ on a manifold iff $R_x(0) = x$ and $DR_x(0) = id_{T_x\mathcal{M}}$, where DR_x denotes the derivative of R_x, $id_{T_x\mathcal{M}}$ denotes an identity map defined on $T_x\mathcal{M}$. It is easy to show that any exponential map is a retraction map. As computing an exponential map is usually expensive, a retraction map is often used as an efficient alternative.*

Definition 3. *Parallel transport and vector transport: Parallel transport is a method to translate a vector along a geodesic on a manifold while preserving norm. A vector transport τ is a smooth map defined on a retraction R of a manifold $\mathcal{M}$, $\tau : T_x\mathcal{M} \times T_x\mathcal{M} \to T_{R(\eta_x)}, (\eta_x, \xi_x) \mapsto \tau_{\eta_x}(\xi_x)$. τ satisfies the following properties: (1) Underlying retraction: $\tau_{\eta_x}(\xi_x) \in T_{R(\eta_x)}$; (2) Consistency: $\tau_{0_x}\xi_x = \xi_x, \forall \xi_x \in T_x\mathcal{M}$; (3) Linearity: $\tau_{\eta_x}(a\xi_x + b\zeta_x) = a\tau_{\eta_x}(\xi_x) + b\tau_{\eta_x}(\zeta_x)$. Usually, a vector transport is a computationally efficient alternative to a parallel transport.*

3.2 STIEFEL MANIFOLD

The Stiefel manifold $St(n, p)$, $n \geq p$, is a Riemannian manifold that is composed of all $n \times p$ orthonormal matrices $\{X \in \mathbb{R}^{n \times p} : X^T X = I\}$. In the rest of the paper, we will use notation $\mathcal{M} = St(n, p)$ to denote the Stiefel manifold. We regard $\mathcal{M}$ as an embeded submanifold of a Euclidean space. Hence, the Riemannian metric ρ is the Euclidean metric as: $\rho_X(Z_1, Z_2) = tr(Z_1^\top Z_2)$, where Z_1, Z_2 are tangent vectors in $T_X\mathcal{M}$. The tangent space of $\mathcal{M}$ at X is defined as

$$T_X\mathcal{M} = \{Z : Z^\top X + X^\top Z = 0\} \tag{1}$$

The projection of a matrix $Z \in \mathbb{R}^{n \times p}$ to $T_X\mathcal{M}$ can be computed as

$$\pi_{T_X}(Z) = WX$$

$$\text{where: } W = \hat{W} - \hat{W}^\top, \quad \hat{W} = ZX^\top - \frac{1}{2}X(X^\top Z X^\top). \tag{2}$$

Given a derivative of the objective function $\nabla f(X)$ at X in the Euclidean space, we can compute the Riemannian gradient $\nabla_\mathcal{M} f(X)$ on the Stiefel manifold as a projection onto $T_X\mathcal{M}$ using $\pi_{T_X}(\nabla f(X))$ given by Eq. 2. It follows that optimization of f on the Riemannian manifold can be computed as follows. First, compute $\nabla_\mathcal{M} f(X_t)$ in $T_X\mathcal{M}$. Second, transport the momentum M_t to the current tangent space $T_X\mathcal{M}$ and combine it linearly with the current Riemannian gradient $\nabla_\mathcal{M} f(X_t)$ to update the momentum M_{t+1}. Finally, third, update the new parameter X_{t+1} along a curve on the manifold with the initial direction as M_{t+1}.

While the exponential map and parallel transport can be used to update parameters and momentums in optimization on the Riemannian manifold, they are computationally infeasible on the Stiefel manifold. In the following section, we specify our computationally efficient alternatives.

3.2.1 PARAMETER UPDATES BY ITERATIVE CAYLEY TRANSFORM

The Cayley transform computes a parametric curve on the Stiefel manifold using a skew-symmetric matrix (Nishimori & Akaho, 2005). The closed-form of the Cayley transform is given by:

$$Y(\alpha) = (I - \frac{\alpha}{2}W)^{-1}(I + \frac{\alpha}{2}W)X, \tag{3}$$

where W is a skew-symmetric matrix, X is on the Stiefel manifold, and $\alpha \geq 0$ is a parameter that represents length on the curve. It is straightforward to verify that

$$Y(0) = X \quad and \quad Y'(0) = WX. \tag{4}$$

From Definition 2 and the definition of the tangent space of the Stiefel manifold given by Eq. 1, the Cayley transform is a valid retraction map on the Stiefel manifold. By choosing $W = \hat{W} - \hat{W}^\top$,

where $\hat{W} = \nabla f(X)X^\top - \frac{1}{2}X(X^\top \nabla f(X)X^\top)$ as in Eq. 2, we see that the Cayley transform implicitly projects gradient on the tangent space as its initial direction. Therefore, the Cayley transform can represent an update for the parameter matrices on the Stiefel manifold.

However, the closed-form Cayley transform in Eq. 3 involves computing the expensive matrix inversion, which cannot be efficiently performed in large deep neural networks.

Our first contribution is an iterative estimation of the Cayley transform that efficiently uses only matrix multiplications, and thus is more efficient than the closed form in Eq. 3. We represent the Cayley transform with the following recurrence relationship:

$$Y(\alpha) = X + \frac{\alpha}{2}W\left(X + Y(\alpha)\right), \tag{5}$$

which can be proved by moving $Y(\alpha)$ on the right-hand side to the left-hand side in Eq. 3. The expression in Eq. 5 is an efficient approximation of Eq. 3. In Sec. 5, we will analyze its convergence rate to the closed-form Eq. 3.

3.2.2 MOMENTUM UPDATES BY THE IMPLICIT VECTOR TRANSPORT

Our second contribution is an efficient way to perform momentum updates on the Stiefel manifold. We specify an implicit vector transport by combining the Cayley transform and momentum update in an elegant way without explicitly computing the vector transport. As the Stiefel manifold can be viewed as a submanifold of the Euclidean space $\mathbb{R}$, we have a natural inclusion of the tangent space $T_X\mathcal{M} \subset \mathbb{R}$. Consequently, the vector transport on the Stiefel manifold is the projection on the tangent space. Formally, for two tangent vectors $\xi_X, \eta_X \in T_X\mathcal{M}$, the vector transport of ξ_X along a retraction map $r(\eta_X)$, denoted as $\tau_{\eta_X}(\xi_X)$, can be computed as:

$$\tau_{\eta_X}(\xi_X) = \pi_{T_{r(\eta_X)}}(\xi_X). \tag{6}$$

We specify the retraction map $r(\cdot)$ as the Cayley transform Y in Eq. 3. At optimization step k, in Eq. 6, we choose $\xi_X = \eta_X = M_k$, where M_k is the momentum in step $k-1$. Then, we compute the vector transport of M_k as $\tau_{M_k}(M_k) = \pi_{T_{X_k}}(M_k)$. As the projection onto a tangent space is a linear map, then $\alpha\tau_{M_k}(M_k) + \beta\nabla_\mathcal{M}f(X_k) = \alpha\pi_{T_{X_k}}(M_k) + \beta\pi_{T_{X_k}}(\nabla f(X_k)) = \pi_{T_{X_k}}(\alpha M_k + \beta\nabla f(X_k))$. Thus we first compute a linear combination of the Euclidean gradient $\nabla f(X)$ and the momentum M_k, as in the Euclidean space, and then use the iterative Cayley transform to update the parameters, without explicitly estimating the vector transport, since the Cayley transform implicitly project vector onto the tangent space.

4 ALGORITHMS

This section specifies our Cayley SGD and Cayley ADAM algorithms. Both represent our efficient Riemannian optimization on the Stiefel manifold that consists of two main steps. As the Cayley transform implicitly projects gradient and momentum vectors onto the tangent space, we first linearly combine the momentum of the previous iteration with the stochastic gradient of the objective function f at the current point X, denoted as $\mathcal{G}(X)$. Then, we use the iterative Cayley transform to estimate the next optimization point based on the updated momentum. This is used to generalize the conventional SGD with momentum and ADAM algorithms to our two new Riemannian optimizations on the Stiefel manifold, as described in Section 4.1 and Section 4.2.

4.1 THE CAYLEY SGD WITH MOMENTUM

We generalize the heavy ball (HB) momentum update (Ghadimi et al., 2015; Zavriev & Kostyuk, 1993) in the kth optimization step[1] to the Stiefel manifold. Theoretically, it can be represented as:

$$M_{k+1} = \beta\pi_{\mathcal{T}_{X_k}}(M_k) - \mathcal{G}_\mathcal{M}(X_k), \quad X_{k+1} = Y(\alpha, X_k, W_k) \tag{7}$$

where $Y(\alpha, X_k, W_k)$ is a curve that starts at X_k with length α on the Stiefel manifold, specified by the Cayley transform in Eq. 3. In practice, we efficiently perform the updates in Eq. 7 by the

---

[1]Note that we use index i in superscript to indicate our iterative steps in estimation of the Cayley transform, and index k in subscript to indicate optimization steps.

Algorithm 1 The Cayley SGD with Momentum

1: **Input:** learning rate lr, momentum coefficient β, $\epsilon=10^{-8}$, $q = 0.5$, $s = 2$.
2: Initialize X_1 as an orthonormal matrix; and $M_1 = 0$
3: **for** $k = 0$ **to** T **do**
4:      $M_{k+1} \leftarrow \beta M_k - \mathcal{G}(X_k)$,   ▷ Update the momentum
5:      $\hat{W}_k \leftarrow M_{k+1}X_k^\top - \frac{1}{2}X_k(X_k^\top M_{k+1} X_k^\top)$ *▷ Compute the auxiliary matrix*
6:      $W_k \leftarrow \hat{W}_k - \hat{W}_k^\top$
7:      $M_{k+1} \leftarrow W_k X_k$.   *▷ Project momentum onto the tangent space*
8:      $\alpha \leftarrow \min\{lr, 2q/(\|W_k\| + \epsilon)\}$ *▷ Select adaptive learning rate for contraction mapping*
9:      Initialize $Y^0 \leftarrow X + \alpha M_{k+1}$ *▷ Iterative estimation of the Cayley Transform*
10:      **for** $i = 1$ **to** s **do**
11:          $Y^i \leftarrow X_k + \frac{\alpha}{2}W_k(X_k + Y^{i-1})$
12:      Update $X_{k+1} \leftarrow Y^s$

Algorithm 2 The Cayley ADAM

1: **Input:** learning rate lr, momentum coefficients β_1 and β_2, $\epsilon = 10^{-8}$, $q = 0.5$, $s = 2$.
2: Initialize X_1 as an orthonormal matrix. $M_1 = 0$, $v_1 = 1$
3: **for** $k = 0$ **to** T **do**
4:      $M_{k+1} \leftarrow \beta_1 M_k + (1 - \beta_1)\mathcal{G}(X_k)$ *▷ Estimate biased momentum*
5:      $v_{k+1} \leftarrow \beta_2 v_k + (1 - \beta_2)\|\mathcal{G}(X_k)\|^2$
6:      $\hat{v}_{k+1} \leftarrow v_{k+1}/(1 - \beta_2^k)$ *▷ Update biased second raw moment estimate*
7:      $r \leftarrow (1 - \beta_1^k)\sqrt{\hat{v_{k+1}}} + \epsilon$ *▷ Estimate biased-corrected ratio*
8:      $\hat{W}_k \leftarrow M_{k+1}X_k^\top - \frac{1}{2}X_k(X_k^\top M_{k+1} X_k^\top)$ *▷ Compute the auxiliary skew-symmetric matrix*
9:      $W_k \leftarrow (\hat{W}_k - \hat{W}_k^\top)/r$
10:     $M_{k+1} \leftarrow rW_k X_k$ *▷ Project momentum onto the tangent space*
11:     $\alpha \leftarrow \min\{lr, 2q/(\|W_k\| + \epsilon)\}$ *▷ Select adaptive learning rate for contraction mapping*
12:     Initialize $Y^0 \leftarrow X_k - \alpha M_{k+1}$ *▷ Iterative estimation of the Cayley Transform*
13:     **for** $i = 1$ **to** s **do**
14:         $Y^i \leftarrow X_k - \frac{\alpha}{2}W(X_k + Y^{i-1})$
15:     Update $X_{k+1} \leftarrow Y^s$

---

proposed iterative Cayley transform and implicit vector transport on the Stiefel manifold. Specially, we first update the momentum as if it were in the Euclidean space. Then, we update the new parameters by iterative Cayley transform. Finally, we correct the momentum M_{k+1} by projecting it to $T_{X_k}\mathcal{M}$. The details of our Cayley SGD algorithm are shown in Alg. 1.

4.2 THE ADAM ON THE STIEFEL MANIFOLD

ADAM is a recent first-order optimization method for stochastic objective functions. It estimates adaptive lower-order moments and uses adaptive learning rate. The algorithm is designed to combine the advantages of both AdaGrad, which performs well in sparse-gradient cases, and RMSProp, which performs well in non-stationary cases.

We generalize ADAM to the Stiefel manifold by making three modifications to the vanilla ADAM. First, we replace the standard gradient and momentum with the corresponding ones on the Stiefel manifold, as described in Section 4.1. Second, we use a manifold-wise adaptive learning rate that assign a same learning rate for all entries in a parameter matrix as in (Absil et al., 2009). Third, we use the Cayley transform to update the parameters. The Cayley ADAM is summarized in Alg 2.

5 CONVERGENCE ANALYSIS

In this section, we analyze convergence of the iterative Cayley transform and Cayley SGD with momentum. To facilitate our analysis, we make the following common assumption.

Assumption 1. *The gradient ∇f of the objective function f is Lipschitz continuous*

$$\|\nabla f(X) - \nabla f(Y)\| \le L\|X - Y\|, \quad \forall X, Y, \text{ where } L > 0 \text{ is a constant.} \tag{8}$$

Lipschitz continuous is widely applicable to deep learning architectures. For some models using ReLU, the derivative of ReLU is Lipschitz continuous almost everywhere, except for a small neighbourhood around 0, i.e. $(-\epsilon, \epsilon)$, where ϵ is a small positive number. In practice, such cases do not affect training.

The above assumption allows proving the following contraction mapping theorem.

Theorem 1. *For $\alpha \in (0, \min\{1, \frac{2}{\|W\|}\})$, the iteration $Y^{i+1} = X + \frac{\alpha}{2}W\left(X + Y^i\right)$ is a contraction mapping and converges to the closed-form Cayley transform $Y(\alpha)$ given by Eq. 3. Specifically, at iteration i, $\|Y^i - Y(\alpha)\| = o(\alpha^{2+i})$.*

Theorem 1 shows the iterative Cayley transform will converge. Specially, it converges faster than other approximation algorithms, such as, e.g., the Newton iterative and Neumann Series which achieves error bound $o(\alpha^i)$ at the i^{th} iteration. We further prove the following result on convergence:

Theorem 2. *Given an objective function $f(X)$ that satisfies Assumption 1, let the Cayley SGD with momentum run for t iterations with $\mathcal{G}(X_k)$. For $\alpha = \min\{\frac{1-\beta}{L}, \frac{A}{\sqrt{t+1}}\}$, where A is a positive constant, we have: $\min_{k=0,\cdots,t} E[\|\nabla_{\mathcal{M}}f(X_k)\|^2] = o(\frac{1}{\sqrt{t+1}}) \to 0, as\ t \to \infty$.*

The proofs of Theorem 1 and Theorem 2 are presented in the appendix.

6 EXPERIMENTS

6.1 ORTHONORMALITY IN CNNS

In CNNs, for a convolutional layer with kernel $\hat{K} \in \mathbb{R}^{c_{out} \times c_{in} \times h \times w}$, we first reshape $\hat{K}$ into a matrix K of size $p \times n$, where $p = c_{out}$, $n = c_{in} \times h \times w$. In most cases, we have $p \leq n$. Then, we restrict the matrix K on the Stiefel manifold using the Cayley SGD or Cayley ADAM, while other parameters are optimized with the SGD and ADAM.

Datasets: We evaluate the Cayley SGD or Cayley ADAM in image classification on the CIFAR10 and CIFAR100 datasets (Krizhevsky & Hinton, 2009). CIFAR10 and CIFAR100 consist of of 50,000 training images and 10,000 test images, and have 10 and 100 mutually exclusive classes.

Models: We use two networks — Vgg (Simonyan & Zisserman, 2014) and Wide Resnet (Zagoruyko & Komodakis, 2016) — that give the state-of-the-art performance on CIFAR10 and CIFAR100. For Vgg, every convolutional layer is followed by a batch normalization layer and a ReLU. For Wide Resnet, we use basic blocks, where two consecutive 3-by-3 convolutional layers are followed by the batch normalization and ReLU activation, respectively.

Training Strategies: We use different learning rates lr_e and lr_{st} for weights on the Euclidean space and the Stiefel manifold, respectively. We set the weight decay as 0.0005, momentum as 0.9, and minibatch size as 128. The initial learning rates are set as $lr_e = 0.01$ and $lr_{st} = 0.2$ for the Cayley SGD and $lr_e = 0.01$ and $lr_{st} = 0.4$ for the Cayley ADAM. During training, we reduce the learning rates by a factor of 0.2 at 60, 120, 160 epochs. The total number of epochs in training is 200. In training, the data samples are normalized using the mean and variance of the training set, and augmented by randomly flipping training images.

Our baselines include the SGD with momentum and ADAM. We follow the same training strategies as mentioned above, except for the initial learning rates set to 0.1 and 0.001, respectively.

Performance: Table 1 and Table 2 show classification errors on CIFAR10 and CIFAR100 respectively using different optimization algorithms. As shown in the tables, the proposed two algorithms achieve competitive performance, and for certain deep architectures, the best performance. Specifically, the network WRN-28-10 trained with the Cayley ADAM achieves the best error rate of 3.57%

Table 1: Classification errors(%) on CIFAR10.

METHOD	VGG-13	VGG-16	VGG-19	WRN 52-1	WRN 16-4	WRN 28-10
SGD	5.88	6.32	6.49	6.23	4.96	3.89
ADAM	6.43	6.61	6.92	6.77	5.32	3.86
CAYLEY SGD	5.90	**5.77**	5.85	6.35	5.15	3.66
CAYLEY ADAM	5.93	5.88	6.03	6.44	5.22	**3.57**

Table 2: Classification errors(%) on CIFAR100.

METHOD	VGG-13	VGG-16	VGG-19	WRN 52-1	WRN 16-4	WRN 28-10
SGD	26.17	26.84	27.62	27.44	23.41	18.66
ADAM	26.58	27.10	27.88	27.89	24.45	18.45
CAYLEY SGD	**24.86**	25.48	25.68	27.64	23.71	18.26
CAYLEY ADAM	25.10	25.61	25.70	27.91	24.18	**18.10**

and 18.10% on CIFAR10 and CIFAR100 respectively. Fig. 1 compares training curves of our algorithms and baselines, and shows that both the Cayley SGD and Cayley ADAM converge faster than the baselines. In particular, the training curves of the baselines tend to get stuck in a plateau before the learning rate drops, which is not the case with our algorithms. This might be because the baselines to do not enforce orthonormality of network parameters. In training, the backpropagation of orthonormal weight vectors, in general, does not affect each other, and thus has greater chances to explore new parameter regions.

(a) CIFAR10

(b) CIFAR100

Figure 1: Training loss curves of different optimization algorithms for WRN-28-10 for epoach 40-100. (a) Results on CIFAR10. (b) Results on CIFAR100. Both figures show that our Cayley SGD and Cayley ADAM achieve the top two fastest convergence rates.

Comparison with State of the Art. We compare the proposed algorithms with two sets of state of the art. The first set of approaches are soft orthonormality regularization approaches (Bansal et al., 2018). Specially, for a weight matrix $K \in \mathbb{R}^{n \times p}$, SO penalizes $||KK^{\top} - I||_F^2$, DSO penalizes $(||KK^{\top} - I||_F^2 + ||K^{\top}K - I||_F^2)$, the SRIP penalizes the spectral norm of $(KK^{\top} - I)$. The second set of approaches includes the following hard orthonormality methods: Polar decomposition(Absil et al., 2009), QR decomposition(Absil et al., 2009), closed-form Cayley transform, Wen&Yin (Wen & Yin, 2013), OMDSM(Huang et al., 2018a), DBN(Huang et al., 2018b). Note that we do not in-

Table 3: Error rate and training time per epoch comparison to baselines with WRN-28-10 on CIFAR10 and CIFAR100. All experiments are performed on one TITAN Xp GPU.

		Error Rate(%)		
	Method	CIFAR10	CIFAR100	Training time(s)
Baselines	SGD	3.89	18.66	102.5
	ADAM	3.85	18.52	115.2
Soft orthonormality	SO (Bansal et al., 2018)	3.76	18.56	297.3
	DSO (Bansal et al., 2018)	3.86	18.21	311.0
	SRIP (Bansal et al., 2018)	3.60	18.19	321.8
Hard orthonormality	OMDSM (Huang et al., 2018a)	3.73	18.61	943.6
	DBN (Huang et al., 2018b)	3.79	18.36	889.4
	Polar (Absil et al., 2009)	3.75	18.50	976.5
	QR (Absil et al., 2009)	3.75	18.65	469.3
	Wen&Yin (Wen & Yin, 2013)	3.82	18.70	305.8
	Cayley closed form w/o momentum	3.80	18.68	1071.5
	Cayley SGD (**Ours**)	3.66	18.26	218.7
	Cayley ADAM (**Ours**)	3.57	18.10	224.4

Table 4: Pixel-by-pixel MNIST accuracy and training time per iteration of the closed-form Cayley Transform, Cayley SGD, and Cayley ADAM for Full-uRNNs (Wisdom et al., 2016). All experiments are performed on one TITAN Xp GPU.

Model	Hidden Size	Closed-Form		Cayley SGD		Cayley ADAM	
		Acc(%)	Time(s)	Acc(%)	Time(s)	Acc(%)	Time(s)
Full-uRNN	116	92.8	2.10	92.6	1.42	92.7	1.50
Full-uRNN	512	96.9	2.44	96.7	1.67	**96.9**	1.74

clude momentum in Polar decomposition and QR decomposition as previous work does not specify the momentum. Also, we use the closed-form Cayley transform without momentum as an ablation study of the momentum effect. All experiments are evaluated on the benchmark network WRN-28-10. Table 3 shows that our algorithms achieve comparable error rates with the state of art work. Moreover, we run all algorithms on one TITAN Xp GPU, and compare their average training time per epoch. Table 3 shows that our algorithms run much faster than existing algorithms, except for the baseline SCD and ADAM which do not impose orthonormality constraints.

6.2 ORTHONORMALITY IN RNNS

In RNNs, the hidden-to-hidden transition matrix K can be modeled as unitary matrix (Arjovsky et al., 2016). Wisdom et al. (2016) model the hidden-to-hidden transition matrix as a full-capacity unitary matrix on the complex Stiefel manifold: $\text{St}(\mathbb{C}^N) = \{K \in \mathbb{C}^{N \times N} : K^H K = I\}$.

Pixel-by-pixel MNIST: We evaluate the proposed algorithms on the challenging pixel-by-pixel MNIST task for long-term memory. The task was used to test the capacity of uRNNs (Arjovsky et al., 2016; Wisdom et al., 2016). Following the same setting as in Wisdom et al. (2016), we reshape MNIST images of 28×28 pixels to a $T = 784$ pixel-by-pixel sequences, and select 5000 out of the 60000 training examples for the early stopping validation.

Training: Wisdom et al. (2016) restricted the transition unitary matrix on the Stiefel manifold via closed-form Cayley transform. On the contrary, we use the Cayley SGD with momentum and Cayley ADAM to reduce the training time. Table 4 shows that the proposed algorithms reduces the training time by about 35% for all settings of the network, while maintaining the same level of accuracy. All experiments are performed on one TITAN Xp GPU.

Checking Unitariness: To show that the proposed algorithms are valid optimization algorithms on the Stiefel manifold, we check the unitariness of the hidden-to-hidden matrix K by computing the error term $||K^H K - I||_F$ during training. Table 5 compares average errors for varying numbers of iterations s. As can be seen, the iterative Cayley transform can approximate the unitary matrix when $s = 2$. The iterative Cayley transform performs even better than the closed form Cayley transform, which might be an effect of the rounding error of the matrix inversion as in Eq. 3.

Table 5: Checking unitariness by computing the error $||K^H K - I||_F$ for varying numbers of iterations in the iterative Cayley transform and the closed-form Cayley transform.

Hidden Size	s=0	s=1	s=2	s=3	s=4	Closed-form
n=116	3.231e-3	2.852e-4	7.384e-6	7.353e-6	7.338e-6	8.273e-5
n=512	6.787e-3	5.557e-4	2.562e-5	2.547e-5	2.544e-5	3.845e-5

7 CONCLUSION

We specified an efficient way to enforce the exact orthonormal constraints on parameters by optimization on the Stiefel manifold. The iterative Cayley transform was applied to the conventional SGD and ADAM for specifying two new algorithms: Cayley SGD with momentum and Cayley ADAM, and the theoretical analysis of convergence of the former. The experiments show that both algorithms achieve comparable performance and faster convergence over the baseline SGD and ADAM in training of the standard Vgg and ResNet on CIFAR10 and CIFAR100, as well as RNNs on the pixel-by-pixel MNIST task. Both Cayley SGD with momentum and Cayley ADAM take less runtime per iteration than all existing hard orthonormal methods and soft orthonormal methods, and can be applied to non-square parameter matrices.

REFERENCES

P-A Absil and Jérôme Malick. Projection-like retractions on matrix manifolds. *SIAM Journal on Optimization*, 22(1):135–158, 2012.

P-A Absil, Robert Mahony, and Rodolphe Sepulchre. *Optimization algorithms on matrix manifolds*. Princeton University Press, 2009.

Martin Arjovsky, Amar Shah, and Yoshua Bengio. Unitary evolution recurrent neural networks. In *International Conference on Machine Learning*, pp. 1120–1128, 2016.

Nitin Bansal, Xiaohan Chen, and Zhangyang Wang. Can we gain more from orthogonality regularizations in training deep cnns? *arXiv preprint arXiv:1810.09102*, 2018.

Gary Becigneul and Octavian-Eugen Ganea. Riemannian adaptive optimization methods. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=r1eiqi09K7.

William M Boothby. *An introduction to differentiable manifolds and Riemannian geometry*, volume 120. Academic press, 1986.

Minhyung Cho and Jaehyung Lee. Riemannian approach to batch normalization. In *Advances in Neural Information Processing Systems*, pp. 5225–5235, 2017.

Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 854–863. JMLR. org, 2017.

Michael Cogswell, Faruk Ahmed, Ross Girshick, Larry Zitnick, and Dhruv Batra. Reducing overfitting in deep networks by decorrelating representations. *arXiv preprint arXiv:1511.06068*, 2015.

Victor Dorobantu, Per Andre Stromhaug, and Jess Renteria. Dizzyrnn: Reparameterizing recurrent neural networks for norm-preserving backpropagation. *arXiv preprint arXiv:1612.04035*, 2016.

Alan Edelman, Tomás A Arias, and Steven T Smith. The geometry of algorithms with orthogonality constraints. *SIAM journal on Matrix Analysis and Applications*, 20(2):303–353, 1998.

Simone Fiori, Tetsuya Kaneko, and Toshihisa Tanaka. Learning on the compact stiefel manifold by a cayley-transform-based pseudo-retraction map. In *The 2012 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8. IEEE, 2012.

Evan S Gawlik and Melvin Leok. High-order retractions on matrix manifolds using projected polynomials. *SIAM Journal on Matrix Analysis and Applications*, 39(2):801–828, 2018.

Euhanna Ghadimi, Hamid Reza Feyzmahdavian, and Mikael Johansson. Global convergence of the heavy-ball method for convex optimization. In *Control Conference (ECC), 2015 European*, pp. 310–315. IEEE, 2015.

Kyle Helfrich, Devin Willmott, and Qiang Ye. Orthogonal recurrent neural networks with scaled cayley transform. *arXiv preprint arXiv:1707.09520*, 2017.

Lei Huang, Xianglong Liu, Bo Lang, Adams Wei Yu, Yongliang Wang, and Bo Li. Orthogonal weight normalization: Solution to optimization over multiple dependent Stiefel manifolds in deep neural networks. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018a.

Lei Huang, Dawei Yang, Bo Lang, and Jia Deng. Decorrelated batch normalization. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018b.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 448–456, Lille, France, 07–09 Jul 2015. PMLR. URL http://proceedings.mlr.press/v37/ioffe15.html.

Bo Jiang and Yu-Hong Dai. A framework of constraint preserving update schemes for optimization on stiefel manifold. *Mathematical Programming*, 153(2):535–575, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Mario Lezcano-Casado and David Martínez-Rubio. Cheap orthogonal constraints in neural networks: A simple parametrization of the orthogonal and unitary group. *arXiv preprint arXiv:1901.08428*, 2019.

Jonathan H Manton. Optimization algorithms exploiting unitary constraints. *IEEE Transactions on Signal Processing*, 50(3):635–650, 2002.

Yasunori Nishimori and Shotaro Akaho. Learning algorithms utilizing quasi-geodesic flows on the stiefel manifold. *Neurocomputing*, 67:106–135, 2005.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Eugene Vorontsov, Chiheb Trabelsi, Samuel Kadoury, and Chris Pal. On orthogonality and learning recurrent networks with long term dependencies. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 3570–3578. JMLR. org, 2017.

Zaiwen Wen and Wotao Yin. A feasible method for optimization with orthogonality constraints. *Mathematical Programming*, 142(1-2):397–434, 2013.

Scott Wisdom, Thomas Powers, John Hershey, Jonathan Le Roux, and Les Atlas. Full-capacity unitary recurrent neural networks. In *Advances in Neural Information Processing Systems*, pp. 4880–4888, 2016.

Wei Xiong, Bo Du, Lefei Zhang, Ruimin Hu, and Dacheng Tao. Regularizing deep convolutional neural networks with a structured decorrelation constraint. In *2016 IEEE 16th International Conference on Data Mining (ICDM)*, pp. 519–528. IEEE, 2016.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

SK Zavriev and FV Kostyuk. Heavy-ball method in nonconvex optimization problems. *Computational Mathematics and Modeling*, 4(4):336–341, 1993.

Jianping Zhou, Minh N. Do, and Jelena Kovacevic. Special paraunitary matrices, Cayley transform, and multidi- mensional orthogonal filter banks. *IEEE Trans. Image Processing*, 15(2):511–519, 2006.

Xiaojing Zhu. A riemannian conjugate gradient method for optimization on the stiefel manifold. *Computational Optimization and Applications*, 67(1):73–110, 2017.

A   CONVERGENCE RATE COMPARISON IN TIME

In this section, we analyse the time convergence rate of the proposed methods. Fig. 2 shows the training loss curve of Cayley SGD and Cayley Adam with other optimization methods for CIFAR10 and CIFAR100. Our Cayley SGD and Cayley Adam converge the fastest in terms of time among methods that also address orthonormality. Although the baselines SGD and Adam converge faster at the beginning due to their training efficiency, our Cayley SGD and Cayley Adam can catch up with the baseline after 12000 seconds, and their classification accuracy are lower as shown in Table 1 and 2, because of the lack of orthogonality constraints.

| (a) CIFAR10 | (b) CIFAR100 |

Figure 2: Training loss curves of different optimization algorithms for WRN-28-10 in terms of seconds. (a) Results on CIFAR10. (b) Results on CIFAR100.

B   PRELIMINARY

In this section, we derive some properties of the Stiefel manifold in this section to facilitate the proofs of **Theorem 1** and **Theorem 2** in the main paper.

Considering the Stiefel manifold $\mathcal{M}$ is a bounded set and Lipschitz Assumption 1 on the gradient in Sec. 5, one straightforward conclusion is that both $\nabla f(X)$ and its Stiefel manifold gradient $\nabla_{\mathcal{M}} f(X)$ that is a projection onto the tangent space are bounded. Formally, there exists a positive constant G, such that

$$||\nabla_{\mathcal{M}} f(X)|| \leq ||\nabla f(X)|| \leq G, \forall X \in \mathcal{M} \tag{9}$$

As stochastic gradient $\mathcal{G}(X) = \mathcal{G}(X; \xi)$ is the gradient of a sub-dataset, where ξ is a stochastic variable for data samples and we are working are a finite dataset, it's straightforward to show that $\mathcal{G}(X)$ and its Riemannian stochastic gradient $\mathcal{G}_{\mathcal{M}}(X)$ are also bounded. For brevity, we still use the same upper bound G, such that:

$$||\mathcal{G}_{\mathcal{M}}(X)|| \leq ||\mathcal{G}(X)|| \leq G, \forall X \in \mathcal{M} \tag{10}$$

Recall the recursion in Eq. 7, we show that the momentum is also bounded:

$$||M_{k+1}|| \leq \beta ||M_k|| + ||\mathcal{G}_{\mathcal{M}}(X_k)||$$
$$\leq \sum_{i=0}^{k} \beta^{k-i} ||\mathcal{G}_{\mathcal{M}}(X_i)||$$
$$\leq \frac{1}{1-\beta} G \tag{11}$$

Therefore, we know that W_k in Eq. 7 is bounded.

C PROOF OF THEOREM 1

Proof. By subtracting the iterative relationship Eq. 5 by its i^{th} iteration $Y^{i+1} = X + \frac{\alpha}{2}W(X + Y^i)$, we have:

$$||Y^{i+1} - Y(\alpha)|| \leq \frac{\alpha||W||}{2}||Y^i - Y(\alpha)|| \tag{12}$$

Therefore, since W is bounded, for $\alpha < \frac{2}{||W||}$, such that $\frac{\alpha||W||}{2} < 1$, the iteration in Eq. 5 is a contraction mapping, and it will converge to the closed-from solution $Y(\alpha)$.

By differentiate Eq. 5, we have:

$$\frac{dY(\alpha)}{d\alpha} = W(\frac{X + Y(\alpha)}{2}) + \frac{\alpha}{2}W\frac{dY(\alpha)}{d\alpha}$$
$$\frac{d^2Y(\alpha)}{d\alpha^2} = (I - \frac{\alpha}{2}W)^{-1}W\frac{dY(\alpha)}{d\alpha} \tag{13}$$

therefore, $\frac{dY(\alpha)}{d\alpha}$ and $\frac{d^2Y(\alpha)}{d\alpha^2}$ are bounded, i.e. there exist a positive constant C, such that:

$$||\frac{d^2Y(\alpha)}{d\alpha^2}|| \leq C \tag{14}$$

Using the Taylor expansion of Y in Eq. 3, we have:

$$Y(\alpha) = X_k + \alpha M_{k+1} + \frac{1}{2}\alpha^2\frac{d^2Y(\gamma_k\alpha)}{d\alpha^2} \tag{15}$$

where $\gamma_k \in (0, 1)$. Given $Y^0 = X_k + \alpha M_{k+1}$, we have:

$$||Y^0 - Y(\alpha)|| = o(\alpha^2) \tag{16}$$

Since W is bounded and $\frac{\alpha||W||}{2} < 1$, then,

$$||Y^i - Y(\alpha)|| \leq (\frac{\alpha||W||}{2})^i||Y^0 - Y(\alpha)|| = o(\alpha^{2+i}) \tag{17}$$

$\square$

D PROOF OF THEOREM 2

Proof. Use Taylor expansion of $Y(\alpha)$, the process of Cayley SGD with momentum Eq. 7 can be written as:

$$M_{k+1} = \pi_{\mathcal{T}_{X_k}}(\beta M_k) - \mathcal{G}_{\mathcal{M}}(X_k)$$
$$X_{k+1} = X_k + \alpha M_{k+1} + \frac{1}{2}\alpha^2\frac{d^2Y(\gamma_k\alpha)}{d\alpha^2} \tag{18}$$

where $\gamma_k \in (0, 1)$.

Using the fact that

$$M = \pi_{\mathcal{T}_X}(M) + \pi_{\mathcal{N}_X}(M) \tag{19}$$

where $\pi_{\mathcal{N}_X}(M)$ is the projection onto the normal space, and

$$\pi_{\mathcal{N}_X}(M) = X\frac{X^\top M + M^\top X}{2} \tag{20}$$

Then, the projection of momentum can be represented as:

$$
\begin{aligned}
\pi_{\mathcal{T}_{X_k}}(M_k) &= M_k - \pi_{\mathcal{N}_{X_k}}(M_k)\\
&= M_k - X_k \frac{X_k^\top M_k + M_k^\top X_k}{2}\\
&= M_k - \frac{1}{2}X_k\{[X_{k-1} + \alpha M_k + \frac{1}{2}\alpha^2 \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}]^\top M_k\\
&\quad + M_k^\top[X_{k-1} + \alpha M_k + \frac{1}{2}\alpha^2 \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}]\}\\
&= M_k - \alpha X_k M_k^\top M_k - \frac{1}{4}\alpha^2 X_k[\frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}^\top M_k + M_k^\top \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}] \quad\quad (21)
\end{aligned}
$$

Then the momentum update in Eq. 7 is equivalent to:

$$
\begin{aligned}
M_{k+1} &= \beta M_k - \alpha\beta X_k M_k^\top M_k - \mathcal{G}_\mathcal{M}(X_k)\\
&\quad - \frac{1}{4}\alpha^2\beta X_k[\frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}^\top M_k + M_k^\top \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}] \quad\quad (22)
\end{aligned}
$$

Therefore, the paramter update in Eq. 7 can be represented as:

$$
\begin{aligned}
X_{k+1} &= X_k + \alpha\beta M_k - \alpha\mathcal{G}_\mathcal{M}(X_k)\\
&\quad - \frac{1}{4}\alpha^3\beta X_k[\frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}^\top M_k + M_k^\top \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}]\\
&\quad - \alpha^2\beta X_k M_k^\top M_k + \frac{1}{2}\alpha^2 \frac{d^2 Y(\gamma_k\alpha)}{d\alpha^2}\\
&= X_k + \beta(X_k - X_{k-1}) - \alpha\mathcal{G}_\mathcal{M}(X_k) + \alpha^2 U \quad\quad (23)
\end{aligned}
$$

where

$$
\begin{aligned}
U &= -\frac{1}{4}\alpha\beta X_k[\frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}^\top M_k + M_k^\top \frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2}]\\
&\quad - \beta X_k M_k^\top M_k + \frac{1}{2}\frac{d^2 Y(\gamma_k\alpha)}{d\alpha^2} - \frac{\beta}{2}\frac{d^2 Y(\gamma_{k-1}\alpha)}{d\alpha^2} \quad\quad (24)
\end{aligned}
$$

Since $||M||$, $||X||$, and $||\frac{d^2 Y}{d\alpha^2}||$ are bounded, there is a positive constant D, such that

$$
||U|| \le D \quad\quad (25)
$$

To facilitate the analysis of Cayle SGD with momentum, we introduce auxiliary variables $\{P_k\}$, such that:

$$
Z_{k+1} = Z_k - \frac{\alpha}{1-\beta}\mathcal{G}_\mathcal{M}(X_k) + \frac{\alpha^2}{1-\beta}U
$$
$$(26)$$

where

$$
Z_k = X_k + P_k \quad\quad (27)
$$

and

$$
P_k = \begin{cases} \dfrac{\beta}{1-\beta}(X_k - X_{k-1}), k \ge 1\\ 0, k = 0 \end{cases}
$$

Since $f(X)$ is a smooth function according to Assumption 1, we have:

$$f(Y) - f(X) - tr(\nabla f(X)^\top (Y - X))$$

$$= \int_0^1 \nabla tr(f(Y + t(Y - X))^\top (Y - X))dt - tr(\nabla f(X)^\top (Y - X))$$

$$\leq || \int_0^1 (\nabla f(Y + t(Y - X)) - \nabla f(X))dt|| \times ||Y - X||$$

$$\leq \int_0^1 L||t(Y - X)||dt \times ||Y - X||$$

$$\leq \frac{L}{2}||Y - X||^2 \tag{28}$$

Then, we have

$$f(Z_{k+1}) \leq f(Z_k) + tr(\nabla f(Z_k)^\top (Z_{k+1} - Z_k)) + \frac{L}{2}||Z_{k+1} - Z_k||^2$$

$$= f(Z_k) + tr(\nabla f(Z_k)^\top (Z_{k+1} - Z_k)) + \frac{L}{2}||\frac{\alpha}{1-\beta}\mathcal{G}_\mathcal{M}(X_k) - \frac{\alpha^2}{1-\beta}U||^2$$

$$\leq f(Z_k) + tr(\nabla f(Z_k)^\top (Z_{k+1} - Z_k)) + \frac{L\alpha^2}{(1-\beta)^2}||\mathcal{G}_\mathcal{M}(X_k)||^2 + \frac{L\alpha^4}{(1-\beta)^2}||U||^2$$

$$\leq f(Z_k) - \frac{\alpha}{1-\beta}tr(\mathcal{G}_\mathcal{M}(X_k)^\top \nabla f(Z_k)) + \frac{\alpha^2}{1-\beta}tr(U^\top \nabla f(Z_k)) + \frac{L\alpha^2}{(1-\beta)^2}G^2$$

$$+ \frac{L\alpha^4}{(1-\beta)^2}D^2$$

$$\leq f(Z_k) - \frac{\alpha}{1-\beta}tr(\mathcal{G}_\mathcal{M}(X_k)^\top \nabla f(Z_k)) + \frac{\alpha^2}{2(1-\beta)}(||U||^2 + ||\nabla f(Z_k)||^2) + \frac{L\alpha^2}{(1-\beta)^2}G^2$$

$$+ \frac{L\alpha^4}{(1-\beta)^2}D^2$$

$$\leq f(Z_k) - \frac{\alpha}{1-\beta}tr(\mathcal{G}_\mathcal{M}(X_k)^\top \nabla f(Z_k)) + \frac{\alpha^2}{2(1-\beta)}(D^2 + G^2)$$

$$+ \frac{L\alpha^2}{(1-\beta)^2}G^2 + \frac{L\alpha^4}{(1-\beta)^2}D^2 \tag{29}$$

By taking expectation over the both sides, we have:

$$\mathbb{E}[f(Z_{k+1}) - f(Z_k))]$$

$$\leq \mathbb{E}[-\frac{\alpha}{1-\beta}tr(\nabla f(Z_k)^\top \nabla_\mathcal{M} f(X_k))] + \frac{\alpha^2}{2(1-\beta)}(D^2 + G^2) + \frac{L\alpha^2}{(1-\beta)^2}G^2 + \frac{L\alpha^4}{(1-\beta)^2}D^2$$

$$\leq \mathbb{E}[-\frac{\alpha}{1-\beta}tr(\nabla f(Z_k) - \nabla f(X_k))^\top \nabla_\mathcal{M} f(X_k) - \frac{\alpha}{1-\beta}tr(\nabla f(X_k)^\top \nabla_\mathcal{M} f(X_k))]$$

$$+ \frac{\alpha^2}{2(1-\beta)}(D^2 + G^2) + \frac{L\alpha^2}{(1-\beta)^2}G^2 + \frac{L\alpha^4}{(1-\beta)^2}D^2$$

$$= \mathbb{E}[-\frac{\alpha}{1-\beta}tr(\nabla f(Z_k) - \nabla f(X_k))^\top \nabla_\mathcal{M} f(X_k) - \frac{\alpha}{1-\beta}||\nabla_\mathcal{M} f(X_k)||^2]$$

$$+ \frac{\alpha^2}{2(1-\beta)}(D^2 + G^2) + \frac{L\alpha^2}{(1-\beta)^2}G^2 + \frac{L\alpha^4}{(1-\beta)^2}D^2 \tag{30}$$

By noticing that:

$$- \frac{\alpha}{1-\beta}(\nabla f(Z_k) - \nabla f(X_k))^\top \nabla_\mathcal{M} f(X_k)$$

$$\leq \frac{1}{2L}||\nabla f(Z_k) - \nabla f(X_k)||^2 + \frac{L\alpha^2}{2(1-\beta)^2}||\nabla_\mathcal{M} f(X_k)||^2 \tag{31}$$

Then

$$
\mathbb{E}[f(Z_{k+1}) - f(Z_k))]
$$
$$
\leq \frac{1}{2L}\mathbb{E}||\nabla f(Z_k) - \nabla f(X_k)||^2 + (\frac{L\alpha^2}{2(1-\beta)^2} - \frac{\alpha}{1-\beta})\mathbb{E}||\nabla_{\mathcal{M}}f(X_k)||^2
$$
$$
+ \frac{\alpha^2}{2(1-\beta)}(D^2 + G^2) + \frac{L\alpha^2}{(1-\beta)^2}G^2 + \frac{L\alpha^4}{(1-\beta)^2}D^2 \tag{32}
$$

According to the Lipschitz continuous property in Assumption 1, we have:

$$
\begin{aligned}
||\nabla f(Z_k) - \nabla f(X_k)||^2 &\leq L^2||Z_k - X_k||^2 \\
&= \frac{L^2\beta^2}{(1-\beta)^2}||X_k - X_{k-1}||^2 \\
&= \frac{L^2\beta^2}{(1-\beta)^2}||\alpha M_k + \frac{1}{2}\alpha^2\frac{d^2Y(\gamma_k\alpha)}{d\alpha^2}||^2 \\
&\leq \frac{2L^2\beta^2}{(1-\beta)^2}(||\alpha M_k||^2 + ||\frac{1}{2}\alpha^2\frac{d^2Y(\gamma_k\alpha)}{d\alpha^2}||^2) \\
&\leq \frac{2L^2\alpha^2\beta^2}{(1-\beta)^2}(\frac{G^2}{(1-\beta)^2} + \frac{\alpha^2C^2}{4})
\end{aligned} \tag{33}
$$

Therefore,

$$
\mathbb{E}[f(Z_{k+1}) - f(Z_k))]
$$
$$
\leq -B\mathbb{E}||\nabla_{\mathcal{M}}f(X_k)||^2 + \alpha^2 B' \tag{34}
$$

where

$$
B = \frac{\alpha}{1-\beta} - \frac{L\alpha^2}{2(1-\beta)^2} \tag{35}
$$
$$
B' = \frac{L\beta^2}{(1-\beta)^2}(\frac{G^2}{(1-\beta)^2} + \frac{\alpha^2C^2}{4}) + \frac{D^2 + G^2}{2(1-\beta)} + \frac{LG^2}{(1-\beta)^2} + \frac{L\alpha^2}{(1-\beta)^2}D^2 \tag{36}
$$

Since $\alpha \leq \frac{1-\beta}{L}$, then

$$
\begin{aligned}
B &= \frac{\alpha}{1-\beta} - \frac{L\alpha^2}{2(1-\beta)^2} \\
&= \frac{\alpha}{1-\beta}(1 - \frac{\alpha L}{2(1-\beta)}) \\
&\geq \frac{\alpha}{2(1-\beta)} > 0
\end{aligned} \tag{37}
$$

By summing Eq. 34 over all k, we have

$$
B\sum_{k=0}^{t}\mathbb{E}||\nabla_{\mathcal{M}}f(X_k)||^2 \leq \mathbb{E}[f(Z_0) - f(Z_{t+1})] + (t+1)\alpha^2 B'
$$
$$
\leq f(Z_0) - f_* + (t+1)\alpha^2 B' \tag{38}
$$

Then

$$
\min_{k=0,\cdots,t}\mathbb{E}[||\nabla_{\mathcal{M}}f(X_k)||^2] \leq \frac{f(Z_0) - f_*}{(t+1)B} + \alpha^2\frac{B'}{B} \tag{39}
$$

$$
\min_{k=0,\cdots,t}\mathbb{E}[||\nabla_{\mathcal{M}}f(X_k)||^2] \leq \frac{2(f(Z_0) - f_*)(1-\beta)}{(t+1)\alpha} + \alpha 2B'(1-\beta) \tag{40}
$$

Use the fact that $\alpha = \min\{\frac{1-\beta}{L}, \frac{A}{\sqrt{t+1}}\}$, and notice that $Z_0 = X_0$, therefore,

$$\min_{k=0,\cdots,t} \mathbb{E}[||\nabla_{\mathcal{M}} f(x_k)||^2]$$

$$\leq \frac{2(f(X_0) - f_*)(1-\beta)}{t+1} \max\{\frac{L}{1-\beta}, \frac{\sqrt{t+1}}{A}\} + \frac{2AB'(1-\beta)}{\sqrt{t+1}}$$

$$\leq \frac{2(f(X_0) - f_*)(1-\beta)}{t+1} \max\{\frac{L}{1-\beta}, \frac{\sqrt{t+1}}{A}\}$$

$$+ \frac{2A(1-\beta)}{\sqrt{t+1}}[\frac{L\beta^2}{(1-\beta)^2}(\frac{G^2}{(1-\beta)^2} + \frac{A^2C^2}{4(t+1)})$$

$$+ \frac{D^2 + G^2}{2(1-\beta)} + \frac{LG^2}{(1-\beta)^2} + \frac{LA^2}{(t+1)(1-\beta)^2}D^2] \tag{41}$$

Therefore, $\min_{k=0,\cdots,t} \mathbb{E}[||\nabla_{\mathcal{M}} f(X_k)||^2] = o(\frac{1}{\sqrt{t+1}}) \to 0$, as $t \to \infty$.

$\square$