A Consistent, Scalable, and Differentiable L_p Canonical Calibration Error Estimator

Abstract

Calibrated probabilistic classifiers are models whose predicted probabilities can directly be interpreted as uncertainty estimates. It has been shown recently that deep neural networks are poorly calibrated and tend to output overconfident predictions. As a remedy, we propose a low-bias, trainable calibration error estimator based on Dirichlet kernel density estimates, which asymptotically converges to the true L_p calibration error. This novel estimator enables us to achieve the strongest notion of multiclass calibration, called canonical calibration, while other common calibration methods are tractable only for top-label and marginal calibration. The computational complexity of our estimator is $\mathcal{O}(n^2)$, while the convergence rate is $\mathcal{O}(n^{-1/2})$, and it is unbiased up to $\mathcal{O}(n^{-2})$ achieved by a geometric series debiasing scheme. In practice, this means that the estimator can be applied to small subsets of the data, enabling efficient estimation and mini-batch updates. The proposed method has a natural choice of kernel, and can be used to generate consistent estimates of other quantities based on conditional expectation, such as the sharpness of a probabilistic classifier. Empirical results validate the correctness of our estimator, and demonstrate its utility in canonical calibration error estimation and calibration error regularized risk minimization.

1 Introduction

Deep neural networks have shown tremendous success in classification tasks, being regularly the best performing models in terms of accuracy. However, they are also known to make overconfident predictions [Guo et al., 2017], which is particularly problematic in safety-critical applications, such as medical diagnosis [Esteva et al., 2017, 2019] or autonomous driving [Caesar et al., 2020, Sun et al., 2020]. Therefore, in many real world applications it is not only the predictive performance that is important, but also the trustworthiness of that prediction, i.e., we are interested in accurate predictions with robust uncertainty estimates. To this end, it is necessary that the models are uncertainty calibrated, which means that, for instance, among all cells that have been predicted with a probability of 0.8 to be cancerous, 80% should indeed belong to a malignant tumor.

Research on calibration has been mostly focused on binary problems, often considering only the confidence score of the predicted class (top label calibration [Guo et al., 2017]). A stronger notion of calibration is marginal (or class-wise) [Kull et al., 2019], that splits up the multiclass problem into K one-vs-all binary ones, and each is required to be calibrated according to the definition of binary calibration. The most strict notion of calibration, called canonical (or distribution) calibration [Bröcker, 2009, Appice et al., 2015, Vaicenavicius et al., 2019], requires the whole probability vector to be calibrated and has been relatively neglected by the community. The curse of dimensionality makes estimation of this form of calibration difficult, and current estimators, such as the binned estimator ECE^{bin} [Naeini et al., 2015], MMCE [Kumar et al., 2018] and Mix-n-Match [Zhang et al.,

Table 1: Properties of ECE^{KDE} and other commonly used calibration error estimators.

		Properties		
	Consistency	Scalability	De-biased	Differentiable
ECE^{KDE} (**Our**)	✓	✓$\mathcal{O}(n^2)$	✓	✓
ECE^{bin}	✗[Vaicenavicius et al., 2019]	✗	✓[Roelofs et al., 2022]	✗
Mix-n-Match	✓[Zhang et al., 2020]	✗	✗	✓
MMCE	✗[Kumar et al., 2018]	✓$\mathcal{O}(n^2)$	✗	✓

2020], have computational or statistical limitations that prevent them from being successfully applied in this important setting.

To this end, we propose *a tractable, differentiable, and consistent estimator of the expected L_p canonical calibration error*. In particular, we use kernel density estimates (KDEs) with a Beta kernel in binary classification tasks and a Dirichlet kernel in the multiclass setting, as these kernels are the natural choices to model density estimation over a probability simplex. In Table 1, we summarize and compare the properties of our ECE^{KDE} estimator and other commonly used estimators. ECE^{KDE} scales well to higher dimensions and it is able to capture canonical calibration with $\mathcal{O}(n^2)$ complexity.

Our contributions can be summarized as follows:

1. We develop a tractable estimator of canonical L_p calibration error that is consistent and differentiable.
2. We demonstrate a natural choice of kernel. Due to the scaling properties of Dirichlet kernel density estimation, evaluating *canonical calibration* becomes feasible in cases that cannot be estimated using other methods.
3. We provide a second order debiasing scheme to further improve the convergence of the estimator.
4. We empirically evaluate the correctness of our estimator and demonstrate its utility in the task of calibration regularized risk minimization on variety of network architectures and several datasets.

2 Related Work

Calibration of probabilistic predictors has long been studied in many fields. This topic gained attention in the deep learning community since Guo et al. [2017] observed that modern neural networks are poorly calibrated and tend to give overconfident predictions due to overfitting on the NLL loss. The surge of interest resulted in many calibration strategies that can be split in two general categories, which we discuss subsequently.

Post-hoc calibration strategies learn a calibration map of the predictions from a trained predictor in a post-hoc manner, using a held-out calibration set. For instance, Platt scaling [Platt, 1999] fits a logistic regression model on top of the logit outputs of the model. A special case of Platt scaling that fits a single scalar, called temperature, has been popularized by Guo et al. [2017] as an accuracy-preserving, easy to implement and effective method to improve calibration. However, it has the undesired consequence that it clamps the high confidence scores of accurate predictions [Kumar et al., 2018]. Similar approaches for post-hoc calibration include histogram binning [Zadrozny and Elkan, 2001], isotonic regression [Zadrozny and Elkan, 2002], Bayesian binning into quantiles [Naeini and Cooper, 2015], Beta [Kull et al., 2017] and Dirichlet calibration [Kull et al., 2019]. Recently, Gupta et al. [2021] proposed a binning-free calibration measure based on the Kolmogorov-Smirnov test. In this approach, the recalibration function is obtained via spline-fitting, rather than minimizing a loss function on a calibration set. Ma et al. [2021] integrate ensamble-based and post-hoc calibration methods in an accuracy-perserving truth discovery framework. Zhao et al. [2021] introduce a new notion of calibration, called decision calibration, however, they do not propose an estimator of calibration error with statistical guarnatees.

Trainable calibration strategies integrate a differentiable calibration measure into the training objective. One of the earliest approaches is regularization by penalizing low entropy predictions [Pereyra et al., 2017]. Similarly to temperature scaling, it has been shown that entropy regularization needlessly suppresses high confidence scores of correct predictions [Kumar et al., 2018]. Another

popular strategy is MMCE (Maxmimum Mean Calibration Error) [Kumar et al., 2018], where the entropy regularizer is replaced by a kernel-based surrogate for the calibration error that can be optimized alongside NLL. It has been shown that label smoothing [Szegedy et al., 2015, Müller et al., 2020], i.e. training models with a weighted mixture of the labels instead of one-hot vectors, also improves model calibration. Liang et al. [2020] propose to add the difference between predicted confidence and accuracy as auxiliary term to the cross-entropy loss. Focal loss [Mukhoti et al., 2020, Lin et al., 2018] has recently been *empirically* shown to produce better calibrated models than many of the alternatives, but does not estimate a clear quantity related to calibration error. Bohdal et al. [2021] derive a differentiable approximation to the commonly-used binned estimator of calibration error by computing differentiable approximations to the 0/1 loss and the binning operator. However, this approach does not eliminate the dependence on the binning scheme and it is not clear how it can be extended to calibration of the whole probability vector.

Kernel density estimation [Parzen, 1962, Rosenblatt, 1956] is a non-parametric method to estimate a probability density function from a finite sample. Zhang et al. [2020] propose a KDE-based estimator of the calibration error (Mix-n-Match) for measuring calibration performance. Although they demonstrate consistency of the method, it requires a numerical integration step that is infeasible in high dimensions. In practice, they only implemented binary calibration, and not canonical calibration.

Although many calibration strategies have been empirically shown to decrease the calibration error, very few of them are based on an estimator of miscalibration. The most extensively used binned estimator has numerous flaws [Vaicenavicius et al., 2019], MMCE is not a consistent estimator of L_p calibration error and Mix-n-Match, although consistent, is intractable in high dimensions and the authors did not implement it in more than one dimension. Our estimator is the first consistent, differentiable estimator with favourable scaling properties that has been successfully applied to the estimation of L_p canonical calibration error in the multi-class setting.

3 Methods

We measure the (mis-)calibration in terms of the L_p calibration error. To this end, let $(\Omega, \mathcal{A}, \mathbb{P})$ be a probability space, let $\mathcal{X} = \mathbb{R}^d, \mathcal{Y} = \{1, ..., K\}$. Let $x : \Omega \to \mathcal{X}$ and $y : \Omega \to \mathcal{Y}$ be random variables while realizations are denoted with subscripts. Furthermore, let $f : \mathcal{X} \to \triangle^K$ be a decision function, where $\triangle^K$ denotes the $K - 1$ dimensional simplex as is achieved e.g. from the output of a final softmax layer in a neural network.

Definition 3.1 (Calibration error, [Naeini et al., 2015, Kumar et al., 2019, Wenger et al., 2020]). The L_p calibration error of f is:

$$\text{CE}_p(f) = \left(\mathbb{E}\left[\left\| \mathbb{E}[y \mid f(x)] - f(x) \right\|_p^p \right] \right)^{\frac{1}{p}}. \tag{1}$$

We note that we consider multiclass calibration, and that $f(x)$ and the conditional expectation in Equation (1) therefore map to points on a probability simplex. We say that a classifier f is perfectly calibrated if $\text{CE}_p(f) = 0$. Kumar et al. [2018] have also considered a minimization problem similar to Equation (6). Instead of using the CE_p they use a metric called maximum mean calibration error (MMCE) that is 0 if and only if $\text{CE}_p = 0$. However, it is unclear how MMCE relates to the canonical multiclass setting or to the norm parameter p for non-zero CE_p.

To optimize Definition 3.1 directly, we need to perform density estimation over the probability simplex in order to empirically compute the conditional expectation. In a binary setting, this has traditionally been done with binned estimates [Naeini et al., 2015, Guo et al., 2017, Kumar et al., 2019]. However, this is not differentiable w.r.t. the function f, and cannot be incorporated into a gradient based training procedure. Furthermore, binned estimates suffer from the curse of dimensionality and do not have a practical extension to multiclass settings. A natural choice for a differentiable kernel density estimator in the binary case is a kernel based on the Beta distribution and the extension to the multiclass case is given by the Dirichlet distribution. Hence, we consider an estimator for the CE_p based on Beta and Dirichlet kernel density estimates in the binary and multiclass setting, respectively. We require that this estimator is consistent and differentiable such that we can train it according to Equation (6). This

estimator is given by:

$$\widehat{\mathrm{CE}_p(f)}^p = \frac{1}{n}\sum_{j=1}^{n}\left[\left\|\left.\widehat{\mathbb{E}[y\mid f(x)]}\right|_{f(x_j)} - f(x_j)\right\|_p^p\right],\tag{2}$$

where $\left.\widehat{\mathbb{E}[y\mid f(x)]}\right|_{f(x_j)}$ denotes $\widehat{\mathbb{E}[y\mid f(x)]}$ evaluated at $f(x) = f(x_j)$. If probability density $p_{x,y}$ is measurable with respect to the product of the Lebesgue and counting measure, we can define: $p_{x,y}(x_i,y_i) = p_{y|x=x_i}(y_i)\,p_x(x_i)$. Then we define the estimator of the conditional expectation as follows:

$$\mathbb{E}[y\mid f(x)] = \sum_{y_k\in\mathcal{Y}} y_k\, p_{y|f(x)}(y_k) = \frac{\sum_{y_k\in\mathcal{Y}} y_k\, p_{f(x),y}(f(x),y_k)}{p_{f(x)}(f(x))}$$

$$\approx \frac{\sum_{i=1}^{n} k(f(x);f(x_i))y_i}{\sum_{i=1}^{n} k(f(x);f(x_i))} =: \widehat{\mathbb{E}[y\mid f(x)]}\tag{3}$$

where k is the kernel of a kernel density estimate evaluated at point x and $p_{f(x)}$ is uniquely determined by p_x and f.

Proposition 3.2. $\widehat{\mathbb{E}[y\mid f(x)]}$ *is a pointwise consistent estimator of* $\mathbb{E}[y\mid f(x)]$, *that is:*

$$\lim_{n\to\infty}\frac{\sum_{i=1}^{n}k(f(x);f(x_i))y_i}{\sum_{i=1}^{n}k(f(x);f(x_i))} = \frac{\sum_{y_k\in\mathcal{Y}}y_k\,p_{f(x),y}(f(x),y_k)}{p_{f(x)}(f(x))}.\tag{4}$$

Proof. By the consistency of kernel density estimators [Silverman, 1986, Chen, 1999, Ouimet and Tolosana-Delgado, 2021], for all $f(x)\in(0,1)$, $\frac{1}{n}\sum_{i=1}^{n}k(f(x);f(x_i))y_i \xrightarrow{n\to\infty} \sum_{y_k\in\mathcal{Y}}y_k\,p_{f(x),y}(f(x),y_k)$ and $\frac{1}{n}\sum_{i=1}^{n}k(f(x);f(x_i)) \xrightarrow{n\to\infty} p_{f(x)}(f(x))$. The fact that the ratio of two convergent sequences converges against the ratio of their limits shows the result. $\square$

The most commonly used loss functions are designed to achieve consistency in the sense of Bayes optimality under risk minimization, however, they do not guarantee calibration - neither for finite samples nor in the asymptotic limit. Since we are interested in models f that are both accurate and calibrated, we consider the following optimization problem bounding the calibration error $\mathrm{CE}(f)$:

$$f = \arg\min_{f\in\mathcal{F}} \mathrm{Risk}(f),\,\text{s.t. } \mathrm{CE}(f)\leq B\tag{5}$$

for some $B > 0$, and its associated Lagrangian

$$f = \arg\min_{f\in\mathcal{F}}\Big(\mathrm{Risk}(f) + \lambda\cdot\mathrm{CE}(f)\Big).\tag{6}$$

Mean squared error in binary classification   As a first instantiation of our framework we consider a binary classification setting, with mean squared error $\mathrm{MSE}(f) = \mathbb{E}[(f(x)-y)^2]$ as the risk function, jointly optimized with the L_2 calibration error CE_2:

$$f = \arg\min_{f\in\mathcal{F}}\Big(\mathrm{MSE}(f) + \lambda\,\mathrm{CE}_2(f)^2\Big) = \arg\min_{f\in\mathcal{F}}\Big(\mathrm{MSE}(f) + \gamma\mathbb{E}\Big[\mathbb{E}[y\mid f(x)]^2\Big]\Big)\tag{7}$$

where $\gamma\in[0,1)$. The full derivation using the MSE decomposition [Murphy, 1973, Degroot and Fienberg, 1983, Kuleshov and Liang, 2015, Nguyen and O'Connor, 2015] is given in Appendix B. For optimization we wish to find an estimator for $\mathbb{E}[\mathbb{E}[y\mid f(x)]^2]$. Building upon Equation (3), a partially debiased estimator can be written as:

$$\mathbb{E}\Big[\widehat{\mathbb{E}[y\mid f(x)]^2}\Big] \approx \frac{1}{n}\sum_{j=1}^{n}\frac{\Big(\sum_{i\neq j}k(f(x_j);f(x_i))y_i\Big)^2 - \sum_{i\neq j}(k(f(x_j);f(x_i))y_i)^2}{\Big(\sum_{i\neq j}k(f(x_j);f(x_i))\Big)^2 - \sum_{i\neq j}(k(f(x_j);f(x_i)))^2}.\tag{8}$$

Thus, the conditional expectation is estimated using a ratio of unbiased estimators of the square of a mean.

Proposition 3.3. *Equation* (8) *is a ratio of two U-statistics and has a bias converging as* $\mathcal{O}\left(\frac{1}{n}\right)$.

The proof is given in Appendix C.

Proposition 3.4. *There exist de-biasing schemes for the ratios in Equation* (8) *and Equation* (3) *that achieve an improved* $\mathcal{O}\left(\frac{1}{n^2}\right)$ *convergence of the bias.*

Proofs are given in Appendix D and E.

In a binary setting, the kernels $k(\cdot, \cdot)$ are Beta distributions defined as:

$$k_{\mathrm{B}}(f(x_j), f(x_i)) := f(x_j)^{\alpha_i - 1}(1 - f(x_j))^{\beta_i - 1}\frac{\Gamma(\alpha_i + \beta_i)}{\Gamma(\alpha_i)\,\Gamma(\beta_i)}, \tag{9}$$

with $\alpha_i = \frac{f(x_i)}{h} + 1$ and $\beta_i = \frac{1 - f(x_i)}{h} + 1$ [Chen, 1999, Bouezmarni and Rolin, 2003, Zhang and Karunamuni, 2010], where h is a bandwidth parameter in the kernel density estimate that goes to 0 as $n \to \infty$. We note that the computational complexity of this estimator is $\mathcal{O}(n^2)$. If we would use this within a gradient descent training procedure, the density can be estimated using a mini-batch and therefore the $\mathcal{O}(n^2)$ complexity is w.r.t. the size of a mini-batch, not the entire dataset.

The estimator in Equation (8) is a ratio of two second order U-statistics that converge as $n^{-1/2}$ [Ferguson, 2005]. Therefore, the overall convergence will be $n^{-1/2}$. Empirical convergence rates are calculated in Appendix H and shown to be close to the theoretically expected value.

Multiclass calibration with Dirichlet kernel density estimates   There are multiple definitions regarding multiclass calibration that differ in the strictness regarding the calibration of the probability vector $f(x)$. The strongest notion of multiclass calibration, and the one that we consider in this paper, is canonical (also called multiclass or distribution) calibration [Bröcker, 2009, Appice et al., 2015, Vaicenavicius et al., 2019], which requires that the whole probability vector $f(x)$ is calibrated (Definition 3.1). Its estimator is:

$$\widehat{\mathrm{CE}_p(f)}^p = \frac{1}{n}\sum_{j=1}^{n}\left\|\frac{\sum_{i \neq j} k_{\mathrm{Dir}}(f(x_j); f(x_i))y_i}{\sum_{i \neq j} k_{\mathrm{Dir}}(f(x_j); f(x_i))} - f(x_j)\right\|_p^p \tag{10}$$

where k_{Dir} is a Dirichlet kernel defined as:

$$k_{Dir}(f(x_j), f(x_i)) = \frac{\Gamma(\sum_{k=1}^{K}\alpha_{ik})}{\prod_{k=1}^{K}\Gamma(\alpha_{ik})}\prod_{k=1}^{K} f(x_j)_k^{\alpha_{ik} - 1} \tag{11}$$

with $\alpha_i = \frac{f(x_i)}{h} + 1$ [Ouimet and Tolosana-Delgado, 2021]. As before, the computational complexity is $\mathcal{O}(n^2)$ irrespective of p.

This estimator is differentiable and furthermore, the following proposition holds:

Proposition 3.5. *The Dirichlet kernel based* CE *estimator is consistent, that is*

$$\lim_{n \to \infty}\frac{1}{n}\sum_{j=1}^{n}\left\|\frac{\sum_{i \neq j}^{n} k_{\mathrm{Dir}}(f(x_j); f(x_i))y_i}{\sum_{i \neq j}^{n} k_{\mathrm{Dir}}(f(x_j); f(x_i))} - f(x_j)\right\|_p^p = \mathbb{E}\left[\left\|\mathbb{E}[y \mid f(x)] - f(x)\right\|_p^p\right]^p.$$

Proof. Dirichlet kernel estimators are consistent [Ouimet and Tolosana-Delgado, 2021], consequently, by Proposition 3.2 the term inside the norm is consistent for any fixed $f(x_j)$ (note, that summing over $i \neq j$ ensures that the ratio of the KDE's does not depend on the outer summation). Moreover, for any convergent sequence also the norm of that sequence converges against the norm of its limit. Ultimately, the outer sum is merely the sample mean of consistent summands, which again is consistent.   □

With this development, we have for the first time a consistent, differentiable, tractable estimator of L_p canonical calibration error with $\mathcal{O}(n^2)$ computational cost and $\mathcal{O}(n^{-1/2})$ convergence rate, with a debiasing scheme that achieves $\mathcal{O}(n^{-2})$ bias for $p \in \{1, 2\}$.

4 Empirical validation of ECE^{KDE}

Accurately evaluating the calibration error is a crucial step towards designing trustworthy models that can be used in high-cost settings. The most widely used metric for evaluating miscalibration, and the only other estimator that can be straightforwardly extended to measure canonical calibration, is the histogram-based estimator ECE^{bin}. However, as discussed in Vaicenavicius et al. [2019], Widmann et al. [2019], Ding et al. [2020], Ashukha et al. [2021], it has numerous flaws, such as: (i) it is sensitive to the binning scheme (ii) it is severely affected by the curse of dimensionality, as the number of bins grows exponentially with the number of classes (iii) it is asymptotically inconsistent in many cases.

To investigate its relationship with our estimator ECE^{KDE}, we first introduce an extension of the top-label binned estimator to the probability simplex in the three class setting. We start by partitioning the probability simplex into equally-sized, triangle-shaped bins and assign the probability scores to the corresponding bin, as shown in Figure 1a. Then, we define the binned estimate of canonical calibration error as follows:

$$\text{CE}_p(f)^p \approx \mathbb{E}\left[\|H(f(x)) - f(x)\|_p^p\right] \approx \frac{1}{n}\sum_{i=1}^n \|H(f(x_j)) - f(x_i)\|_p^p \tag{12}$$

where $H(f(x_j))$ is the histogram estimate, shown in Figure 1b. The surface of the corresponding Dirichlet KDE is presented in Figure 1c. See Appendix G for (i) an experiment investigating their relationship for the three types of calibration (top-label, marginal, canonical) and with varying number of points used for the estimation, and (ii) another example of the binned estimator and Dirichlet KDE on CIFAR-10.

(a) Splitting the simplex in 16 bins   (b) Histogram   (c) Dirichlet KDE

Figure 1: Extension of the binned estimator ECE^{bin} to the probability simplex, compared with the ECE^{KDE}. The ECE^{KDE} achieves a better approximation to the finite sample, and accurately models the fact that samples tend to be concentrated near low dimensional faces of the simplex.

Synthetic experiments We consider an extension of ECE^{bin} to arbitrary number of classes and investigate its performance compared to ECE^{KDE}. Since on real data the ground truth calibration error is unknown, we generate synthetic data with known transformations with the following procedure. First, we sample uniformly from the simplex using the Kraemer algorithm [Smith and Tromble, 2004]. Then, we apply temperature scaling with $t_1 = 0.6$ to simulate realistic scenarios where the probability scores are concentrated along lower dimensional faces of the simplex. We generate ground truth labels according to the sampled probabilities and therefore obtain a perfectly calibrated classifier. Subsequently, the classifier is miscalibrated by additional temperature scaling with $t_2 = 0.6$. Figure 2a depicts the performance of the two estimators as a function of the sample size on generated data for 4 and 8 classes. ECE^{KDE} coverges to the ground truth value obtained by integration in both cases, whereas ECE^{bin} provides poor estimates even with 20000 points.

In another experiment with synthetic data we look at the bias of the sharpness term in a binary setting. In Figure 2b we plot the sharpness term for varying number of samples both for the partially debiased ratio from Equation (8) and for the ratio debiased with the scheme introduced in Appendix E. A sigmoidal function is applied to the calibrated data to obtain an uncalibrated sample that is used to compute the partially debiased and the fully debiased ratio of the sharpness term. The ground truth value is obtained by using 100 million samples to compute the ratio with the partially debiased version, as it converges asymptotically to the true value due to its consistency. We use a bandwidth of

0.5 and average over 10000 repetitions for each number of samples that range from 32 to 16384. We fix the location of the KDE at $f(x_j) = 0.17$.

(a) ECE^{bin} vs. ECE^{KDE} (b) Debiasing

Figure 2: 2a Performance of ECE^{bin} and ECE^{KDE} on synthetic data for varying number of classes, as a function of the sample size. Ground truth represents the true value of the integral. ECE^{bin} is calculated using several common choices for the number of bins (*n_bins* represents number of bins per-class.) *n_bins* and *b* are found as optimal values according to Doane's formula [Doane, 1976] and LOO MLE, respectively. ECE^{KDE} converges to the true value in all settings, in contrast to ECE^{bin}. 2b Sharpness term evaluated for different numbers of samples with the partially debiased ratio from Equation (8) and with the debiasing scheme derived in Appendix E on synthetic data.

5 Calibration regularized training

5.1 Empirical setup

To showcase our estimator in applications where canonical calibration is crucial, we consider two medical datasets, namely Kather and DermaMNIST. The Kather dataset [Kather et al., 2016] consists of 5000 histological images of human colorectal cancer and it has eight different classes of tissue. DermaMNIST [Yang et al., 2021] is a pre-processed version of the HAM10000 dataset [Tschandl, 2018], containing 10015 dermatoscopic images of skin lesions, categorized in seven classes. Both datasets have been collected in accordance with the Declaration of Helsinki. According to standard practice in related works, we trained ResNet [He et al., 2015], ResNet with stochastic depth (SD) [Huang et al., 2016], DenseNet [Huang et al., 2018] and WideResNet [Zagoruyko and Komodakis, 2016] networks also on CIFAR-10/100 [Krizhevsky, 2009]. We use 45000 images for training on the CIFAR datasets, 4000 for Kather and 7007 for DermaMNIST. The code is available in the supplementary material.

Baselines *Cross-entropy*: The first baseline model is trained using cross-entropy (**XE**), with the data preprocessing, training procedure and hyperparameters described in the corresponding paper for the architecture.

Trainable calibration strategies **KDE-XE** is our proposed estimator ECE^{KDE} jointly trained with cross entropy. **MMCE** [Kumar et al., 2018] is a differentiable measure of calibration with a property that it is minimized at perfect calibration. It is used as a regulariser alongside NLL, with the strength of regularization parameterized by λ. **Focal loss (FL)** [Mukhoti et al., 2020] is an alternative to the cross-entropy loss, defined as $\mathcal{L}_f = -(1 - f(y|x))^\gamma \log(f(y|x))$, where γ is a hyperparameter and $f(y|x)$ is the probability score that a neural network f outputs for a class y on an input x. Their best-performing approach is the sample-dependent FL-53 where $\gamma = 5$ for $f(y|x) \in [0, 0.2)$ and $\gamma = 3$ otherwise, followed by the method with fixed $\gamma = 3$.

Post-hoc calibration strategies Guo et al. [2017] investigated the performance of several post-hoc calibration methods and found **temperature scaling** to be a strong baseline, which we use as a representative of this group. It works by scaling the logits with a scalar $T > 0$, typically learned on a validation set by minimizing NLL. Following Kumar et al. [2018], Mukhoti et al. [2020], we also use temperature scaling as a post-processing step for our method.

Metrics We report L_1 canonical calibration using our ECE^{KDE} estimator, calculated according to equation 10. Additional experiments with L_1 and L_2 top-label calibration on CIFAR-10/100 can be found in Appendix F.

Hyperparameters A crucial parameter for KDE is the bandwidth b, a positive number that defines the smoothness of the density plot. Poorly chosen bandwidth may lead to undersmoothing (small bandwidth) or oversmoothing (large bandwidth), as shown in Figure 3. A commonly used non-parametric bandwidth selector is maximum likelihood cross validation [Duin, 1976]. For our experiments we choose the bandwidth from a list of possible values by maximizing the leave-one-out likelihood (LOO MLE). The λ parameter for weighting the calibration error w.r.t the loss is typically chosen via cross-validation or using a holdout validation set. We found that for KDE-XE, values of $\lambda \in [0.001, 0.2]$ provide a good trade-off in terms of accuracy and calibration error. The p parameter is selected depending on the desired L_p calibration error and the corresponding theoretical guarantees. The rest of the

Figure 3: Effect of the bandwidth b on the shape of the estimate.

hyperparameters for training are set as proposed in the corresponding papers for the architectures we benchmark. The only exception is that we use a batch size of 64 for all experiments on the medical datasets, due to their smaller size.

5.2 Experiments

An important property of our ECE^{KDE} estimator is differentiability, allowing it be used in a calibration regularized training framework. In this section, we benchmark KDE-XE with several baselines on medical diagnosis applications, where the calibration of the whole probability vector is of particular interest. For completeness, we also include an experiment on CIFAR-10.

Table 2 summarizes the canonical L_1 ECE^{KDE} and Table 3 the accuracy, measured across multiple architectures. The bandwidth is chosen by LOO MLE. For MMCE and KDE-XE the best performing regularization weight is reported.

In Table 2 we notice that KDE-XE consistently achieves very competitive ECE values, while also boosting the accuracy, as shown in Table 3. Interestingly, we observe that temperature scaling does not improve canonical calibration error, contrary to its reported improvements on top-label calibration. Figure 4 shows the performance of several architectures and datasets in terms of accuracy and L_1 ECE^{KDE} for various choices of the regularization parameter for MMCE and KDE-XE. The 95% confidence intervals for ECE^{KDE} are calculated using 100 and 10 bootstrap samples on the medical datasets and CIFAR-10, respectively. In all settings, KDE-XE Pareto dominates the competitors for several choices of λ. For example, on DermaMNIST trained with DenseNet, KDE-XE with $\lambda = 0.2$ reduces the ECE^{KDE} from 66% to 45%.

Table 2: Canonical L_1 ECE^{KDE} ($\downarrow$) for different loss functions and architectures, both trained from scratch (Pre T) and after temperature scaling on a validation set (Post T). Best results across Pre T methods are marked in bold.

Dataset	Model	XE		MMCE		FL-53		L_1 **KDE-XE (Our)**	
		Pre T	Post T	Pre T	Post T	Pre T	Post T	Pre T	Post T
Kather	ResNet-110	0.335	0.304	0.343	0.3	0.325	0.248	**0.311**	0.289
	ResNet-110 (SD)	0.329	0.334	0.235	0.159	0.209	0.122	**0.198**	0.147
DermaMNIST	ResNet-110	0.579	0.602	0.575	0.603	0.684	0.618	**0.467**	0.516
	ResNet-110 (SD)	0.534	0.571	0.47	0.526	0.567	0.594	**0.461**	0.538
	Wide-ResNet-28-10	0.546	0.599	0.47	0.512	0.623	0.608	**0.455**	0.599
	DenseNet-40	0.573	0.578	0.514	0.558	0.577	0.557	**0.366**	0.418
CIFAR-10	ResNet-110	0.133	0.17	0.171	0.196	0.138	0.171	**0.126**	0.163
	ResNet-110 (SD)	**0.132**	0.172	0.164	0.203	0.156	0.201	0.178	0.223
	Wide-ResNet-28-10	0.083	0.098	0.143	0.155	0.147	0.177	**0.077**	0.091
	DenseNet-40	0.104	0.131	0.133	0.155	0.081	0.081	**0.09**	0.124

Table 3: Accuracy (↑) computed for different architectures. Best results are marked in bold.

Dataset	Model	XE	MMCE	FL-53	L_1 **KDE-XE**
Kather	ResNet-110	0.84	**0.86**	0.844	**0.86**
	ResNet-110 (SD)	0.87	0.9	0.885	**0.914**
DermaMNIST	ResNet-110	0.72	0.721	0.674	**0.744**
	ResNet-110 (SD)	0.743	0.753	0.689	**0.764**
	Wide-ResNet-28-10	0.736	0.741	0.715	**0.754**
	DenseNet-40	0.741	**0.758**	0.705	0.748
CIFAR-10	ResNet-110	0.925	**0.929**	0.922	**0.929**
	ResNet-110 (SD)	**0.926**	0.925	0.92	0.907
	Wide-ResNet-28-10	**0.954**	0.947	0.936	**0.954**
	DenseNet-40	0.947	0.944	**0.948**	0.947

(a) ResNet-110 (SD) on Kather   (b) DenseNet on DermaMNIST   (c) ResNet-110 on CIFAR-10

Figure 4: Canonical calibration on various datasets and architectures.

Training time measurements In Table 4 we summarize the running time per epoch of the four architectures, with regularization (KDE-XE) and without regularization (XE). We observe only an insignificant impact on the training speed when using KDE-XE, dispelling any concerns w.r.t. the computational overhead.

To summarize, the experiments show that our estimator is consistently producing competitive calibration errors with other state-of-the-art ap-

Table 4: Training time [sec] per epoch for XE and KDE-XE for different models on CIFAR-10.

Dataset	**Model**	**XE**	L_1 **KDE-XE**
CIFAR-10	ResNet-110	51.8	53
	ResNet-110 (SD)	45	46
	Wide-ResNet-28-10	152.9	154.9
	DenseNet-40	103.2	106.8

proaches, while maintaining accuracy and keeping the computational complexity at $\mathcal{O}(n^2)$. We note that within the proposed calibration-regularized training framework, this complexity is w.r.t. to a mini-batch, and the added cost is less than a couple percent. Furthermore, the $\mathcal{O}(n^2)$ complexity shows up in other related works [Kumar et al., 2018, Zhang et al., 2020], and is intrinsic to the problem of density estimators of calibration error. As a future work, a larger scale benchmarking will be beneficial for exploring the limits of canonical calibration using Dirichlet kernels.

6 Conclusion

In this paper, we proposed a consistent and differentiable estimator of canonical L_p calibration error using Dirichlet kernels. It has favorable computational and statistical properties, with a complexity of $\mathcal{O}(n^2)$, convergence of $\mathcal{O}(n^{-1/2})$ and a bias that converges as $\mathcal{O}(n^{-1})$, which can be further reduced to $\mathcal{O}(n^{-2})$ using our debiasing strategy. The ECE^{KDE} can be directly optimized alongside any loss function in the existing batch stochastic gradient descent framework. Furthermore, we propose using it as a measure of the highest form of calibration, which requires the entire probability vector to be calibrated. To the best of our knowledge, this is the only metric that can tractably capture this type of calibration, which is crucial in safety-critical applications where downstream decisions are made based on the predicted probabilities. We showed empirically on a range of neural architectures and datasets that the performance of our estimator in terms of accuracy and calibration error is competitive against the current state-of-the-art, while having superior properties as a consistent estimator of canonical calibration error.

References

A. Appice, P. Rodrigues, V. S. Costa, C. Soares, João Gama, and A. Jorge. Novel decompositions of proper scoring rules for classification : Score adjustment as precursor to calibration. 2015.

Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning, 2021.

Ondrej Bohdal, Yongxin Yang, and Timothy Hospedales. Meta-calibration: Meta-learning of model calibration using differentiable expected calibration error, 2021.

Taoufik Bouezmarni and Jean-Marie Rolin. Consistency of the beta kernel density function estimator. *The Canadian Journal of Statistics / La Revue Canadienne de Statistique*, 31(1):89–98, 2003.

Jochen Bröcker. Reliability, sufficiency, and the decomposition of proper scores. *Quarterly Journal of the Royal Meteorological Society*, 135(643):1512–1519, Jul 2009.

Holger Caesar, Varun Kumar Reddy Bankiti, Alex Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, page 11621–11631, 06 2020.

Song Xi Chen. Beta kernel estimators for density functions. *Computational Statistics & Data Analysis*, 31:131–145, 1999.

M. Degroot and S. Fienberg. The comparison and evaluation of forecasters. *The Statistician*, 32: 12–22, 1983.

Yukun Ding, Jinglan Liu, Jinjun Xiong, and Yiyu Shi. Revisiting the evaluation of uncertainty estimation and its application to explore model complexity-uncertainty trade-off. arXiv:1903.02050, 2020.

David P. Doane. Aesthetic frequency classifications. *The American Statistician*, 30(4):181–183, 1976.

Robert Duin. On the choice of smoothing parameters for parzen estimators of probability density functions. *IEEE Transactions on Computers*, C-25(11):1175–1179, 1976.

Andre Esteva, Brett Kuprel, Roberto A. Novoa, Justin Ko, Susan M. Swetter, Helen M. Blau, and Sebastian Thrun. Dermatologist-level classification of skin cancer with deep neural networks. *Nature*, 542:115–, 2017.

Andre Esteva, Alexandre Robicquet, Bharath Ramsundar, Volodymyr Kuleshov, Mark DePristo, Katherine Chou, Claire Cui, Greg Corrado, Sebastian Thrun, and Jeff Dean. A guide to deep learning in healthcare. *Nature Medicine*, 25, 01 2019.

Thomas S. Ferguson. U-statistics. In *Notes for Statistics 200C*. UCLA, 2005.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks, 2017.

Kartik Gupta, Amir Rahimi, Thalaiyasingam Ajanthan, Thomas Mensink, Cristian Sminchisescu, and Richard Hartley. Calibration of neural networks using splines. In *International Conference on Learning Representations*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. arXiv:1512.03385, 2015.

Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Weinberger. Deep networks with stochastic depth. arXiv:1603.09382, 2016.

Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks, 2018.

Jakob Kather, Cleo-Aron Weis, Francesco Bianconi, Susanne Melchers, Lothar Schad, Timo Gaiser, Alexander Marx, and Frank Zöllner. Multi-class texture analysis in colorectal cancer histology. *Scientific Reports*, 6:27988, 06 2016.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

Volodymyr Kuleshov and Percy S Liang. Calibrated structured prediction. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015.

Meelis Kull, Telmo Silva Filho, and Peter Flach. Beta calibration: a well-founded and easily implemented improvement on logistic calibration for binary classifiers. In Aarti Singh and Jerry Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pages 623–631. PMLR, 20–22 Apr 2017.

Meelis Kull, Miquel Perello-Nieto, Markus Kängsepp, Telmo Silva Filho, Hao Song, and Peter Flach. Beyond temperature scaling: Obtaining well-calibrated multiclass probabilities with Dirichlet calibration. arXiv:1910.12656, 2019.

Ananya Kumar, Percy S Liang, and Tengyu Ma. Verified uncertainty calibration. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 3792–3803. 2019.

Aviral Kumar, Sunita Sarawagi, and Ujjwal Jain. Trainable calibration measures for neural networks from kernel mean embeddings. In *ICML*, 2018.

Gongbo Liang, Yu Zhang, Xiaoqin Wang, and Nathan Jacobs. Improved trainable calibration method for neural networks on medical imaging classification. In *British Machine Vision Conference*, 2020.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. arXiv:1708.02002, 2018.

Chunwei Ma, Ziyun Huang, Jiayi Xian, Mingchen Gao, and Jinhui Xu. Improving uncertainty calibration of deep neural networks via truth discovery and geometric optimization. In Cassio de Campos and Marloes H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 75–85. PMLR, 27–30 Jul 2021.

Jishnu Mukhoti, Viveka Kulharia, Amartya Sanyal, Stuart Golodetz, Philip H. S. Torr, and Puneet K. Dokania. Calibrating deep neural networks using focal loss. arXiv:2002.09437, 2020.

A. Murphy. A new vector partition of the probability score. *Journal of Applied Meteorology*, 12: 595–600, 1973.

Rafael Müller, Simon Kornblith, and Geoffrey Hinton. When does label smoothing help? arXiv:1906.02629, 2020.

Mahdi Pakdaman Naeini and Gregory F. Cooper. Binary classifier calibration using an ensemble of near isotonic regression models. arXiv:1511.05191, 2015.

Mahdi Pakdaman Naeini, Gregory F. Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using Bayesian binning. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, pages 2901–2907, 2015.

Khanh Nguyen and Brendan O'Connor. Posterior calibration and exploratory analysis for natural language processing models. arXiv:1508.05154, 2015.

R.C. Ogliore, G.R. Huss, and K. Nagashima. Ratio estimation in SIMS analysis. *Nuclear Instruments and Methods in Physics Research Section B-beam Interactions With Materials and Atoms*, 269, 06 2011.

Frédéric Ouimet and Raimon Tolosana-Delgado. Asymptotic properties of dirichlet kernel density estimators. arXiv:2002.06956, 2021.

Emanuel Parzen. On estimation of a probability density function and mode. *The Annals of Mathematical Statistics*, 33(3):1065–1076, 1962.

Gabriel Pereyra, George Tucker, Jan Chorowski, Łukasz Kaiser, and Geoffrey Hinton. Regularizing neural networks by penalizing confident output distributions. arXiv:1701.06548, 2017.

John C. Platt. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. In *Advances in Large Margin Classifiers*, pages 61–74. MIT Press, 1999.

Rebecca Roelofs, Nicholas Cain, Jonathon Shlens, and Michael C. Mozer. Mitigating bias in calibration error estimation. In Gustau Camps-Valls, Francisco J. R. Ruiz, and Isabel Valera, editors, *Proceedings of The 25th International Conference on Artificial Intelligence and Statistics*, volume 151 of *Proceedings of Machine Learning Research*, pages 4036–4054. PMLR, 28–30 Mar 2022.

Murray Rosenblatt. Remarks on some nonparametric estimates of a density function. *The Annals of Mathematical Statistics*, 27(3):832 – 837, 1956.

Jun Shao. *Mathematical Statistics*, page 180. Springer Texts in Statistics, second edition, 2003.

B. W. Silverman. *Density Estimation for Statistics and Data Analysis*. Chapman & Hall, 1986.

Noah A. Smith and Roy W. Tromble. *Sampling Uniformly from the Unit Simplex*. 2004.

Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, Vijay Vasudevan, Wei Han, Jiquan Ngiam, Hang Zhao, Aleksei Timofeev, Scott M. Ettinger, Maxim Krivokon, Amy Gao, Aditya Joshi, Yu Zhang, Jonathon Shlens, Zhifeng Chen, and Dragomir Anguelov. Scalability in perception for autonomous driving: Waymo open dataset. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2443–2451, 2020.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. arXiv:1512.00567, 2015.

Myint Tin. Comparison of some ratio estimators. *Journal of the American Statistical Association*, 60 (309):294–307, 1965.

Philipp Tschandl. The HAM10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions, 2018.

Juozas Vaicenavicius, David Widmann, Carl Andersson, Fredrik Lindsten, Jacob Roll, and Thomas B. Schön. Evaluating model calibration in classification. arXiv:1902.06977, 2019.

Jonathan Wenger, Hedvig Kjellström, and Rudolph Triebel. Non-parametric calibration for classification. In *International Conference on Artificial Intelligence and Statistics*, pages 178–190, 2020.

David Widmann, Fredrik Lindsten, and Dave Zachariah. Calibration tests in multi-class classification: A unifying framework. *ArXiv*, abs/1910.11385, 2019.

Jiancheng Yang, Rui Shi, and Bingbing Ni. Medmnist classification decathlon: A lightweight automl benchmark for medical image analysis. *2021 IEEE 18th International Symposium on Biomedical Imaging (ISBI)*, Apr 2021.

B. Zadrozny and C. Elkan. Transforming classifier scores into accurate multiclass probability estimates. *Proceedings of the eighth ACM SIGKDD international conference on Knowledge discovery and data mining*, 2002.

Bianca Zadrozny and Charles Elkan. Obtaining calibrated probability estimates from decision trees and naive bayesian classifiers. *ICML*, 1, 05 2001.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *British Machine Vision Conference*, 2016.

Jize Zhang, Bhavya Kailkhura, and T. Yong-Jin Han. Mix-n-match: Ensemble and compositional methods for uncertainty calibration in deep learning. In *International Conference on Machine Learning*, 2020.

Shunpu Zhang and Rohana Karunamuni. Boundary performance of the beta kernel estimators. *Journal of Nonparametric Statistics*, 22:81–104, 01 2010.

Shengjia Zhao, Michael Kim, Roshni Sahoo, Tengyu Ma, and Stefano Ermon. Calibrating predictions to decisions: A novel approach to multi-class calibration. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 22313–22324. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper/2021/file/bbc92a647199b832ec90d7cf57074e9e-Paper.pdf`.

A   Ethical statement

The paper is concerned with estimation of calibration error, a topic for which existing methods are deployed, albeit not typically for canonical calibration error in a multi-class setting. We therefore consider the ethical risks to be effectively the same as for any probabilistic classifier. Experiments apply the method to medical image classification, for which misinterpretation of benchmark results with respect to their clinical applicability has been highlighted as a risk, see e.g.

Varoquaux, G., Cheplygina, V. Machine learning for medical imaging: methodological failures and recommendations for the future. npj Digit. Med. 5, 48 (2022). `https://doi.org/10.1038/s41746-022-00592-y`