Generative Simulators: The Foundations for Self-Adapting Intelligence

Anonymous

Abstract

As machine learning systems become increasingly agentic, static datasets, hand-written environments, and fixed benchmarks are proving insufficient for training, evaluation, and governance. Agents deployed in real-world settings must reason under uncertainty, interact over long horizons, and continuously remember and adapt as their understanding of tasks, tools, and constraints evolves. We introduce *Generative Simulators*, adaptive environments that jointly generate tasks, world dynamics, and reward functions. We formalize these systems under the framework of *Open Recursive Self-Improvement (ORSI)*, in which agents improve through interaction rather than optimization against fixed objectives. We believe that generative simulators constitute the foundational infrastructure for self-adapting world modeling, extending beyond reinforcement learning algorithms and beyond human-curated datasets.

1   Introduction

Modern machine learning systems are most commonly evaluated on static benchmarks, but these are susceptible to contamination, leakage, and saturation [4]. The paradigm of training and evaluating on reinforcement learning environments, each containing a set of tasks, world tools through which the model interacts with the environment and reward functions to evaluate and provide feedback on performance, has given rise to a new era of post training. Most commonly found reinforcement learning post-training environments are designed for domain specific tasks like software engineering [2] and customer service [5, 1] and help assess and improve basic tool use, environment exploration and instruction following capabilities of models. However, with the recent improvements in models, these benchmark environments have come to saturate as well, such as τ^2-Bench getting nearly saturated by GPT-5.2 [3]. This saturation is due to lack of plasticity of these environments. We believe that the future of environments is dynamic and self-adaptive to model capabilities. This report provides a position and showcases our work on environments built to auto-scale with model capabilities. Additionally, we show that careful orchestration and design of task generation processes, tooling infrastructure and reward processes can remove the domain-specific restriction of environments and turn them into high plasticity worlds.

2   Generative Simulators

To demonstrate that automatic increases in plasticity are possible, we propose a novel class of adaptive environment generators called *Generative Simulators*. One such example of a *Generative Simulator* is shown in Figure 1. Once a task's difficulty and simple configurations have been specified, our Task Generation module would sequentially create tasks that satisfy these constraints, coupled with task timelines that are reflective of difficulty (e.g. difficult tasks should take longer to execute). A set of tools is also selected based on the task difficulty, with more challenging tasks

requiring more extensive tool sets. Given the generated tasks, we would perform curriculum-based task filtering based on current agent's capabilities and required difficulty levels and couple these tasks with tool stacks of appropriate complexity. These task-tool tuples would then be used to evaluate and train an agent. The agent then executes the tasks, producing a series of output trajectories. These trajectories are finally scored using a reward function to populate the final evaluation report. In an ideal scenario, this reward function is co-generated with the task definition but is ensured to be verifiable. In such a system, the three synthetic components of task generation, world tooling and reward modeling can be independently or jointly made more difficult which helps scale difficulty for problematic areas of the model specifically. This provides the required plasticity in the world. Furthermore, with this design, the domain specificity of an RL environment can be naturally altered by adding, removing or swapping out toolsets specific to a domain. For example, adding a browser use toolset to an existing SWE-Bench like task can help extend the domain-set to frontend development situations where the agent is required to debug visually using the browser tools.

Figure 1: An illustration of Generative Simulators . Our adaptive environment generators are capable of producing a diverse set of tasks and tool sets with minimal specification.

2.1 Formal Definition of Generative Simulators

Let $\mathcal{L}$ denote a generative LLM. A Generative Simulator is a tuple $\mathcal{G} = (\mathcal{T}, \mathcal{W}, \mathcal{R}, \mathcal{C})$ where each component is an LLM-parameterized generator:

$\mathcal{T} : \Theta \times \mathcal{D} \xrightarrow{\mathcal{L}} \mathcal{M}$ — generates task instances given specifications and directives

$\mathcal{W} : \mathcal{M} \times \mathcal{D} \xrightarrow{\mathcal{L}} 2^{\mathcal{O}}$ — generates tool configurations conditioned on task and directives

$\mathcal{R} : \mathcal{M} \times \mathcal{D} \xrightarrow{\mathcal{L}} (\mathcal{H} \to \mathbb{R})$ — generates verifiable reward functions

$\mathcal{C} : \mathcal{M} \times \Pi \times \mathcal{D} \xrightarrow{\mathcal{L}} 0, 1$ — decides task inclusion based on agent capability

where $\mathcal{D}$ is the space of natural language directives (e.g., "increase task complexity", "add more tools", "make rewards sparser").

3   Limitations and Future Directions

Long-horizon tasks spanning days or weeks remain difficult to evaluate. Many objectives involve non-verifiable rewards such as usefulness or trust. Physical grounding introduces additional challenges, including noisy sensors and irreversible actions. Bridging generative simulators with robotics remains an open research problem.

4   Conclusion

Static datasets, hand-authored environments, and human-curated demonstrations do not scale to the interactive settings required for self-adapting intelligence. Generative simulators provide a principled alternative: environments that evolve, evaluate, and constrain agent behavior over time. Without such environments, progress toward general-purpose intelligence will remain fundamentally limited.

References

[1]   Victor Barres et al. "τ^2-Bench: Evaluating Conversational Agents in a Dual-Control Environment". In: *arXiv preprint arXiv:2506.07982* (2025).

[2]   Carlos E Jimenez et al. "Swe-Bench: Cand Language Models Resolve Real-World Github Issues?" In: *12th International Conference on Learning Representations, ICLR 2024*. 2024.

[3]   OpenAI. *Update to GPT-5 System Card: GPT-5.2.* https://openai.com/index/gpt-5-system-card-update-gpt-5-2/. Accessed: 2025-12-15. Dec. 2025.

[4]   Manley Roberts et al. "To the cutoff . . . and beyond? a longitudinal perspective on llm data contamination". In: *The Twelfth International Conference on Learning Representations*. 2023.

[5]   Shunyu Yao et al. "τ-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains". In: *arXiv preprint arXiv:2406.12045* (2024).

Algorithm 1 Generative Simulator Training with LLM-based Adaptation

Require: Generator LLM $\mathcal{L}_G$, Oversight LLM $\mathcal{L}_O$
Require: Initial directive $d_0 \in \mathcal{D}$, batch size K, threshold η
1: Initialize policy π_θ
2: Initialize directive $d \leftarrow d_0$
3: Initialize oversight memory $\mathcal{B} \leftarrow \emptyset$
4: **for** epoch $e = 1, \ldots, N$ **do**
5:    $\mathcal{D}_e \leftarrow \emptyset$ {Epoch buffer}
6:    **for** episode $k = 1, \ldots, K$ **do**
7:      {**Phase 1: LLM-based Environment Generation**}
8:      Sample base specification $\theta_k \sim p(\Theta)$
9:      $m_k \leftarrow \mathcal{L}_G\big(\texttt{GenTask}(\theta_k, d)\big)$
10:     $O_k \leftarrow \mathcal{L}_G\big(\texttt{GenTools}(m_k, d)\big)$
11:     $r_{m_k} \leftarrow \mathcal{L}_G\big(\texttt{GenReward}(m_k, d)\big)$
12:     {**Phase 2: LLM-based Curriculum Filtering**}
13:     $accept \leftarrow \mathcal{L}_O\big(\texttt{Filter}(m_k, \pi_\theta, d)\big)$
14:     **if not** $accept$ **then**
15:       **continue**
16:     **end if**
17:     {**Phase 3: Agent Rollout**}
18:     $s_0 \sim \rho_0(m_k), \quad \tau_k \leftarrow \langle\rangle$
19:     **for** $t = 0, \ldots, T_{\max} - 1$ **do**
20:       $a_t \sim \pi_\theta(\cdot \mid s_t, O_k)$
21:       $s_{t+1} \sim P(\cdot \mid s_t, a_t, m_k, O_k)$
22:       $\tau_k \leftarrow \tau_k \oplus (s_t, a_t)$
23:       **if** $\textsc{Terminal}(s_{t+1}, m_k)$ **then**
24:         **break**
25:       **end if**
26:     **end for**
27:     $r_k \leftarrow r_{m_k}(\tau_k)$
28:     $\mathcal{D}_e \leftarrow \mathcal{D}_e \cup \{(\tau_k, r_k, m_k, O_k)\}$
29:    **end for**
30:    {**Phase 4: Policy Update**}
31:    $\theta \leftarrow \textsc{RLUpdate}(\theta, \mathcal{D}_e)$
32:    {**Phase 5: Oversight Analysis & Memory**}
33:    $\mathcal{F}_e \leftarrow \{(\tau, m, O) : (\tau, r, m, O) \in \mathcal{D}_e, \ r < \eta\}$
34:    $\mathcal{B} \leftarrow \mathcal{B} \cup \mathcal{F}_e$
35:    $\bar{r}_e \leftarrow \textsc{MeanReward}(\mathcal{D}_e)$
36:    {**Phase 6: LLM-based Directive Update**}
37:    $d \leftarrow \mathcal{L}_O\big(\texttt{Adapt}(d, \bar{r}_e, \mathcal{B})\big)$
38: **end for**
39: **return** π_θ

Algorithm 2 Oversight Directive Adaptation (LLM Subroutine)

Require: Oversight LLM $\mathcal{L}_O$

Require: Current directive d, mean reward $\bar{r}$, failure memory $\mathcal{B}$, threshold η

 1: {**Failure Mode Analysis**}
 2: $report \leftarrow \mathcal{L}_O\big(\textsc{AnalyzeFailures}(\mathcal{B})\big)$
 3: {**Identify Bottleneck Dimensions**}
 4: $bottleneck \leftarrow \mathcal{L}_O\big(\textsc{ClassifyFailures}(report)\big)$
 5: {Returns subset of $\{\texttt{task}, \texttt{tools}, \texttt{reward}\}$}
 6: {**Generate Updated Directive**}
 7: **if** $\bar{r} \geq \eta$ **then**
 8:    $context \leftarrow (d,\ bottleneck,\ \texttt{"increase difficulty"})$
 9:    $d' \leftarrow \mathcal{L}_O\big(\textsc{UpdateDirective}(context)\big)$
10: **else**
11:    $context \leftarrow (d,\ report,\ \texttt{"maintain or simplify"})$
12:    $d' \leftarrow \mathcal{L}_O\big(\textsc{UpdateDirective}(context)\big)$
13: **end if**
14: **return** d'